



US006099194A

United States Patent [19] Durand

[11] Patent Number: **6,099,194**
[45] Date of Patent: **Aug. 8, 2000**

[54] **SPLICE JOINT FOR CONNECTING ADJACENT SIDE RAIL SECTIONS IN A VEHICLE BODY AND FRAME ASSEMBLY**

5,829,219 11/1998 Sugawara et al. 296/29 X

FOREIGN PATENT DOCUMENTS

589640 12/1959 Canada 403/271
720798 4/1942 Germany .
1131524 12/1959 Germany 280/790
6270839 9/1994 Japan 280/790

[75] Inventor: **Robert D. Durand**, Wyomissing, Pa.

[73] Assignee: **Dana Corporation**, Toledo, Ohio

[21] Appl. No.: **08/915,418**

[22] Filed: **Aug. 20, 1997**

[51] **Int. Cl.**⁷ **F16B 5/08**

[52] **U.S. Cl.** **403/270; 403/363; 296/29; 296/204**

[58] **Field of Search** 403/270, 271, 403/272, 363, 265, 404; 296/29, 30, 204, 203.02, 194; 280/800, 781, 790

[56] **References Cited**

U.S. PATENT DOCUMENTS


1,698,179 1/1929 Walker .
2,297,123 9/1942 Almdale .
2,801,864 8/1957 Rancy et al. .
3,614,124 10/1971 Schwabenlender .
5,149,132 9/1992 Ruehl et al. .
5,308,115 5/1994 Ruehl et al. .
5,320,403 6/1994 Kazyak 296/29 X
5,332,281 7/1994 Janotik et al. 296/209
5,609,386 3/1997 Takahashi et al. 296/30 X
5,634,663 6/1997 Krupp et al. 296/29 X
5,645,364 7/1997 Hodozuka et al. 403/270

Primary Examiner—Harry C. Kim
Attorney, Agent, or Firm—MacMillan, Sobanski & Todd, LLC

[57] **ABSTRACT**

A splice joint for connecting a pair of open channel side rail sections in a vehicular body and frame assembly focuses stresses imposed thereon away from the longitudinal edges of the structural members. In a first aspect of this invention, one or both end portions of the side rail sections are formed having an offset. The end portions of the side rail sections overlap one another and are secured together in any conventional manner, such as by welding. Preferably, the welds are made in such a manner that they terminate prior to reaching any of the longitudinally extending edges of the side rail sections. In a second aspect of this invention, the portions of the side rail sections are butt welded together. A support bracket is secured to the side rail sections in any conventional manner, such as by welding. Again, the welds are preferably made in such a manner as to terminate prior to reaching any of the longitudinally extending edges of the side rail sections.

12 Claims, 5 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

SPLICE JOINT FOR CONNECTING ADJACENT SIDE RAIL SECTIONS IN A VEHICLE BODY AND FRAME ASSEMBLY

BACKGROUND OF THE INVENTION

This invention relates in general to body and frame assemblies for vehicles. More specifically, this invention relates to an improved structure for a splice joint for connecting a pair of open channel side rail sections in a vehicular body and frame assembly that focuses stresses imposed thereon away from the longitudinal edges of the structural members.

Many land vehicles in common use, such as automobiles, vans, and trucks, include a body and frame assembly that is supported upon a plurality of ground-engaging wheels by a resilient suspension system. The structures of known body and frame assemblies can be divided into two general categories, namely, separate and unitized. In a typical separate body and frame assembly, the structural components of the body portion and the frame portion are separate and independent from one another. When assembled, the frame portion of the assembly is resiliently supported upon the vehicle wheels by the suspension system and serves as a platform upon which the body portion of the assembly and other components of the vehicle can be mounted. Separate body and frame assemblies of this general type are found in most older vehicles, but remain in common use today for many relatively large or specialized use modern vehicles, such as large vans, sport utility vehicles, and trucks. In a typical unitized body and frame assembly, the structural components of the body portion and the frame portion are combined into an integral unit that is resiliently supported upon the vehicle wheels by the suspension system. Unitized body and frame assemblies of this general type are found in many relatively small modern vehicles, such as automobiles and minivans.

One well known example of a separate type of vehicular body and frame assembly is commonly referred to as a ladder frame assembly. A ladder frame assembly includes a pair of longitudinally extending side rails that are joined together by a plurality of transversely extending cross members. The cross members connect the two side rails together and provide desirable lateral, vertical, and torsional stiffness to the ladder frame assembly. The cross members can also be used to provide support for various components of the vehicle. Depending upon the overall length of the vehicle and other factors, the side rails of a conventional ladder frame assembly may be formed either from a single, relatively long structural member or from a plurality of individual, relatively short structural sections that are secured together. For example, in vehicles having a relatively short overall length, it is known to form each of the side rails from a single integral structural member that extends the entire length of the vehicle body and frame assembly. In vehicles having a relatively long overall length, it is known to form each of the side rails from two or more individual structural sections that are secured together, such as by welding, to provide a unitary structural member that extends the entire length of the vehicle body and frame assembly.

Traditionally, the side rails of known vehicle body and frame assemblies have been formed from open channel structural members, i.e., structural members that have a non-continuous cross sectional shape (U-shaped or C-shaped channel members, for example). Thus, it is known to use a single integral open channel structural member to

form a side rail that extends the entire length of the vehicle body and frame assembly, as described above. Additionally, it is known to secure a plurality of such open channel structural members together to form the individual sections of a unitary side rail for a vehicle body and frame assembly, as also described above. It will be appreciated that each of such open channel structural members has a pair of longitudinally extending edges. It is known that these longitudinal edges are somewhat weaker than the interior portions of the structural members. Thus, when excessive stresses are imposed upon a side rail during use, cracks usually initiate at the longitudinally extending edges of the structural members and migrate inwardly toward the interior regions thereof.

A number of joint structures are known for permanently joining two open channel structural members to provide a unitary side rail in a ladder frame assembly. One known joint structure is commonly referred to as a butt joint. In a typical butt joint, a rearward end of a first side rail section is disposed directly adjacent to a forward end of a second side rail section, with no overlapping of the two side rail sections. The two adjacent ends of the side rail sections are then permanently secured together, such as by welding, to provide a unitary side rail. Another known joint structure is commonly referred to as a splice or overlap joint. In a typical splice joint, a rearward end of a first side rail section partially overlaps a forward end of a second side rail section. The two overlapped ends of the side rail sections are then permanently secured together, such as by welding, to provide a unitary side rail.

Although known butt and splice joint structures have been effective, it has been found that the such joint structures tend to focus stresses imposed upon the side rail at or near the longitudinal edges of the open channel structural members. Thus, it has been necessary to design known joint structures to accommodate the maximum loads at the longitudinal edges of the structural members. As a result, the other portions of the structural members are, in essence, over-designed for the loads intended to be carried thereon. This can result in the use of thicker or heavier materials to form the structural members, adding undesirable additional weight to the vehicle body and frame assembly. Thus, it would be desirable to provide an improved structure for a splice joint for connecting a pair of open channel side rail sections in a vehicular body and frame assembly that focuses stresses imposed thereon away from the longitudinal edges of the structural members.

SUMMARY OF THE INVENTION

This invention relates to an improved structure for a splice joint for connecting a pair of open channel side rail sections in a vehicular body and frame assembly that focuses stresses imposed thereon away from the longitudinal edges of the structural members. In a first aspect of this invention, one or both end portions of the side rail sections are formed having an offset. The end portions of the side rail sections overlap one another and are secured together by any conventional means, such as by welding. Preferably, the welds are made in such a manner that they terminate prior to reaching any of the longitudinally extending edges of the side rail sections. In a second aspect of this invention, the portions of the side rail sections are butt welded together. A support bracket is secured to the side rail sections by any conventional means, such as by welding. Again, the welds are preferably made in such a manner as to terminate prior to reaching any of the longitudinally extending edges of the side rail sections.

Various objects and advantages of this invention will become apparent to those skilled in the art from the follow-

ing detailed description of the preferred embodiments, when read in light of the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an exploded perspective view of a first embodiment of a splice joint for permanently a pair of open channel side rail sections to provide a unitary side rail for a vehicular body and frame assembly in accordance with this invention.

FIG. 2 is a perspective view of the first embodiment of the splice joint illustrated in FIG. 1 shown assembled.

FIG. 3 is a side elevational view of the first embodiment of the splice joint illustrated in FIG. 2.

FIG. 4 is a top plan view of the first embodiment of the splice joint illustrated in FIG. 2.

FIG. 5 is an exploded perspective view of a second embodiment of a splice joint for permanently a pair of open channel side rail sections to provide a unitary side rail for a vehicular body and frame assembly in accordance with this invention.

FIG. 6 is a perspective view of the second embodiment of the splice joint illustrated in FIG. 5 shown assembled.

FIG. 7 is a top plan view of the second embodiment of the splice joint illustrated in FIG. 6.

FIG. 8 is a perspective view of a third embodiment of a splice joint for permanently a pair of open channel side rail sections to provide a unitary side rail for a vehicular body and frame assembly in accordance with this invention.

FIG. 9 is a perspective view of a fourth embodiment of a splice joint for permanently a pair of open channel side rail sections to provide a unitary side rail for a vehicular body, and frame assembly in accordance with this invention.

FIG. 10 is a perspective view of a fifth embodiment of a splice joint for permanently a pair of open channel side rail sections to provide a unitary side rail for a vehicular body and frame assembly in accordance with this invention.

FIG. 11 is a perspective view of a sixth embodiment of a splice joint for permanently a pair of open channel side rail sections to provide a unitary side rail for a vehicular body and frame assembly in accordance with this invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings, there is illustrated in FIGS. 1 through 4 a first embodiment of a splice joint, indicated generally at 10, in accordance with this invention for permanently joining the end portions of a pair of open channel side rail sections, indicated generally at 11 and 21, to provide a unitary side rail, such as for a vehicular body and frame assembly. As will be discussed in detail below, the first and second side rail sections 11 and 21 have respective end portions that are connected together to form the splice joint 10. Throughout this discussion, relative terms, such as horizontal, vertical, upper, lower, front, and rear, will be used for the sake of facilitating the explanation of this invention and are not intended to limit the scope thereof.

The first side rail section 11 is a generally straight, elongated member having a generally C-shaped cross section defined by a vertical web 12, an upper horizontal flange 13 extending from an upper longitudinal edge of the web 12, and a lower horizontal flange 14 extending from a lower longitudinal edge of the web 12. The upper and lower flanges 13 and 14 are preferably formed integrally with the web 12 as shown, although such is not required. The upper and lower flanges 13 and 14 of the first side rail section 11

have respective longitudinally extending edges 15 and 16. Although shown as having a C-shaped cross section, it will be appreciated that the first side rail section 11 may be formed having any desired open channel cross sectional shape.

The second side rail section 21 is also a generally straight, elongated member having a generally C-shaped cross section defined by a vertical web 22, an upper horizontal flange 23 extending from an upper longitudinal edge of the web 22, and a lower horizontal flange 24 extending from a lower longitudinal edge of the web 22. The upper and lower flanges 23 and 24 are preferably formed integrally with the web 22 as shown, although such is not required. The upper and lower flanges 23 and 24 of the second side rail section 21 have respective longitudinally extending edges 25 and 26. Although shown as having a C-shaped cross section, it will be appreciated that the second side rail section 21 may be formed having any desired open channel cross sectional shape.

The end portion of the second side rail section 21 has a first offset portion provided in the web 22 thereof. The first offset portion is characterized by a curved portion 22a and a straight portion 22b extending parallel to, but offset from, the main portion of the web 22 of the second side rail section 21. The purpose for the first offset portion of the second side rail section 21 will be explained below. The end portion of the second rail section 21 further has a second offset portion provided in the upper and lower flanges 23 and 24 thereof. The second offset portion is characterized by curved portions 25a and 26a and straight portions 25b and 26b extending respectively parallel to, but offset from, the main portions of the longitudinal edges 25 and 26 of the upper and lower flanges 23 and 24. The purpose for the second offset portion of the second side rail section 21 will also be explained below. The web portion 22 terminates in a vertically extending edge having a cut-out 22c formed therein. The illustrated cut-out 22c is semi-circular in shape, although it may be formed having any other desired shape. The purpose for the cut-out 22c will also be explained below.

In the illustrated embodiment, the web 22 has a constant height throughout the end portion of the second side rail section 21, although such is not necessary. That height is slightly smaller than the height of the first side rail section 11 such that the second side rail section 21 may be nested within the first side rail section 11 as shown in FIGS. 2, 3, and 4. In this nested position, the web 22 and the upper and lower flanges 23 and 24 of the second side rail section 21 are disposed respectively adjacent to the web 12 and the upper and lower flanges 13 and 14 of the first side rail section 11. It will be appreciated, however, that the first and second side rail sections 11 and 21 may be sized in such a manner that the first side rail section 11 is nested within the second side rail section 21 if desired.

To assemble the splice joint 10, the first and second side rail sections 11 and 21 are disposed in the nested orientation illustrated in FIGS. 2, 3, and 4. Then, portions of the first and second side rail sections 11 and 21 are secured together by any conventional means, such as by welding. As best shown in FIGS. 2 and 4, a first weld 27 is provided between a portion of the leading edge of the upper flange 13 of the first side rail section 11 and a portion of the upper surface of the upper flange 23 of the second side rail section 21. This first weld 27 continues between the leading edge of the web 12 of the first side rail section 11 and the outer surface of the web 22 of the second side rail section 21, and further continues between a portion of the leading edge of the lower

flange **14** of the first side rail section **11** and a portion of the lower surface of the lower flange **24** of the second side rail section **21**. The first weld **27** may be continuous throughout this extent as illustrated, or may be formed in discrete areas. However, it will be noted that on the upper flanges **13** and **23**, the first weld **27** terminates prior to reaching either the longitudinally extending edge **15** of the first side rail upper flange **13** or the longitudinally extending edge **25** of the second side rail upper flange **23**. Similarly, the first weld **27** terminates prior to reaching either the longitudinally extending edge **16** of the first side rail lower flange **14** or the longitudinally extending edge **26** of the second side rail lower flange **24**.

As best shown in FIGS. **3** and **4**, a second weld **28** is provided between the straight portion **25b** of the longitudinally extending edge **25** of the upper flange **23** of the second side rail section **21** and the lower surface of the upper flange **13** of the first side rail section **21**. Similarly, a third weld **29** is provided between the straight portion **26b** of the longitudinally extending edge **26** of the lower flange **24** of the second side rail section **21** and the upper surface of the lower flange **14** of the first side rail section **11**. The second and third welds **28** and **29** may be continuous as illustrated, or may be formed in discrete areas. However, it will be noted that on the upper flanges **13** and **23**, the second weld **28** terminates prior to reaching the leading edge of the upper flange **13** of the first side rail section **11**. Similarly, on the lower flanges **14** and **24**, the third weld **29** terminates prior to reaching the leading edge of the lower flange **14** of the first side rail section **11**.

The single offset structure illustrated in FIGS. **1** through **4** provides a rated transition in stiffness between the first and second side rail sections **11** and **21** such that there is no significant loss in strength throughout the extent of the splice joint **10**. More importantly, the single offset structure creates no significant stress risers at or near any of the edges of the first and second side rail sections **11** and **12**. The termination of the welds **27**, **28**, and **29** prior to reaching such edges focuses the stresses imposed upon the splice joint **10** away from the longitudinally extending edges **15**, **16**, **25**, and **26** (as well as the leading and trailing edges thereof) and toward the interior regions of the first and second side rail members **11** and **21**. Thus, the splice joint **10** tends to prevent cracks or other failures from occurring at the various edges of the first and second side rail members **11** and **21**.

As mentioned above, the web portion **22** of the second side rail member **21** terminates in a vertically extending edge having a cut-out **22c** formed therein. The cut-out is provided to accommodate a certain amount of flexing in the splice joint **10**. With reference to FIG. **3**, it can be seen that when a vertical load is placed upon the overlapping portions of the first and second side rail members **11** and **21**, the central portion of the splice joint **10** will flex upwardly or downwardly in a horizontally extending plane. The cut-out **22c** accommodates a certain amount of this flexing movement by allowing the upper and lower terminal portions of the web **22** (i.e., those portions of the web **22** immediately above and below the cut-out **22c**) to flex relative to one another. In this manner, the creation of another undesirable stress riser is minimized.

Referring now to FIGS. **5** through **7**, there is illustrated a second embodiment of a splice joint, indicated generally at **30**, in accordance with this invention for permanently joining the end portions of a pair of open channel side rail sections, indicated generally at **31** and **41**, to provide a unitary side rail, such as for a vehicular body and frame assembly. The first side rail section **31** is a generally straight,

elongated member having a generally C-shaped cross section defined by a vertical web **32**, an upper horizontal flange **33** extending from an upper longitudinal edge of the web **32**, and a lower horizontal flange **34** extending from a lower longitudinal edge of the web **32**. The upper and lower flanges **33** and **34** are preferably formed integrally with the web **32** as shown, although such is not required. The upper and lower flanges **33** and **34** of the first side rail section **31** have respective longitudinally extending edges **35** and **36**. Although shown as having a C-shaped cross section, it will be appreciated that the first side rail section **31** may be formed having any desired open channel cross sectional shape. The end portion of the first side rail section **31** has an offset portion provided in the web **32** thereof. The first offset portion is characterized by a curved portion **32a** and a straight portion **32b** extending parallel to, but offset from, the main portion of the web **32** of the first side rail section **30**. The purpose for the offset portion of the first side rail section **31** will be explained below.

The second side rail section **41** is also a generally straight, elongated member having a generally C-shaped cross section defined by a vertical web **42**, an upper horizontal flange **43** extending from an upper longitudinal edge of the web **42**, and a lower horizontal flange **44** extending from a lower longitudinal edge of the web **42**. The upper and lower flanges **43** and **44** are preferably formed integrally with the web **42** as shown, although such is not required. The upper and lower flanges **43** and **44** of the second side rail section **41** have respective longitudinally extending edges **45** and **46**. Although shown as having a C-shaped cross section, it will be appreciated that the second side rail section **41** may be formed having any desired open channel cross sectional shape.

The end portion of the second side rail section **41** has a first offset portion provided in the web **42** thereof. The first offset portion is characterized by a curved portion **42a** and a straight portion **42b** extending parallel to, but offset from, the main portion of the web **42** of the second side rail section **40**. The purpose for the first offset portion of the second side rail section **41** will be explained below. The end portion of the second rail section **41** further has a second offset portion provided in the upper and lower flanges **43** and **44** thereof. The second offset portion is characterized by curved portions **45a** and **46a** and straight portions **45b** and **46b** extending respectively parallel to, but offset from, the main portions of the longitudinal edges **45** and **46** of the upper and lower flanges **43** and **44**. The purpose for the second offset portion of the second side rail section **41** will also be explained below. The web portion **42** terminates in a vertically extending edge having a cut-out **42c** formed therein. The illustrated cut-out **42c** is semi-circular in shape, although it may be formed having any other desired shape. The purpose for the cut-out **42c** will also be explained below.

In the illustrated embodiment, the web **42** has a constant height throughout the end portion of the second side rail section **41**, although such is not necessary. That height is slightly smaller than the height of the first side rail section **31** such that the second side rail section **41** may be nested within the first side rail section **31** as shown in FIGS. **6** and **7**. In this nested position, the web **42** and the upper and lower flanges **43** and **44** of the second side rail section **41** are disposed respectively adjacent to the web **32** and the upper and lower flanges **33** and **34** of the first side rail section **31**. It will be appreciated, however, that the first and second side rail sections **31** and **41** may be sized in such a manner that the first side rail section **31** is nested within the second side rail section **41** if desired.

To assemble the splice joint **30**, the first and second side rail sections **31** and **41** are disposed in the nested orientation illustrated in FIGS. **6** and **7**. Then, portions of the first and second side rail sections **31** and **41** are secured together by any conventional means, such as by welding. As best shown in FIGS. **6** and **7**, a first weld **47** is provided between a portion of the leading edge of the upper flange **33** of the first side rail section **31** and a portion of the upper surface of the upper flange **43** of the second side rail section **41**. This first weld **47** continues between the leading edge of the web **32** of the first side rail section **31** and the outer surface of the web **42** of the second side rail section **41**, and further continues between a portion of the leading edge of the lower flange **34** of the first side rail section **31** and a portion of the lower surface of the lower flange **44** of the second side rail section **41**. The first weld **47** may be continuous throughout this extent as illustrated, or may be formed in discrete areas. However, it will be noted that on the upper flanges **33** and **43**, the first weld **47** terminates prior to reaching either the longitudinally extending edge **35** of the first side rail upper flange **33** or the longitudinally extending edge **45** of the second side rail upper flange **43**. Similarly, the first weld **47** terminates prior to reaching either the longitudinally extending edge **36** of the first side rail lower flange **34** or the longitudinally extending edge **46** of the second side rail lower flange **46**.

As shown in FIG. **7**, a second weld **48** is provided between the straight portion **45b** of the longitudinally extending edge **45** of the upper flange **43** of the second side rail section **41** and the lower surface of the upper flange **33** of the first side rail section **31**. Similarly, as shown in FIG. **6**, a third weld **49** is provided between the straight portion **46b** of the longitudinally extending edge **46** of the lower flange **44** of the second side rail section **41** and the upper surface of the lower flange **34** of the first side rail section **31**. The second and third welds **48** and **49** may be continuous as illustrated, or may be formed in discrete areas. However, it will be noted that on the upper flanges **33** and **43**, the second weld **48** terminates prior to reaching the leading edge of the upper flange **33** of the first side rail section **31**. Similarly, on the lower flanges **34** and **44**, the third weld **49** terminates prior to reaching the leading edge of the lower flange **34** of the first side rail section **31**. The double offset structure illustrated in FIGS. **5** through **7** provides the same advantages as described above, but further provides an additional measure of stiffness to the splice joint **30**.

Referring now to FIG. **8**, there is illustrated a third embodiment of a splice joint, indicated generally at **50**, in accordance with this invention for permanently joining the end portions of a pair of open channel side rail sections, indicated generally at **51** and **61**, to provide a unitary side rail, such as for a vehicular body and frame assembly. The first side rail section **51** is a generally straight, elongated member having a generally C-shaped cross section defined by a vertical web **52**, an upper horizontal flange **53** extending from an upper longitudinal edge of the web **52**, and a lower horizontal flange **54** extending from a lower longitudinal edge of the web **52**. The upper and lower flanges **53** and **54** are preferably formed integrally with the web **52** as shown, although such is not required. The upper and lower flanges **53** and **54** of the first side rail section **51** have respective longitudinally extending edges **55** and **56**. Although shown as having a C-shaped cross section, it will be appreciated that the first side rail section **51** may be formed having any desired open channel cross sectional shape.

Similarly, the second side rail section **61** is a generally straight, elongated member having a generally C-shaped

cross section defined by a vertical web **62**, an upper horizontal flange **63** extending from an upper longitudinal edge of the web **62**, and a lower horizontal flange **64** extending from a lower longitudinal edge of the web **62**. The upper and lower flanges **63** and **64** are preferably formed integrally with the web **62** as shown, although such is not required. The upper and lower flanges **63** and **64** of the second side rail section **61** have respective longitudinally extending edges **65** and **66**. Although shown as having a C-shaped cross section, it will be appreciated that the second side rail section **61** may be formed having any desired open channel cross sectional shape.

In the illustrated embodiment, the web **62** has a constant height throughout the end portion of the second side rail section **61**, although such is not necessary. That height is slightly smaller than the height of the first side rail section **51** such that the second side rail section **61** may be nested within the first side rail section **51** as shown in FIG. **8**. In this nested position, the web **62** and the upper and lower flanges **63** and **64** of the second side rail section **61** are disposed respectively adjacent to the web **52** and the upper and lower flanges **53** and **54** of the first side rail section **51**. It will be appreciated, however, that the first and second side rail sections **51** and **61** may be sized in such a manner that the first side rail section **51** is nested within the second side rail section **61** if desired.

To assemble the splice joint **50**, the first and second side rail sections **51** and **61** are disposed in the nested orientation illustrated in FIG. **8**. Then, portions of the first and second side rail sections **51** and **61** are secured together by any conventional means, such as by welding. A first weld **67** is provided between the leading edge of the upper flange **53** of the first side rail section **51** and the upper surface of the upper flange **63** of the second side rail section **61**. This first weld **67** continues between the leading edge of the web **52** of the first side rail section **51** and the outer surface of the web **62** of the second side rail section **61**, and further continues between the leading edge of the lower flange **54** of the first side rail section **51** and the lower surface of the lower flange **64** of the second side rail section **61**. The first weld **67** may be continuous throughout this extent as illustrated, or may be formed in discrete areas. In this embodiment, the first weld **67** may, if desired, extend completely to either the longitudinally extending edges **55** and **65** of the upper flanges **53** and **63** or the longitudinally extending edges **56** and **66** of the lower flanges **54** and **64**.

To prevent or minimize the stress risers that would otherwise be present at the longitudinally extending edges **55**, **56**, **65**, and **66**, the splice joint **50** includes a support bracket, indicated generally at **70**. The support bracket **70** is a generally straight, elongated member having a generally C-shaped cross section defined by a vertical web **71**, an upper horizontal flange **72** extending from an upper longitudinal edge of the web **71**, and a lower horizontal flange **73** extending from a lower longitudinal edge of the web **71**. The upper and lower flanges **72** and **73** are preferably formed integrally with the web **71** as shown, although such is not required. The ends of the web portion **71** of the support bracket **70** terminate in vertically extending edges, each of which has a cut-out **71a** formed therein.

The upper flange **72** of the support bracket **70** extends adjacent to the upper flanges **53** and **63** of the first and second side rail members **51** and **61**, respectively. A second weld **74** is provided between portions of the upper flange **72** of the support bracket **70** and portions of the upper surface of the upper flange **53** of the first side rail section **51**. A third weld **75** is provided between portions of the upper flange **72**

of the support bracket **70** and portions of the upper surface of the upper flange **63** of the second side rail section **61**. Similarly, a fourth weld (not shown) is provided between portions of the lower flange **73** of the support bracket **70** and portions of the lower surface of the lower flange **54** of the first side rail section **51**, and a fifth weld (not shown) is provided between portions of the lower flange **73** of the support bracket **70** and portions of the lower surface of the lower flange **64** of the second side rail section **61**. Each of these welds may be continuous as illustrated, or may be formed in discrete areas. However, it will be noted that on the upper flanges **53**, the second weld **74** terminates prior to reaching the leading edge of the upper flange **53**. Similarly, the third weld **75** terminates prior to reaching the leading edge of the upper flange **53**. The support bracket **70** provides the same advantages as described above by preventing or minimizing the stress risers that would otherwise be present at the longitudinally extending edges **55**, **56**, **65**, and **66** of the splice joint **50**.

Referring now to FIG. **9**, there is illustrated a fourth embodiment of a splice joint, indicated generally at **90**, in accordance with this invention for permanently joining the end portions of a pair of open channel side rail sections, indicated generally at **91** and **101**, to provide a unitary side rail, such as for a vehicular body and frame assembly. The first side rail section **91** is a generally straight, elongated member having a generally C-shaped cross section defined by a vertical web **92**, an upper horizontal flange **93** extending from an upper longitudinal edge of the web **92**, and a lower horizontal flange **94** extending from a lower longitudinal edge of the web **92**. The upper and lower flanges **93** and **94** are preferably formed integrally with the web **92** as shown, although such is not required. The upper and lower flanges **93** and **94** of the first side rail section **91** have respective longitudinally extending edges **95** and **96**. Although shown as having a C-shaped cross section, it will be appreciated that the first side rail section **91** may be formed having any desired open channel cross sectional shape.

Similarly, the second side rail section **101** is a generally straight, elongated member having a generally C-shaped cross section defined by a vertical web **102**, an upper horizontal flange **103** extending from an upper longitudinal edge of the web **102**, and a lower horizontal flange **104** extending from a lower longitudinal edge of the web **102**. The upper and lower flanges **103** and **104** are preferably formed integrally with the web **102** as shown, although such is not required. The upper and lower flanges **103** and **104** of the second side rail section **101** have respective longitudinally extending edges **105** and **106**. Although shown as having a C-shaped cross section, it will be appreciated that the second side rail section **101** may be formed having any desired open channel cross sectional shape.

In the illustrated embodiment, the web **92** has a constant height throughout the end portion of the first side rail section **91**, although such is not necessary. Similarly, the web **102** has a constant height throughout the end portion of the second side rail section **101**, although such is not necessary. The height of the web **92** and the web **102** are approximately equal at the ends thereof such that the leading edge of the first side rail section **91** may be moved into abutment with the trailing edge of the second side rail section **101**. To assemble the splice joint **90**, the abutting edges of the first and second side rail sections **91** and **101** are secured together by any conventional means, such as by a butt weld **107**. The butt weld **107** extends throughout the abutting edges of the upper flanges **93** and **103**, the webs **92** and **102**, and the

lower flanges **94** and **104**. The butt weld **107** may be continuous throughout this extent as illustrated, or may be formed in discrete areas. In this embodiment, the butt weld **107** may, if desired, extend completely to either the longitudinally extending edges **95** and **105** of the upper flanges **93** and **103**, respectively, or the longitudinally extending edges **96** and **106** of the lower flanges **94** and **104**, respectively.

To prevent or minimize the stress risers that would otherwise be present at the longitudinally extending edges **95**, **96**, **105**, and **106**, the splice joint **90** includes a support bracket, indicated generally at **110**. The support bracket **110** is a generally C-shaped member defined by a vertical web **111**, an upper horizontal flange **112** extending from an upper longitudinal edge of the web **111**, and a lower horizontal flange **113** extending from a lower longitudinal edge of the web **111**. The upper flange **111** further includes a curved lip section **114** that extends from the upper flange **112** around the longitudinally extending edges **95** and **105** and across portions of the upper surfaces of the upper flanges **93** and **103**. Similarly, the lower flange **113** further includes a curved lip section **115** that extends from the lower flange **113** around the longitudinally extending edges **96** and **106** and across portions of the lower surfaces of the lower flanges **94** and **104**. The curved lip sections **114** and **115** are preferably formed integrally with the upper and lower flanges **112** and **113** as shown, although such is not required. The longitudinal ends of the web portion **111** of the support bracket **110** terminate in vertically extending edges **116** and **117**.

The support bracket **110** is disposed within the first and second side rail members **91** and **101** at the junction thereof such that the upper flange **112** of the support bracket **110** contacts portions of the lower surface of both the upper flange **93** of the first side rail member **91** and the upper flange **103** of the second side rail member **101**. Similarly, the web **111** of the support bracket **110** contacts portions of the inner surface of both the web **92** of the first side rail member **91** and the web **102** of the second side rail member **101**. Also, the lower flange **113** of the support bracket **110** contacts portions of the upper surface of both the lower flange **94** of the first side rail member **91** and the lower flange **104** of the second side rail member **101**. As further shown therein, the upper lip section **114** of the support bracket **110** extends about portions of the longitudinally extending edges **95** and **105** and the upper surfaces of both the upper flange **93** of the first side rail member **91** and the upper flange **103** of the second side rail member **101**. Similarly, the lower lip section **115** of the support bracket **110** extends about portions of the longitudinally extending edges **96** and **106** and the lower surfaces of both the lower flange **94** of the first side rail member **91** and the lower flange **104** of the second side rail member **101**.

A second weld **118** is provided between the edge of the upper lip section **114** of the support bracket **110** and portions of the upper surface of the upper flange **93** of the first side rail section **91** and of the upper flange **103** of the second side rail section **101**. Similarly, a third weld (not shown) is provided between the edge of the lower lip section **115** of the support bracket **110** and portions of the lower surface of the lower flange **94** of the first side rail section **91** and of the lower flange **104** of the second side rail section **101**. A fourth weld **119** is provided between the leading edge of the support bracket **110** and the upper surface of the lower flange **104**, the inner surface of the web section **102**, and the lower surface of the upper flange **103** of the second side rail member **101**. Similarly, a fifth weld (not shown) is provided between the trailing edge of the support bracket **110** and the upper surface of the lower flange **94**, the inner surface of the

web section **92**, and the lower surface of the upper flange **93** of the first side rail member **91**. The fourth and fifth welds **119** may be continuous as illustrated, or may be formed in discrete areas. However, it will be noted that on the upper flanges **93** and **103** and the lower flanges **94** and **104**, the fourth and fifth welds **119** terminates prior to reaching the longitudinally extending edges **95** and **105** of the upper flanges **93** and **103**, respectively, and the longitudinally extending edges **96** and **106** of the lower flanges **94** and **104**, respectively. The support bracket **110** provides the same advantages as described above by preventing or minimizing the stress risers that would otherwise be present at the longitudinally extending edges **95**, **96**, **105**, and **106** of the splice joint **90**.

Referring now to FIG. **10**, there is illustrated a fifth embodiment of a splice joint, indicated generally at **120**, in accordance with this invention for permanently joining the end portions of a pair of open channel side rail sections, indicated generally at **121** and **131**, to provide a unitary side rail, such as for a vehicular body and frame assembly. The first side rail section **121** is a generally straight, elongated member having a generally C-shaped cross section defined by a vertical web **122**, an upper horizontal flange **123** extending from an upper longitudinal edge of the web **122**, and a lower horizontal flange **124** extending from a lower longitudinal edge of the web **122**. The upper and lower flanges **123** and **124** are preferably formed integrally with the web **122** as shown, although such is not required. The upper and lower flanges **123** and **124** of the first side rail section **121** have respective longitudinally extending edges **125** and **126**. Although shown as having a C-shaped cross section, it will be appreciated that the first side rail section **121** may be formed having any desired open channel cross sectional shape.

Similarly, the second side rail section **131** is a generally straight, elongated member having a generally C-shaped cross section defined by a vertical web **132**, an upper horizontal flange **133** extending from an upper longitudinal edge of the web **132**, and a lower horizontal flange **134** extending from a lower longitudinal edge of the web **132**. The upper and lower flanges **133** and **134** are preferably formed integrally with the web **132** as shown, although such is not required. The upper and lower flanges **133** and **134** of the second side rail section **131** have respective longitudinally extending edges **135** and **136**. Although shown as having a C-shaped cross section, it will be appreciated that the second side rail section **131** may be formed having any desired open channel cross sectional shape.

In the illustrated embodiment, the web **122** has a constant height throughout the end portion of the first side rail section **121**, although such is not necessary. Similarly, the web **132** has a constant height throughout the end portion of the second side rail section **131**, although such is not necessary. The height of the web **122** and the web **132** are approximately equal at the ends thereof such that the leading edge of the first side rail section **121** may be moved into abutment with the trailing edge of the second side rail section **131**. To assemble the splice joint **120**, the abutting edges of the first and second side rail sections **121** and **131** are secured together by any conventional means, such as by a butt weld **137**. The butt weld **137** extends throughout the abutting edges of the upper flanges **123** and **133**, the webs **122** and **132**, and the lower flanges **124** and **134**. The butt weld **137** may be continuous throughout this extent as illustrated, or may be formed in discrete areas. In this embodiment, the butt weld **137** may, if desired, extend completely to either the longitudinally extending edges **125** and **135** of the upper

flanges **123** and **133**, respectively, or the longitudinally extending edges **126** and **136** of the lower flanges **124** and **134**, respectively.

To prevent or minimize the stress risers that would otherwise be present at the longitudinally extending edges **125**, **126**, **135**, and **136**, the splice joint **120** includes a support bracket, indicated generally at **140**. The support bracket **140** is a generally C-shaped member defined by a vertical web **141**, an upper horizontal flange (not shown) extending from an upper longitudinal edge of the web **141**, and a lower horizontal flange **143** extending from a lower longitudinal edge of the web **141**. The longitudinal ends of the web portion **141** of the support bracket **140** terminate in vertically extending edges **144** and **145**. The support bracket **140** is disposed within the first and second side rail members **121** and **131** at the junction thereof such that the upper flange of the support bracket **140** contacts portions of the lower surface of both the upper flange **123** of the first side rail member **121** and the upper flange **133** of the second side rail member **131**. Similarly, the web **141** of the support bracket **140** contacts portions of the inner surface of both the web **122** of the first side rail member **121** and the web **132** of the second side rail member **131**. Also, the lower flange **143** of the support bracket **140** contacts portions of the upper surface of both the lower flange **124** of the first side rail member **121** and the lower flange **134** of the second side rail member **131**.

A second weld **148** is provided between the leading edge of the support bracket **140** and the upper surface of the lower flange **134**, the inner surface of the web section **132**, and the lower surface of the upper flange **133** of the second side rail member **131**. Similarly, a third weld (not shown) is provided between the trailing edge of the support bracket **140** and the upper surface of the lower flange **124**, the inner surface of the web section **122**, and the lower surface of the upper flange **123** of the first side rail member **121**. The second and third welds **148** may be continuous as illustrated, or may be formed in discrete areas. If desired, the second and third welds **148** may be co-extensive, extending along both the upper and lower longitudinal edges of the support bracket **140**, such as shown at **149**. The support bracket **140** provides the same advantages as described above by preventing or minimizing the stress risers that would otherwise be present at the longitudinally extending edges **95**, **96**, **105**, and **106** of the splice joint **90**.

Referring now to FIG. **11**, there is illustrated a sixth embodiment of a splice joint, indicated generally at **150**, in accordance with this invention for permanently joining the end portions of a pair of open channel side rail sections, indicated generally at **151** and **161**, to provide a unitary side rail, such as for a vehicular body and frame assembly. The first side rail section **151** is a generally straight, elongated member having a generally C-shaped cross section defined by a vertical web **152**, an upper horizontal flange **153** extending from an upper longitudinal edge of the web **152**, and a lower horizontal flange **154** extending from a lower longitudinal edge of the web **152**. The upper and lower flanges **153** and **154** are preferably formed integrally with the web **152** as shown, although such is not required. The upper and lower flanges **153** and **154** of the first side rail section **151** have respective longitudinally extending edges **155** and **156**. Although shown as having a C-shaped cross section, it will be appreciated that the first side rail section **151** may be formed having any desired open channel cross sectional shape.

Similarly, the second side rail section **161** is a generally straight, elongated member having a generally C-shaped

cross section defined by a vertical web **162**, an upper horizontal flange **163** extending from an upper longitudinal edge of the web **162**, and a lower horizontal flange **164** extending from a lower longitudinal edge of the web **162**. The upper and lower flanges **163** and **164** are preferably formed integrally with the web **162** as shown, although such is not required. The upper and lower flanges **163** and **164** of the second side rail section **161** have respective longitudinally extending edges **165** and **166**. Although shown as having a C-shaped cross section, it will be appreciated that the second side rail section **161** may be formed having any desired open channel cross sectional shape.

In the illustrated embodiment, the web **152** has a constant height throughout the end portion of the first side rail section **151**, although such is not necessary. Similarly, the web **162** has a constant height throughout the end portion of the second side rail section **161**, although such is not necessary. The height of the web **152** and the web **162** are approximately equal at the ends thereof such that the leading edge of the first side rail section **151** may be moved into abutment with the trailing edge of the second side rail section **161**. To assemble the splice joint **150**, the abutting edges of the first and second side rail sections **151** and **161** are secured together by any conventional means, such as by a butt weld **167**. The butt weld **167** extends throughout the abutting edges of the upper flanges **153** and **163**, the webs **152** and **162**, and the lower flanges **154** and **164**. The butt weld **167** may be continuous throughout this extent as illustrated, or may be formed in discrete areas. In this embodiment, the butt weld **167** may, if desired, extend completely to either the longitudinally extending edges **155** and **165** of the upper flanges **153** and **163**, respectively, or the longitudinally extending edges **156** and **166** of the lower flanges **154** and **164**, respectively.

To prevent or minimize the stress risers that would otherwise be present at the longitudinally extending edges **155**, **156**, **165**, and **166**, the splice joint **150** includes a support bracket, indicated generally at **170**. The support bracket **170** has a vertical web **171** and a pair of end portions **172** and **173**. The web **171** is aligned with the longitudinally extending edges **155**, **156**, **165**, and **166** and is secured thereto by any conventional means, such as by second and third welds **174** and **175**. The end portions **172** and **173** are angled inwardly from the web **171** so as to extend away from the longitudinally extending edges **155**, **156**, **165**, and **166**. A fourth weld **176** is provided for securing a portion of the lower edge of the leading end portion **172** to a portion of the upper surface of the lower flange **165** of the second side rail section **161**. A fifth weld **177** is provided for securing a portion of the lower edge of the trailing end portion **173** to a portion of the upper surface of the lower flange **155** of the first side rail portion **151**. Similar welds (not shown) are provided for securing portions of the upper edges of the end portions **172** and **173** respectively to portions of the lower surfaces of the upper flanges **153** and **163** of the first and second side rail sections **151** and **161**. If desired, the end portions **172** and **173** of the support bracket **170** may terminate in vertically extending edges having respective cut-outs **172a** and **173a** formed therein for the same purpose as described above.

In accordance with the provisions of the patent statutes, the principle and mode of operation of this invention have been explained and illustrated in its preferred embodiments. However, it must be understood that this invention may be

practiced otherwise than as specifically explained and illustrated without departing from its spirit or scope.

What is claimed is:

1. A unitary side rail for use in a vehicular body and frame assembly comprising:

a first side rail section including an end portion having a web; and

a second side rail section including an end portion having a web, said second side rail section web including a main portion and an offset portion extending from said main portion to an end of said second side rail section, said first side rail section web abutting said main portion of said second side rail section web, said first side rail section web being spaced apart from said offset portion and said end of said second side rail section web, said end portions of said first and second side rail sections being secured together at a joint to form the unitary side rail for use in a vehicle body and frame assembly.

2. The unitary side rail defined in claim 1 wherein said offset portion of said second side rail section web includes a curved portion and a straight portion extending parallel, but offset from said main portion of said second side rail section web.

3. The unitary side rail defined in claim 1 wherein said end portion of said first side rail section further includes first and second flanges extending from said web.

4. The unitary side rail defined in claim 1 wherein said end portion of said second side rail section further includes first and second flanges extending from said web.

5. The unitary side rail defined in claim 1 wherein said end portion of said first side rail section further includes first and second flanges extending from said web, and wherein said end portion of said second side rail section further includes first and second flanges extending from said web.

6. The unitary side rail defined in claim 5 wherein said first flange of said first side rail section abuts said first flange of said second side rail section.

7. The unitary side rail defined in claim 5 wherein said second flange of said first side rail section abuts said second flange of said second side rail section.

8. The unitary side rail defined in claim 5 wherein said first flange of said first side rail section abuts said first flange of said second side rail section, and wherein said second flange of said first side rail section abuts said second flange of said second side rail section.

9. The unitary side rail defined in claim 5 wherein said end portion of said second side rail section extends between said first and second flanges of said end portion of said first side rail section.

10. The unitary side rail defined in claim 1 wherein said end portion of said second side rail section further includes first and second flanges extending from said web and terminating in respective edges, said edges having offset portions formed therein.

11. The unitary side rail defined in claim 10 wherein each of said offset portions of said first and second flanges of said second side rail section includes a curved portion and a straight portion extending parallel, but offset from, said edge.

12. The unitary side rail defined in claim 1 wherein said end of said second side rail section terminates in an edge having a cut-out formed therein.