

(12) United States Patent Barraud et al.

(54) MICROPUMP

(71) Applicant: Tandem Diabetes Care Switzerland

Sàrl, St-Sulpice (CH)

(72) Inventors: Antoine Barraud, Lonay (CH); Simon

Kuenzi, Lausanne (CH); Remy Rysman, Lausanne (CH)

Assignee: Tandem Diabetes Care Switzerland

Sarl, St-Sulpice (CH)

Subject to any disclaimer, the term of this (*) Notice:

patent is extended or adjusted under 35

U.S.C. 154(b) by 368 days.

(21) Appl. No.: 15/777,284

(22) PCT Filed: Nov. 15, 2016

(86) PCT No.: PCT/IB2016/056870

§ 371 (c)(1),

(2) Date: May 18, 2018

(87) PCT Pub. No.: WO2017/085624

PCT Pub. Date: May 26, 2017

(65)**Prior Publication Data**

> US 2018/0339102 A1 Nov. 29, 2018

(30)Foreign Application Priority Data

Nov. 20, 2015 (EP) 15195733

(51) Int. Cl.

A61M 5/142 (2006.01)F04B 43/00 (2006.01)

(Continued)

(52) U.S. Cl.

CPC A61M 5/14248 (2013.01); A61M 5/14224 (2013.01); A61M 5/16813 (2013.01);

(Continued)

US 11,806,502 B2 (10) Patent No.:

(45) **Date of Patent:**

Nov. 7, 2023

(58) Field of Classification Search

CPC A61M 5/14248; A61M 5/14244; A61M 5/14224; A61M 2005/14268;

(Continued)

References Cited (56)

U.S. PATENT DOCUMENTS

 $2,105,200\ A\ *\ 1/1938\ Phelps\\ F04B\ 43/082$ 2,412,397 A * 12/1946 Harper F04B 43/082 417/474

(Continued)

FOREIGN PATENT DOCUMENTS

CA2987866 A1 3/2012 DE 102013111800 A1 4/2015 (Continued)

OTHER PUBLICATIONS


Kristin Lewotsky, Tutorial: The Basics of Stepper Motors—Part I, Feb. 12, 2014 (Year: 2014).*

(Continued)

Primary Examiner - Kami A Bosworth Assistant Examiner - Antarius S Daniel (74) Attorney, Agent, or Firm — Eversheds Sutherland (US) LLP; Christopher C. Bolten; Robert D. Ward

ABSTRACT (57)

Micropump (10) including a support structure (14), a pump tube (16), and an actuation system (18) comprising one or more pump chamber actuators (28), the pump tube comprising a pump chamber portion (24) defining therein a pump chamber (26), an inlet portion (20) for inflow of fluid into the pump chamber, and an outlet portion (22) for outflow of fluid from the pump chamber. The inlet, outlet and pump chamber portions form part of a continuous section of tube made of a supple material. The one or more pump chamber actuators are configured to bias against the pump chamber portion to expel liquid contained in the pump (Continued)



Page 2

chamber via the outlet portion, respectively to bias away from the pump chamber portion to allow liquid to enter the pump chamber via the inlet portion. The pump chamber portion has a cross-sectional area Ap in an expanded state that is larger than a cross-sectional area Ai of the pump tube at the inlet and outlet portions.

27 Claims, 9 Drawing Sheets

(51)	Int. Cl.					
	F04B 43/09	(2006.01)				
	F04B 43/04	(2006.01)				
	F04B 19/00	(2006.01)				
	F04B 43/14	(2006.01)				
	A61M 5/168	(2006.01)				
	F04B 49/22	(2006.01)				
	F04B 53/10	(2006.01)				
	B29C 69/02	(2006.01)				
	B29K 27/12	(2006.01)				
	B29L 31/00	(2006.01)				
(52)	U.S. Cl.					
	CPC <i>F04B 19/006</i> (2013.01); <i>F04B 43/0072</i>					
	(2013.01); F04B 43/043 (2013.01); F04B					
	43/09 (2013.01); F04B 43/095 (2013.01);					
	F04B 43/14 (2013.01); F04B 49/22 (2013.01);					
		2 (2013.01); A61M 2005/14268				
	(2013.01); A61.	M 2205/3317 (2013.01); A61M				
		13.01); <i>B29C 69/02</i> (2013.01);				
	B29K 2027/	'12 (2013.01); B29L 2031/7496				
		(2013.01)				
(58)	Field of Classification	on Search				
		; F04B 43/0072; F04B 43/043;				
	F04B 43/	095; F04B 43/09; F04B 49/22;				
	F16K	7/00; F16K 7/066; F16K 7/02;				
		F16K 7/04; F16K 7/06				
	See application file for	or complete search history.				

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,609,069 A *	9/1971	Martinelli F04B 43/082
3,003,003 11	3, 13, 1	
		417/474
4,042,153 A *	8/1977	Callahan B01J 2/02
		222/207
4,199,307 A *	4/1980	Jassawalla A61M 5/14224
4,155,507 A	T/1700	
		128/DIG. 12
4,218,416 A	8/1980	Gokcen
4,236,880 A	12/1980	Archibald
4,273,121 A *	6/1981	Jassawalla A61M 5/14224
1,273,121 11	0, 1501	
		604/153
4,290,346 A	9/1981	Bujan
4,322,201 A *	3/1982	Archibald F04B 7/00
		417/279
4,410,322 A	10/1983	Archibald
4,482,347 A *	11/1984	Borsanyi A61M 5/14244
		417/474
4,493,704 A	1/1985	Beard et al.
4,501,405 A *	2/1985	Usry F04B 43/09
4,501,405 A	2/1903	,
		417/474
4,596,575 A	6/1986	Rosenberg et al.
4,616,802 A	10/1986	Tseng et al.
4,617,014 A	10/1986	Cannon et al.
4,657,490 A	4/1987	Abbott
4,854,836 A *	8/1989	Borsanyi F04B 43/0072
		417/474
4,934,372 A	6/1990	Corenman et al.
	10/1991	Simons et al.
5,050,592 A	10/1991	Simons et al.

5.066.279	4	11/1001	Hirschberg et al.	
5,066,278		11/1991		
5,088,522		2/1992	Rath et al.	
5,137,023	A	8/1992	Mendelson et al.	
5,217,355	A	6/1993	Hyman et al.	
5,252,044	A *	10/1993	Raines	F04B 43/021
				417/479
5,318,546	۸	6/1994	Bierman	1277 175
, ,				
5,482,446		1/1996	Williamson et al.	
5,637,095	A	6/1997	Nason et al.	
5,851,197	A	12/1998	Marano et al.	
5,964,583	A	10/1999	Danby	
6,093,172		7/2000	Funderburk et al.	
6,165,151	A	12/2000	Weiner	
6,293,925		9/2001	Safabash et al.	
6,607,509		8/2003	Bobroff et al.	
6,723,077	B2	4/2004	Pickup et al.	
6,801,420	B2	10/2004	Talbot et al.	
6,830,562		12/2004	Mogensen et al.	
6,881,043		4/2005	Barak	
7,137,964		11/2006	Flaherty	
7,204,823		4/2007	Estes et al.	
7,315,753	B2	1/2008	Baker, Jr. et al.	
7,329,239	B2	2/2008	Safabash et al.	
7,356,364	B1	4/2008	Bullock et al.	
7,879,023		2/2011	Wood, Jr.	
		2/2011	· .	
7,879,026			Estes et al.	
8,152,771	B2	4/2012	Mogensen et al.	
8,377,002	B2 *	2/2013	Hanson	A61M 5/003
				604/533
8,657,807	B2	2/2014	Blomquist	
9,114,208		8/2015	Smith et al.	
9,517,024		12/2016	Kiani et al.	
9,610,018		4/2017	Gulati et al.	
9,615,779		4/2017	Pryor et al.	
9,636,457		5/2017	Newberry et al.	
9,735,502	B2	8/2017	Stevens et al.	
9,735,893	B1	8/2017	Aleksov et al.	
9,820,691	B2	11/2017	Kiani	
9,833,152	B2	12/2017	Kiani et al.	
9,931,065	B2	4/2018	Pryor et al.	
9,967,040	B2	5/2018	Aleksov et al.	
9,980,140	B1	5/2018	Spencer et al.	
	B2	6/2018	Michaud et al.	
10,137,245	B2	11/2018	Melker et al.	
10,278,732	B2	5/2019	Schoonmaker et al.	
	B1		Cook et al.	
		5/2019		
10,398,320		9/2019	Kiani et al.	
10,518,069		12/2019	Boden, Jr. et al.	
11,139,754		10/2021	Shi et al.	
11,241,530		2/2022	Fridez et al.	
11,529,460		12/2022	Pruijs et al.	
2002/0001530	A1	1/2002	Doi et al.	
2002/0071225		6/2002	Sheldon et al.	
2002/0091358	A1	7/2002	Klitmose	
2002/0169439		11/2002	Flaherty	
2004/0064088		4/2004	Gorman et al.	
2004/0082920	Al	4/2004	Mori et al.	
2004/0092873	Al	5/2004	Moberg	
2004/0158207	Al	8/2004	Hunn et al.	
2005/0043687	A1	2/2005	Mogensen et al.	
2005/0101912	A1	5/2005	Faust et al.	
2005/0124936	A1	6/2005	Mogensen et al.	
2005/0277887	A1	12/2005	Douglas et al.	
2006/0036214	$\mathbf{A}1$	2/2006	Mogensen et al.	
2007/0060874	A1	3/2007	Nesbitt et al.	
2007/0191772	A1	8/2007	Wojcik	
2007/0191773	Al	8/2007	Wojcik	
2007/0191775	Al	9/2007	Kamen et al.	
2008/0051727	Al	2/2008	Moberg et al.	
	Al			
2008/0091175		4/2008	Frikart et al.	
2008/0097289	A1	4/2008	Steil et al.	
2008/0281290	Al	11/2008	Yodfat et al.	
2008/0319414	Al	12/2008	Yodfat et al.	
2009/0069750	A1	3/2009	Schraga	
2009/0118667	A1	5/2009	Haueter et al.	
2009/0177146	A1	7/2009	Nesbitt et al.	
2010/0004598	Al	1/2010	Eberhart et al.	
2010/0001336	Al	1/2010	Campbell et al.	
2010/001/141				
ZOTU/UU04730	Al	3/2010	Buck et al.	
2010/000/1250				

US 11,806,502 B2 Page 3

(56)	Referen	ices Cited		2017/0368258 2018/0000999			Fleischer Dolmatch et al.
U.S.	PATENT	DOCUMENTS		2018/0025120	A1	1/2018	Cronrath et al.
				2018/0060520 2018/0207356			Degen et al. Joseph et al.
2010/0064257 A1 2010/0077198 A1		Buck et al. Buck et al.		2018/0256813			Chow et al.
2010/007/198 A1 2010/0082167 A1		Haueter et al.		2018/0280608			Gillett et al.
2010/0106082 A1*		Zhou A61M 5/1423	2	2018/0318550			Chiu et al.
		604/6	7	2018/0333532		1/2018	
2010/0174239 A1*	7/2010	Yodfat B32B 1/0		2019/0001055 2019/0083712		1/2019 3/2019	
2010/0211011 41	0/2010	604/15	3	2019/0091404			Nazzaro et al.
2010/0211011 A1 2010/0228226 A1	8/2010 9/2010	Nielsen		2019/0133505		5/2019	
2011/0054439 A1		Yodfat et al.		2019/0151568			Cardinali et al.
2011/0137297 A1		Kiani et al.		2019/0160225 2019/0175818			Verlaak et al. Meenken
2011/0152769 A1 2011/0152770 A1		Ramey et al. DiPerna et al.		2019/0184072			Madden et al.
2011/0132770 A1 2011/0218495 A1		Remde		2019/0192768			Gupta et al.
2011/0247397 A1		Friedli et al.		2019/0255251			Dilanni et al. Cook et al.
2011/0266999 A1		Yodfat et al.		2019/0351134 2020/0016335			DiPerna et al.
2012/0051946 A1 2012/0059348 A1		Lee et al. Haueter et al.		2020/0023122			McCullough et al.
2012/0039348 A1*		Smith H02J 7/002	9	2020/0037891			Kiani et al.
		604/40		2020/0069875 2020/0101219			Nazzaro et al. Wang et al.
2012/0093311 A1		Nierzwick et al.		2020/0101213			Kruse et al.
2012/0093315 A1 2012/0095393 A1		Nierzwick et al. Reinke et al.		2020/0360235			Møller
2012/0093393 A1 2012/0150144 A1		Campbell et al.		2020/0373009			Shapley et al.
2012/0157655 A1	6/2012	Yoneda et al.		2021/0038813 2021/0093779			O'Connor et al. Trachtenberg
2012/0209187 A1		Kamen et al.		2021/0162119			Barraud et al.
2012/0220939 A1 2012/0226124 A1		Yodfat et al. Blomquist		2021/0213198			Gyory
2012/0232485 A1		Blomquist		2021/0272687 2021/0280309			Klopfenstein et al. Klopfenstein et al.
2012/0232486 A1	9/2012	Blomquist		2021/0280309			Oberg et al.
2012/0232521 A1 2012/0239362 A1		Blomquist Blomquist					
2012/0259302 A1 2012/0259185 A1		Yodfat et al.		FO	REIGN	PATE	NT DOCUMENTS
2012/0302991 A1		Blomquist et al.		NE 100	01011100		4/2015
2013/0041342 A1 2013/0060105 A1		Bernini et al. Shah et al.		DE 1020 EP	01311180 072135		4/2015 7/1996
2013/0000103 A1 2013/0079709 A1		Eberhart et al.		EP	072135		7/1996
2013/0245555 A1		Dirac et al.		EP	141081		4/2004
2013/0267811 A1		Pryor et al.		EP EP	141081 171687		4/2004 11/2006
2013/0338594 A1 2014/0128839 A1		Da Ros et al. DiIanni et al.		EP	171687		11/2006
2014/0148762 A1		Haueter et al.		EΡ	1 944 15	50	7/2008
2014/0188516 A1		Kamen et al.		EP EP	243641		4/2012
2014/0249500 A1 2014/0276419 A1	9/2014	Estes Rosinko et al.		EP	269817 269817		2/2014 2/2014
2014/0276420 A1		Rosinko		EΡ	285212		3/2015
2014/0276574 A1	9/2014			B Vo	2 065 78		7/1981
2014/0288399 A1 2014/0378898 A1		Regittnig Rosinko		WO 19 WO	80/00193 022007		9/1980 3/2002
2015/0073337 A1		Saint et al.			O-022007		3/2002
2015/0182689 A1*	7/2015	Dhami A61M 5/1424			05/01653		2/2005
2015/0182695 A1	7/2015	604/15 Rosinko			00815537 00815537		12/2008 12/2008
2015/0182697 A1		Panzer			01619658		12/2016
2015/0222517 A1	8/2015	McLaughlin et al.			01708562		5/2017
2015/0265768 A1		Vazquez et al.			01708562 01720581		5/2017 11/2017
2016/0008539 A1 2016/0030669 A1		Miyazaki Harris et al.			01720581		11/2017
2016/0067403 A1		Moberg et al.			01911083		6/2019
2016/0106910 A1	4/2016	Yap et al.			01911083 02210707		6/2019 5/2022
2016/0228641 A1 2016/0243302 A1	8/2016 8/2016	Gescheit et al.	v	WO-20	02210707	o Ai	3/2022
2016/0254952 A1		Harvey et al.			OTH	D DIE	BLICATIONS
2016/0296715 A1	10/2016	Clemenz et al.			OTHE	SK PU.	BLICATIONS
2016/0303333 A1		Momose	I	nternational Se	arch Rer	ort and	Written Opinion of the ISA for
2016/0339172 A1 2017/0014572 A1		Michaud et al. Newberry et al.					3, 2017, 12 pages.
2017/0027523 A1	2/2017	Venkatraman et al.					ual, Accu-Check Solo micropump
2017/0056582 A1		Niklaus Bozargan et al		ystem, Roche I			
2017/0072140 A1 2017/0112534 A1		Bazargan et al. Schoonmaker et al.					nealthcare system using cloud of
2017/0188911 A1	7/2017	Halac et al.		-	Compu	ting, v	ol. 20, No. 3, May 5, 2017,pp.
2017/0238805 A1		Addison et al.		211-2229. Somichev et al	"Surve	v and G	Systematization of Secure Device
2017/0259015 A1 2017/0274146 A1		Caspers Newberry et al.				-	versity Library, Sep. 8, 2017.
		·	-	٠,	ـــــــ ري		5 5, -E

(56)**References Cited**

OTHER PUBLICATIONS

International Search Report for PCT/EP2018/084069, dated Apr. 8, 2019, 7 pages.

International Search Report for PCT/EP2019/068053, dated Sep. 19, 2019, 4 pages.

International Search Report for PCT/EP2019/068054, dated Sep. 19, 2019, 4 pages.

Medtronic MiniMed (tm) 770G, System User Guide, https://www. medtronicdiabetes.com/sites/default/files/library/download-library/ user-guides/MiniMed_770G_System_User_Guide.pdf (2020).

Omnipod-Insulin Management System, UST400 User Guide, https:// www.omnipo.com/sites/default/files/2021-04/Omnipod-System_ User-Guide_English (Apr. 2021).

Osram-Light is Wearable, Health Monitoring and Fitness Tracking, Osram Opto Semiconductors, Flyer posted online Jan. 22, 2015, file:///C:/Users/jponton/Desktop/Osram_676865_Flyer_Health_ Monitoring_and_Fitness_Tracking_2016_(GB).pdf (Year: 2015). Park, "Security Mechanism Based on Hospital Authentication Server for Secure Application of Implantable Medical Devices", Biomed Research International, vol. 2014, Jul. 24, 2014, pp. 1-12.

t:slim Insulin Pump, User Guide, Tandem Diabetes Care, https:// www.tandemdiabetes.com/docs/default-source/product-documents/ tslim-insulin-pump (2017).

Written Opinion of the ISA for PCT/EP2018/084069, dated Apr. 8, 2019, 9 pages.

Written Opinion of the ISA for PCT/EP2019/068053, dated Sep. 19, 2019,7 pages.

Written Opinion of the ISA for PCT/EP2019/068054, dated Sep. 19,

2019, 9 pages. Wu et al., "A Secure Proxy-based Access Control Scheme for Implantable Medical Devices", arxiv.org, Cornell University Library,


Camara et al., "Security Mechanism Based on Hospital Authentication Server for Secure Application of Implantable Medical Devices", Journal of Biomedical Informatics, vol. 55, Jun. 1, 2015, pp.


International Search Report & Written Opinion dated Feb. 23, 2022 in Int'l PCT Patent Appl. Serial No. PCT/IB2021/060766.


Invitation to Pay Additional Fees and Communication Relating To The Results of the Partial International Search dated Aug. 10, 2022 in Int'l PCT Patent Appl. Serial No. PCT/IB2022/054863.


International Search Report & Written Opinion dated Oct. 4, 2022 in Int'l PCT Patent Appl. Serial No. PCT/IB2022/054863.


^{*} cited by examiner












































MICROPUMP

This application is the U.S. national phase of International Application No. PCT/IB2016/056870 filed Nov. 15, 2016, which designated the U.S. and claims priority to EP Patent 5 Application No. 15195733.9 filed Nov. 20, 2015, the entire contents of each of which are hereby incorporated by reference.

The present invention relates to a pump system for pumping fluids, in particular a microfluidic pump system. 10

Microfluidic pump systems may be used in a variety of applications, for instance in medical applications or in fluid sampling applications. Microfluidic pumps typically have fluid flow rates in the range of 10×10^{-9} liter per minute to 10×10^{-3} liters per minute. In medical applications, micro- 15 fluidic pumps may be used for administration of medicaments in liquid form to a patient. Microfluidic pumps may also be used in non-medical applications such as flow cytometry or other sampling or measurement applications. In many microfluidic applications, in particular medical 20 applications, it is important to ensure sterility of the pumped liquid. In many applications, there is also an advantage in having a disposable pump system that is thrown away after a predefined action or state depending on the application, for instance: after a single administration, after a supply of 25 medicament in a reservoir of the disposable part is empty, or after a specified time of administration (e.g. a few days).

One of the applications for a microfluidic pump system may for instance be for an infusion set for administration of a liquid medicament, for instance insulin. The infusion set 30 may be provided in the form of a patch pump that is worn by the patient, the patch pump having disposable components.

There is an advantage in providing low cost disposable parts that meet high safety and sterility standards required. 35

It is further advantageous in micropumps to have a particularly accurate pumping volume for very small volumes in order of a few micro liters.

In conventional pump systems, there may be piston type of pumps in which a plunger is advanced in cylindrical 40 reservoir. Other known pump systems comprise a rotating and axially movable rotor, or membrane type pumps. In order to ensure a high degree of accuracy in the pumped volume, especially for small quantities to be pumped, actuation means need to be made with a very high precision and 45 are costly in conventional microfluidic pump systems. Moreover, in conventional pump systems having movable parts intervening in the pump chamber and thus requiring movable sealing means, safety and sterility are difficult to ensure reliably. Peristaltic type of pumps or shuttle pumps 50 that have actuators pressing on an elastic tube, provide a high degree of sterility because the pump liquid is completely separated from the external environment, however the elastic tube is generally made of elastomer which have a restricted compatibility with drugs and are porous to gases. 55 The elastomeric tubes require special coatings and are often costly to manufacture. For demanding applications the elastic properties of such tubes may vary over time and thus leading to a reduced accuracy.

GB2065789 discloses a shuttle type pump including 60 upstream and downstream flexible conduits and first and second movable members operable for constricting and opening the conduits. A disposable cassette is disposed between the upstream and downstream conduits and comprises a rigid enclosure defining a pumping cavity. The 65 enclosure is provided with a window and a flexible diaphragm closing the window and configured to cooperate

2

with an actuator which is operated in sequence with respect to the first and second members in order to pump fluids from the upstream to the downstream conduits.

WO80/01934 discloses also a shuttle pump including a pump housing configured to receive and hold a disposable pump chamber. The disposable pump chamber comprises upstream and downstream conduits and contains two flexible rolling diaphragm chambers therebewteen which act as first and second pumping chambers which cooperate with first and second pistons respectively such as to pump fluids from the upstream to the downstream conduits.

The configuration of above pumps makes it difficult to provide a sterile pump which therefore may have restricted compatibility with the use of drugs. Moreover, to reach a good accuracy, these pumps must be calibrated each time a new cassette/pump chamber is loaded.

It is an object of this invention to provide a micropump for a microfluidic pump system that is very accurate, especially for very small pump volumes, and that is very reliable and sterile

It is advantageous to provide a micropump for a microfluidic pump system that is that is easy to calibrate.

It is advantageous to provide a micropump for a microfluidic pump system that is cost effective to manufacture and thus convenient to integrate in a disposable device.

It is advantageous to provide a micropump for a microfluidic pump system that is safe and reliable for use in medical applications for administration of liquid drugs.

It is advantageous to provide a micropump for a microfluidic pump system that is very versatile, in particular that can be implemented in a wide range of applications.

It is advantageous to provide a micropump for a microfluidic pump system that can be easily calibrated.

It is advantageous to provide a micropump for a microfluidic pump system that may be used for pumping fluids without any risk of contamination or damage to the fluid due to the pumping system, for instance by avoiding moving parts or seals that separate the volume of liquid to be pumped and the external environment.

Objects of the invention have been achieved by providing a micropump according to claim 1, and a method of producing a micropump according to claim 15.

Disclosed herein is a micropump including a support structure, a pump tube, and an actuation system comprising one or more pump chamber actuators. The pump tube comprises a pump chamber portion defining therein a pump chamber, an inlet portion for inflow of fluid into the pump chamber, and an outlet portion for outflow of fluid from the pump chamber, the inlet, outlet and pump chamber portions forming part of a continuous section of tube made of a supple material. The one or more pump chamber actuators are configured to bias against the pump chamber portion to expel liquid contained in the pump chamber via the outlet portion, respectively to bias away from the pump chamber portion to allow liquid to enter the pump chamber via the inlet portion. The pump chamber portion has a crosssectional area Ap in an expanded state that is larger than a cross-sectional area Ai of the pump tube at the inlet and outlet portions.

In an advantageous embodiment, the one or more pump chamber actuators may comprise one or more tube coupling interface elements fixed to one side of the pump chamber portion.

In an advantageous embodiment, the one or more tube coupling interface elements may be bonded to a wall portion of the pump chamber portion.

In an advantageous embodiment, the actuation system further comprises an inlet valve, and an outlet valve in the form of pinch valves that bias against the pump tube on an inlet, respectively outlet side of the pump chamber portion.

The inlet pinch valve may be operated by means of an inlet valve actuator and the outlet valve may be operated by means of an outlet valve actuator.

In an advantageous embodiment, the pinch valves bias against an expanded section of the pump chamber portion.

In an advantageous embodiment, the pinch valve actuators may be bonded to the pump tube.

In an advantageous embodiment, the inlet and outlet valves comprise an elastic body configured to apply elastic pressure closing together opposing surfaces of the pump $_{15}$ chamber portion.

In an advantageous embodiment, the pump chamber actuator and/or the inlet valve actuator and/or the outlet valve actuator is/are passively driven in one direction by means of a spring element.

In an advantageous embodiment, the pump chamber actuator and/or the inlet valve actuator and/or the outlet valve actuator is/are actively driven in at least one direction by means of an electromagnetic actuator.

In advantageous embodiments, the ratio of the pump 25 chamber portion cross-sectional area over the inlet and outlet portions cross-sectional area Ap/Ai is in a range of 4 to 100.

In advantageous embodiments, the ratio of the pump chamber portion cross-sectional area over the inlet and 30 outlet portions cross-sectional area Ap/Ai may be more particularly in a range of 9 to 64.

In advantageous embodiments, the micropump is configured for pumping liquids in the range of 1 nl/min to 100 ml/min.

In advantageous embodiments, the micropump may be configured for pumping liquids more particularly in the range of 10 nl/min to 300 μ l/min.

In an advantageous embodiment, the pump chamber portion is a blow molded section of polymer tube.

In an advantageous embodiment, the polymer is a thermoplastic polymer, for instance selected from Perfluoro-alkoxy (PFA), Fluorinated ethylene propylene (FEP), or a fluoropolymer.

In an advantageous embodiment, opposed wall portions 45 of the pump chamber portion are fixed to elements that form parts of the actuation system and housing that move relatively with respect to each other, configured to pull apart or press together the wall portions.

In an advantageous embodiment, the actuators may comprise position sensors configured to determine the state of operation of the pump.

In an advantageous embodiment, the position sensors may comprise capacitive sensors that detect the position of the biasing organ.

In a variant, the position sensors may comprise magnetic sensors that detect the position of the biasing organ.

Also disclosed herein is a method of manufacturing a micropump including a support structure, a pump tube, and an actuation system, the pump tube comprising a pump 60 chamber portion defining therein a pump chamber, an inlet portion for inflow of fluid into the pump chamber, and an outlet portion for outflow of fluid from the pump chamber, wherein the inlet portion, outlet portion and pump chamber portion form part of a continuous section of tube made of a supple material, the method characterized by forming the pump chamber portion by blow molding.

4

In an advantageous embodiment, the method comprises flattening the pump chamber portion after the blowmolding step.

In an advantageous embodiment, the method comprises bonding opposed wall portions of the pump chamber portion to respective elements of the actuation system and housing that move relatively with respect to each other configured to pull apart or press together the wall portions.

Also disclosed herein is a microfluidic pump system for administering a liquid medication, comprising a reusable part including a drive unit and an electronic control system and a disposable part including a liquid supply system, a delivery system for administering the liquid medication to a patient, and a micropump as described above.

In an advantageous embodiment, the microfluidic pump system is configured in the form a patch pump comprising an adhesive surface for adhering to the skin of a patient for delivery of a liquid medication.

Further objects and advantageous features of the inven-20 tion will be apparent from the claims, from the detailed description, and annexed drawings, in which:

FIG. 1a is a schematic simplified perspective view of a medical patch pump system according to an embodiment of the invention:

FIG. 1b is a schematic simplified perspective of the patch pump system of FIG. 1a showing separation of reusable and disposable parts;

FIG. 1c is a schematic simplified perspective cross-sectional view of the pump system of FIG. 1a;

FIG. 2a is a schematic simplified perspective view of a microfluidic pump system according to an embodiment of this invention;

FIG. 2b is a perspective view of a microfluidic pump system according to an embodiment of this invention with a portion of housing removed;

FIG. 2c is a view similar to FIG. 2b but of another embodiment according to the invention;

FIG. 2d is a perspective cross-sectional view of a microfluidic pump system according to an embodiment of the invention;

FIG. 3a is a perspective view of a pump chamber portion of a microfluidic pump system according to an embodiment of the invention, the pump chamber portion being in an empty state;

FIG. 3b is a view similar to FIG. 3a with the pump chamber in a partially full state;

FIG. 4a is a top view of a microfluidic pump system with a portion of housing removed according to an embodiment of this invention;

FIG. 4b is a cross-sectional view through lines G-G of FIG. 4a;

FIG. 4c is a cross-sectional view through line A-A of FIG. 4a:

FIG. 4*d* is a cross-sectional view through line B-B of FIG. 4*a*;

FIGS. 5a, 5c, 5e, 5g are similar to figure to FIG. 4c but showing the microfluidic pump system in different pumping stages whereby FIG. 4c shows the pump chamber in an empty state, FIG. 5a shows the inlet valve open and the pump chamber being filled, FIG. 5c shows the pump chamber full and the valves closed, FIG. 5c shows the outlet valve open and the pump chamber being emptied; and FIG. 5c shows the outlet valve about to be closed and the pump chamber just emptied;

FIGS. 5b, 5d, 5f, 5h are similar to FIG. 4d showing the position of actuators during the pumping steps illustrated in FIGS. 5a, 5c, 5e, 5j respectively;

FIG. 6 is schematic cross-sectional view of a microfluidic pump system according to another embodiment of the invention:

FIG. 7 is a perspective cross-sectional view with portions of housing removed of a microfluidic pump system according to an embodiment of this invention illustrating position sensors of actuating elements;

FIG. **8** is a graph schematically illustrating a pumping sequence and opening and closing of valves of a microfluidic pump system according to embodiments of the invention:

FIGS. 9a to 9d are simplified schematic perspective views illustrating steps in manufacturing a pump chamber portion of a microfluidic pump system according to an embodiment of the invention.

Referring to the figures, starting with FIGS. 1a to 1c, a microfluidic pump system 2 according to an embodiment of this invention is in the form of a pump system for administering medical liquids, comprising a reusable part 4 and a disposable part 6. The reusable part 4 includes a drive unit 20 5 and an electronic control system 7. The disposable part 6 includes a liquid supply system, for instance incorporating a liquid reservoir containing the medication to be administered, a delivery system 8 for administering the liquid to a patient, for instance incorporating a needle for subcutaneous 25 administration of liquid or for feeding into a catheter, and a micropump 10 for pumping the liquid from the liquid reservoir to the delivery system 8.

The microfluidic pump system may for instance be in the form of a patch pump comprising an adhesive surface **3** for 30 adhering to the skin of a patient for delivery of a medication over a few days to a few weeks. Patch pump systems are per se well known, for instance for administration of insulin to patients suffering from diabetes. In such systems it is well known to have a reusable part comprising a drive and 35 electronics that may be reused multiple times with a plurality of disposable systems that are thrown away once removed from the patient or after the liquid in the reservoir is empty or nearly empty, or after a specified time.

A micropump 10 according to embodiments of this invention may advantageously be implemented in a disposable part of a patch pump configuration. A micropump 10 according to embodiments of the invention may however be implemented in many other systems requiring pumping of small quantities of liquids, particularly in the range of 10 45 nl/min (10×10⁻⁹ litres/minute) to 10 ml/min, more particularly in the range of 10 nl/min to 300 ul/min.

The micropump 10 according to embodiments of this invention comprises a housing or support structure 14, a pump tube 16, and an actuation system 18.

The pump tube 16 comprises a pump chamber portion 24 defining therein a pump chamber 26, an inlet 20 for inflow of fluid into the pump chamber, and an outlet 22 for outflow of fluid from the pump chamber. The inlet, outlet and pump chamber portion form part of a continuous section of tube 55 made of a supple material, for instance a polymeric material such as Perfluoroalkoxy (PFA), Fluorinated ethylene propylene (FEP), a thermoplastic fluoropolymer or various other thermoplastic materials, the choice of which may depend inter alia on the intended application and need for 60 compatibility with the liquid to be pumped.

In the figures, the inlet and outlet are shown with end faces however the inlet and outlet may continue with long sections of tube connected at their respective ends to a delivery system respectively a liquid supply reservoir. The 65 section of tube may be provided without interruptions such that the pump chamber portion 24 is connected to the liquid

6

supply and delivery system by respective connectors at the liquid supply system and delivery system respectively. This ensures, similar to peristaltic type of pump systems, a continuous flow of liquid within the pump system separated from the external environment by a continuous wall without the need for sealed moving parts separating the liquid to be pumped from the external environment. This ensures a high degree of sterility in the separation of the liquid to be pumped from the external environment.

Referring to FIGS. 9a to 9d, the pump chamber portion 24 may be advantageously manufactured by a blow molding process. As illustrated in FIG. 9a, a section of polymer tube 24' is placed within a die 46 comprising a cavity 48 configured to form the pump chamber portion. As is per se known in blow molding processes, the section of polymer 24' is heated and gas pressure is applied within the tube so that it expands outwardly until the tube contacts and conforms to the chamber 48 in the die. The die may then be opened and the section of tube removed. In a subsequent step, the expanded blow molded section 24 may then be flattened to form the pump chamber portion 24 for assembly within the housing of the micropump.

The volume of the pump chamber 28 formed within the pump chamber portion 24 may be varied for the pumping operation by pulling apart the opposed flattened wall portions 24a, 24b of the pump chamber portion 24 to increase the volume therein, or by pressing together the opposite wall portions 24a, 24b to expel fluid out of the pump chamber. The blow molded pump chamber portion 24 is particularly cost effective to manufacture while at the same time ensuring a very high level of reliability and safety from contamination. Moreover, contrary to peristaltic or shuttle type of pumps, the pumping action does not rely on the inherent elasticity of the tube and is not limited to the initial diameter of the tube.

In the present invention, the tube section as shown by the illustrated inlets and outlets 20, 22, can have a very small diameter D, relative to the pump chamber portion diameter D_n . The ratio of diameters D_n/D_i may advantageously be in a range of 2 to 10, preferably in range of 3 to 8. The relatively small tube reduces the dead volume of liquid between the liquid supply and micropump, respectively from the micropump to the delivery system, while at the same time allowing to pump a volume of liquid defined by the expanded pump chamber portion 24 that has a diameter D_n that may be 2 to 8 times or more the diameter D_i of the inlet and outlet portions of the tube. The actual amount of liquid to be pumped may be controlled by the degree of separation of the opposite wall portions 24a, 24b thus defining the volume of the pump chamber therebetween as well as the number of inflow and outflow (pumping) cycles. Within the scope of the invention, the tube original shape may not necessarily be a circular or essentially circular shape in cross-section, an may have a variety of other cross-sectional profiles such as square, polygonal, elliptical and various irregular profiles. More generally, in advantageous embodiments, the ratio of the pump chamber portion cross-sectional area (in its fully expanded operational state) over the inlet and outlet portions cross-sectional area Ap/Ai is in a range of 4 to 100, more preferably in a range of 9 to

In order to effect the pumping operation, the opposed wall portion **24***a*, **24***b* of the pump chamber portion **24** are fixed to elements that form parts of the actuation system and housing that move relatively with respect to each other to pull apart or press together the wall portions **24***a*, **24***b*.

In the embodiment illustrated in FIG. 2d, a surface portion 25 of the upper wall portion 24a of the pump chamber portion 24 is fixed to a tube coupling interface element 34 of a pump chamber actuator 28 of the actuation system 18 whereas the opposite side 24b is fixed to a base wall 14b of 5 the housing 14. The fixing means between the housing and wall portion 24b, respectively between the interface element 34 and wall portion 24a of the pump chamber portion 24 may be by welding, brazing, adhesive bonding, cold or hot heading or various other per se known bonding techniques 10 between materials, in particular the polymeric material of the pump chamber portion and material of the housing interface element. The interface element and housing may also be made of a polymeric material, for instance injected plastic of similar or different polymer than that of the tube 15 section, although non-polymeric materials may also be used depending on the applications, provided that fixing technique is also adapted for the pair of materials used. Welding may for instance be performed by known techniques such as ultrasonic welding or laser welding.

In an advantageous embodiment, the pinch valve actuators 31, 33 may be bonded to the pump tube 16, in particular to ends of the pump chamber portion 24. The bonding of the pinch valve actuators to the pump tube may be by welding, brazing, adhesive bonding, cold or hot heading or various 25 other per se known bonding techniques between materials in a similar manner than the pump chamber actuator bonded to the pump chamber portion. This allows to use a non-elastic material for the pump tube 16 yet ensure that the pinch valve actively opens the tube sufficiently to ensure low fluidic 30 resistance when opened. The active drawing in of liquid into the pump chamber confers an important advantage, in particular in the case of an underpressure upstream (e.g. in the reservoir), or for pumping viscous fluids.

The actuation system 18 comprises one or more pump 35 chamber actuators 28 comprising one or more tube coupling interface elements 34 fixed to one side of the pump chamber portion 24, an inlet valve 30, and an outlet valve 32. In a preferred embodiment the inlet and outlet valves 30, 32 are in the form of pinch valves that bias against the pump tube 40 16 on the inlet and outlet side of the pump chamber portion 24. In an advantageous embodiment, the pinch valves bias against the expanded section of the pump chamber portion 24. In a variant however, the pinch valves may also pinch the tube sections outside of the expanded portion, on the tube 45 sections that are not expanded (i.e. not blow molded).

The inlet and outlet valves 30, 32 may advantageously comprise an elastic body, for instance made of an elastomer, configured to apply elastic pressure closing together the opposing surfaces of the pump chamber portion while 50 reducing local pressure to avoid damage to the pump tube 16 while ensuring a good pinch sealing of the valve.

The inlet pinch valve 30 is opened and closed by means of a pinch valve actuator 31. The outlet valve may be operated by means of an outlet valve actuator 33.

In a variant, the outlet valve actuator may be a passive actuator that is spring biased such that the outlet valve pinches the tube in a closed position during inflow of liquid in the pump chamber portion when the inlet valve is open. In the latter variant, the outlet valve biases open under 60 pressure of the liquid within the pump chamber when the inlet valve is closed and the pump chamber actuator is actuated to reduce the volume in the pump chamber portion.

In a variant, the inlet and outlet valves may be provided at the liquid supply system, respectively the needle actuation 65 system, rather than at the entry and exit of the micropump 10.

8

The pump chamber actuator 28 and pinch valve actuators 31, 33 may have similar configurations or may have different actuating mechanisms. In embodiments shown, the actuation system comprises a biasing mechanism 47 with springs 45 that bias both inlet and outlet pinch valves as well as the interface element 34 of the pump chamber actuator 28 to the closed position, as best illustrated in FIG. 2d or 6 where the pump chamber 26 is empty and the pinch valves closed. This configuration provides a fail safe mode whereby in case of loss of power or failure of the actuation system, fluid flow between liquid supply system and delivery system is closed. Such fail safe mode is useful in many applications, for instance in medical applications. Nevertheless, for certain applications that may require fluid connection between the fluid supply and the delivery system to remain open, the fail safe mode or power off mode may require the springs to bias the biasing mechanism 47 to an open position where both the inlet and outlet valves are open and the interface element 34 20 of the pump chamber actuator is in a raised position to allow liquid to flow through the pump chamber.

In embodiments with a spring biasing mechanism to the open or the closed position as needed by the system, the actuation system comprises a drive mechanism that acts in the direction opposite to the spring biasing force to effect the opposite action. In the embodiment illustrated in FIG. 2b, the interface element drive 36 of the pump chamber actuator 38 is provided in the form of a rotating camshaft 38. The rotating camshaft comprises a cam profile portion 38b that, in opposition to the spring force, raises and lowers the biasing organ 42 coupled to the interface element 34 to increase, respectively decrease the volume in the pump chamber as a function of the angle of rotation of the cam. The rotating cam may be turned by an electrical motor directly or through a reduction gearing system or by other known electrical actuation means for rotating a component. The camshaft 38 may be provided with cam profile portions 38a, 38c for actuating the pinch valves in a similar manner as a function of rotation of the camshaft. In this embodiment, the opening and closing of the pinch valves and raising and lowering of the pump chamber interface element are thus directly mechanically synchronised and the pumping volume per rotation of camshaft is a fixed amount.

While in the aforegoing it is mentioned that the inlet is connected to a liquid supply system and outlet connected to a delivery system, the micropump according to embodiments of the invention may be made as a bi-directional pump and therefore an inlet may act also as an outlet and an outlet as an inlet for flow of liquid in both directions depending on the order of opening and closing of the pinch valves and actuation of the pump chamber portion. Using a rotating cam this may be done for instance by simply reversing the direction of movement of the rotating cam. A reverse flow of liquid may for instance be implemented in certain applications to provide a drawback of liquid from the delivery system to the supply systems for mixing or other operations.

In the illustrated embodiments, the biasing mechanism 47 is in the form of a leaf spring plate with cantilever arms 43 that are pivotally connected to a base portion 41, the spring biasing force acting on the spring arms 43 being provided by coil springs 45. In other possible variants, various other spring mechanisms may be used that are per se well known to the skilled person. Also, the spring force may be provided by the cantilever arms 43 due to their inherent elasticity without the use of additional coil springs or other additional springs.

In the illustrated embodiments, the pinch valves and interface element of the pump chamber actuator are positioned on a portion of the arm that is intermediate the base 41 and free end 43 of the arms, the actuators being positioned proximate the free end 43 of the arms. The actuation 5 of the spring arms 42 may thus be effected with a larger displacement than the actual displacement of the pinch valve, respectively pump chamber actuators, thus increasing the control and accuracy of the variation of volume in the pump chamber 26.

In another embodiment, instead of a rotating cam, each of the biasing organs 42 of the pump chamber actuator 28 and the inlet and outlet valves 30, 32 may be effected by other individual actuation means such as linear actuators for instance in the form of solenoids as illustrated in the 15 embodiment of FIG. 6 or by piezo electric actuators.

In variants, the actuation means may be provided by other per se well known actuators such as pneumatic or hydraulic actuators, or other forms of electromagnetic actuators.

In a variant, instead of acting against spring means, the 20 actuators may also effect forward and reverse movements without spring means to effect the pump chamber volume variation and opening and closing of valves. The actuators may effect the forward and reverse movements actively, or in a variant, actively in one direction and passively in the 25 other by the force of the spring means. Spring means may also be integrated within the actuators to effect the passive movement in one direction.

In using individual actuators **40**, the displacement of each actuator may have a fixed displacement travel similar to the 30 cam operation of the biasing organ. In a variant, the pump chamber actuator **28** may have a variable travel that may be controlled in order to change, as needed, the pumping volume per cycle.

The actuators may further be provided with position 35 sensors 44 (see FIG. 7) for instance in the form of capacitive sensors that detect the height of the biasing organ 42, for instance the position of the free ends 43 of the biasing organ, for the pump chamber and for the pinch valves in order to determine the state of operation of the pumping. The position sensors may also be used to determine a malfunction in the pump, in particular malfunction of the pinch valves or the pump chamber actuator. The sensors may also be used to determine or to control the pumping operation in particular the pumping volume rate.

Referring to FIGS. 4c to 5h and FIG. 8, a pumping cycle according to embodiments of the invention is illustrated. As shown in FIG. 4c, the inlet pinch valve is opened by the inlet valve actuator 31 and then the pump chamber actuator 28 is raised to increase the volume in the pump chamber 26 as shown in FIGS. 5a and 5b. The inlet valve is then closed as shown in FIGS. 5c, 5d and then the outlet valve is opened as shown in FIGS. 5e and 5f and the pump chamber actuator 28 is depressed until the liquid is expelled as shown in FIGS. 5g and 5h. The outlet valve may then be closed and a pump 55 cycle repeated.

As mentioned previously, the outlet valve can be actively actuated by a motorized actuation element or may be passive in the sense of being a spring biased pinch valve that opens due to the pressure of the liquid in the pump chamber when 60 the pump chamber actuator is depressed.

The micropump can be in different manners to create a flow. For instance, in an embodiment, the fluid flow is a sequence of discrete amounts, by successively repeating complete pumping cycles, thus the flow is given by the 65 pumped volume per cycle and its frequency. A time delay can be introduced between pumping cycles. Another possi-

10

bility is to create a continuous flow by first filling the pumping chamber through the inlet and then expelling the fluid by the compression of the pumping chamber over a certain time (push). Alternatively the pumping chamber can be filled over a certain time to create a continuous flow (pull). These operations may be repeated and/or combined in any chosen sequence.

```
List of references used
```

```
Pump system 2 (e.g. patch pump)
       adhesive base 3
reusable part 4
       drive unit 5
       control system 7
disposable part 6
       delivery system 8 (e.g. needle system)
       liquid supply system 12
              e.g. liquid reservoir
       micropump 10
              housing/support 14
              pump tube 16
                     outlet 22
                     pump chamber portion 24
                            attachment surface portion 25
                            pump chamber 26
              actuation system 18
                     inlet valve 30
                            pinch valve
                                   elastic body
                     outlet valve 32
                            pinch valve
                                   elastic body
                     pump chamber actuator(s) 28
                            tube coupling interface, element 34
                            interface element drive 36
                                    1st embodiment
                                   rotating cam 38
                                   biasing mechanism 47
                                   (leaf spring plate & springs)
                                    spring biasing organ 42
                                           pivot arm -> leaf spring arm
                                                 base portion 41
                                                 free end 43
                                           compression spring 45
                                   2nd embodiment
                                   linear actuators 40
                                    spring biasing organ 42
                                    3rd embodiment
                                   linear actuators 40
                                    no spring for return
                                   (active two way displacement)
                            position sensor(s) 44
blow molding die 46
       chamber 48
```

The invention claimed is:

1. A micropump including a support structure, a pump tube, and an actuation system comprising one or more pump chamber actuators comprising a camshaft and first and second cantilever arms, the pump tube comprising a pump chamber portion defining therein a pump chamber, an inlet portion for inflow of liquid into the pump chamber, and an outlet portion for outflow of liquid from the pump chamber, an adhesive surface configured to adhere to skin of a patient, the outlet portion coupled to a needle for subcutaneous administration of liquid to the patient having the micropump adhered thereto via the adhesive surface, the inlet portion, the outlet portion, and the pump chamber portion monolithically forming part of a continuous section of tube made of a supple material, the pump chamber portion bonded to a wall within the support structure via welding, brazing, adhesive bonding, or cold or hot heading, the first cantilever arm configured to cause, responsive to a spring force pro-

vided by the first cantilever arm and rotation of the camshaft, the pump chamber portion to expel liquid contained in the pump chamber via the outlet portion to the needle for subcutaneous administration to the patient, the second cantilever arm configured to allow liquid to enter the pump 5 chamber via the inlet portion responsive to rotation of the camshaft, wherein the pump chamber portion has a cross-sectional area \mathbf{A}_p in an expanded state that is larger than a cross-sectional area \mathbf{A}_i of the pump tube at the inlet portion and the outlet portion, wherein an end of the inlet portion forms an inlet of the micropump and an end of the outlet portion forms an outlet of the micropump.

- 2. The micropump of claim 1, wherein the one or more pump chamber actuators comprise one or more tube coupling interface elements.
- 3. The micropump of claim 1, wherein the actuation system further comprises an inlet valve and an outlet valve in the form of pinch valves that bias against the pump tube on an inlet side and an outlet side of the pump chamber portion, respectively, the inlet pinch valve being operated by movement from an inlet valve actuator and the outlet pinch valve being operated by movement from an outlet valve actuator.
- **4**. The micropump of claim **3**, wherein the pinch valves bias against an expanded section of the pump chamber 25 portion.
- 5. The micropump of claim 3, wherein the inlet pinch valve and the outlet pinch valve each comprise an elastic body configured to apply elastic pressure closing together opposing surfaces of the pump chamber portion.
- 6. The micropump of claim 3, wherein the inlet and outlet valve actuators individually actuate the inlet and outlet pinch valves, respectively, responsive to corresponding movement at the inlet and outlet valve actuators.
- 7. The micropump of claim 3, wherein the one or more 35 pump chamber actuators and/or the inlet valve actuator and/or the outlet valve actuator is/are passively driven in one direction
- **8**. The micropump of claim **3**, wherein the one or more pump chamber actuators and/or the inlet valve actuator 40 and/or the outlet valve actuator is/are actively driven in at least one direction by an electromagnetic actuator.
- 9. The micropump of claim 8, wherein a ratio of the pump chamber portion cross-sectional area over the inlet and outlet portions cross-sectional area A_p/A_i is in a range of 4 45 to 100.
- 10. The micropump of claim 9, wherein the micropump is configured for pumping liquids in a range of 1 nl/min to 100 ml/min.
- 11. The micropump of claim 3, wherein the one or more 50 pump chamber actuators and/or the inlet valve actuator and/or the outlet valve actuator comprise position sensors configured to determine a state of operation of the micropump.
- 12. The micropump of claim 11, wherein the position 55 sensors comprise capacitive and/or magnetic sensors that detect a position of a biasing organ.
- 13. The micropump of claim 1, wherein the pump chamber portion of the pump tube is a blow molded section of polymer tube.
- 14. The micropump of claim 1, wherein opposed wall portions of the pump chamber portion are fixed to elements that form parts of the actuation system and the support structure that move relatively with respect to each other, to pull apart or press together the wall portions.
- 15. A microfluidic pump system for administering a liquid medication, the microfluidic pump system comprising a

12

reusable part including a drive unit and an electronic control system and a disposable part including a liquid supply system, a delivery system for subcutaneously administering the liquid medication to the patient, and the micropump of claim 1 for pumping the liquid from a liquid reservoir to the delivery system.

- **16**. The microfluidic pump system of claim **15**, configured in the form a patch pump for delivery of the liquid medication.
- 17. The micropump of claim 1, wherein the micropump is configured to pump insulin for subcutaneous administration to the patient.
- 18. The micropump of claim 1, wherein the pump chamber portion is bonded to the wall within the support structure via welding.
- 19. The micropump of claim 18, wherein the pump chamber portion is bonded to the wall within the support structure via laser welding.
- 20. The micropump of claim 1, wherein the first and second cantilever arms are configured to independently move, responsive to the spring force provided by the first cantilever arm and a spring force provide by the second cantilever arm respectively, relative to the pump tube.
- 21. The micropump of claim 20, wherein the one or more pump chamber actuators further comprise a third cantilever arm configured to move, response to a spring force provided by the third cantilever arm, relative to the pump tube.
- 22. The micropump of claim 20, wherein each of the first and second cantilever arms comprises an elongated, flat portion.
- 23. A micropump including a support structure, a monolithic blow-molded pump tube, and an actuation system comprising a camshaft, a first cantilever arm, and a second cantilever arm, an adhesive surface configured to adhere to skin of a patient, the monolithic blow-molded pump tube consisting of a continuous piece of tube made of a supple material and a pump chamber portion defining a pump chamber, an inlet portion, and an outlet portion coupled to a needle for subcutaneous administration of liquid to the patient having the micropump adhered thereto via the adhesive surface, the first cantilever arm configured to cause, responsive to a spring force provided by the first cantilever arm and rotation of the camshaft, the pump chamber portion to expel liquid contained in the pump chamber via the outlet portion to the needle for subcutaneous administration to the patient, the second cantilever arm configured to allow liquid to enter the pump chamber via the inlet portion responsive to rotation of the camshaft, wherein the pump chamber portion has a cross-sectional area A_p in an expanded state that is larger than a cross-sectional area A, of the pump tube at the inlet and outlet portions.
- 24. The micropump of claim 23, wherein the pump chamber portion is bonded to a wall within the support structure via welding, brazing, adhesive bonding, or cold or hot heading.
- **25**. The micropump of claim **24**, wherein the pump chamber portion is bonded to the wall within the support structure via laser welding.
 - 26. The micropump of claim 23, wherein each of the first and second cantilever arms comprises an elongated, flat portion, and
 - wherein the second cantilever arm allows liquid to enter the pump chamber responsive to a spring force provided by the second cantilever arm.

27. The micropump of claim 23, further comprising a third cantilever arm configured to move relative to the pump tube.

* * * * *