

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
6 July 2006 (06.07.2006)

PCT

(10) International Publication Number  
**WO 2006/070296 A1**

(51) International Patent Classification:  
A61C 17/20 (2006.01) A61C 17/34 (2006.01)

Maria; P.O. Box 3001, Briarcliff Manor, NY 10510-8001 (US).

(21) International Application Number:  
PCT/IB2005/051148

(74) Agent: GROSS, Russell; c/o Philips Electronics, P.O. Box 3001, Briarcliff Manor, NY 10510-8001 (US).

(22) International Filing Date: 7 April 2005 (07.04.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
11/022,910 27 December 2004 (27.12.2004) US

(71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(71) Applicant (for AE only): U.S. PHILIPS CORPORATION [US/US]; 1251 Avenue of the Americas, New York, NY 10020 (US).


(72) Inventors: GREZ, Joseph W.; P.O. Box 3001, Briarcliff Manor, NY 10510-8001 (US). BOERSMA, Joldert,

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: POWER TOOTHBRUSH USING ACOUSTIC WAVE ACTION FOR CLEANSING OF TEETH



(57) Abstract: The toothbrush includes a handle portion and a brushhead assembly which comprises a head portion and a stem portion. The head portion includes a bellows-like acoustic action member for creating acoustic wave action as it moves in and out in response to an acoustic driving force. A drive system is located in the handle and includes an audio speaker-type assembly to create acoustic waves which are transmitted through a transmission line to the acoustic action member. The acoustic action member is driven toward and away from the teeth when the toothbrush is operatively positioned within the mouth. The action of the acoustic member is directly or indirectly coupled to the fluid in the mouth, producing a foam which couples shear forces between the acoustic action member and the teeth/gums to produce a desired cleaning/therapeutic effect.

WO 2006/070296 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— *with international search report*

**Declarations under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

DescriptionPOWER TOOTHBRUSH USING ACOUSTIC WAVE ACTION  
FOR CLEANSING OF TEETH

5

Related Applications

This is a continuation-in-part of PCT application No. IB2004/0510, filed on June 24, 2004, which designated the United States of America.

10

Technical Field

This invention relates generally to power toothbrushes, and more specifically concerns power toothbrushes which use acoustic wave action to produce a  
15 cleansing effect for the teeth of the user.

Background of the Invention

In general, power toothbrushes for cleaning teeth, including plaque removal, are well known. Typically, such  
20 power toothbrushes rely on a set of bristles attached to a bristle mounting plate which is moved by a driver to scrub the surfaces of the teeth. There are various known bristle configurations which are designed to effectively scrub exposed surfaces on the teeth, as well as to reach to some extent  
25 between the teeth or just under the gum line. Such brushing devices which rely on the scrubbing action of bristles for cleaning typically require significant pressure exerted by the user against the teeth to accommodate the differences in the shapes of the various teeth and to effectively clean the  
30 teeth. However, such pressure exerted against the teeth by the bristles typically results in a significant abrasion effect, including damage to both the soft and hard tissues in the mouth. This is of course undesirable, but often unavoidable to obtain the desired cleansing.

35

There are also limitations on the size (length and diameter) of the bristles insofar as while a small size may be desirable to reach between the teeth and under the gum line, the bristles still must be stiff enough to effectively scrub

the teeth. Hence, with respect to a bristle-type toothbrush, effective cleaning is important but it is also desirable that as light a pressure as possible on the bristles be used, to reduce abrasion and tissue damage.

5           In addition, ultrasonic energy is used, either alone, or in addition to bristle action, to clean plaque from teeth. However, the level of ultrasonic energy used in the mouth is typically too low to be effective for plaque removal if reasonable safety is to be maintained.

10           Still other toothbrushes, particularly those using a resonant system, produce some degree of acoustic action by moving fluids in the mouth by the action of the moving bristles at the resonant frequency of the toothbrush. However, the resonant frequency of such a toothbrush is  
15 typically not the most effective frequency for all areas of the mouth. Further, the acoustic effect of such devices, produced by the bristle action, is typically not sufficient by itself to produce a clinically effective cleansing action. Such devices still rely to a significant extent on the  
20 scrubbing action of the bristles for cleaning.

          The fact that the bristles themselves create the limited acoustic effect described above is significant relative to the effectiveness of the acoustic action. Increasing the amount of acoustic energy generated, in order  
25 to make that portion of the cleansing action more effective, will result in increased bristle motion and tissue abrasion. Further, providing additional power to increase the acoustic effect will result in additional bulk and cost to the device.

          Hence, it is desirable to have a toothbrush which  
30 effectively cleans teeth, including the hard to reach areas, such as between the teeth and under the gum line, which relies primarily on acoustic action not produced by bristle movement.

#### Summary of the Invention

35           Accordingly, the present invention is a power toothbrush which includes a handle portion, a head portion, the head portion containing a member for creating acoustic action outwardly from the head portion, acting on fluid in a

user's mouth; and a drive system for moving the acoustic member relative to the teeth, such that when the head portion is operatively positioned in the mouth of a user, the acoustic member moves toward and away from the teeth of the user, wherein movement of the acoustic member causes an acoustic wave action on fluid contacting the teeth, producing a cleansing effect on the teeth.

#### Brief Description of the Drawings

Figure 1 is a cross-sectional diagram showing one embodiment of the acoustic toothbrush of the present invention.

Figure 2 shows a functional block diagram of the operation of the toothbrush of Figure 1.

Figure 3 is a cross-sectional view showing in more detail a portion of the toothbrush in Figure 1.

Figure 4 is a cross-sectional view showing another embodiment of the toothbrush of the present invention.

Figures 5A-5B show surface additions to the embodiment of Figure 1 or Figure 4 to accomplish direct engagement of the teeth.

Figures 6-8 show various views of another embodiment of the present invention.

Figure 9 is a cross-sectional view of a variation of the embodiment of Figures 6-8.

Figure 10 is a cross-section of a further embodiment of the present invention.

Figures 11-13 are cross-sectional views of variations of a still further embodiment of the present invention.

#### Best Mode for Carrying Out the Invention

In general, the present invention is an acoustic power toothbrush, that is, a power toothbrush which produces acoustic wave action in the sonic frequency range, typically less than 1 KHz, which when operatively positioned in the mouth, either directly or indirectly activates the fluid in the mouth to produce an acoustic cleaning action on the teeth

of the user. Typically, the acoustic action is effective on the exposed surfaces of the teeth, as well as between the teeth and below the gum line. The acoustic action is produced by a non-bristled acoustic cleansing member, such as a bellows  
5 diaphragm made from flexible material such as rubber, or an equivalent member, as opposed to bristles, although bristles can be used as a boundary, i.e. partially surrounding the diaphragm, to enhance the acoustic action of the toothbrush or to contain the acoustic action to a particular volume, i.e.  
10 region, of the mouth, covering selected teeth adjacent the acoustic member. The bristles could also be configured to serve as a distance element for proper standoff between the membrane and the teeth during operation of the device. A wall element could be used for this purpose as well. The bristles  
15 or wall element can also assist in focusing of fluid flow to the teeth.

As disclosed in more detail below, in one embodiment, an acoustic system driver can be positioned in a handle portion of the toothbrush, with the driving energy  
20 transmitted up to a head portion of the toothbrush, where it acts on the acoustic cleansing member, or the acoustic system driver and the acoustic cleansing member can be contained entirely in the head portion of the toothbrush.

Referring now specifically to Figure 1, a first  
25 embodiment of the acoustic toothbrush of the present invention is shown generally at 10. The toothbrush includes a handle 12, a stem portion 14 and a head portion 16. The combination of the stem 14 and the head portion 16 is also referred to as a brushhead assembly. In handle 12 is a conventional battery  
30 18, a charging coil 20 to periodically charge the battery 18, and an electronic control and drive circuit, including a control microprocessor, shown generally at 22. The handle also includes the acoustic system driver which is similar in structure and operation to a high powered audio speaker.  
35 Generally, the acoustic system driver is capable of supplying at least a few watts of power for the acoustic cleansing member in the head portion of the toothbrush.

The acoustic system driver includes a magnet 24 and a voice coil 26, such as might be part of a conventional audio speaker. The acoustic system driver is controlled by drive signals produced by electronic circuit 22. The acoustic system driver also includes a speaker diaphragm, in this embodiment a bellows 28, to produce the acoustic waves. Typically, the frequency of the acoustic waves from the bellows 28 will be in the range of 20 Hz to 300 Hz, with 250-260 Hz being generally preferred. Frequencies up to 1000 Hz are possible, however. The control circuit 22 has the capability of storing and providing different driving frequencies, so that different individual frequencies can be selected during operation of the toothbrush, as well as a combination of frequencies. In this way, the frequency of the acoustic wave action can be matched to particular areas of the mouth or different cleansing actions can be provided, as discussed in more detail below.

The acoustic waves produced off of bellows diaphragm 28 is directed to an acoustic transmission line 30 which extends through the stem portion 14 of the toothbrush. The transmission line 30 can be, for instance, a fluid-filled tube, an air-filled tube, or even a mechanical actuator arm which transmits the acoustic action/energy. The fluid in the transmission line for instance could be a natural oil, which provides little if any opportunity for bacterial growth, even in the event of a pinhole opening in the line. Water-based materials may also be used with additives to prevent bacterial growth. The transmission line 30 transmits the acoustic energy produced by the drive system to an acoustic action member in head portion 16 of the toothbrush, typically in the form of a flexible acoustic cleansing member 32, also referred to as an acoustic action member, which in the embodiment shown is a bellows. The acoustic action bellows is driven in and out by the acoustic drive energy from the fluid in the transmission line, producing acoustic waves off a front surface 33 thereof.

Figure 3 shows additional detail of the acoustic action bellows 32. It is made from a flexible material, such

as rubber, which is capable of moving toward and away from the teeth when the toothbrush is properly oriented in the mouth, in response to the acoustic drive energy from the drive system in the handle. Generally, acoustic bellows 32 includes a front flat portion 34 and a peripheral edge portion 36 which moves between a concave configuration, such as shown in Figure 3, and a straighter, extended configuration, during which time the front portion 34 moves toward the teeth. The bellows arrangement permits a lower peristaltic volume as well as a convenient means for moving the acoustic member close to the teeth. In operation, the front portion will move a maximum of 5 mm and a minimum of 0.5 mm in response to the drive system action to produce the acoustic cleaning action.

While the flexible bellows-type element 32 provides good results, a solid piston like member or a paddle could alternatively be used. Typically, the acoustic action member will move toward and away from, in some cases approximately at right angle to, the teeth, producing acoustic wave action necessary for effective cleansing of the teeth.

This physical action by the acoustic action member 32 (bellows) will be coupled to the fluid within the mouth either directly, meaning that the front portion 34 of the bellows contacts the fluid directly, or indirectly (through air or an impedance matching material), in which an acoustic wave is produced which in turn affects the fluids in the mouth to produce an acoustic effect.

The fluids in the mouth, under the influence of the acoustic action produced by the bellows 32, produces a desired cleansing action for the teeth which is clinically effective. The front portion of the acoustic member can be configured in various ways other than flat. The action on the fluid will typically create a significant amount of foam, with the foam, driven by the acoustic action, producing significant cleansing effects for the teeth.

This is accomplished by what is referred to herein as acoustic action, which generally refers to the transmission of wave action in a medium, such as foam, that flows with a speed within the sound range and has a particular density.



The medium molds to surfaces within the mouth and on the generating membrane, so that shear forces can be transmitted in the mouth from the membrane to the oral surfaces, with desired cleansing effects.

5           Foam is created from air and fluid in the mouth. The creation of foam is dependent to some extent on frequency, with lower frequencies producing larger bubbles and higher frequencies creating smaller bubbles. A frequency range of 100-700Hz will likely be effective for the acoustic frequency.

10       Plaque is removed from hard tooth surfaces by foam shear action. The moving foam, or liquid with a little foam, will force the biofilm away from the tooth surfaces.

          Interproximal cleaning occurs by oscillating foam bubbles producing a cleansing action, with pressure

15       oscillations creating expansion and contraction of foam bubbles in liquid. Cleaning has been shown to occur significantly at the liquid/bubble interface. Cleaning also occurs below the gum line, due to gingival pockets being vibrated open and closed to cause flow of oxygenated foam into

20       those areas to oxygenate and then kill anaerobic bacteria. Both high and low frequencies (the range of 100-700Hz) are effective to produce pocket movement (lower frequencies) and oxygenated foam (higher frequencies).

          The front portion 34 of the bellows could have

25       various configurations/arrangements, including smooth rubber, rubber fingers extending therefrom, or individual conventional or rubber bristles, as shown in Figures 5A and 5B. Typically, rubber fingers 41 will be approximately 5 mm long and 1.8 mm in diameter, while the conventional bristles 43 will be

30       approximately 10 mm long and 0.15 mm in diameter. The front portion 34 could also have various surface configurations, including focusing arrangements to provide different acoustic effects into the fluid.

          Figure 2 shows the functional operation of the

35       acoustic toothbrush of the present invention. In the electronic circuit 22 is a drive signal recorder (storage) 38. The drive signal recorder is capable of storing a plurality of acoustic drive signals or waveforms of different frequencies.

Alternatively, the waveforms could be generated by an analog device/circuit. In a typical case, five to ten preprogrammed waveforms may be available, with the capability of storing additional waveforms, such as may be provided by a dental professional. These driving waveforms can be a single frequency, for instance, which may be matched with particular tissues in various portions of the mouth, such as the gums or different sections of the teeth, or they can be a particular combination of frequencies to produce different specific desirable effects in the mouth, including those frequencies or combinations of frequencies which are effective for gum massage, or various kinds of cleansing action, such as subgingival cleaning, which, as explained above, could be effective through the use of a lower frequency (approximately 200Hz) to open up the pockets and a higher frequency (approximately 400Hz) to produce the cleansing foam action to kill the bacteria in the pockets.

Thus, one significant advantage to the system of the present invention is the variety of frequencies available to produce various cleansing/treatment/therapeutic action for the teeth and gums.

A conventional charge coil and charge controller 40 and 42, respectively, charge the conventional batteries 44 which power the toothbrush. Charge coil 40 is responsive to a conventional charging device 46 in which the toothbrush may be positioned when not in use. Additional program information, such as additional drive frequencies, or combinations thereof, can be provided, at block 48, through charge coil 40 to the drive signal recorder 38. A microprocessor 50, with a resonator 52, which can be of various materials such as ceramic, or a crystal or an LRC circuit, controls the application of the drive signals to the speaker elements, and is responsive to commands from the user for a particular program or selection of frequencies.

Microprocessor 50 controls a conventional audio amplifier 54, the output of which drives the audio driver (speaker portion) 58 of the system. Referring to Figure 1, the acoustic effect from the speaker 58 is then coupled via

the transmission line 30 to the acoustic action member 32 in the head portion of the toothbrush.

The acoustic action member 32, such as the bellows in Figure 1, can be used by itself or it can be surrounded or partially surrounded by a line of bristle tufts 56. The line of bristles 56 can be conventional nylon bristles, or they can be rubber bristles. While the line of bristles 56 is not necessary to the acoustic cleansing action they can enhance the overall effect, for instance, by forming at least a partial boundary for the acoustic fluid/foam produced by the bellows member. Hence, the bristles can act as a volume containment for the fluid action relative to particular teeth. Further, the bristles may provide position information back to the user.

In addition, the fluid action produced by the acoustic action member 32 can produce a movement of the bristles, or the acoustic action member can be arranged so that the movement thereof acts on the bristles directly, moving them to a certain extent, such as a range of movement of approximately 5 mm. The bristles will move in phase with the pressure waves created by the acoustic member, such that there is a bristle cleaning effect (scrubbing) in addition to the acoustic cleaning effect. In this way, a combined cleansing action is obtained. Further, the bristles may be mounted on the flexible portion of the bellows, such that the bristles are forced to move with the bellows, providing an increased bristle cleaning action as part of the total cleaning effect.

Referring to Figure 4, another embodiment of the present invention is shown in which the entire acoustic assembly is provided in a head portion of the toothbrush. In this arrangement, there is no fluid transmission line through the stem of the toothbrush. The audio speaker assembly is shown generally at 60, which in the above embodiment is in the handle of the toothbrush. The speaker assembly 60 includes a front diaphragm or membrane 66 which moves (0.5 mm-5 mm) in response to the speaker being driven by an energizing or drive signal from a driver circuit (not shown). The action of

membrane 66 produces the desired acoustic wave action which is coupled to the fluid in the mouth, producing the foam which in turn couples shear force from the membrane 66 to the teeth or other oral cavity member, such as the gums. This embodiment  
5 may be advantageous in certain situations, but it has the disadvantages of a larger head size and generally less power. It should be understood that bristles 68 could also be used with this embodiment, surrounding the moving membrane, with similar effect and purpose to that shown and described above  
10 in the embodiment of Figure 1.

Figures 6-8 show another embodiment of the present invention. In this embodiment, a central flexible member, such as a membrane, 80 is substantially surrounded by a set of conventional bristle tufts 82. The bristle tufts are  
15 positioned, generally by stapling, in a plastic bristle holder member 84. The bristle tufts are scalloped at the upper edge 83 thereof, as shown in Figure 6, to fit closely around adjacent teeth and slightly into the interproximal area between the teeth.

20 .Positioned in the center area 87 of the brush is a flexible member or membrane 80, generally in the shape of an "M". Flexible member 80 includes two substantially vertical outside wall portions 90 and 92 and two slightly curved convex inner wall portions 94 and 96. Member 80 and bristle holder  
25 member 84 are supported by an overmold member 98 into which they are snapped or otherwise mounted during manufacture. Overmold member 98 forms a base for the brush and includes an upstanding central rib 100 which extends down the center of the brush for a substantial portion of its length. The two  
30 inner portions 94 and 96 are connected at their lower ends to rib portion 100.

Surrounding rib 100 over a substantial portion of its length and to the outside wall portions 90 and 92 of the member 80 is an additional bristle holder member 85. The  
35 outside wall portions 90 and 92 are relatively thick, approximately 60/1000s inches, while the inner portions are approximately 20/1000s thick. Member 80 is driven so that the outer wall portions 90 and 92 thereof move outwardly a

selected distance while the inner wall portions 94 and 96 move inwardly toward each other and somewhat in the direction of the teeth, as shown by the dotted lines in Figure 7. The outside wall portions 90 and 92 are in contact with the  
5 bristle holder member 84, which substantially surrounds flexible member (membrane) 80, providing a back and forth motion toward and away from the member 80. The movement of the inner wall portions 94 and 96 produce a fluid jet along a center line of the toothbrush outward from the toothbrush in  
10 the direction of the teeth.

The fluid is squeezed outwardly toward the teeth in a repetitive manner by action of the membrane to produce a stream of fluid droplets toward the gum line and the interdental spaces.

15 The back and forth action of the bristles 82 produces a cleansing action on the face of the teeth, in particular the accessible areas of the teeth. The action of the flexible member with the fluid jet produces cleansing in the inter-proximal areas and gum line pockets. The particular  
20 size of the flexible member can be optimized to produce effective acoustic cleaning with the fluid jet.

Figure 9 is a variation of the embodiment of Figures 6-8. It includes a brush holder member 106 in which are stapled conventional bristle tufts 108. The bristle holder  
25 member 106 is secured to a base overmold element 110. A flexible member/membrane 112, also generally in the shape of an "M", is mounted on the central portion of the brush holder member and extends lengthwise of the brush. Positioned longitudinally on the brush holder member at the center  
30 thereof is a support rib member 113. The outer portions 114 and 116 of the member are thicker than the internal portions 118 and 120, which extend from the top of the outer portions to rib 112.

On the exterior surface of the two outer portions  
35 114 and 116 are projections 122 and 124 which extend outwardly therefrom. Projections 122 and 124 contact bristle tufts 108. In operation, the brush holder member does not move by virtue of the flexible member action; the bristle tufts 108 are,

however, moved by outward action of the projections 122, 124 when outer portions 114 and 116 of the flexible member 112 move. Fluid is directed toward the teeth by action of the inner portions 118 and 120 of the flexible member, similar to the action of the embodiment of Figures 6-8.

Figure 10 shows a further embodiment of the invention. This embodiment includes a flexible member 128 acting on a matrix 130, which in the embodiment shown is a sponge member. This embodiment is designed to clean complex teeth surfaces. In operation, pressure is applied to the member 128 by a conventional drive system (not shown), moving the member toward the teeth, compressing the sponge 130, with fluid exiting from the sponge and along the surfaces of the teeth and into the interproximal areas of the teeth to create a shear cleaning effect. The outer peripheral boundary 132 of the matrix sponge 130 is sealed to prevent fluid flow out of the matrix portion not in contact with the teeth.

The characteristics of the sponge restrict the flow of fluid and gas. It can thus transmit shear force to the complex surfaces of the teeth. Further, the direct contact of the matrix sponge member 130 with the surfaces of the teeth produces mechanical cleaning of the exposed surfaces of the teeth. Access to hard-to-reach areas with the fluid is achieved with the matrix. The sponge, because of its flexibility, may by application of pressure be brought into contact with some interdental space. The fluid shear cleaning, mechanical cleaning and transmission of force to the teeth surfaces produces a good cleaning of the teeth.

The material for the sponge is, for example, silicone, such as Silastic from Dow Corning. The porosity of the sponge material should be less than 80% open volume, but more than 50%. Below 50%, the sponge is too dense and unable to flex adequately to reach interdental areas. The openness of the cell structure should be greater than 50%, since below 50%, the fluid is not sufficiently impeded by the structure to produce efficient surface shear forces. The cell structure can be up to 100% closed.

Figure 11 shows another embodiment of the present invention involving a complex flexible member (membrane) structure 138. The membrane structure 138 is mounted on a toothbrush stem 140, which is a plastic or similar material. This arrangement of Figure 11 does not include any bristles. Flexible member 138 includes an outer sealing portion 142 which extends around the periphery of the brushhead and is positioned against adjacent teeth to provide a sealing function for the fluid. The sealing portion 142 is preferably substantially continuous but may have breaks or spaces therein. A center portion 144 of the membrane 138 is driven to move generally toward and away from the teeth. The resulting fluid flow produces fluid motion and resulting cleansing of the teeth. The sealing portion 142 encloses an area on the teeth being cleaned and produces effective fluid flow dynamics and resulting cleaning.

An alternative to the flexible member of Figure 11 is shown in Figure 12, involving a more complex flexible member/membrane 148, with an outer, substantially continuous sealing portion 150 and two spaced inner sealing ribs 152 and 154 which extend the width of the brushhead. Sealing ribs 152 and 154 are arranged and spaced to contact adjacent teeth. Movement of the flexible member 148, in response to a driving action, produces a complex fluid flow. Inner central section 156 moves toward the teeth, while outer central sections 160 and 162 move away from the teeth and vice versa. Fluid moves in shear across the face of the teeth as well as into the inter-proximal areas, as shown by the arrows in Figure 12. This arrangement provides mechanical cleaning of the teeth as well as shear cleaning.

This operation of this embodiment is enhanced by a higher viscosity fluid, for example one-third toothpaste, with the remaining being saliva or water.

Figure 13 shows a further variation of the embodiment of Figure 11, using tufts of bristles 166 mounted to the outer portion (edge) of flexible member 168. When the flexible member 168 flexes in operation to produce fluid flow in the direction of the teeth, bristle tufts 166 in the

flexible member (membrane) move outward producing a mechanical cleansing action on the teeth, in addition to the acoustic cleaning by action of the fluid caused by movement of the membrane.

5           The embodiments of Figures 11 or 12 can be combined with Figure 13 to produce bristle motion inward while the central section of the flexible member moves toward the teeth.

          In summary, the flexible member (membrane) assembly, specifically the flexible membrane portion of the assembly, will move at a frequency within the range of 30-700 Hz, with an amplitude of the 0.5 to 5 millimeters in one direction, for example, 5 millimeters from a rest position toward the teeth and then 5 millimeters back to the rest position. The flexible membrane can be driven with signal waveforms of various shapes, including sinusoidal and sawtooth, which in some cases may be preferred, but also including triangular, square wave, and other shapes. The system with its programmable capability can be used to match selected signal waveforms with selected areas of the mouth during a brushing event or events.

          As briefly discussed above, the membrane may be partially surrounded by a wall element which serves as a boundary for fluid action as it comes into contact with the teeth. A range of distance from the top of the membrane to the top of the surrounding (or partially surrounding) wall element can vary from 2 millimeters to 8 millimeters. When the top edge of the boundary wall is positioned against the teeth, the membrane is positioned a fixed distance away from the teeth, improving the consistency of cleaning, particularly in interproximal (interdental) areas.

          The shape of the membrane may also be significant. In many cases, a circular membrane is effective but other shapes are effective as well, including oval and rectangular, with the rectangular configuration being typically rounded at the corners. The length of such a membrane can vary from 10 to 25 millimeters. Typically, one membrane will be used, although in many situations, more than one membrane, i.e. one, two or three separate membranes, will be effective.



Still further, the driving signal may include one or multiple harmonics, including, for instance, three harmonics of the fundamental frequency.

The assembly can be configured such that the  
5 flexible membrane (member) can move toward or away from the teeth, even at right angles to the teeth as discussed above, or at other angles relative to the teeth, including approximately parallel to the teeth. The action, however, must be such as to maintain the fluid dynamic action to remove  
10 biofilm from the teeth.

All of the above assist to various degrees in the cleaning of the teeth, including the interproximal and/or sub-gingival areas. The action of the flexible member (membrane) interacts with the fluid in the mouth to produce a fluid  
15 dynamic action in the vicinity of the teeth which results in sufficient shear pressure to surpass the threshold value necessary to remove biofilm from the teeth, as well as interproximal and sub-gingival areas. The fluid used in the mouth can be either compressible or noncompressible.

Accordingly, a new power toothbrush has been described which uses acoustic action produced by an acoustic action member, such as a flexible membrane, for example, a bellows-like member, to produce acoustic wave action in fluids in the mouth to in turn result in cleansing of the teeth  
25 through shear-type action against biofilms on the teeth, as well as interdentally and subgingivally. The cleansing effect is clinically significant, i.e. the results are substantially equivalent to or better than conventional commercial electric scrubbing toothbrushes, including removal of a substantial  
30 amount of biofilm. It has the advantage of virtually no tissue abrasion; and because it acts with a fluid foam medium, it has the advantage of reaching hard-to-reach places between the teeth and under the gum line. It thus produces effective cleansing action independent of scrubbing, although bristles  
35 can also be used and moved by action of the acoustic action membrane to enhance the overall cleansing action.

Although a preferred embodiment of the invention has been disclosed for purposes of illustration, it should be

16

understood that various changes, modifications and substitutions may be incorporated into the embodiment without departing from the spirit of the invention which is defined by the claims which follow.

5                   What is claimed is:

Claims

1. A power toothbrush, comprising:  
a handle portion;  
a brushhead portion, the brushhead portion including a flexible acoustic member for creating an acoustic wave effect on fluid in a user's mouth and a set of bristles which at least partially surround the periphery of the acoustic member, wherein the acoustic member is in the shape of an "M" having two opposing inner walls and two opposing outer walls; and  
a drive system for moving the acoustic member, such that the inner walls of the acoustic member move inwardly toward each other and then back to a rest position, wherein such movement of the inner walls produces fluid movement to the teeth, producing a cleansing effect on the teeth.
2. The power toothbrush of claim 1, wherein the brushhead portion includes a base member into which the acoustic member is mounted, the base member including an upstanding central rib to which lower ends of the inner walls of the acoustic member are secured.
3. The power toothbrush of claim 1, wherein movement of the acoustic member results in back and forth movement of the bristles for cleaning of the surfaces of the teeth.
4. The power toothbrush of claim 1, including outwardly directed projections on the outer walls of the acoustic member, such that movement of the acoustic member results in the projections moving the bristles.
5. The power toothbrush of claim 1, including a sponge member mounted on the acoustic member, the sponge member having a porosity of 50%-80% open volume and having an openness greater than 50%, wherein in operation, the sponge member is brought into contact with the teeth for cleaning.

6. The power toothbrush of claim 1, wherein the acoustic member includes a central portion which moves toward and away from the teeth and a pair of opposing upstanding rib portions on either side of the central portion which contact the teeth, providing a sealing effect for the fluid.

7. The power toothbrush of claim 6, including two additional upstanding rib portions outboard of the pair of rib portions, and two additional central portions between each additional rib portion and the pair of rib portions, wherein the additional rib portions move in a direction opposing the movement of the central portion.

8. A power toothbrush, comprising:

a handle portion,

a head portion, the head portion containing a member for creating acoustic action away from the head portion, acting on fluid in the user's mouth; and

a drive system for moving the acoustic member relative to the teeth with a drive signal having a frequency in the range of 30-to 700 Hz, the movement of the acoustic member having an amplitude in the range of 0.5-5 millimeters from a rest position, wherein movement of the acoustic member produces a fluid dynamic action with the fluid in the mouth to produce a value of shear stress which is greater than the threshold to remove biofilm from the teeth, including interproximal areas of the teeth.

9. The toothbrush of claim 8, wherein the acoustic member is a flexible membrane.

10. The toothbrush of claim 9, including a boundary wall element substantially surrounding the acoustic member, wherein the top of the boundary wall is approximately at least 2 millimeters above the top of the acoustic member.

11. The toothbrush of claim 9, including more than one acoustic member.

19

12. The system of claim 9, wherein the acoustic member is driven by a waveform of selected configuration.

13. The toothbrush of claim 9, wherein the selected waveform configuration is sinusoidal.

14. The toothbrush of claim 12, wherein the selected waveform configuration is a sawtooth.

15. The toothbrush of claim 10, wherein the drive waveform includes at least one harmonic frequency.

16. The toothbrush of claim 8, including a programmable control system for operating the drive system with different waveforms, so that selected waveforms can be used on selected areas of the mouth.

1/6




FIG. 1

2/6




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B






FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

6/6




FIG. 12




FIG. 13

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB2005/051148

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61C17/20 A61C17/34

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 92/10146 A (GEMTECH, INC) 25 June 1992 (1992-06-25)	8,12-15
A	the whole document	1
X	US 5 378 153 A (GIULIANI ET AL) 3 January 1995 (1995-01-03)	8,12-15
A	the whole document	1
X	EP 0 893 106 A (LES PRODUITS ASSOCIES L.P.A. BROXO S.A) 27 January 1999 (1999-01-27)	8,12-15
A	the whole document	1



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

11 July 2005

Date of mailing of the international search report

25/07/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Salvatore, C

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB2005/051148

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9210146	A	25-06-1992	AT 164993 T	15-05-1998
			AU 660640 B2	06-07-1995
			AU 9158591 A	08-07-1992
			CA 2097505 A1	14-06-1992
			DE 69129273 D1	20-05-1998
			DE 69129273 T2	17-09-1998
			DK 565598 T3	04-01-1999
			EP 0565598 A1	20-10-1993
			ES 2114557 T3	01-06-1998
			JP 6504924 T	09-06-1994
			JP 3243528 B2	07-01-2002
			WO 9210146 A1	25-06-1992
			US 5476384 A	19-12-1995
			US 5309590 A	10-05-1994
US 5378153	A	03-01-1995	AT 192905 T	15-06-2000
			AU 3610493 A	03-09-1993
			CA 2129757 A1	08-08-1993
			DE 69328670 D1	21-06-2000
			DE 69328670 T2	23-11-2000
			DK 625017 T3	11-09-2000
			EP 0625017 A1	23-11-1994
			ES 2145771 T3	16-07-2000
			GR 3033572 T3	29-09-2000
			JP 3459064 B2	20-10-2003
			JP 7505069 T	08-06-1995
			PT 625017 T	31-08-2000
			WO 9315628 A1	19-08-1993
EP 0893106	A	27-01-1999	US 5934908 A	10-08-1999
			EP 0893106 A2	27-01-1999