



US 20130031004A1


(19) **United States**(12) **Patent Application Publication**
DORSEY et al.(10) **Pub. No.: US 2013/0031004 A1**(43) **Pub. Date: Jan. 31, 2013**(54) **PAYMENT METHODS WITH A PAYMENT SERVICE AND TABS SELECTED BY A FIRST PARTY AND OPENED BY A SECOND PARTY AT ANY GEOGRAPHIC LOCATION OF THE FIRST PARTYS MOBILE DEVICE**(76) Inventors: **Jack DORSEY**, San Francisco, CA (US); **William HENDERSON**, San Francisco, CA (US); **Brian GRASSADONIA**, San Francisco, CA (US); **Jim McKELVEY**, Miami, FL (US)(21) Appl. No.: **13/605,489**(22) Filed: **Sep. 6, 2012****Related U.S. Application Data**

(63) Continuation of application No. 13/088,038, filed on Apr. 15, 2011, which is a continuation-in-part of application No. 12/903,753, filed on Oct. 13, 2010, which is a continuation-in-part of application No. 12/903,823, filed on Oct. 13, 2010, which is a continuation-in-part of application No. 12/985,982, filed on Jan. 6, 2011, which is a continuation-in-part of application No. 13/005,822, filed on Jan. 13, 2011, which is a continuation-in-part of application No. 13/010,976, filed on Jan. 21, 2011, which is a continuation-in-part of application No. 13/012,495, filed on Jan. 24, 2011, which is a continuation-in-part of application No. 13/042,203, filed on Mar. 7, 2011, now Pat. No. 8,247,176, which is

a continuation-in-part of application No. 13/043,258, filed on Mar. 8, 2011, which is a continuation-in-part of application No. 13/043,263, filed on Mar. 8, 2011, which is a continuation-in-part of application No. 13/043,268, filed on Mar. 8, 2011, now Pat. No. 8,302,860, which is a continuation-in-part of application No. 13/043,270, filed on Mar. 8, 2011, now Pat. No. 8,235,287.

Publication Classification(51) **Int. Cl.**
G06Q 20/08 (2012.01)(52) **U.S. Cl.** **705/44**(57) **ABSTRACT**

A method of paying a second party is provided. A first party accesses the names of one or more qualified second parties. The second parties (i) have an association with the payment service, and (ii) that if they do not have an established association with the payment service have established one prior to payment. The first party has an association with the payment service. A tab is opened by the first party that can be selected by the second party at any geographic location of a first party's mobile device. The second party is only able to charge a first party's financial account when the first party's mobile device is within a defined geographic area. The tab is a relationship between the first party, the payment service and the second party. The second party can engage in a financial transaction when the first party is within the defined geographic area.






FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B



FIG. 5




FIG. 6A




FIG. 6B





FIG. 6C

SignalScope Source: Headset Mic


Ch1: Time: 24.40 ms Ampl: -22.58 mFS



Track 1 forward


FIG. 7A**SignalScope Source: Headset Mic**

Ch1: Time: 12.56 ms Ampl: -104.46 mFS



Track 1 reverse

FIG. 7B

**FIG. 8**




FIG. 9




FIG. 10




FIG. 11




FIG. 12






FIG. 13

**FIG. 14**

**FIG. 15**

Carrier

 8:28 PM

Settings

Pay
Sightglass Coffee

Pay

\$15.33

Enter an optional note

AMEX

1004

Clear

7	8	9
4	5	6
1	2	3
00	0	

FIG. 16A





FIG. 16B

**FIG. 16C**


	\$18.40	— Tip 20% \$3.07 +
× 		
 1004	Jackson Walker	
Cancel	I agree to pay the above total amount according to my card issuer agreement	Done

FIG. 16D




FIG. 16F




FIG. 16E




FIG. 17





FIG. 18

***FIG. 19***




FIG. 20




FIG. 21

**PAYMENT METHODS WITH A PAYMENT
SERVICE AND TABS SELECTED BY A FIRST
PARTY AND OPENED BY A SECOND PARTY
AT ANY GEOGRAPHIC LOCATION OF THE
FIRST PARTYS MOBILE DEVICE**

**CROSS-REFERENCE TO RELATED
APPLICATIONS**

[0001] This application is a continuation of U.S. Ser. No. 13/088,038 filed Apr. 15, 2011, which is a continuation-in-part of U.S. Ser. No. 12/903,753, U.S. Ser. No. 12/903,823, both filed Oct. 13, 2010, U.S. Ser. No. 12/985,982 filed Jan. 6, 2011 and U.S. Ser. No. 13/005,822 filed Jan. 13, 2011, U.S. Ser. No. 13/010,976, filed Jan. 21, 2011 and U.S. Ser. No. 13/012,495, filed Jan. 24, 2011, U.S. Ser. Nos. 13/042,203, 13/043,258, 13/043,263, 13/043,268 and 13/043,270, all filed Mar. 8, 2011, all of which applications are incorporated herein by reference. This application is related to U.S. patent application Ser. No. 12/456,134, filed Jun. 10, 2009, and is hereby incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] 1 Field of the Invention

[0003] The present invention relates generally to payments of a first party to a second party, and more particularly to payments by a first party to a second party using a payment service by the first party opening a tab that is selected by the second party at any geographic location of the first parties mobile device.

[0004] 2. Description of the Related Art

[0005] Plastic cards having a magnetic stripe embedded on one side of the card are prevalent in everyday commerce. These cards are used in various transactions such as to pay for purchases by using a credit card, a debit card, or a gasoline charge card. A charge card or a debit card may also be used to transact business with a bank through use of an automated teller machine (ATM). The magnetic stripe card is capable of storing data by modifying the magnetism of magnetic particles embedded in the stripe. The data stored on the magnetic stripe may be sensed or read by swiping the stripe past a read head. The analog waveform obtained by sensing the magnetic stripe must undergo a process known as decoding to obtain the digital information stored in the magnetic stripe of the card.

[0006] Currently, there are hundreds of magnetic stripe readers/swipers on the market, all of them are at least as long as the credit card itself. These existing readers/swipers can be classified as either platform card readers or plunge card readers. Platform card readers are traditional card swipers with single rails, which allow a card to be held against the base of the reader by the user and moved across the read head of the reader. Plunge swipers guide a card by two sets of rails and a backstop. Once the user has inserted the card against the backstop, the card is read as it is removed from the plunge swipers. Plunge swipers are common on ATMs and other self-pay devices because they are less prone to hacking.

[0007] Magnetic stripe cards having standard specifications can typically be read by point-of-sale devices at a merchant's location. When the card is swiped through an electronic card reader, such as a platform card reader, at the checkout counter at a merchant's store, the reader will usually use its built-in modem to dial the number of a company that handles credit authentication requests. Once the account is

verified and an approval signal will be sent back to the merchant to complete a transaction.

[0008] Although magnetic stripe cards are universally used by merchants, there is no way for an individual to take advantage of the card to receive a payment from another individual (who is not a merchant) by swiping the card through a simple reader attached to his/her mobile device. For a non-limiting example, one person may owe another person money for a debt, and the conventional way to pay the debt is to provide cash or a check. It would be convenient to be able to use a credit card or a debit card to pay off the debt. In addition, it is advantageous for an individual to make payment to another individual or merchant by swiping his magnetic stripe card through a reader connected to a mobile device.

[0009] The foregoing examples of the related art and limitations related therewith are intended to be illustrative and not exclusive. Other limitations of the related art will become apparent upon a reading of the specification and a study of the drawings.

SUMMARY OF THE INVENTION

[0010] An object of the present invention is to provide methods for a first party to pay a second party using a payment service.

[0011] Another object of the present invention is to provide methods for a first party to pay a second party using a payment service by the first party opening a tab that is selected by the second party at any geographic location of the first parties mobile device.

[0012] Yet another object of the present invention is to provide methods for a first party to pay a second party using a payment service by the first party opening a tab that is selected by the second party at any geographic location of the first parties mobile device, but the financial transaction can only be completed when the first party is within a defined geographic area.

[0013] These and other objects of the present are achieved in a method is provided of paying a second party is provided. A first party accesses the names of one or more qualified second parties. The qualified second parties are second parties that, (i) have an association with the payment service, and (ii) second parties that if they do not have an established association with the payment service then they have established one prior to payment. The first party has an association with the payment service. A tab is opened by the first party that can be selected by the qualified second party at any geographic location of a first party's mobile device. The qualified second party is only able to charge a first party's financial account when the first party's mobile device is within a defined geographic area. The tab is a relationship between the first party, the payment service and the qualified second party. The qualified second party can engage in a financial transaction with the first party is within the defined geographic area.

[0014] In another embodiment, a method of paying a second party includes accessing by a first party, with the first party's mobile device, names of one or more qualified second parties. Second parties have an association with the payment service or if not, they established an association with the payment service prior to payment. The first party has an association with the payment service. A tab is opened by the first party that can be selected by the qualified second party at any geographic location of a first party's mobile device. The qualified second party is only able to charge a first party's

financial account when the first party's mobile device is within a defined geographic area. The tab is a relationship between the first party, the payment service and the qualified second party. The qualified second party can engage in a financial transaction with the first party within the defined geographic area.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] FIG. 1 depicts an example of a system diagram to support financial transaction between a payer and a payee through a miniaturized card reader connected to a mobile device.

[0016] FIG. 2 depicts an example of an external structural diagram of a miniaturized card reader.

[0017] FIGS. 3(a)-(b) depict examples of actual card reader with miniaturized design.

[0018] FIGS. 4(a)-(b) depict examples of alignment between read head of the card reader and magnetic stripe of card being swiped.

[0019] FIG. 5 depicts an example of a TRS connector as a part of card reader.

[0020] FIGS. 6(a)-(c) depict examples of internal structures of a miniaturized card reader.

[0021] FIGS. 7(a)-(b) depict examples of waveforms of data read from one track of the magnetic stripe by read head when the card is swiped through the slot of the card reader in the forward and reverse directions, respectively.

[0022] FIG. 8 depicts a flowchart of an example of a process to support swiping of a card with a magnetic stripe through a miniaturized portable card reader.

[0023] FIG. 9 depicts an example of schematic diagram of passive ID circuitry embedded in the card reader.

[0024] FIG. 10 depicts an example of schematic diagram that contains additional components of passive ID circuitry 22 that contribute to the user experience.

[0025] FIG. 11 depicts an example of an implementation for passive ID circuitry 22 depicted in FIG. 10.

[0026] FIG. 12 depicts a flowchart of an example of a process to deliver the unique ID to mobile device via the passive ID circuitry.

[0027] FIG. 13 depicts an example of additional encryption and/or decryption systems included in the passive ID circuitry for encrypting and decrypting of unique ID of card reader.

[0028] FIG. 14 depicts a flowchart of an example of a process to support decoding of incoming signals from swiping of a card with a magnetic stripe through a miniaturized portable card reader.

[0029] FIG. 15 depicts a flowchart of an example of a process to support financial transaction between a payer and a payee through a miniaturized card reader connected to a mobile device.

[0030] FIGS. 16(a)-(f) depict screenshots of an example of a financial transaction between a purchaser and a merchant through a miniaturized card reader connected to a mobile device.

[0031] FIG. 17 illustrates an integrated read head/mobile device embodiment of the present invention.

[0032] FIG. 18 illustrates one embodiment of a method of making payments using a mobile device where a tab is opened by a first party and is selected by a qualified second party at any geographic location of the first party's mobile device.

[0033] FIG. 19 illustrates an overall system architecture of a payment service that can be used in various embodiments of the present invention.

[0034] FIG. 20 illustrates an embodiment of the present invention for a method of conducting on-line purchases using a mobile device.

[0035] FIG. 21 illustrates an embodiment of the present invention where a method is provided for transferring funds to and/or from a first party's financial account, and the first party's financial account information is entered with a single initial entry to the payment service and for future payments the information need not be re-entered.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0036] The approach is illustrated by way of example and not by way of limitation in the figures of the accompanying drawings in which like references indicate similar elements. It should be noted that references to "an" or "one" or "some" embodiment(s) in this disclosure are not necessarily to the same embodiment, and such references mean at least one.

[0037] A new approach is proposed that contemplates systems and methods to enable an individual to complete a financial transaction by swiping a magnetic stripe card through a card reader connected to a mobile device. It will be appreciated that the systems and methods of the present invention can be used with financial transactions cards characterized as: (i) allowing a user to choose to pay with reward points or credit, (ii) one that is a credit and a debit card, (iii) having fraud protection built into the card, (iv) having an integrated chip instead of a magnetic strip and the like. In the embodiment of card with an integrated chip, the card has electrical connectors which when fed a current respond with a signal indicative of information stored on the card. A read head is not used with this type of card.

[0038] Here, the financial transaction can be any transaction that involves receiving or sending payment from one person to another. The magnetic stripe card can be but is not limited to a credit card, a debit card, or other types of payment authenticating pieces capable of carrying out the financial transaction. The size of the card reader is miniaturized to be portable for connection with the mobile device. The card reader is configured to reliably read data encoded in a magnetic strip of the card with minimum error in a single swipe and provide a signal that corresponds to the data read to the mobile device, which then decodes the incoming signal from the card reader and acts as a point-of-sale device to complete the financial transaction. Such an approach enables a person to become either a micro-merchant (payee or second party) or a buyer/customer (payer or first party) without having to purchase expensive card reader devices or software.

[0039] FIG. 1 depicts an example of a system diagram to support financial transaction between a payer and a payee through a miniaturized card reader connected to a mobile device. Although the diagrams depict components as functionally separate, such depiction is merely for illustrative purposes. It will be apparent that the components portrayed in this figure can be arbitrarily combined or divided into separate software, firmware and/or hardware components. Furthermore, it will also be apparent that such components, regardless of how they are combined or divided, can execute on the same host or multiple hosts, and wherein multiple hosts can be connected by one or more networks.

[0040] In the example of FIG. 1, the system includes a mobile device 100, a miniaturized card reader 10 connected to mobile device 100, a decoding engine 110, a user interaction engine 120, and a transaction engine 130, all running on

mobile device **100**. Additionally, the system may also include one or more of user database **140**, product or service database **150**, and transaction database **160**, all coupled to the transaction engine **130**.

[0041] As used herein, the term engine refers to software, firmware, hardware, or other component that is used to effectuate a purpose. The engine will typically include software instructions that are stored in non-volatile memory (also referred to as secondary memory). When the software instructions are executed, at least a subset of the software instructions is loaded into memory (also referred to as primary memory) by a processor. The processor then executes the software instructions in memory. The processor may be a shared processor, a dedicated processor, or a combination of shared or dedicated processors. A typical program will include calls to hardware components (such as I/O devices), which typically requires the execution of drivers. The drivers may or may not be considered part of the engine, but the distinction is not critical.

[0042] As used herein, the term database is used broadly to include any known or convenient means for storing data, whether centralized or distributed, relational or otherwise.

[0043] In the example of FIG. 1, mobile device **100** to which the portable card reader **10** is connected to can be but is not limited to, a cell phone, such as Apple's iPhone® (mobile digital device), other portable electronic devices, such as Apple's iPod Touches® (mobile digital device), Apple's iPads® (mobile digital devices), and mobile devices based on Google's Android™ operating system, and any other portable electronic device that includes software, firmware, hardware, or a combination thereof that is capable of at least receiving the signal, decoding if needed, exchanging information with a transaction server to verify the buyer and/or seller's account information, conducting the transaction, and generating a receipt. Typical components of mobile device **100** may include but are not limited to persistent memories like flash ROM, random access memory like SRAM, a camera, a battery, LCD driver, a display, a cellular antenna, a speaker, a Bluetooth® circuit, and WIFI circuitry, where the persistent memory may contain programs, applications, and/or an operating system for the mobile device.

[0044] In one embodiment of the present invention a system is provided with transaction engine **130** running on mobile device **100**. In response to a financial transaction between a buyer and a seller, the mobile device **100** accepts information selected including but not limited to information from financial transaction or information pertaining to financial transaction card used by the buyer in the transaction. Additionally, a financial transaction device can be utilized. Non-limiting examples of financial transaction devices include but are not limited to a, wristband, RFID chip, cell phone, biometric marker and the like. At least a portion of this information is communicated with a third party financial institution or payment network to authorize the transaction. The buyer receives confirmation of the payment. Payment confirmation can be in real time by a payment service.

[0045] Payment confirmation can be made with a communication channel of the buyer's choice. As non-limiting examples, confirmation of payment can be an electronic notification in the form selected from at least one of, email, SMS message, tweet (message delivered via Twitter® (online social networking service)), instant message, communication within a social network and the like.

[0046] In response to the transaction, a confirmation is made that the buyer is authorized to use the financial transaction card in order to prevent fraud. There can also be a confirmation that there are sufficient funds for the purchase made by the buyer.

[0047] In one embodiment, it is determined that the buyer, authorized to use the financial transaction card, is present with the seller at the time of the financial transaction.

Miniaturized Card Reader

[0048] In the example of FIG. 1, miniaturized card reader **10** is configured to read data encoded in a magnetic strip of a card being swiped by a buyer and send a signal that corresponds to the data read to mobile device **100** via a signal plug **18**. This signal is at least partially if not fully decoded in the mobile device **100**.

[0049] The size of card reader **10** is miniaturized to be portable for connection with mobile device **100**. For a non-limiting example, the size of card reader **10** can be miniaturized to an overall length of less than 1.5". In addition, the miniaturized card reader **10** is also designed to reliably read the card with minimum error via a single swipe by counteracting vendor specific filtering done by mobile device **100**. Note that this broad overview is meant to be non-limiting as components to this process are represented in different embodiments. For instance the decoding engine **110** can be embedded in the card reader **10** as shown in FIG. 13 as the decoding system **42**. FIG. 2 depicts an example of an external structural diagram of miniaturized card reader **10**. Although the diagrams depict components as functionally separate, such depiction is merely for illustrative purposes. It will be apparent that the components portrayed in this figure can be arbitrarily combined or divided into separate software, firmware and/or hardware components.

[0050] In the example of FIG. 2, miniaturized card reader **10** is shown to comprise at least a housing **12** having a slot **14**, a read head **16** embedded on a wall of slot **14**, a signal plug **18** extending out from the housing **12**, and an optional passive ID circuit **22**.

[0051] FIG. 3(a) depicts an example of an actual card reader with miniaturized design and FIG. 3(b) depicts other examples of miniaturized card reader with width around 0.5".

[0052] The card reader **10** includes the slot **14** and is miniaturized relative to the size of the mobile device **100**. In some embodiments, the housing **12** is not included.

[0053] In one embodiment, the slot **14** is configured to maintain contact between the read head **16**, and the magnetic stripe of the financial transaction card during a swipe. The signal is decoded in the mobile device **100**. The decoding includes determining pulses in the signal and converting at least some of the pulses to characters. In one embodiment, the slot **14** has a width of no greater than 1 mm. The width of the slot **14** is sufficient to enable a successful swiping of the financial transaction card, while producing the signal. It is sized to enable the successful swipe without creating sufficient torque between the signal plug **18** or output jack and the read head **16** or at the mobile device **100** to cause damage due to excessive torque. If the slot **14** is too wide, then it is more difficult to achieve a successful swipe that produce the signal. If there is a miss, or insufficient data is generated, then the resulting signal is not competent. If the slot **14** is too narrow, then the financial transaction card can not be swiped. The size of the slot **14** is selected to reduce torque as discussed above. Additionally, in one embodiment, the output jack **18** is at least

partially if not fully rotatable relative to the port it is coupled to in the mobile device **100**. The decoding includes error checking. In one embodiment, the decoding includes detecting that data in the signal is from the financial transaction card, seeing the beginning and ending sentinels and reconstructing data in the signal from a pattern of pulses.

[0054] In one embodiment of the present invention, the mobile device **100** has an audio input port and a line input port. In one embodiment, a sampling rate of the signal at the audio input port or a line input port of the mobile device is at least 15 kHz. In various other embodiments, the sample rate of the signal at the audio input port or line input port can be, least 20 kHz; at least 25 kHz, at least 30 kHz, at least 35 kHz or at least 40 kHz.

[0055] In one embodiment, the slot **14** is oriented and sized to reduce torque applied on the read head **10** when the financial transaction card is swiped through the slot **14** in order to maintain accuracy and reliability of the data read by the read head **10**.

[0056] In the example of FIG. 2, housing **12** of card reader **10** is designed to be asymmetrical with respect to slot **14**, with texture such as logo on one side of the housing that can be felt and recognized by a user with a touch of a finger. For correct swiping of the card, the texture side of housing **12** should match with the texture (front) side of the card, so that a user can easily identify the right side of the reader to swipe the card through slot **14** without actually looking at the reader or card. Even a blind person is able to swipe the card correctly by matching the texture side of the reader with the texture side of the card.

[0057] In the example of FIG. 2, the slot **14** is wide enough and deep enough to accept a card having a magnetic stripe so that the stripe will fit within the slot **14**. More importantly, the slot **14** is configured to reduce the torque applied on the reader **10** when the card is swiped through slot **14** in order to maintain accuracy and reliability of the data read by read head **16**. Since the size of card reader **10** is miniaturized, slot **14** also has a length that is significantly less than the length of the card to be inserted into the slot **14**.

[0058] To correctly read the data on the magnetic stripe of the card, the read head **16** must maintain contact with the stripe as the card moves past slot **14**. If the card rocks during the swipe, the alignment of the head **12** with the stripe may be compromised. As the length of the slot **14**, i.e., the card path through which the card swiped through slot **14**, is shortened, rocking and head alignment may become significant issues. As shown in FIG. 4(a), if the magnetic stripe card is swiped through without the base of the card resting against the flat bottom piece, the magnetic stripe will not align with the read head **16** when the card is swiped through slot **14** having a flat base **15**.

[0059] In some embodiments, the base **15** of slot **14** can be changed from flat to a curved base with a radius in order to increase contact between the read head **16** and the magnetic stripe to address the rocking problem. As shown in FIG. 4(b), the read head **16** can maintain contact with the magnetic stripe, even with some additional error due to the gradation of contact introduced by the curved base **15**.

[0060] FIG. 5 depicts an example of signal plug **18** as part of card reader **10**. Here, signal plug **18** can be but is not limited to a TRS (tip, ring, sleeve) connector also known as an audio plug, phone plug, plug plug, stereo plug, mini-plug, or a

mini-stereo audio connector. The signal plug **18** may be formed of different sizes such as miniaturized versions that are 3.5 mm or 2.5 mm.

[0061] In some embodiments, signal plug **18** may be retractable within the housing **12**. In some embodiments, signal plug **18** is configured to extend beyond housing **12** of the reader in order to accommodate connection with mobile devices **100** having cases or having a recessed plug-in socket, wherein the socket can be but is not limited to a microphone input socket or a line in audio input of the mobile device.

[0062] In some embodiments, housing **12** of card reader **10** is made of non-conductive material such as plastic so that the reader will not interfere with the function of mobile device **100** it is connected with. Such choice of material is important since the outer case of certain mobile devices, such as iPhone®4, is conductive and serves as an antenna for the device, which function could potentially be interfered with if the metal case of the device gets in touch with the housing of a card reader made of conductive material.

[0063] FIG. 6(a) depicts an example of an internal structural diagram of a miniaturized card reader. Although the diagrams depict components as functionally separate, such depiction is merely for illustrative purposes. It will be apparent that the components portrayed in this figure can be arbitrarily combined or divided into separate software, firmware and/or hardware components.

[0064] In the example of FIG. 6(a), the internal structure inside housing **12** of card reader **10** is shown to comprise at least a read head **16** with embedded circuitry, and a spring structure **20** to support read head **16**. FIG. 6(b) depicts an example of an internal structure an actual miniaturized card reader. FIG. 6(c) depicts an example of separated components of read head **16** and spring structure **20** used in the actual miniaturized card reader.

[0065] In the example of FIGS. 6(a)-(c), read head **16**, which for a non-limiting example, can be an inductive pickup head, detects and provides data stored in the magnetic stripe of a card to a connected mobile device **100**. More specifically, as the magnetic stripe of a card is swiped through slot **14** and in contact with read head **16**, the card reader device **10** reads one or more tracks of data or information stored in the magnetic stripe of the card via the detection circuitry embedded inside the read head. Here, data stored in the magnetic stripe may be in the form of magnetic transitions as described in the ISO 7811 standards. As the card moves past the read head **16**, magnetic transitions representing data induce a voltage or waveform in a coil (not shown) of read head **16** due to such relative movement between read head **16** and the stripe (called the Hall Effect), wherein a resistor (not shown) inside read head **16** sets the amplitude of the waveform. This waveform is sent via the signal plug **18** into the socket which is registered by the microphone of the mobile device **100** connected with card reader **10**.

[0066] In some embodiments, read head **16** in card reader is capable of reading only one track of data (either track 1 or 2, but not both) from the magnetic stripe in order to reduce the size and structural complexity of compact read head **16** as only one pin needs to be included in the read head. FIGS. 7(a)-(b) depict examples of waveforms of data read from track 1 (instead of both tracks 1 and 2 as by a traditional read head) of the magnetic stripe by read head **16** when the card is swiped through slot **14** in the forward and reverse directions, respectively.

[0067] In some embodiments, the size or thickness of the housing 12 of card reader 10 is configured to be narrow enough to accommodate only a single read head 16. Such design is intended to be tampering-proof so that even if the housing 12 is tampered with, no additional circuitry can be added to the card reader 10 and such tampering will render the card reader non-functional.

[0068] In the example of FIGS. 6(a)-(c), spring structure 20 is a flexible spring mounting to read head 16 without a screw, causing the read head to be suspended to housing 12 of card reader 10. Here, spring 20 can either be connected to housing 12 via screws or welded to plastic housing 12 without using any screws. As the card moves past the read-head 16 on the miniaturized card reader, any card bending or misalignment may cause the read head to lose contact with the magnetic stripe. Spring 20 allows suspended read head 16 to swivel while maintaining contact pressure to track the stripe of the card being swiped. Spring 20 is designed to be sufficiently small to fit within the miniaturized card reader 10, yet powerful enough to maintain good contact during the stripe. Unlike traditional spring structures, spring 20 positions the supports for read head 20 inside the overall form of the spring, which allows the spring to flex without having to make one support moveable.

[0069] FIG. 8 depicts a flowchart of an example of a process to support swiping of a card with a magnetic stripe through a miniaturized portable card reader. Although this figure depicts functional steps in a particular order for purposes of illustration, the process is not limited to any particular order or arrangement of steps. One skilled in the relevant art will appreciate that the various steps portrayed in this figure could be omitted, rearranged, combined and/or adapted in various ways.

[0070] In the example of FIG. 8, the flowchart 800 starts at block 802 where a miniaturized card reader is structured to provide sufficient contact between a read head and the magnetic stripe during a swipe of a card. The flowchart 800 continues to block 804 where a card with a magnetic stripe is swiped through a slot of the miniaturized card reader. The flowchart 800 continues to block 806 where the read head reliably reads data stored in the magnetic stripe and generates an analog signal or waveform indicative of data stored in the magnetic stripe. The flowchart 800 continues to block 808 where amplitude of the waveform is set by the circuitry inside the read head. The flowchart 800 ends at block 810 where the set waveform is provided to a mobile device 100 connected with the miniaturized card reader via the signal plug 18.

Passive ID Circuit

[0071] In some embodiments, housing 12 of card reader 10 may further encapsulate a passive ID circuitry 22 powered by the mobile device 100 through signal plug 18, wherein passive ID circuitry 22 delivers a unique ID of the card reader to mobile device 100 only once upon the card reader being connected to (and powered up by) the mobile device. Although both are integrated in the same housing 12, passive ID circuitry 22 functions independently and separately from read head 18 without interfering with the read head's card swiping functions described above.

[0072] FIG. 9 depicts an example of schematic diagram of passive ID circuitry embedded in the card reader. In the example of FIG. 9, passive ID circuitry 22 may comprise at least five main subsystem/components: unique ID storage 24, communication subsystem 26, which reads and transmits the

unique ID from unique ID storage 24, power subsystem 28, which provides power to enable communication with mobile device 100, a pathway subsystem 30 to route signals to signal plug 18 through the circuitry, and a control unit 32, to orchestrate the communication between different systems. All of these subsystems can be implemented in hardware, software or a combination thereof. Communication subsystem 26, power subsystem 28, and read head 16 share the same signal plug 18 for connection with the mobile device. The components portrayed in this figure can be arbitrarily combined or divided into separate software, firmware and/or hardware components.

[0073] In the example of FIG. 9, unique ID storage 24 is memory containing the Unique ID of the card reader. The unique ID storage 24 can be any persistent memory containing bytes that can be accessed by the communication subsystem 26.

[0074] In the example of FIG. 9, the power subsystem 28 comprises of a modified charge pump, which utilizes a digital circuit to artificially raise the voltage of a power source to a higher level. Normal charge pump operation requires large current which is then fed into several capacitors, and switching logic switches the capacitors between series and parallel configurations. In the example of FIG. 10, the power source is a bias voltage provided by the mobile device meant for detection of a connected component. It is nominally 1.5V and is supplied through a 2 k Ω resistor, resulting in a maximum current of 750 μ A. Details of how the power subsystem 28 function is described in FIG. 11.

[0075] In standard operation the pathway subsystem 30 is configured to direct the mobile device's 100 bias voltage to the power subsystem 28. After the power subsystem converts the bias voltage to a system voltage, the control unit 32 is able to operate. Control unit 32 configures the pathway subsystem 30 to allow the communication subsystem 26 access to the mobile device 100. The communication subsystem 26 relays the unique ID from the unique ID storage 24. The control unit 32 then configures the pathway subsystem 30 to allow the card reader circuit 16 access to the mobile device 100.

[0076] FIG. 10 depicts an example of schematic diagram that contains additional components of passive ID circuitry 22 that contribute to the user experience. These additional systems prevent the mobile device 100 from perceiving that the card reader 10 has been disconnected during power cycles. These additional systems also ensure that the unique ID sent from unique ID storage 24 is sent as specified by the designer. This extra feature set comprises of a discharge subsystem 34 to force the device to power cycle, a fake load 36 so the mobile device 100 does not perceive a disconnect, and a monitor system 38 to manage card reader 10 behavior between power cycles.

[0077] In the example of FIG. 10, communication subsystem 26 comprises a signal driver connected with control unit 32 and unique ID storage 24. In a non-limiting embodiment of a system which sends an ID only once to a mobile device 100, after the control unit 32 boots up, communication subsystem 26 will check a status bit in the monitor subsystem 38. The first time this process occurs, the status bit will be not set. When the status bit is not set the ID is sent immediately. FIG. 12 contains a detailed flowchart of a non-limiting example of this process. In one embodiment the control unit 32 will write to the status bit in monitor subsystem 38. It will then use the discharge system 34 to reset itself. During this time the pathway subsystem 30 will be configured to direct

the signal path to the fake load preventing the mobile device 100 from detecting a disconnect with the card reader 10. Once the power subsystem 28 has completed its power cycle, the control unit 32 will read the status bit. Upon seeing that the status bit is cleared it will configure the pathway subsystem 30 to direct the signal path to the card reader circuit 16. The control unit 32 will then put the system into an extremely low power state (from here referred to as a sleep state). Only the monitoring subsystem 38 will remain active. The monitor subsystem 38 will wake the system from the sleep state at some time (time depending on implementation) before a power cycle. The control unit 32 will be notified of the system awakening by the monitoring subsystem 38. The control unit 32 will then set the status bit on the monitor subsystem 38 only if there is a voltage detected on the fake load indicating the reader is still connected. The control unit 32 will then force a power cycle.

[0078] FIG. 11 depicts an example of an implementation for passive ID circuitry 22 depicted in FIG. 10. In some embodiments, power subsystem 28 has multiple capacitors in parallel. A voltage breaker (e.g., zener diode etc) and a latch are used to trigger the transition between parallel and series configurations. Once the latch is flipped, power subsystem 28 will remain in series configuration until the combined voltage drops below the CMOS trigger gate voltage at about 0.4V. At this time the passive ID circuitry 22 will reset and the unique ID delivery process will begin again.

[0079] In the example of FIG. 11, pathway subsystem 30 comprises a plurality of latches controlled by control unit 32 for switching among various subsystems of passive ID circuitry 22. When passive ID circuitry 22 is in operation, the default configuration allocates the output signal through signal plug 18 to modified charge pump of power subsystem 28. After the latch to turn off modified charge pump 28 is triggered, control unit 32 will route signal plug 18 from read head 16 to communication subsystem 26 and transmit the unique ID through signal plug 18 after checking the status bit in unique ID storage 24. Pathway subsystem 30 will then write to the status bit in unique ID storage 24 and discharge the power subsystem 28. FIG. 12 depicts a flowchart of an example of a process to deliver the unique ID to mobile device 100 via the passive ID circuitry 22.

[0080] In some embodiments, passive ID circuitry 22 may further include additional encryption and/or decryption systems as shown in FIG. 13 for encrypting and decrypting of unique ID of card reader 10. In the example of FIG. 13, the decoding system 42 and encryption system 40 can both use the control unit 32 from the passive ID circuitry 22 to communicate with the mobile device 100 over the communication subsystem 26.

Signal Decoding

[0081] Once card reader 10 provides the set waveform to the attached mobile device 100, the incoming signals (waveform) may be amplified, sampled, and converted to a stream of digital values or samples by decoding engine 110 running via a microprocessor inside the mobile device. Here, decoding engine 110 may comprise a pipeline of software decoding processes (decoders) to decode and process the incoming signals as described below, where each software process in this pipeline can be swapped out and replaced to accommodate various densities of track data read in order to reduce card swipe error rate. The incoming signals may be of low quality due to one or more of: low quality of data read from a single

and/or low density track of a magnetic stripe of the card, sampling speed limitations of the microphone input socket of the mobile device, and noise introduced into the mobile device 100 from card reader 10. FIG. 14 depicts a flowchart of an example of a process to support decoding of incoming signals from swiping of a card with a magnetic stripe through a miniaturized portable card reader.

[0082] In the example of FIG. 14, the flowchart 1400 starts at block 1402 where decoding engine 110 initializes its internal state by waiting for the system voltage to reach a steady state. Upon initial connection of a card reader, there is usually a burst of signal due to feedback caused by slight impedance mismatches and the presence of non-linear elements like the read head. After at least 3 time constants, the signal is determined to be in a steady state. During such initialization phase, the DC offset of the incoming signals are computed when the mobile device is first connected to the card reader over signal plug 18. In some embodiments, initialization goes through at least the following steps:

[0083] Take one system buffer of audio signal and compute the DC offset of this buffer.

[0084] Save the computed DC offset.

[0085] Compute the average of the last three DC offsets.

[0086] Compute the variance of the current DC offset from the average computed in step 3.

[0087] The following values presented were found to be optimum for performance in the decoding system. In the spirit of full disclosure they have been provided here to allow someone trained in the arts to be able to replicate this process. It is fully realized that many other values can be used here and depending on hardware implementation. The values here are meant to be non-limiting. If the variance computed in step 4 is less than the variance threshold, 0.06% of full scale or less than the offset percentage, 10% of the offset average computed in step 3, and the DC offset computed in step 1 is less than the noise ceiling, 3% of full scale, of the mobile device 100. After initialization is complete, decoding engine 110 can proceed to process the incoming signals to detect the swipe of the card. Otherwise, Steps 1-4 need to be repeated.

[0088] The flowchart 1400 continues to block 1404 where decoding engine 110 detects the card swipe once the incoming signals are in a steady state. This signal detection phase processes the incoming signals in steady state in order to detect the presence of a swipe of a card through the card reader. The signal detection phase is a light-weight procedure that operates at near real time. It parses the incoming signals quickly and stitches multiple system buffers of signals together to form a signal of interest. In some embodiments, the signal detection process goes through at least the following steps:

[0089] Apply a software upscale of system buffers of the incoming signals.

[0090] Begin taking buffers of incoming signals and look for points that exceed a minimum signal amplitude threshold, which is a hardware-based parameterization found empirically.

[0091] Set a flag that triggers the detection of a swipe once a single point that exceeds the threshold is detected.

[0092] Once the flag triggered, the incoming signal is appended to a larger buffer until the signal drops below a minimum signal amplitude threshold for a certain period of time, e.g., 10 ms.

[0093] Trim the last 10 ms of data to reduce the amount of signal data to be processed later.

[0094] Check to see if at least a certain number of samples have been collected in the buffer to make sure that there are enough information for later decoding. This number is parameterized based on the hardware of the mobile device used.

[0095] Alternatively, a hardware independent swipe detection process can be utilized to capture the signal of interest via Fast Fourier Transform (FFT), while trimming the front and back of the signal. Such process would include at least the following steps:

[0096] Retrieve system buffers of incoming signals and keep a certain number of buffers of history of the signals.

[0097] Compute the frequency distribution of the signal history kept via FFT.

[0098] Locate two maxima in the histogram and check if one maximum is located at $2\times$ the frequency of the other maximum. If this condition is satisfied, continue to add on buffers of history that exhibit such behavior.

[0099] Once such behavior has stopped, begin removing signals from the beginning and ending of the signals in the buffers until SNR is maximized, wherein SNR is defined to be the two maxima's amplitudes that are greatest from the next maximum.

[0100] The flowchart 1400 continues to block 1406 once a card swipe is detected to be present where decoding engine 110 identifies peaks in the incoming signals. Peak detection is the most complex portion of decoding of incoming signals from credit card swipes, and credit card swipe decodes have traditionally not been done on heavily filtered signals like the signal that enters through the TRS plug, since most mobile device manufacturers assume the incoming signal is audio based. This results in a wide variety of signal filtering that peak detection must account for. Different peak detection approaches discussed below can be utilized by the microprocessor to perform peak detection in the incoming signals in different ways, all applying a basic, moving average low-pass filter to smooth out some of the high frequency noise in order to overcome the low quality data read, sampling speed limitations of the mobile device, and the noise introduced into the mobile device.

Reactive Peak Detection

[0101] Reactive peak detection is a heuristics based approach for peak detection, which is well suited for situations where the incoming signals from the card swipe is not excessively distorted by the mobile device's filter circuitry. This approach utilizes at least the following steps to detect signal peaks:

[0102] Seed an adaptive positive and adaptive negative threshold with an ambient noise value that is dependent on the hardware of the mobile device. These thresholds will be used for initial peak detection.

[0103] Begin processing through the sample buffer, and for each sample in the buffer:

[0104] Wait for the threshold to be crossed again when either the negative or positive threshold is crossed, except with a hysteresis factor applied to the threshold for the second crossing. The hysteresis factor is key in making this approach resistant to ringing in the incoming signals, which is associated with the active filter(s) of the platform hardware.

[0105] Begin looking for slope changes within this time frame once the two samples where the threshold is crossed have been established.

[0106] If more than one slope change is found, compute the midpoint of the two samples.

[0107] If only a single slope change is detected, then

[0108] Pick the maximum point for the slope change.

[0109] Compare the peak's amplitude to the previously found peak's amplitude (if this has been established).

[0110] Skip the current peak and move on if its amplitude is greater than $(([\text{full scale}] - [\text{current peak amplitude}] / ([\text{full scale}] * 100) + 100) \%$ of the previous peak's amplitude.

[0111] If the prior step did not result in skipping of the peak, check the peak's polarity against the previous peak's polarity.

[0112] If the peak's polarity is the same as the previous peak's polarity, then remove the previous peak and put the current peak in its place.

[0113] If the polarity of the current peak has changed, then simply add the current peak to the list of peaks. This step is another key component for making this approach resistant to ringing.

[0114] Upon the finding of a peak, update the adaptive threshold of the corresponding polarity as the polarity of the peak just found and the amplitude to be a percentage of this peak's amplitude. Here, the percentage is a parameter varied by the detection approach being used, since higher values more accurately detects peaks, but are not as resistant to noise, while lower values are more resistant to noise, but may pick up errant peaks associated with ringing.

Predictive Peak Detection

[0115] Predictive peak detection defers the heavy processing to the digitizing stage of decoding. Predictive peak detection is highly resistant to scratches in the card that could cause low quality or false peak information to manifest in the incoming signals. This approach is more memory intensive than the reactive peak detection approach since more peaks are stored. The approach utilizes at least the following steps to detect signal peaks:

[0116] Seed a positive and adaptive negative threshold with an ambient noise value that is dependent on the hardware of the mobile device.

[0117] Begin going through the sample buffer. For each sample in the buffer:

[0118] Begin waiting for the slope to change when either the positive or negative threshold is crossed.

[0119] When the slope changes, store the current sample as a peak.

Maxima Peak Detection

[0120] Maxima peak detection detects peaks by looking for local maxima and minima within a window of digital samples. If either of these is at the edges of the window of samples, then the approach skips the window and moves to the next window to look for local maxima and minima. These local maxima and minima are then stored into a list of peaks.

[0121] The flowchart 1400 continues to block 1408 where decoding engine 110 identifies the track from which data of the incoming signals are read through the swipe of the card via the card reader. Traditionally, track 1 and track 2 came off of different pins on the read head of a card reader, and so there was no need to guess which track is being read. Since read head 16 in card reader is capable of reading only one track of data from the magnetic stripe, track identification becomes an important issue. This track identification process is run by detection engine 110 after peaks are detected to guess and

recognize the track (track 1 or track 2) from which the data is read by card reader by inferring a range of peaks to be expected for signals coming from each track. Since track 1 is known to be much denser in data than track 2, it is thus reasonable to expect more peaks to be identified in data coming from track 1. Although this process is not a definitive guess, it yields the correct track value 99.9% when coupled with the peak detection algorithms described herein in testing. Alternatively, track guessing can be based on the number of bits found in the digital signals after the digitizing stage of decoding. When a decoder fails due to guessing the wrong track (since track identification affects how the bits from the digital signals are framed and matched against character sets), the decoder may simply choose another track type, though this makes the card processing more processor intensive.

[0122] The flowchart **1400** continues to block **1410** where decoding engine **110** digitizes the identified peaks in the incoming signals into bits. The digitizing process takes the given peak information turns them into binary data and appends them to an array of digital bits. There are two types of digitizers: reactive digitizing and predictive digitizing.

Reactive Digitizing

[0123] Reactive digitizing takes the given peak information as fact, and attempts to convert them into 1s and 0s in the following steps:

[0124] Go through all peak information. For each peak:

[0125] Identify the distance between each pair of adjacent peaks.

[0126] If these distances are similar (e.g., based on a parameter for finding a series of peaks that are equidistant from each other), begin looking for 1s and 0s. The initial peaks always represent zeros, since the credit card is padded with zeros at the front and back of the signal.

[0127] Once equidistant peaks are found, identify the number of samples between peaks, which is the number of samples that roughly equate to a bit.

[0128] Examine the number of samples between the current peak and the next peak.

[0129] Examine the number of samples between the current peak and the peak after the next.

[0130] Compare the results from Steps **5** and **6** against the value from Step **4**:

[0131] If the result from Step **5** is closer to the value from Step **4**, then identify the bit found as a 0.

[0132] If the result from Step **6** is closer, then identify the bit found as a 1.

[0133] Tie breaking: if the distances are equal and the next two peak amplitudes are smaller than the current peak amplitude, then identify the bit found as a 1. Otherwise, identify the bit found as a 0.

[0134] Once the peak is determined, update the bit length based on the peak found: if the peak found was a 0, update with the value of Step **5**; otherwise, use the value of step **6**.

[0135] Predictive Digitizing

[0136] Predictive digitizing of detected peaks in the incoming signals does not treat the list of peaks as facts. It first finds bit length, and then seeks to a point in the peak list where the next relevant peak should be. Once it reaches this location, it then searches before and after the location for the nearest peak. The process then checks the polarity of this peak compared to the previous peak examined. If the polarities are the same, the bit found is identified as a 1. Otherwise, it is identified

as a 0. This method of digitizing a peak list is effective in that it simply ignores any information that is likely irrelevant.

[0137] The flowchart **1400** ends at block **1412** where decoding engine **110** converts the array of digitized bits into words of card information. This converting process locates the bit sequence that is the start sentinel in the array. At that point, it takes frames of bits (e.g., 5 bits for track 2, 7 bits for track 1) and decodes them based on a symbol table. Along the way, the process constantly checks for parity and the LRC at the end to ensure the data is correct. If there are any errors in parity, LRC, or track length, blocks **1406-1412** may be repeated with a different set of parameters to get the correct signal data.

[0138] When a card swipe begins, decoding engine **110** can combine various peak detectors and digitizers discussed above in order to cover various ranges of degradation in quality of the analog input signal generated by card reader **10**. In some embodiments, different process combinations and parameters can be chosen and optimized depending on the hardware platform of the mobile device. These combinations and parameter values can be pre-determined based on experimentation and testing and initialized upon starting of the decoding process. The decoding then runs through all processes specified and runs certain specific processes multiple times in order to get the correct signal. Such decoding process allows automatic scaling and adjustment during each run to account for different amounts of noise, sampling speed variations, signal ringing, and swipe direction.

Card Present Transaction Without Information Sharing

[0139] In the example of FIG. **1**, user interaction engine **120** is a software application running on mobile device **100** associated with a payee (merchant) that enables the payer (buyer) and the merchant to interact with transaction engine **130** to complete a financial transaction. More specifically, it may take input of information related to the financial transaction from the buyer and/or the merchant, provide such input to transaction engine to initiate and complete the transaction, and present the result of the transaction to the buyer and the merchant. Here, the input of information accepted by user interaction engine **120** may include but is not limited to one or more of: amount of the transaction, including list price and optionally tips, additional notes related to the transaction such as written description and/or pictures of the item to be purchased, authorization and/or signature of the buyer.

[0140] In some embodiments, other than the conventional keyboard, user interaction engine **120** may utilize a touch screen of mobile device **100** to enable the buyer and the merchant to input numbers, characters, and signatures by touching the screen via a stylus or a finger.

[0141] In some embodiments, in addition to the result of the transaction, user interaction engine **120** may also present products or services provided by the merchant to the buyer in combination of one or more of text, pictures, audio, and videos, and enable the buyer to browse through the products and services on the mobile device to choose the one he/she intended to purchase. Such product information can be stored and managed in product database **150**.

[0142] In the example of FIG. **1**, transaction engine **130** takes as its input the decoded credit card information from decoding engine **110** and transaction amount from user interaction engine **120**. Transaction engine **130** then contacts third party financial institutions such as an acquiring bank that

handles such authorization request, directly or through a payment system, which may then communicate with the card issuing bank to either authorize or deny the transaction. If the third party authorizes the transaction, then transaction engine 130 will transfer the amount of money deducted from the account of the card holder (e.g., the buyer) to an account of the merchant and provide the transaction results to user interaction engine 120 for presentation to the buyer and the merchant. In this manner, the merchant may accept a payment from the buyer via card reader 10 and mobile device 100.

[0143] In the example of FIG. 1, although mobile device 100 is associated with the merchant, transaction engine 130 running on mobile device 100 protects the privacy of the buyer/payer during the card-present transaction by taking card information from the buyer directly from decoding engine 110 and do not share such information with the merchant via user interaction engine 120. Here, the card information that are not shared with the merchant includes but is not limited to, card number, card holder's name, expiration date, security code, etc. In essence, transaction engine 130 serves as an intermediary between the buyer and the merchant, so that the buyer does not have to share his/her card information with the merchant as in a typical card-present transaction or an online transaction. Still, the buyer is able to obtain an itemized receipt for the transaction completed as discussed later.

[0144] In some embodiments, although transaction engine 130 does not share card information of the buyer to the merchant, it may present identity information of the buyer, such as a picture of the buyer on record in user database 140, with the merchant via user interaction engine 120 so that merchant can reliably confirm the identity of the buyer during the card-present transaction to prevent credit fraud.

[0145] In the example of FIG. 1, user database 140, product database 150, and transaction database 160 can be used to store information of buyer and the merchant, products and services provided by the merchant, and transactions performed, respectively. This information can also be stored by the payment system. Here, user information (e.g., name, telephone number, e-mail, etc.) can be obtained through online user registration and product information can be provided by the merchant, while transaction database 160 is updated every time a transaction is processed by the transaction engine 130. Information stored can be selectively accessed and provided to the buyer and/or merchant as necessary.

[0146] In the example of FIG. 1, transaction engine 130 communicates and interacts with the third party financial institution directly or through the payment system, user database 140, product database 150, and transaction database 160 over a network through the payment system (not shown). Here, the network can be a communication network based on certain communication protocols, such as TCP/IP protocol. Such network can be but is not limited to, internet, intranet, wide area network (WAN), local area network (LAN), wireless network, Bluetooth, WiFi, and mobile communication network. The physical connections of the network and the communication protocols are well known to those of skill in the art.

Dynamic Receipt

[0147] In various embodiments, upon the completion of a financial transaction through, for a non-limiting example, card reader 10 connected to mobile device 100 associated with a merchant, transaction engine 130 running on the

mobile device 100 can be configured to capture additional data associated with the transaction and incorporate the additional data into a dynamic receipt for the transaction, wherein in addition to transaction information typically included in a conventional receipt, the dynamic receipt may also include additional environmental information of the transaction. For non-limiting examples, the financial transaction can be an electronic transaction conducted over the Internet or a card present point-of-sale transaction where the buyer/payer makes the purchase at a store front, other "brick-and-mortar" location, or simply in presence of a merchant/payee.

[0148] In some embodiments, the additional environmental information included in the dynamic receipt may include information pertaining to the transaction environment. In one non-limiting example, a mobile device equipped with a Global Positioning System (GPS) receiver can be used to capture the coordinates/location of the transaction, and record it as a part of the information on the dynamic receipt. This way, the physical location of the point of sale (which may be different from the merchant/payee's registered address) can be recorded and used by transaction engine 120 to verify the transaction. In another non-limiting example, a mobile device equipped with a camera and/or audio and/or video recorder can be used to capture a photo and/or a video and/or an audio recording of the product or service involved in the transaction and incorporate such data or link/reference to such data into the dynamic receipt. In another non-limiting example, a mobile device with a biometric scanner can be used to scan the fingerprint or palm print of the buyer/payer and/or merchant/payee and includes at least a portion of such information in the dynamic receipt. In another non-limiting example, the mobile device can record certain information associated with the transaction in the dynamic receipt, wherein such information includes but is not limited to, how quickly the buyer swipes the card, the angle at which the card is swiped. In another non-limiting example, special characteristics of the card being swiped, also referred to as the magnetic fingerprint of the card, can be recorded and included in the dynamic receipt.

[0149] In some embodiments, the dynamic receipt can be in electronic form that can be accessed electronically or online and may also include link or reference pointing to multimedia information such as image, video or audio that are relevant to the transaction.

[0150] In some embodiments, transaction engine 130 can use the environmental information included in the dynamic receipt to assess risk associated with a transaction. For a non-limiting example, if the GPS information indicates that the transaction is taking place in a high crime/high risk area, the risk associated with the transaction is adjusted accordingly, and the buyer's bank may be notified accordingly. Alternatively, biometric information scanned and included in the dynamic receipt can be used for identity verification purposes to prevent identity theft and credit fraud.

[0151] In some embodiments, transaction engine 130 can use the dynamic receipt can be used as a non-intrusive way to communicate with the buyer and/or the merchant. For a non-limiting example, the additional information included in the dynamic receipt can be used to make offers to the buyer. If a dynamic receipt includes the GPS location of the point of sale of the transaction, coupons or other promotional offers made by vendors at nearby locations can be presented to the buyer when the buyer chooses to view the receipt electronically online. Alternatively, if a specific product involved the trans-

action can be identified by the transaction engine either directly through product description or indirectly by analyzing pictures or videos taken, offers of similar or complementary products can be made by a vendor to the merchant of the product.

[0152] In some embodiments, transaction engine **130** may notify buyer and/or the merchant of the receipt via an electronic message, which can be but is not limited to, an email message, a Short Message Service (SMS) message, Twitter® (online social networking service), or other forms of electronic communication. The recipient of the electronic message may then retrieve a complete itemized dynamic receipt online at his/her convenience via a telephone number on his/her record in user database **140** to retrieve his/her electronic receipts stored in transaction database **160**. In some embodiments, the electronic message may include an indication such as a code that the recipient can use to retrieve the electronic receipt online as an alternative or in combination with the telephone number.

[0153] FIG. **15** depicts a flowchart of an example of a process to support financial transaction between a payer and a payee through a miniaturized card reader connected to a mobile device. In the example of FIG. **15**, the flowchart **1500** starts at block **1502** where an amount of a financial transaction is provided through an interactive user application launched on the mobile device as shown in FIG. **16(a)**. The flowchart **1500** continues to block **1504** where a miniaturized card reader structured to minimize swipe error is connected to the mobile device as shown in FIG. **16(b)**. The flowchart **1500** continues to block **1506** where a card is swiped through the card reader to initiate the financial transaction as shown in FIG. **16(c)**. The flowchart **1500** continues to block **1508** where the payer confirms the amount of the card-present transaction via a signature signed via the interactive user application on the mobile device to complete the transaction as shown in FIG. **16(d)**. Payments are made with the use of the payment system which is coupled to the mobile device **100**. Note that the signature is required as an additional layer of confirmation for the protection for the payer even when such signature may not be technically required to authorize the transaction. The flowchart **1500** continues to block **1510** where result of the transaction is received and presented to the payer and/or merchant as shown in FIG. **16(e)** through the use of the payment system. The flowchart **1500** ends at block **1512** where an electronic receipt of the transaction is provided to the payer in the form of an electronic message as shown in FIG. **16(f)**.

[0154] In one embodiment, a longitudinal plane of the of the output jack **18** lies within the plane that the card travels in the slot **14** within 5 mm, and in another embodiment within 3 mm.

[0155] Referring now to FIG. **17**, in one embodiment of the present invention an integrated read head system includes mobile device **212** with an audio jack **214** at least one microphone input port **216**. A read head **218** is physically coupled to the mobile device **212**. The read head **218** has a slot **220** for swiping a magnetic stripe of a financial transaction card to enable a financial transaction between a buyer and seller with the payment system. The read head **218** reads data on the magnetic stripe and produces a signal indicative of data stored on the magnetic stripe. The read head **218** has an output jack **222** that physically connects the read head **218** to at least one of the audio jack **214** or microphone port **216** of the mobile device **212**. The read head **218** provides the signal to the

mobile device **212**. The signal is decoded at the mobile device **212**. The decoding includes determining pulses in the signal and converts at least some of the pulses to characters.

[0156] In another embodiment of the present invention, a method is provided for conducting a financial transaction with a financial transaction card using the integrated read head system **210**.

[0157] In one embodiment of the present invention, as illustrated in FIG. **18**, a method of paying a second party (payee) is provided. In this embodiment, a first party (payer) views the names of one or more qualified second parties. The qualified second parties are second parties that, (i) have an association with the payment service, and (ii) second parties that if they do not have an established association with the payment service then they have established one prior to payment. The first party has an association with the payment service. A tab is opened by the first party that can be selected by the qualified second party at any geographic location of a first party's mobile device **100**. The qualified second party is only able to charge a first party's financial account when the first party's mobile device **100** is within a defined geographic area. The tab is a relationship between the first party, the payment service and the qualified second party. The qualified second party can engage in a financial transaction with the first party is within the defined geographic area. The overall architecture of the payment system is illustrated in FIG. **19**.

[0158] The first party's mobile device **100** is configured to communicate with the payment service. The first party views the names of the one or more qualified second parties with the first party's mobile device **100**. The first party establishes the first party's financial account. The first party enters financial account information with a single initial entry to the payment service and additional entries of the financial account information to the payment service are not required for future financial transactions between the first party and any qualified second party when the same payment service is used.

[0159] The financial account is selected from at least one of, a bank account, credit card, debit card, pre-paid card, a second party financial account and the like. The financial account is selected by the first party by at least one of, use of a mobile device **100**, from a bank terminal, done on-line and the like. The first party's financial account can be a financial transaction card, and the entering of the first party's financial card information is with a mobile device **100**. Entering of the financial card information can be done by, swiping the financial transaction card through a slot of a card reader coupled to the mobile device **100**, through a slot of the mobile device **100**, by touch of the financial transaction card to the mobile device **100**, by typing in information at the mobile device **100**, with photos, by selecting a card from an application on a mobile device **100**, from an on-line entity and the like. The mobile device **100** is a device as described above.

[0160] The qualified second party can see a list of first parties that have an association with the payment service. The qualified second party can view a list of first parties with open tabs. The list of first parties seen by the qualified second party has first party identifying information. The identifying information is anything that reliably identifies the first party and can include, but is not limited to, names, photos, cell number, social security number, e-mail address, other personal identifying information for a first party and the like.

[0161] In another embodiment, a method of paying a second party a first party views the names of one or more qualified second parties with a mobile device **100**. Preferably, the

mobile device **100** is the first party's mobile device **100**. A tab is then opened by the first party as recited above that can be selected by the qualified second party at any geographic location of the first party's mobile device **100**, but the qualified second party is only able to charge a first party's financial transaction card when the first party's mobile device **100** is within a defined geographic area. In one embodiment, the mobile device **100** is coupled to a card reader that includes an output jack adapted to be inserted at least one of the audio input port or microphone input port of the mobile device **100** and delivers a signal to the mobile device **100**. In various embodiments, the sampling rate of the signal at the audio input port or a line input port of the mobile device **100** is at least 15 kHz, 20 kHz, 30 kHz, 40 kHz and the like.

[0162] Entering of the financial card information can be achieved by a variety of methods including but not limited to, swiping the financial transaction card through a slot of a card reader coupled to the mobile device **100**, through a slot of the mobile device **100**, with a touch of the financial transaction card to the mobile device **100**, typing in information at the mobile device **100**, with photos, selecting a card from an application on a mobile device **100** and from an on-line entity and the like.

[0163] A confirmation of payment can be made to the first party in response to a transfer of funds from the financial transaction card. In various embodiments, the financial transaction card is selected from at least one of, credit financial transaction card, debit financial transaction card, gift financial transaction card, fund transfer financial transaction card, other types of payment authenticating piece capable of carrying out a transfer of funds and the like, as set forth above.

[0164] In another embodiment of the present invention, illustrated in FIG. **20**, a method is provided of conducting on-line purchases using a mobile device **100**. A first party visits a second party on-line entity. The first party accesses a second party on-line entity. The first party is already registered with the payment service or becomes registered prior to the conclusion of completing a transaction. The mobile device **100** is configured to communicate with the payment service. The first party considers conducting a transaction with the second party on-line entity. The second party on-line entity is registered with the payment service, or in response to the first party's desire to transact with the second party on-line entity, the second party on-line entity becomes registered with the payment service. The first party enters personal identifying information that is sent to the payment service. In response, the first party receives a push notification to the first party's mobile device **100** that enables the first party to complete the transaction with the second party on-line entity.

[0165] In various embodiments, the first party's personal identifying information is entered by at least one of, use of a mobile device **100**, from a bank terminal, done on-line and the like. For the transaction, the first party uses the first party's financial account. The first party enters financial account as recited above, which does not require re-entry with the payment service for future transactions with second parties that are also registered with the payment service.

[0166] In one embodiment, the first party uses the first party's financial transaction card for the transaction where the card information is entered to the payment service as recited above. Additionally, the first party enters its personal identifying information with the payment service only once as recited above and need not re-enter for second party transactions.

[0167] In various embodiments, the on-line entity is any second party that can transact business with the payment service including but not limited to, merchants, peers and the like.

[0168] In one specific embodiment, the first party enters its personal identifying information, that is sent to the payment service, using the first party's mobile device **100**. In this embodiment, the first party can use a first party financial card to complete the transaction. The first party's mobile device **100** is coupled to a card reader that includes an output jack adapted to be inserted at least one of the audio input port or microphone input port of the mobile device **100** and delivers a signal to the mobile device **100**.

[0169] In another embodiment of the present invention, illustrated in FIG. **21**, a method is provided for transferring funds to and/or from the first party's financial account. The first party's financial account information is entered with a single initial entry to the payment service. Funds are transferred to and/or from the first party's financial account using the payment service. The funds can be transferred to the first party, or to second parties. The first party's financial account, including but not limited to a financial transaction card can be the destination of the funds. A simple swipe of the first party's financial transaction card can make the financial transaction card a funding source. The first party is either registered with the payment service, or becomes registered prior to the transfer of funds to and/or from the financial account using the payment service. For future uses of the first party's financial account, to transfer funds to and/or from the first party's financial account, the first party's financial account information need not be re-entered again with the payment service.

[0170] In another embodiment, funds are transferred from the first party's financial account to a second party using the payment service.

[0171] In one embodiment, the second party is already registered with the payment service or becomes registered with the payment service prior to the transfer of funds from the first party. In another embodiment, the second party is not registered with the payment service.

[0172] In one specific embodiment, funds are transferred to and/or from the first party's financial account using the payment service, e.g., to the first party or to a second party, where the financial account is a bank account, credit card, debit card, pre-paid card, a third party funding source and the like. In another specific embodiment,

[0173] In another embodiment, the first party's financial card is entered with a single initial entry to the payment service using a mobile device **100**. Again, for future uses of the first party's financial transaction card to transfer funds using the payment service to a second party, the first party's financial transaction card information need not be entered again.

[0174] Again, the entering of the financial card information to the payment service can be achieved by, swiping the financial transaction card through a slot of a card reader coupled to the mobile device **100**, through a slot of the mobile device **100**, with a touch of the financial transaction card to the mobile device **100**, typing in information at the mobile device **100**, with photos, selecting a card from an application on a mobile device **100**, from an on-line entity and the like.

[0175] In another embodiment of the present invention, a method of conducting a financial transaction includes the first party's financial account information being entered once, e.g., with a single initial entry to the payment service. For future

uses of the first party's financial account to transfer funds using the payment service to a second party, the first party's financial account information need not be entered again with the payment service. The second party's personal identifying information is entered. Funds are transferred from the first party's financial account to an account of the second party with the use of the payment service.

[0176] In another embodiment, the first party's financial transaction card information is entered with a single initial entry to the payment service. Again, for future uses of the first party's financial transaction card to transfer funds using the payment service to a second party, the first party's financial account information need not be entered again with the payment service. The second party's personal identifying information is entered and funds are transferred from the first party's financial account to an account of the second party with the use of the payment service.

[0177] In various embodiments, (i) the second party has an association with the payment system, (ii) the first party and the second party each have an association with the payment system, (iii) the first party has an association with the payment system but the second party does not.

[0178] In one embodiment, the first party uses a send money mode of the first party's mobile device 100. In various embodiments, the second party is (i) anybody on the first party's phone list, (ii) not on the first party's phone list but is added to the first party's phone list in response to a transaction, (iii) the second party has an association with a payment system or is a database of the payment system, (iv) the second party does not have an association but then has one in response to a text message or equivalent sent to the second party, and the like. In response to the text message, the second party either accepts or rejects.

[0179] In another embodiment, the first party's financial transaction card information is entered with a single initial entry to the payment service. Again, for future uses of the first party's financial transaction card information to transfer funds using the payment service to a second party, the first party's financial account information need not be entered again with the payment service. The second party's mobile device 100 number is entered in the first party's mobile device 100. In response, funds are transferred from the first party to an account of the second party.

[0180] The foregoing description of various embodiments of the claimed subject matter has been provided for the purposes of illustration and description. It is not intended to be exhaustive or to limit the claimed subject matter to the precise forms disclosed. Many modifications and variations will be apparent to the practitioner skilled in the art. Particularly, while the concept "component" is used in the embodiments of the systems and methods described above, it will be evident that such concept can be interchangeably used with equivalent concepts such as, class, method, type, interface, module, object model, and other suitable concepts. Embodiments were chosen and described in order to best describe the principles of the invention and its practical application, thereby enabling others skilled in the relevant art to understand the claimed subject matter, the various embodiments and with various modifications that are suited to the particular use contemplated.

What is claimed is:

1. A method of paying a second party, comprising: providing, for access by a first party, names of one or more qualified second parties, the qualified second parties

defined as second parties having an association with the payment service, and second parties that if they do not have an established association with the payment service, have an established association with the payment service prior to payment, the first party having an association with the payment service;

receiving second party identifying information into a payment service to create qualified second parties, the payment service being coupled to a first party's financial institution;

receiving, from the first party, an indication to open a tab with the qualified second party;

creating a tab that is a relationship between the first party the payment system and the qualified second party, the qualified second party being only able to receive funds from the first party's financial account when the first party's mobile device is within proximity, the tab being a relationship between the first party, the payment service and the qualified second party, wherein the qualified second party can engage in a financial transaction with the first party is within proximity; and

using a money mode of a first party's mobile device to send money to the second party.

2. The method of claim 1, wherein the money mode is used to send money to the second party.

3. The method of claim 1, further comprising:

establishing the first party's financial account by the first party.

4. The method of claim 1, wherein the first party's mobile device is configured to communicate with the payment service.

5. The method of claim 1, wherein the first party views the names of the one or more qualified second parties with the first party's mobile device.

6. The method of claim 1, wherein the first party enters financial account information with a single initial entry to the payment service and not requiring additional entries of the financial account information to the payment service for future financial transactions between the first party and any qualified second party when the same payment service is used.

7. The method of claim 1, wherein the financial account is selected from at least one of, a bank account, credit card, debit card, pre-paid card and a second party financial account.

8. The method of claim 7, wherein the financial account is selected by the first party by at least one of, use of a mobile device, from a bank terminal and done on-line,

9. The method of claim 1, wherein the first party's financial account is a financial transaction card, and the entering of the first party's financial card information is with a mobile device, wherein the entering is done by at least one of, swiping the financial transaction card through a slot of a card reader coupled to the mobile device, through a slot of the mobile device, by touch of the financial transaction card to the mobile device, by typing in information at the mobile device, with photos, by selecting a card from an application on a mobile device and from an on-line entity.

10. The method of claim 9, wherein the mobile device is a portable electronic device that includes at least one of, software, firmware, hardware, or a combination thereof, that is capable of at least receiving a signal, decoding the signal if required, exchange information with the first party's financial

account or payment network to verify the buyer and/or qualified second party's account information and conduct the transaction.

11. The method of claim **1**, wherein the qualified second party can see a list of first parties that have an association with the payment service.

12. The method of claim **1**, wherein the qualified second party can access a list of first parties with open tabs.

13. The method of claim **11**, wherein the list of first parties accessible by the qualified second party has first party identifying information.

14. The method of claim **13**, wherein the identifying information is anything that reliably identifies the first party.

15. The method of claim **13**, wherein the identifying information is selected from, names, photos, cell number, social security number, e-mail address and other personal identifying information for a first party.

16. A method of paying a second party, comprising:

accessing by a first party with a first party's mobile device, names of one or more qualified second parties, second parties having an association with the payment service, and second parties that if they do not have an established association with the payment service, have an established association with the payment service prior to payment, the first party having an association with the payment service; and

opening a tab by the first party that can be selected by the qualified second party at any geographic location of the first party's mobile device, the qualified second party being only able to charge a first party's financial transaction card when the first party's mobile device is within a defined geographic area, the tab is a relationship between the first party, the payment service and the qualified second party wherein the qualified second party can engage in a financial transaction with the first party is within the defined geographic area.

17. The method of claim **16**, wherein the mobile device is coupled to a card reader that includes an output jack adapted to be inserted at least one of the audio input port or microphone input port of the mobile device and delivers a signal to the mobile device; and

wherein a sampling rate of the signal at the audio input port or a line input port of the mobile device is at least 15 kHz.

18. The method of claim **17**, wherein a sampling rate of the signal at the audio input port or a line input port of the mobile device is at least 20 kHz.

19. The method of claim **17**, wherein a sampling rate of the signal at the audio input port or a line input port of the mobile device is at least 30 kHz.

20. The method of claim **17**, wherein a sampling rate of the signal at the audio input port or a line input port of the mobile device is at least 40 kHz.

21. The method of claim **16**, wherein the entering is done by at least one of, swiping the financial transaction card through a slot of a card reader coupled to the mobile device, through a slot of the mobile device, with a touch of the financial transaction card to the mobile device, by typing in information at the mobile device, with photos, by selecting a card from an application on a mobile device and from an on-line entity.

22. The method of claim **16**, wherein a confirmation of payment is made to the first party in response to a transfer of funds from the financial transaction card.

23. The method of claim **16**, wherein the financial transaction card is selected from at least one of, credit financial transaction card, debit financial transaction card, gift financial transaction card, fund transfer financial transaction card, and other types of payment authenticating piece capable of carrying out a transfer of funds.

24. The method of claim **17**, wherein the signal includes financial transaction data selected from at least one of, amount of the transaction, additional notes related to the transaction, authorization and/or signature of the first party.

25. The method of claim **17**, wherein the signal includes financial transaction card information selected from at least one of, one or more of financial transaction card number, financial transaction card holder's name, expiration date, and security code.

26. The method of claim **16**, wherein the mobile device is coupled to a card reader that includes a slot configured to reduce torque applied on the card reader when the financial transaction card is swiped through the slot in order to maintain accuracy and reliability of the data read by the card reader.

27. The method of claim **17**, wherein the signal produced is indicative of data stored on the magnetic stripe with minimum error via a single swipe of the financial transaction card.

28. The method of claim **17**, wherein acceptance and initialization of incoming signals from a swipe of the financial transaction card are done until the signals reach a steady state, the financial transaction card swipe is detected once steady state is reached, and peaks in the incoming signals are identified when the financial transaction card swipe is detected.

29. The method of claim **16**, wherein the financial transactions is completed without sharing financial transaction card information with the second party.

* * * * *