(19) DANMARK

(10) DK/EP 3180408 T3

(12) Oversættelse af europæisk patentskrift

Patent- og Varemærkestyrelsen

(51) Int.Cl.: *C 09 K 8/05 (2006.01)* *C 02 F 1/00 (2006.01)*

(45) Oversættelsen bekendtgjort den: **2019-03-25**

(80) Dato for Den Europæiske Patentmyndigheds bekendtgørelse om meddelelse af patentet: **2018-12-12**

(86) Europæisk ansøgning nr.: **15744840.8**

(86) Europæisk indleveringsdag: **2015-07-23**

(87) Den europæiske ansøgnings publiceringsdag: **2017-06-21**

(86) International ansøgning nr.: **US2015041662**

(87) Internationalt publikationsnr.: **WO2016025137**

(30) Prioritet: **2014-08-13 US 201462036912 P**
2015-01-15 US 201562103668 P
2015-06-26 US 201562185171 P

(84) Designerede stater: **AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**

(73) Patenthaver: **Albemarle Corporation, 451 Florida Street, Baton Rouge, LA 70801-1765, USA**

(72) Opfinder: **NALEPA, Christopher, J., 2340 Saint Andrews Avenue, Zachary, LA 70791, USA**
LIU, Yunqi, 3828 Twelve Oaks Avenue, Baton Rouge, LA 70820, USA
LAMBETH, Gregory, H., 18226 Creek Hollow Road, Baton Rouge, LA 70817, USA
GODAVARTHY, Srinivasa, S., 20051 Old Scenic Highway 1405, Zachary, LA 70791, USA
COPPOLA, Kevin, 437 LSU Avenue, Baton Rouge, LA 70808, USA
LOUWEN, Jacobus, N., Klipper 38, 1625 EK Hoorn, Holland

(74) Fuldmægtig i Danmark: **AWA Denmark A/S, Strandgade 56, 1401 København K, Danmark**

(54) Benævnelse: **VANDIGE BOREHULSFLUIDER MED HØJ DENSITET**

(56) Fremdragne publikationer:
WO-A1-99/23188
WO-A1-2004/050557
US-A1- 2005 101 490

DESCRIPTION

TECHNICAL FIELD

[0001] This invention relates to high density aqueous brines suitable for use as well fluids.

BACKGROUND

[0002] Conventional aqueous brine fluids, like calcium bromide, which can have densities up to about 14.2 pounds per gallon (1.70 kg/L), are widely used in oilfield production as clear completion fluids, drilling fluids, packer fluids, and so forth. For some wells, downhole pressures can reach 30,000 psi (2.1×10^8 Pa). Such high pressures occur downhole at least in the Gulf of Mexico, and temperatures at the mud line in the Gulf of Mexico can reach 40°F (4.4°C). As a general observation, each 10,000 pounds per square inch (6.9×10^7 Pa) increase in pressure can increase the crystallization temperature of an aqueous brine by about ten Fahrenheit degrees (about 5.6 Celsius degrees).

[0003] Typical aqueous brine fluids include calcium bromide having densities up to about 14.2 ppg (1.70 kg/L). A calcium bromide aqueous brine of about 14.2 ppg (1.70 kg/L) density has a true crystallization temperature of 10°F (-12.2°C). Calcium bromide aqueous brines having densities as high as 15 ppg (1.8 kg/L) can be made; however, these solutions have a true crystallization temperature of about 61°F (16.1°C). These higher density calcium bromide aqueous brines are not suitable for use in some downhole applications, such as conditions often found in the Gulf of Mexico, because precipitates will form in these higher density calcium bromide aqueous brines due to their relatively high true crystallization temperatures.

[0004] Zinc-containing calcium bromide aqueous brines of high density, *e.g.*, about 14.5 pounds per gallon (1.74 kg/L) or greater, are easily obtained by blending enough zinc bromide into the calcium bromide aqueous brine to reach the desired density value. Zinc-containing calcium bromide aqueous brines have true crystallization temperatures that are usually about 20°F (-6.7°C) or lower, making these zinc-containing brines more suitable for downhole use. However, inclusion of zinc necessitates increased reporting to government agencies for environmental reasons, resulting in more costly environmental mitigation measures. For example, zinc is regulated as a Priority Pollutant by the United States Environmental Protection Agency (EPA). Document WO2004/050557 discloses aqueous brines comprising $CaBr_2$ mixed with $CaCl_2$ and brines comprising mixtures of $CaBr_2$ and calcium bromide hydrates.

[0005] Hence, there is a need to develop high density aqueous brine fluids that are zinc-free, and that have true crystallization temperatures that are suitably low for downhole use.

SUMMARY OF THE INVENTION

[0006] This invention provides aqueous brines of high density and low crystallization temperature that are zinc-free. It has been discovered, for example, that a high density, zinc-free aqueous brine can be prepared from a combination of water and one or more inorganic bromide salts such as calcium bromide, manganese bromide ($MnBr_2$) tin bromide ($SnBr_2$ or $SnBr_4$), bismuth bromide, and/or indium bromide; calcium bromide is used in combination with one or more other water-soluble inorganic salts, selected from an inorganic bromide salt and manganese(II) nitrate; lithium bromide is used in combination with an alkali metal polytungstate salt; bismuth(III) bromide is used in combination with one or more other water-soluble inorganic salts, preferably selected from an inorganic bromide salt; when lithium bromide is present, calcium bromide is absent. Such brines can exhibit densities of 15.0 ppg (1.78 kg/L) or greater, and have crystallization temperatures of 20°F (-6.7°C) or less, often 10°F (-12.2°C) or less. These brines are suitable for use as wellbore fluids, such as completion fluids, especially clear completion fluids, drilling fluids, packer fluids, workover fluids, and other fluids that employ aqueous brines, particularly aqueous brines of high density. The aqueous brines of this invention are well suited for offshore completion activities involving high pressure reservoirs, such as oil and gas fields located in the Gulf of Mexico.

[0007] An embodiment of this invention is a zinc-free aqueous brine composition. The composition has a density of 14.3 pounds per gallon (1.71 kg/L) or more, and a true crystallization temperature of 20°F (-6.7°C) or less, preferably 10°F (-12.2°C) or less, and comprises water and one or more inorganic bromide salts, with the proviso that when calcium bromide is present, one or more other water-soluble inorganic salts is also present, selected from an inorganic bromide salt and manganese(II) nitrate; with the proviso that when bismuth(III) bromide is present, one or more other water-soluble inorganic salts is also present, preferably selected from an inorganic bromide salt, with the proviso that when lithium bromide is present, calcium bromide is absent, and with the proviso that for true crystallization temperatures of -12.2°C (10°F) or less, when manganese(II) bromide is present, one or more other water-soluble inorganic salts are also present. Processes for forming these aqueous brine compositions are also provided.

[0008] These and other embodiments and features of this invention will be still further apparent from the ensuing description and appended claims.

FURTHER DETAILED DESCRIPTION OF THE INVENTION

[0009] As used throughout this document, the phrase "zinc-free" means that except for adventitious impurities, neither zinc nor zinc compounds are present in, or introduced into, the compositions or processes of this invention. Generally, there is 25 ppm or less of zinc present in the aqueous brines of this invention.

[0010] The term ppm means parts per million (wt/wt), as used throughout this document, unless specifically stated otherwise herein. Throughout this document, both "ppg" and "1b/gal" are abbreviations for pounds per gallon.

[0011] The abbreviation "TCT" stands for true crystallization temperature (or true crystallization point) as used throughout this document. True crystallization temperature is the temperature at which precipitate begins to form in the absence of supercooling. A method for determining true crystallization temperature is described hereinbelow.

[0012] The phrases "inorganic bromide salt", "inorganic bromide", and "bromide salt" are used interchangeably throughout this document.

[0013] Solutions comprising one or more inorganic bromide salts and manganese(II) nitrate or a water-soluble polytungstate are aqueous brines of the present invention.

[0014] Because the compositions of the invention can be used as clear completion fluids, precipitates and/or cloudiness in the aqueous brines of the invention are undesirable. To be suitable for use as well fluids, the aqueous brines of the invention have little or no precipitate formation over time (*e.g.*, one week) at ambient temperature and pressure (*e.g.*, 17 to 25°C and 14 to 15 psi) or at elevated temperature (*e.g.*, 60°C) and ambient pressure.

[0015] The compositions of the invention are aqueous brine solutions comprising one or more inorganic bromide salts other than zinc bromide. Although it is convenient to refer to compounds of bromide salts and to metal cations and bromide anions, the species in the compositions may be complexed with water, or in some other form. Similarly, the other water-soluble inorganic salts which are comprised in the aqueous brine solutions of the invention that are referred to as salts or their respective cations and/or anions may be complexed with water, or in some other form.

[0016] In the practice of this invention, the inorganic bromide salts are selected from calcium bromide, manganese(II) bromide, tin(II) bromide, tin(IV) bromide, bismuth(III) bromide, indium(III) bromide, and mixtures of any two or more of these; when calcium bromide is used, one or more other water-soluble inorganic salts is also used, and is selected from an inorganic bromide salt, manganese(II) nitrate; when bismuth(III) bromide is used, one or more other water-soluble inorganic salts is also used, and preferably is selected from an inorganic bromide salt. Manganese(II) bromide is preferably used in combination with one or more other water-soluble inorganic salts, especially when a brine with a true crystallization temperature of 10°F (-12.2°C) or less is needed; in preferred embodiments, the other inorganic salt is preferably selected from an inorganic bromide salt, manganese(II) nitrate, and a water-soluble polytungstate salt, more preferably an inorganic bromide, which inorganic bromide is preferably calcium bromide or a combination of calcium bromide and one or more other inorganic bromide salts. In some embodiments, the inorganic bromide salt is lithium bromide in combination with an alkali metal polytungstate salt. Preferred inorganic bromide salts when only one bromide salt is present include tin(IV) bromide and indium(III) bromide, especially

tin(IV) bromide. When two bromide salts are used, they are preferably a combination of calcium bromide and manganese(II) bromide; when three bromide salts are used, they are preferably a combination of calcium bromide, manganese(II) bromide and tin(IV) bromide, or a combination of calcium bromide, manganese(II) bromide, and bismuth(III) bromide.

[0017] In some preferred embodiments, the inorganic bromide salt is manganese(II) bromide, tin(II) bromide, tin(IV) bromide, indium(III) bromide, or a mixture of any two or more of these. In other preferred embodiments, the inorganic bromide salt is a combination of calcium bromide and one or more inorganic bromide salts selected from manganese(II) bromide, tin(II) bromide, tin(IV) bromide, bismuth(III) bromide, indium(III) bromide, or a mixture of any two or more of these. In another preferred embodiment, the inorganic bromide salt is a combination of bismuth(III) bromide and one or more inorganic bromide salts selected from manganese(II) bromide, tin(II) bromide, tin(IV) bromide, indium(III) bromide, or a mixture of any two or more of these. In still another preferred embodiment, one inorganic bromide salt is present, and the inorganic bromide salt is tin(IV) bromide or indium(III) bromide.

[0018] When the other water-soluble inorganic salt is a water-soluble polytungstate salt, it can be an alkali metal polytungstate, an alkaline earth metal polytungstate, manganese polytungstate, and the like. Alkali metal polytungstates include lithium polytungstate, lithium metatungstate, sodium polytungstate, sodium metatungstate, potassium polytungstate, potassium metatungstate, and the like; preferred alkali metal polytungstates include sodium metatungstate and potassium metatungstate. Alkaline earth metal polytungstates include calcium polytungstate, magnesium polytungstate, and strontium polytungstate; preferred alkaline earth polytungstates include calcium polytungstate. The term "metatungstate" often refers to a hydrated form of a polytungstate salt.

[0019] For the combination of lithium bromide with an alkali metal polytungstate salt, the alkali metal polytungstate salts include lithium polytungstate, lithium metatungstate, sodium polytungstate, sodium metatungstate, potassium polytungstate, potassium metatungstate, and the like; preferred alkali metal polytungstates include lithium metatungstate and sodium metatungstate.

[0020] When the inorganic salts of the aqueous brine are comprised only of inorganic bromide salts, the total amount of inorganic bromide salt(s) in the aqueous brine is typically in the range of 40 wt% to 75 wt%, relative to the total weight of the composition. Preferred total amounts of inorganic bromide salt(s) are from 45 wt% to 75 wt%, relative to the total weight of the composition.

[0021] In some embodiments, the total amount of inorganic bromide salt(s) in the aqueous brine is preferably in the range of 45 wt% to 65 wt%, more preferably 55 wt% to 65 wt%, relative to the total weight of the composition, especially when calcium bromide and one other inorganic bromide salt are used, and the other inorganic bromide salt is selected from tin(II) bromide, tin(IV) bromide, bismuth(III) bromide, and indium(III) bromide.

[0022] In other embodiments, the total amount of inorganic bromide salt(s) in the aqueous brine is preferably in the range of 55 to 70 wt%, relative to the total weight of the composition, especially when the inorganic bromide salts are calcium bromide and two other inorganic bromide salts, which other inorganic bromide salts are a combination of manganese(II) bromide and one other metal bromide selected from tin(II) bromide, tin(IV) bromide, bismuth(III) bromide, and indium(III) bromide.

[0023] When the inorganic salts of the aqueous brine are comprised of one or more inorganic bromide salts and one or more other water-soluble inorganic salts, the total amount of inorganic bromide salt(s) in the aqueous brine is typically in the range of 15 wt% to 60 wt%, preferably 20 wt% to 55 wt%, more preferably 25 wt% to 55 wt%, relative to the total weight of the composition. The total amount of the other water-soluble inorganic salt(s) varies, depending on the identity of the inorganic salt. For manganese(II) nitrate, the total amount in the aqueous brine is usually in the range of a 5 wt% to 75 wt%, sometimes preferably 35 wt% to 70 wt%, sometimes preferably 10 wt% to 50 wt%, relative to the total weight of the composition; for water-soluble polytungstate salts, the total amount in the aqueous brine is typically in the range of 5 wt% to 40 wt%, preferably 10 wt% to 35 wt%, relative to the total weight of the composition.

[0024] The total amount of inorganic salts in an aqueous brine comprised of one or more inorganic bromide salts and one or more other water-soluble inorganic salts is in the range of 60 wt% to a 85 wt%, sometimes preferably in the range of 65 wt% to 85 wt%, relative to the total weight of the composition when the other water-soluble inorganic salt is manganese(II) nitrate. When the other water-soluble inorganic salt is a water-soluble polytungstate, the total amount of inorganic salts in an aqueous brine comprised of one or more inorganic bromide salts and one or more other water-soluble inorganic salts is in the range of 50 wt% to 75 wt%, preferably in the range of 55 wt% to 70 wt%, relative to the total weight of the composition.

[0025] Compositions of the invention have densities of 14.3 pounds per gallon (1.71 kg/L) or more. Preferably, the compositions have densities of 14.6 ppg (1.75 kg/L) or more. In some embodiments, the compositions preferably have densities of 14.8 ppg (1.77 kg/L) or more, or preferably a 15.0 ppg (1.80 kg/L) or more, or more preferably a 15.1 ppg (1.81 kg/L) or more. In other embodiments, especially when the inorganic bromide salt is calcium bromide and one or more inorganic bromide salts selected from tin(IV) bromide, bismuth(III) bromide, or indium(III) bromide, the compositions preferably have densities of 16.0 ppg (1.92 kg/L) or more.

[0026] Density ranges for the compositions of this invention are preferably 14.3 ppg (1.71 kg/L) to 19.0 ppg (2.28 kg/L), more preferably 14.6 ppg (1.75 kg/L) to 18.0 ppg (2.16 kg/L). In some embodiments, preferred densities are 14.8 ppg (1.77 kg/L) to 16.0 ppg (1.92 kg/L),more preferably 15.0 ppg (1.80 kg/L) to 16.0 ppg (1.92 kg/L), and still more preferably 15.1 ppg (1.81 kg/L) to 15.6 ppg (1.87 kg/L). In other embodiments, preferred densities are 14.6 ppg (1.75 kg/L) to 15.0 ppg (1.80 kg/L), more preferably 14.6 to about 14.8 ppg (1.77 kg/L). In still other embodiments, preferred densities are 15.0 ppg (1.80 kg/L) to 18.0 ppg (2.16 kg/L), more

preferably 15.5 ppg (1.86 kg/L) to 17.75 ppg (2.13 kg/L). In yet other embodiments, especially when the inorganic bromide salt is calcium bromide and one other inorganic bromide salt selected from tin(IV) bromide, bismuth(III) bromide, or indium(III) bromide, preferred densities are 16.0 ppg (1.92 kg/L) to 17.5 ppg (2.10 kg/L), more preferably 16.2 ppg (1.94 kg/L) to 17.2 ppg (2.06 kg/L). In another embodiment, especially when the inorganic bromide salt is calcium bromide and manganese(II) nitrate is the other water-soluble inorganic salt, preferred densities are 14.5 ppg (1.74 kg/L) to 16.0 ppg (1.92 kg/L). In yet another embodiment, preferred densities are 14.5 ppg (1.74 kg/L) to 17.5 ppg (2.10 kg/L), more preferably 14.5 ppg (1.74 kg/L) to 16.5 ppg (1.98 kg/L), especially when the inorganic bromide salt is calcium bromide or manganese(II) bromide and the other water-soluble inorganic salt is a water-soluble polytungstate salt, or when the inorganic bromide salt is lithium bromide in combination with an alkali metal polytungstate salt.

[0027] For the compositions of the invention, the true crystallization temperatures are generally 20°F (-6.7°C) or less, preferably 10°F (-12.2°C) or less, more preferably 8°F (-13.3°C) or less, and still more preferably 7.5°F (-13.6°C) or less.

[0028] Aqueous brine compositions of the invention have preferred pH values are in the range of 0 to 7; more preferred are pH values in the range of 1 to 6; still more preferred are pH values in the range of 1.5 to 5, especially 2.5 to 5. Even more preferred are pH values in the range of 3 to 4.

[0029] As is known in the art, it is often useful to include one or more optional additives in an aqueous brine, and the inclusion of such additives is within the scope of this invention. Optional additives can include, for example, corrosion inhibitors, lubricants, pH control additives, surfactants, and/or solvents. Glycerol and formic acid are preferred optional additives.

[0030] In some preferred zinc-free aqueous brine compositions of the invention, only water, inorganic bromide salts, one or more other water-soluble inorganic salts, and species derived from these components are present in the composition; in some of these preferred embodiments, one of the inorganic bromide salts is calcium bromide. In some of these preferred embodiments, the other water-soluble inorganic salts are selected from manganese(II) nitrate, and a water-soluble polytungstate salt, and more preferably, one of the inorganic bromide salts is calcium bromide.

[0031] In other preferred zinc-free aqueous brine compositions of the invention, only water, inorganic bromide salts, and species derived from these components are present in the composition; in some of these preferred embodiments, one of the inorganic bromide salts is calcium bromide. In other preferred zinc-free aqueous brine compositions of the invention, only water, tin(IV) bromide, and species derived from these components are present in the composition.

[0032] Preferred compositions of this invention include zinc-free aqueous brines which comprise water; calcium bromide; and one or more other inorganic bromide salts, preferably

selected from manganese(II) bromide, tin(II) bromide, tin(IV) bromide, bismuth(III) bromide, indium(III) bromide, and mixtures of any two or more of these; wherein the composition has a density of 14.3 ppg (1.71 kg/L) or more, preferably 14.6 ppg (1.75 kg/L) or more, more preferably 15.0 ppg (1.80 kg/L) or more; and a true crystallization temperature of 20°F (-6.7°C) or less, preferably 10°F (-12.2°C) or less, more preferably 8°F (-13.3°C) or less. In these calcium bromide-containing compositions, the inorganic bromide salt(s) other than calcium bromide is preferably in an amount of 3.0 wt% to 40 wt%, relative to the total weight of the composition; preferably, these calcium bromide-containing compositions have a pH in the range of a 0 to 8, more preferably 1 to 7.

[0033] Additional preferred compositions of this invention include zinc-free aqueous brines which comprise water and one inorganic bromide salt selected from tin(IV) bromide and indium(III) bromide; more preferably tin(IV) bromide; wherein the composition has a density of 15.0 ppg (1.80 kg/L) or more, preferably 16.0 ppg (1.92 kg/L) or more, more preferably 18.0 ppg (2.16 kg/L) or more.

[0034] In a preferred embodiment, the inorganic bromide salts are calcium bromide and manganese(II) bromide, and the composition has a density of 14.6 ppg (1.75 kg/L) or more and a true crystallization temperature at atmospheric pressure of 20°F (-6.7°C) or less, preferably 10°F (-12.2°C) or less. Particularly preferred are compositions containing calcium bromide and manganese(II) bromide which have densities of 15 1b/gal (1.8 kg/L) or more, and true crystallization temperatures at atmospheric pressure of 8°F (-13.3°C) or less. Preferably, these compositions containing calcium bromide and manganese(II) bromide have pH values in the range of 2.5 to 5, more preferably 3 to 4.

[0035] In some preferred embodiments, the inorganic bromide salts are calcium bromide and manganese(II) bromide in combination with another inorganic bromide salt selected from tin(IV) bromide, tin(II) bromide, bismuth(III) bromide, and indium(III) bromide.

[0036] In another preferred embodiment, the inorganic bromide salts are calcium bromide, manganese(II) bromide, and tin(IV) bromide, and the composition has a density of 15.0 ppg (1.80 kg/L) or more. Particularly preferred compositions containing calcium bromide, manganese(II) bromide, and tin(IV) bromide as the inorganic bromide salts have densities of 16.0 ppg (1.92 kg/L) or more, more preferably densities of 16.5 ppg (1.98 kg/L) or more.

[0037] In still another preferred embodiment, the inorganic bromide salts are calcium bromide, manganese(II) bromide, and bismuth(III) bromide, and the composition has a density of 16.0 ppg (1.92 kg/L) or more. Particularly preferred compositions containing calcium bromide, manganese(II) bromide, and bismuth(III) bromide as the inorganic bromide salts have densities of 16.3 ppg (1.95 kg/L) or more.

[0038] In another preferred embodiment, the inorganic bromide salt is calcium bromide, and manganese(II) nitrate is present; preferably, the composition has a density of 14.5 ppg (1.74 kg/L) or more, more preferably 14.8 ppg (1.77 kg/L) or more.

[0039] In yet another preferred embodiment, the inorganic bromide salt is calcium bromide or manganese(II) bromide, and a water-soluble polytungstate, preferably an alkali metal polytungstate, more preferably sodium metatungstate, is present; more preferably, the composition has a density of 14.5 ppg (1.74 kg/L) or more, more preferably 14.8 ppg (1.77 kg/L) or more,

[0040] In a further preferred embodiment, the inorganic bromide salt is lithium bromide in combination with an alkali metal polytungstate salt; more preferably the alkali metal polytungstate salt is lithium metatungstate or sodium metatungstate; more preferably, the composition has a density of 14.5 ppg (1.74 kg/L) or more, more preferably 14.8 ppg (1.77 kg/L) or more.

[0041] Zinc-free aqueous brines having a density of 14.3 pounds per gallon (1.71 kg/L) or more and a true crystallization temperature of 20°F (-6.7°C) or less are formed by processes which comprise combining, in any order, components comprising water and one or more inorganic bromide salts, with the proviso that when calcium bromide is present, one or more other water-soluble inorganic salts is also present, and is selected from an inorganic bromide salt, manganese(II) nitrate; with the proviso that when lithium bromide is present, calcium bromide is absent; with the proviso that when bismuth(III) bromide is present, one or more other water-soluble inorganic salts are also present; and with the proviso that, for a true crystallization temperature of 10°F or less, when manganese(II) bromide is present, one or more other water-soluble inorganic salts are also present.

[0042] The inorganic bromide salt(s) include calcium bromide, manganese(II) bromide, tin(II) bromide, tin(IV) bromide, bismuth(III) bromide, indium(III) bromide, and mixtures of any two or more of these. When calcium bromide is used, one or more other water-soluble inorganic salts, selected from an inorganic bromide salt, manganese(II) nitrate, is also used. When bismuth(III) bromide is used, one or more other water-soluble inorganic salts, preferably selected from an inorganic bromide salt, is also used. When lithium bromide is used, an alkali metal polytungstate salt is also used. Manganese(II) bromide is preferably used in combination with one or more other water-soluble inorganic salts, especially when a brine with a true crystallization temperature of 10°F (-12.2°C) or less is needed; in preferred embodiments, the other inorganic salt is an inorganic bromide, manganese(II) nitrate, or a water-soluble polytungstate salt; the inorganic bromide is preferably calcium bromide or a combination of calcium bromide and one or more other inorganic bromide salts. When one inorganic bromide salt is used, it is preferably tin(IV) bromide or indium(III) bromide, more preferably, tin(IV) bromide. Manganese(II) bromide is preferred as an inorganic bromide salt to use with calcium bromide, especially when calcium bromide and one other bromide salt are present; when two bromide salts are used with calcium bromide, they are preferably a combination of manganese(II) bromide and tin(IV) bromide, or a combination of manganese(II) bromide and bismuth(III) bromide.

[0043] The combining of the water and inorganic bromide salt(s), and, when used, other

water-soluble inorganic salts can be conducted in any manner used to mix inorganic salts and water. Normally and preferably, concentrated solutions of the inorganic salts can be mixed with addition or removal of water to provide the composition desired. Alternatively, the inorganic bromide salt(s) are added to the water. When there are two or more inorganic bromide salts, the inorganic bromide salts can be mixed with a portion of water before being combined with each other and, if needed, more water. When cofeeding the components or mixtures thereof, there is no requirement that the feeds be entirely coextensive in time, and each feed may be interrupted at one or more points during the cofeeding. Another preferred way of operating when there are two or more inorganic bromide salts is to introduce one or more of the inorganic bromide salt(s) as a solid into a preformed aqueous solution of the other inorganic bromide salts(s). A combination of methods can be used as desired.

[0044] One or more of the inorganic bromide salts can be formed during the process. Formation of an inorganic bromide salt during the process can be used to form a portion of, or all of, the inorganic bromide salt. When an inorganic bromide salt is formed during the process, it can be formed in water before some or all of any other inorganic bromide(s) are introduced, or, preferably, in an aqueous solution of the other inorganic bromide(s).

[0045] An inorganic bromide salt can be formed during the process in various ways. In some embodiments, an inorganic bromide salt can be formed from the metal in elemental form and elemental bromine (Br_2), especially where the metal is calcium, manganese, tin, bismuth, and/or indium. For example, manganese metal and elemental bromine can be used to form manganese(II) bromide. In other embodiments, an inorganic bromide salt can be formed from an inorganic oxide and/or hydroxide and a bromide source which is hydrogen bromide and/or elemental bromine. In preferred embodiments, the inorganic bromide salt is formed from (i) an inorganic oxide and/or hydroxide and (ii) hydrogen bromide and/or bromine.

[0046] Inorganic oxides and/or hydroxides that can be used to form an inorganic bromide salt during the process include one or more of calcium oxide and/or hydroxide, manganese oxides and/or hydroxides, tin(II) oxide and/or hydroxide, tin(IV) oxide and/or hydroxide, bismuth(III) oxide and/or hydroxide, indium(III) oxide and/or hydroxide, or mixtures of any two or more of the foregoing. Preferred inorganic oxides and hydroxides include one or more manganese oxides and/or hydroxides, tin(IV) oxide and/or hydroxide, and bismuth(III) oxide and/or hydroxide. Of the manganese oxides and/or hydroxides, more preferred are manganese(II) oxide, manganese(II) hydroxide, and mixtures thereof; even more preferred is manganese(II) oxide.

[0047] When one or more inorganic oxides and/or hydroxides are used, the bromide source for forming an inorganic bromide during the process is hydrogen bromide, bromine, or a mixture thereof. Preferably, the bromide source is hydrogen bromide or a mixture of hydrogen bromide and bromine; more preferred is a mixture of hydrogen bromide and bromine. In these mixtures, the hydrogen bromide and bromine can be in any desired proportions from 100% hydrogen bromide to 100% Br_2, or at any relative proportion therebetween. For convenience, it may be preferable to employ a mixture in which hydrogen bromide is present. When bromine

(elemental bromine, Br_2) is used, either alone or in admixture with hydrogen bromide, a reducing agent is also present, and is typically methanol, ethanol, formic acid, hydrazine.

[0048] For the combination of lithium bromide and an alkali metal polytungstate salt, the lithium bromide can be made by any of the methods described above, including from lithium metal and elemental bromine, and from lithium oxide and/or hydroxide and a bromide source (typically hydrogen bromide or elemental bromine).

[0049] In some preferred processes, the inorganic bromide salt is manganese(II) bromide, tin(II) bromide, tin(IV) bromide, indium(III) bromide, or a mixture of any two or more of these. In other preferred processes, the inorganic bromide salt is a combination of calcium bromide and manganese(II) bromide, tin(II) bromide, tin(IV) bromide, bismuth(III) bromide, indium(III) bromide, or a mixture of any two or more of these. In another preferred embodiment, a combination of bismuth(III) bromide and manganese(II) bromide, tin(II) bromide, tin(IV) bromide, indium(III) bromide, or a mixture of any two or more of these, is used. In still another embodiment, only one inorganic bromide salt is used, and the inorganic bromide salt is tin(IV) bromide or indium(III) bromide.

[0050] When one inorganic bromide salt is used to form a zinc-free aqueous brine of the invention, the inorganic bromide is typically in an amount in the range of 40 wt% to 75 wt%, preferably 45 wt% to 75 wt%, relative to the total weight of the aqueous brine composition being formed. When there are two or more inorganic bromide salts, this range refers to the combined weight of all of the inorganic bromide salts. When the composition contains calcium bromide, preferred amounts of inorganic bromide salts other than the calcium bromide in the aqueous brine are from 5 wt% to 35 wt%; more preferably 6 wt% to 30 wt%, relative to the total weight of the composition.

[0051] When an inorganic bromide and one or more other water-soluble inorganic salts are used to form a zinc-free aqueous brine of the invention, especially manganese(II) nitrate or a water-soluble polytungstate salt, the inorganic bromide is typically 15 wt% to 60 wt%, preferably 20 wt% to 55 wt%, more preferably 25 wt% to 55 wt%, relative to the total weight of the composition. When the other water-soluble inorganic salt is manganese(II) nitrate, the manganese(II) nitrate is generally in the range of 5 wt% to 75 wt%, sometimes preferably 35 wt% to 70 wt%, sometimes preferably 10 wt% to 50 wt%, relative to the total weight of the composition. When the other water-soluble inorganic salt is a water-soluble polytungstate salt, the polytungstate salt is usually in the range of wt% to 40 wt%, preferably 10 wt% to 35 wt%, relative to the total weight of the composition.

[0052] When an inorganic bromide salt is formed during the process, the amount of that inorganic bromide salt is calculated as if the inorganic bromide salt had been added. Amounts of inorganic bromide salt will vary, depending to some extent on the amount(s) of other inorganic bromide(s), because less inorganic bromide salt is needed to reach a particular density value as the amount of other inorganic bromide salt(s) increases.

[0053] In some embodiments, when forming a zinc-free aqueous brine of the invention, the amount of inorganic bromide salt in the aqueous brine is preferably in the range of 45 wt% to 65 wt%, more preferably 55 wt% to 65 wt%, relative to the total weight of the composition, especially when calcium bromide and one other inorganic bromide salt are used, and the other inorganic bromide salt is selected from tin(II) bromide, tin(IV) bromide, bismuth(III) bromide, and indium(III) bromide.

[0054] In other embodiments, when forming a zinc-free aqueous brine of the invention, the amount of inorganic bromide salt in the aqueous brine is preferably in the range of 55 to 70 wt%, relative to the total weight of the composition, especially when the inorganic bromide salts are calcium bromide and two other inorganic bromide salts, which are a combination of manganese(II) bromide and another metal bromide selected from tin(II) bromide, tin(IV) bromide, bismuth(III) bromide, and indium(III) bromide.

[0055] The amount of water and/or the inorganic bromide salt(s) and/or other water-soluble inorganic salt(s) used to form the aqueous brines of the invention can be adjusted to reach the desired density. Removal of water, for example by heating and/or applying a vacuum, can be employed to reach the desired density for the zinc-free aqueous brine composition.

[0056] The zinc-free aqueous brine can be heated during combination of the components and/or after the components are combined, to ensure dissolution of the components. In this optional heating step, the mixture being formed during the process and/or the aqueous brine formed by the process is heated at a temperature of 40°C or above to form a heated solution. Elevated temperatures can increase the rate of dissolution of the inorganic bromide salt(s). Such elevated temperatures for heating the aqueous brine are typically in the range of 40°C up to the boiling point of the mixture, preferably 45°C to 100°C, more preferably 50°C to 95°C, and still more preferably 60°C to 95°C. In some embodiments, it is preferred to operate under increased pressure, typically 20 psi to 40 psi ($1.4x10^5$ to $2.77x10^5$ Pa), because higher temperatures can be achieved. Upon cooling the aqueous brine to ambient temperatures (typically 15°C to 25°C, often 17°C to 23°C), the inorganic bromide salt(s) usually remain dissolved.

[0057] Optionally, the pH of the zinc-free aqueous brine can be adjusted by adding an acid or a base as needed. Suitable acids include mineral acids and water-soluble organic acids; suitable bases are usually inorganic oxides and/or hydroxides. In some instances, upon introduction of an inorganic oxide and/or hydroxide to the zinc-free aqueous brine, a precipitate may form; after filtration, a clear aqueous brine is obtained.

[0058] For pH adjustment, suitable inorganic oxides and hydroxides which include oxides and hydroxides of manganese(II), tin(II), tin(IV), bismuth(III), indium(III), alkali metals including lithium, sodium, and potassium, alkaline earth metals including calcium and magnesium, and mixtures of any of these oxides and/or hydroxides, may be used. Preferred inorganic oxides and hydroxides include those of manganese, tin, calcium, and sodium. In some preferred embodiments, the inorganic oxide(s) and/or hydroxide(s) has one or more of the same cations

already present in the aqueous brine. In some embodiments, a small amount of precipitate forms when an inorganic oxide and/or hydroxide is used to increase the pH. Once the precipitate has been removed, *e.g.*, by filtration, additional precipitate formation usually does not occur.

[0059] Acids suitable for pH adjustment include mineral acids and organic acids that are water-soluble. Suitable mineral acids include hydrogen chloride, hydrogen bromide, hydrogen iodide, nitric acid, sulfuric acid, phosphoric acid, and the like. Suitable organic acids include formic acid, tartaric acid, citric acid, gluconic acid, lactic acid, malic acid, maleic acid, malonic acid, oxalic acid, and the like. Mixtures of any two or more acids can be employed if desired. Hydrogen bromide is a preferred acid, and can be used in gaseous form, or, preferably, as an aqueous solution.

[0060] Any optional additives that are included in the aqueous brines can be introduced in any of the ways that the inorganic bromide salt(s) are introduced, or in any other convenient manner.

[0061] Under storage conditions, aqueous brines having a density of 15.0 ppg (1.80 kg/L) or greater often form a precipitate. Stabilization of these dense aqueous brines can be achieved by adjusting the pH of the aqueous brine. Adjustment of the pH value is accomplished by adding an inorganic hydroxide and/or oxide and/or by adding an acid, preferably hydrogen bromide, usually to a value in the range of 1 to 7, more preferably 1 to 6; still more preferably 2.5 to 5.

[0062] Small amounts of fine precipitates are sometimes formed in aqueous brine compositions of the invention which have a pH of 3.5 or higher, and in which the inorganic bromide salts are calcium bromide and manganese(II) bromide. In particular, it has been discovered that decreasing the pH of the aqueous brine compositions may minimize or prevent further precipitate formation in the aqueous brine. In such instances, the pH can be adjusted as described above.

[0063] In some embodiments of this invention, the presence of glycerol and/or formic acid in the composition is preferred. Glycerol can be introduced at any point during the process of the invention by any convenient method for combining the glycerol and/or formic acid with the components of the process. A preferred method for inclusion of glycerol and/or formic acid is by adding glycerol and/or formic acid to the aqueous brine. When present, the amount of glycerol is preferably 3 wt% to 15 wt%, more preferably about 5 wt% to 10 wt%, relative to the total weight of the composition. The amount of formic acid, when present, is typically 500 ppm to 5000 ppm, preferably 750 ppm to 3000 ppm, more preferably 1000 ppm to 2500 ppm, relative to the total weight of the composition. It has been observed that the presence of glycerol in manganese-containing aqueous brines of the invention may prevent or minimize precipitation in the aqueous brines, especially at pH values of 3.5 or above.

[0064] In some preferred processes of this invention, only water, one or more inorganic

bromide salts, and one or more other water-soluble inorganic salts are combined to form the zinc-free aqueous brines of this invention. In some of these preferred embodiments, the other water-soluble inorganic salts are selected from manganese(II) nitrate and a water-soluble polytungstate salt.

[0065] In some preferred processes of this invention, only water, one or more inorganic bromide salts, one or more inorganic oxides and/or hydroxides, and/or hydrogen bromide and/or bromine are combined to form the zinc-free aqueous brines of this invention.

[0066] Preferred processes of this invention comprise combining, in any order, components comprising water and one or more inorganic bromide salts preferably selected from the group consisting of calcium bromide, manganese(II) bromide, tin(II) bromide, tin(IV) bromide, bismuth(III) bromide, indium(III) bromide, and mixtures of any two or more of these; when calcium bromide is present, one or more other water-soluble inorganic salts, selected from an inorganic bromide salt, manganese(II) nitrate, is also present. When bismuth(III) bromide is present, one or more other water-soluble inorganic salts, preferably selected from an inorganic bromide salt, is also present. Lithium bromide is used in combination with one or more alkali metal polytungstate salts. Manganese(II) bromide is preferably used in combination with one or more other water-soluble inorganic salts preferably selected from an inorganic bromide salt, manganese(II) nitrate, and a water-soluble polytungstate salt; in preferred embodiments, the other inorganic salt is a bromide, and is calcium bromide or a combination of calcium bromide and one or more other inorganic bromide salts. When only one bromide salt is present, preferred inorganic bromide salts include tin(IV) bromide and indium(III) bromide, especially tin(IV) bromide. When two bromide salts are used, they are preferably a combination of calcium bromide and manganese(II) bromide; when three bromide salts are used, they are preferably a combination of calcium bromide, manganese(II) bromide and tin(IV) bromide, or a combination of calcium bromide, manganese(II) bromide, and bismuth(III) bromide.

[0067] The composition formed has a density of 14.3 ppg (1.71 kg/L) or more, preferably of 14.6 ppg (1.75 kg/L) or more; and a true crystallization temperature of 20°F (-6.7°C) or less, preferably 1.0°F (-12.2°C) or less. An aqueous brine in which the only salt is manganese(II) bromide at a density of 15.0 ppg (1.80 kg/L) has a true crystallization temperature of -10.3°C. In some embodiments, the compositions formed preferably have densities of 14.8 ppg (1.77 kg/L) or more, or preferably 15.0 ppg (1.80 kg/L) or more, or more preferably 15.1 ppg (1.81 kg/L) or more. In other embodiments, especially when the inorganic bromide salts are calcium bromide and another inorganic bromide selected from tin(IV) bromide, bismuth(III) bromide, or indium(III) bromide, the compositions preferably have densities of 16.0 ppg (1.92 kg/L) or more. When in combination with calcium bromide, the other inorganic bromide salt is usually in an amount of 3.0 wt% to 45 wt%, preferably 5 wt% to 40 wt%; more preferably 6 wt% to 35 wt%, relative to the total weight of the composition formed. When calcium bromide is used in combination with manganese(II) nitrate, the manganese(II) nitrate is usually in the range of 30 wt% to 75 wt%, sometimes preferably 35 wt% to 70 wt%, sometimes preferably 10 wt% to 50 wt%, relative to the total weight of the composition formed. When calcium bromide or manganese(II) bromide is used in combination with a water-soluble polytungstate salt, the

water-soluble polytungstate salt is typically in the range of 5 wt% to 40 wt%, preferably 10 wt% to 35 wt%, relative to the total weight of the composition formed. When a combination of lithium bromide and one or more alkali metal polytungstate salts is used, the alkali metal polytungstate salt is generally in the range of 5 wt% to 40 wt%, preferably 10 wt% to 35 wt%, relative to the total weight of the composition formed.

[0068] In some preferred processes, the water, inorganic bromide salt(s) and, when used, one or more other water-soluble inorganic salts are combined to form an aqueous solution. In other preferred processes, one or more inorganic bromide salts are formed during the process from hydrogen bromide and/or bromine and an inorganic oxide and/or hydroxide. The inorganic oxide and/or hydroxide is preferably selected from oxides and/or hydroxides of calcium, manganese(II), tin(II), tin(IV), bismuth(III), indium(III), and mixtures of any two or more of the foregoing. When oxides and/or hydroxides of calcium are used, one or more other water-soluble inorganic salts, preferably selected from an inorganic bromide salt, manganese(II) nitrate, and a water-soluble polytungstate salt, are also included. When oxides and/or hydroxides of manganese are used, they are preferably used in combination with one or more other water-soluble inorganic salts preferably selected from an inorganic bromide salt, manganese(II) nitrate, and a water-soluble polytungstate salt. For lithium bromide in combination with a water-soluble polytungstate salt, lithium bromide can be formed from lithium oxide and/or hydroxide with hydrogen bromide and/or bromine.

[0069] Preferred combinations of inorganic oxides and/or hydroxides are oxides and/or hydroxides of manganese(II), tin(II), tin(IV), indium(III), and/or bismuth(III), in combination with calcium bromide or oxides and/or hydroxides of calcium. Also preferred as the inorganic oxides and/or hydroxides are combinations of calcium bromide or oxides and/or hydroxides of calcium with oxides and/or hydroxides of manganese(II); and/or tin(IV); combinations of calcium bromide or oxides and/or hydroxides of calcium with oxides and/or hydroxides of manganese(II) and oxides and/or hydroxides of tin(IV), or a combination of calcium bromide with oxides and/or hydroxides of manganese(II) bromide and oxides and/or hydroxides bismuth(III) bromide. When only one inorganic bromide salt is present, preferred inorganic oxides and/or hydroxides are oxides and/or hydroxides of tin(IV), and oxides and/or hydroxides of indium(III), especially oxides and/or hydroxides of tin(IV).

[0070] Optionally, the processes further comprise heating the aqueous brine during and/or after combining the components; temperatures and preferences therefor are as described above.

[0071] These preferred processes can further comprise adjusting the pH to a value in the range of 1 to 7 by adding an acid and/or an inorganic oxide and/or hydroxide to the aqueous brine composition; preferably, the inorganic oxide and/or hydroxide is an oxide and/or hydroxide of calcium, manganese(II), or tin(II), tin(IV), bismuth(III), indium(III), or mixtures of any two or more of these. Preferred pH ranges are as described above.

[0072] Naturally-occurring manganese is present in manganese nodules, more accurately

called polymetallic nodules, on the seabed. These nodules are formed in oceans throughout the world, and the most abundant metals in these nodules are manganese and iron.

[0073] The following examples are presented for purposes of illustration, and are not intended to impose limitations on the scope of this invention.

[0074] In the following Examples, the densities of the solutions were determined by the oscillating U-tube technique, which measures the frequency of the oscillation of the liquid sample.

[0075] True crystallization temperature determinations in the Examples were determined by one of the two the procedures described here.
Classical procedure. A jacketed glass tube containing 50 mL of sample was mechanically stirred while being cooled using a recirculating bath containing a cooling fluid (for example, glycol). When the sample reached a temperature about 10°C above the expected first crystal to appear (FCTA) temperature, the sample was cooled at a rate of approximately 0.5°C/min. or a smaller temperature increment until the TCT (true crystallization temperature) is observed. The FCTA temperature was recorded at the lowest temperature reached before precipitation, and the TCT was recorded at the highest temperature achieved immediately after precipitation started. The sample was removed from the recirculating bath and warmed; when all of the precipitate had disappeared, the last crystal to dissolve (LCTD) temperature was recorded. Each determination was run with a seed crystal of silica (≤ 50 µm, -0.03 g) in the sample.
Instrument procedure. A sample cup containing 0.25 mL of the sample was placed in a Cloud, Pour, and Freeze Point Lab Analyzer (model no. 70Xi; Phase Technology, Richmond, Canada), and the sample was cooled at 0.5 degrees Celsius per minute until freezing was detected by diffusive light-scattering.

COMPARATIVE EXAMPLE 1

[0076] Measurements of the true crystallization temperature (TCT) were made on three samples of calcium bromide aqueous solutions. These samples contained only water and calcium bromide. Results are summarized in Table 1 below.

COMPARATIVE EXAMPLE 2

[0077] Two samples were prepared starting from 50.0 g of an aqueous $CaBr_2$, solution having a density of 14.2 ppg (1.70 kg/L). To one sample more $CaBr_2$ (4.32 g) was added; to the other sample, $ZnBr_2$ (3.19 g) was added. Results are summarized in Table 1 below.

COMPARATIVE EXAMPLE 3

[0078] Two samples were prepared starting from 40.0 g of an aqueous $CaBr_2$ solution having a density of 12.8 ppg (1.53 kg/L). To one sample more $CaBr_2$ (13.18 g) was added; to the other sample, $ZnBr_2$ (11.90 g) was added. Results are summarized in Table 1 below.

COMPARATIVE EXAMPLE 4

[0079] A series of samples was prepared starting from 50.0 g of an aqueous $CaBr_2$ solution having a density of 14.2 ppg (1.70 kg/L). The salts LiBr (4.18 g), $SrBr_2 \cdot 6H_2O$ (7.01 g), and $BaBr_2$ (2.21 g) were added to separate $CaBr_2$ solutions. Testing of the strontium-containing and barium-containing samples was discontinued due to solubility and density issues.

[0080] Another series of samples was prepared, starting from 40.0 g of an aqueous $CaBr_2$ solution having a density of 12.8 ppg (1.53 kg/L). The salts LiBr (15.18 g), and $MgBr_2 \cdot 6H_2O$ were added to separate $CaBr_2$ solutions. Testing of the magnesium-containing sample was discontinued due to solubility and density issues. Results are summarized in Table 1 below.

TABLE 1

Compar. Ex.	Run	Inorganic bromides	Non-$CaBr_2$ bromide amount[a]	Total bromide amount[a]	Density	TCT[b]
1	a	$CaBr_2$	none	56.3 wt%	14.76 ppg (1.769 kg/L)	35.6°F (2.0°C)
	b	$CaBr_2$	none	56.0 wt%	14.68 ppg (1.759 kg/L)	32.9°F (0.5°C)
	c	$CaBr_2$	none	55.4 wt%	14.58 ppg (1.747 kg/L)	24.8°F (-4.0°C)
2	a	$CaBr_2$	none	56.9 wt%	14.54 ppg (1.742 kg/L)	22.1°F(-5.5°C)
	b	$CaBr_2$, $ZnBr_2$	6.0 wt%	56.0 wt%	14.57 ppg (1.746 kg/L)	<-5.8°F(<-21.0°C)
3	a	$CaBr_2$	none	58.5 wt%	14.63 ppg (1.753 kg/L)	26.6°F (-3.0°C)
	b	$CaBr_2$, $ZnBr_2$	22.9 wt%	57.5 wt%	14.67 ppg (1.757 kg/L)	<-5.8°F(<-21.0°C)

Compar. Ex.	Run	Inorganic bromides	Non-$CaBr_2$ bromide amount[a]	Total bromide amount[a]	Density	TCT[b]
4	a	$CaBr_2$, LiBr	7.7 wt%	56.8 wt%	14.55 ppg (1.743 kg/L)	33.8°F(1.0°C)
	b	$CaBr_2$, LiBr	27.5 wt%	66.1 wt%	14.60 ppg (1.749 kg/L)	39.2°F (4.0°C)
[a]Relative to total weight of solution. [b]True crystallization temperature; determined by the classical procedure.						

EXAMPLE 1

[0081] A sample was prepared starting from 50.0 g of an aqueous $CaBr_2$ solution having a density of 14.2 ppg (1.70 kg/L). $MnBr_2$ (3.27 g) was added to the $CaBr_2$ solution. Results are summarized in Table 2 below.

EXAMPLE 2

[0082] A sample was prepared starting from 40.0 g of an aqueous $CaBr_2$ solution having a density of 12.8 ppg (1.53 kg/L). $MnBr_2$ (10.18 g) was added to the $CaBr_2$ solution. Results are summarized in Table 2 below.

EXAMPLE 3

[0083] Five separate samples were prepared by adding an amount of $MnBr_2$ to aqueous $CaBr_2$ solutions of densities ranging from 13.4 to 14.0 ppg (1,61 to 1.68 kg/L) to obtain aqueous brines with densities of about 14.6 to 15.1 ppg (1.75 to 1.81 kg/L). Some of the samples were filtered to remove haziness. All of the samples were then analyzed to determine their density and true crystallization temperature (TCT). Results are summarized in Table 2 below.

EXAMPLE 4

[0084] Into a 500 ml flask was placed 160 grams of a $CaBr_2$ solution having a density of 14.2

ppg (1.70 kg/L). The solution was heated to 60°C and then 30 grams of $SnBr_2$ powder was added with stirring. After stirring for about 1 hour at 60°C, all of the $SnBr_2$ had dissolved, to give a hazy light tan solution. The solution was cooled to ambient temperature and then vacuum filtered through a 1 micron filter medium, to give a clear colorless solution having a density of 16 ppg (1.9 kg/L). To a portion (about 90 g) of this solution, deionized water (9 g) was added to give, after mixing, a solution with a density of 15 ppg (1.8 kg/L). Both samples were stored in a 6 to 7°F (-14.4 to -13.9°C) freezer overnight, and after 24 hours remained clear and colorless with no precipitate. Results are summarized in Table 2 below.

EXAMPLE 5

[0085] Into a 3 L jacketed round-bottom flask equipped with a mechanical stirrer, a thermocouple, and an addition funnel was charged aqueous $CaBr_2$ (14.2 ppg; 673.68 g), deionized water (126.32 g), and MnO powder (99 wt%, 67.92 g). While mixing, this slurry was heated at 67°C, and aqueous HBr (48 wt%; 320.96 g) was added over 1 hour via the addition funnel. After holding at 67°C for 40 minutes, aqueous NaOH (50 wt%) or aqueous HBr (48 wt%) was used to titrate the pH to 4.89; some solid formation was observed. The total amount of HBr and/or NaOH solution added was less than 10 g. After cooling to room temperature, the mixture was filtered under vacuum, more aqueous HBr (48 wt%) was added to adjust the pH to 3.0 to 3.5. A total of 2.04 g of NaOH solution was added; less than 5 g of aqueous HBr were added. Water (159 g) was removed under weak vacuum at 54°C to give a clear pink solution (1004 g) with a density of 1.78 g/mL (14.8 ppg) and a pH of 3.4. Results are summarized in Table 2 below.

EXAMPLE 6

[0086] Into a 3 L jacketed round-bottom flask equipped with a mechanical stirrer, a thermocouple, and an addition funnel was charged aqueous $CaBr_2$ (14.2 ppg; 673.68 g), deionized water (126.32 g), and MnO powder (99 wt%, 67.92 g). While mixing, this slurry was heated at 67°C and aqueous HBr (48 wt%; 320.96 g) was added over 1 hour via the addition funnel. After holding at 67°C for 35 minutes, aqueous HBr (48 wt%; 0.12 g) was added to titrate the pH to 3.18; some solid formation was observed. After cooling to room temperature, the mixture was filtered under vacuum. Water (165.6 g) was removed under weak vacuum at 54°C to give a clear pink solution (1010 g) with a density of 1.78 g/mL (14.9 ppg) and a pH of 3.03. Results are summarized in Table 2 below.

TABLE 2

Ex.	Run	Inorganic bromides	Non-$CaBr_2$ bromide amount[a]	Total bromide amount[a]	Density	TCT[b]
1	--	$CaBr_2$, $MnBr_2$	6.1 wt%	56.1 wt%	14.76 ppg (1.769 kg/L)	10.4°F (-12.0°C)
2	--	$CaBr_2$, $MnBr_2$	20.3 wt%	56.0 wt%	14.63 ppg (1.753 kg/L)	<-13°F (-25°C)
3	a	$CaBr_2$, $MnBr_2$	9.3 wt%	56.5 wt%	14.89 ppg (1.784 kg/L)	<-7.6°F (-22°C)
	b	$CaBr_2$, $MnBr_2$	14.4 wt%	56.5 wt%	15.01 ppg (1.799 kg/L)	-9.4°F (-23.0°C)
	c	$CaBr_2$, $MnBr_2$	13.6 wt%	55.3 wt%	15.10 ppg (1.809 kg/L)	7.7°F (-13.5°C)
	d	$CaBr_2$, $MnBr_2$	13.6 wt%	57.6 wt%	14.67 ppg (1.758 kg/L)	< -13°F (-25°C)
	e	$CaBr_2$, $MnBr_2$	20.1 wt%	57.2 wt%	14.63 ppg (1.753 kg/L)	< -13°F (-25°C)
4	a	$CaBr_2$, $SnBr_2$	15.8 wt%	60.6 wt%	16 ppg (1.9 kg/L)	low[c]
	b	$CaBr_2$, $SnBr_2$	6.4 wt%	47.1 wt%	15 ppg (1.8 kg/L)	low[c]
5	-	$CaBr_2$, MnO/HBr	20.0 wt%[d]	55.7 wt%	14.8 ppg (1.78 kg/L)	-14.8°F(-26°C)
6	--	$CaBr_2$, MnO/HBr	20.1 wt%[d]	55.6 wt%	14.9 ppg (1.78 kg/L)	-13°F (-25°C)

[a] Relative to total weight of solution.
[b] True crystallization temperature; determined by the classical procedure.
[c] Below the temperature of the freezer (6 to 7°F; -14.4 to -13.9°C); no precipitate had formed in the samples after 1 week in the freezer.
[d] Calculated as $MnBr_2$.

EXAMPLE 7

[0087] Several $CaBr_2/MnBr_2$ aqueous brine samples with different pH values were prepared starting from a $CaBr_2/MnBr_2$ aqueous brine prepared as in Example 5. The pH value of each sample was adjusted by adding aqueous HBr (48 wt%) and/or aqueous NaOH (50%) until the

desired pH value was reached. In each sample, the total amount of HBr and/or NaOH solution added was less than 5 g. Some of the samples to which NaOH was added formed a small amount of precipitate; these samples were filtered. These samples with different pH values were placed in a 60°C oven to heat-age for one week. The turbidity and presence or absence of a precipitate were observed visually and recorded at the end of the week. Results are summarized in Table 3 below.

EXAMPLE 8

[0088] Several $CaBr_2/MnBr_2$ aqueous brine samples with different pH values were prepared starting from a $CaBr_2/MnBr_2$. aqueous brine prepared as in Example 5. The pH value of each sample was adjusted by adding aqueous HBr (48 wt%) and/or aqueous NaOH (50%) until the desired pH value was reached. In each sample, the total amount of HBr and/or NaOH solution added was less than 10 g. Some of the samples to which NaOH was added formed a small amount of precipitate; these samples were filtered. To some of the samples, enough glycerol was added to make a solution containing either 5 wt% or 10 wt% glycerol. These samples were placed in a 60°C oven to heat-age for one week. The turbidity and presence or absence of a precipitate were observed visually and recorded at the end of the week. Results are summarized in Table 3 below.

EXAMPLE 9

[0089] Example 8 was repeated, except that the samples were allowed to sit at ambient temperature rather than oven-aging. Results are summarized in Table 3 below.

EXAMPLE 10

[0090] Several $CaBr_2/MnBr_2$ aqueous brine samples having a pH of about 3.5 or less as in Example 5 were used. To these samples, enough glycerol was added to make a solution containing either 5 wt% or 10 wt% glycerol. All of these solutions remained clear; no precipitate was observed in any of the solutions over time at room temperature.

TABLE 3

Ex.	Inorganic bromides	Glycerol amt.[a]	pH	Turbidity	Precip.	Aging temp.
			1.00	clear	none	
			1.99	clear	none	
			3.00	clear	none	
			3.16	clear	none	

Ex.	Inorganic bromides	Glycerol amt.[a]	pH	Turbidity	Precip.	Aging temp.
7	$CaBr_2$, $MnBr_2$	0	3.30	clear	none	60°C
			3.40	clear	none	
			3.62	cloudy	none	
			3.99	cloudy	yes	
			4.28	cloudy	yes	
8	$CaBr_2$, $MnBr_2$	0	4.58	cloudy	yes	60°C
		5%	4.58	cloudy	none	
		0	4.28	cloudy	yes	
		5%	4.28	clear	none	
		10%	4.28	clear	none	
9	$CaBr_2$, $MnBr_2$	0	4.58	cloudy	yes	ambient
		5%	4.58	clear	none	
		0	4.28	cloudy	yes	
		5%	4.28	clear	none	
		10%	4.28	clear	none	
[a] Relative to total weight of solution.						

EXAMPLE 11

[0091] A sample was prepared starting from 100.0 g of an aqueous $CaBr_2/MnBr_2$ (1.75:1 (wt:wt) $CaBr_2$:$MnBr_2$) clear brine fluid having a density of 15.0 ppg (1.80 kg/L). $SnBr_2$ (7.00 g) was mixed with the $CaBr_2/MnBr_2$ clear brine fluid at 48°C. After the solids had dissolved, the mixture was cooled to room temperature and then vacuum filtered through a 2 micron glass filter, to give a clear liquid having a density of 15.8 ppg (1.89 kg/L). Some of the water was removed under vacuum at 54°C to give a clear brine fluid with a density of 16.0 ppg (1.92 kg/L). A sample of this clear brine fluid was analyzed to determine its true crystallization temperature (TCT), which was below -23°C. Results are summarized in Table 4 below.

[0092] In Examples 12, 13, 14, 15 and 16, the densities were measured with calibrated graduated cylinders. In this method, a 50 mL graduated cylinder was calibrated using 30.000 g of deionized water. The volume (29.7 mL) was recorded to calibrate the scale on the graduated cylinder. Each well fluid sample (29.7 mL) was weighed, and the density was calculated by using the following formula: density (g/mL) = mass (g)/29.7 mL. For smaller sample sizes, a 10 mL graduated cylinder was calibrated and used in the same manner to determine the densities.

EXAMPLE 12

[0093] Several samples were prepared by mixing an amount of either $SnBr_4$ (4.00 g; 9.00 g) or $BiBr_3$ (4.00 g; 6.00 g) with 27.00 g of an aqueous $CaBr_2/MnBr_2$ (1.75:1 (wt:wt) $CaBr_2$:$MnBr_2$) clear brine fluid having a density of 14.8 ppg (1.77 kg/L). All of the samples were then analyzed to determine their density. Each sample was filtered through a 1 micron syringe filter, and a portion of each sample was placed in a freezer at -16°C, and another portion of each sample was placed in an oven at 60°C. All of the samples in both the oven and the freezer remained clear after 3 days or longer. Results are summarized in Table 4 below.

TABLE 4

Ex.	Run Inorganic bromides		Non-$CaBr_2$ bromide amount[a]	$MnBr_2$ amount[a]	Total bromide amount[a]	Density	Soln. remained clear at -16°C
11	--	$CaBr_2$, $MnBr_2$, $SnBr_2$	26.3 wt%	19.6 wt%	60.6 wt%	16.0 ppg (1.92 kg/L)	at least one week
12	a	$CaBr_2$, $MnBr_2$, $SnBr_4$	30.6 wt%	17.7 wt%	61.5 wt%	16.1 ppg (1.93 kg/L)	at least one week[b]
	b	$CaBr_2$, $MnBr_2$, $SnBr_4$	40.3 wt%	15.3 wt%	66.9 wt%	17.5 ppg (2.10 kg/L)	at least 3 days[c]
	c	$CaBr_2$, $MnBr_2$, $SnBr_4$	34.9 wt%	16.7 wt%	64.0 wt%	16.7 ppg (2.00 kg/L)	at least one day
	d	$CaBr_2$, $MnBr_2$, $BiBr_3$	30.6 wt%	17.7 wt%	61.5 wt%	16.3 ppg (1.95 kg/L)	at least one week[c]
	e	$CaBr_2$, $MuBr_2$, $BiBr_3$	41.0 wt%	20.7 wt%	61.5 wt%	16.5 ppg (1.98 kg/L)	at least one week

[a] Relative to total weight of solution.
[b] True crystallization temperature -34.95°C; determined by the instrument procedure.
[c] True crystallization temperature below -32°C; determined by the instrument procedure.

EXAMPLE 13

[0094] Two samples were prepared by mixing an amount of $SnBr_2$ (1.30 g; 4.00 g) with 27.00 g of an aqueous $CaBr_2/MnBr_2$ (1.75:1 (wt:wt) $CaBr_2$:$MnBr_2$) clear brine fluid having a density of 15.3 ppg (1.83 kg/L). Both of the samples were then analyzed to determine their density. Each sample was filtered through a 1 micron syringe filter, then enough formic acid to make a concentration of 2000 ppm in the solution was added. Then a portion of each sample was placed in a freezer at -16°C, and another portion of each sample was placed in an oven at 60°C. The samples in both the oven and the freezer remained clear after one week. Results are summarized in Table 5 below.

EXAMPLE 14

[0095] Two separate samples were prepared by mixing either $SnBr_2$ (6.00 g) or $BiBr_3$ (6.00 g) with an aqueous $CaBr_2$ solution containing formic acid (2000 ppm) and having a density of 14.2 ppg (1.70 kg/L). Both of the samples were then analyzed to determine their density. Each sample was filtered through a 1 micron syringe filter, then enough formic acid to make a concentration of 2000 ppm in the solution was added. Then a portion of each sample was placed in a freezer at -16°C, and another portion of each sample was placed in an oven at 60°C. The samples in both the oven and the freezer remained clear overnight or longer. Results are summarized in Table 5 below.

TABLE 5

Ex.	Run	Inorganic bromides	Non-$CaBr_2$ bromide amount[a]	$MnBr_2$ amount[a]	Total bromide amount[a]	Density	Soln. remained clear at -16°C
13	a	$MnBr_2$, $SnBr_2$	24.0 wt%	19.4 wt%	57.9 wt%	15.9 ppg (1.90 kg/L)	at least one week
	b	$CaBr_2$, $MnBr_2$, $SnBr_2$	30.6 wt%	17.7 wt%	61.5 wt%	16.3 ppg (1.95 kg/L)	at least one week
14	a	$CaBr_2$, $SnBr_2$	18.2 wt%	none	61.7 wt%	16.2 ppg (1.94 kg/L)	at least overnight
	b	$CaBr_2$, $BiBr_3$	18.2 wt%	none	61.7 wt%	16.6 ppg (1.99 kg/L)	at least 2 days

[a] Relative to total weight of solution.

EXAMPLE 15

[0096] Several samples were prepared by mixing an amount of one or more inorganic bromide salts, and in some instances deionized water and formic acid, with an amount of an aqueous calcium bromide solution having a density of 14.2 ppg (1.70 kg/L; WellBrom®, Albemarle Corporation). Each mixture was heated to dissolve the solids. Details for each solution are as follows:

formic acid (80.0 mg) and $InBr_3$ (6.00 g); deionized water (0.50 g) had been added to 27.00 g of the calcium bromide solution; heating was at 50°C;

$InBr_3$ (6.90 g) and 27.00 g of the calcium bromide solution; heating was at 48 to 50°C;

an aqueous solution of $MnBr_2$ (14.10 g; 50.3 wt%) and $InBr_3$ (6.96 g); 13.15 g of the calcium bromide solution; heating was at 48 to 50°C; and

formic acid (80.0 mg) and $SnBr_4$ with 27.00 g of the calcium bromide solution, to which deionized water (0.73 g) had been added; heating was at 49°C.

[0097] After the solids had dissolved, the mixture was cooled to room temperature. After cooling to room temperature, each solution was analyzed to determine its density. A sample from each solution was placed in a freezer at -16°C, and another sample from each solution was placed in an oven at 60°C. Results are summarized in Table 6 below.

EXAMPLE 16

[0098] A sample was prepared by mixing $SnBr_4$ (10.17 g) and deionized water (4.11 g) containing HBr (0.02 g; 48%). The mixture was heated at 35°C to dissolve the solids. After the solids had dissolved, the mixture was cooled to room temperature, yielding a clear liquid having a density of 18.8 ppg (2.25 kg/L). A sample from the solution was placed in a freezer at -16°C, and another sample from the solution was placed in an oven at 60°C. The samples in both the oven and the freezer remained clear after 72 hours. Results are summarized in Table 6 below.

EXAMPLE 17

[0099] A sample was prepared by mixing $InBr_3$ and deionized water in amounts to form a clear

solution having a density of 16.0 ppg (1.92 kg/L), a sample of which was placed in a freezer at -16°C. Results are summarized in Table 6 below.

TABLE 6

Ex.	Run	Inorganic bromide(s)	Non-$CaBr_2$ bromide amount[a]	Total bromide amount[a]	Formic acid[a]	Density	Soln. remained clear at -16°C
15	a	$CaBr_2$, $InBr_3$	17.9 wt%	60.8 wt%	2280 ppm	16.0 ppg (1.92 kg/L)	at least 6 days
	b	$CaBr_2$, $MnBr_2$, $InBr_3$	36.6 wt%	64.9 wt%	none	17.2 ppg (2.06 kg/L)	at least 72 hrs.[b]
	c	$CaBr_2$, $MnBr_2$, $InBr_3$	41.0 wt%	61.5 wt%	none	16.6 ppg (1.99 kg/L)	at least 96 hrs.
	d	$CaBr_2$, $SnBr_4$	24.5 wt%	63.7 wt%	2700 ppm	16.5 ppg (1.98 kg/L)	at least 6 days
16	--	$SnBr_4$	71.1 wt%	71.1 wt%	none	18.8 ppg (2.25 kg/L)	at least 72 hrs.
17	--	$InBr_3$	60 wt%	60 wt%	none	16.0 ppg (1.92 kg/L)	at least 24 hrs.

[a] Relative to total weight of solution.
[b] True crystallization temperature below -32°C; determined by the instrument procedure.

EXAMPLE 18

[0100] Several samples were prepared by dissolving an amount of $Mn(NO_3)_2 \cdot H_2O$ in deionized water at ambient temperature, adding $CaBr_2$ to the solution, and in some instances also adding HNO_3 or HCl. Each mixture was heated to dissolve the solids. Details for each solution are as follows:

1. a) $Mn(NO_3)_2 \cdot H_2O$ (24.4 g) and deionized water (10.70 g), $CaBr_2$ (20.45 g) added at

56°C;

2. b) $Mn(NO_3)_2•H_2O$ (12.20 g) and deionized water (5.35 g), $CaBr_2$ (10.23 g), HNO_3 (conc., 65 mg) was then added;
3. c) $Mn(NO_3)_2•H_2O$ (12.20 g) and deionized water (2.09 g), $CaBr_2$ (5.02 g);
4. d) $Mn(NO_3)_2•H_2O$ (12.20 g) and deionized water (5.35 g), then added HCl (conc.; 58 mg), then $CaBr_2$ (10.23 g).

[0101] After the solids had dissolved, each mixture was cooled to room temperature. The cooled solutions were clear. After cooling to room temperature, each sample was filtered through a 1 micron syringe filter and analyzed to determine its density. A portion of each sample was placed in a freezer at -16°C. All of the samples in the freezer remained crystal-free for at least one week. Results are summarized in Table 7 below.

EXAMPLE 19

[0102] A sample was prepared by adding $Mn(NO_3)_2•H_2O$ (3.00 g) to an aqueous $CaBr_2$ solution (57.6 wt%, 25.05 g). The mixture was heated to 50°C and then cooled to room temperature to give a clear, light pink solution with a density of 15.3 ppg (1.83 kg/L). After filtration through a 1-micron syringe filter, a portion of the sample was placed in a freezer at -16°C, and another portion of the sample was placed in an oven at 60°C. Both samples remain clear after 24 hours. Results are summarized in Table 7 below.

TABLE 7

Ex.	Run	Inorganic bromide	Total bromide amount[a]	Total $Mn(NO_3)_2$ amount[a]	Acid	Density	Soln. remained clear at -16°C
18	a	$CaBr_2$	36.8 wt%	43.9 wt%	--	14.9 ppg (1.79 kg/L)	at least one week
18	b	$CaBr_2$	36.7 wt%	43.8 wt%	HNO_3	14.9 ppg (1.79 kg/L)	at least one week
18	c	$CaBr_2$	26.0 wt%	57.2 wt%	--	15.1 ppg (1.81 kg/L)	at least one week
18	d	$CaBr_2$	36.7 wt%	39.7 wt%	HCl	15.0 ppg (1.80 kg/L)	at least one week
19	--	$CaBr_2$	51.4 wt%	10.7 wt%	--	15.3 ppg (1.83 kg/L)	at least 24 hrs.

[a] Relative to total weight of solution.

EXAMPLE 20

[0103] Several samples were prepared by diluting an aqueous solution of either $CaBr_2$ or $MnBr_2$ with deionized water and adding an amount of sodium metatungstate to the diluted solution at ambient temperature. Each mixture was then heated. Details for each solution are as follows:

1. a) $CaBr_2$ (aq., 53.2 wt%, 15.05 g), deionized water (2.81 g), sodium metatungstate hydrate (4.50 g); heating was at 54-56°C;
2. b) $MnBr_2$ (aq., 50 wt%, 15.00 g), deionized water (2.00 g), sodium metatungstate hydrate (3.29 g); heating was at 35°C;
3. c) $MnBr_2$ (aq., 50 wt%, 15.00 g), deionized water (2.00 g), sodium metatungstate hydrate (6.00 g); heating was at 50 to 58°C.

[0104] After the solids had dissolved, each mixture was cooled to room temperature. After cooling to room temperature, each sample was filtered through a 1 micron syringe filter, and clear, colorless solutions were obtained. Each sample was then analyzed to determine its density. A portion of each sample was placed in a freezer at -16°C. All of the samples in the freezer remained clear at least overnight. Results are summarized in Table 8 below.

EXAMPLE 21

[0105] Two samples were prepared by mixing an amount of lithium bromide with a metatungstate salt. Details for each solution are as follows:

1. A) LiBr (8.00g) was dissolved in deionized water (12.04 g). Into this solution was added sodium metatungstate hydrate (8.33 g), to give a colorless solution with a density of 15.0 ppg (1.80 kg/L); and
2. B) LiBr (10.00g) was dissolved in deionized water (10.00 g). Into this solution was added an aqueous lithium metatungstate solution (ρ = 2.95 g/mL) to give a colorless solution with density of 16.3 ppg (1.95 kg/L).

[0106] Each solution was filtered through a 1-micron syringe filter, after which a portion of each sample was placed in a freezer at -16°C, and another portion of each sample was placed in an oven at 60°C. Both the freezer and oven samples from run A remained clear after one week.

Both the freezer and oven samples from run B remained clear after at least 20 hours. Results are summarized in Table 8 below.

TABLE 8

Ex.	Run	Inorganic bromide	Total bromide amount[a]	Total metatungstate salt amount[a]	Density	TCT[b]
20	a	$CaBr_2$	35.8 wt%	20.0 wt%	14.9 ppg (1.79 kg/L)	-27.8°C
20	b	$MnBr_2$	37.0 wt%	18.8 wt%	15.3 ppg (1.83 kg/L)	--[c]
20	c	$MnBr_2$	32.6 wt%	25.9 wt%	16.4 ppg (1.97 kg/L)	-31.01°C
21	A	LiBr	28.2 wt%	29.4 wt%	15.0 ppg (1.80 kg/L)	-29.8°C
21	B	LiBr			16.3 ppg (1.95 kg/L)	--[d]

[a] Relative to total weight of solution.
[b] True crystallization temperature; determined by the instrument procedure.
[c] Solution remained clear at -16°C overnight.
[d] Solution remained clear at -16°C for at least 20 hours.

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO2004050557A [0004]

P A T E N T K R A V

1. Sammensætning, der er zinkfrit, vandigt saltvand med en densitet på 1,71 kg/L (14,3 pund pr. gallon) eller mere, og en sand krystallisationstemperatur på -6,7°C (20°F) eller mindre, hvilken sammensætning omfatter vand og ét eller flere uorganiske bromidsalte, med betingelserne at:

når calciumbromid foreligger, er der også ét eller flere andre vandopløselige uorganiske salte foreliggende, hvor det andet vandopløselige uorganiske salt er valgt fra uorganisk bromidsalt og mangan(II)nitrat,

når lithiumbromid foreligger, er calciumbromid undladt,

når bismuth(III)bromid foreligger, foreligger der også ét eller flere andre vandopløselige uorganiske salte, og

for en sand krystallisationstemperatur på -12,2°C (10°F) eller mindre, når mangan(II)bromid foreligger, foreligger der også én eller flere andre vandopløselige uorganiske salte.

2. Sammensætning ifølge krav 1, hvor det uorganiske bromidsalt er:

mangan(II)bromid, tin(II)bromid, tin(IV)bromid, indium(III)bromid, eller en blanding af hvilke som helst to eller flere af disse; eller

en kombination af calciumbromid og ét eller flere uorganiske bromidsalte valgt fra mangan(II)bromid, tin(II)bromid, tin(IV)bromid, bismuth(III)bromid, indium(III)bromid, eller en blanding af hvilken som helst to eller flere af disse; eller

en kombination af bismuth(III)bromid og ét eller flere uorganiske bromidsalte valgt fra mangan(II)bromid, tin(II)bromid, tin(IV)bromid, indium(III)bromid, eller en blanding af hvilke som helst to eller flere af disse; eller

hvor kun ét uorganisk bromidsalt foreligger, og det uorganiske bromidsalt er tin(IV)bromid eller indium(III)bromid.

3. Sammensætning ifølge krav 2, hvor det uorganiske bromidsalt er en kombination af calciumbromid og mangan(II)bromid, en kombination af calciumbromid, mangan(II)bromid og tin(IV)bromid, eller en kombination af calciumbromid, mangan(II)bromid og bismuth(III)bromid.

4. Sammensætning ifølge krav 1, hvor det andet vandopløselige uorganiske salt, der er til stede med bismuth(III)bromid, er et uorganisk bromidsalt.

5. Sammensætning ifølge krav 1, hvor det uorganiske bromidsalt er mangan(II)bromid, hvor ét eller flere andre vandopløselige uorganiske salte foreligger, og hvor det ene eller flere andre vandopløselige uorganiske salte er mangan(II)nitrat eller et vandopløseligt polywolframatsalt.

6. Sammensætning ifølge et hvilket som helst af kravene 1–3, hvor sammensætningen har en densitet på 1,75 kg/L (14,6 pund pr. gallon) eller mere.

7. Sammensætning ifølge et hvilket som helst af kravene 1–3, hvor sammensætningen har en densitet på 1,80 kg/L (15,0 pund pr. gallon) eller mere.

8. Sammensætning ifølge krav 1, hvor:

det uorganiske bromidsalt er en kombination af calciumbromid og mangan(II)bromid, og sammensætning har en densitet på 1,75 kg/L (14,6 pund pr. gallon) eller mere, og en pH-værdi i området 2,5 til 5; eller

det uorganiske bromidsalt er en kombination af calciumbromid, mangan(II)bromid og tin(IV)bromid, og sammensætningen har en densitet på 1,80 kg/L (15,0 pund pr. gallon) eller mere; eller

det uorganiske bromidsalt er en kombination af calciumbromid, mangan(II)bromid og bismuth(III)bromid, og sammensætningen har en densitet på 1,92 kg/L (16,0 pund pr. gallon) eller mere; eller

det uorganiske bromidsalt er calciumbromid, og det andet vandopløselige uorganiske salt er mangan(II)nitrat, og sammensætningen har en densitet på 1,74 kg/L (14,5 pund pr gallon) eller mere; eller

det uorganiske bromidsalt er mangan(II)bromid, og det andet vandopløselige uorganiske salt er et vandopløseligt polywolframatsalt, og sammensætningen har en densitet på 1,74 kg/L (14,5 pund pr. gallon) eller mere.

9. Sammensætning ifølge et hvilket som helst af kravene 5 eller 8, hvor det vandopløselige polywolframatsalt er en alkalimetal-polywolframat, jordalkalimetal-polywolframat eller mangan-polywolframat.

10. Fremgangsmåde at fremstille en zinkfri, vandig saltvandsammensætning med en densitet på 1,71 kg/L (14,3 pund pr. gallon) eller mere, og en sand krystallisationstemperatur på -6,7°C (20°F) eller mindre, hvilken fremgangsmåde omfatter at kombinere, i en hvilken som helst rækkefølge, komponenter omfattende vand og ét eller flere uorganiske bromidsalte, med betingelserne at:

når det uorganiske bromidsalt er calciumbromid, foreligger også ét eller flere andre vandopløselige uorganiske salte, hvor det andet vandopløselige uorganiske salt er valgt fra et uorganisk bromidsalt og mangan(II)nitrat,

når det uorganiske bromidsalt er lithiumbromid, anvendes ikke calciumbromid,

når det uorganiske bromidsalt er bismuth(III)bromid, foreligger også ét eller flere andre vandopløselige uorganiske salte, og

for en sand krystallisationstemperatur på -12,2°C (10°F) eller mindre, når det uorganiske bromid er mangan(II)bromid, foreligger også ét eller flere andre vandopløselige uorganiske salte.

11. Fremgangsmåde ifølge krav 10, hvor ét eller flere uorganiske bromidsalte frembringes under fremgangsmåden med (i) en uorganisk oxid og/eller hydroxid og (ii) hydrogenbromid og/eller brom.

12. Fremgangsmåde ifølge krav 11, hvor den uorganiske oxid/eller hydroxid er

én eller flere oxider og/eller hydroxider af calcium, mangan(II), tin(II), tin(IV), indium(III),

eller en blanding af to eller flere af hvilke som helst af de ovenstående; eller

én eller flere oxider og/eller hydroxider af mangan(II), tin(IV), og/eller bismuth(III) i kombination med calciumbromid, og/eller oxider og/eller hydroxider af calcium.

13. Fremgangsmåde ifølge et hvilket som helst af kravene 10-12, hvor det uorganiske bromidsalt er mangan(II)bromid, tin(II)bromid, tin(IV)bromid, indium(III)bromid, eller en blanding af hvilke som helst to eller flere af disse; eller

en kombination af calciumbromid og mangan(II)bromid, tin(II)bromid, tin(IV)bromid, bismuth(III)bromid, indium(III)bromid, eller en blanding af hvilke som helst to eller flere af disse; eller

en kombination af bismuth(III)bromid og mangan(II)bromid, tin(II)bromid, tin(IV)bromid, indium(III)bromid, eller en blanding af hvilke som helst to eller flere af disse; eller hvor kun ét uorganisk bromidsalt foreligger, og det uorganiske bromidsalt er tin(IV)bromid eller indium(III)bromid.

14. Fremgangsmåde ifølge krav 13, hvor det uorganiske bromidsalt er en kombination af calciumbromid og mangan(II)bromid, en kombination af calciumbromid, mangan(II)bromid og tin(IV)bromid, eller en kombination af calciumbromid, mangan(II)bromid og bismuth(III)bromid.

15. Fremgangsmåde ifølge krav 10, hvor det uorganiske bromidsalt er bismuth(III)bromid, det andet vandopløselige uorganiske salt er et uorganisk bromidsalt.

16. Fremgangsmåde ifølge krav 10, hvor det uorganiske bromidsalt er mangan(II)bromid, hvor ét eller flere andre vandopløselige uorganiske salte anvendes, og hvor det ene eller flere andre vandopløselige uorganiske salte er mangan(II)nitrat eller et vandopløseligt polywolframatsalt.

17. Fremgangsmåde ifølge krav 16, hvor det vandopløselige polywolframatsalt er et alkalimetal-polywolframat, en jordalkalimetal-polywolframat, eller mangan-polywolframat.

18. Fremgangsmåde ifølge et hvilket som helst af kravene 10–14, hvor sammensætningen har en densitet på 1,75 kg/L (14,6 pund pr. gallon) eller mere, og/eller hvor det uorganiske bromidsalt er i en total mængde på 40 vægt% til 75 vægt%, i forhold til sammensætningens samlede vægt.

19. Fremgangsmåde ifølge et hvilket som helst af kravene 10-14, som yderlige omfatter opvarmning under og/eller efter kombineringen.

20. Fremgangsmåde ifølge et hvilket som helst af kravene 10–18, hvor dannet sammensætningen har en sand krystallisationstemperatur på -12,2°C (10°F) eller mindre.

21. Anvendelse af en sammensætning som defineret i krav 1 som borehulfluid.

22. Anvendelse ifølge krav 21, hvor fluidet er en færdiggørelsesvæske (completion fluid), borevæske, pakningsvæske (packer fluid) eller arbejdsvæske (workover fluid).

23. Anvendelse ifølge krav 21, hvor fluidet er en klar færdiggørelsesfluid (completion fluid).

24. Anvendelse ifølge krav 21 i offshore-brøndkompletteringsaktiviteter med høj-

tryksreservoirer.