



US009418719B2

(12) **United States Patent**
Akerib et al.

(10) **Patent No.:** **US 9,418,719 B2**

(45) **Date of Patent:** **Aug. 16, 2016**

(54) **IN-MEMORY COMPUTATIONAL DEVICE**

(71) Applicant: **GSI TECHNOLOGY ISRAEL LTD.**,
Tel Aviv (IL)

(72) Inventors: **Avidan Akerib**, Tel Aviv (IL); **Eli Ehrman**, Beit Shemesh (IL)

(73) Assignee: **GSI TECHNOLOGY ISRAEL LTD.**,
Tel Aviv (IL)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/555,638**

(22) Filed: **Nov. 27, 2014**

(65) **Prior Publication Data**

US 2015/0146491 A1 May 28, 2015

Related U.S. Application Data

(60) Provisional application No. 61/910,068, filed on Nov. 28, 2013.

(51) **Int. Cl.**
G11C 7/10 (2006.01)
G11C 8/10 (2006.01)
G11C 7/18 (2006.01)

(52) **U.S. Cl.**
CPC **G11C 8/10** (2013.01); **G11C 7/1006** (2013.01); **G11C 7/1051** (2013.01); **G11C 7/18** (2013.01)

(58) **Field of Classification Search**

CPC G11C 7/1006
USPC 365/189.02
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,137,730 A *	10/2000	Chien	G11C 7/18
				365/189.02
6,937,535 B2 *	8/2005	Ahn	G11C 7/18
				365/189.04
7,002,864 B2 *	2/2006	Kim	G11C 11/406
				365/205
7,088,637 B2 *	8/2006	Ko	G11C 7/1051
				365/185.21
7,230,869 B1 *	6/2007	Redgrave	G11C 7/06
				365/189.18
7,505,298 B2 *	3/2009	Yang	G11C 7/12
				365/189.02

* cited by examiner


Primary Examiner — Son Mai

(74) *Attorney, Agent, or Firm* — Eitan, Mehulal & Sadot

(57) **ABSTRACT**

A computing device comprising includes a memory array having a plurality of sections with memory cells arranged in rows and column, at least one cell in each column of the memory array connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0. The computing device additionally includes at least one multiplexer to connect a bit line in a column of a first section to a bit line in a column in a second section different from the first section and a decoder to activate a word line connected to a cell in the column in the second section to write the bit line voltage into the cell.

9 Claims, 4 Drawing Sheets






Figure 1




Figure 2




Figure 3




Figure 4

IN-MEMORY COMPUTATIONAL DEVICE**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims benefit from U.S. Provisional Patent Application No. 61/910,068 filed Nov. 28, 2013, which is hereby incorporated in its entirety by reference.

FIELD OF THE INVENTION

The present invention relates to computing devices in general, and more particularly to a device and a method used for search and/or computational operations.

BACKGROUND OF THE INVENTION

Memory arrays, which store large amounts of data, are known in the art. Over the years, manufacturers and designers have worked to make the arrays physically smaller but the amount of data stored therein larger.

Computing devices typically have one or more memory array to store data and a central processing unit (CPU) and other hardware to process the data. The CPU is typically connected to the memory array via a bus. Unfortunately, while CPU speeds have increased tremendously in recent years, the bus speeds have not increased at an equal pace. Accordingly, the bus connection acts as a bottleneck to increased speed of operation.

U.S. Pat. No. 8,238,173 to Akerib et al. and assigned to the common assignee of the present invention discloses a processor which may perform in-memory computations. The processor includes a memory array to store data, and an activation unit to activate at least two cells in a column of the memory array at generally the same time to generate a Boolean function output of the data of the at least two cells. The Boolean function output may then be stored inside the memory array for further processing, including to generate new Boolean function outputs. This operation may be repeated numerous times until the desired results are achieved. The results may then be output for further use. Also disclosed therein is a content addressable memory (CAM) unit, including a ternary CAM (T-CAM) unit which may be implemented using the principles of operation of the in-memory processor.

SUMMARY OF THE PRESENT INVENTION

There is provided, in accordance with an embodiment of the present invention, a computing device including a memory array having a plurality of sections with memory cells arranged in rows and column, at least one cell in each column of the memory array connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0. There is also included at least one multiplexer to connect a bit line in a column of a first section to a bit line in a column in a second section different from the first section, and a decoder to activate a word line connected to a cell in the column in the second section to write the bit line voltage into the cell.

In accordance with an embodiment of the present invention, the computing device may additionally include a controller to provide the decoder with an instruction set for decoding.

In accordance with an embodiment of the present invention, the instruction set may be of a small size.

In accordance with an embodiment of the present invention, the instruction set from the controller comprises a maximum size of 64 bits.

In accordance with an embodiment of the present invention, the instruction set represents compressed data associated with the operation of any one of the memory array, the at least one multiplexer, and the decoder.

In accordance with an embodiment of the present invention, the decoder decompresses the compressed data.

In accordance with an embodiment of the present invention, the decoder activates the at least one multiplexer to connect the bit lines in the first section and the second section.

In accordance with an embodiment of the present invention, the decoder simultaneously accesses a plurality of read word lines and write word lines in the memory array.

In accordance with an embodiment of the present invention, the decoder decodes the instruction set from the controller into an instruction set for accessing in parallel a plurality of read word lines and write word lines in the memory array.

In accordance with an embodiment of the present invention, the decoder may include a memory array having a plurality memory cells arranged in rows and column, at least one cell in each column connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0.

In accordance with an embodiment of the present invention, the activation of the word line may be through the bit line in the decoder.

In accordance with an embodiment of the present invention, the at least one cell connected to a bit line may include only one memory cell in each column.

In accordance with an embodiment of the present invention, the at least one cell connected to a bit line may include all the memory cells in each column.

In accordance with an embodiment of the present invention, the memory cells may include non-destructive cells.

In accordance with an embodiment of the present invention, the memory cells may include volatile memory cells.

There is provided, in accordance with an embodiment of the present invention, a method of performing in-memory computations in a memory array including a plurality of sections having memory cells arranged in rows and column, at least one cell in each column of the memory array connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0, the method includes connecting a bit line in a column of a first section to a bit line in a column in a second section different from the first section; activating a word line connected to a cell in the column in the second section; and writing the bit line voltage into the cell.

In accordance with an embodiment of the present invention, the method may further include decompressing compressed data represented by a small size instruction set into a large size instruction set.

In accordance with an embodiment of the present invention, the method may further include simultaneously accessing a plurality of read word lines and write word lines.

In accordance with an embodiment of the present invention, the method may further include decoding an instruction set from a controller into an instruction set having a plurality of read and write commands.

In accordance with an embodiment of the present invention, the method may further include activating the word line with a bit line voltage.

BRIEF DESCRIPTION OF THE DRAWINGS

The subject matter regarded as the invention is particularly pointed out and distinctly claimed in the concluding portion

of the specification. The invention, however, both as to organization and method of operation, together with objects, features, and advantages thereof, may best be understood by reference to the following detailed description when read with the accompanying drawings in which:

FIG. 1 schematically illustrates an exemplary in-memory computational device, according to an embodiment of the present invention;

FIG. 2 schematically illustrates a section of an MLB in FIG. 1 including two exemplary MLB data sections interconnected by a multiplexer, according to an embodiment of the present invention;

FIG. 3 schematically illustrates an exemplary arrangement of memory cells in rows and columns in a decoder shown in FIG. 1, according to an embodiment of the present invention; and

FIG. 4 schematically illustrates an exemplary in-memory computational device suitable for big data processing, according to an embodiment of the present invention.

It will be appreciated that for simplicity and clarity of illustration, elements shown in the figures have not necessarily been drawn to scale. For example, the dimensions of some of the elements may be exaggerated relative to other elements for clarity. Further, where considered appropriate, reference numerals may be repeated among the figures to indicate corresponding or analogous elements.

DETAILED DESCRIPTION OF THE PRESENT INVENTION

In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the invention. However, it will be understood by those skilled in the art that the present invention may be practiced without these specific details. In other instances, well-known methods, procedures, and components have not been described in detail so as not to obscure the present invention.

Applicants have realized that the performance of devices which use in-memory computations may be vastly improved by dividing the device's memory into blocks of memory cells which may be individually accessed and which in parallel may carry out different operations. Applicants have additionally realized that performance may be further improved by using the results of the operations carried out in a memory logic block (MLB), as a block of memory cells will be referred to hereinafter, in other MLBs to perform other operations, without first having to output the result of each operation and rewriting them into memory for use by the other MLBs. Only when the desired final result is obtained is the data output from memory.

Applicants have realized that an in-memory computational device which can perform in-memory computations as described above may require a decoder which can decode controller instruction sets in known size formats (8 bit, 16 bit, 32 bit, 64 bit, etc.) into an instruction set of hundreds and even thousands of bits with which to access, in parallel, the numerous number of rows of cells in the MLBs. In effect, the decoder should be able to decode the "small size" controller instructions which may represent compressed code into decompressed "large size" read/write instructions to activate the MLB cells.

It may be appreciated that an in-memory computational device as described above, which may execute a multiplicity of different operations in parallel, may operate as a MIMD (multiple instructions, multiple data) machine. It may be further appreciated that the in-memory computational device may also operate as an SIMD (single instruction, multiple

data) machine, the selection to operate as a MIMD or a SIMD defined in the controller instructions.

It may also be appreciated that an in-memory computational device as described above may find numerous applications in diverse field which may require search and/or compute operations. These may include database and storage applications including distributed storage and cloud storage, signal processing including image and audio processing, biometrics, data compression, communications network switching, caching applications, among many others, some of which may include CAM and T-CAM operations.

Reference is made to FIG. 1 which schematically illustrates an exemplary in-memory computational device 100, according to an embodiment of the present invention. Device 100 may include a memory logic block (MLB) 102, a decoder 104, a code storage unit 106, a controller 108, and a data line buffer 110.

MLB 102 may include a plurality of MLB data sections 114, shown in the figure as MLB DATA SECTION 0 to MLB DATA SECTION K, and a plurality of multiplexer units (MUX) 116, each multiplexer unit interconnecting two MLB data sections 114 located one above the other. MLB 102 may include any number of MLB data sections 114, the number generally limited by physical constraints associated with chip design, or by electrical constraints associated with the operation of sensing circuitry and/or driver circuitry, among other possible constraints. Applicants have determined that between 16 to 64 MLB data sections 114 may be used satisfactorily in MLB 102, although operation with lesser or greater numbers of MLB data sections may still be satisfactory.

Reference is now also made to FIG. 2, which schematically illustrates a section of MLB 102 including two exemplary MLB data sections 114 (designated 114A and 114B respectively in the figure) interconnected by MUX 116, according to an embodiment of the present invention. As may be appreciated from the figure, MLB data sections 114A and 114B each include a plurality of memory cells 150 arranged in M rows and N columns. The number of cells in each row and in each column, as previously described with reference to MLB 102, may generally be limited by physical constraints associated with chip design, or by electrical constraints which may be associated with sensing circuitry, precharge circuitry and/or driver circuitry operation, among other possible constraints. Applicants have determined that 16 memory cells may be used satisfactorily in each MLB data section 114, although operation with lesser or greater numbers of cells may still be satisfactory.

The architecture of MLB 102, including MLB data section 114A and 114B, may resemble that of a NOR-type memory array (for NOR Boolean operations), or alternatively, that of a NAND-type memory array (for NAND Boolean operations). It is well known that NOR functions may be combined to generate the same results as NAND functions, and the inverse. Therefore, with reference to the present invention, Applicants understand that the skilled person practicing the invention may use either type of architecture.

Cells 150 may each be identified by the letter "C" followed by the row and column in which it is located in the MLB data section. For example, cells 150 in the first row and located in the 1 to Nth column are designated C11, C12, C13, to C1N, respectively. Similarly cells 150 located in the second row and third row, as shown, are designated C21, C22, C23, to C2N, and C31, C32, C33, to C3N, respectively. Cells 150 in the Mth row are designated CM1, CM2, CM3, to CMN, respectively.

Each cell **150** in a row may be connected to a read word line **158** (RE) and a write word line **160** (WE) through which each cell in the row may be activated for reading and writing respectively. Each cell **150** in a column may be connected to a bit line **156**.

Cells **150** may include volatile memory cells or non-destructive (non-volatile) memory cells, or a combination of both. The volatile memory cells may be implemented using SRAM or DRAM technologies or other volatile memory technologies. The non-destructive cells may be implemented using non-volatile memory (NVM) technologies such as ReRAM, MRAM, STT-RAM, T-RAM, PC-RAM, nvSRAM, SONOS, Z-RAM, FeRAM, NRAM, among other NVM technologies and memristor technologies known in the art, or which may be under development, or yet to be developed, and may also include flash memory technologies (e.g. floating gate, etc.).

MUX **116** may connect bit line **156** in a column of an MLB data section **114** with bit lines **156** of one or more columns in the MLB data section above or below. In one embodiment, MUX **116** may connect bit line **156** in one column to a bit line in one of three columns in the section above or below, although it may be appreciated that the number of bit line connections varies with the design of MUX **116**, and may include less than or more than three connection. The columns to which bit line **156** may connect through MUX **116** may include that directly above, or below, the bit line, and the adjacent column on each side. For example, MUX **116** may connect cell column **162** in MLB data section **114A** with cell columns **164**, **166**, and **168**. Through MUX **116**, a voltage charge (data) on bit line **156** in cell column **162** may be transferred to bit line **156** in any one of columns **164**, **166**, **168**, or the inverse.

It may be appreciated that MUXs **116** may be used to transfer data between MBL data sections **114** within a same MBL or different MBLs (in devices with multiple MBLs shown in FIG. 4), or both, without having to output the data from memory and rewriting into memory. That is, by activating one or more MUXs **116**, the data result of an operation performed in a column, may be transferred from the column in one MLB data section to one or more columns in other MLB data sections in the same MLB or other MLBs. As an example, to write the result of a NAND or NOR operation performed in column **168** in MLB data section **114B** to cell **C32** (column **162**) in MLB data section **114A**, MUX **116** connects (responsive to a command) bit line **156** in column **162** to bit line **156** in column **168** so that the two bit lines are now at substantially the same potential (a logical "0" or "1"). Write word line **160** connecting to **C32** in MLB data section **114A** is activated (write enabled) and the data on bit line **156** is written into **C32**. The data written into **C32** in MLB data section **114A** may be used to perform a Boolean operation in column **168**.

MUXs **116** may also be used to distribute data arriving from a host connected to device **100** through data line buffer **110** to memory cells **150**. Additionally, MUXs **116** may be used to direct output data results through MLB data sections **114** to data line buffer **110**, and therefrom to the host.

Decoder **104** may receive instructions sets in known size formats (e.g. 8 bit, 16 bit, 32 bit, 64 bit) from controller **108** and may decode the instructions into an instruction set of hundreds or thousands, and possibly tens of thousands, read and write instructions, and MUX **116** operation instructions. The instructions generated by decoder **104** may be applied, in parallel, to the rows of cells **150**, and to MUXs **116**, in MLB **102**.

Decoder **104** may be implemented in a NOR-type memory array, or alternatively a NAND-type memory array, and may be able to perform in-memory computations including generation and combination of NOR and NAND Boolean functions. Decoder **104** may additionally use results of operations without having to output the results and rewrite them into the decoder. The output results may be the instructions to MLB **102**. In some embodiments, the architecture of decoder **104** may resemble that of an MLB **102**, and may be divided into sections resembling a MLB data section **114**. Multiplexers may be included, but may not be necessary, and may depend on the number of rows of cells in the decoder.

Reference is now also made to FIG. 3 which schematically illustrates an exemplary arrangement of memory cells **150** in rows **170** and columns **172** in decoder **104**, according to an embodiment of the present invention.

Decoder read and write instructions and MUX control signals are output from the decoder through bit lines **174** in each column, one bit line for every read word line **158**, one for every write word line **160**, and one for every MUX control line **117**, in MLB **102**. Therefore, a minimum number of columns **172** required may be determined by the following equation:

$$COL=2*CM*K*L;$$

where COL=number of columns **172**, CM=number of cells in an MLB data section **114** (multiplied by 2, one bit line for read word line **158**, and one bit line for write word line **160**), K=number of MLB data sections in MLB **102**, and L=number of multiplexed columns per bit line. Other columns **172** may be required to provide for additional bit lines **174** as may be required for other operations, for example, for MLB **102** data input/output through data line buffer **110**, which may require a multiplexer to connect the buffer to the first MLB data section (i.e. K*L may be replaced by (K+1)*L).

For example, assuming that MLB **102** has 64 MLB data sections **102** and each MLB data section has 16 cells **150** in each column, each MUX **116** connects multiplexes 3 columns to every column, then:

$$COL=2*16*64+64*3=2115;$$

that is, at least 2115 columns **172** are required in decoder **104** to connect to MLB **102**, and 2018 if a multiplexer is to be used to connect data line buffer **110** to MLB data section **0**.

As may be appreciated from the figure, cell rows **170** and columns **172** in decoder **104** may be oriented perpendicularly to cell rows **176** and columns **178** in MLB **102** to facilitate the connection between the bit line outputs from the decoder with the input lines (read word lines **158**, write word lines **160**, and MUX control lines **117**). This may be potentially advantageous in the design of the layout of the chip of device **100** as decoder **104** may be placed at substantially a right angle (90°) to MLB **102**, possibly reducing space requirements.

The instructions from controller **108** may activate read and write lines (not shown) connecting cells **150** in rows **170**. Responsive to the activation of the read and write lines, similarly to MLB **102**, Boolean operations may be performed in columns **172** and the results stored in cells **150** of other columns **172** for performing other Boolean operations. Only the desired final result, which may be the instruction set for MLB **102**, may be output.

A number of rows **170** in decoder **104** may correspond to, but not be limited to, the width of the bus of controller **108**, but may be more or less. For example, if the width of the bus is 64 bits, then the number of rows **170** may also be 64 rows, although it may also be 32 rows. Alternatively, if the width of the bus is 32 bits, the number of rows **170** may be 64 rows.

Whichever may be the case, decoder **104** may include suitable firmware including appropriate buffering as may be required to transfer the controller instructions into the decoder.

As previously mentioned, decoder **104** may be able to perform in-memory computations including generation of NAND and/or NOR Boolean functions, and may use results of operations without having to output the results and rewrite them into the decoder. The instruction sets from controller **108** may represent compressed data stored in code storage unit **106**, and may be delivered to the decoder every clock cycle. The compressed data may include low level instructions which may specify how to perform Boolean operations, including NAND and/or NOR operations, the order of performing the operations, in which MLB data section to execute the operations, which MLB data section results are combined in which cycle, which MLB data section results are to be multiplexed, among other instructions for performing in-memory computations in MLB **102** to generate the desired output results.

It may be appreciated that decoder **104** decompresses the compressed data received from code storage unit **106** through controller **108** every clock cycle, converting the controller instruction sets of relatively small size into a much larger instruction set of decoded read/write instructions and MUX control instructions which are delivered in parallel to MLB **102**. Each decoded instruction set may be delivered to MLB **102** in every clock cycle. It may be appreciated that a decoder which may receive small size controller instructions every clock cycle and may also output large set decoded instructions every clock cycle may be potentially advantageous as relatively little memory is required. For example, in the art, a function that requires 100 cycles to complete would require memory space to store approximately 20K signals (assuming approximately 2000 word lines in the MLB) The decoder of the present invention solves this problem as the required memory space may be that required to perform the computational operations to decompress the compressed code data.

Reference is now made to FIG. **4** which schematically illustrates an exemplary in-memory computational device **200**, according to an embodiment of the present invention. Device **200** includes an MLB block **202** including a plurality of MLBs **102**, a decoder block **204**, code storage unit **106**, controller **108**, and data lines buffer **210**. Device **200** may be functionally similar to device **100** shown in FIG. **1** and may also be suitable for performing big data search and computational operations in MLB block **202**. Decoder **204** and data lines buffer **210** are functionally similar to decoder **104** and data line buffer **110** shown in FIG. **1** but may be scaled in size to enable manipulation and processing of the big data.

From the above discussion, it may be further appreciated that a small MIMD machine may be implemented in device **100** where many different operations may be carried out in parallel in MLB **102** by simultaneously providing different read and write instructions to the plurality of MLB data sections **114** (and by activating MUXs **116** accordingly so that the results of column operations in one MLB data section may be used in the operations of other MLB data sections. A larger MIMD machine may be implemented in device **200** by providing the different read and write instructions to the plurality of MLBs **102** and activating the MUXs accordingly. Furthermore, a small MIMD machine may be implemented in device **100** by simultaneously providing the same read and write instructions to the plurality of MLB data sections **114**, and activating MUXs **116** accordingly. A large SIMD machine may be implemented in device **200** by providing the same read and write instructions to a plurality of MLBs **102** and activating MUXs **116** accordingly.

Unless specifically stated otherwise, as apparent from the preceding discussions, it is appreciated that, throughout the specification, discussions utilizing terms such as “processing,” “computing,” “calculating,” “determining,” or the like, refer to the action and/or processes of a computer, computing system, or similar electronic computing device that manipulates and/or transforms data represented as physical, such as electronic, quantities within the computing system’s registers and/or memories into other data similarly represented as physical quantities within the computing system’s memories, registers or other such information storage, transmission or display devices.

Embodiments of the present invention may include apparatus for performing the operations herein. This apparatus may be specially constructed for the desired purposes, or it may comprise a general-purpose computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a computer readable storage medium, such as, but not limited to, any type of disk, including floppy disks, optical disks, magnetic-optical disks, read-only memories (ROMs), compact disc read-only memories (CD-ROMs), random access memories (RAMs), electrically programmable read-only memories (EPROMs), electrically erasable and programmable read only memories (EEPROMs), magnetic or optical cards, Flash memory, or any other type of media suitable for storing electronic instructions and capable of being coupled to a computer system bus.

The processes and displays presented herein are not inherently related to any particular computer or other apparatus. Various general-purpose systems may be used with programs in accordance with the teachings herein, or it may prove convenient to construct a more specialized apparatus to perform the desired method. The desired structure for a variety of these systems will appear from the description below. In addition, embodiments of the present invention are not described with reference to any particular programming language. It will be appreciated that a variety of programming languages may be used to implement the teachings of the invention as described herein.

While certain features of the invention have been illustrated and described herein, many modifications, substitutions, changes, and equivalents will now occur to those of ordinary skill in the art. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the invention.

What is claimed is:

1. A computing device comprising:

a memory array comprising a plurality of sections having memory cells arranged in rows and column, at least one cell in each column of said memory array connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0; and

at least one multiplexer to connect a bit line in a column of a first section to a bit line in a column in a second section different from said first section; and

a decoder to activate a word line connected to a cell in said column in said second section to write said bit line voltage into said cell; and

a controller to provide said decoder with an instruction set for decoding in said decoder wherein said instruction set represents compressed data associated with the operation of any one of said memory array, said at least one multiplexer, and said decoder.

2. A computing device according to claim 1 wherein said decoder decompresses said compressed data.

9

3. A computing device comprising:
 a memory array comprising a plurality of sections having memory cells arranged in rows and column, at least one cell in each column of said memory array connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0; and
 at least one multiplexer to connect a bit line in a column of a first section to a bit line in a column in a second section different from said first section; and
 a decoder to activate a word line connected to a cell in said column in said second section to write said bit line voltage into said cell and to simultaneously access a plurality of read word lines and write word lines in said memory array.
4. A computing device comprising:
 a memory array comprising a plurality of sections having memory cells arranged in rows and column, at least one cell in each column of said memory array connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0; and
 at least one multiplexer to connect a bit line in a column of a first section to a bit line in a column in a second section different from said first section; and
 a decoder to activate a word line connected to a cell in said column in said second section to write said bit line voltage into said cell; and
 a controller to provide said decoder with an instruction set for decoding in said decoder wherein said decoder decodes said instruction set from said controller into an instruction set for accessing in parallel a plurality of read word lines and write word lines in said memory array.
5. A computing device comprising:
 a memory array comprising a plurality of sections having memory cells arranged in rows and column, at least one cell in each column of said memory array connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0; and
 at least one multiplexer to connect a bit line in a column of a first section to a bit line in a column in a second section different from said first section; and
 a decoder to activate a word line connected to a cell in said column in said second section to write said bit line voltage into said cell wherein said decoder comprises a memory array comprising a plurality of memory cells arranged in rows and columns, at least one cell in each column being connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0 wherein activation of said word line is through said bit line in said decoder.
6. A computing device comprising:
 a memory array comprising a plurality of sections having memory cells arranged in rows and column, at least one cell in each column of said memory array connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0; and

10

- at least one multiplexer to connect a bit line in a column of a first section to a bit line in a column in a second section different from said first section; and
 a decoder to activate a word line connected to a cell in said column in said second section to write said bit line voltage into said cell wherein said decoder comprises a memory array comprising a plurality of memory cells arranged in rows and columns with only one memory cell in each column and wherein said memory cell is connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0.
7. A method of performing in-memory computations in a memory array comprising a plurality of sections having memory cells arranged in rows and column, at least one cell in each column of said memory array connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0, the method comprising:
 connecting a bit line in a column of a first section to a bit line in a column in a second section different from said first section;
 activating a word line connected to a cell in said column in said second section; and writing said bit line voltage into said cell; and
 decompressing compressed data represented by a small size instruction set into a large size instruction set.
8. A method of performing in-memory computations in a memory array comprising a plurality of sections having memory cells arranged in rows and column, at least one cell in each column of said memory array connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0, the method comprising:
 connecting a bit line in a column of a first section to a bit line in a column in a second section different from said first section;
 activating a word line connected to a cell in said column in said second section; and writing said bit line voltage into said cell; and
 comprising simultaneously accessing a plurality of read word lines and write word lines.
9. A method of performing in-memory computations in a memory array comprising a plurality of sections having memory cells arranged in rows and column, at least one cell in each column of said memory array connected to a bit line having a bit line voltage associated with a logical 1 or a logical 0, the method comprising:
 connecting a bit line in a column of a first section to a bit line in a column in a second section different from said first section;
 activating a word line connected to a cell in said column in said second section; and writing said bit line voltage into said cell; and
 activating said word line with a bit line voltage.

* * * * *