



Office de la Propriété

Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2725121 C 2014/01/07

(11)(21) **2 725 121**

(12) **BREVET CANADIEN
CANADIAN PATENT**

(13) **C**

(86) Date de dépôt PCT/PCT Filing Date: 2009/05/27
(87) Date publication PCT/PCT Publication Date: 2009/12/03
(45) Date de délivrance/Issue Date: 2014/01/07
(85) Entrée phase nationale/National Entry: 2010/11/19
(86) N° demande PCT/PCT Application No.: GB 2009/050573
(87) N° publication PCT/PCT Publication No.: 2009/144496
(30) Priorité/Priority: 2008/05/30 (GB0809865.9)


(51) Cl.Int./Int.Cl. *A24D 3/04* (2006.01)

(72) Inventeur/Inventor:
FIEBELKORN, RICHARD, GB

(73) Propriétaire/Owner:
BRITISH AMERICAN TOBACCO (INVESTMENTS)
LIMITED, GB

(74) Agent: FETHERSTONHAUGH & CO.

(54) Titre : FILTRE POUR ARTICLE A FUMER
(54) Title: FILTER FOR A SMOKING ARTICLE



(57) Abrégé/Abstract:

A multi-section filter (5) for a smoking article comprises at least a first (5B) and a second filter section (5A). The first filter section (5B) is at a mouth end of the filter (5) and the second filter section includes a set of ventilation holes (17) and a set of grooves (7). The grooves (7) extend from respective ventilation holes (17) along the second filter section (5A) up to but not into the first filter section (5B).

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
3 December 2009 (03.12.2009)(10) International Publication Number
WO 2009/144496 A1

(51) International Patent Classification:

A24D 3/04 (2006.01)

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(21) International Application Number:

PCT/GB2009/050573

(22) International Filing Date:

27 May 2009 (27.05.2009)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0809865.9 30 May 2008 (30.05.2008) GB

(71) Applicant (for all designated States except US):
BRITISH AMERICAN TOBACCO (INVESTMENTS) LIMITED [GB/GB]; Globe House, 1 Water Street, London WC2R 3LA (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **FIEBELKORN, Richard** [GB/GB]; BRITISH AMERICAN TOBACCO (INVESTMENTS) LIMITED, R & D Centre, Regents Park Road, Millbrook, Southampton SO15 8TL (GB).(74) Agents: **GILL, Siân** et al.; 20 Little Britain, London EC1A 7DH (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: FILTER FOR A SMOKING ARTICLE




Fig. 1

WO 2009/144496 A1

(57) Abstract: A multi-section filter (5) for a smoking article comprises at least a first (5B) and a second filter section (5A). The first filter section (5B) is at a mouth end of the filter (5) and the second filter section includes a set of ventilation holes (17) and a set of grooves (7). The grooves (7) extend from respective ventilation holes (17) along the second filter section (5A) up to but not into the first filter section (5B).

Filter for a Smoking Article

Field of the Invention

The invention relates to multi-section filters for smoking articles, for example, for

5 cigarettes.

Background to the Invention

Cigarettes typically include a tobacco rod and a filter. The filter is located at the mouth end of the cigarette, between the smoker and the tobacco rod. The filter modifies the tobacco 10 smoke (mainstream smoke) drawn through it. Filters may be intended to reduce or alter various smoke constituents, including particulate matter and/or vapour phase matter.

Multi-segment filters are becoming more common. For example, in one arrangement a filter includes a section comprising activated carbon, which has good filtration properties.

15 The filter may include another section between the activated carbon and the mouth-end of the cigarette. This helps to ensure that the activated carbon does not enter the mouth of the user.

There are many known techniques for altering filter behaviour. One technique is to 20 include ventilation holes in the outside of the filter. This allows air to be drawn into the filter, and so dilutes the cigarette smoke inhaled by a user. Another known technique is to provide grooves in a filter, often along the outside of the filter. These grooves can be used to control flow properties through the filter. Examples of grooves and/or ventilation holes can be found in: WO 03/051144; GB 2150809; GB 2150412; GB 2118819; GB 2089641; 25 GB 2088692; GB 2088193; GB 2088191; GB 1585862; GB 1308661; EP 047969; US 4527573; US 4527572; US 4256122; US 4135523; US 3768489; and US 3752165.

It remains desirable to provide improved filtration properties for a multi-segmented filter.

Summary of the Invention

One embodiment of the invention provides a multi-section filter for a smoking article. The filter comprises at least first and second filter sections. The first filter section is at a mouth end of the filter. The second filter section includes a set of ventilation holes and a set of

grooves or channels. The grooves extend from respective ventilation holes along the second filter section towards but not into the first filter section.

Such a filter allows separation from the external entrance of air into the filter from the 5 atmosphere (also referred to herein as the actual air entry point), which occurs at the start of the grooves, and the internal entrance of air into the main body of the filter where it joins the mainstream smoke, which occurs at the end of the grooves (also referred to as the ventilation hole position or ventilation zone). This gives increased flexibility in the filter design. For example, the external air entrance is relatively far from the mouth end, thereby 10 reducing the risk of the external entrance of the air becoming occluded by the smoker, while allowing the air to mix with the smoke relatively near to the mouth end of the filter.

The area of filter material between the actual air entry point and the ventilation hole position, is subject to a slower flow of smoke for any given puff than would be the case if the diluting air entered the body of the filter at the position of the ventilation holes. The 15 reduced velocity results in the smoke being subject to an increased level of filtration. This also makes the filter particularly suited to having a multi-segmented configuration, and especially a configuration wherein filter sections contain adsorbent materials, such as carbon, to enhance the filtration of particular toxicants. The grooves may be restricted to a single segment of the filter, for ease of filter construction.

20

In one particular embodiment, the grooves extend along the outside of the filter body parallel with a major axis of the filter. The grooves are substantially non-permeable along their length. The grooves extend substantially the length of the second filter section. The filter is arranged such that air passes through the ventilation holes, travels along the 25 grooves towards the first filter section and exits the grooves into a body portion of the filter adjacent the first filter section. There are three filter sections in an end-to-end arrangement in this particular embodiment, and the second (grooved) filter section comprises the middle section of the filter. The second filter section has a non-permeable inner plug-wrap and is joined to the other filter sections with a permeable outer plug-wrap. The grooves are located between the inner plug-wrap and the outer plug-wrap, and the 30 body of the second filter section is therefore separated from the grooves by a non-permeable barrier. The filter is then joined to the tobacco rod with an outer non-permeable tipping layer through which ventilation holes are formed. Accordingly, the grooves are

substantially impermeable to air and smoke entering or leaving the filter body. The only air ingress into the grooves is via the ventilation holes in the outer tipping and then through the permeable outer plug-wrap into the grooves. This diluting air travels along the grooves to enter the filter body at or towards the junction of the first and second filter sections.

5

In some embodiments, all the ventilating air entering through the ventilation holes is directed along the grooves. In other embodiments, a groove extends from some of the ventilation holes in the ventilation zone, and but other ventilation holes are directed into a body portion of the filter section, thus some of the ventilating air enters the filter body directly at the position of the ventilation zone. These additional ventilation holes of the ventilation zone may be directed into a body portion of the filter section between the grooves. The additional ventilation holes may be directed into the body portion near the ends of the grooves furthest away from the first filter section (mouth end), and/or the additional ventilation holes may be directed into the body portion near the ends of the grooves closest to the first filter section.

10

In a further embodiment, the tipping is fabricated from a naturally permeable material, and thus ventilating air can enter the grooves over the whole length of the second filter section. Additional ventilation holes may also be added to further enhance the overall ventilation

15

level.

20

These different configurations give considerable flexibility in the design and operation of the filter. For example, some air can be made to enter the body of the grooved filter section to mix there with the main smoke flow, and further air (from the grooves) can be made to mix with smoke as it enters the first filter section.

25

In one embodiment, the ventilation holes are located at least about 11mm from the mouth end of the first filter section. For example, the ventilation holes may be located from about 12 to about 25mm from the mouth end of the first filter section.

30

In one embodiment, a barrier is located at the end of each groove furthest away from the first filter section. The barrier ensures that entry into this end of the grooves occurs only via the ventilation holes. The barrier may be provided by hot melt fusion of the filter

material, by glue applied to the end of each groove, or by an annular member located at the end of the second filter section furthest away from the first filter section, or by any other suitable mechanism. In a further embodiment, the barrier is provided due to the fact that the grooves in the second section only extend part way along the filter section, such that 5 the open ends of the grooves butt up against the end of the first filter section.

The invention also provides a smoking article incorporating a tobacco rod and such a multi-section filter.

10 The invention further provides a smoking article comprising a tobacco rod and a multi-section filter having at least first and second filter sections, wherein the first filter section is at a mouth end of the filter and wherein the second filter section includes a set of ventilation holes and a set of grooves, the grooves extending from respective ventilation holes along the second filter section towards but not into the first filter section.

15 Another embodiment of the invention provides a method of making a smoking article comprising: combining a grooved second filter section and a mouth end filter section by overlaying the grooved filter section with a permeable plug-wrap and then overlaying the combined grooved and mouth-end filter sections with a tipping paper which contains 20 ventilation holes, wherein the position of some or all of the ventilation holes corresponds to the position of the grooves. Further sections can be added to the tobacco end of the second section during combining. The grooves may be blocked at the end opposite to the mouth end during the combining operation. In some embodiments this blockage is done by addition of adhesive. Alternatively, the blockage is done by hot melt of the filter 25 material, or by addition of an annular material at the end of the grooved filter section.

The ventilation holes can be easily applied using standard on-machine laser techniques such as on-line or off-line perforation.

30 In one particular embodiment, the grooved filter section is made by shaping a filter rod or by shaping a plug-wrap and wrapping the shaped plug-wrap around a filter rod.

31511-20

- 5 -

Another method of making a smoking article comprises combining a fully grooved second filter section with a mouth end section within a porous plug-wrap, the grooves within the second section being blocked at the tobacco end by the addition of material such as adhesive applied in spots or a band around the filter during the combining. Further sections can be

5 added to the tobacco end of the second section during the combining.

Another method of making a smoking article comprises combining a fully grooved second filter section within first and third filter sections, and inserting an annular material between the second and third filter sections such that the end of the grooves are blocked by the annular material.

10 Yet another embodiment of the invention provides a smoking article comprising a tobacco rod and a multi-section filter combined by means of a tipping paper containing ventilation holes, the multi-section filter comprising at least first and second filter sections, wherein the first filter section is at a mouth end of the filter and wherein the second filter section includes a set of grooves, the grooves extending from some of the ventilation holes along the second filter

15 section towards but not into the first filter section, wherein the filter further comprises a barrier located at the end of each groove furthest away from the first filter section, such that entry into this end of the grooves is only via the ventilation holes, and wherein the first and second filter sections are combined by means of a porous plug-wrap.

Still another embodiment of the invention provides a method of making a smoking article

20 comprising combining a grooved filter section and a mouth-end filter section by overlaying the grooved filter section with a permeable plug-wrap, combining the grooved and mouth-end filter sections using a porous plug-wrap, and then overlaying the combined grooved and mouth-end filter sections with a tipping paper which contains ventilation holes, wherein the position of some or all of the ventilation holes corresponds to the position of the grooves, and

25 wherein the grooves are blocked at the end opposite to the mouth end during the combining operation.

31511-20

- 5a -

Brief Description of the Drawings

Embodiments of the invention are described, by way of example only, with reference to the accompanying drawings in which:

Figure 1 depicts a longitudinal cross-section of a cigarette comprising a multi-section filter in
5 accordance with one embodiment of the invention;

Figure 2 is a schematic diagram of the filter of the cigarette of Figure 1;

Figure 3 is an axial cross-section of the filter of the cigarette of Figure 1;

Figures 4a and 4b are schematic diagrams of the filter in accordance with two further
embodiments of the invention having additional ventilation holes; and

10 Figures 5a to 5d form a schematic illustration of the assembly of a grooved filter section in
accordance with one embodiment of the invention.

Detailed Description

Figure 1 depicts a cigarette 1 comprising a tobacco rod 3 and a multi-section filter 5, which
can be held together by tipping paper 15 as is well-known in the art. The multi-section filter 5
15 is made up of three filter sections 5A, 5B, 5C arranged end-to-end. In particular, filter 5
comprises a grooved middle filter section 5A, a mouth-end filter section 5B, and a filter
section 5C adjacent to the tobacco rod 3. The grooved filter section 5A is arranged in the
middle between the other two filter sections 5B, 5C (with respect to the main cylindrical axis
of the filter). The grooves 7 are located on the outside of the filter and extend in a generally
20 axial direction. The filter section 5A is provided with a plurality of grooves 7, which are
distributed around the circumference of filter section 5A. The

grooves extend along substantially the length of the middle filter section 5A, from near the tobacco end section 5C to the mouth-end section 5B. However, the grooves do not extend into the tobacco-end filter section 5C or into the mouth end filter section 5B.

5 The grooves 7 are separated from the tobacco-end filter section 5C by an impermeable barrier 9. Likewise, the grooves are separated from the body 11 of the middle filter section 5A by an impermeable layer 6. However, the grooves are open at the end opposite barrier 9 to allow air or other gas/vapour flowing along groove 7 to pass into the mouth-end filter section 5B.

10

In one embodiment, the impermeable layer 6 comprises a non-porous plug-wrap which surrounds (the circumference of) the body of filter material 11 in filter section 5A. This filter material 11 may comprise any suitable filter material or structure, for example cellulose acetate tow, paper, etc. The filter material may be provided with one or more additives, such as activated carbon, etc. The non-porous plug-wrap 6 may be corrugated to define grooves 7 (with the corrugations running parallel to the cylindrical axis of the filter). The filter material 11 inside the non-porous plug-wrap will generally deform to occupy all the space inside the non-porous plug-wrap.

20

The individual filter sections are combined with a porous outer plug-wrap 13. This outer plug-wrap then sits on the ridges or raised corrugations of the inner plug-wrap, with the grooves being formed between the outer plug-wrap and the lower (reduced radius) portions of the inner plug-wrap 6.

25

In use, a smoker draws on the mouth-end section of the filter 5B. This causes smoke from the combustion end 2 of the tobacco rod to travel through the filter rod towards the smoker (as indicated by the arrows). The smoke travels through the remaining (unburnt) tobacco rod 3 before entering the filter 5. The smoke first passes through the tobacco-end filter section 5C, then through the body 11 of the middle filter section (since the smoke is 30 unable to pass into the grooves 7). The smoke then exits the filter 5 through the mouth-end filter section 5B.

When a smoker draws on the mouth-end section of the filter 5B, this also draws air into grooves 7 via the ventilation holes 17 and through the plug-wrap 13, as indicated by arrow A. In general, the flow resistance through the ventilation holes 17 and along grooves 7 is low compared to the flow resistance through the body portion 11 of the filter, for example.

5

After the air has entered a groove 7 as indicated by arrow A, the air is constrained to travel along the groove, as indicated by arrow B, since the groove walls, which are formed by non-porous inner plug-wrap 6 and tipping 15 papers, plus barrier 9, are generally impermeable. Accordingly, the incoming air finally exits the grooves 7 into the mouth-end 10 filter portion 5B, where it mixes with and dilutes the mainstream smoke from combustion zone 2.

Figure 2 is a further schematic view of the embodiment of Figure 1. Thus, Figure 2 is a perspective view illustrating the circumferential distribution of grooves 7 around a filter. In 15 addition, Figure 2 specifically shows the ventilation holes 17 located over the ends of the grooves 7 remote from the mouth-end of the filter. In one embodiment these ventilation holes 17 are formed via laser perforation, but any other suitable mechanism may be used. The ventilation holes may be sited directly over the grooves (as shown schematically in Figure 2) or sited in a random band or bands which may or may not coincide with the 20 grooves.

Figure 3 is a cross-section through the filter 5 at the location of the ventilation holes 17 in the outer tipping 15. According to the embodiment shown in Figure 3 the ventilation holes in the outer tipping do not all coincide with the grooves. Although there is a gap shown in 25 Figure 3 for clarity between the inner plug-wrap 6 and the outer plug-wrap 13, and likewise a gap between the outer plug-wrap 13 and the tipping paper 15, it will be appreciated that in practice no appreciable gaps are present, except for the grooves themselves.

It will be appreciated that the number and distribution of grooves 7, as shown in Figures 2, 30 3, and 4 is by way of example only. Other embodiments may have a different number and/or distribution of grooves.

Providing the grooves 7 in the filter 5 allows a separation between: (a) the location of the ventilation holes for incoming air, now at the end of the middle filter section 5A remote from the mouth; and (b) the location of the point where the ventilating air joins the main smoke flow, now at the junction between the middle filter section 5A and the mouth-end filter section 5B. The ability to separate these two locations gives more flexibility in the design and control of filter 5.

For example, placing the ventilation holes at the far end of the middle filter section 5A, away from the mouth end, reduces the risk that the ventilation holes are accidentally 10 blocked by the mouth (e.g. lips) during smoking. In one particular embodiment, the ventilation holes are located at least about 11mm from the mouth end of the filter, for example between about 12mm and about 25mm from the mouth end.

On the other hand, having the ventilation air entering the smoke flow of the filter relatively 15 near the mouth causes smoke passing through the body 11 of the middle section to travel comparatively slowly, which in turn enhances the filtration efficiency of the body 11 of this filter section. In particular, since the smoke constituents spend longer in the vicinity of filter material 11 of the middle section, they have an increased likelihood of being adsorbed by this material. Accordingly, the filter material may comprise adsorbent material such as 20 activated carbon or other suitable adsorbents.

Two alternative embodiments are illustrated in Figure 4a and 4b. In both of these 25 embodiments, additional ventilation holes are provided for the middle (grooved) filter section 5A. In the embodiment of Figure 4a, the additional ventilation holes 17A are provided at the far end of the middle filter section 5A, remote from the mouth; i.e. at the same end as the ventilation holes 17 into the grooves. However, the circumferential positioning of these holes 17A is such that they do not lie above the grooves. Thus, air passes through the ventilation holes 17A directly into the main body 11 of filter material for filter section 5A. Accordingly, the air passing through the ventilation holes 17A does 30 not bypass the filter material 11 of the middle filter section 5A, in contrast to the air entering through the ventilation holes 17, which is channelled by the grooves directly towards the mouth-end filter section 5B.

The configurations of Figures 4a and 4b therefore provide two effective positions of entry for ventilating air, and so allow enhanced control of smoke and filter properties. For example, the additional ventilation provides increased dilution of the mainstream smoke, including carbon monoxide and tar. The additional ventilation also increases the flow speed through the filter body 11, which decreases the filtration efficiency for materials such as tar. In the embodiment of Figure 4b, the additional ventilation holes 17B are provided at the mouth end of the grooved section 5A. The air passing through ventilation holes 17B therefore enters the main portion of filter 5 at a slightly upstream position to the air entering through ventilation holes 17 (and travelling along grooves 7). The overall result of the configurations of Figure 4a and 4b are to provide increased ventilation and hence increased smoke dilution compared to the arrangement of Figure 2.

It will be appreciated that the embodiments of Figures 4a and 4b may be combined in a single embodiment that has both additional ventilation holes 17A and additional ventilation holes 17B. That is, additional ventilation holes at both ends of the grooved filter section 5A. It will also be appreciated that the ventilation provided either into the grooves 17, or as additional ventilation via perforations 17A or 17B, can be provided in a wide band or zone across part or all of the filter section 5A.

It will also be appreciated that the number of filter sections may be different from the 3 filter sections shown in Figures 1, 2 and 4. For example, some multi-segment filters may only have 2 filter sections, while other multi-segment filters may have four, five or more filter sections. In general, the grooved filter section is separated from the mouth end of the filter by at least one other filter section (to help avoid lip blocking). Furthermore, while the grooves in Figures 1-4 have been shown extending the full length of the grooved filter section 5A, in other embodiments the grooves may extend only partway along the grooved filter section. In such a case the grooves may start away from the tobacco end of the section and/or terminate away from the mouth end of the section. Conversely, in some cases the grooves may extend (wholly or partially) across multiple filter sections.

Figure 5 illustrates a method of manufacturing a filter in accordance with one embodiment of the invention. In this example, a sheet of non-permeable plug-wrap material 6 is corrugated or embossed to produce the grooves 7. The grooved material is wrapped

around a cylinder of filter material 11 (Figure 5a). The grooves shown in Figure 5 have a U-shaped profile, but may have any other suitable profile, for example, V-shaped, or with square corners at the top and bottom. While the grooves (Figure 5a) are shown as being on the inner surface of plugwrap material 6, hence creating channels within the body of the filter material itself, it will be appreciated that channels may form externally to the main body of the filter material 11. In addition the number and spacing of the grooves may vary from one embodiment to another. For example, there may be continuous V-shaped grooves (no spacing), so that the inner plug-wrap in effect has a zigzag configuration.

10 In the approach of Figure 5, a layer of outer plug-wrap material 13 is now wrapped around the outside of the grooved filter rod (Figure 5b). The grooves 7 in the inner plug-wrap material therefore become closed channels between the inner plug-wrap 6 and the outer plug-wrap 13. The outer plug-wrap 13 may be used to bind the filter section 11 with one or more other filter sections if so desired.

15 Additional ventilation holes 17 may be formed in the outer plug-wrap 13 using laser 51 (Figure 5c). Although the outer plug-wrap 13 is shown separated from the inner plug-wrap 6 for clarity, again they will in practice be touching, as shown in Figure 5b, except where the grooves are located. The ventilation holes 17 coincide with the grooves 7, and 20 therefore provide entrance holes for air to pass into the grooves. Additional ventilation holes may be provided which are not linked to the grooves (as illustrated above in Figures 4a and 4b). Such ventilation holes may be formed passing through both the outer and also the inner plug-wrap as well as the outer tipping paper.

25 A further layer of sheet material 15, commonly known as tipping paper, may be subsequently applied to the ventilated wrapper and overlays the grooved filter section 5A (Figure 5d). The tipping paper may be used to join the combined filter sections to the tobacco rod thereby securing together the components of a complete cigarette 1. The tipping paper may be permeable (pre-perforated) or impermeable. Impermeable 30 tipping paper may be ventilated by means of on-machine laser techniques.

In another embodiment, on-line continuous grooving is applied to a filter rod, for example by wrapping the impermeable inner plug-wrap around the whole length of the rod, then

grooving by passing through a shaped former.. This filter rod can then be segmented for combination with other segments in a multi-element filter. Alternatively, discontinuous grooving may be applied to the filter rod, for example by impressing discontinuous grooves into the wrapped rod, using heated formers.

5

Where continuous grooving methods are used, the grooves are closed to the element on the tobacco side of the grooved section by any suitable technique. For example, an outer annulus (doughnut) made of plastic may be inserted between the two elements (as illustrated in Figure 1). Another possibility for this sealing is to apply glue to the end of the 10 groove furthest from the mouth.

Where discontinuous grooving methods are used, the filter segments are combined in such a way that the grooves do not reach the end of the tobacco side of the filter section.

15

The grooves or channels may be formed by any of the known methods. For example in some embodiments, the grooves may be formed directly in the filter material, such as by heat forming of cellulose acetate filters. In other embodiments, the non-permeable inner plug-wrap may be shaped or embossed prior to being wrapped around a cylinder of filter material.

20

In some embodiments, continuous grooving is applied, by any suitable means, to a length of filter rod, which is subsequently segmented. In other embodiments, grooving is applied to pre-sized filter sections.

25

In some embodiments a layer of permeable plug-wrap may be used to further encapsulate the grooved filter section. This permeable plug-wrap may also function to combine two or more filter sections.

30

The barrier 9 may be formed by any suitable material and/or mechanism. For example, one option is to apply a spot or band of glue or other non-permeable material into each groove 7. Another option is to provide an annulus of non-permeable material, e.g. plastic, that goes around near the circumference of the filter 5, and separates (and blocks off) the

grooves 7 from the tobacco-end filter section 5C. Another possibility is to provide barrier 9 by hot melt fusion of the filter material 11.

A further layer of perforated or non-perforated sheet material 15, commonly known as 5 tipping paper, is subsequently applied to the combined filter and overlays the outer plug-wrap. The tipping paper may be used to join the combined filter to the tobacco rod. The tipping paper may be adhered to the filter and the tobacco rod, by any suitable means, but may retain a largely non-adhered portion over the grooved section 5A.

10 In some embodiments, tipping paper perforations may be provided by means of a laser, or by other suitable means. Tipping paper may be perforated before or after being bound to the filter.

15 The tipping paper is adhered to the three filter sections using a skip gap gluing technique such that a largely glue free area is positioned between the ventilation holes and the plug-wrap overlying the grooves. It will be appreciated that using adhesives to join the three layers (inner plug-wrap, outer plug-wrap and tipping) together at the position where the ventilation holes occur would result in blocking of the airflows and therefore the area is left predominantly non-glued.

20

The skilled person will be aware of various modifications that may be made to the embodiments described above. Accordingly, the scope of the present invention is defined by the appended claims and their equivalents.

31511-20

- 13 -

CLAIMS:

1. A smoking article comprising a tobacco rod and a multi-section filter combined by means of a tipping paper containing ventilation holes, the multi-section filter comprising at least first and second filter sections, wherein the first filter section is at a mouth end of the filter and wherein the second filter section includes a set of grooves, the grooves extending from some of the ventilation holes along the second filter section towards but not into the first filter section, wherein the filter further comprises a barrier located at the end of each groove furthest away from the first filter section, such that entry into this end of the grooves is only via the ventilation holes, and wherein the first and second filter sections are combined by means of a porous plug-wrap.
2. The smoking article according to claim 1, wherein the grooves extend along the outside of the second filter section substantially parallel with a major axis of the filter.
3. The smoking article according to either of claims 1 or 2, wherein the grooves are substantially non-permeable along their length.
- 15 4. The smoking article according to any one of claims 1 to 3, wherein the body of the second filter section is separated from the grooves in said section by a non-permeable barrier.
5. The smoking article according to any one of claims 1 to 4, wherein at least one of the filter sections comprises adsorbent material.
- 20 6. The smoking article according to any one of claims 1 to 5, wherein the air enters the grooves from the ventilation holes via a permeable membrane.
7. The smoking article according to any one of claims 1 to 6, wherein the filter is arranged such that air passes through the ventilation holes, travels along the grooves towards the first filter section and exits the grooves into a body portion of the filter adjacent the first filter section.

31511-20

- 14 -

8. The smoking article according to any one of claims 1 to 7, wherein a groove extends from some of the ventilation holes, and wherein some of the ventilation holes are directed into a body portion of the filter section.
9. The smoking article according to claim 8, wherein the ventilation holes that are directed into the body portion are located near the ends of the grooves furthest away from the first filter section.
10. The smoking article according to claim 8, wherein the ventilation holes that are directed into the body portion are located near the ends of the grooves closest to the first filter section.
- 10 11. The smoking article according to any one of claims 1 to 10, wherein the ventilation holes are located more than 11mm from the mouth end of the first filter section.
12. The smoking article according to claim 11, wherein the ventilation holes are located about 12 to 25mm from the mouth end of the first filter section.
13. The smoking article according to any one of claims 1 to 12, wherein the grooves extend substantially the length of the second filter section.
14. The smoking article according to claim 1, wherein the barrier is provided by hot melt fusion of the filter material.
15. The smoking article according to claim 1, wherein the barrier is provided by glue applied to the end of each groove.
- 20 16. The smoking article according to claim 1, wherein the barrier is provided by an annular member located at the end of the second filter section furthest away from the first filter section.
17. The smoking article according to any one of claims 1 to 16, comprising three filter sections in an end-to-end arrangement, wherein the second filter section comprises the middle section of the filter.

31511-20

- 15 -

18. The smoking article according to any one of claims 1 to 17, wherein the second filter section has an inner plug-wrap within the porous plug-wrap, and wherein the inner plug-wrap is non-permeable.
19. A method of making a smoking article comprising combining a grooved filter section and a mouth-end filter section by overlaying the grooved filter section with a permeable plug-wrap, combining the grooved and mouth-end filter sections using a porous plug-wrap, and then overlaying the combined grooved and mouth-end filter sections with a tipping paper which contains ventilation holes, wherein the position of some or all of the ventilation holes corresponds to the position of the grooves, and wherein the grooves are blocked at the end opposite to the mouth end during the combining operation.
20. The method according to claim 19, wherein the grooved filter section is made by shaping a filter rod.
21. The method according to claim 19, wherein the grooved filter section is made by shaping a plug-wrap and wrapping the shaped plug-wrap around a filter rod.
- 15 22. The method according to any of claims 19 to 21, wherein the ventilation holes are formed using on-line or off-line perforation.
23. The method according to claim 19, wherein the blockage is done by addition of adhesive.
24. The method according to claim 19, wherein the blockage is done by hot melt of 20 the filter material.
25. The method according to claim 19, wherein the blockage is done by addition of an annular material at the end of the grooved filter section.

1/4




Fig. 1

2/4




Fig. 3




Fig. 2

3/4




Fig. 4a




Fig. 4b

