

[19]	INTELLECTUAL PROPERTY PHILIPPINES		
[12]	INVENTION PUBLICATION		
[11]	Publication Number:	12014502137	Document Code: B1
[22]	Publication Date:	1/12/2014	
[21]	Application Number:	12014502137	Document Code: A
[22]	Date Filed:	24/9/2014	
[54]	Title:	IMAGE CODING DEVICE, IMAGE CODING METHOD, IMAGE CODING PROGRAM, TRANSMISSION DEVICE, TRANSMISSION METHOD, TRANSMISSION PROGRAM, IMAGE DECODING DEVICE, IMAGE DECODING METHOD, IMAGE DECODING PROGRAM, RECEPTION DEVICE, RECEPTION METHOD, AND RECEPTION PROGRAM	
[71]	Applicant(s):	JVC KENWOOD CORP	
[72]	Inventor(s):	KUMAKURA TORU FUKUSHIMA SHIGERU	
[30]	Priority Data:	13/4/2012 JP20120092078	
[51]	International Class 8:		
[57]	Abstract:	<p>In a picture coding device that partitions differential information between a picture that is a coding target and a picture that is a prediction target into a plurality of sub blocks and codes the partitioned sub blocks in a predetermined sequence, a significant sub block information coding controller and a calculation encoder code significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero. A significant coefficient information coding controller and the calculation encoder code significant differential coefficient information that represents whether or not the value of the differential coefficient is zero. A differential coefficient value coding controller and the calculation encoder code the value of the differential coefficient.</p>	

IMAGE CODING DEVICE, IMAGE CODING METHOD, IMAGE CODING PROGRAM,
TRANSMISSION DEVICE, TRANSMISSION METHOD, TRANSMISSION PROGRAM,
IMAGE DECODING DEVICE, IMAGE DECODING METHOD, IMAGE DECODING
PROGRAM, RECEPTION DEVICE, RECEPTION METHOD, AND RECEPTION
PROGRAM

5

[TECHNICAL FIELD]

The present invention relates to a picture coding and decoding technology, and more particularly, to a technology for entropy coding and decoding of a residual signal.

10

[BACKGROUND ART]

In MPEG-4 AVC that is an international standard of moving picture coding, as an entropy coding system, context switching-type arithmetic coding called CABAC is employed. CABAC includes a plurality of variables called a context that stores the occurrence probability of information to be coded. An optimal context is selected from among neighboring coding information and is used for coding. In addition, since the occurrence probability is updated according to a coding process also in each context, the occurrence probability of coding information can be estimated with high accuracy, whereby efficient coding can be performed.

20

[CITATION LIST]

[PATENT LITERATURE]

25

Patent Literature 1: JP 2007-300517 A

[DISCLOSURE OF THE INVENTION]

In the MPEG-4 AVC, in addition to the estimation of the occurrence probability of information according to switching a context based on the neighboring decoded information, the occurrence probability according to a decoding result is learned.

5 The occurrence probability of information to be decoded can be optimized for each context, and accordingly, the improvement of the coding efficiency is realized. However, for all the significant differential coefficient information within the block to be processed, it is necessary to sequentially process

10 the calculation of context indexes and decoding of the significant differential coefficient information, and a calculation time is required.

In Patent Literature 1, a technique for decreasing a processing delay relating to decoding is disclosed by arranging

15 a context for a syntax element having a high occurrence frequency on a memory having a small access delay time. However, the technique disclosed in Patent Literature 1, does not resolve the dependency between the calculation of the context index and the decoding of a syntax element, and these processes cannot be

20 performed in a parallel manner and is not an essential solution for a processing delay.

The present invention is contrived in consideration of such a situation, and an object thereof is to provide a picture coding technology, in the differential coefficient coding/decoding,

25 realizing a context index calculation method having a small calculation amount by enabling a parallel process, having a simple

configuration, and being appropriate for real-time processing. In addition, another object thereof is to provide a picture coding and decoding technology having high coding efficiency by realizing the calculation of a context index referring to neighboring differential coefficient that are appropriate in terms of correlation.

In order to solve the problem, a picture coding device according to one aspect of the present invention is one that partitions differential information between a picture that is a coding target and a picture that is a prediction target into a plurality of sub blocks and codes the partitioned sub blocks in a predetermined sequence, and the picture coding device includes: a significant sub block information encoder (708, 701) that codes significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero; a significant differential coefficient information encoder (706, 701) that codes significant differential coefficient information that represents whether or not the value of the differential coefficient is zero; a differential coefficient value encoder (707, 701) that codes the value of the differential coefficient; and a context deriver (703) that derives an index based on the significant sub block information of a coded sub block that is neighboring to the sub block that is a coding target in the horizontal direction and the significant sub block information of a coded sub block that is neighboring in the vertical direction and derives a context used

for coding the significant differential coefficient information of the differential coefficient that is a coding target based on the index and the position of the differential coefficient that is the coding target in the sub block that is the coding target.

5 According to another aspect of the present invention, there is provided a picture coding method. This method is a picture coding method in which differential information between a picture that is a coding target and a picture that is a prediction target is partitioned into a plurality of sub blocks, and the partitioned
10 sub blocks are coded in a predetermined sequence, the picture coding method including: coding significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero; coding significant differential coefficient information that
15 represents whether or not the value of the differential coefficient is zero; coding the value of the differential coefficient; and deriving an index based on the significant sub block information of a coded sub block that is neighboring to the sub block that is a coding target in the horizontal direction and
20 the significant sub block information of a coded sub block that is neighboring in the vertical direction and deriving a context used for coding the significant differential coefficient information of the differential coefficient that is a coding target based on the index and the position of the differential
25 coefficient that is the coding target in the sub block that is the coding target.

According to a further another aspect of the present invention, there is provided a transmission device. This device is a transmission device including: a packet processing unit configured to obtain coding data by packetizing a bitstream that is coded by using a picture coding method in which differential information between a picture that is a coding target and a picture that is a prediction target is partitioned into a plurality of sub blocks, and the partitioned sub blocks are coded in a predetermined sequence; and a transmitter configured to transmit the packetized coding data. The picture coding method includes: coding significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero; coding significant differential coefficient information that represents whether or not the value of the differential coefficient is zero; coding the value of the differential coefficient; and deriving an index based on the significant sub block information of a coded sub block that is neighboring to the sub block that is a coding target in the horizontal direction and the significant sub block information of a coded sub block that is neighboring in the vertical direction and deriving a context used for coding the significant differential coefficient information of the differential coefficient that is a coding target based on the index and the position of the differential coefficient that is the coding target in the sub block that is the coding target.

According to a further another aspect of the present

invention, there is provided a transmission method. This method is a transmission method including: obtaining coding data by packetizing a bitstream that is coded by using a picture coding method in which differential information between a picture that is a coding target and a picture that is a prediction target is partitioned into a plurality of sub blocks, and the partitioned sub blocks are coded in a predetermined sequence; and transmitting the packetized coding data. The above-described picture coding method includes: coding significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero; coding significant differential coefficient information that represents whether or not the value of the differential coefficient is zero; coding the value of the differential coefficient; and deriving an index based on the significant sub block information of a coded sub block that is neighboring to the sub block that is a coding target in the horizontal direction and the significant sub block information of a coded sub block that is neighboring in the vertical direction and deriving a context used for coding the significant differential coefficient information of the differential coefficient that is a coding target based on the index and the position of the differential coefficient that is the coding target in the sub block that is the coding target.

According to an aspect of the present invention, there is provided a picture decoding device that decodes a bitstream in

which differential information between a picture that is a decoding target and a picture that is a prediction target is partitioned into a plurality of sub blocks, and the partitioned sub blocks are coded in a predetermined sequence. The picture
5 decoding device includes: a significant sub block information decoder (1008, 1001) configured to decode significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero; a significant differential coefficient information decoder (1006,
10 1001) configured to decode significant differential coefficient information that represents whether or not the value of the differential coefficient is zero; a differential coefficient value decoder (1007, 1001) configured to decode the value of the differential coefficient; and a context deriver (1003) configured
15 to derive an index based on the significant sub block information of a decoded sub block that is neighboring to the sub block that is a decoding target in the horizontal direction and the significant sub block information of a decoded sub block that is neighboring in the vertical direction and derive a context used
20 for decoding the significant differential coefficient information of the differential coefficient that is a decoding target based on the index and the position of the differential coefficient that is the decoding target in the sub block that is the decoding target.

25 According to another aspect of the present invention, there is provided a picture decoding method. This method is a picture

decoding method decoding a bitstream in which differential information between a picture that is a decoding target and a picture that is a prediction target is partitioned into a plurality of sub blocks, and the partitioned sub blocks are coded in a predetermined sequence. The picture decoding method includes: decoding significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero; decoding significant differential coefficient information that represents whether or not the value of the differential coefficient is zero; decoding the value of the differential coefficient; and deriving an index based on the significant sub block information of a decoded sub block that is neighboring to the sub block that is a decoding target in the horizontal direction and the significant sub block information of a decoded sub block that is neighboring in the vertical direction and deriving a context used for decoding the significant differential coefficient information of the differential coefficient that is a decoding target based on the index and the position of the differential coefficient that is the decoding target in the sub block that is the decoding target.

According to further another aspect of the present invention, there is provided a reception device. This device is a reception device that receives a bitstream in which a moving picture is coded and decodes the received bitstream. The reception device includes: a reception unit configured to receive

coding data obtained by packetizing a bitstream in which differential information between a picture that is a decoding target and a picture that is a prediction target is partitioned into a plurality of sub blocks, and the partitioned sub blocks are coded in a predetermined sequence; a restoration unit configured to restore the bitstream by performing packet processing of the received packetized coding data; a significant sub block information decoder (1008, 1001) configured to decode significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero from the restored bitstream; a significant differential coefficient information decoder (1006, 1001) configured to decode significant differential coefficient information that represents whether or not the value of the differential coefficient is zero from the restored bitstream; a differential coefficient value decoder (1007, 1001) configured to decode the value of the differential coefficient from the restored bitstream; and a context deriver (1003) configured to derive an index based on the significant sub block information of a decoded sub block that is neighboring to the sub block that is a decoding target in the horizontal direction and the significant sub block information of a decoded sub block that is neighboring in the vertical direction and derive a context used for decoding the significant differential coefficient information of the differential coefficient that is a decoding target based on the index and the position of the differential

coefficient that is the decoding target in the sub block that is the decoding target.

According to further another aspect of the present invention, there is provided a reception method. This method is a reception method receiving a bitstream in which a moving picture is coded and decoding the received bitstream. The reception method includes: receiving coding data obtained by packetizing a bitstream in which differential information between a picture that is a decoding target and a picture that is a prediction target is partitioned into a plurality of sub blocks, and the partitioned sub blocks are coded in a predetermined sequence; restoring the bitstream by performing packet processing of the received packetized coding data; decoding significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero from the restored bitstream; decoding significant differential coefficient information that represents whether or not the value of the differential coefficient is zero from the restored bitstream; decoding the value of the differential coefficient from the restored bitstream; and deriving an index based on the significant sub block information of a decoded sub block that is neighboring to the sub block that is a decoding target in the horizontal direction and the significant sub block information of a decoded sub block that is neighboring in the vertical direction and deriving a context used for decoding the significant differential coefficient information of the differential

coefficient that is a decoding target based on the index and the position of the differential coefficient that is the decoding target in the sub block that is the decoding target.

Furthermore, an arbitrary combination of the constituent
5 elements described above or a conversion of the representation of the present invention among a method, a device, a system, a recording medium, a computer program, and the like is also valid as an aspect of the present invention.

According to the present invention, coding of a
10 differential signal that is appropriate for real-time processing using a simple circuit configuration can be realized.

[BRIEF DESCRIPTION OF THE DRAWINGS]

FIG. 1 is a flowchart that illustrates a conventional decoding sequence of differential coefficients;

15 FIG. 2 is a flowchart that illustrates a conventional decoding sequence of sub block differential coefficients;

FIG. 3 is a flowchart that illustrates a conventional decoding sequence of significant differential coefficients;

FIG. 4 is a flowchart that illustrates a conventional
20 decoding sequence of differential coefficient values;

FIG. 5 is a block diagram that illustrates the configuration of a picture coding device, which is used for executing a method for coding differential coefficients, according to an embodiment;

FIG. 6 is a block diagram that illustrates the configuration
25 of a picture decoding device, which is used for executing a method for decoding differential coefficients, according to an

embodiment;

FIG. 7 is a diagram that illustrates the scanning sequence of sub block differential coefficients;

FIG. 8 is a block diagram that illustrates the detailed
5 configuration of the picture decoding device, which is illustrated in FIG. 6, according to a first example;

FIG. 9 is a diagram that illustrates the definition of a neighboring differential coefficient in the decoding sequence of significant differential coefficients illustrated in FIG. 3;

10 FIG. 10 is a diagram that illustrates the definition of a neighboring differential coefficient in the decoding sequence of significant differential coefficients illustrated in FIG. 4;

FIG. 11 is a diagram that illustrates the definition of a context in the decoding sequence of significant differential
15 coefficients illustrated in FIG. 4;

FIG. 12 is a diagram that illustrates a sub block partition of the differential coefficients;

FIG. 13 is a flowchart that illustrates the decoding sequence of differential coefficient values according to the
20 first example;

FIG. 14 is a diagram that illustrates the size of a coding block;

FIG. 15 is a block diagram that illustrates the detailed configuration of the picture coding device, which is illustrated
25 in FIG. 5, according to the first example;

FIG. 16 is a flowchart that illustrates the coding sequence

of differential coefficients according to the first example;

FIG. 17 is a flowchart that illustrates the coding sequence of sub block differential coefficients according to the first example;

5 FIG. 18 is a flowchart that illustrates the coding sequence of significant differential coefficients according to the first example;

FIG. 19 is a flowchart that illustrates the coding sequence of differential coefficient values according to the first
10 example;

FIG. 20 is a diagram that illustrates the configuration in which a sub block position is included in the calculation of the context of significant differential coefficient information;

FIG. 21 is a flowchart that illustrates the coding sequence
15 of significant differential coefficients according to a second example;

FIG. 22 is a flowchart that illustrates the decoding sequence of significant differential coefficients according to the second example;

20 FIG. 23 is a diagram that illustrates the definition of a context in the decoding sequence of significant differential coefficients according to the second example;

FIG. 24 is a flowchart that illustrates the coding sequence of significant differential coefficients according to a third
25 example; and

FIG. 25 is a flowchart that illustrates the decoding

sequence of significant differential coefficients according to the third example.

[BEST MODE FOR CARRYING OUT THE INVENTION]

5 First, technologies that are the premise of embodiments of the present invention will be described.

A technique of associating a plurality of contexts with each coding syntax and selecting a context based on the correlation among syntax elements can optimize code allocation, and thereby enabling efficient coding.

10 As an example of context switching entropy coding, the decoding sequence of a quantization orthogonal transform coefficient of a differential signal that is coded into the size of 16×16 will be described with reference to a flowchart illustrated in FIG. 1. FIG. 12 illustrates a quantization
15 orthogonal transform coefficient to be processed. Hereinafter, the quantization orthogonal transform coefficient will be referred to as a differential coefficient. In this sequence, a differential coefficient of 16×16 to be processed is partitioned into sub blocks 401 to 416 each having the size of 4×4 , and
20 scanning in units of sub blocks is performed first.

A sub block to be processed is determined in accordance with the scanning sequence to be described later (S101). When the scanning of all the sub blocks is completed, the decoding process of the differential coefficient ends. The scanning sequence of
25 sub blocks is denoted by reference numeral 902 illustrated in FIG.

7. The scanning sequence of sub blocks is denoted by reference numeral 902 illustrated in FIG. 7. In this sequence, scanning is started from a sub block disposed on the lower rightmost side of the differential coefficient region, scanning according to a rule of the lower right side to the upper left side and the upper right side to the upper left side is performed, and the scanning is completed at a sub block disposed on the upper leftmost side. Reference numeral 901 illustrated in FIG. 7 illustrates the scanning sequence of sub blocks using arrows. In a case where the scanning sequence illustrated in FIG. 7 is applied, in all the sub blocks to be processed, the scanning of sub blocks spatially positioned respectively on the right side and the lower side is in the completed state.

Referring back to the flowchart illustrated in FIG. 1, the decoding process of all the differential coefficient values of the sub block to be processed is performed (S102). After the decoding of the sub block differential coefficient values is completed, the process proceeds to step S101.

The decoding process of the sub block differential coefficient values will be described in detail with reference to a flowchart illustrated in FIG. 2.

Significant sub block information is decoded (S201). The significant sub block information is a one-bit flag used for representing the presence of a differential coefficient having a value other than "0" in a sub block to be processed. In a case where the significant sub block information is "1", it represents

that at least one differential coefficient having a value other than "0" is present in a sub block to be processed. On the other hand, in a case where the significant sub block information is "0", it represents that all the differential coefficients of a sub block to be processed are "0"s.

Subsequently, the value of the significant sub block information is determined (S202). When the significant sub block information has a value of "0", all the differential coefficient values of the sub block to be processed are set to "0" (S209), and the sub block differential coefficient value decoding process ends.

On the other hand, when the significant sub block information is "1", the decoding process of all the significant differential coefficient information of the sub block to be processed is performed (S203). The significant differential coefficient information is a one-bit flag used for representing that a differential coefficient value of a processing target position is not "0". In a case where the significant coefficient information is "1", it represents that the differential coefficient value of the processing target position is not "0". On the other hand, in a case where the significant coefficient information is "0", it represents that the differential coefficient value of the processing target position is "0". The decoding sequence of the significant differential coefficient information of a sub block will be described later in detail. After the decoding of all the significant differential

coefficient information of the sub block is completed, the process proceeds to the decoding of differential coefficient values that is performed in step S204.

Subsequently, the decoding process of differential
5 coefficient values is performed (S204). The decoding process of differential coefficient values will be described later in detail. After the completion of the decoding process of differential coefficient values, the process proceeds to step S101, and the scanning of the next sub block is performed.

10 [Sequence of Decoding Process of Significant Differential Coefficient]

The sequence of decoding of the significant differential coefficient information of the sub block that is performed in step S203 will be described with reference to a flowchart illustrated
15 in FIG. 3.

A sub block to be processed is determined in accordance with a predetermined scanning sequence (S301). The scanning sequence of differential coefficients within the sub block, similarly to the scanning sequence of the sub block in the differential
20 coefficient region, is assumed to follow the rule illustrated in FIG. 7.

A neighboring significant differential coefficient sum countCoeff that is the sum of the numbers of decoded differential coefficients, which are neighboring to the processing target
25 differential coefficient position, having values other than "0" is calculated (S302). FIG. 9 illustrates an example of the

differential coefficient position used for calculating the neighboring significant differential coefficient sum countCoeff. Reference numeral 202 denotes neighboring differential coefficients of a case where the processing target position is as denoted by reference numeral 201, and reference numeral 204 denotes neighboring differential coefficients of a case where the processing target position is as denoted by reference numeral 203. As illustrated in FIG. 9, five differential coefficients that are located respectively on the right side and the lower side of the processing target differential coefficient position and are neighboring to the processing target differential coefficient position are set as neighboring differential coefficients. Since the scanning sequence of differential coefficients follows the sequence illustrated in FIG. 7, the decoding of differential coefficients that belong to the same sub block as that of the processing target differential coefficient and are located respectively on the right side and the lower side of the processing target differential coefficient position is completed. Similarly, the decoding of the significant differential coefficients belonging to sub blocks located respectively on the right side and the lower side of the sub block to which the processing target position belongs is completed. The neighboring differential coefficient sum countCoeff is a variable used for estimating the occurrence probability of the significant differential coefficient. In accordance with the characteristics of a picture and the visual characteristics, as

the significant differential coefficient, "1" may be easily concentrated in the low region, and "0" may be easily concentrated in the high region. Since the significant differential coefficients have a spatial correlation, differential coefficients neighboring to the processing target position are set as targets for the calculation of the neighboring differential coefficient sum countCoeff. The neighboring differential coefficients representing the outside of the differential coefficient region are excluded from the calculation of the neighboring significant coefficient sum countCoeff.

Referring back to the flowchart illustrated in FIG. 3, it is determined whether the neighboring significant coefficient sum countCoeff is "0" (S303). In a case where the neighboring significant coefficient sum countCoeff is "0", a context index ctxIdx used for decoding the significant differential coefficient information is set to "0" (S304), and the significant differential coefficient information is decoded by using a context that corresponds to the context index ctxIdx. Then, the significant differential coefficient information is set to the differential coefficient value (S308).

In a case where the neighboring significant coefficient sum countCoeff is not "0", it is determined whether the neighboring significant coefficient sum countCoeff is smaller than or equal to "2" (S305). In a case where the neighboring significant coefficient sum countCoeff is smaller than or equal to "2", the context index ctxIdx used for decoding the significant

differential coefficient information is set to "1" (S306), and the significant differential coefficient information is decoded by using a context that corresponds to the context index `ctxIdx`. Then, the significant differential coefficient information is set
5 to the differential coefficient value (S308).

In a case where the neighboring significant coefficient sum `countCoeff` is not smaller than or equal to "2", in other words, in a case where the neighboring significant coefficient sum `countCoeff` is larger than or equal to "3", the context index `ctxIdx`
10 used for decoding the significant differential coefficient information is set to "2" (S307), and the significant differential coefficient information is decoded by using a context that corresponds to the context index `ctxIdx`. Then, the significant differential coefficient information is set to the differential
15 coefficient value (S308).

A context is a variable used for storing the occurrence probability of information to be decoded, and the assignment of a code word changes based on the occurrence probability represented by the context. In the example described above, three
20 contexts coding the significant differential coefficient are defined, and the context decoding the significant differential coefficient is determined based on the magnitude of the neighboring significant differential coefficient sum. It is set in advance such that, for a context corresponding to the context
25 index `ctxIdx = 0` at a time when the neighboring significant coefficient sum `countCoeff` is "0", the occurrence probability of

the significant coefficient information that is "0" is high, and, for a context corresponding to the context index $ctxIdx = 2$ at a time when the neighboring significant coefficient sum $countCoeff$ is larger than or equal to "3", the occurrence probability of the significant coefficient information that is "1" is high. For information of which the occurrence probability is high, the coding amount can be decreased, and accordingly, by increasing the estimation accuracy of the occurrence probability, the coding efficiency can be improved.

10 In MPEG-4 AVC, by performing switching between contexts based on neighboring decoded information, in addition to the estimation of the occurrence probability of information, the occurrence probability according to a decoding result is learned. Thus, the occurrence probability of information to be decoded for each context can be optimized, whereby the improvement of the coding efficiency is realized.

Generally, in orthogonally transformed components of a picture, information may be easily concentrated in the low region. In addition, since there is a low influence of the degradation of a high region component on visual characteristics, frequently, the high region component is roughly quantized for a practical use. Accordingly, the significant coefficient information tends to be concentrated in the low region component. The significant coefficient information has a high correlation with the neighboring significant coefficient, and it is reasonable to perform switching among contexts based on the number of pieces

of the neighboring significant coefficient information from the viewpoint of the coding efficiency.

[Differential Coefficient Value Decoding Process]

The decoding sequence of differential coefficient values of the sub block in step S204 of the flowchart illustrated in FIG. 2 will be described with reference to a flowchart illustrated in FIG. 13.

A sub block to be processed is determined in accordance with a predetermined scanning sequence (S501). The scanning sequence of differential coefficients disposed within a sub block, similarly to the scanning sequence of the significant differential coefficient information, is assumed to follow the rule illustrated in FIG. 7. When the scanning of all the differential coefficients of the sub block is completed, the decoding process of differential coefficient values is completed, and the process proceeds to the sequence (S101) of determining the next sub block.

Subsequently, it is determined whether or not the differential coefficient value of the processing target differential coefficient position is "0" (S502). In a case where the differential coefficient value of the processing target differential coefficient position is "0", the decoding of the differential coefficient value of the processing target differential coefficient position is completed, and the process proceeds to step S501.

In a case where the differential coefficient value of the

processing target differential coefficient position is "1", the absolute value of the differential coefficient of the processing target differential coefficient position is decoded (S503). In a case where this sequence is performed, it is determined that the differential coefficient value is not "0", and, as a bitstream, a code word corresponding to a value derived by decreasing one from the absolute value of the differential coefficient is coded. Accordingly, as the absolute value of the differential coefficient, a value derived by adding "1" to a value that is derived by performing entropy decoding of a code word is set.

Subsequently, the sign of the differential coefficient of the processing target differential coefficient position is decoded (S504). A differential coefficient value is determined based on the absolute value of the differential coefficient and the sign of the differential coefficient.

In the decoding sequence of the significant differential coefficient information described above, a differential coefficient 201 illustrated in FIG. 9, as is represented in the scanning sequence denoted by reference numeral 902 illustrated in FIG. 7, is scanned last in the sub block, and the scanning sequence thereof is 16 as is denoted by reference numeral 902 illustrated in FIG. 7. In addition, among the neighboring differential coefficients 202 of the differential coefficient 201, the scanning sequence of a position neighboring to the lower side of the differential coefficient 201 is 15 and is scanned immediately before the differential coefficient 201. Since the

context index `ctxIdx` that is necessary for decoding the significant differential coefficient information of the differential coefficient 201 is calculated based on the significant differential coefficient sum of the differential coefficients 202, the context index `ctxIdx` of the differential coefficient 201 cannot be determined until the decoding of the significant differential coefficient information of the differential coefficient 202 is completed. This means that it is necessary to process the calculation of the context index `ctxIdx` and the decoding of the significant differential coefficient information in order for all the significant differential coefficient information within the sub block, and a decrease in the time or the calculation amount through parallel processing cannot be obtained. Meanwhile, the occupancy rate of the differential coefficient in the bitstream is high, and the context index calculating process and the decoding process of the significant differential coefficient information have a long time and a large calculation amount occupied in the entire decoding process. In other words, the decoding process of the significant coefficient information is the most significant bottleneck in the real-time decoding process.

In Patent Literature 1, a technique for decreasing a processing delay relating to a decoding process by arranging a context for a syntax element having a high occurrence frequency in a memory having a short access delay time has been disclosed. However, the technique disclosed in Patent Literature 1 does not

solve the dependency between the calculation of a context index and the decoding of a syntax element and cannot perform the processes thereof in a parallel manner, whereby it cannot be an essential solution for the processing delay.

5 Thus, an embodiment of the present invention provides a picture coding technology that, in the coding/decoding of differential coefficients, eliminates the dependency between the calculation of context indexes and the coding/decoding of the significant differential coefficient information, realizes a
10 context index calculating method that can perform processes in a parallel manner and has a small amount of calculation, and has a simple circuit configuration so as to be appropriate for real-time processing. In addition, by realizing the calculation of context indexes performed with reference to neighboring
15 differential coefficients, which is appropriate in terms of the correlation, a picture coding technology having high coding efficiency is provided. Hereinafter, embodiments of the present invention will be described.

 In description presented below, a "block to be processed"
20 is a coding target block in the case of a coding process performed by a picture coding device and is a decoding target block in the case of a decoding process performed by a picture decoding device. In addition, a "processed block" is a decoded block of which coding has been completed in the case of a coding process performed by
25 the picture coding device and is a block of which decoding has been completed in the case of a decoding process performed by the

picture decoding device. Hereinafter, such a meaning will be used unless otherwise noted.

[Coding Device]

A preferred picture coding device according to the present invention will be described with reference to the drawings. FIG. 5 is a block diagram that illustrates the configuration of the picture coding device according to an embodiment. The picture coding device according to the embodiment includes: a subtractor 501; an orthogonal transformer/quantizer 502; an inverse quantizer/inverse transformer 503; an adder 504; a decoded picture memory 505; a predictor 506; a differential information encoder 507; a prediction information encoder 508; and a mode determiner 509.

The mode determiner 509 tentatively codes all the prediction candidates and determines prediction information that is optimal to each block of the picture. As the prediction information, a partitioned block size and a prediction mode representing an inter prediction or an intra prediction. In addition, in a case where the prediction mode is the inter prediction, motion information such as a motion vector and a reference picture index is included in the prediction information. On the other hand, in a case where the prediction mode is the intra prediction, an intra prediction mode is included in the prediction information. The mode determiner 509 gives the determined prediction information to the predictor 506 and the prediction information encoder 508.

The prediction information encoder 508 performs variable length coding of the input prediction information and outputs a bitstream of the prediction information.

5 The predictor 506 generates a predicted picture using the input prediction information and the decoded picture stored in the decoded picture memory 505 and gives the generated predicted picture to the subtractor 501.

10 The subtractor 501 generates a differential picture by subtracting the predicted picture from the original picture that is a coding target and gives the generated differential signal to the orthogonal transformer/quantizer 502.

15 The orthogonal transformer/quantizer 502 generates differential coefficients by performing an orthogonal transform and quantization of the differential picture and gives the generated differential coefficients to the inverse quantizer/inverse transformer 503 and the differential information encoder 507.

20 The differential information encoder 507 performs entropy coding of the differential coefficients and outputs a bitstream of the differential information.

25 The inverse quantizer/inverse transformer 503 generates a decoded differential signal by performing the inverse quantization and the inverse orthogonal transform of the differential coefficients received from the orthogonal transformer/quantizer 502 and gives the generated decoded differential signal to the adder 504.

The adder 504 generates a decoded picture by adding the predicted picture and the decoded differential signal and stores the generated decoded picture in the decoded picture memory 505.

[Decoding Device]

5 A preferred picture decoding device according to the present invention will be described with reference to the drawings. FIG. 6 is a block diagram that illustrates the configuration of the picture decoding device according to an embodiment. The picture decoding device according to the embodiment includes: a
10 differential information decoder 801; an inverse quantizer/inverse transformer 802; a prediction information decoder 803; an adder 804; a decoded picture memory 805; and a predictor 806.

The decoding process of the picture decoding device
15 illustrated in FIG. 6 corresponds to the decoding process arranged inside the picture coding device illustrated in FIG. 5. Accordingly, the configurations of the inverse quantizer/inverse transformer 802, the adder 804, the decoded picture memory 805, and the predictor 806 illustrated in FIG. 8 have functions
20 respectively corresponding to the configurations of the inverse quantizer/inverse transformer 503, the adder 504, the decoded picture memory 505, and the predictor 506 of the picture coding device illustrated in FIG. 5.

The prediction information decoder 803 generates
25 prediction information by performing entropy decoding of an input prediction information bitstream and gives the generated

prediction information to the predictor 806.

The predictor 806 generates a predicted picture by using the input prediction information and the decoded picture that is stored in the decoded picture memory 805 and gives the generated
5 predicted picture to the adder 804.

The differential information decoder 801 generates differential information by performing entropy decoding of the differential information. Then, the differential information decoder 801 gives the generated differential information to the
10 inverse quantizer/inverse transformer 802.

The inverse quantizer/inverse transformer 802 generates a decoded differential signal by performing the inverse quantization and the inverse orthogonal transform of the differential information received from the differential
15 information decoder 801 and gives the generated decoded differential signal to the adder 804.

The adder 804 generates a decoded picture by adding the predicted picture and the decoded differential signal together, stores the generated decoded picture in the decoded picture memory
20 805, and outputs the generated decoded picture.

The coding process and the decoding process of differential coefficients according to an embodiment of the present invention are respectively performed by the differential information encoder 507 of the motion picture coding device illustrated in
25 FIG. 5 and the differential information decoder 801 of the motion picture decoding device illustrated in FIG. 8. Hereinafter, the

coding process and the decoding process of the differential information according to an embodiment will be described in detail.

[Coding Block]

5 According to the embodiment, as illustrated in FIG. 14, the screen is hierarchically partitioned into rectangular blocks, and the blocks are processed in order according to a predetermined processing sequence. Each block that is partitioned will be referred to as a coding block. A block 1817 illustrated in FIG.
10 14 is a maximum unit of the partition according to the embodiment and will be referred to as a maximum coding block. In addition, a block 1816 illustrated in FIG. 14 is a minimum unit of the partition according to the embodiment and will be referred to as a minimum coding block. Hereinafter, the minimum coding block
15 will be described as a block of 4×4 pixels and the maximum coding block will be described as a block of 16×16 pixels.

[Prediction Block]

 Among the coding blocks, a unit in which the intra prediction is performed will be referred to as a prediction block. The
20 prediction block has several sizes as below that are larger than or equal to that of the minimum coding block and are smaller than or equal to that of the maximum coding block. In FIG. 14, blocks 1802, 1803, and 1804 are 16×16 blocks, blocks 1805, 1810, 1811, and 1801 are 8×8 blocks, and blocks 1806, 1807, 1808, and 1809
25 are 4×4 blocks. Blocks 1812, 1813, 1814, and 1815 are blocks

that have not been processed, and the coding block sizes thereof are not determined. In the coding sequence, an optimal prediction block size is determined, and blocks of the prediction block size are coded. In the decoding sequence, the prediction block size is derived from the bitstream. Hereinafter, the description will be presented with the prediction block being assumed as the processing unit.

[Processing Unit of Differential Coefficient]

While the unit in which the quantization and the orthogonal transform are performed is the same as the unit of the prediction block, in the coding process and the decoding process, the scanning is performed with the differential coefficient region being partitioned into a plurality of sub blocks. The size of the sub block is a size of 4×4 . FIG. 12 illustrates a differential coefficient region of a size of 16×16 . Here, reference numerals 401 to 416 represent sub blocks. However, the unit in which the quantization and the orthogonal transform are performed may be determined independently from the unit of the prediction block.

(First Example)

[Coding Sequence]

A first example of the method of coding the differential information according to an embodiment of the present invention will now be described. FIG. 15 is a block diagram that illustrates the detailed configuration of the differential information encoder 507, which is illustrated in FIG. 5, according to the first example. The differential information encoder 507 according to

the first example includes: an arithmetic encoder 701; a differential coefficient buffer 702; a coding controller 703; a context memory 704; and a scan controller 705. In addition, the coding controller 703 includes: a significant coefficient information coding controller 706; a differential coefficient value coding controller 707; and a significant sub block information coding controller 708.

Hereinafter, the coding sequence of differential coefficients will be described with reference to the flowcharts illustrated in FIGS. 16, 17, 18, and 19.

The scan controller 705 determines a sub block to be processed (S601). When the scanning of all the sub blocks is completed, the decoding process of differential coefficients ends. Reference numeral 902 represented in FIG. 7 illustrates the scanning sequence of sub blocks. In this sequence, scanning is started from a sub block disposed on the lower rightmost side of the differential coefficient region, scanning according to a rule of the lower right side to the upper left side and the upper right side to the upper left side is performed, and the scanning is completed at a sub block disposed on the upper leftmost side. As described above, the context is updated in accordance with the coding process. By taking this scanning sequence, a low region component in which a differential coefficient can easily occur is scanned after a high region component, and accordingly, there is an advantage in the process that the estimated accuracy of the occurrence probability of a differential coefficient of the low

region component is improved. Reference numeral 901 illustrated in FIG. 7 is a diagram that illustrates the scanning sequence of sub blocks using arrows. In a case where the scanning sequence illustrated in FIG. 7 is applied, the scanning of sub blocks spatially positioned respectively on the right side and the lower side of the sub block to be processed is in the completed state. The coding process of the sub block to be processed is performed (S602).

[Coding Sequence of Sub Block (S602)]

10 The significant sub block information coding controller 708 derives a sub block to be processed from the differential coefficient buffer 702. All the differential coefficients of the sub block are scanned, and, in a case where all the differential coefficient values are "0", the significant sub block information is set to "0". Otherwise (in a case where there is at least one differential coefficient value other than "0"), the significant sub block information is set to "1" (S701).

20 The significant sub block information coding controller 708 refers to differential coefficients that are neighboring to the sub block to be processed and are included in the sub block that has been decoded from the differential coefficient buffer 702 and determines a context index $ctxIdx$ used for coding the significant sub block information. Then, the significant sub block information coding controller 708 reads a context that corresponds to the context index $ctxIdx$ from the context memory 704. Then, the significant sub block information and the context

are transmitted to the arithmetic encoder 701. Then, arithmetic encoder 701 codes the significant sub block information using the context (S702).

The significant sub block information coding controller 708
5 determines the value of the significant sub block information (S703). When the significant sub block information is "0", the sub block differential coefficient value coding process ends, and the process proceeds to step S601.

When the significant sub block information is "1", the
10 coding process of all the significant differential coefficient information of the sub block to be processed is performed (S704). The coding sequence of the significant differential coefficient information will be described later in detail. After the coding of all the significant differential coefficient information of
15 the sub block ends, the process proceeds to the coding of differential coefficient values of step S704.

The differential coefficient value coding controller 707 performs the coding process of all the differential coefficient values of the sub block to be processed (S705). The coding
20 sequence of differential coefficient values of the sub block will be described later in detail. After the coding of all the differential coefficient values of the sub block is completed, the process proceeds to step S601.

[Sequence of Coding Process of Significant Differential
25 Coefficient Information (S704)]

The significant coefficient information coding controller

706 calculates a sum of differential coefficients, which have values other than "0", neighboring to the sub block to be processed, in other words, a neighboring significant coefficient sum countCoeff (S801). In this sequence, differential coefficients that belong to sub blocks spatially disposed respectively on the right side and the lower side of the sub block to be processed and are neighboring to the sub block to be processed are defined as neighboring differential coefficients.

FIG. 10 illustrates the positions of the neighboring differential coefficients. Reference numeral 301 represents a sub block to be processed, and reference numeral 302 represents the neighboring differential coefficients. A neighboring differential coefficient representing the outside of the differential coefficient region is excluded from the calculation of the neighboring significant coefficient sum countCoeff. A differential coefficient 303 that belongs to both sub blocks disposed on the right side and the left side of the sub block to be processed may be configured to be included in the neighboring differential coefficients or may be configured not to be included therein. In the configuration in which the differential coefficient 303 is included in the neighboring differential coefficients, the number of the neighboring differential coefficients increases, and the occurrence probability of the significant differential coefficient information can be estimated with high accuracy. On the other hand, in the configuration in which the differential coefficient 303 is not

included in the neighboring differential coefficients, the amount of calculation and the circuit scale can be decreased by reducing the adding process relating to the neighboring significant coefficient sum countCoeff and reducing the boundary determining
5 process of the differential coefficient region.

The significant coefficient information coding controller 706 determines differential coefficients that are the processing targets (S802). The scanning sequence of differential coefficients within the sub block, similarly to the scanning
10 sequence of sub blocks in the differential coefficient region, follows the rule represented in FIG. 7. When the scanning of all the significant differential coefficients of the sub block is completed, the coding process of the significant differential coefficients is completed, and the process proceeds to the coding
15 sequence (S704) of differential coefficient values.

The significant coefficient information coding controller 706 determines whether or not the neighboring significant coefficient sum countCoeff is "0" (S803).

In a case where the neighboring significant coefficient sum
20 countCoeff is "0", the processing target differential coefficient position within the sub block to be processed is determined (S804). Here, it is represented such that a horizontal differential coefficient position is posX, a vertical differential coefficient position is posY, and the processing target differential
25 coefficient position is $pos = posX + posY$. In a case where $pos \leq 2$, a context index ctxIdx used for coding the significant

coefficient information is set to "1" (S805). Otherwise ($pos > 2$), the context index $ctxIdx$ is set to "0" (S806). The definition of the context index $ctxIdx$ of a case where $countCoeff = 0$ is denoted by reference numeral 601 in FIG. 11.

5 When the neighboring significant coefficient sum $countCoeff$ is not "0", it is determined whether or not the neighboring significant coefficient sum $countCoeff$ is smaller than or equal to "1" (S807). In a case where the neighboring significant coefficient sum $countCoeff$ is smaller than or equal
10 to "1", the processing target differential coefficient position within the sub block to be processed is determined (S408). In a case where the processing target differential coefficient position $pos \leq 3$, the context index $ctxIdx$ used for decoding the significant coefficient information is set to "1" (S809).
15 Otherwise ($pos > 3$), the context index $ctxIdx$ is set to "0" (S810). The definition of the context index $ctxIdx$ of a case where $countCoeff = 1$ is denoted by reference numeral 602 in FIG. 11.

 When the neighboring significant coefficient sum $countCoeff$ is not smaller than or equal to "1", it is determined
20 whether or not the neighboring significant coefficient sum $countCoeff$ is smaller than "2" (S811). In a case where the neighboring significant coefficient sum $countCoeff$ is smaller than or equal to "2", the processing target differential coefficient position within the sub block to be processed is
25 determined (S812). In a case where the processing target differential coefficient position $pos \leq 2$, the context index

ctxIdx used for decoding the significant coefficient information is set to "2" (S813). Otherwise (pos > 2), the context index ctxIdx is set to "1" (S814). The definition of the context index ctxIdx of a case where the neighboring significant coefficient sum countCoeff = 2 is denoted by reference numeral 603 in FIG. 11.

When the neighboring significant coefficient sum countCoeff is not smaller or equal to "2", the context index ctxIdx used for decoding the significant coefficient information is set to "2" (S815). The definition of the context index ctxIdx of a case where the neighboring significant coefficient sum countCoeff > 2 is denoted by reference numeral 605 in FIG. 11.

The significant coefficient information coding controller 706 derives the differential coefficient of the processing target position from the differential coefficient buffer 702. In a case where the differential coefficient value is not "0", the significant differential coefficient information is set to "1". Otherwise (in a case where the differential coefficient value is "0"), the significant differential coefficient information is set to "0" (S816).

After a context corresponding to the determined context index ctxIdx is read from the context memory 704, the significant coefficient information coding controller 706 transmits the significant differential coefficient information and the context to the arithmetic encoder 701. The arithmetic encoder 701 codes the significant differential coefficient information using the

context (S817).

[Differential Coefficient Value Coding Process (S705)]

The differential coefficient value coding controller 707 determines a differential coefficient that is the processing target (S901). The scanning sequence of differential coefficients disposed within a sub block, similarly to the scanning sequence of the significant differential coefficients, is assumed to follow the rule illustrated in FIG. 7. When the scanning of all the differential coefficients of the sub block is completed, the coding process of differential coefficient values is completed, and the process proceeds to the sequence (S601) of determining the next sub block.

The differential coefficient value coding controller 707 determines whether or not the differential coefficient value of the processing target differential coefficient position is "0" (S902). In a case where the differential coefficient value of the processing target differential coefficient position is "0", the coding of the differential coefficient value of the processing target differential coefficient position is completed, and the process proceeds to step S901.

In a case where the differential coefficient value of the processing target differential coefficient position is "not 0", the absolute value of the coded differential coefficient of the processing target differential coefficient position and the sign are calculated (S903 and S904). When this sequence is performed, the differential coefficient value is determined not to be "0".

Accordingly, the absolute value of the coded differential coefficient is set as a value derived by decreasing one from the absolute value of the differential coefficient. In addition, in a case where the differential coefficient is positive, the sign is set to "0". On the other hand, in a case where the differential coefficient is negative, the sign is set to "1".

After the context is read from the context memory 704, the differential coefficient value coding controller 707 transmits a coding absolute value and the context to the arithmetic encoder 701. The arithmetic encoder 701 codes the coding absolute value using the context (S905).

After the context is read from the context memory 704, the differential coefficient value coding controller 707 transmits a sign and the context to the arithmetic encoder 701. The arithmetic encoder 701 codes the coding absolute value using the context (S905).

[Decoding Sequence]

A method of decoding differential coefficients according to a first example of the embodiment of the present invention will be described. FIG. 8 is a block diagram that illustrates the detailed configuration of the differential information decoder 801, which is illustrated in FIG. 6, according to the first example. The differential information decoder 801 according to the first example includes: an arithmetic decoder 1001; a differential coefficient buffer 1002; a decoding controller 1003; a context memory 1004; and a scan controller 1005. In addition, the

decoding controller 1003 includes: a significant coefficient information decoding controller 1006; a differential coefficient value decoding controller 1007; and a significant sub block information decoding controller 1008.

5 Since the differential information decoding process performed by the differential information decoder 801 illustrated in FIG. 8 corresponds to the differential information coding process performed by the differential information encoder 507 illustrated in FIG. 5, the configurations of the differential
10 coefficient buffer 1002, the context memory 1004, and the scan controller 1005 of the differential information encoder illustrated in FIG. 8 respectively have functions corresponding to the configurations of the differential coefficient buffer 702, the context memory 704, and the scan controller 705 illustrated
15 in FIG. 15.

Hereinafter, the decoding sequence of the differential information will be described with reference to the flowcharts illustrated in FIGS. 1, 2, 4, and 13.

The scan controller 1005 determines a sub block to be
20 processed (S101). When the scanning of all the sub blocks is completed, the decoding process of differential coefficients ends. Reference numeral 902 represented in FIG. 7 illustrates the scanning sequence of sub blocks. In this sequence, scanning is started from a sub block disposed on the lower rightmost side of
25 the differential coefficient region, scanning according to a rule of the lower right side to the upper left side and the upper right

side to the upper left side is performed, and the scanning is completed at a sub block disposed on the upper leftmost side. Reference numeral 901 represented in FIG. 7 illustrates the scanning sequence of sub blocks using arrows. In a case where
5 the scanning sequence illustrated in FIG. 7 is applied, the scanning of sub blocks spatially positioned respectively on the right side and the lower side of the sub block to be processed is in the completed state. The decoding process of the sub block to be processed is performed (S102).

10 [Sub Block Decoding (S102)]

The significant sub block information decoding controller 1008 refers to differential coefficients that are neighboring to the sub block to be processed and are included in the sub block that has been decoded from the differential coefficient buffer
15 1002, determines a context used for decoding the significant sub block information, and reads the determined context from the context memory 1004. The significant sub block information decoding controller 1008 transmits a decoding command together with the context to the arithmetic decoder 1001. The arithmetic
20 decoder 1001 performs the decoding process of a bitstream by using the context, thereby decoding the significant sub block information (S201).

The significant sub block information decoding controller 1008 determines the value of the significant sub block information
25 (S202). When the significant sub block information is "0", all the differential coefficient values of the processing target sub

block stored in the differential coefficient buffer 1002 are set to "0" (S209), and the decoding process of sub block differential coefficient values ends.

When the significant sub block information is "1", the
5 decoding process of all the significant differential coefficient information of the sub block to be processed is performed (S203). The sequence of decoding of the significant differential coefficient information of a sub block will be described later in detail. After the decoding of all the significant differential
10 coefficient information of the sub block is completed, the process proceeds to the decoding of differential coefficient values of step S204.

Subsequently, the decoding process of all the differential coefficient values of the sub block to be processed is performed
15 (S204). The sequence of the decoding of the differential coefficient values of the sub block will be described later in detail. After the decoding of all the differential coefficient values of the sub block is completed, the process proceeds to step S101.

20 [Sequence of Decoding Process of Significant Differential Coefficient Information (S203)]

The significant coefficient information decoding controller 1006 calculates a sum countCoeff of the number of the neighboring significant differential coefficients of the
25 processing target differential coefficient position (S401). In this sequence, differential coefficients that belong to sub

blocks spatially disposed respectively on the right side and the lower side of the sub block to be processed and are neighboring to the sub block to be processed are defined as neighboring differential coefficients.

5 FIG. 10 illustrates the positions of the neighboring differential coefficients. Reference numeral 301 represents a sub block to be processed, and reference numeral 302 represents the neighboring differential coefficients. A neighboring differential coefficient representing the outside of the
10 differential coefficient region is excluded from the calculation of the neighboring significant coefficient sum countCoeff. A differential coefficient 303 that belongs to both sub blocks disposed on the right side and the lower side of the sub block to be processed may be configured to be included in the neighboring
15 differential coefficients or may be configured not to be included therein. In the configuration in which the differential coefficient 303 is included in the neighboring differential coefficients, the number of the neighboring differential coefficients increases, and the occurrence probability of the
20 significant differential coefficient information can be estimated with high accuracy. On the other hand, in the configuration in which the differential coefficient 303 is not included in the neighboring differential coefficients, the amount of calculation and the circuit scale can be decreased by reducing
25 the adding process relating to the neighboring significant coefficient sum countCoeff and reducing the boundary determining

process of the differential coefficient region.

The significant coefficient information decoding controller 1006 determines differential coefficients that are the processing targets (S402). The scanning sequence of differential coefficients within the sub block, similarly to the scanning sequence of sub blocks in the differential coefficient region, follows the rule represented in FIG. 7. When the scanning of all the significant differential coefficients of the sub block is completed, the decoding process of the significant differential coefficients is completed, and the process proceeds to the decoding sequence (S204) of differential coefficient values.

The significant coefficient information decoding controller 1006 determines whether or not the neighboring significant coefficient sum countCoeff is "0" (S403). In a case where the neighboring significant coefficient sum countCoeff is "0", the processing target differential coefficient position within the sub block to be processed is determined (S404). Here, it is represented such that a horizontal differential coefficient position is posX, a vertical differential coefficient position is posY, and the processing target differential coefficient position is $pos = posX + posY$. In a case where $pos \leq 2$, a context index ctxIdx used for decoding the significant coefficient information is set to "1" (S405). Otherwise ($pos > 2$), the context index ctxIdx is set to "0" (S406). The definition of the context index ctxIdx of a case where countCoeff = 0 is denoted by reference

numeral 601 in FIG. 11. After the determined context is read from the context memory 1004, a decoding command is transmitted to the arithmetic decoder 1001 together with the context. The arithmetic decoder 1001 performs a decoding process of a bitstream using the context, thereby decoding the significant differential coefficient information (S416).

When the neighboring significant coefficient sum countCoeff is not "0", it is determined whether or not the neighboring significant coefficient sum countCoeff is smaller than or equal to "1" (S407). In a case where the neighboring significant coefficient sum countCoeff is smaller than or equal to "1", the processing target differential coefficient position within the sub block to be processed is determined (S408). In a case where the processing target differential coefficient position $pos \leq 3$, the context index ctxIdx used for decoding the significant coefficient information is set to "1" (S409). Otherwise ($pos > 3$), the context index ctxIdx is set to "0" (S410). The context index ctxIdx of a case where countCoeff = 1 is denoted by reference numeral 602 in FIG. 11. After the determined context is read from the context memory 1004, a decoding command is transmitted to the arithmetic decoder 1001 together with the context. The arithmetic decoder 1001 performs a decoding process of a bitstream using the context, thereby decoding the significant differential coefficient information (S416).

When the neighboring significant coefficient sum countCoeff is not smaller than or equal to "1", it is determined

whether or not the neighboring significant coefficient sum
countCoeff is smaller than or equal to "2" (S411). In a case where
the neighboring significant coefficient sum countCoeff is smaller
than or equal to "2", the processing target differential
5 coefficient position within the sub block to be processed is
determined (S412). In a case where the processing target
differential coefficient position $pos \leq 2$, the context index
ctxIdx used for decoding the significant coefficient information
is set to "2" (S413). Otherwise ($pos > 2$), the context index
10 ctxIdx is set to "1" (S414). The definition of the context index
ctxIdx of a case where the neighboring significant coefficient
sum countCoeff = 2 is denoted by reference numeral 603 in FIG.
11. After the determined context is read from the context memory
1004, a decoding command is transmitted to the arithmetic decoder
15 1001 together with the context. The arithmetic decoder 1001
performs a decoding process of a bitstream using the context,
thereby decoding the significant differential coefficient
information (S416).

When the neighboring significant coefficient sum
20 countCoeff is not smaller or equal to "2", the context index ctxIdx
used for decoding the significant coefficient information is set
to "2" (S415). The definition of the context index ctxIdx of a
case where the neighboring significant coefficient sum countCoeff
> 2 is denoted by reference numeral 605 in FIG. 11. After the
25 determined context is read from the context memory 1004, a
decoding command is transmitted to the arithmetic decoder 1001

together with the context. The arithmetic decoder 1001 performs a decoding process of a bitstream using the context, thereby decoding the significant differential coefficient information (S416).

5 When the neighboring significant coefficient sum countCoeff is large, there is a high possibility that all the significant coefficient information within the sub block to be processed is "1". Accordingly, in the above-described sequence, in a case where the neighboring significant coefficient sum
10 countCoeff is larger than or equal to "3", the context index ctxIdx is set to "2" regardless of the value of the processing target differential coefficient position pos. In addition, the determination criterion for the neighboring significant coefficient sum countCoeff may be subdivided. For example, in
15 a case where the neighboring significant coefficient countCoeff is larger than or equal to "3", when the neighboring significant coefficient sum countCoeff is "3", the definition of the context index that is denoted by reference numeral 604 illustrated in FIG.
11 is configured to be taken, and, when the neighboring
20 significant coefficient sum countCoeff is larger than or equal to "4", the definition of the context index that is denoted by reference numeral 605 illustrated in FIG. 11 is configured to be taken. In a case where such a configuration is taken, the correlation use efficiency of the neighboring information is
25 improved, and accordingly, the coding efficiency can be improved.

In this sequence, for the calculation of the context index

ctxIdx used for the significant differential coefficient information, a sum of the numbers of pieces of the significant coefficient information of the decoded neighboring sub block and the position of the processing target differential coefficient within the sub block are referred to. Hereinafter, the reason for taking such a configuration will be described.

Generally, the orthogonal transform coefficients of a picture may be easily concentrated in the low region component, and there is a high possibility that the significant coefficient information is "1". In addition, since it is difficult for the high region component of the orthogonal transform coefficient to receive a visual influence, the high region component is quantized in a rough manner in many cases, and accordingly, there is a high possibility that the coefficient value of the high region component is "0", and the significant coefficient information of the high region component is "0". Such a characteristic is not limited to the entire differential coefficient region but is the same for each sub block, and it can be regarded that, for a component present on the low region side of the sub block, a probability that the significant coefficient information is "1" is higher than that for a component present on the high region side of the same sub block. Setting the value of the context index ctxIdx of the significant differential coefficient information presented in the low region within the sub block to be larger than the value of the context index ctxIdx of the significant differential coefficient information present in the high region

leads to the improvement of the estimation accuracy of the occurrence probability of the significant coefficient information. In addition, the neighboring significant coefficient sum tends to be small in the high region in which the probability that the significant differential coefficient is "0" is high, and the neighboring significant coefficient sum tends to increase in the low region in which the probability that the significant differential coefficient is "1" is high. Thus, by using the neighboring significant coefficient sum as an index representing the degree of inclusion of the significant differential coefficient information in the sub block to be processed improves the estimation accuracy of the occurrence probability of the significant coefficient information.

In this sequence, by calculating the neighboring significant differential coefficient sum for the sub block once, the context indexes of all the coefficient positions within the sub block can be calculated. Thus, compared to a method in which the neighboring significant differential coefficient sum is calculated at each coefficient position, the amount of calculation of the neighboring significant differential coefficient sum can be reduced. In addition, in a configuration in which a decoding result of the prior significant differential coefficient in the scanning sequence is used for the calculation of the context index, it is necessary to sequentially process the calculation of the context indexes within the sub block and the decoding of the significant differential coefficient. In this

example, while the neighboring significant differential coefficient sum and the processing target coefficient position are referred to for the calculation of context indexes, the differential coefficient belonging to the processing target sub block is not targeted for the neighboring significant differential coefficient sum, and accordingly, there is no dependency within the sub block for the calculation of context indexes. Since the context indexes for all the significant differential coefficients can be calculated from the start of the sub block, the calculation of the context indexes can be performed in parallel with the decoding process of the significant differential coefficient information. Thus, a processing delay relating to the decoding of significant coefficient information having a high occurrence frequency in the bitstream can be decreased.

The context calculation may be performed by referring to the significant sub block information instead of the neighboring significant coefficient. In addition, compared to a configuration in which the neighboring significant coefficient sum is obtained, the amount of calculation and the circuit scale can be reduced. In addition, the position of the sub block can be reflected on the context calculation. As described above, the low region component has a characteristic having the occurrence probability of the significant coefficient to be higher than that of the high region. By reflecting the position of the sub block on the context calculation, context estimation having higher

accuracy can be realized. FIG. 20 illustrates an example in which the differential coefficient region is classified into two areas including a low-region area and a high-region area. In FIG. 20, areas denoted by reference numerals 1101, 1102, 1103, 1104, 1105, 5 and 1109 are low region components, and areas denoted by reference numerals 1106, 1107, 1108, 1110, 1111, 1112, 1113, 1114, 1115, and 1116 are high-region areas. After the context indexes `ctxIdx` are calculated in the above-described sequence for the high-region areas, predetermined offsets corresponding to the 10 positions of sub blocks may be configured to be added to the context indexes `ctxIdx` described above for the low-region areas, or a conditional branch according to the position of the sub block may be configured to be added during the calculation of the context indexes `ctxIdx` described above. In addition, after the context 15 indexes `ctxIdx` are calculated in the above-described sequence for the low-region areas, for the high-region area, generally, there is a high possibility that the significant differential coefficient is "0", and the number of the neighboring significant differential coefficients may easily include an error in the 20 probability estimation, and accordingly, a configuration in which the context `ctxIdx = 0` is constantly set may be employed.

In addition, the context indexes may be calculated by using the sum of the absolute values of neighboring coefficients instead of the neighboring significant differential coefficient sum. 25 Generally, the absolute value of the differential coefficient of the low-region component is large, and accordingly, by setting

a context in which the occurrence probability of the significant differential coefficient information increases in a case where the sum of the absolute values of the neighboring differential coefficients is large, the coding efficiency can be improved.

5 Furthermore, by adding the prediction mode used at the time of calculating the differential coefficients to the condition determination performed during the sequence of calculating the context indexes of the significant differential coefficients, the accuracy of the context estimation can be improved. The reason
10 for this is that, generally, compared to an intra prediction in which only a decoded area of a decoding target picture is set as a reference target, an inter prediction capable of referring to a plurality of decoded pictures has characteristics that the prediction accuracy is high and a differential cannot easily
15 occur.

[Decoding Process of Differential Coefficient Value
(S204)]

The significant coefficient information decoding controller 1006 determines differential coefficients that are the
20 processing targets (S501). The scanning sequence of differential coefficients within the sub block, similarly to the scanning sequence of the significant differential coefficients, follows the rule represented in FIG. 7. When the scanning of all the differential coefficients of the sub block is completed, the
25 decoding process of the differential coefficients is completed, and the process proceeds to the sequence (S101) of determining

the next sub block.

The significant coefficient information decoding controller 1006 determines whether or not the differential coefficient value of the processing target differential coefficient position is "0" (S502). In a case where the differential coefficient value of the processing target differential coefficient position is "0", the decoding of the differential coefficient value of the processing target differential coefficient position is completed, and the process proceeds to step S501.

In a case where the differential coefficient value of the processing target differential coefficient position is "1", the absolute value of the differential coefficient of the processing target differential coefficient position is decoded (S503). In a case where this sequence is performed, it is determined that the differential coefficient value is not "0", and, as a bitstream, a code word corresponding to a value derived by decreasing one from the absolute value of the differential coefficient is decoded. Accordingly, as the absolute value of the differential coefficient, a value derived by adding "1" to a value that is derived by performing entropy decoding of a code word is set.

Subsequently, the sign of the differential coefficient of the processing target differential coefficient position is decoded (S504). A differential coefficient value is determined based on the absolute value of the differential coefficient and the sign of the differential coefficient.

In this example, while a context index used for decoding the significant differential coefficient information is calculated based on the significant differential coefficient information of the decoded sub block, a similar sequence may be applied to the calculation of the context index of the differential coefficient value. Similarly to the significant differential coefficient information, the differential coefficient value has correlation with the neighboring coefficient values and has concentration in the low region component. Thus, by setting a context index representing a high occurrence probability of a large differential coefficient value when the neighboring significant differential coefficient sum or the sum of the absolute values of the neighboring differential coefficients is large and setting a context index representing a high occurrence probability of a small differential coefficient value when the neighboring significant differential coefficient sum or the sum of the absolute values of the neighboring differential coefficients is small, the differential coefficient values can be efficiently coded.

According to the picture coding device and the picture decoding device of the first example described above, the following operations and advantages are obtained.

(1) The context index of the processing target differential coefficient can be calculated based on differential coefficients belonging to a decoded sub block that is neighboring to the sub block, to which the processing target differential coefficient

belong. By setting a context that estimates the occurrence probability of the significant differential coefficient information of "1" to be high when the neighboring significant differential coefficient sum is large and estimates the occurrence probability of the significant differential coefficient information of "0" to be high when the neighboring significant differential coefficient sum is small, an appropriate probability model that is based on the neighboring correlation of the significant differential coefficient information can be set. Accordingly, the significant differential coefficient information can be efficiently coded.

(2) The context index is calculated based on the position of the processing target differential coefficient within the sub block. A context is set, which estimates the differential coefficient disposed in the low region within the sub block to have an occurrence probability of the significant differential coefficient of "1" to be higher than the differential coefficient disposed in the high region within the sub block. Thus, a probability model that is based on the characteristics of the significant differential coefficient information on the frequency domain can be set, and the significant differential coefficient information can be efficiently coded.

(3) The calculation of the neighboring significant differential coefficient sum and the position of the processing target differential coefficient within the sub block do not depend on a decoding result of the significant differential coefficient

information within the sub block. Accordingly, a configuration can be employed in which the calculation of the context index within the sub block and the decoding of the significant differential coefficient information are processed in a parallel manner, and therefore, a processing delay relating to the decoding process of the significant differential coefficient information can be reduced. Accordingly, the differential coefficients decrease a processing delay of the significant differential coefficient information having a high occupancy rate in the bitstream and having a large number of processes, and therefore, a decoding device that is appropriate for real-time processing can be realized. In addition, also in the coding device, a processing delay of the coding of the significant differential coefficient information can be similarly decreased.

(4) The significant differential coefficient sum relating to the calculation of the context index of the significant differential coefficient information does not depend on the position of the processing target differential coefficient, and accordingly, the significant differential coefficient sum may be calculated once for the sub block. Accordingly, compared to a configuration in which each neighboring significant differential coefficient sum is calculated in accordance with the position of the processing target differential coefficient, the amount of calculation relating to the calculation of the context indexes can be decreased.

(Second Example)

A second example of the method of coding the differential information according to an embodiment of the present invention will now be described. A differential information encoder 507 according to the second example, similarly to the differential information encoder 507 according to the first example illustrated in FIG. 15, includes: an arithmetic encoder 701; a differential coefficient buffer 702; a coding controller 703; a context memory 704; and a scan controller 705. In addition, the coding controller 703 includes: a significant coefficient information coding controller 706; a differential coefficient value coding controller 707; and a significant sub block information coding controller 708.

The coding sequence of the differential information according to this example is the same as that of the first example except for the sequence (S704 illustrated in FIG. 17) of the coding process of the significant differential coefficient information, and thus, hereinafter, the sequence of the coding process of the significant differential coefficient information according to this example will be described with reference to a flowchart illustrated in FIG. 21.

[Sequence of Coding Process of Significant Differential Coefficient Information (S704)]

The significant coefficient information coding controller 706 derives the significant sub block information of decoded sub blocks that are respectively neighboring to the right side and the lower side of a sub block to be processed. It is set such

that the significant sub block information of the sub block neighboring to the right side is sigGroupRight, and the significant sub block information of the sub block neighboring to the lower side is sigGroupBottom (S1001).

5 The significant coefficient information coding controller 706 determines differential coefficients that are the processing targets (S1002). The scanning sequence of differential coefficients within the sub block, similarly to the scanning sequence of sub blocks in the differential coefficient region,
10 follows the rule represented in FIG. 7. When the scanning of all the significant differential coefficients of the sub block is completed, the coding process of the significant differential coefficients is completed, and the process proceeds to the coding sequence (S704) of differential coefficient values.

15 The significant coefficient information coding controller 706 evaluates the significant sub block information sigGroupRight and the significant sub block information sigGroupBottom (S1003).

 In a case where both the significant sub block information sigGroupRight and the significant sub block information sigGroupBottom are "0", the position of the processing target differential coefficient within the sub block to be processed is determined (S1004). Here, it is represented such that a horizontal differential coefficient position is posX, a vertical differential coefficient position is posY, and the processing
20 target differential coefficient position is $pos = posX + posY$.
25 In a case where $pos \leq 2$, a context index ctxIdx used for coding

the significant coefficient information is set to "1" (S1005).
Otherwise ($pos > 2$), the context index `ctxIdx` is set to "0" (S1006).
The definition of the context index `ctxIdx` of a case where both
the significant sub block information `sigGroupRight` and the
5 significant sub block information `sigGroupBottom` are "0" is
denoted by reference numeral 1201 in FIG. 23.

In a case where both the significant sub block information
`sigGroupRight` and the significant sub block information
`sigGroupBottom` are not "0", it is determined whether the
10 significant sub block information `sigGroupRight` is "1" and the
significant sub block information `sigGroupBottom` is "0" (S1007).
In a case where the significant sub block information
`sigGroupRight` is "1" and the significant sub block information
`sigGroupBottom` is "0", the position of the processing target
15 differential coefficient within the sub block to be processed is
determined (S1008). In a case where the vertical differential
coefficient position $posY \leq 1$, the context index `ctxIdx` used for
decoding the significant coefficient information is set to "1"
(S1009). Otherwise ($posY > 2$), the context index `ctxIdx` is set
20 to "0" (S1010). The definition of the context index `ctxIdx` of
a case where the significant sub block information `sigGroupRight`
is "1" and the significant sub block information `sigGroupBottom`
is "0" is denoted by reference numeral 1202 in FIG. 23.

When the significant sub block information `sigGroupRight`
25 and the significant sub block information `sigGroupBottom` are not
respectively "1" and "0", it is determined whether the significant

sub block information sigGroupRight and the significant sub block information sigGroupBottom are respectively "0" and "1" (S1011). In a case where the significant sub block information sigGroupRight and the significant sub block information sigGroupBottom are respectively "0" and "1", the position of the processing target differential coefficient within the sub block to be processed is determined (S1012). In a case where the horizontal differential coefficient position $posX \leq 1$, the context index ctxIdx used for decoding the significant coefficient information is set to "1" (S1013). Otherwise ($posX > 2$), the context index ctxIdx is set to "0" (S1014). The definition of the context index ctxIdx of a case where the significant sub block information sigGroupRight is "0" and the significant sub block information sigGroupBottom is "1" is denoted by reference numeral 1203 in FIG. 23. In other words, the sequence of setting the context index ctxIdx of a case where the significant sub block information sigGroupRight is "0" and the significant sub block information sigGroupBottom is "1" is a process in which the X-direction process and the Y-direction process of a case where the significant sub block information sigGroupRight is "1" and the significant sub block information sigGroupBottom is "0" are interchanged. For this reason, the process can be configured to be common, and the circuit scale of the hardware or the coding amount of the software can be reduced.

When the significant sub block information sigGroupRight and the significant sub block information sigGroupBottom are not

respectively "0" and "1", in other words, when the significant sub block information sigGroupRight and the significant sub block information sigGroupBottom are respectively "1" and "1", the position of the processing target differential coefficient within the sub block to be processed is determined (S1015). In a case where the processing target differential coefficient position $pos \leq 4$, the context index ctxIdx used for decoding the significant coefficient information is set to "2" (S1016). Otherwise ($pos > 5$), the context index ctxIdx is set to "1" (S1017). The definition of the context index ctxIdx of a case where the significant sub block information sigGroupRight is "0" and the significant sub block information sigGroupBottom is "1" is denoted by reference numeral 1204 in FIG. 23.

The significant coefficient information coding controller 706 derives the differential coefficient of the processing target position from the differential coefficient buffer 702. In a case where the differential coefficient value is not "0", the significant differential coefficient information is set to "1". Otherwise (in a case where the differential coefficient value is "0"), the significant differential coefficient information is set to "0" (S1018).

After a context corresponding to the determined context index ctxIdx is read from the context memory 704, the significant coefficient information coding controller 706 transmits the significant differential coefficient information and the context to the arithmetic encoder 701. The arithmetic encoder 701 codes

the significant differential coefficient information using the context (S1019).

[Decoding Sequence]

A method of decoding differential coefficients according to the second example of the embodiment of the present invention will be described. The differential information decoder 801 according to the second example, similarly to the differential information decoder 801 according to the first example illustrated in FIG. 8, includes: an arithmetic decoder 1001; a differential coefficient buffer 1002; a decoding controller 1003; a context memory 1004; and a scan controller 1005. In addition, the decoding controller 1003 includes: a significant coefficient information decoding controller 1006; a differential coefficient value decoding controller 1007; and a significant sub block information decoding controller 1008.

A differential information decoding process performed by the differential information decoder 801 illustrated in FIG. 8 corresponds to the differential information coding process performed by the differential information encoder 507 illustrated in FIG. 5. Thus, the configurations of the differential coefficient buffer 1002, the context memory 1004, and the scan controller 1005 of the differential information encoder illustrated in FIG. 8 respectively have functions corresponding to the configurations of the differential coefficient buffer 702, the context memory 704, and the scan controller 705 illustrated in FIG. 15.

Since the decoding sequence of the differential information according to this example is the same as that of the first example except for the sequence (S203 illustrated in FIG. 2) of the coding process of the significant differential coefficient information, hereinafter, the sequence of the decoding process of the significant differential coefficient information according to this example will be described with reference to a flowchart illustrated in FIG. 22.

[Sequence of Decoding Process of Significant Differential
Coefficient Information (S203)]

The significant coefficient information decoding controller 1006 derives the significant sub block information of decoded sub blocks that are neighboring to the right side and the lower side of the sub block to be processed. The significant sub block information of the sub block neighboring to the right side will be denoted by sigGroupRight, and the significant sub block information of the sub block neighboring to the lower side will be denoted by sigGroupBottom (S1101).

The significant coefficient information decoding controller 1006 determines differential coefficients that are the processing targets (S1102). The scanning sequence of differential coefficients within the sub block, similarly to the scanning sequence of sub blocks in the differential coefficient region, follows the rule represented in FIG. 7. When the scanning of all the significant differential coefficients of the sub block is completed, the decoding process of the significant

differential coefficients is completed, and the process proceeds to the decoding sequence (S204) of differential coefficient values.

The significant coefficient information decoding controller 1006 evaluates the significant sub block information sigGroupRight and the significant sub block information sigGroupBottom (S1103). In a case where the significant sub block information sigGroupRight is "0" and the significant sub block information sigGroupBottom is "0", the position of the processing target differential coefficient within the sub block to be processed is determined (S1104). Here, it is represented such that a horizontal differential coefficient position is posX, a vertical differential coefficient position is posY, and the processing target differential coefficient position is pos = posX + posY. In a case where $pos \leq 2$, a context index ctxIdx used for decoding the significant coefficient information is set to "1" (S1105). Otherwise ($pos > 2$), the context index ctxIdx is set to "0" (S1106). The definition of the context index ctxIdx of a case where the significant sub block information sigGroupRight is "0" and the significant sub block information sigGroupBottom are "0" is denoted by reference numeral 1201 in FIG. 23. After the determined context is read from the context memory 1004, a decoding command is transmitted to the arithmetic decoder 1001 together with the context. The arithmetic decoder 1001 performs a decoding process of a bitstream using the context, thereby decoding the significant differential coefficient

information (S1116).

In a case where the significant sub block information sigGroupRight and the significant sub block information sigGroupBottom are not "0", it is determined whether the
5 significant sub block information sigGroupRight is "1" and the significant sub block information sigGroupBottom is "0" (S1107). In a case where the significant sub block information sigGroupRight is "1" and the significant sub block information sigGroupBottom is "0", the position of the processing target
10 differential coefficient within the sub block to be processed is determined (S1108). In a case where the vertical differential coefficient position $posY \leq 1$, the context index ctxIdx used for decoding the significant coefficient information is set to "1" (S1109). Otherwise ($posY > 2$), the context index ctxIdx is set
15 to "0" (S1110). The definition of the context index ctxIdx of a case where the significant sub block information sigGroupRight is "1" and the significant sub block information sigGroupBottom is "0" is denoted by reference numeral 1202 in FIG. 23. After the determined context is read from the context memory 1004, a
20 decoding command is transmitted to the arithmetic decoder 1001 together with the context. The arithmetic decoder 1001 performs a decoding process of a bitstream using the context, thereby decoding the significant differential coefficient information (S1116).

25 When the significant sub block information sigGroupRight and the significant sub block information sigGroupBottom are not

respectively "1" and "0", it is determined whether the significant sub block information sigGroupRight and the significant sub block information sigGroupBottom are respectively "0" and "1" (S1111). In a case where the significant sub block information sigGroupRight and the significant sub block information sigGroupBottom are respectively "0" and "1", the position of the processing target differential coefficient within the sub block to be processed is determined (S1112). In a case where the horizontal differential coefficient position $posX \leq 1$, the context index ctxIdx used for decoding the significant coefficient information is set to "1" (S1113). Otherwise ($posX > 2$), the context index ctxIdx is set to "0" (S1114). The definition of the context index ctxIdx of a case where the significant sub block information sigGroupRight is "0" and the significant sub block information sigGroupBottom is "1" is denoted by reference numeral 1203 in FIG. 23. After the determined context is read from the context memory 1004, a decoding command is transmitted to the arithmetic decoder 1001 together with the context. The arithmetic decoder 1001 performs a decoding process of a bitstream using the context, thereby decoding the significant differential coefficient information (S1116).

When the significant sub block information sigGroupRight and the significant sub block information sigGroupBottom are not respectively "0" and "1", in other words, when both the significant sub block information sigGroupRight and the

significant sub block information sigGroupBottom are "1", the position of the processing target differential coefficient within the sub block to be processed is determined (S1117). In a case where the processing target differential coefficient position pos

5 <= 4, the context index ctxIdx used for decoding the significant coefficient information is set to "2" (S1118). Otherwise (pos > 5), the context index ctxIdx is set to "1" (S1114). The definition of the context index ctxIdx of a case where both the significant sub block information sigGroupRight and the

10 significant sub block information sigGroupBottom are "1" is denoted by reference numeral 1204 in FIG. 23. After the determined context is read from the context memory 1004, a decoding command is transmitted to the arithmetic decoder 1001 together with the context. The arithmetic decoder 1001 performs

15 a decoding process of a bitstream using the context, thereby decoding the significant differential coefficient information (S1116).

In this sequence, for the calculation of the context index ctxIdx for the significant differential coefficient information,

20 the significant sub block information of the decoded neighboring sub blocks and the position of the processing target differential coefficient within the sub block are referred to, and the significant sub block information of the right side and the significant sub block information of the lower side are

25 individually determined. Hereinafter, the reason for employing such a configuration will be described.

Generally, the orthogonal transform coefficients of a picture may be easily concentrated in the low region component, and there is a high possibility that the significant coefficient information is "1". In addition, since it is difficult for the high region component of the orthogonal transform coefficient to receive a visual influence, the high region component is quantized in a rough manner in many cases, and accordingly, there is a high possibility that the coefficient value of the high region component is "0", and the significant coefficient information of the high region component is "0". Such a characteristic is not limited to the entire differential coefficient region but is the same for each sub block, and it can be regarded that, for a component present on the low region side of the sub block, a probability that the significant coefficient information is "1" is higher than that for a component present on the high region side of the same sub block. Setting the value of the context index $ctxIdx$ of the significant differential coefficient information present in the low region within the sub block to be larger than the value of the context index $ctxIdx$ of the significant differential coefficient information present in the high region leads to the improvement of the estimation accuracy of the occurrence probability of the significant coefficient information. In addition, the decoded neighboring significant sub block information tends to be small in the high region in which the probability that the significant differential coefficient is "0" is high, and the decoded neighboring significant sub block

information tends to increase in the low region in which the probability that the significant differential coefficient is "1" is high. Thus, using the decoded neighboring significant sub block information as an index representing the degree of inclusion
5 of the significant differential coefficient information in the sub block to be processed improves the estimation accuracy of the occurrence probability of the significant coefficient information.

In the context calculating process of this example, in a
10 case where the right-side significant sub block information sigGroupRight is "1" and the lower-side significant sub block information sigGroupBottom is "0" and in a case where the right-side significant sub block information sigGroupRight is "0" and the lower-side significant sub block information
15 sigGroupBottom is "1", mutually-different context indexes can be set, which is different from the first example. In a case where the right-side significant sub block information sigGroupRight is "1" and the lower-side significant sub block information sigGroupBottom is "0", a significant differential coefficient is
20 not present on the lower side of the sub block to be processed, and accordingly, there is a high possibility that a significant differential coefficient is not present in the high region component of the vertical direction within the sub block to be processed. On the other hand, in a case where the right-side
25 significant sub block information sigGroupRight is "0" and the lower-side significant sub block information sigGroupBottom is

"1", a significant differential coefficient is not present on the right side of the sub block to be processed, and accordingly, there is a high possibility that a significant differential coefficient is not present in the high region component of the horizontal direction within the sub block to be processed. Therefore, by employing the configuration of this example in which a context index is appropriately selected in accordance with the occurrence probabilities of significant differential coefficients in the vertical and horizontal directions, the estimation accuracy of the occurrence probabilities of significant differential coefficients can be improved.

In addition, in this example, from the viewpoint of a decrease in the processing amount, while the sub block that is neighboring to the right side of the sub block to be decoded and the sub block that is neighboring to the lower side thereof are referred to as the decoded neighboring sub blocks, the decoded neighboring sub blocks according to the present invention are not limited thereto. Particularly, the sub block that is neighboring to the lower right side of the sub block to be decoded is close to the sub block to be decoded and has a high correlation with the sub block to be decoded. Accordingly, by adding the significant sub block information sigGroupBottomRight of the sub block that is neighboring to the lower right side to the determination target for the calculation of the context index ctxIdx, the accuracy of the occurrence probabilities of significant differential coefficients can be improved. However,

compared to the sub blocks neighboring to the right side of the sub block to be decoded and the sub block neighboring to the lower side thereof, the sub block that is neighboring to the lower right side of the sub block to be decoded is positioned far from the sub block to be decoded and has a low correlation with the sub block to be decoded. Accordingly, in the configuration in which the context index of the significant differential coefficient is calculated based on the right-side significant sub block information sigGroupRight, the lower-side significant sub block information sigGroupBottom, and the significant sub block information sigGroupBottomRight, it is preferable to set the degree of reflection of the significant differential coefficient of the significant sub block information sigGroupBottomRight on the context index to be lower than those of the significant sub block information sigGroupBottom and the significant sub block information sigGroupBottomRight. As a method for setting the degree of reflection of the significant differential coefficient of the significant sub block information sigGroupBottomRight on the context index to be low, for example, in a case where both the lower-side significant sub block information sigGroupBottom and the significant sub block information sigGroupBottomRight are "0", the occurrence probability of the significant differential coefficient is set to be low regardless of the value of the significant sub block information sigGroupBottomRight.

In this example, while the right-side significant sub block information sigGroupRight, the lower-side significant sub block

information sigGroupBottom, and the position of the processing target coefficient are referred to, the differential coefficient belonging to the processing target sub block is not targeted for the right-side significant sub block information sigGroupRight and the lower-side significant sub block information sigGroupBottom, and accordingly, there is no dependency within the sub block for the calculation of context indexes. Since the context indexes for all the significant differential coefficients can be calculated from the start of the sub block, the calculation of the context indexes can be performed in parallel with the decoding process of the significant differential coefficient information. Thus, a processing delay relating to the decoding of significant coefficient information having a high occurrence frequency in the bitstream can be decreased.

In this example, while a context index used for decoding the significant differential coefficient information is calculated based on the significant differential coefficient information of the decoded sub block, a similar sequence may be applied to the calculation of the context index of the differential coefficient value. Similarly to the significant differential coefficient information, the differential coefficient value has correlation with the neighboring coefficient values and has concentration in the low region component. Thus, by setting a context index representing a high occurrence probability of a large differential coefficient value when the neighboring significant differential coefficient sum or

the sum of the absolute values of the neighboring differential coefficients is large and setting a context index representing a high occurrence probability of a small differential coefficient value when the neighboring significant differential coefficient sum or the sum of the absolute values of the neighboring differential coefficients is small, the differential coefficient values can be efficiently coded.

According to the picture coding device and the picture decoding device of the second example described above, the following operations and advantages are obtained in addition to the operations and the advantages (1) to (4) of the first example described above.

(5) The context index is calculated based on a combination of the right-side significant sub block information and the lower-side significant sub block information. The occurrence probability of the significant differential coefficient of the vertical high region component of the sub block to be processed is estimated to be low when a significant differential coefficient is not present on the lower side of the sub block to be processed, and the occurrence probability of the significant differential coefficient of the horizontal high region component of the sub block to be processed is estimated to be low when a significant differential coefficient is not present on the right side of the sub block to be processed, whereby an appropriate probability model of the significant differential coefficient information can be set, and the significant differential coefficient information

can be efficiently coded.

(Third Example)

A third example of the method of coding the differential information according to an embodiment of the present invention will now be described. A differential information encoder 507 according to the third example, similarly to the differential information encoder 507 according to the first example illustrated in FIG. 15, includes: an arithmetic encoder 701; a differential coefficient buffer 702; a coding controller 703; a context memory 704; and a scan controller 705. In addition, the coding controller 703 includes: a significant coefficient information coding controller 706; a differential coefficient value coding controller 707; and a significant sub block information coding controller 708.

The coding sequence of the differential information according to this example is the same as that of the first example except for the sequence (S704 illustrated in FIG. 17) of the coding process of the significant differential coefficient information, and thus, hereinafter, the sequence of the coding process of the significant differential coefficient information according to this example will be described with reference to a flowchart illustrated in FIG. 24.

[Sequence of Coding Process of Significant Differential Coefficient Information (S704)]

The significant coefficient information coding controller 706 calculates a neighboring significant index sigCoeffIndex

based on the significant sub block information of the decoded sub blocks neighboring to the right side and the lower side of the sub block to be processed. It is set such that the significant sub block information of the sub block neighboring to the right side is sigGroupRight, the significant sub block information of the sub block neighboring to the lower side is sigGroupBottom, and the neighboring significant index sigCoeffIndex = sigGroupRight + 2 × sigGroupBottom (S1201).

The significant coefficient information coding controller 706 determines differential coefficients that are the processing targets (S1202). The scanning sequence of differential coefficients within the sub block, similarly to the scanning sequence of sub blocks in the differential coefficient region, follows the rule represented in FIG. 7. When the scanning of all the significant differential coefficients of the sub block is completed, the coding process of the significant differential coefficients is completed, and the process proceeds to the coding sequence (S704) of differential coefficient values.

The significant coefficient information coding controller 706 evaluates the neighboring significant index sigCoeffIndex (S1203).

In a case where the neighboring significant index sigCoeffIndex is "0", the position of the processing target differential coefficient within the sub block to be processed is determined (S1204). In a case where the neighboring significant index sigCoeffIndex is "0", it represents that the significant

sub block information sigGroupRight is "0" and the significant sub block information sigGroupBottom is "0". Here, it is represented such that a horizontal differential coefficient position is posX, a vertical differential coefficient position is posY, and the processing target differential coefficient position is pos = posX + posY. In a case where pos ≤ 2, the context index ctxIdx used for coding the significant coefficient information is set to "1" (S1205). Otherwise (pos > 2), the context index ctxIdx is set to "0" (S1206). The definition of the context index ctxIdx of a case where the neighboring significant index sigCoeffIndex is "0" is denoted by reference numeral 1201 in FIG. 23.

On the other hand, in a case where the neighboring significant index sigCoeffIndex is not "0", it is determined whether the neighboring significant index sigCoeffIndex is "1" (S1207). In a case where the neighboring significant index sigCoeffIndex is "1", it represents that the significant sub block information sigGroupRight is "1" and the significant sub block information sigGroupBottom is "0". In a case where the neighboring significant index sigCoeffIndex is "1", the position of the processing target differential coefficient within the sub block to be processed is determined (S1208). In a case where the vertical differential coefficient position posY ≤ 1, the context index ctxIdx used for decoding the significant coefficient information is set to "1" (S1209). Otherwise (posY > 2), the context index ctxIdx is set to "0" (S1210). The definition of

the context index `ctxIdx` of a case where the neighboring significant index `sigCoeffIndex` is "1" is denoted by reference numeral 1202 in FIG. 23.

On the other hand, in a case where the neighboring significant index `sigCoeffIndex` is not "1", it is determined whether the neighboring significant index `sigCoeffIndex` is "2" (S1211). In a case where the neighboring significant index `sigCoeffIndex` is "2", it represents that the significant sub block information `sigGroupRight` is "0" and the significant sub block information `sigGroupBottom` is "1". In a case where the neighboring significant index `sigCoeffIndex` is "2", the position of the processing target differential coefficient within the sub block to be processed is determined (S1212). In a case where the horizontal differential coefficient position `posX` ≤ 1 , the context index `ctxIdx` used for decoding the significant coefficient information is set to "1" (S1213). Otherwise (`posX` > 2), the context index `ctxIdx` is set to "0" (S1214). The definition of the context index `ctxIdx` of a case where the neighboring significant index `sigCoeffIndex` is "2" is denoted by reference numeral 1203 in FIG. 23. In other words, the sequence of setting the context index `ctxIdx` of a case where the neighboring significant index `sigCoeffIndex` is "2" is a process in which the X-direction process and the Y direction process of a case where the neighboring significant index `sigCoeffIndex` is "1" are interchanged. For this reason, the process can be configured to be common, and the circuit scale of the hardware or the coding

amount of the software can be reduced.

In addition, in a case where the neighboring significant index sigCoeffIndex is not "2", in other words, in a case where the neighboring significant index sigCoeffIndex is "3", the position of the processing target differential coefficient within the sub block to be processed is determined (S1215). In a case where the neighboring significant index sigCoeffIndex is "3", it represents that both the significant sub block information sigGroupRight and significant sub block information sigGroupBottom are "1". In a case where the processing target differential coefficient position pos \leq 4, the context index ctxIdx used for decoding the significant coefficient information is set to "2" (S1216). Otherwise (pos > 5), the context index ctxIdx is set to "1" (S1217). The definition of the context index ctxIdx of a case where neighboring significant index sigCoeffIndex is "3" is denoted by reference numeral 1204 in FIG. 23.

The significant coefficient information coding controller 706 derives the differential coefficient of the processing target position from the differential coefficient buffer 702. In a case where the differential coefficient value is not "0", the significant differential coefficient information is set to "1". Otherwise (in a case where the differential coefficient value is "0"), the significant differential coefficient information is set to "0" (S1218).

After a context corresponding to the determined context

index ctxIdx is read from the context memory 704, the significant coefficient information coding controller 706 transmits the significant differential coefficient information and the context to the arithmetic encoder 701. The arithmetic encoder 701 codes
5 the significant differential coefficient information using the context (S1219).

[Decoding Sequence]

A method of decoding differential coefficients according to the third example of the embodiment of the present invention
10 will be described. The differential information decoder 801 according to the third example, similarly to the differential information decoder 801 according to the first example illustrated in FIG. 8, includes: an arithmetic decoder 1001; a differential coefficient buffer 1002; a decoding controller 1003;
15 a context memory 1004; and a scan controller 1005. In addition, the decoding controller 1003 includes: a significant coefficient information decoding controller 1006; a differential coefficient value decoding controller 1007; and a significant sub block information decoding controller 1008.

20 A differential information decoding process performed by the differential information decoder 801 illustrated in FIG. 8 corresponds to the differential information coding process performed by the differential information encoder 507 illustrated in FIG. 5. Thus, the configurations of the differential
25 coefficient buffer 1002, the context memory 1004, and the scan controller 1005 of the differential information encoder

illustrated in FIG. 8 respectively have functions corresponding to the configurations of the differential coefficient buffer 702, the context memory 704, and the scan controller 705 illustrated in FIG. 15.

5 Since the decoding sequence of the differential information according to this example is the same as that of the first example except for the sequence (S203 illustrated in FIG. 2) of the coding process of the significant differential coefficient information, hereinafter, the sequence of the decoding process of the
10 significant differential coefficient information according to this example will be described with reference to a flowchart illustrated in FIG. 25.

[Sequence of Decoding Process of Significant Differential Coefficient Information (S203)]

15 The significant coefficient information decoding controller 1006 calculates a neighboring significant index sigCoeffIndex based on the significant sub block information of the decoded sub blocks neighboring to the right side and the lower side of the sub block to be processed. It is set such that the
20 significant sub block information of the sub block neighboring to the right side is sigGroupRight, the significant sub block information of the sub block neighboring to the lower side is sigGroupBottom, and the neighboring significant index
$$\text{sigCoeffIndex} = \text{sigGroupRight} + 2 \times \text{sigGroupBottom} \text{ (S1301)}.$$

25 The significant coefficient information decoding controller 1006 determines differential coefficients that are the

processing targets (S1302). The scanning sequence of differential coefficients within the sub block, similarly to the scanning sequence of sub blocks in the differential coefficient region, follows the rule represented in FIG. 7. When the scanning
5 of all the significant differential coefficients of the sub block is completed, the decoding process of the significant differential coefficients is completed, and the process proceeds to the decoding sequence (S204) of differential coefficient values.

10 The significant coefficient information decoding controller 1006 evaluates the neighboring significant index sigCoeffIndex (S1303).

In a case where the neighboring significant index sigCoeffIndex is "0", the position of the processing target
15 differential coefficient within the sub block to be processed is determined (S1304). In a case where the neighboring significant index sigCoeffIndex is "0", it represents that both the significant sub block information sigGroupRight and the significant sub block information sigGroupBottom are "0". Here,
20 it is represented such that a horizontal differential coefficient position is posX, a vertical differential coefficient position is posY, and the processing target differential coefficient position is $pos = posX + posY$. In a case where $pos \leq 2$, the context index ctxIdx used for decoding the significant coefficient
25 information is set to "1" (S1305). Otherwise ($pos > 2$), the context index ctxIdx is set to "0" (S1306). The definition of

the context index `ctxIdx` of a case where the neighboring significant index `sigCoeffIndex` is "0" is denoted by reference numeral 1201 in FIG. 23. After the determined context is read from the context memory 1004, a decoding command is transmitted
5 to the arithmetic decoder 1001 together with the context. The arithmetic decoder 1001 performs a decoding process of a bitstream using the context, thereby decoding the significant differential coefficient information (S1316).

On the other hand, in a case where the neighboring
10 significant index `sigCoeffIndex` is not "0", it is determined whether the neighboring significant index `sigCoeffIndex` is "1" (S1307). In a case where the neighboring significant index `sigCoeffIndex` is "1", it represents that the significant sub block information `sigGroupRight` is "1" and the significant sub block
15 information `sigGroupBottom` is "0". In a case where the neighboring significant index `sigCoeffIndex` is "1", the position of the processing target differential coefficient within the sub block to be processed is determined (S1308). In a case where the vertical differential coefficient position `posY` ≤ 1 , the context
20 index `ctxIdx` used for decoding the significant coefficient information is set to "1" (S1309). Otherwise (`posY` > 2), the context index `ctxIdx` is set to "0" (S1310). The definition of the context of a case where the neighboring significant index `sigCoeffIndex` is "1" is denoted by reference numeral 1202 in FIG.
25 23. After the determined context is read from the context memory 1004, a decoding command is transmitted to the arithmetic decoder

1001 together with the context. The arithmetic decoder 1001 performs a decoding process of a bitstream using the context, thereby decoding the significant differential coefficient information (S1316).

5 On the other hand, in a case where the neighboring significant index sigCoeffIndex is not "1", it is determined whether the neighboring significant index sigCoeffIndex is "2" (S1311). In a case where the neighboring significant index sigCoeffIndex is "2", it represents that the significant sub block
10 information sigGroupRight is "0" and the significant sub block information sigGroupBottom is "1". In a case where the neighboring significant index sigCoeffIndex is "2", the position of the processing target differential coefficient within the sub block to be processed is determined (S1312). In a case where the
15 horizontal differential coefficient position $posX \leq 1$, the context index ctxIdx used for decoding the significant coefficient information is set to "1" (S1313). Otherwise ($posX > 2$), the context index ctxIdx is set to "0" (S1314). The definition of the context index ctxIdx of a case where the
20 neighboring significant index sigCoeffIndex is "2" is denoted by reference numeral 1203 in FIG. 23. After the determined context is read from the context memory 1004, a decoding command is transmitted to the arithmetic decoder 1001 together with the context. The arithmetic decoder 1001 performs a decoding process
25 of a bitstream using the context, thereby decoding the significant differential coefficient information (S1316).

In addition, in a case where the neighboring significant index sigCoeffIndex is not "2", in other words, in a case where the neighboring significant index sigCoeffIndex is "3", the position of the processing target differential coefficient within the sub block to be processed is determined (S1317). In a case where the neighboring significant index sigCoeffIndex is "3", it represents that both the significant sub block information sigGroupRight and significant sub block information sigGroupBottom are "1". In a case where the processing target differential coefficient position $pos \leq 4$, the context index ctxIdx used for decoding the significant coefficient information is set to "2" (S1318). Otherwise ($pos > 5$), the context index ctxIdx is set to "1" (S1314). The definition of the context index ctxIdx of a case where neighboring significant index sigCoeffIndex is "3" is denoted by reference numeral 1204 in FIG. 23. After the determined context is read from the context memory 1004, a decoding command is transmitted to the arithmetic decoder 1001 together with the context. The arithmetic decoder 1001 performs a decoding process of a bitstream using the context, thereby decoding the significant differential coefficient information (S1316).

In this example, in the sequence for calculating the context index ctxIdx of the significant differential coefficient information, instead of directly referring to the significant sub block information sigGroupRight of the sub block neighboring to the right side and the significant sub block information

sigGroupBottom of the sub block neighboring to the lower side, after the neighboring significant index sigCoeffIndex is calculated based on the significant sub block information sigGroupRight and sigGroupBottom, the context index ctxIdx is
5 calculated by referring to the neighboring significant index sigCoeffIndex, which is different from the first example. Accordingly, the number of times of performing the determination process relating to context index based on the neighboring significant index sigCoeffIndex can be reduced.

10 According to the picture coding device and the picture decoding device of the third example described above, the following operations and advantages are obtained in addition to the operations and the advantages (1) to (4) of the first example and the operations and the advantages (5) of the second example
15 described above.

(6) After the neighboring significant index sigCoeffIndex is calculated based on the significant sub block information sigGroupRight of the sub block neighboring to the right side and the significant sub block information sigGroupBottom of the sub
20 block neighboring to the lower side, the context index is calculated based on the neighboring significant index sigCoeffIndex. Compared to a method in which the context index is calculated based on the significant sub block information sigGroupRight of the sub block neighboring to the right side and
25 the significant sub block information sigGroupBottom of the sub block neighboring to the lower side, the number of times of

performing the determination process relating to the calculation of context indexes can be reduced.

A bitstream of a picture that is output by the picture coding device according to the embodiment described above has a specific data format so as to be decodable in accordance with a coding method used in the embodiment, and the picture decoding device corresponding to the picture coding device can decode the bitstream of the specific data format.

In a case where a wired or wireless network is used for exchanging a bitstream between the picture coding device and the picture decoding device, the bitstream may be converted into a data format that is appropriate for the transmission form in a communication path and be transmitted. In such a case, a picture transmission device is disposed, which converts a bitstream output by the picture coding device into coding data of a data format that is appropriate to the transmission form in the communication path and transmits the converted coding data to the network, and a picture reception device is disposed, which receives the coding data from the network, restores the bitstream from the coding data, and supplies the restored bitstream to the picture decoding device.

The picture transmission device includes: a memory that buffers a bitstream output by the picture coding device; a packet processing unit that packetizes the bitstream; and a transmitter that transmits packetized coding data through a network. The picture reception device includes: a reception unit that receives

packetized coding data through a network; a memory that buffers the received coding data; and a packet processing unit that constructs a bitstream by performing a packet process of coding data and supplies the constructed bitstream to the picture
5 decoding device.

The processes relating to the coding and decoding described above may be realized not only by a transmission/storage/reception device using hardware but also by firmware stored in a read only memory (ROM), a flash memory, or
10 the like or software of a computer or the like. The firmware or the software program may be provided with being recorded in a recording medium that can be read by a computer or the like, may be provided from a server through a wired or wireless network, or may be provided by data broadcasting of terrestrial wave or
15 satellite digital broadcasting.

As above, the present invention has been described based on the embodiments. However, such embodiments are merely examples, and it is understood to a person skilled in the art that various modifications may be made in each constituent element
20 thereof or a combination of each process sequence, and such modified examples also belong to the scope of the present invention.

[Item 1]

A picture coding device that partitions differential
25 information between a picture that is a coding target and a picture that is a prediction target into a plurality of sub blocks and

codes the partitioned sub blocks in a predetermined sequence, the picture coding device comprising:

a significant sub block information encoder that codes significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero;

a significant differential coefficient information encoder that codes significant differential coefficient information that represents whether or not the value of the differential coefficient is zero;

a differential coefficient value encoder that codes the value of the differential coefficient; and

a context deriver that derives an index based on the significant sub block information of a coded sub block that is neighboring to the sub block that is a coding target in the horizontal direction and the significant sub block information of a coded sub block that is neighboring in the vertical direction and derives a context used for coding the significant differential coefficient information of the differential coefficient that is a coding target based on the index and the position of the differential coefficient that is the coding target in the sub block that is the coding target.

[Item 2]

The picture coding device according to item 1, wherein the context deriver derives the mutually-different indexes in a case where the significant sub block information of the coded sub block

that is neighboring in the horizontal direction is "1" and the significant sub block information of the coded sub block that is neighboring in the vertical direction is "0" and in a case where the significant sub block information of the coded sub block that is neighboring in the horizontal direction is "0" and the significant sub block information of the coded sub block that is neighboring in the vertical direction is "1".

[Item 3]

The picture coding device according to item 1, wherein the context deriver derives the mutually-different indexes in a case where the significant sub block information of the coded sub block that is neighboring in the horizontal direction is "0" and the significant sub block information of the coded sub block that is neighboring in the vertical direction is "0" and in a case where the significant sub block information of the coded sub block that is neighboring in the horizontal direction is "1" and the significant sub block information of the coded sub block that is neighboring in the vertical direction is "1".

[Item 4]

The picture coding device according to item 1, wherein the context deriver derives the mutually-different indexes in a case where the significant sub block information of the coded sub block that is neighboring in the horizontal direction is "0" and the significant sub block information of the coded sub block that is neighboring in the vertical direction is "0", in a case where the significant sub block information of the coded sub block that is

neighboring in the horizontal direction is "1" and the significant sub block information of the coded sub block that is neighboring in the vertical direction is "0", in a case where the significant sub block information of the coded sub block that is neighboring
5 in the horizontal direction is "0" and the significant sub block information of the coded sub block that is neighboring in the vertical direction is "1", and in a case where the significant sub block information of the coded sub block that is neighboring
10 in the horizontal direction is "1" and the significant sub block information of the coded sub block that is neighboring in the vertical direction is "1".

[Item 5]

The picture coding device according to any one of items 1 to 4, wherein the context deriver, in a case where the significant
15 sub block information of the coded sub block that is neighboring in the horizontal direction is "1" and the significant sub block information of the coded sub block that is neighboring in the vertical direction is "0", derives the context based on the position of the differential coefficient, which is the coding
20 target, in the vertical direction in the sub block that is the coding target.

[Item 6]

The picture coding device according to any one of items 1 to 5, wherein the context deriver, in a case where the significant
25 sub block information of the coded sub block that is neighboring in the horizontal direction is "0" and the significant sub block

information of the coded sub block that is neighboring in the vertical direction is "1", derives the context based on the position of the differential coefficient, which is the coding target, in the horizontal direction in the sub block that is the coding target.

[Item 7]

The picture coding device according to any one of items 1 to 6, wherein the context deriver, in a case where both the significant sub block information of the coded sub block that is neighboring in the horizontal direction and the significant sub block information of the coded sub block that is neighboring in the vertical direction are "1", sets the context as a predetermined value regardless of the position of the differential coefficient that is the coding target in the sub block that is the coding target.

[Item 8]

The picture coding device according to any one of items 1 to 7, wherein the context deriver, in a case where both the significant sub block information of the coded sub block that is neighboring in the horizontal direction and the significant sub block information of the coded sub block that is neighboring in the vertical direction are "0", derives the context based on an equation adding the positions of the differential coefficient, which is the coding target, in the horizontal and vertical directions in the sub block that is the coding target.

[Item 9]

The picture coding device according to any one of items 1 to 8, wherein the context deriver derives the index based on a calculating equation adding a value of the significant sub block information of the coded sub block that is neighboring in the horizontal direction to a value derived by doubling the significant sub block information of the coded sub block that is neighboring in the vertical direction.

[Item 10]

A picture coding method in which differential information between a picture that is a coding target and a picture that is a prediction target is partitioned into a plurality of sub blocks, and the partitioned sub blocks are coded in a predetermined sequence, the picture coding method comprising:

coding significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero;

coding significant differential coefficient information that represents whether or not the value of the differential coefficient is zero;

coding the value of the differential coefficient; and deriving an index based on the significant sub block information of a coded sub block that is neighboring to the sub block that is a coding target in the horizontal direction and the significant sub block information of a coded sub block that is neighboring in the vertical direction and deriving a context used for coding the significant differential coefficient information

of the differential coefficient that is a coding target based on the index and the position of the differential coefficient that is the coding target in the sub block that is the coding target.

[Item 11]

5 A picture coding program in which differential information between a picture that is a coding target and a picture that is a prediction target is partitioned into a plurality of sub blocks, and the partitioned sub blocks are coded in a predetermined sequence, the picture coding program causing a computer to
10 perform:

coding significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero;

coding significant differential coefficient information
15 that represents whether or not the value of the differential coefficient is zero;

coding the value of the differential coefficient; and

deriving an index based on the significant sub block information of a coded sub block that is neighboring to the sub
20 block that is a coding target in the horizontal direction and the significant sub block information of a coded sub block that is neighboring in the vertical direction and deriving a context used for coding the significant differential coefficient information of the differential coefficient that is a coding target based on
25 the index and the position of the differential coefficient that is the coding target in the sub block that is the coding target.

[Item 12]

A transmission device comprising:

a packet processing unit that obtains coding data by
packetizing a bitstream that is coded by using a picture coding
5 method in which differential information between a picture that
is a coding target and a picture that is a prediction target is
partitioned into a plurality of sub blocks, and the partitioned
sub blocks are coded in a predetermined sequence; and

a transmitter that transmits the packetized coding data,
10 wherein the picture coding method comprises:

coding significant sub block information that represents
whether or not all the values of differential coefficients
belonging to the sub block are zero;

coding significant differential coefficient information
15 that represents whether or not the value of the differential
coefficient is zero;

coding the value of the differential coefficient; and

deriving an index based on the significant sub block
information of a coded sub block that is neighboring to the sub
20 block that is a coding target in the horizontal direction and the
significant sub block information of a coded sub block that is
neighboring in the vertical direction and deriving a context used
for coding the significant differential coefficient information
of the differential coefficient that is a coding target based on
25 the index and the position of the differential coefficient that
is the coding target in the sub block that is the coding target.

[Item 13]

A transmission method comprising:

obtaining coding data by packetizing a bitstream that is coded by using a picture coding method in which differential
5 information between a picture that is a coding target and a picture that is a prediction target is partitioned into a plurality of sub blocks, and the partitioned sub blocks are coded in a predetermined sequence; and

transmitting the packetized coding data,

10 wherein the picture coding method comprises:

coding significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero;

15 coding significant differential coefficient information that represents whether or not the value of the differential coefficient is zero;

coding the value of the differential coefficient; and

20 deriving an index based on the significant sub block information of a coded sub block that is neighboring to the sub block that is a coding target in the horizontal direction and the significant sub block information of a coded sub block that is neighboring in the vertical direction and deriving a context used for coding the significant differential coefficient information of the differential coefficient that is a coding target based on
25 the index and the position of the differential coefficient that is the coding target in the sub block that is the coding target.

[Item 14]

A transmission program that causes a computer to perform:

obtaining coding data by packetizing a bitstream that is
coded by using a picture coding method in which differential
5 information between a picture that is a coding target and a picture
that is a prediction target is partitioned into a plurality of
sub blocks, and the partitioned sub blocks are coded in a
predetermined sequence; and

transmitting the packetized coding data,

10 wherein the picture coding method comprises:

coding significant sub block information that represents
whether or not all the values of differential coefficients
belonging to the sub block are zero;

coding significant differential coefficient information
15 that represents whether or not the value of the differential
coefficient is zero;

coding the value of the differential coefficient; and

deriving an index based on the significant sub block
information of a coded sub block that is neighboring to the sub
20 block that is a coding target in the horizontal direction and the
significant sub block information of a coded sub block that is
neighboring in the vertical direction and deriving a context used
for coding the significant differential coefficient information
of the differential coefficient that is a coding target based on
25 the index and the position of the differential coefficient that
is the coding target in the sub block that is the coding target.

[CLAIMS]

1. A picture coding device that partitions differential information between a picture that is a coding target and a picture
5 that is a prediction target into a plurality of sub blocks and codes the partitioned sub blocks in a predetermined sequence, the picture coding device comprising:

a significant sub block information encoder that codes significant sub block information that represents whether or not
10 all the values of differential coefficients belonging to the sub block are zero;

a significant differential coefficient information encoder that codes significant differential coefficient information that represents whether or not the value of the differential
15 coefficient is zero;

a differential coefficient value encoder that codes the value of the differential coefficient; and

a context deriver that derives an index based on the significant sub block information of a coded sub block that is
20 neighboring to the sub block that is a coding target in the horizontal direction and the significant sub block information of a coded sub block that is neighboring in the vertical direction and derives a context used for coding the significant differential coefficient information of the differential coefficient that is
25 a coding target based on the index and the position of the differential coefficient that is the coding target in the sub

sequence;

a restoration unit that restores the bitstream by performing packet processing of the received packetized coding data;


5 a significant sub block information decoder that decodes significant sub block information that represents whether or not all the values of differential coefficients belonging to the sub block are zero from the restored bitstream;

a significant differential coefficient information decoder
10 that decodes significant differential coefficient information that represents whether or not the value of the differential coefficient is zero from the restored bitstream;

a differential coefficient value decoder that decodes the value of the differential coefficient from the restored
15 bitstream; and

a context deriver that derives an index based on the significant sub block information of a decoded sub block that is neighboring to the sub block that is a decoding target in the horizontal direction and the significant sub block information
20 of a decoded sub block that is neighboring in the vertical direction and derives a context used for decoding the significant differential coefficient information of the differential coefficient that is a decoding target based on the index and the position of the differential coefficient that is the decoding
25 target in the sub block that is the decoding target.

FIG.1



JVC KENWOOD CORPORATION


Applicant

mirandah asia (philippines) inc

By: *Amelito Mendoza*

AMELITO B. MENDOZA

FIG.7




902

16	14	11	7
15	12	8	4
13	9	5	2
10	6	3	1

JVC KENWOOD CORPORATION


Applicant

mirandah asia (philippines) inc

By: 

AMELITO B. MENDOZA

FIG.17



JVC KENWOOD CORPORATION

Applicant

mirandah asia (philippines) inc

By: *Amelito Mendoza*

AMELITO B. MENDOZA