



US006193100B1

(12) **United States Patent**  
**Royster**

(10) **Patent No.:** **US 6,193,100 B1**  
(45) **Date of Patent:** **Feb. 27, 2001**

(54) **TILTING CONTAINER SYSTEM WITH DAMPENING**

(75) Inventor: **Randy G. Royster**, White House, TN (US)

(73) Assignee: **Nashville Wire Products**, Springfield, TN (US)

(\*) Notice: Under 35 U.S.C. 154(b), the term of this patent shall be extended for 0 days.

(21) Appl. No.: **09/280,922**

(22) Filed: **Mar. 29, 1999**

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 08/897,331, filed on Jul. 21, 1997.

(51) Int. Cl.<sup>7</sup> ..... **B65D 90/00**

(52) U.S. Cl. .... **220/694; 629/1.5**

(58) Field of Search ..... 220/694, 1.5, 628, 220/629

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

235,123 12/1880 Bovey .

1,924,824 8/1933 Yeager .  
3,898,873 8/1975 Glassmeyer ..... 73/88  
4,795,057 1/1989 Jungels et al. .... 220/401  
5,368,179 11/1994 Bulle ..... 220/1.5  
5,806,863 9/1998 Heger et al. .... 280/33.998


*Primary Examiner*—Steven Pollard

(74) *Attorney, Agent, or Firm*—Wadley & Patterson;  
Lucian Wayne Beavers

(57) **ABSTRACT**

A tilting container apparatus includes a container and a leg pivotally mounted to the container for movement between a raised position and a lowered position. The leg supports the container in a tilted position when the leg is in the lowered position. A gas spring is connected between the container and the pivotal leg to dampen the movement of the pivotal leg as it moves downward from its raised position toward its lowered position. After the tiltable leg swings downward to a position approximately 90° to the horizontal base of the container, the gas spring functions to extend the movement of the tiltable leg toward its fully extended position and to hold the tiltable leg in its fully extended position.

**20 Claims, 7 Drawing Sheets**






FIG. 1




FIG. 1A




FIG. 2




FIG. 3







FIG. 4






FIG. 6




FIG. 7A




FIG. 7B







FIG. 7C




*FIG. 8A*



*FIG. 8B*



*FIG. 8C*



*FIG. 9*



1

## TILTING CONTAINER SYSTEM WITH DAMPENING

The present application is a continuation-in-part of my U.S. patent application Ser. No. 08/897,331 filed Jul. 21, 1997, entitled "Tilting Container System".

### BACKGROUND OF THE INVENTION

The present invention relates generally to containers used in the materials handling industry. More particularly, this invention pertains to a tilting container system which enables the user to access all the material in a container. This system is particularly applicable to larger containers.

It will be appreciated by those having ordinary skill in the art that it is difficult to access all the materials stored in the containers typically used in the materials handling industry. An example of such a container is a large wire mesh bin which can be used to store a variety of replacement parts, fasteners and other bulk products that are found in a manufacturing facility. To be more practical, such containers are also very large and therefore very difficult to tilt so that the user may reach materials at the bottom of the container.

To this end there have been a series of expensive tilting tables that have been developed. An example of such a tilting table is the E-Z Reach Container Tilter manufactured by Southwork. It is also necessary for the end user to purchase such a table in addition to purchasing the large storage containers.

What is needed, then, is a container system that enables the user to access all the material in the container but which is inexpensive and can be used as part of the container itself. Such a system is currently lacking in the prior art.

### SUMMARY OF THE INVENTION

A tilting container apparatus includes a container and a leg pivotally mounted to the container for movement between a raised position and a lowered position. The leg supports the container in a tilted orientation when the leg is in a lowered position. A dampening controller is connected between the container and the leg, for dampening pivotal movement of the leg between its raised and lowered positions.

The dampening controller is preferably a gas spring which also functions to urge the leg past a 90° angle relative to the base of the container and to hold the leg in a fully extended position at more than 90° relative to the base of the container.

Methods of tilting a container using the apparatus just described are also disclosed.

Accordingly, it is an object of this invention to provide a tilting container system.

It is a further object of this invention to provide a tilting container system that includes a pivoting leg which enables the container to be supported when it is in a tilted position.

It is a further object of this invention to provide a tilting container that is self-supported.

It is still a further object of this invention to provide a tilting container which allows ergonomic access to all parts or other materials contained inside the container.

It is still a further object of this invention to provide a tilting container system that can be tilted and maintained in a tilted position without having to use a separate piece of equipment such as a tilting table.

It is yet another object of this invention to provide a portable, stable and self-contained tilting container system.

2

It is still a further object of this invention to provide a tilting container system which allows for a complete access to the parts or other materials stored within the container.

Still another object of the present invention is the provision of a tilting container system which includes a damping controller for dampening pivotal movement of a leg between its raised and lowered positions.

And another object of the present invention is the provision of a tilting container system which includes a means for holding a tilting leg in its lowered position.

Other objects of this invention will be apparent from the foregoing detailed description.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view of the tilting container system of this invention wherein the container is tilted and the pivoting support leg is in a lowered position.

FIG. 1A is a perspective view of the flat brace 32 that is mounted between the support legs in an embodiment of the system of this invention.

FIG. 2 is a close-up side view of the connection between the support leg and container of the system of this invention.

FIG. 3 is a close-up back view of the connection between the support leg and container of the system of this invention.

FIG. 4 is a back view of the system of this invention.

FIG. 5A is a side view of the system of this invention cooperatively interacting with a lift truck but before the system is raised to a tilted position.

FIG. 5B is a side view of the system of this invention in cooperative interaction with a lift truck where the system is raised to a tilted position and the support leg is placed in a lowered position.

FIG. 5C is a side view of the system of this invention in a tilted position with the support leg of this invention in a lowered position after the lift truck has been removed.

FIG. 6 is a side elevation view of an alternative embodiment of the invention including a gas spring connected to the tiltable leg. The embodiment of FIG. 6 is shown in its tilted orientation.

FIG. 7A is a view of the apparatus of FIG. 6 in its initial horizontal orientation with the tiltable leg pinned in a retracted position. The apparatus has been engaged by a fork lift truck just prior to lifting the apparatus.

FIG. 7B shows the fork lift truck having lifted the apparatus of FIG. 7A, and illustrates the positions of the tilting leg as it swings downward from its retracted position to its fully extended position.

FIG. 7C shows the apparatus of FIGS. 7A and 7B having been lowered down onto the ground surface and resting in its tilted orientation with its tilting leg fully extended.

FIG. 8A is an illustration of an elevation partially sectioned view looking from underneath the base framework to the side showing an alternative mounting arrangement for the tiltable leg and gas spring.

FIG. 8B shows the apparatus of FIG. 8A in a partially lowered position.

FIG. 8C shows the apparatus of FIG. 5A in a fully lowered position.

FIG. 9 is a schematic sectioned elevation view taken along line 9—9 of FIG. 8A to further illustrate the manner in which the tiltable leg is mounted and to illustrate an optional detachable protective cover over the gas spring.

### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings, wherein like reference numerals refer to like parts throughout, the system of this

3

invention is referred to generally at **10**. References are made in the detailed description to right and left; bottom and top; interior and exterior; and front and rear. Such references are made for clarity of the written description, and should not be construed as limitations on the scope of this invention.

Referring now to FIGS. **1** and **4**, system **10** comprises container **12** and pivotally mounted support leg **18**. A leg mount **22** is welded to the base **23** of container **12** adjacent to the rear end **13** of container **12**. Heavy angle **30** is then welded to the exterior surface of leg mount **22**.

As best seen in FIGS. **1-3**, heavy angle **30** includes three sides, top side **30a**, interior side **30b** and rear side **30c**. Support leg **18** is pivotally mounted to leg mount **22** and heavy angle **30** via swivel pivot pin **20**. Swivel pivot pin **20** passes through support leg **18** through interior side **30b** of heavy angle **30** and through leg mount **22**. Swivel pivot pin **20** preferably also comprises a nut **21** (FIG. **3**). The pivoting of leg **18** is facilitated by notch **15** formed in the side edge of leg **18**. Notch **15** fits with heavy angle **30** when the leg **18** is in a lowered position. Additionally, end **19** of leg **18** is rounded to facilitate movement within heavy angle **30**. Leg **18** is also preferably standard channeled steel and thus is "I" shaped in cross-section.

Continuing on FIGS. **1**, **1A** and **4**, leg **18** is therefore pivotally mounted via swivel pivot pin **20**. In the raised position, shown in phantom in FIG. **1**, the leg **18** is secured to the base **23** of container **12** via the interaction of pin **28** through bore **36** and into bore **24**. Bore **24** is formed into base **23** of container **12**. Bore **36** is formed into flange **34** of flat brace **32**, as can be best seen in FIG. **1A**. As seen in FIG. **4**, brace **32** is mounted between pivoting support legs **18** of system **10**.

Referring back to FIGS. **1-3**, pin **28** secures leg **18** in the lowered position when it is mounted into bore **26**. As best seen in FIGS. **2** and **3**, bore **26** is formed through leg **18** and through interior side **30b** of heavy angle **30** and through leg mount **22**. Heavy angle **30** is welded to base **23** of container **12** along its top side **30a**. Heavy angle **30** is welded to leg mount **22** along its back side **30b**.

Continuing on FIG. **1**, system **10** also includes a front leg **14** to further support container **12** when system **10** is tilted as shown in FIG. **1**. As is apparent in FIG. **1**, front legs **14** are fixed non-pivoted legs, and are shorter than the pivoted legs **18**. Thus, in FIG. **1**, when system **10** is in a tilted position, the leg **18** is in a lowered position. End **38** of leg **18** is cut off at an angle to rest flush against floor **40**, thus providing stability to system **10**. The user can then access all materials within container **12** as the materials proceed toward the front end **11** of the container **12**.

Referring now to FIGS. **5A**, **5B** and **5C**, the mode of operation of the system **10** of the present invention is further described. A lift truck is maneuvered such that tines **43** of lift truck **42** are positioned beneath base **23** of the container **12** of system **10**. The embodiment depicted in FIGS. **5A-5C** further includes rear leg **56**. The support leg **18** of FIGS. **5A-5C** may also be referred to as a leg extender **18** or an extendable support member **18**. Support leg **18** is mounted to rear leg **56** in an identical fashion as it is mounted to leg mount **22** as described above, except that support leg **18** is pivotally mounted behind rear leg **56**. The system also includes braces **46** mounted between base **23** and legs **14** and **56**. Finally, the system also includes a door **48** which the user opens to access materials within container **12**.

Continuing on FIGS. **5A**, leg **18** is secured in the raised position by placing a pin **28** through bore **54** and through bore **52** that is formed in mounting stud **50**. Thus, in the

4

embodiment depicted in FIGS. **5A-5C**, leg **18** is secured in a raised position to mounting stud **50** as opposed to directly to base **23**. Stud **50** is welded to base **23**.

Referring particularly to FIG. **5B**, in continuing to describe the operation of the system in this invention, tines **43** of lift truck **42** are moved to a raised position to tilt container **12** forward. Leg **18** is then pivoted at swivel pivot **20** and placed against floor **40**. The foot **38** of leg **18** is cut off at an angle to provide for flush contact with floor **40**. This enhances the stability of system **10**.

Continuing to FIG. **5C**, the fork lift **42** is then removed and the user can then open door **48** to access materials within container **12**. In the lowered position of FIG. **5C**, leg **18** provides stable support for container **12** in the tilted position so that the user can easily access materials within container **12**. Thus, the angle of foot **38** and leg **18** is selected to provide the most suitable stability. A suitable example for the angle between the floor **40** and the leg **18** as provided by the angled end **38** is  $45^\circ$ . This is referred to at **58** in FIG. **5C**.

The apparatus of FIGS. **5A-5C** and the methods of using the same may be generally summarized as follows.

The container **12** has a front end **11** adjacent the front legs **14** and a rear end **13** adjacent the rear legs **56**. The rear and front ends may also be referred to as first and second ends of the container **12**.

The rear and front legs **56** and **14** may be described as first and second pairs of fixed legs **56** and **14** extending downward from the first and second ends, respectively, of the container **12** for supporting the container **12** in a level orientation when the first and second pairs of fixed legs **56** and **14** engage a ground surface as shown in FIG. **5A**.

The pivotable members **18** may be described as a pair of leg extenders **18** operably associated with the first or rear pair of legs **56** so that the leg extenders **18** can support the container **12** in a tilted orientation as shown in FIG. **5C**.

As shown in the figures of the preferred embodiment, it is preferred that container **12** comprise a wire mesh container as such containers are most commonly used in material handling industries. However, other containers are contemplated to be within the scope of this invention.

#### THE EMBODIMENTS OF FIGS. **6-8**

Another alternative embodiment is shown in FIGS. **6** and **7A-7C**. The tilting container apparatus of FIG. **6** is generally designated by the numeral **100**. The apparatus **100** includes a wire mesh container **102** supported on a base framework **104**. Container **102** has a front end **106** and a rear end **108**. The front end **106** includes a door **110**.

The container **102** and its base framework **104** are generally rectangular in shape, and the apparatus **100** includes a pair of rigid front legs **112** extending downward from the base framework **104** into engagement with the ground surface **114**. Apparatus **100** further includes a pair of rigid rear legs **116**. The front and rear legs **112** and **116** are joined by lengthwise braces **118**. Legs **112** and **116** and braces **118** may be considered to be a part of the base framework **104**.

The apparatus **100** includes a pair of tilting legs **120** on opposite sides of the base framework **104**. Only one of the tilting legs **120** is visible in FIGS. **6** and **7A-7C**. The tilting leg **120** is pivotally mounted to the brace **118** of container **102** for movement between a raised position as shown in FIG. **7A** and a lowered position as shown in FIGS. **6** and **7C**. The tilting leg **120** may also be referred to as an extendable support member **120**.

A gas spring 122 is connected between the brace 118 of container apparatus 100 and the tilting leg 120. The gas spring 122 includes a cylinder portion 124 and a piston portion 126. The cylinder portion 124 is pinned to brace 118 at pin 128. The piston portion 126 is pinned to tilting leg 120 at pin 130.

The tilting leg 120 is pivotally connected to brace 118 at pin 132.

The gas spring 122 is of the type that provides a resilient outward force on the piston 126, yet will resist rapid pulling of the piston 126 outward from cylinder 122.

Thus, the gas spring 122 will work as follows with reference to the sequential figures of 7A-7B.

In FIG. 7A, the tilting leg 120 is pinned in its raised position by a removable pin 134 which is received through a pin bore 136 in tilting leg 120 and a pin bore 138 in brace 118.

As seen in FIG. 7A, when the tilting leg 120 is pinned in its raised position, it does not contact the ground surface 114 in any way. The container apparatus 100 rests upon the lower ends of its front and rear legs 112 and 116 with the container 102 in a level orientation.

To change the orientation of the container apparatus 100 to its tilted position of FIG. 7C, the apparatus 100 is first lifted with a fork lift truck 140 as shown in FIG. 7B. The pin 134 is removed to allow the tilting leg 120 to swing downward through an intermediate position such as 120A to a final position such as 120B shown in FIG. 7B.

When the pin 134 is first removed, the weight of the tilting leg 120 will cause it to drop rather rapidly pivoting downward about pivot pin 132. This downward pivoting motion will, however, be resisted by the dampening effect provided by the movement of the piston 126 within the cylinder 124 of gas spring 122. Thus the gas spring 122 may in one aspect be described as a dampening controller 122 connected between the container apparatus 100 and the tilting leg 120 for dampening pivotal movement of the tilting leg 120 between its raised and lowered positions.

Furthermore, it will be apparent in viewing FIG. 7B, that as the tilting leg 120 swings downward it eventually reaches a substantially vertical position where it is at an angle of approximately 90° to the horizontal and to the brace 118 of the container 100. At this position the forces of gravity no longer move the tilting leg 120, but the resilient outward biasing force of the gas spring 122 will continue to urge tilting leg 120 past the vertical position to its rearward most extended position as indicated by 120B. Then, the apparatus 100 is lowered back to the ground surface 114 by the lift truck 140 and is allowed to rest upon the ground 114 in its tilted orientation as shown in FIG. 7C.

Thus, the gas spring 122 may be further described as including a means for holding the tilting leg 120 in its lowered or most extended position 120B. When the tilting leg 120 is in its most extended position it forms an obtuse angle 142 relative to its raised position of FIG. 7A and relative to the horizontal brace 118 of the container apparatus 100. In the embodiment illustrated the obtuse angle 142 is approximately 128°.

It is noted that a stability plate 144 is attached to the forward legs 112 at an angle such that when the container apparatus 100 is in its tilted orientation as shown in FIG. 7C, the stability plate 144 will be substantially horizontally oriented and will rest upon the floor 114.

It is also noted, that the tilting leg 120 has a lower end 146 which is formed at an angle such that when the apparatus

100 rests in its tilted position, the lower end 146 of tiltable leg 120 will flatly engage the ground surface 114, again to add stability to the tilted orientation of the apparatus 100.

#### THE EMBODIMENT OF FIGS. 8A-8C

FIGS. 8A-8C illustrate a further modified arrangement of the base framework 104 with a modified gas spring. The apparatus shown in FIGS. 8A-8C is generally designated by the numeral 150. It will be understood that although the apparatus 150 shows only the base framework 104, it also includes a wire mesh basket such as the basket 102 shown in FIGS. 6 and 7A-7C.

FIGS. 8A-8C are each partially sectioned elevation views looking from a position under the central portion of the apparatus 150 out toward one side, and thus these views show a view of the leg 152 which is somewhat hidden from external view.

In the embodiment of FIGS. 8A-8C, a tilting leg 152 is pinned to the cross brace 118 at pivot point 154. A kick plate 156 is attached to tilting leg 152 and is constructed to be engaged by the human foot to push the tilting leg 152 downward toward its extended position of FIG. 8C. A similar tilting leg (not shown) is attached to the opposite side of framework 104, and the two tilting legs are connected by a cross brace so that the legs move as one piece.

A mounting bracket 158 extends upward from the rear end of tilting leg 152.

When the tilting leg 152 is in its retracted position as shown in FIG. 8A the mounting bracket 158 extends upward above the cross brace 118. A gas spring 160 has its cylinder end connected at pivot point 164 to a bracket 162 attached to cross brace 118. The piston end of gas spring 160 is connected at pivot 166 to the bracket 158.

Thus, when the tilting leg 152 is in its raised position as shown in FIG. 8A, the gas spring 160 lies in a substantially horizontal orientation located just above the elevation of the cross brace 118.

The outward resilient force of the gas spring 160 will tend to hold the tilting leg 152 in its raised position as shown in FIG. 8A.

To move the tilting leg 152 downward, a human operator will engage the foot plate 156 and push downward on it, thus causing the tilting leg 152 to begin to rotate counterclockwise about pivot 154 through the position shown in FIG. 8B toward the position shown in FIG. 8C.

As the tilting leg 152 begins to rotate from its initial position of FIG. 8A, it will compress the piston portion of the gas spring 160 into the cylinder thereof, and the gas spring 160 will resist that motion. This will continue to be the case, until the bracket 158 pivots past a position substantially aligned with the length of the gas spring 160 after which the outward resilient force of the gas spring 160 will tend to reinforce the counterclockwise rotation of tilting leg 152. Thus the gas spring 160 will, in the final stages of rotation, help to move the tilting leg 152 past a vertical position toward and to its fully extended position as shown in FIG. 8C.

After the tilting leg 152 is moved to its fully extended position as shown in FIG. 8C, the apparatus 150 will be lowered to engagement with the ground floor in a manner analogous to that shown in FIG. 7C and the base framework 104 and the container attached thereto will rest upon the floor in a tilted position analogous to that shown in FIG. 7C.

FIG. 9 is a somewhat schematic sectioned view taken along line 9-9 of FIG. 8A and it shows an additional optional feature.

Preferably, a detachable cover **168** is supported from cross brace **118** to cover the gas cylinder **160** to help protect it from damage by possible engagement with the fork lift tines of the fork life truck.

Thus it is seen that the apparatus and methods of the present invention readily achieve the ends and advantages mentioned as well as those inherent therein. While certain preferred embodiments of the invention have been illustrated and described for purposes of the present disclosure, numerous changes in the arrangement and construction of parts and steps may be made by those skilled in the art, which changes are encompassed within the scope and spirit of the present invention as defined by the appended claims.

What is claimed is:

- 1. A tilting container apparatus comprising:
  - a container;
  - a leg pivotally mounted to the container for movement between a raised position and a lowered position, the leg supporting the container in a tilted position when the leg is in the lowered position;
  - a dampening controller connected between the container and the leg, for dampening pivotal movement of the leg between its raised and lowered positions; and
  - a kick plate attached to the leg, and extending laterally outward from the leg away from the container so that a human can move the leg between its raised and lowered positions by engaging the kick plate with a human foot.
- 2. The apparatus of claim 1, wherein:
  - the dampening controller also includes a means for holding the leg in its lowered position.
- 3. The apparatus of claim 2, wherein the means for holding the leg in its lowered position comprises a means for holding the leg at a greater than 90° angle from its raised position.
- 4. The apparatus of claim 1, wherein:
  - the dampening controller comprises a gas spring.
- 5. The apparatus of claim 1, further comprising:
  - a removable protective shield covering the dampening controller to prevent damage to the dampening controller from a fork lift lifting the container.
- 6. A tiltable container apparatus, comprising:
  - a container having first and second ends;
  - a pair of legs pivotally attached to the first end of the container;
  - a resilient retaining device connected between the container and at least one of the legs, for resiliently holding the legs in an extended position in which the legs support the container in a tilted orientation; and
  - a protective shield covering the resilient retaining device.
- 7. The apparatus of claim 6, wherein:
  - the resilient retaining device also comprises a means for dampening pivotal movement of the legs from their retracted position to their extended position.
- 8. The apparatus of claim 6, wherein:
  - the container includes a base; and
  - the legs are extended at an angle of greater than 90° from the base of the container when the legs are in their extended position.
- 9. The apparatus of claim 6, wherein:
  - the resilient retaining device comprises a gas spring.

- 10. The apparatus of claim 6, further comprising:
  - a kick plate attached to at least one of the legs.
- 11. A tiltable container apparatus, comprising:
  - a container;
  - a base for supporting the container in a level orientation from a ground surface, the base having a first end and a second end, and the base having a length from the first end to the second end; and
  - a pivotable support leg, having a length greater than one half the length of the base, the leg being pivotally attached to the base and pivotable between a retracted position wherein the base supports the container in a level orientation, and an extended position wherein the first end of the base is held above the ground surface so that the base and container are tilted, the support leg forming an obtuse angle with the base when the support leg is in its extended position.
- 12. The apparatus of claim 11, further comprising:
  - a gas spring connected between the base and the support leg.
- 13. The apparatus of claim 12, wherein:
  - the gas spring comprises a means for dampening movement of the pivotable support leg to its extended position.
- 14. The apparatus of claim 12, wherein:
  - the gas spring comprises a means for pushing the pivotable support leg past a 90° angle with the base to the obtuse angle.
- 15. The apparatus of claim 12, further comprising:
  - a shield surrounding the gas spring.
- 16. The apparatus of claim 11, further comprising:
  - a kick plate attached to the pivotable support leg.
- 17. A method of tilting a container to provide better access to an interior of the container, said method comprising the steps of:
  - (a) providing a container having an extendable support member at one end thereof;
  - (b) initially retaining the support member in a retracted position so that the container rests in a level orientation on a ground surface;
  - (c) lifting the container off of the ground surface;
  - (d) pushing on a kick plate attached to the support member and thereby extending the support member;
  - (e) during step (d), dampening movement of the support member; and
  - (f) lowering the container back onto the ground surface so that the support member holds the one end of the container higher than the other end and the container is supported in a tilted orientation.
- 18. The method of claim 17, wherein:
  - step (d) further comprises, pushing the support member past a 90° angle relative to a base of the container to a fully extended position wherein the support member forms an obtuse angle with the base of the container.
- 19. The method of claim 18, wherein the pushing step is accomplished with a gas spring.
- 20. The method of claim 17, wherein step (e) is further characterized as dampening the movement of the support member with a gas spring.