



(86) Date de dépôt PCT/PCT Filing Date: 2011/08/12
(87) Date publication PCT/PCT Publication Date: 2012/02/16
(45) Date de délivrance/Issue Date: 2018/10/16
(85) Entrée phase nationale/National Entry: 2014/02/11
(86) N° demande PCT/PCT Application No.: US 2011/047595
(87) N° publication PCT/PCT Publication No.: 2012/021810
(30) Priorités/Priorities: 2010/08/13 (US61/373,680);
2010/08/26 (US61/377,315); 2011/08/12 (US13/208,854)

(51) Cl.Int./Int.Cl. *B01J 19/00* (2006.01),
C07C 1/00 (2006.01), *C07C 7/10* (2006.01),
C10L 3/06 (2006.01), *E21B 43/295* (2006.01)
(72) Inventeurs/Inventors:
BRYANT, STEVEN L., US;
POPE, GARY A., US
(73) Propriétaire/Owner:
BOARD OF REGENTS, THE UNIVERSITY OF TEXAS
SYSTEM, US
(74) Agent: AVENTUM IP LAW LLP

(54) Titre : STOCKAGE DE DIOXYDE DE CARBONE ET PRODUCTION DE METHANE ET D'ENERGIE
GEOOTHERMIQUE A PARTIR DES AQUIFERES SALINS PROFONDS
(54) Title: STORING CARBON DIOXIDE AND PRODUCING METHANE AND GEOTHERMAL ENERGY FROM DEEP
SALINE AQUIFERS

(57) **Abrégé/Abstract:**

A novel idea involving the coupling of CO₂ geological storage with methane and/or heat production (geothermal energy) from geopressured-geothermal aquifers is described herein. The production of energy from the extracted brine offsets the cost of capture, pressurization, and injection and the subsequent injection of brine containing carbon dioxide back into the aquifer. Calculations described in the present invention indicate that this offset would reduce the cost of carbon capture and sequestration (CCS) to a point that CCS could survive in a competitive market environment without subsidies or a price on carbon.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property

Organization

International Bureau



WIPO | PCT



(10) International Publication Number

WO 2012/021810 A3

(43) International Publication Date
16 February 2012 (16.02.2012)

(51) International Patent Classification:

B01J 19/00 (2006.01) C07C 1/00 (2006.01)

E21B 43/295 (2006.01) C07C 7/10 (2006.01)

C10L 3/06 (2006.01)

(21) International Application Number:

PCT/US2011/047595

(22) International Filing Date:

12 August 2011 (12.08.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/373,680 13 August 2010 (13.08.2010) US

61/377,315 26 August 2010 (26.08.2010) US

13/208,854 12 August 2011 (12.08.2011) US

(71) Applicant (for all designated States except US): **BOARD OF REGENTS, THE UNIVERSITY OF TEXAS SYSTEM** [US/US]; 201 West 7th Street, Austin, TX 78701 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BRYANT, Steven, L.** [US/US]; 4109 Ramsey Avenue, Austin, TX 78756 (US). **POPE, Gary, A.** [US/US]; 302 Jeffrey Drive, Cedar Park, TX 78613 (US).(74) Agent: **SINGLETON, Chainey, P.**; Chalker Flores, LLP, 14951 North Dallas Parkway, Suite 400, Dallas, TX 75254 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(88) Date of publication of the international search report:

31 May 2012

(54) Title: STORING CARBON DIOXIDE AND PRODUCING METHANE AND GEOTHERMAL ENERGY FROM DEEP SALINE AQUIFERS

(57) Abstract: A novel idea involving the coupling of CO₂ geological storage with methane and/or heat production (geothermal energy) from geopressured-geothermal aquifers is described herein. The production of energy from the extracted brine offsets the cost of capture, pressurization, and injection and the subsequent injection of brine containing carbon dioxide back into the aquifer. Calculations described in the present invention indicate that this offset would reduce the cost of carbon capture and sequestration (CCS) to a point that CCS could survive in a competitive market environment without subsidies or a price on carbon.

WO 2012/021810 A3

STORING CARBON DIOXIDE AND PRODUCING METHANE AND GEOTHERMAL ENERGY FROM DEEP SALINE AQUIFERS

Technical Field of the Invention

The present invention relates in to general methane production, and more particularly to a method for storing CO₂ and producing methane and geothermal energy from an aquifer.

Background Art

Without limiting the scope of the invention, its background is described in connection with methods for carbon dioxide capture and methane production.

U.S. Patent No. 7,172,030 issued to Horner et al. (2007) discloses a process for the removal of a carbon dioxide constituent from a waste gas comprising a composition of constituents including carbon dioxide and another constituent. The carbon dioxide constituent in the Horner patent is retained in a subterranean reservoir having a water presence and the process comprising the steps of (i) providing at least one injection well and at least one production well, each completed in the reservoir, (ii) injecting the waste gas through the at least one injection well, (iii) separating at least some of the carbon dioxide constituent out of the waste gas by the water presence, a separated carbon dioxide constituent being retained in the water presence for retarding the movement of the separated carbon dioxide constituent towards the at least one production well, and (iv) producing gas from the at least one production well, the produced gas being substantially free of the separated carbon dioxide constituent.

Disclosure of the Invention

The invention described herein discloses a method for storing carbon dioxide and other greenhouse gases and producing methane, geothermal energy (heat) or both from deep saline aquifers and in particular from geopressured-geothermal geological formations containing brine with methane dissolved in the brine. The current approach to carbon capture and sequestration (CCS) from, for example, a pulverized coal-fired power plant, is not economically viable without either large subsidies or a very high price on carbon. Current schemes require roughly 1/3rd of a power plant's energy for CO₂ capture and pressurization, and neither merchant nor regulated utilities can accommodate this magnitude of added cost. The production of energy from geothermal aquifers has evolved as a separate, independent technology from the sequestration of carbon dioxide and other greenhouse gases in deep, saline aquifers. The method of the present invention combines these two technologies and adds another: dissolution of carbon dioxide into extracted brine, which is then re-injected. The production of energy from the extracted brine in the form of methane and/or thermal energy offsets the cost of capture,

pressurization and injection of the carbon dioxide into the aquifer.

According to one aspect of the present invention, there is provided a process for obtaining methane from a surface of the Earth, the process comprising: collecting a native brine comprising methane at the surface from a first well; contacting the collected native brine comprising methane with a gas comprising carbon dioxide (CO₂) thereby obtaining the methane from the collected native brine and forming a composition comprising the collected native brine and the gas comprising CO₂; and injecting the composition comprising the collected native brine and the gas comprising CO₂ into a second well.

According to another aspect of the present invention, there is provided a process for obtaining methane from, beneath a surface of the Earth, the process comprising: collecting a native brine comprising methane at the surface from a first well;—contacting the collected native brine comprising methane with a gas comprising carbon dioxide (CO₂) thereby obtaining the methane from the collected native brine and forming a composition comprising the collected native brine and the gas comprising CO₂;—injecting the composition comprising the collected native brine and the gas comprising CO₂ into a second well; and burning the methane in a gas turbine or steam boiler to generate electricity; or compressing the methane to form compressed natural gas (CNG), rocket fuel, liquefied natural gas, or any combination thereof.

According to a further aspect of the present invention, there is provided a method for carbon capture and sequestration (CCS) and obtaining methane in a deep saline aquifer beneath a surface of the Earth, the method comprising: collecting a native brine comprising methane at the surface from a first well; contacting the collected native brine comprising methane with a gas thereby obtaining the methane from the collected native brine and forming a composition comprising the collected native brine and the gas; wherein the gas comprises carbon dioxide (CO₂) or other greenhouse gases, the gas being from an industrial emitter, a coal-fired electric plant, a petrochemical plant or refinery, a flue, or any commercial, industrial, or household operation; injecting the collected native brine comprising the gas into a second well, thereby capturing and sequestering the gas in the native brine in the second well; and burning the methane in a gas turbine or steam boiler to generate electricity.

One embodiment of the present invention discloses a process for producing methane from an aquifer, a reservoir, or combinations thereof comprising the steps of: collecting a native brine obtained by

flowing or pumping to the surface from a first well or a set of wells made by drilling, digging, driving, boring, or combinations thereof, at a first location in the aquifer or the reservoir and extracting methane from a gas phase comprising methane in the native brine, wherein the extraction is done by contacting the native brine with carbon dioxide (CO₂) under pressure or by reducing pressure at a surface of the native brine, wherein the CO₂ displaces the gas phase comprising methane from the native brine. In some cases, free methane gas may exist or form in the aquifer (e.g., due to pressure drawdown near the production wells or by expulsion when mixed with the CO₂), so some methane gas will be produced at the surface in such cases without either of the operations of “contacting with CO₂ under pressure” or “reducing pressure at a surface”. The CO₂ used in the extraction is in a pure form or is a mixture of gases. The process described hereinabove further comprises the step of using the methane to generate electricity, as a fuel or to convert into chemicals.

In one aspect of the present invention the process further comprises the step of storing the carbon dioxide by injection of CO₂ dissolved in brine after separation of the methane or injection of both supercritical CO₂ and CO₂ dissolved in brine as a two-phase mixture into a second location in the aquifer or reservoir by the use of a second well or a set of wells, wherein the second well or set of wells is created by drilling, digging, driving, boring, or combinations thereof. In another aspect the aquifer is a non-geopressured-geothermal aquifer. In another aspect the aquifer is a geopressured-geothermal aquifer. In yet another aspect the mixture of gases comprises a flue gas from an industrial emitter, a gas from a coal-fired electric power plant, a gas from a petrochemical plant or refinery or gases from any commercial, industrial or household operations. In another aspect the pure CO₂ or the mixture of gases is contacted with the brine at pressures of about 100 psi to 1,000 psi or greater to dissolve it into the brine before injection of the brine into the aquifer, reservoir, or combinations thereof. In another aspect the pure CO₂ or the mixture of gases is contacted with the brine at pressures of 100 psi, 200 psi, 300 psi, 400 psi, 500 psi, 700 psi, 900 psi, 1,000 psi, 2,500 psi, 5,000 psi, and 10,000 psi. One aspect of the process described hereinabove further comprises the step of producing of geothermal energy from the brine by the extraction of energy from the native brine by heat exchange or any other suitable method.

Another embodiment of the present invention relates to a process for producing geothermal energy from an aquifer, a reservoir, or combinations thereof comprising the steps of: (i) collecting a native brine obtained by flowing or pumping to the surface from a first well or a set of wells made by drilling, digging, driving, boring, or combinations thereof, at a first location in the aquifer or the reservoir and extracting energy from the native brine by heat exchange, wherein the extraction results in a reduction of the temperature of the native brine. The process for producing geothermal energy further comprises the steps of: contacting carbon dioxide (CO₂) under pressure with the native brine after extraction of the geothermal energy, wherein the CO₂ is in a liquid, a supercritical fluid or is a two-phase mixture, wherein the CO₂ is in a pure form or is a mixture of gases and injecting the native

brine after extraction of geothermal energy into a second location in the aquifer or reservoir by the use of a second well or set of wells to store the CO₂, wherein the second well or set of wells is created by drilling, digging, driving, boring, or combinations thereof. In one aspect the aquifer is a non-geopressured-geothermal aquifer. In another aspect of the process the aquifer is a geopressured-geothermal aquifer. In yet another aspect the mixture of gases comprises a flue gas from an industrial emitter, a gas from a coal-fired electric power plant, a gas from a petrochemical plant or refinery or gases from any commercial, industrial or household operations.

In one aspect the pure CO₂ or the mixture of gases is contacted with the brine at pressures of about 100 psi to 1,000 psi or greater to dissolve it into the brine before injection of the brine into the aquifer, reservoir, or combinations thereof. In another aspect the pure CO₂ or the mixture of gases is contacted with the brine at pressures of 100 psi, 200 psi, 300 psi, 400 psi, 500 psi, 700 psi, 900 psi, 1,000 psi, 2,500 psi, 5,000 psi, and 10,000 psi. Yet another aspect of the process describes a step of producing methane from the brine by contacting carbon dioxide (CO₂) under pressure with the native brine or by reducing pressure at a surface of the native brine, wherein the CO₂ displaces a gas phase comprising methane from the native brine. The methane generated by the process described hereinabove is used to generate electricity, as a fuel or to convert into chemicals.

In yet another embodiment the present invention describes a process for producing methane and geothermal energy from an aquifer, a geopressured formation, a reservoir, or combinations thereof comprising the steps of: (i) pumping and collecting a native brine from a first location in the aquifer or the geopressured formation to a surface by the use of a first water well, wherein the first water well is created by digging, drilling, driving, boring, or combinations thereof, (ii) extracting methane from a gas phase comprising methane in the native brine, wherein the extraction is done by contacting the native brine with carbon dioxide (CO₂) under pressure or by reducing pressure at a surface of the native brine, wherein the CO₂ displaces the gas phase comprising methane from the native brine, and (iii) generating energy from the separated methane by a conversion of the methane to electricity by burning in a gas turbine or steam boiler, compressed natural gas (CNG), rocket fuel, liquefied natural gas, methane engine, and combinations and modifications thereof.

In one aspect the process further comprises injecting the brine after separation of the gas phase into a second location in aquifer or the geopressured formation by the use of a second well, wherein the second water well is created by digging, drilling, driving, boring, or combinations thereof. In another aspect the CO₂ is in a pure form or is a mixture of gases.

One embodiment of the present invention is related to a method for carbon capture and sequestration (CCS) in a deep saline aquifer, producing methane or both comprising the steps of: (i) providing carbon in the form of carbon dioxide (CO₂) or other greenhouse gases from an industrial emitter, a coal-fired electric plant, a petrochemical plant or refinery, a flue gas or any commercial, industrial or household operation, (ii) pumping and collecting a native brine from a first location in the aquifer to

a surface by the use of a first water well, wherein the first water well is created by digging, drilling, driving, boring, or combinations thereof, (iii) contacting the CO₂ under pressure with the native brine, wherein the CO₂ displaces a gas phase comprising methane from the native brine, (iv) separating the gas phase comprising methane from the brine, (v) injecting the brine after separation
5 of the gas phase into a second location in aquifer to capture and sequester the CO₂ in the brine by the use of a second well, wherein the second water well is created by digging, drilling, driving, boring, or combinations thereof, and (vi) generating electricity with the separated methane.

Another embodiment of the instant invention describes a closed-loop system for carbon capture and sequestration (CCS) in a geothermal aquifer, producing methane and geothermal energy or both
10 comprising: a pumping system for pumping a native brine from a first location in the aquifer to a surface by the use of a first water well, wherein the first water well is created by digging, drilling, driving, boring, or combinations thereof, a container, a tank, a well, a reservoir, and combinations and modifications thereof for collecting the native brine at the surface, providing carbon in the form of carbon dioxide (CO₂) or other greenhouse gases from an industrial emitter, a coal-fired electric
15 plant, a petrochemical plant or refinery, a flue gas or any commercial, industrial or household operation, extracting methane from a gas phase comprising methane in the native brine, wherein the extraction is done by contacting the native brine with carbon dioxide (CO₂) under pressure or by reducing pressure at a surface of the native brine wherein, the CO₂ displaces the gas phase comprising methane from the native brine, a system for separating the gas phase comprising methane
20 from the brine, an injection system for injecting the brine after separation of the gas phase into a second location in aquifer to sequester the CO₂ in the brine by the use of a second well, wherein the second water well is created by digging, drilling, driving, boring, or combinations thereof, and an energy generating system for converting the separated methane to electricity by burning in a gas turbine or steam boiler, compressed natural gas (CNG), rocket fuel, liquefied natural gas, methane
25 engine, and combinations and modifications thereof.

Description of the Drawings

None.

Description of the Invention

While the making and using of various embodiments of the present invention are discussed in detail
30 below, it should be appreciated that the present invention provides many applicable inventive concepts that can be embodied in a wide variety of specific contexts. The specific embodiments discussed herein are merely illustrative of specific ways to make and use the invention and do not delimit the scope of the invention.

To facilitate the understanding of this invention, a number of terms are defined below. Terms
35 defined herein have meanings as commonly understood by a person of ordinary skill in the areas relevant to the present invention. Terms such as “a”, “an” and “the” are not intended to refer to only

a singular entity, but include the general class of which a specific example may be used for illustration. The terminology herein is used to describe specific embodiments of the invention, but their usage does not delimit the invention, except as outlined in the claims.

5 The term “aquifer” as used herein relates to a water-bearing bed or stratum of permeable rock, sand or gravel capable of yielding considerable quantities of water to wells or springs. As used herein, the term “geothermal aquifer” refers to a porous zone in the earth’s crust which contains water which is at least about 60°C. As used herein the term “geopressed aquifer” refers to a porous zone in the earth’s crust, which contains water at a pressure exceeding the pressure corresponding to the normal hydrostatic value of about 0.45 psi/ft.

10 The term “brine” as used herein in various embodiments is used in a broad sense to denote the entire range of concentrations of aqueous solutions of water soluble inorganic compounds, for example, natural saline water containing sodium chloride, including brackish water, sea water, and saturated or nearly saturated brines, such as the brine in the Great Salt Lake or brines obtained from wells. In addition to sodium chloride-containing solutions, other brines to which the process may be applied
15 include aqueous solutions of dissolved mineral salts, for examples, halides, carbonates and sulfates of sodium, potassium, lithium, calcium, magnesium, zinc and copper.

The term “geothermal” as used in the specification and claims refers to those unusual occurrences of nature when hot fluids such as water and gas occur in pockets beneath the earth and have been tapped for their heat content.

20 The term “flue gas” as used herein includes the exhaust gas from any sort of combustion process (including coal, oil, natural gas, etc.).

The term “methane” as used herein includes natural gas comprising the elements carbon and hydrogen.

25 The term “petrochemical plant or refinery” as used herein refers to an industrial processing plant where crude oil is processed and refined into commercially valuable petroleum products, such as gasoline, diesel fuel, liquefied petroleum gas, etc.

The term “supercritical fluid” as used in the specification and claims refers to the state of matter of a material above its critical point, i.e., a critical temperature, T_c , and critical pressure, P_c , at which two phases of a substance, in equilibrium with each other, become identical, forming one phase. The
30 term “supercritical CO₂” as used herein refers to CO₂ that exhibits a pressure and temperature equal to or above its critical pressure and critical temperature (73.8 bar; 31.1° C.).

The term “wellbore” as used in the present application is defined as a bore hole extending from the earth surface to a target hydrocarbon-bearing formation. Thus, a wellbore is a conduit providing fluid communication between the surface and the target formation. The term “well” as used herein
35 is synonymous with the term “wellbore”. The term “boring” is intended to encompass any method of

forming a passage in an earth formation extending laterally or radially from a wellbore. The term “drilling”, likewise, will be taken to include exploration for and extraction of materials from the earth as well as formation of a deep hole through which the materials are extracted.

5 The term “psi” as used throughout the specification and claims is defined as pounds per square inch gauge pressure.

The term “gas turbine” as used herein refers to any turbine system having a compression section, combustion section, and turbine section.

The term “compressed natural gas (CNG)” as used herein refers to a fossil fuel substitute for gasoline (petrol), diesel, or propane/LPG.

10 A “greenhouse gas” of the present invention may include any gas which is known to contribute to the greenhouse effect. The term “greenhouse effect” herein is intended to encompass the environmental effects of global warming and/or acid rain. The “greenhouse gas” may comprise methane (CH₄), or any carbon oxide (CO_x) or nitrogen oxide (NO_x) gas. A carbon oxide of the present invention may comprise carbon monoxide (CO) or carbon dioxide (CO₂). The “greenhouse gas” may further
15 comprise any carbon-halogen or sulfur-halogen containing gas. A carbon-halogen containing gas may comprise methyl bromide (CH₃Br) or carbon tetrachloride (CCl₄). A carbon-halogen containing gas may further comprise a gas selected from hydrofluorocarbons (HFCs), chlorofluorocarbons (CFCs), and/or perfluorocarbons (PFCs).

20 The term “carbon sequestration” as used in the present application generally refers to the long-term storage of carbon in a multitude of ways, including, but not limited to, terrestrial, underground, or ocean environments to reduce the buildup of carbon dioxide in the atmosphere.

The invention involves producing by extraction or production wells brine from an aquifer, e.g., a geopressed-geothermal aquifer, containing methane dissolved in the brine, and/or producing methane gas that has been exsolved from the brine by contact with injected CO₂ by the use of
25 extraction or production wells. Brine with methane dissolved in it and/or methane gas is extracted from one or more production wells at the same time that carbon dioxide (CO₂) is dissolved into the produced brine and injected in one or more injection wells. In some cases however, free methane gas may exist or form in the aquifer (e.g. due to pressure drawdown near the production wells or by expulsion when mixed with the CO₂), so some methane gas will be produced at the surface in such
30 cases without either of the operations of “contacting with CO₂ under pressure” or “reduced the pressure at the surface” as indicated herein. Although it may not be common, it is possible for a small gas cap to already exist in the aquifer or to form in the aquifer while pumping it.

The produced methane is sold into the natural gas supply or used directly as a fuel or chemical and in addition thermal energy is extracted from the hot produced brine before it is mixed with carbon
35 dioxide and injected back into the same formation. The process thus is a “closed loop” with respect to brine, and a waste product (CO₂) replaces a valuable product (CH₄) in the aquifer.

An important application of the present invention is associated with the capture of carbon dioxide from a large industrial emitter such as a coal-fired electricity-generating power plant or a petrochemical plant or a refinery among many other possible sources of carbon dioxide or gases containing carbon dioxide. The cost of capturing and storing that CO₂, which is a key technology for mitigating greenhouse gas emissions, can be offset significantly by the revenue from selling the methane and/or geothermal energy of the hot brine from sufficiently deep, hot formations. Moreover, the simultaneous extraction and injection of brine through two sets of wells can be done in such a way that very little pressure buildup occurs in the formation whereas when fluids are injected without any production, as in the conventional way of storing CO₂ in deep, saline aquifers, the storage will often be severely limited by the pressure buildup in the aquifer. Still another method of accomplishing this purpose would be to inject both brine and gases containing carbon dioxide or other greenhouse gases while producing brine from other wells in the same aquifer.

One unusual feature of the present invention is the dissolution of CO₂ into the brine. The technology currently anticipated for geologic CO₂ storage is the injection of bulk phase (supercritical) CO₂. The other unusual feature is the production of methane and/or thermal energy from the extracted brine. Other proposed strategies for storing CO₂ in saline aquifers that extract brine do not recover valuable products from the brine.

The cost of capturing and storing anthropogenic CO₂ is large. The method of the present invention will reduce that cost and greatly increase the acceptance and feasibility of this method for mitigating “greenhouse” gas emissions. In addition the present invention possesses number of advantages over existing technologies: current technologies for injecting CO₂ in saline aquifers do not anticipate extraction from those aquifers. Consequently, the pressure buildup will restrict the injection rate since the pressure must be kept below a certain maximum value to avoid unacceptable risks associated such as fracturing of the aquifer’s seal. It has been proposed to extract brine to relieve this problem, but this leads to the issue of disposing the extracted brine. The advantages of the present invention are that (i) it closes the loop (the extracted brine is reinjected into the same formation) while deriving revenue from methane and thermal energy removed from the brine, (ii) injecting CO₂ dissolved in brine into these deep geopressured formations does not require large injection pressures, whereas injecting bulk phase CO₂ -- which would also sequester CO₂ and drive methane (CH₄) out of solution -- would require very large injection pressures in the surface equipment. This is expensive and imposes greater safety concerns. The present invention requires significantly smaller injection pressures, because the greater density of brine compared to the CO₂ gives a much larger bottom-hole pressure in these deep formations, and (iii) the brine in these formations is hot and could be used as a source of geothermal energy.

The conventional vehicle for carbon (CO₂) capture and pressurization from flue gas requires upwards of 30% of a power plant’s energy (1-6), making the cost of retrofitting the existing plants for carbon capture prohibitive. This energy penalty cannot be significantly reduced because of the

thermodynamic limit [$\sim 12\%$, (3)] for conventional capture methods and pressurization requirements. In addition, fundamental problems with current geological carbon sequestration methods (GCS) include, but are not limited to, the need to pressurize sufficiently to overcome aquifer pressure for injection, the increase in aquifer pressure resulting from limited CO_2 injectivity and from limited
5 brine diffusivity in the aquifer, and the risk of leakage of the buoyant CO_2 phase after injection. Beyond these technical problems is the economic challenge: CCS in aquifers is “pure cost” with no offsetting benefit [in the absence of a cost for CO_2 emission (e.g., cap and trade or carbon tax)].

To address these problems the present inventors developed an approach to CO_2 injection, taking advantage of both dissolved methane and geothermal energy from saline aquifers. Several very
10 important differences from conventional CCS are notable. First, instead of injecting CO_2 directly into the aquifer, native brine is pumped from the aquifer to the surface, and CO_2 captured from the flue gas is injected under modest pressure ($\sim 1,000$ psi) into the saline solution. Pressurization is required to return the saline water with dissolved CO_2 into the aquifer (through a different well), but injection is aided by the density of the CO_2 -saturated brine. Per unit volume of fluid this is less
15 costly energetically than pumping the same amount of CO_2 directly into a geopressured aquifer. Larger volumes of brine are needed, however, so that the total pumping costs are comparable to conventional CCS. Secondly, when CO_2 contacts water containing dissolved methane, almost all of the dissolved methane is expelled from solution (7) and forms a gas phase since methane is supercritical at the temperature of interest. The production of methane during the injection of
20 supercritical CO_2 into an aquifer has already been observed in the field (8). Thus, methane can be extracted and used to produce energy. Thirdly, the saline water comes to the surface at about 300°F and thus contains significant amounts of thermal energy that can be used in various ways. Fourthly, the CO_2 -saturated brine is denser than the native brine, which eliminates buoyant leakage and thus provides a much more robust permanence for CO_2 storage.

25 Formations of abnormally high pressure and temperature lie along the Gulf Coast of the United States at depths exceeding 10,000 feet. The water is often saturated or nearly saturated with dissolved methane (9, 10). During the 1970s, the U.S. Department of Energy funded several studies related to the development of these geopressured-geothermal reservoirs as an energy resource, both from the standpoint of heat recovery and as a source of natural gas (11). Several “wells of
30 opportunity” were tested on a short-term basis, primarily to assess the amount and quality of the natural gas associated with geopressured-geothermal waters. Table 1 from (11) is a summary of some of the results from test wells showing substantial production of methane. For example, the Pleasant Bayou No. 2 well produced 330 million SCF of natural gas from 1979 to 1983.

The methane content of these brines is on the order of 35 SCF per barrel of brine. Because these
35 aquifers are regionally extensive, the total amount of methane is enormous with estimates ranging from 3,000 to 46,000 TcF (11). In addition to the well characterized geopressured-geothermal aquifers along the Gulf Coast of Texas and Louisiana, there are likely to be other large sources of

methane dissolved in normally pressured saline aquifers in the U.S.; located in most geological basins where oil and gas are produced including but not limited to, the mid west, mid continent and west coast.

5 The energy content of the hot brine is also very significant. The temperature of Gulf Coast geothermal aquifers is about 300°F, and the energy that can be extracted from produced brine is of the same order of magnitude as the energy from the produced methane. For example, the change in enthalpy when the temperature of one barrel (42 gallons) of hot water is reduced from 300°F to 100°F is 70,000 Btu, which is about twice the energy content of the dissolved methane.

10 The manner of injecting CO₂ is a crucial component of this approach. The conventional and most straightforward way to sequester CO₂ is to inject it directly into the aquifer as a supercritical fluid. When the CO₂ mixes with the methane-saturated brine in the aquifer, the methane will come out of solution and flow upward where it can be captured and produced from a production well at a higher elevation in the aquifer (7). However, injecting only CO₂ requires another aquifer or separate costly injection wells in the same aquifer to receive the extracted brine. Moreover, calculations by the
15 inventors show that it is preferable to inject brine containing dissolved CO₂ rather than just CO₂. In this case, injected brine displaces the native brine bearing dissolved methane toward the production wells in the aquifer. The displacement of one brine by another brine is a much more efficient process than the displacement of a less viscous and less dense fluid such as supercritical CO₂, in the sense that one volume of injected brine displaces nearly one volume of native brine, while one volume of
20 injected supercritical CO₂ may displace only a small fraction of native brine due to well known mechanisms for preferential flow (gravity override by the less dense CO₂ and fingering of the less viscous CO₂ phase through the brine phase). The brine-displacement-by-brine process thus results in a much higher recovery of the methane and thermal energy (heat) than injecting supercritical CO₂ and has other significant advantages, notably the ability to control the aquifer backpressure that limits
25 injection rates in conventional CCS. Bryant and co-workers (17, 18) have proposed injecting dissolved CO₂ in conventional aquifers as a way to eliminate buoyant leakage and reduce the “footprint” of pressure and fluid displacement, but they did not couple this process with the production of methane and/or geothermal energy.

Table 1: Summary of field data taken from (11).

	Pleasant Bayou No.2	Amoco Fee No.1	Girouard No.1	Saldana No.2	Prairie Canal No.2	Crown Zellerbach No.1
Parish or County	Brazoria, TX	Cameron, LA	Lafayette, LA	Zapata, TX	Calcasieu, LA	Livingston, LA
Shut-in Surface Pressure, psi	-	-	6,695	2,443	6,420	2,736
Max Flow Rate, BWPD	28,900	36,500	15,000	1,950	7,100	2,832
Max Gas Rate, Mcfd	-	-	600	105	390	93
Produced Gas-Water Ratio, scf/bbl	23	27-29.8	40	47-54	43-55	33
Water Salinity-TDS, ppm	131,320	97,800	23,500	12,800	42,600	32,000
Carbon Dioxide, mole %	11.28	9.92	6	26.4-16.4	9.6	22.6
Formation	Lower Miocene Oligocene	Upper Oligocene	Frio-Marg. Tex No.1	Upper Wilcox	Hackberry, Upper Frio	Tuscaloosa
Perforations, ft	14,644-14,704	15,160-15,470	14,774-14,819	9,745-9,820	14,782-14,820	16,720-16,750
Net Interval, ft	53	333	91	79	14	35
Original Reservoir Pressure, psi	11,168	12,799	13,203	6,627	12,942	10,075
Original Reservoir Temperature, °F	305	291	274	300	294	327
Porosity-Log, %	18	16	26	16	28	17
Permeability-Test, md	192	160	200-240	16.7	95	16.6

The manner of injecting CO₂ is a crucial component of this approach. The conventional and most straightforward way to sequester CO₂ is to inject it directly into the aquifer as a supercritical fluid. When the CO₂ mixes with the methane-saturated brine in the aquifer, the methane will come out of solution and flow upward where it can be captured and produced from a production well at a higher elevation in the aquifer (7). However, injecting only CO₂ requires another aquifer or separate costly injection wells in the same aquifer to receive the extracted brine. Moreover, calculations by the inventors show that it is preferable to inject brine containing dissolved CO₂ rather than just CO₂. In this case, injected brine displaces the native brine bearing dissolved methane toward the production wells in the aquifer. The displacement of one brine by another brine is a much more efficient process than the displacement of a less viscous and less dense fluid such as supercritical CO₂, in the sense that one volume of injected brine displaces nearly one volume of native brine, while one volume of injected supercritical CO₂ may displace only a small fraction of native brine due to well known mechanisms for preferential flow (gravity override by the less dense CO₂ and fingering of the less viscous CO₂ phase through the brine phase). The brine-displacement-by-brine process thus results in a much higher recovery of the methane and thermal energy (heat) than injecting supercritical CO₂ and has other significant advantages, notably the ability to control the aquifer backpressure that limits injection rates in conventional CCS. Bryant and co-workers (17, 18) have proposed injecting dissolved CO₂ in conventional aquifers as a way to eliminate buoyant leakage and reduce the “footprint” of pressure and fluid displacement, but they did not couple this process with the production of methane and/or geothermal energy.

Table 2 lists the properties of an idealized geopressured-geothermal aquifer with characteristics such as porosity, permeability, temperature and pressure typical of those in the Gulf Coast. An equation-of-state compositional simulator with a coupled wellbore model was used to study the proposed process for this and similar geopressured-geothermal aquifers. Brine saturated with CO₂ was injected at 200,000 B/D, and brine saturated with methane was produced at the same rate to keep the aquifer pressure constant and avoid problems associated with increasing or decreasing pressure. The equation of state was tuned to fit experimental solubility of CO₂ and CH₄ in brine under these conditions.

The brine saturated with CO₂ is injected until it reaches the production well. At this time, the simulations show that 560 billion scf (29.4 million tons) of CO₂ has been stored in the aquifer, and about 56% of the original methane (98 billion scf) has been produced. The molar ratio of stored CO₂ to produced methane is 5.7, which is close to the solubility ratio under these conditions. Other simulations for aquifers with different net pay, well rates and so forth show very similar ratios, so the results can be easily scaled using this ratio. At \$8 per million Btu, the value of the methane would be \$784 million. If 1/2 of the heat could be used by reducing the temperature of the hot water from 300°F to 100°F, then at the same value per Btu it would be worth about \$800 million for a total revenue of \$1.584 billion. Assuming \$50 per ton for capturing and pressurizing CO₂ from power plants using conventional CCS, the total revenue exceeds the total cost of \$1.47 billion needed to capture and pressurize the CO₂ and it eliminates the need to build new power plants to provide the enormous amount of energy needed for that purpose. The actual economics will also depend on the cost of the wells and facilities among other factors and requires further analysis.

Table 2: Summary of aquifer properties.

Length and width, ft	10000
Thickness, ft	2000
Depth at top of the formation, ft	15000
Temperature, °F	300
Initial Pressure, psi	12000
Porosity	0.15
Horizontal Permeability, md	200
Vertical Permeability, md	20
Initial CH ₄ in place, Billions of scf	175
Initial brine in place, Billions of stb	5.0

Although much research has been done and is currently underway to investigate CO₂ geological storage, the coupling of CO₂ geological storage with methane and/or thermal energy production from geopressured-geothermal aquifers as described herein is novel. The potential for reducing the cost of CO₂ capture and storage from pulverized coal-fired power plants and other sources by producing large quantities of valuable methane and/or geothermal energy is very significant.

It is contemplated that any embodiment discussed in this specification can be implemented with respect to any method, kit, reagent or composition of the invention, and vice versa. Furthermore, compositions of the invention can be used to achieve methods of the invention.

5 It will be understood that particular embodiments described herein are shown by way of illustration and not as limitations of the invention. The principal features of this invention can be employed in various embodiments without departing from the scope of the invention. Those skilled in the art will recognize or be able to ascertain using no more than routine experimentation, numerous equivalents to the specific procedures described herein. Such equivalents are considered to be within the scope of this invention and are covered by the claims.

10 All publications and patent applications mentioned in the specification are indicative of the level of skill of those skilled in the art to which this invention pertains.

The use of the word “a” or “an” when used in conjunction with the term “comprising” in the claims and/or the specification may mean “one,” but it is also consistent with the meaning of “one or more,” “at least one,” and “one or more than one.” The use of the term “or” in the claims is used to mean “and/or” unless explicitly
15 indicated to refer to alternatives only or the alternatives are mutually exclusive, although the disclosure supports a definition that refers to only alternatives and “and/or.” Throughout this application, the term “about” is used to indicate that a value includes the inherent variation of error for the device, the method being employed to determine the value or the variation that exists among the study subjects.

20 As used in this specification and claim(s), the words “comprising” (and any form of comprising, such as “comprise” and “comprises”), “having” (and any form of having, such as “have” and “has”), “including” (and any form of including, such as “includes” and “include”) or “containing” (and any form of containing, such as “contains” and “contain”) are inclusive or open-ended and do not exclude additional, unrecited elements or method steps.

The term “or combinations thereof” as used herein refers to all permutations and combinations of the listed
25 items preceding the term. For example, “A, B, C or combinations thereof” is intended to include at least one of: A, B, C, AB, AC, BC or ABC, and if order is important in a particular context, also BA, CA, CB, CBA, BCA, ACB, BAC or CAB. Continuing with this example, expressly included are combinations that contain repeats of one or more item or term, such as BB, AAA, AB, BBC, AAABCCCC, CBBAAA, CABABB, and so forth. The skilled artisan will understand that typically there is no limit on the number of items or terms in
30 any combination, unless otherwise apparent from the context.

All of the compositions and/or methods disclosed and claimed herein can be made and executed without undue experimentation in light of the present disclosure. While the compositions and methods of this invention have been described in terms of preferred embodiments, it will be apparent to those of skill in the

art that variations may be applied to the compositions and/or methods and in the steps or in the sequence of steps of the method described herein without departing from the concept, spirit and scope of the invention. All such similar substitutes and modifications apparent to those skilled in the art are deemed to be within the scope of the invention as defined by the appended claims.

5 References

U.S. Patent No. 7,172,030: Applications of Waste Gas Injection into Natural Gas Reservoirs.

1. H. Jesse Smith et al., *Science* 325, 1641 (2009).
2. R. S. Haszeldine, *Science* 325, 1647 (2009).
3. G. T. Rochelle, *Science* 325, 1652 (2009).
- 10 4. D. W. Keith, *Science* 325, 1654 (2009).
5. F. M. Orr, Jr., *Science* 325, 1656 (2009).
6. D. P. Schrag, *Science* 325, 1658 (2009).
7. I. Taggart, Society of Petroleum Engineers, SPE 124630, Proceedings of the Annual Technical Conference and Exhibition, New Orleans, 4-7 October (2009).
- 15 8. K. Romanak, et al., Bureau of Economic Geology, The University of Texas at Austin, Texas, private communication (2010).
9. M. Dorfman and R.O. Kehle, Bureau of Economic Geology, The University of Texas at Austin, Geological Circular 74-4 (1977).
10. P. H. Jones, Proceedings, First Geopressured Geothermal Energy Conference, Austin, Texas, Ed. M. Dorfman and R. W. Deller (1975).
- 20 11. J. Griggs, Proceedings of the 30th Workshop of Geothermal Reservoir Engineering, Stanford University, an 21-Feb. 2 (2005).
12. H. Ohkuma et al., Geothermal Resources Council, Transactions, 3 September (1979).
13. R. C. MacDonald et al., Final Report (Year 3), Center for Energy studies, The University of Texas at Austin (1979).
- 25 14. R. C. MacDonald et al., Final Report (Year 4), Center for Energy studies, The University of Texas at Austin (1980).
15. O. Isokari and R. M. Knapp, Society of Petroleum Engineers SPE 6037, 51st Annual Fall Technical Conference, New Orleans, 3-6 October (1976).
- 30 16. R. C. MacDonald et al., *J. Energy Resources Technology* 103 (1981).

17. M. Burton and S. L. Bryant, Energy Procedia 1(1): 3707-3714, ISSN 1876-6102, DOI: 10.1016/j.egypro.02.169 (2009).
18. M. Burton and S. L. Bryant, Society of Petroleum Engineers, SPE Reservoir Evaluation & Engineering, 12, 399 (2009).

CLAIMS

1. A process for obtaining methane from a surface of the Earth, the process comprising:
collecting a native brine comprising methane at the surface from a first well;
5 contacting the collected native brine comprising methane with a gas comprising carbon dioxide (CO₂) thereby obtaining the methane from the collected native brine and forming a composition comprising the collected native brine and the gas comprising CO₂; and
injecting the composition comprising the collected native brine and the gas
10 comprising CO₂ into a second well.
2. The process of claim 1, wherein the gas is pure CO₂; or a mixture of CO₂ and one or more gases.
3. The process of claim 1, wherein the composition further comprises supercritical CO₂.
4. The process of claim 1, wherein the first well is in a non-geopressured-geothermal
15 aquifer.
5. The process of claim 1, wherein the first well is in a geopressured-geothermal aquifer.
6. The process of claim 1, wherein the gas comprises a flue gas from: an industrial emitter; a gas from a coal-fired electric power plant; a gas from a petrochemical plant or refinery; or a gas from a commercial, industrial or household operations.
- 20 7. The process of claim 1, wherein the gas is contacted with the collected native brine at a pressure of from 100 psi to 1,000 psi.
8. The process of claim 1, further comprising extracting geothermal energy from the collected native brine comprising methane by heat exchange.

9. A process for obtaining methane from, beneath a surface of the Earth, the process comprising:
- collecting a native brine comprising methane at the surface from a first well;
 - contacting the collected native brine comprising methane with a gas comprising carbon dioxide (CO₂) thereby obtaining the methane from the collected native brine and forming a composition comprising the collected native brine and the gas comprising CO₂;
 - injecting the composition comprising the collected native brine and the gas comprising CO₂ into a second well; and
 - burning the methane in a gas turbine or steam boiler to generate electricity; or
 - compressing the methane to form compressed natural gas (CNG), rocket fuel, liquefied natural gas, or any combination thereof.
10. The process of claim 9, wherein the gas is pure CO₂; or a mixture of CO₂ and one or more gases.
11. A method for carbon capture and sequestration (CCS) and obtaining methane in a deep saline aquifer beneath a surface of the Earth, the method comprising:
- collecting a native brine comprising methane at the surface from a first well;
 - contacting the collected native brine comprising methane with a gas thereby obtaining the methane from the collected native brine and forming a composition comprising the collected native brine and the gas;
 - wherein the gas comprises carbon dioxide (CO₂) or other greenhouse gases, the gas being from an industrial emitter, a coal-fired electric plant, a petrochemical plant or refinery, a flue, or any commercial, industrial, or household operation;
 - injecting the collected native brine comprising the gas into a second well, thereby capturing and sequestering the gas in the native brine in the second well; and
 - burning the methane in a gas turbine or steam boiler to generate electricity.