



(22) Date de dépôt/Filing Date: 2017/09/22

(41) Mise à la disp. pub./Open to Public Insp.: 2018/05/29

(45) Date de délivrance/Issue Date: 2022/07/26

(30) Priorités/Priorities: 2016/11/29 (US62/427,393);
2017/09/14 (US15/704,762)

(51) Cl.Int./Int.Cl. *E21B 33/04* (2006.01),
E21B 19/06 (2006.01)


(72) Inventeur/Inventor:
ROSS, STEPHEN C., US

(73) Propriétaire/Owner:
INNOVEX DOWNHOLE SOLUTIONS, INC., US

(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : DISPOSITIF DE SUSPENSION DE COLONNE DE PRODUCTION DOTE D'UN ACCES AU TROU DE FORAGE, ET METHODE D'ACCES A UN TROU DE FORAGE

(54) Title: TUBING HANGER ASSEMBLY WITH WELLBORE ACCESS, AND METHOD OF ACCESSING A WELLBORE



(57) Abrégé/Abstract:

A tubing hanger assembly for suspending a tubing string within a wellbore is provided. The tubing hanger assembly comprises a tubing head, a tubing hanger and a tubing head adapter. The tubing hanger and the tubing head adapter have aligned through-openings such that a chemical injection line and a communications line may each be passed through respective through-openings, thereby enabling an operator to have access to the wellbore. Beneficially, the assembly also comprises a bottom flange that secures the tubing head adapter to the tubing head once the tubing hanger and connected string of production tubing are landed in the wellbore. The bottom flange may be rotated so that ports in the bottom flange may be aligned with ports in an upper flange in the tubing head. A method for hanging a string of production tubing in a wellbore is also provided herein.

ABSTRACT

A tubing hanger assembly for suspending a tubing string within a wellbore is provided. The tubing hanger assembly comprises a tubing head, a tubing hanger and a tubing head adapter. The tubing hanger and the tubing head adapter have aligned through-openings such that a chemical injection line and a communications line may each be passed through respective through-openings, thereby enabling an operator to have access to the wellbore. Beneficially, the assembly also comprises a bottom flange that secures the tubing head adapter to the tubing head once the tubing hanger and connected string of production tubing are landed in the wellbore. The bottom flange may be rotated so that ports in the bottom flange may be aligned with ports in an upper flange in the tubing head. A method for hanging a string of production tubing in a wellbore is also provided herein.

TUBING HANGER ASSEMBLY WITH WELLBORE ACCESS, AND METHOD OF ACCESSING A WELLBORE

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Serial No. 62/427,393 filed November 29, 2016. That application is entitled "Tubing Hanger Assembly With Wellbore Access, and Method of Accessing a Wellbore".

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

[0002] Not applicable.

THE NAMES OF THE PARTIES TO A JOINT RESEARCH AGREEMENT

[0003] Not applicable.

BACKGROUND OF THE INVENTION

[0004] This section is intended to introduce various aspects of the art, which may be associated with exemplary embodiments of the present disclosure. This discussion is believed to assist in providing a framework to facilitate a better understanding of particular aspects of the present disclosure. Accordingly, it should be understood that this section should be read in this light, and not necessarily as admissions of prior art.

Field of the Invention

[0005] The present disclosure relates to the field of hydrocarbon recovery operations. More specifically, the present invention relates to a system for hanging a string of production tubing in a wellbore, while allowing an operator access to the wellbore from the surface. The invention also relates to a method of accessing a wellbore through a tubing hanger assembly using a novel adapter.

Technology in the Field of the Invention

[0006] In the drilling of oil and gas wells, a wellbore is formed using a drill bit that is urged downwardly at a lower end of a drill string. The drill bit is rotated while force is applied

through the drill string and against the rock face of the formation being drilled. After drilling to a predetermined depth, the drill string and bit are removed and the wellbore is lined with a string of casing.

[0007] It is common to place several strings of casing having progressively smaller outer diameters into the wellbore. In this respect, the process of drilling and then cementing progressively smaller strings of casing is repeated several times until the well has reached total depth. The final string of casing, referred to as a production casing, is typically cemented into place.

[0008] As part of the completion process, the production casing is perforated at a desired level. Alternatively, a sand screen may be employed at a lowest depth in the event of an open hole completion. Either option provides fluid communication between the wellbore and a selected zone in a formation. In addition, production equipment such as a string of production tubing, a packer and a pump may be installed within the wellbore.

[0009] During completion, a wellhead is installed at the surface. Fluid gathering and processing equipment such as pipes, valves and separators are also provided. Production operations may then commence.

[0010] In typical land-based production operations, the wellhead includes a tubing head and a tubing hanger. The tubing head seals the wellbore at the surface while the tubing hanger serves to gravitationally support the long string of production tubing. The tubing string extends down from the tubing hanger proximate to a first pay zone.

[0011] During the production process, the production tubing may experience thermal expansion over time. This is due to the presence of warm production fluids being produced up through the pipe and to the surface. To offset the anticipated expansion, it is known to place the production tubing under some degree of tension when the well is completed. This will maintain the production tubing in a linear state even while the pipe string relaxes in response to thermal expansion. Thus, even when the production tubing expands over time, the tubing does not buckle within the wellbore. This is of particular benefit when the wellbore is being rod pumped, as pre-tensioning minimizes frictional contact between the rod string and the surrounding production tubing during pumping.

[0012] In connection with hanging the tubing in the wellbore, it is sometimes desirable to run an electric line to provide power to a resistive heater or to an electric submersible pump (or “ESP”) downhole. U.S. Patent No. 6,688,386 entitled “Tubing Hanger and Adapter Assembly” provides one wellhead arrangement for running a power cable at the surface through a tubing hanger system. Such a wellhead arrangement uses an adapter above the tubing head to accommodate and to isolate the electric line. However, this and other known wellhead assemblies have limitations concerning the alignment of ports drilled in the adapter with through-openings located in the top flange of the tubing head.

[0013] In connection with hanging the tubing in the wellbore, it is further desirable to provide a fluid supply line into the well. However, existing tubing tensioning arrangements generally prevent the use of the somewhat non-ductile fluid supply line that will descend through and below the tubing hanger. Moreover, known tubing hangers generally require that the tubing string be rotated or turned five or more times in connection with setting the tubing anchor downhole and locking the tubing hanger at the surface. Typical stainless steel chemical injection lines cannot tolerate the stress and tension induced by the produced torque, nor can they be “snaked” through access ports that are not perfectly aligned.

[0014] Accordingly, a need exists for a tubing hanger assembly that enables hanging tubing from a tubing head at the surface with less than one complete rotation of the production string during hanging. Further, a need exists for an improved tubing hanging system that is able to accommodate a chemical injection line without twisting the metal line as it enters the wellhead and travels downhole. Still further, a need exists for an adapter that is part of the wellhead that enables a communications line to be run through the tubing hanger and down the wellbore, and that connects to survey equipment downhole.

SUMMARY OF THE INVENTION

[0015] A tubing hanger assembly for suspending a tubing string within a wellbore is provided herein. Beneficially, the tubing hanger assembly provides a rotating flange that freely rotates relative to a tubing head in order to eliminate alignment issues with connection ports during installation.

[0016] The tubing hanger assembly first includes a tubing head. The tubing head resides over the wellbore and seals the wellbore in order to isolate wellbore fluids. The tubing head defines a cylindrical bore that is configured to receive the tubing string. The tubing head is configured to land over a wellbore and to help seal the wellbore at the surface during production operations.

[0017] The tubing hanger system also includes a tubing hanger. The tubing hanger defines a cylindrical body having an upper end and a lower end. The lower end includes female threads for making a threaded connection with an uppermost joint of the tubing string.

[0018] The tubing hanger is configured to reside within the cylindrical bore of the tubing head over the wellbore. In this way, the tubing hanger gravitationally supports the tubing string. In one aspect, a beveled surface along an outer diameter of the tubing hanger lands on a matching conical shoulder along an inner diameter of the tubing head. This is referred to as a “landed” position and seals by means of elastomers (or “o-rings”).

[0019] Preferably, the tubing string is connected to a tubing anchor within the wellbore such that the tubing string is maintained in tension. Preferably, the tubing hanger and the tubing anchor are each configured to be set through a rotation of the tubing string that is less than one full rotation. This avoids placing a chemical injection line running down the tubing string under torque.

[0020] In one embodiment of the current invention, the cylindrical body of the tubing hanger comprises at least one, and preferably two, elongated through-openings. The through-openings extend from a bottom end of the cylindrical body, up to a top end. An inner diameter of a first through-opening may be dimensioned to receive a chemical injection line, while an inner diameter of a second through-opening may be dimensioned to receive a separate communications line. The communications line may be an electric line, a power line or a fiber optic cable.

[0021] The tubing hanger system further includes a tubing hanger adapter. The tubing hanger adapter resides over the tubing head. The tubing hanger adapter also defines a cylindrical body having a bore, wherein the cylindrical bore of the tubing head adapter is in alignment with the cylindrical bore of the tubing head when the tubing head adapter is installed.

[0022] The body of the tubing head adapter also contains at least one elongated through opening that runs generally from the lower end to the upper end of the tubing head adapter. These through openings are referred to as auxiliary holes. A first auxiliary hole has an inner diameter that matches the inner diameter of the first through-opening in the tubing hanger, while a second auxiliary hole has an inner diameter that matches the inner diameter of the second through-opening in the tubing hanger. In addition, the auxiliary holes are positioned within the cylindrical body of the tubing head adapter to align with (or to be alignable with) the respective through-openings in the cylindrical body of the tubing hanger.

[0023] Using the first auxiliary hole, the chemical injection line passes through the tubing head adapter and the body of the tubing hanger, and then runs along the tubing string to a designated depth within the wellbore. Similarly, using the second auxiliary hole, the communications line passes through the tubing head adapter and the body of the tubing hanger. The communications line then runs along the tubing string to a designated depth within the wellbore, and connects to one or more sensors. Preferably, the chemical injection line and the communications line are clamped to selected joints of the tubing string.

[0024] The tubing hanger system may further include a bottom rotating flange. The bottom rotating flange defines a cylindrical body having a plurality of ports formed there through. Preferably, 8 to 12 ports are equi-distantly spaced around the body. The bottom rotating flange includes a beveled surface along an inner diameter. The beveled inner surface is dimensioned to land on a matching conical surface that resides along an outer diameter of the tubing head adapter. More specifically, the conical surface resides along a top flange of the tubing head.

[0025] Beneficially, the bottom rotating flange rotates along the matching conical shoulder along the outer diameter of the tubing head's top flange. This means that the matching conical shoulder serves as a bearing surface. In this way, ports drilled in the bottom rotating flange may be rotated to align with ports located along an upper shoulder of the tubing head. Threaded connectors may then be placed through the aligned ports and tightened to create a sealed connection between the tubing head adapter and the tubing head.

[0026] During completion, the chemical injection line passes through the first auxiliary hole of the tubing head adapter, and then passes through the aligned through-opening of the

tubing hanger. The chemical injection line continues down hole to a depth proximate a pump. Similarly, the communications line passes through the second auxiliary hole of the tubing head adapter, and then passes through the aligned through-opening in the tubing hanger. The communications line continues down hole to a designated depth.

[0027] The communications line has a connected sensor such as a temperature sensor or a pressure sensor. The communications line may be an electric line or a fiber optic cable. In one aspect, the communications line is a power cable that provides power to a downhole resistive heater element or to an ESP.

[0028] A method for accessing a wellbore is also provided herein. The method involves securing a tubing head to a casing string above the wellbore. The tubing head defines a cylindrical body having an elongated through-opening, forming a bore.

[0029] Next, a tubing string is lowered through the bore of the tubing head, joint-by-joint, and into the wellbore. The tubing string defines a series of tubing joints having threaded connections. A tubing hanger is then threadedly connected to an upper tubing joint.

[0030] The method next provides landing the tubing hanger onto the tubing head. As noted above, the tubing hanger is configured to reside within the cylindrical bore of the tubing head over the wellbore. In this way, the tubing hanger gravitationally supports the tubing string. A conical surface along an outer diameter of the tubing hanger lands on a matching conical shoulder along an inner diameter of the tubing head to place the tubing hanger in its landed position.

[0031] In one aspect, the method also provides for running both a chemical injection line and a communications line into the wellbore. Preferably, both the chemical injection line and the communications line are clamped to the production tubing, joint-by-joint, as the production tubing is run into the wellbore. Preferably, the method also includes securing at least one downhole sensor to a bottom end of the communications line before the communications line is run into the wellbore.

[0032] The method also includes providing a tubing head adapter. The tubing head adapter also defines a cylindrical body having a bore. The cylindrical body contains at least

one elongated through-opening that runs generally from the lower end to the upper end. The through openings are again referred to as auxiliary holes. The method then includes aligning the auxiliary holes with matching through-openings residing along the body of the tubing hanger.

[0033] In one aspect, a first auxiliary hole is dimensioned to receive an upper end of the chemical injection line. The chemical injection lines runs through the tubing hanger body, then through the tubing hanger, and then along the tubing string to a designated depth within the wellbore. The designated depth is preferably at or just below the pump. A second auxiliary hole is dimensioned to receive an upper end of the communications line. The communications line also runs through the tubing hanger body, then through the tubing hanger, and is clamped to the tubing string. The communications line is connected to a sensor such as a temperature sensor or a pressure sensor. The communications line may be an electric line or a fiber optic cable.

[0034] In another embodiment, a third auxiliary hole is dimensioned to receive a power cable. The power cable provides power to a downhole resistive heater element or to an ESP.

[0035] The method may further include placing a rotating bottom flange onto an outer diameter of the body of the tubing head adapter. The bottom flange is then rotated in order to align ports residing in the bottom flange with ports residing in a top flange of the tubing head. Threaded connectors are then run through the aligned ports and are tightened in order to secure the tubing head adapter to the tubing head itself.

BRIEF DESCRIPTION OF THE DRAWINGS

[0036] So that the manner in which the present inventions can be better understood, certain illustrations, charts and/or flow charts are appended hereto. It is to be noted, however, that the drawings illustrate only selected embodiments of the inventions and are therefore not to be considered limiting of scope, for the inventions may admit to other equally effective embodiments and applications.

[0037] Figure 1 is a cut-away view of a tubing head assembly for supporting a string of production tubing from the surface. The tubing head assembly includes a tubing head, a tubing hanger and a tubing head adapter.

[0038] Figure 2 is a cut-away view of the tubing head of Figure 1, without the tubing head adapter. The tubing head has received a tubing hanger, with the tubing hanger being in its landed position, supporting a string of production tubing.

[0039] Figure 3 is a side view of a portion of a well head wherein the tubing head assembly of Figure 1 is installed. The tubing head adapter and a rotating flange for the adapter are shown installed below the well head. The adapter is configured to be secured onto a top of the tubing head of Figure 1.

[0040] Figure 4A is a perspective view of a tubing hanger of the tubing hanger system of Figure 1, in one embodiment.

[0041] Figure 4B is a side view of the tubing hanger of Figure 4A.

[0042] Figure 4C is a cross-sectional view of the tubing hanger of Figure 4A.

[0043] Figure 4D is an end view of the tubing hanger of Figure 4A, taken from a bottom end.

[0044] Figure 5A is a first side view of a tubing head adapter of the present invention, in one embodiment. The tubing head adapter includes a pair of illustrative auxiliary holes machined through a body (holes shown in Figure 6).

[0045] Figure 5B is a second side view of the tubing head adapter of Figure 5A, wherein the tubing head adapter has been rotated 90° clockwise relative to the view of Figure 5A.

[0046] Figure 5C is a bottom view of the tubing head adapter of Figures 5A and 5B.

[0047] Figure 6 is a cut-away view of the tubing head adapter of Figures 5A and 5B. First and second auxiliary holes are visible.

[0048] Figure 7A is a perspective view of a rotating flange of the tubing head adapter of Figure 2. The rotating flange is a “bottom flange,” and is configured to be placed on and around the tubing head adapter. The rotating flange is used to fixedly secure the tubing head adapter to the tubing head.

[0049] Figure 7B is a side view of the rotating flange of Figure 7A.

[0050] Figure 8A is a perspective view of a seal sub of the present invention, in one embodiment. The seal sub is a cylindrical body used to provide a fluid seal between the tubing head adapter and the tubing hanger.

[0051] Figure 8B is a side view of the seal sub of Figure 8A.

[0052] Figure 8C is an end view of the seal sub of Figure 8A, taken from the lower end.

[0053] Figure 9A is a perspective view of a spin-on flange. The spin-on flange is a threaded “upper flange,” and is used to secure the upper threaded end of the tubing head adapter to an upper portion of the wellhead, or to a valve.

[0054] Figure 9B is a side view of the spin-on flange of Figure 9A.

[0055] Figure 9C is an end view of the spin-on flange of Figure 9A, taken from a bottom end.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS

Definitions

[0056] For purposes of the present application, it will be understood that the term “hydrocarbon” refers to an organic compound that includes primarily, if not exclusively, the elements hydrogen and carbon. Hydrocarbons may also include other elements, such as, but not limited to, halogens, metallic elements, nitrogen, oxygen, and/or sulfur.

[0057] As used herein, the term “hydrocarbon fluids” refers to a hydrocarbon or mixtures of hydrocarbons that are gases or liquids. For example, hydrocarbon fluids may include a hydrocarbon or mixtures of hydrocarbons that are gases or liquids at formation conditions, at processing conditions, or at ambient condition. Hydrocarbon fluids may include, for example, oil, natural gas, coalbed methane, shale oil, pyrolysis oil, pyrolysis gas, a pyrolysis product of coal, and other hydrocarbons that are in a gaseous or liquid state.

[0058] As used herein, the terms “produced fluids,” “reservoir fluids” and “production fluids” refer to liquids and/or gases removed from a subsurface formation, including, for example, an organic-rich rock formation. Produced fluids may include both hydrocarbon fluids and non-hydrocarbon fluids. Production fluids may include, but are not limited to, oil, natural gas, pyrolyzed shale oil, synthesis gas, a pyrolysis product of coal, oxygen, carbon dioxide, hydrogen sulfide and water.

[0059] As used herein, the term “fluid” refers to gases, liquids, and combinations of gases and liquids, as well as to combinations of gases and solids, combinations of liquids and wellbore fines, and combinations of gases, liquids, and fines.

[0060] As used herein, the term “wellbore fluids” means water, hydrocarbon fluids, formation fluids, or any other fluids that may be within a wellbore during a production operation.

[0061] As used herein, the term “gas” refers to a fluid that is in its vapor phase.

[0062] As used herein, the term “subsurface” refers to geologic strata occurring below the earth's surface.

[0063] As used herein, the term “formation” refers to any definable subsurface region regardless of size. The formation may contain one or more hydrocarbon-containing layers, one or more non-hydrocarbon containing layers, an overburden, and/or an underburden of any geologic formation. A formation can refer to a single set of related geologic strata of a specific rock type, or to a set of geologic strata of different rock types that contribute to or are encountered in, for example, without limitation, (i) the creation, generation and/or entrapment

of hydrocarbons or minerals, and (ii) the execution of processes used to extract hydrocarbons or minerals from the subsurface.

[0064] As used herein, the term “communication line” or “communications line” refers to any line capable of transmitting signals or data. The term also refers to any insulated line capable of carrying an electrical current, such as for power.

[0065] As used herein, the term “wellbore” refers to a hole in the subsurface made by drilling or insertion of a conduit into the subsurface. A wellbore may have a substantially circular cross section, or other cross-sectional shapes. The term “well,” when referring to an opening in the formation, may be used interchangeably with the term “wellbore.” When used in connection with a drilling process, the term “bore” refers to the diametric opening formed in the subsurface through the drilling process.

Description of Selected Specific Embodiments

[0066] A tubing hanger assembly is provided herein. The tubing hanger assembly enables a string of production tubing to be hung from a wellhead at the surface. At the same time, the assembly enables access to the wellbore below the tubing head from the surface. Access means that one or more chemical injection lines and/or one or more communications lines may be run through the tubing head en route to the wellbore.

[0067] **Figure 1** is a cut-away view of a tubing hanger assembly **100** for supporting a string of production tubing **20**. The tubing hanger assembly **100** is designed to reside at a surface. The surface may be a land surface; alternatively, the surface may be an ocean bottom or a lake bottom, or a production platform offshore. The tubing hanger system **100** is designed to be part of a larger wellhead (not shown, but well-familiar to those of ordinary skill in the art) used to control and direct production fluids from the wellbore and to enable access to the “back side” of the tubing string **20**.

[0068] The tubing hanger assembly **100** includes a tubing head **200**, a tubing head adapter **300**, and a tubing hanger **400**. The illustrative tubing hanger assembly **100** also includes a rotating flange **700**, referred to herein at times as a “bottom rotating flange.” The bottom rotating flange **700** is used to secure the tubing head adapter **300** to the tubing head **200**.

[0069] **Figure 2** is a cut-away view of the full tubing head **200** of **Figure 1**. Here, the tubing head adapter **300** has been removed for illustrative purposes. The tubing head **200** has received a tubing hanger **400**, with the tubing hanger being in its landed position along an inner bore **205** of the tubing head **200**. A string of production tubing **20** is shown extending down from the tubing hanger **400**.

[0070] The tubing head **200** resides over a wellbore **110**. The tubing head **200** serves to seal the wellbore **110** and to isolate wellbore fluids at the surface. The tubing head **200** defines a cylindrical body **210** that is configured to closely receive the tubing string **20**. The tubing head **200** has an upper (or top) flange **202** and a lower (or bottom) flange **204**. As will be described in further detail below, the top flange **202** is configured to receive a tubing head adapter **300** using threaded connectors **309** having threads (seen at **319** in **Figure 3**). Nuts **317** threadedly fasten onto the threads **319** to tighten the tubing head adapter **300**. Preferably, the upper flange offers a plurality of openings (seen in **Figure 2** at **215**) to receive respective connectors **309**. The bottom flange **204** is configured to cover the wellbore **110**.

[0071] As noted, the tubing hanger system **100** also includes a tubing head adapter **300**. **Figure 3** is a side view of a portion of a well head, showing the tubing head adapter **300**. The bottom rotating flange **700** is also shown in **Figure 3**.

[0072] The tubing head adapter **300** is designed to reside over the tubing head **200**. More specifically, the adapter **300** is configured to be secured onto the top flange **202** of the tubing head **200** by means of the threaded connectors **309**. The threaded connectors **309** are placed through openings **715** (shown in **Figure 3**) in the bottom rotating flange **700**, and then through aligned openings **215** in the top flange **202** of the tubing head **200**.

[0073] The tubing head adapter **300** also defines a cylindrical body (shown best at **310** in **Figures 5A** and **5B**). The body **310** defines a bore (shown at **305** in **Figures 5C** and **6**). The cylindrical bore **305** of the tubing head adapter **300** is in parallel alignment with the cylindrical bore **205** of the tubing head **200** when the tubing head adapter **300** is installed. Additional details concerning the tubing head adapter **300** are described in connection with **Figures 5A, 5B, 5C** and **6**, below.

[0074] As noted, the tubing hanger system 100 also includes a tubing hanger 400. **Figure 4A** is a perspective view of a tubing hanger 400 of the tubing hanger assembly 100 of **Figure 1**, in one embodiment. The tubing hanger 400 defines a cylindrical body 410, having an upper end 402 and a lower end 404. The lower end 404 includes female threads for making a threaded connection with an upper joint of the tubing string 20. Those of ordinary skill in the art will know that the upper end of a joint of tubing string is referred to as the “pin end.”

[0075] **Figure 4B** is a side view of the tubing hanger 400 of **Figure 4A**. **Figure 4C** is a cross-sectional view of the tubing hanger 400 of **Figure 4A**. It can be seen that the tubing hanger 400 is essentially a male-to-male threaded connector sub. **Figure 4D** is an end view of the tubing hanger 400, taken from a bottom end 404. A bore 405 runs from the bottom end 404 up to the top end 402.

[0076] The tubing hanger 400 is configured to reside within the bore of the tubing head 200 over the wellbore 110. In this way, the tubing hanger 400 gravitationally supports the tubing string 20. The bore 405 of the tubing hanger 400 is aligned with the production tubing 20. In one aspect, a beveled surface 415 along an outer diameter of the body 410 lands on a matching conical surface 220 (shown in **Figure 2**) along an inner diameter of the tubing head 200. This provides a metal-to-metal seal, referred to as a landed (or “resting”) position.

[0077] The tubing hanger 400 includes two lower recessed portions 418. These recessed portions 418 are configured to receive “o-rings” (seen in **Figure 1** at 408). The o-rings 408 provide a seal between the tubing hanger 400 and the surrounding tubing head 200 below lock pins 211. The tubing hanger 400 also includes an upper recessed portion 419. Recessed portion 419 is configured to receive an optional o-ring (not shown) above the lock pins 211.

[0078] The lock pins 211 are seen in **Figures 1** and **2**. The lock pins 211 reside on opposing sides of the tubing head 200. The lock pins 211 help secure the tubing string 20 in place, meaning they prevent relative rotation of the tubing string 20 within the tubing head 200. The opposing pins 211 are tightened into the tubing head 200 and lock into the tubing hanger 400 which supports the tubing string 20. As the pins 211 are tightened within the upper flange 202 of the tubing head 200, the pins 211 engage a central recessed outer diameter portion 420 of the tubing hanger 400.

[0079] As noted, the tubing hanger **400** supports a tubing string **20**. Preferably, the tubing string **20** is connected to a tubing anchor (not shown) within the wellbore **110**. In this way, the tubing string **20** may be maintained in tension. It is understood by those of ordinary skill in the art that by suspending the tubing string **20** from the surface, at least an upper portion of the tubing string **20** will reside in a state of tension. However, in long strings of jointed tubing when a reciprocating pump is used, the portion of the tubing string **20** closest to the tubing anchor will rest on the anchored pump barrel, causing at least the lower portion of the tubing string **20** to go into compression. This, in turn, causes buckling which causes premature wear of the rods and tubing. Accordingly, operators will pull the tubing string **20** into slight tension before “hanging,” and then lock the tubing string **20** into place using the tubing hanger **400**.

[0080] Preferably, the tubing hanger **400** and/or the tubing anchor (not shown) are each configured to be set through a rotation of the tubing string that is less than one full rotation. This avoids placing a chemical injection line running down the tubing string **20** under stress. For a description of this technology, U.S. Serial No. 15/643,202 filed July 06, 2017 and entitled “Tubing Hanger System, and Method of Tensioning a Production Tubing in a Wellbore” is referred to. This application is co-owned by Applicant herein.

[0081] In one embodiment of the current invention, the cylindrical body **410** of the tubing hanger **400** comprises at least one, and preferably two, elongated through-openings **422**, **423**. These are seen best in **Figures 2** and **4C**. The through-openings **422**, **423** extend from the top end **402** of the cylindrical body **410**, down to the bottom end **404**. An inner diameter of a first through-opening **422** may be dimensioned to receive a chemical injection line (seen best in **Figure 2** at **106**), while an inner diameter of a second through-opening **423** may be dimensioned to receive a communications line (seen best in **Figure 2** at **107**).

[0082] The chemical injection line **106** is preferably a small-diameter (such as 1/4"), stainless steel tubing. The chemical injection line **106** is used to inject chemicals such as steam, corrosion inhibitors, foam and water. The injection line **106** extends down into the wellbore **110** and terminates at a pump inlet (not shown). In this way, treating fluid is delivered proximate a reciprocating pump (not shown) below the anchor to treat the pump hardware.

[0083] The communications line **107** may be an electric data line or a fiber optic cable. The communications line **107** likewise extends down into the wellbore **110** to a designated depth. One or more sensors (not shown) are connected to the communications line **107** proximate a bottom end. The sensors may sense, for example, down hole temperature, pressure or fluid density. Sensor readings may be transmitted up the communications line **107** where they may be stored in memory at the surface. More preferably, sensor readings are transmitted at the surface to a remote processor for storage and analysis.

[0084] In order to facilitate routing the chemical injection line **106** and the communications line **107** from the surface, the tubing head adapter **300** is provided. Features of the tubing head adapter **300** are better seen in **Figures 5A, 5B and 5C**. **Figure 5A** is a first side view of the tubing head adapter **300** of the present invention, in one embodiment. **Figure 5B** is a second side view of the tubing head adapter **300** of **Figure 5A**, taken from a side opposite the first side view. In **Figure 5B**, the tubing head adapter **300** has been rotated 90-degrees clockwise relative to the view of **Figure 5A**. **Figure 5C** is a bottom view of the tubing head adapter **300** of **Figures 5A and 5B**.

[0085] It can be seen that the tubing head adapter **300** again includes a somewhat cylindrical and somewhat bell-shaped body **310**. The body **310** of the tubing head adapter **300** also contains at least one elongated through opening that runs generally from the upper end **302** down to the lower end **304**. These through openings are referred to as auxiliary holes. Auxiliary holes **522, 523** are best seen in **Figures 3, 5A and 5C**.

[0086] The upper end **302** of the tubing head adapter **300** defines a cylindrical neck **325**. The cylindrical neck **325** is configured to threadedly receive a spin-on flange (shown in **Figure 9A** at **900**). Male Acme threads **315** receive female threads within a bore **905** of the flange **900** to secure a lower flange **55** and connected valve **25**.

[0087] A first auxiliary hole **522** has an inner diameter that matches the inner diameter of the first through-opening **422** in the tubing hanger **400**. At the same time, a second auxiliary hole **523** has an inner diameter that matches the inner diameter of the second through-opening **423** in the tubing hanger **400**.

[0088] **Figure 6** is a cut-away view of the tubing head adapter **300** of **Figures 3, 5A and 5B**. Here the auxiliary hole **522** for the chemical injection line **106** and the auxiliary hole **523** for the communications line / electrical wires **107** are more clearly seen. In addition, a central bore **305** of the tubing head adapter **300** is visible.

[0089] It is again observed that the tubing head adapter **300** defines a generally cylindrical body **310**. A top end **302** of the body **310** defines a connector having threads **315**, while a bottom end **304** of the body **310** is flanged outward. The body **310** includes a conical surface **320** configured to receive a beveled surface (seen at **720** in **Figure 7A**) of a bottom flange **700**.

[0090] As noted, the tubing head adapter **300** includes a pair of auxiliary holes **522, 523** machined there through. The auxiliary holes **522, 523** are shown in phantom in **Figure 5A**. However, the auxiliary holes **522, 523** are better seen in **Figure 6**.

[0091] Also visible in **Figure 6** is a test port **312**. The test port **312** allows an operator or a regulatory agency to test whether the tubing hanger system **100** is able to hold pressure after the system **100** is completely assembled.

[0092] It is understood that during well completion, sections of production tubing **20** in the form of joints are run into the wellbore **110**. The 1/4" tubing **106** and the communications line **107** are banded to the tubing joints until the production tubing **20** reaches a specific depth. Once the specific depth is achieved, the tubing hanger **400** is threadedly connected to the tubing **20** at the surface. At that point, the 1/4" tubing **106** and the communications line **107** are cut near the top of the derrick where the pulleys are located. Then, the remaining length of the banded 1/4" tubing **106** and communication line **107** for sensors (and associated survey equipment) are pulled through the tubing hanger **400**.

[0093] Compression fittings **126, 127** are connected to each of the auxiliary holes **422, 423** on the bottom of the tubing hanger **400**. The 1/4" tubing **106** is then inserted through the bottom end of the tubing hanger **400** in auxiliary hole **422** and the electrical wire (or, optionally, fiber optic cable) **107** is inserted through auxiliary hole **423** from the bottom of the tubing hanger **400**. This procedure allows the 1/4" tubing to have no splices within the

wellbore **110**, and the tubing hanger **400** can be tested through the test port **312** on the tubing head adapter **300** for holding pressure when completely assembled.

[0094] The tubing anchor is intended to be run into the wellbore **110** near the bottom of the tubing string **20**. Below the tubing anchor, perhaps less than 100 feet, is a downhole pump (not shown). The pump is installed along the tubing string **20** in conjunction with the tubing anchor at the surface before run-in. In operation, the tubing string **20** is lowered into the wellbore **110** while keeping the proximal (or top) end of the tubing anchor still at the surface. Another section of pipe is connected to the tubing connector. From that point, a check valve (not shown) connected to the 1/4" chemical injection line is banded to the joint of pipe. The tubing anchor is then threaded to a joint of tubing string **20** for run-in.

[0095] Returning to the assembly **100**, the tubing hanger assembly **100** further includes a bottom rotating flange **700**. **Figure 7A** is a perspective view of a rotating flange **700** of the tubing head adapter **300** of **Figure 6**. **Figure 7B** is a side view of the rotating flange **700** of **Figure 7A**.

[0096] The bottom rotating flange **700** is configured to be placed on the tubing head adapter **300**, and is used to fixedly secure the tubing head adapter **300** to the tubing head **200**. The rotating flange **700** defines a cylindrical body **710**. The body **710** has a plurality of ports **715** formed there through. Preferably, 8 to 12 ports **715** are equi-distantly spaced around the body **710**. In addition, the bottom rotating flange **700** has a bore **705** dimensioned to receive the body **310** of the tubing head adapter **300**.

[0097] The bottom rotating flange **700** also includes a beveled surface **720**. The beveled surface **720** is placed along an inner diameter. The beveled inner surface **720** is dimensioned to land on a matching conical surface (shown at **320** in **Figure 6**) that resides along an outer diameter of the tubing head adapter **300**.

[0098] Beneficially, the bottom rotating flange **700** rotates along the matching conical surface **320** of the tubing head adapter **300**. This means that the matching conical surface **320** serves as a bearing surface. In this way, ports **715** drilled in the bottom flange **700** may be manually rotated to align with two or more ports (seen at **215** in **Figure 2**) located along an upper shoulder (or flange) **202** of the tubing head **200** during assembly. Threaded connectors

309 may then be placed through the aligned ports **715, 215** and tightened (such as by using nuts **317**) to create a sealed connection between the tubing head adapter **300** and the tubing head **200**.

[0099] In order to further provide a sealed fluid connection between the tubing head adapter **300** and the tubing head **200**, a seal sub **800** is provided. The seal sub **800** is shown in **Figure 2** extending up from the tubing hanger **400**.

[00100] **Figure 8A** is a perspective view of a seal sub **800** of the present invention, in one embodiment. As can be seen, the seal sub **800** defines a cylindrical body **810** having a bore **805** there through. The seal sub **800** has a top end **802** that is received in the bore **305** of the tubing head adapter **300**, and a male-threaded bottom end **804** configured to be threadedly connected with the upper (box) end **402** of the tubing hanger **400**.

[00101] **Figure 8B** is a side view of the seal sub **800** of **Figure 8A**, while **Figure 8C** is an end view, taken from the lower end **804**. Upon assembly, the bore **805** of the seal sub **800** is aligned with the bore **305** of the tubing head adapter **300** and the bore **405** of the body **410** of the tubing hanger **400**. Various seals or o-rings may be placed about an outer diameter of the body **810**. This serves to fluidically seal the seal sub **800** within the tubing hanger **400** and the tubing head adapter **300** at opposing ends.

[00102] As can be seen, a tubing hanger assembly **100** is provided that includes both a novel tubing head adapter **300** and a tubing hanger **400**. The tubing hanger system **100** allows an operator to have access to the wellbore **110** for the purpose of injecting treatment chemicals. Treatment chemicals are injected through a chemical injection line **106** which passes through an auxiliary hole **522** in the tubing head adapter **300** and extending through the tubing hanger **400**. In addition, the tubing hanger system **100** allows an operator to have access to the wellbore **110** for the purpose of monitoring well pressure and temperature by using survey equipment with communications line **107** which passes through an auxiliary hole **523** strategically placed within the tubing head adapter **300** and extending through the tubing hanger **400**.

[00103] The tubing hanger **400** is suited with concentric tubing connections along with two other through openings **422, 423** that are drilled axially in reference to the wellbore **110**. These

through openings **422**, **423** provide a route for chemicals to be passed on to sub-surface equipment (through line **106**) and for electrical wires or fiber optic cable (via line **107**) to deliver energy to well survey equipment and to optionally transmit readings or data signals to the surface.

[00104] In operation, once the tubing hanger **400** is in its landed position, the lock pins **211** are engaged and the seal sub **800** is inserted to connect and seal the tubing hanger **400** and the tubing head adapter **300**. Before the tubing head adapter **300** is placed on top of the tubing head **200**, it is assembled for installation. **Figure 3** demonstrates the bottom rotating flange **700** of the tubing head adapter **300** in place so that the conical surface **320** of the tubing head adapter **300** and the matching beveled surface **720** of the bottom rotating flange **700** engage to form a metal-to-metal seal. All bolts **309** specified for the size of the flange **700** are placed through the holes **715** of the bottom rotating flange **700** and the aligned through-openings **215** of the top flange **202** of the tubing head **200** in preparation to receive the fasteners (nuts **317**) that connect the tubing head **200** and the tubing head adapter **300** together.

[00105] Compression fittings **116**, **117** are connected to the top end of the auxiliary ports **522**, **523** on the tubing head adapter **300**. The test port **312** is plugged off until it is used for testing the holding pressure after complete installation.

[00106] As part of the wellhead, a tubing valve **25** may be placed on the top of the tubing head adapter **300**. The valve **25** includes an actuator **50** for either manually or mechanically opening and closing the valve **25**. The valve **25** includes upper **15** and lower **55** flanges. The upper flange **15** may be used for connecting to additional valves or a lubricator. The upper flange **15** also serves as a “lifting flange” to enable the operator to pick up the valve **25** and place it over the tubing head assembly **100**. In one aspect, the lifting flange **15** is removed after the valve **25** is installed onto the tubing head assembly **100**.

[00107] The lower flange **55** is used to connect to the upper end **302** (shown in **Figure 5A**) of the tubing head adapter **300**. Below the lower flange **55** is an upper rotating flange (called a “spin-on” flange) **900**. The lower flange **55** and the upper rotating flange **900** are connected by means of a connector **909**.

[00108] **Figure 9A** is a perspective view of the spin-on flange **900**, in one embodiment. **Figure 9B** is a side view of the spin-on flange **900** of **Figure 9A**, while **Figure 9C** is an end view, taken from a bottom end. It can be seen that the spin-on flange **900** defines a cylindrical body **910** having a bore **905** there through. The body **910** has a threaded inner diameter. In addition, the body **910** has a plurality of ports **915** spaced equi-distantly about its radius. The ports **915** are dimensioned to receive a threaded connector **909**. The threaded connector **909** comprises threads **919** which secure the lower flange **55** to the spin-on flange **900**, thereby rotatingly securing the valve **25** to the tubing head adapter **300**.

[00109] In one embodiment, a connection ring (or “ring bonnet” shown at **10** in **Figure 1**) is provided above an end face of the threads **315** of the tubing head adapter **300**. More specifically, the ring bonnet **10** is placed in ring groove **930** residing in an upper face of the spin-on flange **900**. A matching ring groove is placed along an under-surface of the lower flange **55**. A ring bonnet **10** then resides in aligned ring groove **930** between the under-surface of the lower flange **55** and the top of the spin-on flange **900**.

[00110] Similarly, a ring bonnet **30** may be placed along ring groove **34** residing in an upper face of the upper flange **202**. A matching ring groove **36** is placed along an under-surface of the tubing head adapter **300**. The tubing head adapter **300** is then placed on the top of the tubing head **200** to engage the separate ring bonnet **30**. Thus, a ring bonnet **30** also resides in aligned ring grooves **34**, **36** between the bottom **304** of the tubing head adapter **300** and the top **202** of the tubing head **200**.

[00111] During installation, the valve **25** is orientated to benefit the installer's specific requirements. Ports radially disposed about the lower flange **55** are aligned with ports radially disposed about the spin-on flange **900**. Then, two or more threaded fasteners **909** of the spin-on flange **900** are placed through aligned ports and torqued accordingly to tighten the lower flange **55** onto the tubing head adapter **300**. The ring bonnet **10** is secured tightly there between.

[00112] Next, the lifting flange **15** is placed on the top end of the valve **25** so that the valve **25** and connected tubing head adapter **300** can be lifted and installed on the tubing head **200**. In one aspect, the valve **25** is secured to the tubing head adapter **300**, with the tubing hanger **400** residing in the tubing head bore and with a ring bonnet **30** in place over the tubing head **200**, before the tubing head adapter **300** is lowered onto the tubing head **200**.

[00113] The 1/4" (or, optionally, 3/8" or 5/8") i.d. chemical injection tubing **106** is passed through the bottom of the adapter's **300** auxiliary port **522**. In addition, the electrical wire **107** for downhole survey equipment is passed through the bottom of the tubing head adapter's **300** first auxiliary port **523**. Ports **715** are aligned with ports **215**. The all-thread connectors **309** are then fastened using nuts **317** to bring the tubing head adapter **300** and the tubing head **200** together. In one aspect, the lifting flange **15** is then removed.

[00114] The operator finally routes the 1/4" (or other size) chemical injection tubing **106** and communications line **107** used for the downhole survey equipment to their proper locations above ground. In one aspect, the communications line **107** is a data cable connected to a processor (not shown) in communication with a transceiver. In this way, data signals may be received and analyzed remotely. Optionally, a control signal may be sent by a well operator from a remote location to increase or decrease a distribution of treatment chemical through the chemical injection tubing **106**.

[00115] As can be seen, an improved tubing hanger assembly **100** is provided. The tubing hanger assembly **100** provides a system of engineered parts that enable an operator to access a wellbore with a chemical injection line **106** and a communications line **107** while overcoming port alignment issues present in existing wellheads. At the same time, the tubing string **20** may be maintained in the wellbore in tension from the surface.

[00116] Using the assembly **100**, the operator may monitor well activity with survey equipment. The rotating flange **700** on the body **310** of the adapter **300** enables the operator to secure the adapter **300** to the tubing head **200** with the tubing hanger **400** already in place and with the through-openings **422**, **423** in the tubing hanger **400** already aligned with the auxiliary holes **522**, **523** in the adapter **300**.

[00117] Yet another advantage of the assembly **100** is the spin-on flange **900** on the top end of the adapter **300**. With this flange **900** having rotation, it gives the freedom to place a valve **25** or other flange on top of the adapter **300** with alignment capabilities.

[00118] While it will be apparent that the inventions herein described are well calculated to achieve the benefits and advantages set forth above, it will be appreciated that the inventions are susceptible to modification, variation and change without departing from the spirit thereof.

CLAIMS

What is claimed is:

1. A tubing hanger assembly for suspending a tubing string within a wellbore, comprising:

- a tubing head having an upper end and a lower end, wherein the upper end comprises a flange having a plurality of radially disposed ports, and wherein the tubing head defines a central bore having a conical surface;

- a tubing hanger configured to reside along the central bore of the tubing head over the wellbore, and to connect to and support the tubing string, wherein the tubing hanger comprises:

- a generally tubular body having an upper end, a lower end and an outer diameter, with the outer diameter having a beveled surface configured to land on and to be gravitationally supported by the conical surface of the tubing head;

- a central bore extending from the upper end to the lower end; and

- a first through-opening extending through the tubular body from the upper end to the lower end, and configured to receive a line therethrough;

- a tubing head adapter configured to reside over the tubing head and over the tubing hanger, the tubing head adapter comprising:

- a body having an upper end, a lower end, and an outer diameter, with the outer diameter having a conical surface;

- a central bore extending from the upper end of the tubing head adapter to the lower end; and

- a first auxiliary hole extending through the body of the tubing head adapter, the first auxiliary hole having an open top end in the body of the tubing head adapter and an open bottom end located in the lower end of the tubing head adapter, and configured to receive the line therethrough when the first auxiliary hole is aligned with the first through-opening of the tubing hanger;

- wherein the tubing head adapter may be rotated during assembly to place the first auxiliary hole in alignment with the first through-opening of the tubing hanger; and

- a bottom rotating flange defining a tubular body having a central bore dimensioned to rotatably receive the body of the tubing head adapter, and a plurality of ports radially placed around the central bore, wherein the central bore includes a beveled surface dimensioned to

land on the conical surface along the outer diameter of the tubing head adapter when the body of the tubing head adapter is received within said central bore;

wherein the bottom rotating flange is position able on the tubing head adapter such that, when mounted on the tubing head adapter, the bottom rotating flange can be rotated independently of the tubing head adapter with the beveled surface of the central bore rotating on the conical surface of the tubing head adapter such that the conical surface serves as a bearing surface, and further wherein such rotation of the bottom rotating flange during assembly serves to align the ports in the bottom rotating flange with the ports in the tubing head, without rotation of the tubing head adapter, such that threaded connectors can be secured within the aligned ports in order to secure the bottom rotating flange and the tubing head adapter to the tubing head after the first auxiliary hole of the tubing head adapter has been aligned with the first through-opening of the tubing hanger.

2. The tubing hanger assembly of claim 1, wherein:

the tubing hanger further comprises a second through-opening also extending through the tubular body from the upper end to the lower end of the tubing hanger;

the tubing head adapter further comprises a second auxiliary hole extending through the body of the tubing head adapter, the second auxiliary hole having an open top end in the body of the tubing head adapter and an open bottom end located in the lower end of the tubing head adapter;

wherein the tubing head adapter and tubing hanger are configured such that when the tubing head adapter is positioned over the tubing hanger with the first auxiliary hole in alignment with the first through-opening of the tubing hanger, the second auxiliary hole will be in alignment with the second through-opening of the tubing hanger.

3. The tubing hanger assembly of claim 2, wherein:

the tubing head further comprises two or more lock pins disposed equi-radially about the tubing head flange, wherein the lock pins are configured to be rotated into engagement with the tubing hanger to rotatably lock the tubing hanger and supported tubing string in place within the tubing head.

4. The tubing hanger assembly of claim 2, wherein:

the upper end of the tubing head comprises a face having a radial groove;

the lower end of the tubing head adapter also comprises a face having a radial groove;
and

the tubing hanger assembly further comprises a ring bonnet defining an annular body having a ring along an outer diameter, wherein the ring is dimensioned to be received within both the radial groove of the tubing head and the radial groove of the tubing head adapter when the tubing head adapter is lowered into place on the tubing head.

5. The tubing hanger assembly of claim 2, wherein:

the upper end of the tubing head adapter comprises a threaded end; and

the tubing hanger assembly further comprises a spin-on flange adapted for rotationally adjustable attachment of a valve to the tubing hanger assembly, said spin-on flange defining a generally cylindrical body having a threaded bore, wherein the threaded bore of the spin-on flange is dimensioned to threadedly connect to the upper threaded end of the tubing head adapter.

6. The tubing hanger assembly of claim 5, wherein:

the spin-on flange further comprises a plurality of threaded openings equi-radially disposed about the cylindrical body of the spin-on flange, and dimensioned to receive a connector for threadedly connecting a flange of a valve above the tubing hanger assembly.

7. The tubing hanger assembly of claim 2, further comprising:

a chemical injection line passing through the first auxiliary hole of the tubing head adapter and an aligned first through-opening in the tubing hanger, wherein the chemical injection line extends down into and through the central bore of the tubing head; and

a communications line passing through the second auxiliary hole of the tubing head adapter and an aligned second through-opening in the tubing hanger, wherein the communications line also extends down into and through the central bore of the tubing head.

8. The tubing hanger assembly of claim 7, wherein:

the chemical injection line comprises steel tubing.

9. The tubing hanger assembly of claim 7, wherein the communications line comprises an electrical line, a power cable, a fiber optic cable, or combinations thereof.

10. The tubing hanger assembly of claim 7, further comprising:
a compression fitting residing around the chemical injection line proximate the upper end of the tubing head adapter;
a compression fitting residing around the communications line proximate the upper end of the tubing head adapter;
a compression fitting residing around the chemical injection line proximate the lower end of the tubing hanger; and
a compression fitting residing around the communications line proximate the lower end of the tubing hanger;
wherein the compression fittings secure the chemical injection line and the communications line within the tubing hanger assembly to prevent relative movement.

11. The tubing hanger assembly of claim 7, further comprising:
a sub seal defining a tubular body, wherein the sub seal has an outer diameter configured to closely reside within the central bore of the tubing hanger and the central bore of the tubing head adapter; and
one or more o-rings around the sub seal;
wherein the sub seal is configured to provide fluid communication between the central bore of the tubing hanger and the central bore of the tubing head adapter.

12. The tubing hanger assembly of claim 1, further comprising a continuous line extending through the first auxiliary hole of the tubing head adapter and an aligned first through-opening in the tubing hanger, wherein the line extends down into and through the central bore of the tubing head.

13. The tubing hanger assembly of claim 12, wherein said continuous line comprises steel tubing.

14. The tubing hanger assembly of claim 1, wherein the body of said tubing head adapter has a height and said bottom rotating flange has an upper surface and a thickness, with the height of the tubing head adapter greater than the thickness of the bottom rotating flange such that, when the bottom rotating flange is mounted on the tubing head adapter with the beveled surface landed on the conical surface of the tubing head adapter, the top end of the first auxiliary hole is spaced upwardly away from the upper surface of the bottom rotating flange.

15. A method of hanging a string of production tubing within a wellbore, comprising:
 providing a tubing hanger system comprising a tubing head, a tubing hanger, a tubing head adapter, and a bottom rotating flange, wherein:

- the tubing head has an upper end and a lower end, with the upper end comprising a flange having a plurality of radially disposed ports;
- the tubing hanger comprises:
 - a generally tubular body having an upper end, a lower end, and an outer diameter, wherein a central bore extends from the upper end to the lower end of the tubular body, and
 - a first through-opening extending through the tubular body from the upper end to the lower end and dimensioned to receive a first line;
- the tubing head adapter comprises:
 - a body having an upper end, a lower end, and an outer diameter, wherein a central bore extends from the upper end to the lower end of the body and a conical surface is located around the outer diameter of the body, and
 - a first auxiliary hole extending through the body of the tubing head adapter, the first auxiliary hole having an open top end in the body of the tubing head adapter and an open bottom end located in the lower end of the tubing head adapter, the first auxiliary hole dimensioned to receive a line therethrough;
- and
- the bottom rotating flange comprises cylindrical body having a central bore dimensioned to receive the body of the tubing head adapter and a plurality of ports radially placed around the central bore, wherein the central bore includes a beveled inner surface;
- placing the tubing head over a wellbore;
- running a string of production tubing into the wellbore;
- clamping a first line to the production tubing as the string of production tubing is run into the wellbore;
- threadably securing the tubing hanger to an upper end of the production tubing;
- running the first line up through the first through-opening in the tubing hanger;

landing a beveled surface residing along an outer diameter of the tubing hanger on a conical surface along an inner diameter of the tubing head, whereby the tubing hanger resides within the tubing head over the wellbore and gravitationally supports the string of production tubing threadably secured to the tubing hanger;

running the first line up through the first auxiliary hole in the tubing head adapter;

landing the tubing head adapter onto the tubing head such that the first auxiliary hole of the tubing head adapter is rotationally aligned with the first through-opening of the tubing hanger, with the first line extending through said first through-opening and said first auxiliary hole;

placing the bottom rotating flange onto the body of the tubing head adapter such that the beveled inner surface of the central bore of the bottom rotating flange lands on the conical surface of the tubing head adapter;

after the tubing head adapter is landed onto the tubing head such that the first auxiliary hole of the tubing head adapter is rotationally aligned with the first through-opening of the tubing hanger, rotating the bottom rotating flange about the body of the tubing head adapter such that ports in the bottom rotating flange are aligned with two or more ports in the upper flange of the tubing head to form a plurality of aligned ports; and

securing the tubing head adapter to the tubing head by connectors inserted through the aligned ports of the bottom rotating flange and the upper flange of the tubing head.

16. The method of claim 15, wherein:

the tubing hanger further comprises a second through-opening also extending through the tubular body of the tubing hanger from the upper end to the lower end, and dimensioned to receive a second line;

the tubing head adapter further comprises a second auxiliary hole also extending through the body of the tubing head adapter, the second auxiliary hole having an open top end in the body of the tubing head adapter and an open bottom end located in the lower end of the tubing head adapter and dimensioned to receive the second line;

and the method further comprises:

clamping a second line to the production tubing as the string of production tubing is run into the wellbore;

running the second line up through the second auxiliary hole in the tubing head adapter; and

running the second line up through the second through-opening in the tubing hanger.

17. The method of claim 16, wherein:

the tubing head further comprises two or more lock pins disposed equi-radially about the tubing head flange; and

the method further comprises rotating the lock pins into engagement with the tubing hanger to lock the tubing hanger and supported tubing string in place within the tubing head.

18. The method of claim 17, wherein:

the upper end of the tubing head comprises a face having a radial groove;

the lower end of the tubing head adapter comprises a face having radial groove; and

the method further comprises placing a ring bonnet between the upper end of the tubing head and the lower end of the tubing head adapter such that, after the tubing head adapter has been lowered into place onto the tubing head, the ring bonnet resides within the radial groove of the tubing head and the radial groove of the tubing head adapter.

19. The method of claim 16, wherein:

the upper end of the tubing head adapter comprises a threaded end; and

the tubing hanger assembly further comprises a spin-on flange defining a generally cylindrical body having a threaded bore and a plurality of openings equi-radially disposed about the threaded bore, wherein the threaded bore of the spin-on flange is dimensioned to threadedly connect to the upper threaded end of the tubing head adapter; and

further comprising the steps of securing a valve to said spin-on flange using two or more threaded fasteners inserted into the openings in said spin-on flange, and rotatably securing said spin-on flange to the threaded upper end of the tubing head adapter.

20. The method of claim 19, wherein:

the first line is a chemical injection line comprising steel tubing that extends, unspliced, through the tubing hanger system and into, the wellbore; and

the second line is a communications line comprising an electrical line, a power cable, a fiber optic cable, or combinations thereof.

21. The method of claim 16, further comprising:

securing the first line in position using a compression fitting located proximate the upper end of the tubing head adapter and a compression fitting located proximate the lower end of the tubing hanger;

securing the second line in position using a compression fitting located proximate the upper end of the tubing head adapter and a compression fitting located proximate the lower end of the tubing hanger;

wherein the compression fittings secure the first and second lines within the tubing hanger assembly to prevent relative movement.

22. The method of claim 16, wherein said second line comprises a communications line.

23. The method of claim 15, further comprising:

placing a lower end of a sub seal within the bore of the tubing hanger, the sub seal defining a tubular body, wherein the sub seal has an outer diameter configured to closely reside within the central bore of the tubing hanger and the central body of the tubing head adapter; and

said step of landing the tubing head adapter onto the tubing head comprises lowering the tubing head adapter onto the tubing head such that the sub seal is received within the central bore of the tubing head adapter, wherein the sub seal sealingly provides fluid communication between the central bore of the tubing hanger and the central bore of the tubing head adapter.

24. The method of claim 15, wherein said first line comprises steel tubing.

25. An apparatus, comprising:

a tubing head adapter defining through-openings, wherein the tubing head adapter is configured to be received onto a tubing head in any rotational orientation so as to align the through-openings with through-openings in a tubing hanger received in the tubing head; and

a connector received at least partially around the tubing head adapter, wherein the connector is configured to be connected to the tubing head so as to secure the tubing head adapter to the tubing head;

wherein the through-openings in the tubing head adapter comprise a first through-opening for receiving an injection line through the tubing head adapter, a second through-opening for receiving a communications line through the tubing head adapter, and a third

through-opening for fluid communication with a production tubing through the tubing head adapter, the third through-opening being positioned between the first and second through-openings;

wherein the tubing head adapter being receivable onto the tubing head in any rotational orientation is configured to permit the first, second, and third through-openings to be aligned with the respective injection line, communications line, and production tubing extending through the through-openings in the tubing hanger; and

wherein the first and second through-openings extend at a non-zero angle to the third through-opening.

26. The apparatus of claim 25, wherein the connector is configured to be connected to the tubing head adapter in a plurality of different rotational orientations with respect to the tubing head, the tubing head adapter, or both.

27. The apparatus of claim 25, wherein the connector comprises a connector flange configured to be connected to a top flange of the tubing head.

28. The apparatus of claim 27, wherein the connector flange defines a plurality of openings, and wherein the connector flange is configured to be rotated with respect to the top flange so as to align at least two of the plurality of openings thereof with at least two openings of the top flange.

29. The apparatus of claim 25, further comprising a ring bonnet configured to be positioned between a bottom surface of the tubing head adapter and a top flange of the tubing head.

30. The apparatus of claim 25, wherein at least one of the through-openings in the tubing head adapter defines a bend from an axial direction toward a radial direction.

31. The apparatus of claim 25, wherein the tubing head adapter is configured to engage a top surface of a top flange of the tubing head, so as to seal a central bore of the tubing head, and wherein the tubing head adapter is configured to not be received into the central bore of the tubing head.

32. The apparatus of claim 25, further comprising the injection line and the communications line, the injection line being configured to carry a chemical therethrough, and the communications line comprising an electric or fiber-optic cable configured to transmit communication signals therethrough.

33. The apparatus of claim 32, wherein the injection line and the communications line are both configured to be banded to the production tubing.

34. The apparatus of claim 25, wherein the third through-opening is positioned laterally between the first and second through-openings, such that the first and second through-openings are separated apart 180 degrees as proceeding circumferentially about the third through-opening.

35. The apparatus of claim 25, further comprising a spin-on flange configured to couple to a valve in a plurality of rotational orientations, wherein the tubing head adapter further comprises a main body in which the first, second, and third through-openings are defined, and a cylindrical neck extending upwards from the main body, wherein an upper end of the cylindrical neck is threaded and connected to the spin-on flange.

36. The apparatus of claim 25, wherein the tubing head adapter defines a lower radial surface configured to engage the tubing head, a lower beveled surface, an upper beveled surface, a cylindrical surface that extends between the lower beveled surface and the upper beveled surface, and an upper radial surface that extends radially inward from the upper beveled surface, wherein the first through-opening extends from the upper beveled surface to the lower radial surface, wherein the second through-opening extends from the upper beveled surface to the lower radial surface, and wherein the third through-opening extends from the upper radial surface to the lower radial surface.

37. The apparatus of claim 36, wherein at least a portion of the upper beveled surface comprises a first upper beveled surface and a second upper beveled surface that intersects the cylindrical surface, the first and second upper beveled surfaces intersecting at a first obtuse angle, wherein the second through-opening is defined in the first upper beveled surface and not through the second upper beveled surface.

38. The apparatus of claim 37, wherein the tubing head adapter further defines a shoulder extending from the upper beveled surface at a second obtuse angle and intersecting the upper radial surface.

39. The apparatus of claim 36, wherein the tubing head adapter further defines a test port extending from the upper beveled surface.

40. The apparatus of claim 36, wherein the second through-opening comprises a first section and a second section, the first and second sections intersecting at an obtuse angle such that the communications line is bent within the tubing head adapter, wherein the first through-opening extends in a straight line between the lower radial surface and the upper beveled surface such that the injection line is not bent in the tubing head adapter, and wherein the third through-opening extends vertically through the tubing head adapter along a centerline thereof from the upper radial surface to the lower radial surface.

41. The apparatus of claim 25, wherein the tubing head adapter comprises a cylindrical surface and a shoulder extending outwards from the cylindrical surface, and wherein the connector bears upon the shoulder so as to secure the tubing head adapter to a top flange of the tubing head.

42. An apparatus for suspending a production tubing within a wellbore, comprising:
a tubing head having a central bore, the tubing head comprising a top flange;
a tubing hanger received into the central bore, the tubing hanger defining:
a bore therethrough that is configured to connect to the production tubing; and
one or more through-openings therein configured to receive tubing therethrough;
a tubing head adapter having a first through-opening for receiving an injection line through the tubing head adapter, a second-through opening for receiving a communications line through the tubing head adapter, and a third through-opening for fluid communication through the tubing head adapter with a production tubing, wherein the tubing head adapter is configured to be disposed at any rotational orientation with respect to the tubing head, so as to align the first, second, and third through-openings of the tubing head adapter with the one or more through-openings of the tubing hanger, wherein the tubing head adapter being receivable onto the tubing head in any rotational orientation is configured to permit the first, second, and

third through-openings to be aligned with the respective injection line, communications line, and production tubing extending through the one or more through-openings in the tubing hanger; and

a connector received around the tubing head adapter and configured to be fastened to the top flange, wherein fastening the connector to the top flange presses the tubing head adapter toward the top flange, so as to secure the tubing head adapter to the tubing head;

wherein the second through-opening comprises a first section and a second section, the first and second sections intersecting at an obtuse angle such that the communications line is bent within the tubing head adapter, wherein the first through-opening extends in a straight line through the tubing head adapter and at a non-zero angle to the third through-opening such that the injection line is not bent in the tubing head adapter, and wherein the third through-opening extends vertically through the tubing head adapter along a centerline thereof.

43. The apparatus of claim 42, further comprising a ring bonnet between a bottom surface of the tubing head adapter and a top surface of the tubing head.

44. The apparatus of claim 42, wherein the connector is connectable to the top flange in a plurality of different rotational positions.

45. The apparatus of claim 44, wherein the connector comprises a connector flange defining a plurality of openings, and wherein the top flange comprises a plurality of openings, and wherein, when the connector is in any of the plurality of different rotational positions, at least two of the plurality of openings of the connector flange are aligned with at least two of the plurality of openings in the top flange.

46. The apparatus of claim 42, wherein the tubing head is not received into the central bore of the tubing head adapter, but is configured to seal to a top surface of the top flange.

47. The apparatus of claim 42, wherein the injection line and the communications line are both banded to the production tubing.

48. The apparatus of claim 42, wherein the tubing head adapter is generally bell-shaped and comprises cylindrical surface and a shoulder extending outwards from the cylindrical

surface, and wherein the connector comprises a connector flange that bears upon the shoulder so as to secure the tubing head adapter to the top flange of the tubing head.

49. An apparatus, comprising:

a tubing head adapter having one or more through-openings therein, wherein the tubing head adapter is configured to be receivable onto a tubing head in any rotational orientation so as to align the one or more through openings with one or more through-openings in a tubing hanger received in the tubing head; and

means for connecting the tubing head adapter in any rotational orientation to the tubing head;

wherein the one or more through-openings in the tubing head adapter comprise a first opening for receiving an injection line through the tubing head adapter, a second opening for receiving a communications line through the tubing head adapter, and a third opening for fluid communication with a production tubing through the tubing head adapter, the third opening being positioned between the first and second openings, wherein the tubing head adapter further defines a test port extending radially through the tubing head adapter; and

wherein the tubing head adapter being receivable onto the tubing head in any rotational orientation is configured to permit the first, second, and third openings to be aligned with the respective injection line, communications line, and production tubing extending in the one or more through-openings in the tubing hanger.

50. The apparatus of claim 49, wherein the means for connecting comprise a flange that is connectable to a top flange of the tubing head in a plurality of different rotational orientations, and wherein the flange is configured to press a bottom surface of the tubing head adapter toward the top flange, so as to form a seal therebetween.

51. The apparatus of claim 50, wherein a ring bonnet is positioned between the bottom surface and the top flange, such that pressing the bottom surface toward the top flange forms the seal between the tubing head and the tubing head adapter.

52. The apparatus of claim 49, wherein the tubing head adapter is configured to not be received into a central bore of the tubing head.

53. A tubing hanger assembly, comprising:

a tubing head adapter configured to be secured to a tubing head having a central bore in which a tubing hanger is received, such that the tubing head adapter seals with the tubing head around the central bore, the tubing head adapter defining a lower radial surface configured to engage the tubing head, a lower beveled surface, an upper beveled surface, a cylindrical surface that extends between the lower beveled surface and the upper beveled surface, and an upper radial surface that extends radially inward from the upper beveled surface, the tubing head adapter further defining a first through-opening extending from the upper beveled surface to the lower radial surface, a second through-opening extending from the upper beveled surface to the lower radial surface, and a third through-opening extending from the upper radial surface to the lower radial surface, wherein the first and second through-openings extend at a non-zero angle relative to the third through-opening; and

a bottom flange engaging the lower beveled surface and configured to secure the tubing head adapter to the tubing head without altering alignment of the first, second, and third through-openings of the tubing head adapter with the tubing hanger, wherein the bottom flange is positionable on the tubing head adapter such that the bottom flange can be rotated independently of the tubing head adapter.

54. The tubing hanger assembly of claim 53, wherein the bottom flange includes a central bore dimensioned to rotatably receive a portion of the tubing head adapter.

55. The tubing hanger assembly of claim 54, wherein the central bore of the bottom flange includes an inner surface having a shape complimentary to an outer surface of the tubing head adapter.

56. The tubing hanger assembly of claim 55, wherein the inner surface of the central bore of the bottom flange is configured to bear against the outer surface of the tubing head adapter after the bottom flange is positioned on the tubing head adapter.

57. The tubing hanger assembly of claim 56, wherein the inner surface of the central bore is a beveled surface shaped complementary to the lower beveled surface of the tubing head adapter.

58. The tubing hanger assembly of claim 53, further comprising a ring configured to be received between a lower end of the tubing head adapter and the upper end of the tubing head.
59. The tubing hanger assembly of claim 58, wherein said ring is configured to be received within a groove in the lower end of the tubing head adapter and within a groove in the upper end of the tubing head.
60. The tubing hanger assembly of claim 53, further comprising a plurality of connectors configured to be received within openings located in the bottom flange and an upper flange of the tubing head for securing the bottom flange to the tubing head, thereby securing the tubing head adapter with respect to the tubing head.
61. The tubing hanger assembly of claim 53, wherein the tubing head adapter comprises a body and a neck extending upwardly away from the body, wherein the third through-opening of the tubing head adapter extends through said body and the neck and an upper end of said neck is configured to be operatively connected to a valve.
62. The tubing hanger assembly of claim 53, wherein the first through-opening is configured to receive a communications line therethrough, wherein the second through-opening is configured to receive a chemical injection line therethrough, and wherein the third through-opening is configured to communicate with an interior of a production tubing coupled to the tubing hanger, the third through-opening extending through a center of the tubing head adapter.
63. The tubing hanger assembly of claim 53, wherein the tubing head adapter further defines a test port extending from the upper beveled surface to the third through-opening.
64. A method of assembling a tubing hanger assembly, comprising:
 securing a tubing hanger within a tubing head, said tubing hanger comprising a first through-opening, a second through-opening, and a third through-opening, the first, second, and third through-openings extending through the tubing hanger;
 positioning a tubing head adapter over the tubing hanger, said tubing head adapter comprising a first through-opening, a second through-opening, and a third through-opening,

the first, second, and third through-openings extending through a portion of the tubing head adapter;

positioning a bottom flange over the tubing head adapter;

rotationally aligning the first, second, and third through-openings in the tubing head adapter with the first, second, and third through-openings in the tubing hanger; and

securing the tubing head adapter with respect to the tubing hanger and tubing head by securing the bottom flange to the tubing head, without altering the alignment of the first, second, and third through-openings of the tubing head adapter and first, second, and third through-openings in the tubing hanger,

wherein the tubing head has a central bore in which the tubing hanger is received, wherein the tubing head adapter seals with the tubing head around the central bore, the tubing head adapter defining a lower radial surface configured to engage the tubing head, a lower beveled surface, an upper beveled surface, a cylindrical surface that extends between the lower beveled surface and the upper beveled surface, and an upper radial surface that extends radially inward from the upper beveled surface, wherein the first through-opening in the tubing head adapter extends from the upper beveled surface to the lower radial surface, the second through-opening in the tubing head adapter extends from the upper beveled surface to the lower radial surface, and the third through-opening in the tubing head adapter extends from the upper radial surface to the lower radial surface, and wherein an inner surface of the bottom flange engages the lower beveled surface to secure the tubing head adapter to the tubing head.

65. The method of claim 64, wherein the first, second, and third through-openings in the tubing head adapter are rotationally aligned with the first, second, and third through-openings in the tubing hanger prior to positioning the bottom flange over the tubing head adapter.

66. The method of claim 64, further comprising the step of routing a line through at least one of the first, second, or third through-openings in the tubing head adapter.

67. The method of claim 66, further comprising the step of routing said line through at least one of the first, second, or third through-openings in the tubing hanger.

68. The method of claim 66, further comprising the step of securing the line to the tubing head adapter with a fitting.

69. The method of claim 64, wherein the step of securing the bottom flange to the tubing head comprises rotating the bottom flange until openings located in the bottom flange are aligned with openings in an upper flange of the tubing head, and thereafter securing the bottom flange to the tubing head using connectors inserted through the aligned openings in the bottom flange and tubing head.

70. The method of claim 64, further comprising the step of positioning a ring between a lower end of the tubing head adapter and an upper end of the tubing head.

71. The method of claim 64, further comprising the steps of securing the tubing hanger to a tubing string, and operatively connecting a valve to the tubing head adapter such that fluid communication between the valve and the tubing string is provided by the tubing head adapter and the tubing hanger.

72. The method of claim 64, further comprising the steps of:
running a tubing string into a wellbore, with a first line and a second line connected to said tubing string; and
thereafter, routing the first line through the first through-opening in the tubing hanger, routing the first line through the first through-opening in the tubing head adapter, routing the second line through the second through-opening in the tubing hanger and the second through-opening in the tubing head adapter, and securing the tubing hanger to the tubing string.

73. An assembly for use with a tubing head, comprising:
a tubing head adapter configured to be secured with respect to said tubing head, the tubing head having a central bore in which a tubing hanger is received, such that the tubing head adapter seals with the tubing head around the central bore, the tubing head adapter defining a lower radial surface configured to engage the tubing head, a lower beveled surface, an upper beveled surface, a cylindrical surface that extends between the lower beveled surface and the upper beveled surface, and an upper radial surface that extends radially inward from the upper beveled surface, the tubing head adapter further defining a first through-opening extending from the upper beveled surface to the lower radial surface, a second through-opening extending from the upper beveled surface to the lower radial surface,

and a third through-opening extending from the upper radial surface to the lower radial surface; and

a bottom flange engaging the lower beveled surface and configured to secure the tubing head adapter to the tubing head, the bottom flange having a central bore dimensioned to rotatably receive a portion of the tubing head adapter, wherein the bottom flange is positionable on the tubing head adapter such that the bottom flange can be rotated independently of the tubing head adapter so as to maintain alignment of first, second and third through-openings of the tubing hanger with the first, second, and third openings of the tubing head adapter, respectively.

74. The assembly of claim 73, wherein the central bore of the bottom flange includes an inner surface having a shape complimentary to an outer surface of the tubing head adapter.

75. The assembly of claim 74, wherein the inner surface of the central bore is configured to bear against the outer surface of the tubing head adapter after the bottom flange is positioned on the tubing head adapter.

76. The assembly of claim 74, wherein the inner surface of the central bore is a beveled surface and the outer surface of the tubing head adapter is a conical surface.

77. The assembly of claim 73, wherein the tubing head adapter includes a central bore that is configured to be aligned with a central bore of the tubing head.

78. A tubing hanger assembly, comprising:

a tubing head adapter configured to be secured to a tubing head having a central bore in which a tubing hanger is received, such that the tubing head adapter seals with the tubing head around the central bore, the tubing head adapter defining a lower radial surface configured to engage the tubing head, a lower beveled surface, an upper beveled surface, a cylindrical surface that extends between the lower beveled surface and the upper beveled surface, and an upper radial surface that extends radially inward from the upper beveled surface, the tubing head adapter further defining a first through-opening extending from the upper beveled surface to the lower radial surface, a second through-opening extending from the upper beveled surface to the lower radial surface, and a third through-opening extending from the upper radial surface to the lower radial surface; and


a bottom flange engaging the lower beveled surface and configured to secure the tubing head adapter to the tubing head without altering alignment of the first, second, and third through-openings of the tubing head adapter with the tubing hanger, wherein the bottom flange is positionable on the tubing head adapter such that the bottom flange can be rotated independently of the tubing head adapter,

wherein the first through-opening is configured to receive a communications line therethrough, wherein the second through-opening is configured to receive a chemical injection line therethrough, and wherein the third through-opening is configured to communicate with an interior of a production tubing coupled to the tubing hanger, the third through-opening extending through a center of the tubing head adapter, and

wherein the first through-opening comprises a first section and a second section, the first and second sections intersecting at an obtuse angle such that the communications line is bent within the tubing head adapter, wherein the second through-opening extends in a straight line between the bottom radial surface and the upper beveled surface such that the chemical injection line is not bent in the tubing head adapter, and wherein the third through-opening extends vertically through the tubing head adapter along a centerline thereof from the upper radial surface to the lower radial surface.

79. The tubing hanger assembly of claim 78, wherein at least a portion of the upper beveled surface comprises a first upper beveled surface and a second upper beveled surface that intersects the cylindrical surface, the first and second upper beveled surfaces intersecting at an obtuse angle, wherein the second through-opening is defined in the first upper beveled surface and not through the second upper beveled surface.

80. The tubing hanger assembly of claim 79, wherein the tubing head adapter further defines a shoulder extending from the first beveled surface at an acute angle and intersecting the upper radial surface.



3/10




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C






FIG. 4D

6/10



7/10




FIG. 5C




FIG. 6




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A




FIG. 9B




FIG. 9C

