



(86) Date de dépôt PCT/PCT Filing Date: 2011/03/07
(87) Date publication PCT/PCT Publication Date: 2012/09/13
(85) Entrée phase nationale/National Entry: 2013/08/20
(86) N° demande PCT/PCT Application No.: US 2011/027353
(87) N° publication PCT/PCT Publication No.: 2012/121697

(51) Cl.Int./Int.Cl. *G01V 3/28* (2006.01)
(71) Demandeur/Applicant:
HALLIBURTON ENERGY SERVICES, INC., US
(72) Inventeurs/Inventors:
WU, HSU-HSIANG, US;
BITTAR, MICHAEL, US
(74) Agent: NORTON ROSE FULBRIGHT CANADA
LLP/S.E.N.C.R.L., S.R.L.

(54) Titre : PROCEDES DE TRAITEMENT DE SIGNAUX PERMETTANT D'ORIENTER UNE CIBLE SOUTERRAINE
(54) Title: SIGNAL PROCESSING METHODS FOR STEERING TO AN UNDERGROUND TARGET




Fig. 12

(57) Abrégé/Abstract:

A method of processing data from an electromagnetic resistivity logging tool which includes a transmitter coil and a receiver coil is disclosed. The electromagnetic resistivity logging tool is placed at a desired location. The transmitter coil and the receiver coil are

(57) **Abrégé(suite)/Abstract(continued):**

positioned at a first azimuthal angle. A signal is transmitted from the receiver coil. The receiver coil then receives a signal. The signal at the receiver coil, a tilt angle of the transmitter coil, a tilt angle of the receiver coil and the first azimuthal angle are then used to calculate a first complex voltage representing at least one component of the received signal.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 September 2012 (13.09.2012)

WIPO | PCT

(10) International Publication Number
WO 2012/121697 A1

(51) International Patent Classification:
G01V 3/28 (2006.01)

(21) International Application Number:

PCT/US2011/027353

(22) International Filing Date:

7 March 2011 (07.03.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant (for all designated States except US): **HAL-LIBURTON ENERGY SERVICES, INC.** [US/US]; 10200 Bellaire Boulevard, Houston, TX 77072 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WU, Hsu-Hsiang** [—/US]; 6007 Parkwood Place, Sugar Land, TX 77479 (US). **BITTAR, Michael** [US/US]; 8711 Wheatland Drive, Houston, TX 77064 (US).

(74) Agent: **ANJOM, Masood**; Baker Botts LLP, 910 Louisiana Street, Houston, TX 77002 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,

CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))


Published:

— with international search report (Art. 21(3))

— with amended claims and statement (Art. 19(1))

(54) Title: SIGNAL PROCESSING METHODS FOR STEERING TO AN UNDERGROUND TARGET

Fig. 12



(57) Abstract: A method of processing data from an electromagnetic resistivity logging tool which includes a transmitter coil and a receiver coil is disclosed. The electromagnetic resistivity logging tool is placed at a desired location. The transmitter coil and the receiver coil are positioned at a first azimuthal angle. A signal is transmitted from the receiver coil. The receiver coil then receives a signal. The signal at the receiver coil, a tilt angle of the transmitter coil, a tilt angle of the receiver coil and the first azimuthal angle are then used to calculate a first complex voltage representing at least one component of the received signal.

SIGNAL PROCESSING METHODS FOR STEERING TO AN UNDERGROUND TARGET

Background

5 The basic techniques for electromagnetic logging for earth formations are well known. For instance, induction logging to determine resistivity (or its inverse, conductivity) of earth formations adjacent a borehole has long been a standard and important technique in the search for and recovery of hydrocarbons. Generally, a transmitter transmits an electromagnetic signal that passes through formation materials around the borehole and induces a signal in one or more
10 receivers. The properties of the signal received, such as its amplitude and/or phase, are influenced by the formation resistivity, enabling resistivity measurements to be made. The measured signal characteristics and/or formation properties calculated therefrom may be recorded as a function of the tool's depth or position in the borehole, yielding a formation log that can be used to analyze the formation.

15 The resistivity of a given formation may be isotropic (equal in all directions) or anisotropic (unequal in different directions). In electrically anisotropic formations, the anisotropy is generally attributable to extremely fine layering during the sedimentary build-up of the formation. As a result, in a formation Cartesian coordinate system oriented such that the x-y plane is parallel to the formation layers and the z axis is perpendicular to the formation layers,
20 resistivities R_x and R_y in the x and y directions, respectively, tend to be similar, but resistivity R_z in the z direction tends to be different. The resistivity in a direction parallel to the formation plane (i.e., the x-y plane) is known as the horizontal resistivity, R_h , and the resistivity in the direction perpendicular to the plane of the formation (i.e., the z direction) is known as the vertical resistivity, R_v . The index of anisotropy, η , is defined as $\eta = [R_v/R_h]^{1/2}$.

25 As a further complication to measuring formation resistivity, boreholes are generally perpendicular to formation beds. The angle between the axis of the well bore and the orientation of the formation beds (as represented by the normal vector) has two components. These components are the dip angle and the strike angle. The dip angle is the angle between the borehole axis and the normal vector for the formation bed. The strike angle is the direction in
30 which the borehole's axis "leans away from" the normal vector.

Electromagnetic resistivity logging measurements are a complex function of formation resistivity, formation anisotropy, and the formation dip and strike angles, which may all be

unknown. Logging tools that fail to account for one or more of these parameters may produce inaccurate measurements. Moreover, tools that are able to provide dip and strike measurements along with azimuthal orientation information can be used to adjust the drilling direction to increase the borehole's exposure to a hydrocarbon bearing formation ("geosteering").
5 Specifically, it is desirable to be able to steer a tool to an underground target using the information available from the logging tool. Moreover, it is desirable to be able to match raw measurements to the modeled response for the system to evaluate the system performance.

Brief Description of the Drawings

10 Figure 1 shows an illustrative logging while drilling environment including dipping formation beds;

Figure 2 shows an illustrative wireline logging environment including dipping formation beds;

15 Figure 3 shows a relationship between the orientation of a borehole and a dipping formation bed;

Figure 4 shows a hypothetical antenna arrangement for a tool having an orthogonal triaxial transmitter and two orthogonal triaxial receivers;

Figure 5 shows angles for defining the orientation of a tilted antenna;

20 Figure 6 shows a block diagram of an exemplary electronics module for an electromagnetic resistivity tool;

Figure 7 shows an illustrative electromagnetic resistivity logging tool having tilted transmitter and receiver antennas;

Figures 8a and 8b show an illustrative configuration of an antenna system equipped with a tilted transmitter and a tilted receiver.

25 Figures 9a, 9b, and 9c show an illustrative configuration of a rotating tool's relationship to surrounding environments.

Figure 10 shows an illustrative Cartesian coordinate system that is rotated along z-directional axis with a clockwise angle ϕ_i in the x-y plane;

Figure 11 shows an illustrative configuration of tool bin positions and corresponding azimuthal angles;

Figure 12 shows a flowchart of a processing scheme in accordance with an exemplary embodiment of the present invention;

5 Figure 13 shows an illustrative configuration of an antenna system with two transmitters and one receiver;

Figure 14 shows an illustrative configuration of a formation model of two layered isotropic media.

10 Figure 15 shows illustrative signal responses with azimuthal angle of 30° to the formation boundary.

Figure 16 shows illustrative signal responses with x-axis of tool coordinate system pointing to the formation boundary.

Figure 17 shows illustrative signal responses with x-axis of tool coordinate system parallel to the formation boundary.

15 Figure 18 shows illustrative raw measurements of ADR-TT in a water tank with a surrounding casing target.

Figure 19 shows illustrative processed signals of ADR-TT in a water tank to steer the surrounding casing.

Detailed Description

20 The terms “couple” or “couples,” as used herein are intended to mean either an indirect or direct connection. Thus, if a first device couples to a second device, that connection may be through a direct connection, or through an indirect electrical connection via other devices and connections. The term “upstream” as used herein means along a flow path towards the source of the flow, and the term “downstream” as used herein means along a flow path away from the source of the flow. The term “uphole” as used herein means along the drillstring or the hole from the distal end towards the surface, and “downhole” as used herein means along the drillstring or the hole from the surface towards the distal end.

It will be understood that the term “oil well drilling equipment” or “oil well drilling system” is not intended to limit the use of the equipment and processes described with those terms to drilling an oil well. The terms also encompass drilling natural gas wells or hydrocarbon wells in general. Further, such wells can be used for production, monitoring, or injection in relation to the recovery of hydrocarbons or other materials from the subsurface.

The present application discloses processing schemes for a rotating electromagnetic tool equipped with tilt antenna systems having arbitrary tilted angles for transmitters and receivers. Accordingly, the methods disclosed herein provide a novel approach to steering an underground target surrounding the electromagnetic tool. A relative azimuthal angle sensitivity of the tool is introduced and various mathematical relations of tool signal responses are discussed upon a defined relative azimuthal angle between the tool and the surrounding target. By finding the relative azimuthal angle, one can steer the tool to its surrounding target as well as match raw measurements to the forwarding model responses.

Turning now to Figure 1, an illustrative logging while drilling (“LWD”) environment is shown. A drilling platform 2 supports a derrick 4 having a traveling block 6 for raising and lowering a drill string 8. A kelly 10 supports the drill string 8 as it is lowered through a rotary table 12. A drill bit 14 is driven by a downhole motor and/or rotation of the drill string 8. As bit 14 rotates, it creates a borehole 16 that passes through various formations 18. A pump 20 may circulate drilling fluid through a feed pipe 22 to kelly 10, downhole through the interior of drill string 8, through orifices in drill bit 14, back to the surface via the annulus around drill string 8, and into a retention pit 24. The drilling fluid transports cuttings from the borehole into the pit 24 and aids in maintaining the borehole integrity.

An electromagnetic resistivity logging tool 26 may be integrated into the bottom-hole assembly near the bit 14. As the bit extends the borehole through the formations, logging tool 26 collects measurements relating to various formation properties as well as the tool orientation and position and various other drilling conditions. The orientation measurements may be performed using an azimuthal orientation indicator, which may include magnetometers, inclinometers, and/or accelerometers, though other sensor types such as gyroscopes may be used in some embodiments, the tool includes a 3-axis fluxgate magnetometer and a 3-axis accelerometer. The logging tool 26 may take the form of a drill collar, i.e., a thick-walled tubular that provides weight and rigidity to aid the drilling process. A telemetry sub 28 may be included to transfer tool measurements to a surface receiver 30 and to receive commands from the surface receiver 30.

In one embodiment, rotational position indicator array may contain both a 3-axis fluxgate magnetometer and a 3-axis accelerometer. As would be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, the combination of those two sensor systems enables the measurement of the tool face, inclination, and azimuth orientation angles of the borehole.

5 The tool face and hole inclination angles are calculated from the accelerometer sensor output. The magnetometer sensor outputs are used to calculate the hole azimuth. With the tool face, the hole inclination, and the hole azimuth information, a tool in accordance with the present invention can be used to steer the bit to the desirable bed. Specifically, the response difference or the response ratio can be used effectively to enter a desired payzone or to stay within the payzone of interest.

10 At various times during the drilling process, the drill string 8 may be removed from the borehole as shown in Figure 2. Once the drill string has been removed, logging operations can be conducted using a wireline logging tool 34, i.e., a sensing instrument sonde suspended by a cable having conductors for transporting power to the tool and telemetry from the tool to the surface. A resistivity imaging portion of the logging tool 34 may have centralizing arms 36 that center the tool
15 within the borehole as the tool is pulled uphole. A logging facility 44 may collect measurements from the logging tool 34, and may include computing facilities for processing and storing the measurements gathered by the logging tool.

Returning now to Figure 1, it shows that the formations 18 are not perpendicular to the borehole, which may occur naturally or due to directional drilling operations. The borehole may
20 have a Cartesian coordinate system 50 defined in accordance with the borehole's long axis (the z-axis) and the north side (or alternatively, the high side) of the hole (the x-axis). The formations 18, when characterized as a plane, may have a Cartesian coordinate system 51 defined in accordance with the normal to the plane (the z''-axis) and the direction of steepest descent (the x''-axis). As shown in Figure 3, the two Cartesian coordinate systems are related by two
25 rotations. Beginning with the borehole's Cartesian coordinate system (x,y,z), a first rotation of angle γ is made about the z-axis. The resulting Cartesian coordinate system is denoted (x',y',z'). Angle γ is the relative strike angle, which indicates the direction of the formation dip relative to the borehole's Cartesian coordinate system. A second rotation of angle α is then made about the y' axis. This aligns the borehole Cartesian coordinate system with the formation Cartesian
30 coordinate system. Angle α is the relative dip angle, which is the slope angle of the beds relative to the long axis of the borehole.

The vertical resistivity is generally found to be the resistivity as measured perpendicular to the plane of the formation, and the horizontal resistivity is the resistivity as measured within the plane of the formation. Determination of each of these parameters (dip angle, strike angle, vertical resistivity, and horizontal resistivity) is desirable.

5 Figure 4 shows a hypothetical antenna configuration for a multi-component electromagnetic resistivity logging tool which may be embodied as a wireline tool as well as a logging while drilling tool. A triad of transmitter coils T_X , T_Y , and T_Z , each oriented along a respective axis, may be provided. At least one triad of similarly oriented receiver coils R_{1X} , R_{1Y} , and R_{1Z} may also be provided. For received signal measurements relative to the amplitude and
10 phase of the transmitted signal (sometimes called “absolute” measurements) only one receiver triad would be used. A second triad of similarly oriented receiver coils pairs R_{2X} , R_{2Y} , and R_{2Z} may also be provided when differential measurements are desired (e.g., a signal amplitude ratio or a phase difference between receiver coils oriented along a given axis). Differential measurements may offer increased spatial resolution.

15 Moran and Gianzero, in “Effects of Formation Anisotropy on Resistivity Logging Measurements” Geophysics, Vol. 44, No. 7, p. 1266 (1979), noted that the magnetic field h in the receiver coils can be represented in terms of the magnetic moments m at the transmitters and a coupling matrix C :

$$h = Cm \quad (1)$$

20 In express form, equation (1) is:

$$\begin{bmatrix} H_x \\ H_y \\ H_z \end{bmatrix} = \begin{bmatrix} C_{xx} & C_{xy} & C_{xz} \\ C_{yx} & C_{yy} & C_{yz} \\ C_{zx} & C_{zy} & C_{zz} \end{bmatrix} \begin{bmatrix} M_x \\ M_y \\ M_z \end{bmatrix} \quad (2)$$

where M_x , M_y , and M_z are the magnetic moments (proportional to transmit signal strength) created by transmitters T_x , T_y , and T_z , respectively. H_x , H_y , H_z are the magnetic fields (proportional to received signal strength) at the receiver antennas R_x , R_y , and R_z , respectively.

25 In the antenna configuration of Fig. 4, if each transmitter is fired in turn, and signal measurements are made at each receiver in response to each firing, nine absolute or differential measurements are obtained. These nine measurements enable the determination of a complete coupling matrix C . ($C_{IJ} = a_{IJ} v_I^J$, where I is the index for receiver R_x , R_y , or R_z , J is the index

for transmitter Tx, Ty, or Tz, a_{IJ} is a constant determined by the tool design, and v_I^J is a complex value representing the signal amplitude and phase shift measured by receiver I in response to the firing of transmitter J.). Knowledge of the complete coupling matrix enables the determination of dip angle, strike angle, vertical resistivity, and horizontal resistivity. A number of techniques may be used to determine these parameters. For example, dip and strike angle may be determined from coupling matrix values as explained by Li Gao and Stanley Gianzero, U.S. Patent No. 6,727,706, "Virtual Steering of Induction Tool for Determination of Formation Dip Angle." Given these angles, vertical and horizontal resistivity can be determined in accordance with equations provided by Michael Bittar, U.S. Patent No. 7,019,528 "Electromagnetic Wave Resistivity Tool Having a Tilted Antenna for Geosteering Within a Desired Payzone." Alternatively, a simultaneous solution for these parameters may be found as described in the Bittar reference.

Figure 5 shows two angles that may be used to specify the orientation of a coil antenna. The coil antenna may be considered as residing in a plane having a normal vector. Tilt angle θ is the angle between the longitudinal axis of the tool and the normal vector. Azimuth angle β is the angle between the projection of the normal vector in the X-Y plane and the tool scribe line. Alternatively, in the downhole context, azimuthal angle β may represent the angle between projection of the normal vector in the X-Y plane and the x-axis of the borehole Cartesian coordinate system. As would be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, the methods and systems disclosed herein are not limited to any particular azimuthal angle. Specifically, the transmitter and receiver coils may have any azimuthal angle suitable for a particular application. Moreover, although the present application discloses an embodiment with a transmitter coil having the same azimuthal angle as a receiver coil, as would be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, the methods and systems disclosed herein may also be applied in instances where the transmitter coil(s) and the receiver coil(s) have differing azimuthal angles. For instance, in one exemplary embodiment, one or both of the transmitter coil(s) and the receiver coil(s) may be positioned in a window inside the tool facing outwards rather than being wrapped around the tool 902. Further, in one embodiment, the normal vector of the coil antenna may be co-planar with the X-Y plane.

It is noted that three transmitter antenna orientations and three receiver antenna orientations are employed in the antenna configuration of Fig. 4. It has been discovered that when tool rotation is exploited, it is possible to determine the full coupling matrix with only one transmitter and two receiver antenna orientations (or equivalently, one receiver and two

transmitter antenna orientations). Moreover, with certain assumptions about the configuration of the formation, one transmitter and receiver antenna orientation may be sufficient.

Before considering various tools having specific antenna configurations, the electronics common to each tool are described. Figure 6 shows a functional block diagram of the electronics for a resistivity tool. The electronics include a control module 602 that is coupled to an analog switch 604. Analog switch 604 is configured to drive any one of the transmitter coils T_1 , T_2 , T_3 , T_4 with an alternating current (AC) signal from a signal source 606. In some embodiments, the signal source provides radio frequency signals. The control module 602 preferably selects a transmitter coil, pauses long enough for transients to die out, then signals data storage/transmit module 610 to accept an amplitude and phase sample of the signals received by each of the receivers. The control module 602 preferably repeats this process sequentially for each of the transmitters. The amplitude and phase shift values are provided by amplitude and phase shift detector 608 which is coupled to each of the receiver coils R_1 and R_2 for this purpose.

Control module 602 may process the amplitude and phase shift measurements to obtain compensated measurements and/or measurement averages. The raw, compensated, or averaged measurements, may be transmitted to the surface for processing to determine dip and strike angles, vertical and horizontal resistivity, and other information such as (i) distance to nearest bed boundary, (ii) direction of nearest bed boundary, and (iii) resistivity of any nearby adjacent beds. The data storage/transmitter module 610 may be coupled to telemetry unit 28 (Figure 1) to transmit signal measurements to the surface. Telemetry unit 28 can use any of several known techniques for transmitting information to the surface, including but not limited to, (1) mud pressure pulse; (2) hard-wire connection; (3) acoustic waves; and (4) electromagnetic waves.

Figure 7 shows an electromagnetic resistivity logging tool 702 having only two receiver antenna orientations. The tool 702 is provided with one or more regions 706 of reduced diameter. A wire coil 704 is placed in the region 706 and in some embodiments is spaced away from the surface of subassembly 702 by a constant distance. To mechanically support and protect the coil 704, a non-conductive filler material (not shown) such as epoxy, rubber, or ceramic may be used in the reduced diameter regions 706. Coil 704 is a transmitter coil, and coils 710 and 712 are receiving coils. In operation, transmitter coil 704 transmits an interrogating electromagnetic signal which propagates through the borehole and surrounding formation. Receiver coils 710, 712 detect the interrogating electromagnetic signal and provide a measure of the electromagnetic signal's amplitude attenuation and phase shift. For differential

measurements, additional receiver coils parallel to coils 710, 712 may be provided at an axially spaced distance. From the absolute or differential amplitude attenuation and phase shift measurements, the coupling matrix components can be determined and used as the basis for determining formation parameters and as the basis for geosteering.

5 In one embodiment, the transmitter coil 704 may be spaced approximately 30 inches from the receiver coils 710, 712. The transmitter and receiver coils may comprise as little as one loop of wire, although more loops may provide additional signal power. The distance between the coils and the tool surface is preferably in the range from 1/16 inch to 3/4 inch, but may be larger. Transmitter coil 704 and receiver coil 712 may each have a tilt angle of about 45° and be aligned
10 with the same azimuthal angle, while receiver coil 710 may have a tilt angle of about 45° and an azimuthal angle of 180° apart from receiver coil 712 (or equivalently, a tilt angle of minus 45° at the same azimuth angle as receiver coil 712).

The signal measured by a tilted receiver in response to the firing of a tilted transmitter can be expressed in terms of the signals v_i^j that would be measured by the tool of Figure 4.
15 Specifically, Figures 8a and 8b depict a configuration of an antenna system equipped with a tilted transmitter 802 and a tilted receiver 804 in accordance with an embodiment of the present invention. As shown in Figure 8a, the Cartesian coordinate system may be divided into 4 quadrants.

An electromagnetic resistivity logging tool may then be provided which may include a
20 rotational position sensor. The electromagnetic resistivity logging tool may further include a first transmitter antenna oriented in the first quadrant. A receiver antenna may be oriented in the first quadrant or the third quadrant which is located diagonal to the first quadrant. A second transmitter may be oriented in one of the second quadrant or the fourth quadrant. As shown in Figure 8a, each of the second quadrant and the fourth quadrant are located adjacent to the first
25 quadrant. With substantially same distance between the first transmitter antenna and the receiver antenna and the second transmitter antenna and the receiver antenna, the following steps may be performed as discussed in more detail below. First, an expression of raw measurements at the receiver antenna in response to the firing of the first transmitter may be obtained as a first expression. Next, an expression of raw measurements at the receiver antenna in response to
30 firing of the second transmitter may be determined as a second expression. The first expression and the second expression may then be used to obtain an expression for the processed signals matching to forward model responses of the system.

When both transmitter and receiver coils are oriented at the same azimuth angle β , the tilted receiver signal V_R^T is

$$V_R^T(\beta) = \begin{bmatrix} \sin \theta_t \cos \beta \\ \sin \theta_t \sin \beta \\ \cos \theta_t \end{bmatrix}^T \begin{bmatrix} v_x^x & v_y^x & v_z^x \\ v_x^y & v_y^y & v_z^y \\ v_x^z & v_y^z & v_z^z \end{bmatrix} \begin{bmatrix} \sin \theta_r \cos \beta \\ \sin \theta_r \sin \beta \\ \cos \theta_r \end{bmatrix} = \begin{bmatrix} \sin \theta_t \cos \beta \\ \sin \theta_t \sin \beta \\ \cos \theta_t \end{bmatrix}^T v_M \begin{bmatrix} \sin \theta_r \cos \beta \\ \sin \theta_r \sin \beta \\ \cos \theta_r \end{bmatrix} \quad (3)$$

where, θ_t is the tilt angle of the transmitter related to the z-axis which is denoted by line 800 of Figure 8b; θ_r is the tilt angle of the receiver related to the z-axis which is denoted by line 800; v_I^J is a complex value representing the signal amplitude and phase shift measured by the receiver 804 in the *I*-directional dipole in response to firing of transmitter 802 in the *J*-directional dipole; and v_M is the 3x3 complex voltage matrix corresponding to v_I^J . As would be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, v_I^J in Eq. (3) is affected by environmental conditions. Specifically, v_I^J in Eq. (3) may be affected by two environmental conditions, a surrounding target such as a casing in a homogeneous isotropic medium and a surrounding boundary.

Figures 9a depicts configuration of a rotating tool's relationship to surrounding casing and Figure 9b depicts configuration of a rotating tool's relationship to a surrounding boundary and Figure 9c depicts configuration of a rotating tool's relationship to electrical anisotropy of a thinly laminated formation.

With reference to Figure 9c, electrical anisotropy exists in laminated thin layers 910 each with different resistivity values, producing a higher resistivity in the direction perpendicular to the fracture plan (vertical resistivity R_v , as shown on axis 912) than the resistivity (horizontal resistivity R_h , as shown on axis 912) in the parallel direction. While operating the tool 902 downhole in an anisotropic formation, the tool's 902 highside may not point to the formation plane where horizontal resistivity R_h exists. Therefore, measurements will be affected by the azimuth difference ϕ_i between the tool's 902 high side and the direction pointing to the formation plane 910.

As shown in Figures 9a, 9b and 9c, all environments present a relative azimuthal angle ϕ_i between the coordinate defined by the tool 902 and surrounding environments. While operating a tool 902 downhole, a z-directional axis of the tool's Cartesian coordinate system 904 may be

selected based on the tool's current borehole path. Similarly, an azimuthal angle β for the tool may be determined in the x-y plane of the tool Cartesian coordinate system 904. Specifically, the x-directional axis may be defined in the high side of tool 902 based on magnetometer and/or gravity system of the tool 902 with corresponding azimuthal angle of zero. Accordingly, as depicted in Figures 9a, 9b, and 9c, the angle ϕ_i between high side direction of the tool 902 and the direction with the closest distance (L) to the casing position 906 as shown in Figure 9a, a boundary plane 908 as shown in Figure 9b, or a thinly laminated formation 910 is herein defined as relative azimuthal angle ϕ_i .

In order to determine the relative azimuthal angle ϕ_i , the high side of the tool 902 may be hypothetically rotated along with the z-axis of the tool Cartesian coordinate system 904 toward the target in Figure 9. Accordingly, by applying the rotating angle ϕ_i into Eq. (3), the measured angle in response to the new azimuthal angle β' defined in the rotated Cartesian coordinate system denoted x', y', and z' as shown in Figure 10 may be given by

$$V_R^T(\beta') = \begin{bmatrix} \sin \theta_i \cos \beta' \\ \sin \theta_i \sin \beta' \\ \cos \theta_i \end{bmatrix}^T \begin{bmatrix} v'_x & v'_y & v'_z \\ v'_x & v'_y & v'_z \\ v'_x & v'_y & v'_z \end{bmatrix} \begin{bmatrix} \sin \theta_r \cos \beta' \\ \sin \theta_r \sin \beta' \\ \cos \theta_r \end{bmatrix} = \begin{bmatrix} \sin \theta_i \cos \beta' \\ \sin \theta_i \sin \beta' \\ \cos \theta_i \end{bmatrix}^T v'_M \begin{bmatrix} \sin \theta_r \cos \beta' \\ \sin \theta_r \sin \beta' \\ \cos \theta_r \end{bmatrix} \quad (4)$$

where β' equals $(\beta + \phi_i)$ and v'_M is a 3x3 complex voltage matrix corresponding to v'_J measured in the rotated Cartesian coordinate system or a new Cartesian coordinate system with the x-directional axis pointing to the surrounding target. Specifically, the relationship when the Cartesian coordinate system is rotated along with the z-directional axis with a clockwise relative azimuthal angle ϕ_i in the x-y plane may be characterized as shown in Figure 10.

Because the high side of the tool 902 points to the target after the rotation of the Cartesian coordinate system 904 as shown in Figure 10, based on the electromagnetic concept, Equation (4) may be simplified as:

$$V_R^T(\beta') = \begin{bmatrix} \sin \theta_i \cos \beta' \\ \sin \theta_i \sin \beta' \\ \cos \theta_i \end{bmatrix}^T \begin{bmatrix} v'_x & 0 & v'_z \\ 0 & v'_y & 0 \\ v'_x & 0 & v'_z \end{bmatrix} \begin{bmatrix} \sin \theta_r \cos \beta' \\ \sin \theta_r \sin \beta' \\ \cos \theta_r \end{bmatrix} = \begin{bmatrix} \sin \theta_i \cos \beta' \\ \sin \theta_i \sin \beta' \\ \cos \theta_i \end{bmatrix}^T v'_M \begin{bmatrix} \sin \theta_r \cos \beta' \\ \sin \theta_r \sin \beta' \\ \cos \theta_r \end{bmatrix} \quad (5)$$

The relationship between Eq. (3) and Eq. (5) is the rotation of the Cartesian coordinate system 904 of the tool 902 along the z-directional axis and may be described by the relative azimuthal angle ϕ_t as shown in Figure 10. Based on the relationship shown in Figure 10, v'_M may be obtained as:

$$5 \quad v'_M = \begin{bmatrix} \cos \phi_t & \sin \phi_t & 0 \\ -\sin \phi_t & \cos \phi_t & 0 \\ 0 & 0 & 1 \end{bmatrix} v_M \begin{bmatrix} \cos \phi_t & \sin \phi_t & 0 \\ -\sin \phi_t & \cos \phi_t & 0 \\ 0 & 0 & 1 \end{bmatrix} \quad (6)$$

As would be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, if only one surrounding target is considered, four equations related to the measured complex voltage components v_I^J may be derived as shown below:

$$v_x^y + v_y^x = 0 \quad (7a)$$

$$10 \quad (v_x^x + v_y^y) \cos \phi_t \sin \phi_t + v_x^y \sin^2 \phi_t + v_y^x \cos^2 \phi_t = 0 \quad (7b)$$

$$v_x^z \sin \phi_t + v_y^z \cos \phi_t = 0 \quad (7c)$$

$$-v_x^x \sin \phi_t + v_y^y \cos \phi_t = 0 \quad (7d)$$

In order to analyze Eq. (7), two conditions may be taken into consideration. The first assumed condition is instances where the rotation angle ϕ_t is assumed to be either $\pi/2$ (90°) or $3\pi/2$ (270°). Under the first assumed condition from Eq. (7), it may be concluded that $v_y^x = v_x^y = v_z^x = v_x^z = 0$. Therefore, the measured raw signal presented in Eq. (3) may be expressed as:

$$\begin{aligned} V_R^T(\beta) &= \begin{bmatrix} \sin \theta_t \cos \beta \\ \sin \theta_t \sin \beta \\ \cos \theta_t \end{bmatrix}^T \begin{bmatrix} v_x^x & 0 & 0 \\ 0 & v_y^y & v_z^y \\ 0 & v_y^z & v_z^z \end{bmatrix} \begin{bmatrix} \sin \theta_r \cos \beta \\ \sin \theta_r \sin \beta \\ \cos \theta_r \end{bmatrix} \\ &= \left(\frac{v_x^x}{2} \sin \theta_t \sin \theta_r - \frac{v_y^y}{2} \sin \theta_t \sin \theta_r \right) \cos 2\beta + (v_y^z \cos \theta_t \sin \theta_r + v_z^y \sin \theta_t \cos \theta_r) \sin \beta \quad (8) \\ &\quad + \left(\frac{v_x^x}{2} \sin \theta_t \sin \theta_r + \frac{v_y^y}{2} \sin \theta_t \sin \theta_r + v_z^z \cos \theta_t \cos \theta_r \right) \\ &= V_1 \cos 2\beta + V_2 \sin \beta + V_3 \end{aligned}$$

where V_1 , V_2 , and V_3 may be determined by current environments and tool 902 antenna structures as:

$$V_1 = \frac{v_x^x}{2} \sin \theta_t \sin \theta_r - \frac{v_y^y}{2} \sin \theta_t \sin \theta_r$$

$$V_2 = v_y^z \cos \theta_t \sin \theta_r + v_z^y \sin \theta_t \cos \theta_r$$

$$5 \quad V_3 = \frac{v_x^x}{2} \sin \theta_t \sin \theta_r + \frac{v_y^y}{2} \sin \theta_t \sin \theta_r + v_z^z \cos \theta_t \cos \theta_r$$

On the other hand, under a second assumed condition, if the rotation angle ϕ_t is neither $\pi/2$ (90°) nor $3\pi/2$ (270°), the following relationships may be derived from Eq. (7):

$$v_x^y = -v_y^x \quad (9a)$$

$$\begin{cases} v_y^x = -\frac{1}{2} \tan(2\phi_t) (v_x^x + v_y^y), \text{ if } \cos(2\phi_t) \neq 0 \\ v_x^x = -v_y^y, \text{ if } \cos(2\phi_t) = 0 \end{cases} \quad (9b)$$

$$10 \quad v_y^z = -v_x^z \tan \phi_t \quad (9c)$$

$$v_z^y = v_z^x \tan \phi_t \quad (9d)$$

and therefore, the measured raw signal may be modified as:

$$\begin{aligned}
V_R^T(\beta) &= \begin{cases} \begin{bmatrix} \sin\theta_i \cos\beta \\ \sin\theta_i \sin\beta \\ \cos\theta_i \end{bmatrix}^T \begin{bmatrix} v_x^x & -\frac{1}{2}\tan(2\phi_i)(v_x^x + v_y^y) & v_z^x \\ \frac{1}{2}\tan(2\phi_i)(v_x^x + v_y^y) & v_y^y & v_z^x \tan\phi_i \\ v_x^z & -v_x^z \tan\phi_i & v_z^z \end{bmatrix} \begin{bmatrix} \sin\theta_r \cos\beta \\ \sin\theta_r \sin\beta \\ \cos\theta_r \end{bmatrix}, & \text{if } \cos(2\phi_i) \neq 0 \\ \begin{bmatrix} \sin\theta_i \cos\beta \\ \sin\theta_i \sin\beta \\ \cos\theta_i \end{bmatrix}^T \begin{bmatrix} v_x^x & v_y^x & v_z^x \\ -v_y^x & -v_x^x & v_z^x \tan\phi_i \\ v_x^z & -v_x^z \tan\phi_i & v_z^z \end{bmatrix} \begin{bmatrix} \sin\theta_r \cos\beta \\ \sin\theta_r \sin\beta \\ \cos\theta_r \end{bmatrix}, & \text{if } \cos(2\phi_i) = 0 \end{cases} \\
&= \left(\frac{v_x^x \sin\theta_i \sin\theta_r}{2} - \frac{v_y^y \sin\theta_i \sin\theta_r}{2} \right) \cos 2\beta \\
&\quad + (v_x^z \cos\theta_i \sin\theta_r + v_z^x \sin\theta_i \cos\theta_r) \cos\beta + (v_z^x \sin\theta_i \cos\theta_r - v_x^z \cos\theta_i \sin\theta_r) \tan\phi_i \sin\beta \\
&\quad + \left(\frac{v_x^x \sin\theta_i \sin\theta_r}{2} + \frac{v_y^y \sin\theta_i \sin\theta_r}{2} + v_z^z \cos\theta_i \cos\theta_r \right) \\
&= V_1 \cos 2\beta + V_4 \cos\beta + V_5 \sin\beta + V_3
\end{aligned} \tag{10}$$

Again, V_4 and V_5 may be determined by the existing environment and tool 902 antennal structures where $V_4 = v_x^z \cos\theta_i \sin\theta_r + v_z^x \sin\theta_i \cos\theta_r$ and $V_5 = (v_z^x \sin\theta_i \cos\theta_r - v_x^z \cos\theta_i \sin\theta_r) \tan\phi_i$.

Equations (8) and (10) provide a better understanding of raw measurements from a rotating tool equipped with a tilt antenna system with only one surrounding target. In order to simplify the analysis, the forwarding model normally only considers one target surrounding the tool 902 with its high side pointing to that target. As a result, in instances where there is more than one target surrounding the tool 902, and/or there is a significant relative azimuthal angle ϕ_i , the modeling responses could explain real behaviors of tool measurements but not get accurate inversion results. Consequently before inverting formation parameters based on raw measurements, it is desirable to process the raw measurements first to obtain better signal quality that is closer to the modeling responses. Eq. (5) represents the modeling responses and may be expressed as:

$$\begin{aligned}
V_R^T(\beta') &= \left[\left(\frac{v_x'^x \sin\theta_i \sin\theta_r}{2} - \frac{v_y'^y \sin\theta_i \sin\theta_r}{2} \right) \cos 2\beta' \right] + \left[(v_x'^z \cos\theta_i \sin\theta_r + v_z'^x \sin\theta_i \cos\theta_r) \cos\beta' \right] \\
&\quad + \left(v_z'^z \cos\theta_i \cos\theta_r + \frac{v_x'^x \sin\theta_i \sin\theta_r}{2} + \frac{v_y'^y \sin\theta_i \sin\theta_r}{2} \right)
\end{aligned} \tag{11}$$

Based on Eq. (6) and Eqs. (7a)-(7d), if ϕ_i is $\pi/2$ (90°) or $3\pi/2$ (270°), Eq. (11) may be rewritten as:

$$\begin{aligned}
V_R^T(\beta') &= \left[\left(\frac{v_x^x \sin \theta_i \sin \theta_r}{2} - \frac{v_y^y \sin \theta_i \sin \theta_r}{2} \right) \cos 2\beta' \right] + \left[(v_z^z \sin \theta_i \cos \theta_r - v_y^y \cos \theta_i \sin \theta_r) \sin \phi_i \cos \beta' \right] \\
&+ \left(v_z^z \cos \theta_i \cos \theta_r + \frac{v_x^x \sin \theta_i \sin \theta_r + v_y^y \sin \theta_i \sin \theta_r}{2 \cos 2\phi_i} \right) \\
&= V_1 \cos 2\beta' + V_6 \sin \phi_i \cos \beta' + V_7
\end{aligned} \tag{12}$$

where $V_6 = v_z^z \sin \theta_i \cos \theta_r - v_y^y \cos \theta_i \sin \theta_r$ and $V_7 = v_z^z \cos \theta_i \cos \theta_r + \frac{v_x^x \sin \theta_i \sin \theta_r + v_y^y \sin \theta_i \sin \theta_r}{2 \cos 2\phi_i}$. In

contrast, if the rotation angle ϕ_i is neither $\pi/2$ (90°) nor $3\pi/2$ (270°), Eq. (11) may be modified as:

$$\begin{aligned}
V_R^T(\beta') &= \left[\left(\frac{v_x^x \sin \theta_i \sin \theta_r}{2} - \frac{v_y^y \sin \theta_i \sin \theta_r}{2} \right) \cos 2\beta' \right] + \left[\frac{(v_z^z \cos \theta_i \sin \theta_r + v_x^x \sin \theta_i \cos \theta_r)}{\cos \phi_i} \cos \beta' \right] \\
&+ \left(v_z^z \cos \theta_i \cos \theta_r + \frac{v_x^x \sin \theta_i \sin \theta_r + v_y^y \sin \theta_i \sin \theta_r}{2 \cos 2\phi_i} \right) \\
&= V_1 \cos 2\beta' + \frac{V_4}{\cos \phi_i} \cos \beta' + V_7, \text{ if } \cos(2\phi_i) \neq 0
\end{aligned} \tag{13a}$$

$$\begin{aligned}
V_R^T(\beta') &= \left[\left(\frac{v_x^x \sin \theta_i \sin \theta_r}{2} - \frac{v_y^y \sin \theta_i \sin \theta_r}{2} \right) \cos 2\beta' \right] + \left[\frac{(v_z^z \cos \theta_i \sin \theta_r + v_x^x \sin \theta_i \cos \theta_r)}{\cos \phi_i} \cos \beta' \right] \\
&+ (v_z^z \cos \theta_i \cos \theta_r + v_x^x \sin \theta_i \sin \theta_r \sin 2\phi_i) \\
&= V_1 \cos 2\beta' + \frac{V_4}{\cos \phi_i} \cos \beta' + V_8, \text{ if } \cos(2\phi_i) = 0
\end{aligned} \tag{13b}$$

where $V_8 = v_z^z \cos \theta_i \cos \theta_r + v_x^x \sin \theta_i \sin \theta_r \sin 2\phi_i$.

Accordingly, Eq. (8) and Eq. (10) present signal behaviors of raw tool measurements in an environment condition of a relative azimuthal angle ϕ_i toward surrounding target, whereas Eq. (12) and Eqs. (13a) and (13b) demonstrate how forwarding model signals are presented by the measured raw signals. Consequently, these equations provide processing schemes on raw measurements to match to forwarding model responses. As would be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, the relationships identified in Equations (8), (10), (12) and (13a)-(13b) may be used to reveal that the amplitude of double sine wave responses is consistent. Accordingly, these equations may be used to match raw measurements to forwarding model responses.

Figure 11 depicts the configuration of the bin positions and corresponding azimuthal angles of a tool 902 in accordance with an embodiment of the present invention. As shown in Figure 11, N is the total number of bins in the rotating tool 902 and a bin i with azimuthal angle β_i and a bin j with azimuthal angle β_j are located opposite each other so that $\beta_i = \beta_j + 180^\circ$.

5 Figure 12 depicts a flow chart for the proposed processing scheme of the raw measurements in accordance with an embodiment of the present invention. First, at step 1202, raw measurements are obtained from the tool 902. As would be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, obtaining raw measurements from the tool 902 is well known in the art and will therefore not be discussed in detail herein. Once the raw
10 measurements are obtained, they may be processed in accordance with an embodiment of the present invention.

The calculations in accordance with an embodiment of the present invention may be simplified by assuming that the rotating angle ϕ_i is neither $\pi/2$ (90°) nor $3\pi/2$ (270°) and accordingly, $\cos(2\phi_i) \neq 0$. As would be appreciated by those of ordinary skill in the art, with the
15 benefit of this disclosure, this assumption does not exclude other rotating angles from the proposed processing scheme and is merely used to simplify the conditions to obtain the following general expressions for the proposed processing scheme. Accordingly, the methods disclosed herein are applicable to any rotating angle in implementation. Under the assumed condition that the rotating angle ϕ_i is neither $\pi/2$ (90°) nor $3\pi/2$ (270°) and using a tool as shown
20 in Figure 11, three steps may be used to analyze the raw measurements in step 1204. In the first step, all the bin measurements are averaged as follows to obtain V_{step1} :

$$V_{\text{Step1}} \equiv \frac{1}{N} \sum_{i=1}^N V_R^T(\beta_i)$$

Next, step 2 entails averaging two raw complex voltage measurements where one is in a bin direction and the other is in the opposite bin direction. Specifically, V_{step2} may be determined as:

$$25 \quad V_{\text{Step2}}(\beta_i) \equiv \frac{V_R^T(\beta_i) + V_R^T(\beta_j)}{2} - V_{\text{step1}}, i = 1, 2, K, N$$

Finally, step 3 is averaging the subtraction of one raw measurement in a bin direction from the other raw measurement in opposite bin direction to obtain V_{step3} as follows:

$$V_{Step3}(\beta_i) \equiv \frac{V_R^T(\beta_i) - V_R^T(\beta_j)}{2}$$

The three steps above may be used to distribute the raw measurements of Eq. (10) into three parts: (1) a complex voltage; (2) azimuthal voltages as a sinusoid wave response with double periods; and (3) azimuthal voltages as a sinusoid wave response with a single period with
 5 respect to tool's azimuthal angle (0~360°, or the tool's bin 1 to bin N as shown in Figure 11).

As would be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, both cosine wave fitting and sine wave fitting functions may be used to fit processed responses. Specifically, because cosine wave and sine wave responses are theoretically similar except for a 180° phase shift, the only difference between cosine and sine fitting functions is 180°
 10 phase shift on estimated ϕ_i . Accordingly, the methods and systems disclosed herein may be carried out using both sine wave or cosine wave fitting methods.

After applying the three steps, at step 1206, the second step with two period sinusoid wave responses is examined. As discussed above, the amplitude of the cosine wave responses of the second step remains the same, regardless of the relative azimuthal rotation angle ϕ_i . As a result,
 15 investigation of this part will provide a good estimated result for the relative azimuthal rotation angle ϕ_i . Since the response at this second step is a sinusoid wave with two period, there are four rotation angles that may be found by cosine curve fitting. Cosine curve fitting is well known to those of ordinary skill in the art and will therefore not be discussed in detail herein. After the cosine curve fitting is performed and four rotation angles are determined, at step 1208,
 20 the process may be simplified by only considering the two smallest values obtained for the relative azimuthal rotation angle ϕ_i , where one of the two values could be the real value of ϕ_i and the other will be either ($\phi_i + 90^\circ$) or ($\phi_i - 90^\circ$) depending on which absolute value is smaller. Accordingly, at step 1208, the amplitude (V1 from Eq. (10)) corresponding to each of the values of the relative azimuthal rotation angle ϕ_i may be determined. Once the value of V1 (from Eq.
 25 (10)) and the two possible values of relative azimuthal rotation angle ϕ_i are known, at step 1210, a single period sinusoid wave is identified. Next, cosine curve fitting is utilized and the two computed relative azimuthal rotation angles ϕ_i may be used to calculate the corresponding amplitude of V4 and V5 (from Eq. (10)). Specifically, the two possible values of the relative azimuthal rotation angle ϕ_i are applied to step 1210 to identify the correct value of the relative

azimuthal rotation angle ϕ_i as well as V4 and V5 in Eq. (10). The two possible values of the relative azimuthal rotation angle ϕ_i will cause different estimated values of V4 and V5 after cosine curve fitting between steps 1210 and 1212.

Next, at step 1212, an accurate value for the relative azimuthal rotation angle ϕ_i , V1, V4, and V5 of Eq. (10) may be determined. Based on the distinct tilt angle designs of the antenna system, V4 may be larger than V5 in amplitude for some tilt transmitter and tilt receiver designs and V4 may be smaller than V5 in amplitude for other tilt antenna designs. Knowing the antenna structure in advance, one can differ V4 and V5 in their amplitudes. Accordingly, an accurate relative azimuthal rotation angle ϕ_i may be obtained by applying the two estimated values found in the second step and the third step and then comparing the corresponding amplitudes of V4 and V5. Specifically, the correct value of the relative azimuthal rotation angle ϕ_i may be determined when (1) the tilt angles of Tx and Rx are known; (2) two possible values of the relative azimuthal rotation angle ϕ_i are identified in step 1208; (3) V4 and V5 values are calculated based on two possible values of the relative azimuthal rotation angle ϕ_i and (4) the absolute amplitude of V4 and V5 are known and can be compared.

In one exemplary embodiment, a constant voltage of the first step is obtained at step 1214, which is the value of V3 in Eq. (10) at step 1216. Next, at step 1216, the constant voltage of the third step may be used to determine the value of V3 in Eq. (10). Using the value of V3 obtained in step 1216 in conjunction with the values obtained for V1, V4, V5 and ϕ_i , the raw measurement may be curve-fitted and described as Eq. 10 at step 1218.

In another exemplary embodiment, once the values for V1, V4, V5 and ϕ_i are determined, at step 1220 the signal's match with the forwarding model may be determined as shown in Figure 12.

However, as would be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, using a single tilt transmitter-receiver pair does not permit matching raw measurements of Eq. (10) to the modeling responses of Eq. (13a) because calculating V7 in Eq. (13a) requires the evaluation of values of the measured voltage components of V_z^z and $V_x^x + V_y^y$. In order to overcome this problem, a two antenna system design with the same spacing between transmitter and receiver but different tilt angles of transmitter or different tilt angles of receiver

such as the one depicted in Figure 13 may be used. In one exemplary embodiment, a commercially available azimuthal directional resistivity tool with a tilt transmitter and a tilt receiver (ADR-TT) such as ones available from Halliburton Energy Services of Duncan, Oklahoma, may be used.

- 5 As shown in Figure 13, transmitters and receivers may be placed along an axis 1300. A distance d between upper transmitter T_{up} and central receiver Rx may be the same as the distance between lower transmitter T_{dn} and central receiver Rx. However, the upper transmitter T_{up} and the central receiver Rx are parallel to each other while the lower transmitter T_{dn} and the central receiver Rx are perpendicular to each other. Accordingly, the raw measured signals received in
10 the central receiver Rx in response to firing of the upper transmitter T_{up} may be represented as:

$$V_{R_x}^{T_{up}}(\beta) = \left[\left(\frac{v_x^x}{4} - \frac{v_y^y}{4} \right) \cos 2(\beta' - \phi_i) \right] + \left[\frac{1}{2} (v_x^z + v_z^x) \cos(\beta' - \phi_i) + \frac{1}{2} (v_z^x - v_x^z) \tan \phi_i \sin(\beta' - \phi_i) \right] + \left(\frac{v_x^x}{4} + \frac{v_y^y}{4} + \frac{v_z^z}{2} \right) \quad (14a)$$

In contrast, the measured signals receiver in the center receiver Rx in response to firing of lower transmitter T_{dn} may be represented as:

$$V_{R_x}^{T_{dn}}(\beta) = \left[\left(\frac{v_x^x}{4} - \frac{v_y^y}{4} \right) \cos 2(\beta' - \phi_i) \right] + \left[\frac{1}{2} (v_x^z - v_z^x) \cos(\beta' - \phi_i) - \frac{1}{2} (v_z^x + v_x^z) \tan \phi_i \sin(\beta' - \phi_i) \right] + \left(\frac{v_x^x}{4} + \frac{v_y^y}{4} - \frac{v_z^z}{2} \right) \quad (14b)$$

- 15 Accordingly, after performing the first step procedure on both Eq. (14a) and Eq. (14b), the constant complex voltages may be expressed as:

$$V_{Step1\_TupRx} = \frac{v_x^x}{4} + \frac{v_y^y}{4} + \frac{v_z^z}{2} \quad (15a)$$

$$V_{Step1\_TdnRx} = \frac{v_x^x}{4} + \frac{v_y^y}{4} - \frac{v_z^z}{2} \quad (15b)$$

- Consequently, the processed signals matching to the forwarding model responses may be
20 represented as:

$$V_{R_x}^{T_{up}}(\beta') = \left[\left(\frac{v_x^x}{4} - \frac{v_y^y}{4} \right) \cos 2\beta' \right] + \left[\frac{1}{2 \cos \phi_i} (v_x^z + v_z^x) \cos \beta' \right] + \left(\frac{V_{Step1\_TupRx} - V_{Step1\_TdnRx}}{2} \right) + \left(\frac{V_{Step1\_TupRx} + V_{Step1\_TdnRx}}{2 \cos(2\phi_i)} \right) \quad (16a)$$

$$V_{R_x}^{T_{dn}}(\beta') = \left[\left(\frac{v_x^x}{4} - \frac{v_y^y}{4} \right) \cos 2\beta' \right] + \left[\frac{1}{2 \cos \phi_i} (v_x^z - v_z^x) \cos \beta' \right] + \left(\frac{V_{Step1\_TdnRx} - V_{Step1\_TupRx}}{2} \right) + \left(\frac{V_{Step1\_TdnRx} + V_{Step1\_TupRx}}{2 \cos(2\phi_i)} \right) \quad (16b)$$

As would be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, the methods and systems disclosed herein are applicable to antenna systems with arbitrary tilt angle for transmitters (Tx) and receivers (Rx). The systems and methods disclosed herein are not limited to any specific antenna configuration and may be applied to a number of systems, including, but not limited to, antenna systems having one tilt Tx and one tilt Rx, combinations of two tilt Txs and one Rx, combinations of two tilt Rxs and one Tx, or combinations of multiple tilt Txs and multiple tilt Rxs. Moreover, the tilt angles of the transmitters and receivers may be the same or different. Further, as would be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, based on the reciprocity theorem, antennas may operate equally well as transmitters or receivers. Accordingly, an antenna may be applied as a transmitter in one implementation and as a receiver in another. As a result, all the configurations of transmitters-receivers of the antenna systems disclosed herein may be interchangeable. Specifically, transmitters may be used as receivers and receivers may be used as transmitters.

EXAMPLE I

Figure 14 depicts the configuration of a formation model of two layered isotropic media with a boundary between the two layers 1402 and 1404. In this example, the upper layer 1402 has a resistivity of 1Ω.m and the lower layer 1204 has a resistivity of 4 Ω.m. In the example, the relative dip angle is 15° and the reference point of ADR-TT tool is about 3.58 ft. away from the boundary as shown in Figure 14. Figure 15 depicts the modeling signals of Eq. (14a) and Eq. (14b) for this formation model with a relative azimuthal rotation angle ϕ_i of 30°. The total 32 bin signals were calculated with a spacing of 52 inch (denoted as d in Figure 13) and operating frequency of 125 kHz.

Figure 16 signal response with x-axis of the tool Cartesian coordinate system 904 pointing to the formation boundary. Specifically, Figure 16 represents the signals of Eq. (14a) and Eq. (14b) if rotating wrong angle of -60°. As would be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, the amplitude of single cosine wave responses from parallel transmitter-receiver pair (T_{up} and Rx) should be bigger than the amplitude of the single

cosine wave responses from the perpendicular transmitter-receiver pair (T_{dn} and Rx). As would be appreciated by those of ordinary skill in the art, with the benefit of this disclosure, this relationship may also be confirmed using Eq. (16a) and Eq. (16b). As discussed above, in conjunction with Figure 12, a comparison of the amplitudes of V4 and V5 of Eq. (10) may be used to evaluate which of the two relative azimuthal rotation angles (ϕ_i) from the procedure of the second step reflects the true value of the relative azimuthal rotation angle ϕ_i . Accordingly, while rotating the tool 90° to the boundary target, the amplitude of the single cosine wave of parallel pair increases, whereas that of the perpendicular pair decreases, which verifies that the angle of 30° is the relative azimuthal angle. Figure 17 shows signal responses for an exemplary embodiment where the x-axis of the tool coordinate system is parallel to the formation boundary.

EXAMPLE II

A commercially available ADR-TT tool was examined in a water tank with a surrounding conductive casing target to validate the methods disclosed herein. In order to verify the methods disclosed herein, experiments were conducted in a water tank with a surrounding conductive casing parallel to the tool ADR-TT. In order to steer the casing position, the flowchart in Figure 12 and the processing schemes described herein were applied to the raw measurements from the water tank experiments. Figure 18 represents raw measurements of a spacing of 44 inches between transmitter and receiver in Figure 13 with operating frequency of 500 kHz. Figure 19 shows the processed signals after rotating the tool high side to the target casing. Because there is only one target surrounding the tool, it can be proven using Eq. (16a) and Eq. (16b.) that the single cosine wave responses of perpendicular Tx-Rx pair should be smaller than the responses of parallel Tx-Rx pair. Accordingly, the ADR-TT may be steered to the target casing by using the proposed concept and processing schemes disclosed herein. The results of the experiment confirm that the methods disclosed herein may be used to determine surrounding casing position. Moreover, the experiments confirm that the responses after the processing scheme are similar to the modeling responses.

The present invention is therefore well-adapted to carry out the objects and attain the ends mentioned, as well as those that are inherent therein. While the invention has been depicted, described and is defined by references to examples of the invention, such a reference does not imply a limitation on the invention, and no such limitation is to be inferred. The invention is capable of considerable modification, alteration and equivalents in form and function, as will occur to those ordinarily skilled in the art having the benefit of this disclosure. The depicted and

described examples are not exhaustive of the invention. Consequently, the invention is intended to be limited only by the spirit and scope of the appended claims, giving full cognizance to equivalents in all respects.

AMENDED CLAIMS

received by the International Bureau on 17 May 2012 (17.05.2012)

What is claimed is:

1. A method of processing data from an electromagnetic resistivity logging tool comprising:
placing the electromagnetic resistivity logging tool at a desired location;
wherein the electromagnetic resistivity tool comprises a transmitter coil and a receiver coil;
positioning the transmitter coil and the receiver coil at a first azimuthal angle; and
expressing a signal at the receiver coil as a complex voltage representing at least one of a phase and an amplitude of the signal at the receiver coil oriented at the first azimuthal angle.
2. The method of claim 1, further comprising:
defining a relative azimuthal angle between a Cartesian coordinate system defined by the electromagnetic resistivity logging tool and a surrounding environment.
3. The method of claim 2, wherein the surrounding environment is selected from a group consisting of a casing and a boundary plane.
4. The method of claim 2, further comprising:
rotating the Cartesian coordinate system defined by the electromagnetic resistivity logging tool by the relative azimuthal angle to define a second azimuthal angle for the receiver coil;
expressing the signal at the receiver coil as a complex voltage representing at least one of a phase and an amplitude of the signal at the receiver coil oriented at the second azimuthal angle;
5. The method of claim 4, wherein the second azimuthal angle is a sum of the first azimuthal angle and the relative azimuthal angle.
6. The method of claim 4, further comprising:
assuming a first condition wherein the relative azimuthal angle is selected from the group consisting of 90° and 270°;

expressing a signal at the receiver coil as a complex voltage representing at least one of a phase and an amplitude of the signal at the receiver coil under the first assumed condition;

7. The method of claim 6, further comprising:

assuming a second condition wherein the relative azimuthal angle is an angle that is different from an angle selected from the group consisting of 90° and 270°;

expressing a signal at the receiver coil as a complex voltage representing at least one of a phase and an amplitude of the signal at the receiver coil under the second assumed condition;

using the expression of the signal at the receiver coil under the first assumed condition and the expression of the signal at the receiver coil under the second assumed condition to present a signal behavior of raw measurements from the electromagnetic resistivity logging tool in an environment having the relative azimuthal angle toward a surrounding target.

8. The method of claim 4, further comprising deriving a representation of forwarding model signals.

9. The method of claim 8, further comprising:

obtaining raw measurements of received signal at the receiver coil; and

determining if forwarding model signals represent raw measurements of received signal at the receiver coil.

10. The method of claim 1, further comprising:

obtaining raw measurements at the receiver coil;

averaging all bin measurements at the receiver coil in a first step;

averaging two raw complex voltage measurements at the receiver coil in a second step;

wherein the two raw complex voltage measurements comprise a first raw complex voltage measurement in a bin direction and a second raw complex voltage measurement in an opposite bin direction; and

averaging a difference between one raw measurement at the receiver coil in a bin direction and another raw measurement at the receiver coil in opposite bin direction in a third step.

11. The method of claim 10, further comprising distributing the raw measurements at the receiver coil into a group consisting of one or more of a constant complex voltage; an azimuthal voltage as a sinusoid wave response with double periods; and an azimuthal voltage as a sinusoid wave response with a single period.
12. The method of claim 11, further comprising curve fitting the raw measurements obtained at the receiver coil.
13. The method of claim 12, wherein curve fitting the raw measurements obtained at the receiver coil comprises using cosine curve fitting.
14. The method of claim 12, further comprising calculating signal match with a forwarding model.
15. The method of claim 14, wherein calculating signal match with a forwarding model comprises determining a relative azimuthal rotation angle of the electromagnetic resistivity logging tool.
16. The method of claim 1, wherein the transmitter coil is a first transmitter antenna oriented in a first quadrant; wherein the receiver coil is a receiver antenna oriented in one of the first quadrant and a third quadrant, wherein the third quadrant is diagonal to the first quadrant; further comprising:
 - providing a second transmitter oriented in one of a second quadrant and a fourth quadrant, wherein the second quadrant and the fourth quadrant are adjacent to the first quadrant; and wherein a distance between the first transmitter antenna and the receiver antenna is substantially same as a distance between the second transmitter antenna and the receiver antenna;
 - determining an expression of raw measurements at the receiver antenna in response to firing of the first transmitter as a first expression;
 - determining an expression of raw measurements at the receiver antenna in response to firing of the second transmitter as a second expression; and
 - obtaining an expression for processed signals matching to forward model responses using the first expression and the second expression.

17. The method of claim 16, wherein the electromagnetic resistivity logging tool further comprises a rotational position sensor.
18. The method of claim 16, wherein the receiver antenna is substantially parallel to the first transmitter antenna.
19. The method of claim 16, wherein the receiver antenna is substantially perpendicular to the second transmitter antenna.
20. The method of claim 16, wherein the first expression is a function of a tilt angle of the first transmitter, a tilt angle of the receiver antenna and a complex voltage matrix.



Fig. 1




Fig. 2





Fig. 3






Fig. 4




Fig. 5




Fig. 6




Fig. 7







Fig. 8A




Fig. 8B






Fig. 9A




Fig. 9B




Fig. 9C






Fig. 10




Fig. 11





Fig. 12






Fig. 13




Fig. 14





Fig. 15




Fig. 16




Fig. 17






Fig. 18







Fig. 19






Fig. 12

