



(51) International Patent Classification:
G06Q 30/00 (2006.01)

(21) International Application Number:
PCT/EP2010/064101

(22) International Filing Date:
24 September 2010 (24.09.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09305989.7 16 October 2009 (16.10.2009) EP

(71) Applicant (for all designated States except US): **ALCATEL LUCENT** [FR/FR]; 3, avenue Octave Gréard, F-75007 Paris (FR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PICAULT, Jérôme** [FR/FR]; Alcatel-Lucent Bell Labs France, Route de Villejust, F-91620 Nozay (FR). **KOSTADINOV, Dimitre, Davidov** [FR/FR]; Alcatel-Lucent Bell Labs France, Route de Villejust, F-91620 Nozay (FR). **BOUZID, Makram** [FR/FR]; Alcatel-Lucent Bell Labs France, Route de Villejust, F-91620 Nozay (FR).

(74) Agent: **NICOLLE, Olivier**; Alcatel-Lucent International, 32, avenue de Kléber, F-92700 Colombes (FR).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: DEVICE FOR DETERMINING POTENTIAL FUTURE INTERESTS TO BE INTRODUCED INTO PROFILE(S) OF USER(S) OF COMMUNICATION EQUIPMENT(S)



(57) Abstract: A device (D) is intended for determining potential interests of users (U1-U3) that are clients of at least one network operator, each user being associated to a profile defining at least his interests. This device (D) comprises i) a tracking means (TM) arranged for analyzing the profile of at least one user (U1) to determine new real interest(s) it contains and for storing an identifier representative of a determined new real interest of this user (U1) in correspondence with a first date at which it has been considered as a new real interest into his profile, and ii) a recommendation means (RM) arranged for analyzing the first dates of a user (U1) to determine a time ordered sequence of interests preceding a determined new real interest, and for comparing this determined user interest sequence to at least one other sequence of interests of at least one other user (U2) to predict at least one potential future interest for this user (U1), to be introduced into his profile.

DEVICE FOR DETERMINING POTENTIAL FUTURE INTERESTS TO BE INTRODUCED INTO PROFILE(S) OF USER(S) OF COMMUNICATION EQUIPMENT(S)

5

The present invention relates to the recommendation of content items for users of communication equipments capable of being connected to at least one communication network, and more precisely to personalization of user content recommendations.

10 One means here by "user profile" a set of data (or metadata) describing the identity of a user, such as socio-demographic data and interests (or preferences or else habits) relative to one or more subjects (television programs, radio programs, news, music, advertising, entertainment, items to buy or use of services, for instance). (Meta)Data describing user
15 interests can be words or expressions or else concepts that most of the time may be found also in the descriptions that are associated to the content items.

Moreover, one means here by "user content recommendations" recommendations (or suggestions) of content items that are proposed to a user based on interests (or preferences or else habits) contained into his
20 profile.

More, one means here by "concept" something defined by one or more words or from one or several taxonomies or ontologies, and therefore associated to a semantic content. It is usually described by a set of at least one property (i.e. a set of descriptors having a type and a value).

25 One major challenge in the domain of personalization of user content recommendations is to understand the interests of users as properly as possible in order to provide them with content items suited to their respective needs.

30 As it is known by the man skilled in the art, usual techniques for content recommendation (such as content-based filtering algorithms) do not allow introducing in the user profiles concepts that did not appear in the descriptions of content that have been consumed by the users. Indeed, when

a content item is consumed by a user, metadata that describe this content item can be added (according to various heuristics) to the user profile, and then recommendations are generated on the basis of similarities between the user profile and the content metadata. So, content items for which there are
5 no corresponding metadata in a user profile will not be recommended to the user.

These approaches tend to overspecialise the recommendations and do not enable to add enough diversity/discovery in the recommendations. More precisely, these approaches do not allow anticipating user interests: the
10 user must have consumed something described by a concept (or equivalent) to have further recommendations related to that concept. For example, with existing systems if a user liked one book of Victor Hugo, the recommender system will tend to recommend him other books of Victor Hugo, whereas this user (but also many others) may be interested in discovering other writers, just
15 because his (their) taste(s) evolve(s) naturally with time and also because of the influence of the items he (they) has (have) consumed, and of other interests he (they) may have had in the meantime.

Other approaches have been recently proposed to improve the user content recommendations.

20 A first approach concerns the so-called "collaborative recommenders". Typical collaborative recommenders comprise a core mechanism consisting in finding hidden links between users based on the similarity of their preferences or historic behaviour. Items are recommended to a certain user with respect to the interests he shares with other users or
25 according to opinions, comparatives, and ratings of items given by other users having similar profiles.

So, in this first approach, the comparison between users and items is done globally, without taking into account the temporal dimension, and therefore this approach may be not very relevant when there is a strong
30 dependency between two items. Moreover, even if collaborative recommenders allow to bring some diversity in the recommendations, they are not able to address directly the problem of anticipating the next (or future) user interests. More, collaborative recommenders require a significant number of

user ratings in order to be effective (this is the so called "cold-start problem").

A second approach concerns the so-called "frequent pattern mining algorithms". These algorithms enable finding dependencies between the appearance of items in a set of transactions, as described notably in the article of Goethals, B., "Survey on frequent pattern mining", Technical report, Helsinki Institute for Information Technology, 2003. The goal of a frequent pattern mining algorithm is to find a set of frequent and confident association rules of the form " $X \Rightarrow Y$ ", which means: "if the set of items X appears in a transaction, then another set of items Y also appears in that transaction". An association rule is considered as frequent if the ratio between the number of transactions in which X and Y appear together and the total number of transactions satisfies a frequency threshold. Similarly, an association rule is confident if the percentage of transactions where X and Y appear together among all transactions containing X is greater than a confidence threshold.

Even if frequent pattern mining algorithms enable finding relationship between items, they are only concerned with the presence of items in transactions, but they do not consider the moment of appearance of preferences (or items). There exist approaches for frequent temporal pattern mining (for example the one described in the article of Sivaselvan, B. et al, "An efficient frequent temporal pattern mining algorithm," Information Technology Journal, vol. 5, pp. 1043-1047, 2006) which takes into account the order of appearance of items in transactions. However, the temporality is considered in terms of the number of items separating the two frequent sets of items and not in terms of the time elapsed between them.

A third approach concerns the so-called "temporal probabilistic models". Some probabilistic models have been proposed for user interest and interest transition capturing and predicting. They have been notably described in the article of Suzuki, T. et al., "Learning to estimate user interest utilizing the Variational Bayes' estimator", Proceedings of 5th International Conference on Intelligent Systems Design and Applications, Wroclaw, Poland, 94-99, 2005, and in the article of Wang, S. et al, "Mining Interest Navigation Patterns with Hidden Markov Model", Lecture Notes in Computer Science Volume 4027/2006, pp. 470-478, Springer, 2000.

These last models have been conceived for single user interest transition capturing, but not for applying captured interest transition patterns of one user to similar users.

5 So the object of this invention is to anticipate future users' interests, in order to improve users' acceptance and confidence in recommender systems, and alleviate drawbacks of content-based recommender systems which require prior observations prior to updating user interests.

For this purpose, the invention provides a device, intended for determining potential interest(s) of user(s) that is/are client(s) of at least one
10 network operator, each user being associated to a profile defining at least his interests, and comprising:

- a tracking means arranged for analyzing the profile of at least one user to determine new real interest(s) it contains and for storing an identifier representative of a determined new real interest of this user in
15 correspondence with a first date at which it has been considered as a new real interest into his profile, and
- a recommendation means arranged for analyzing the first dates of a user to determine a time ordered sequence of interests preceding a determined new real interest and for comparing this determined user interest sequence
20 to at least one other sequence of interests of at least one other user to predict at least one potential future interest for said user, to be introduced into his profile.

The device according to the invention may include additional characteristics considered separately or combined, and notably:

- 25 - its recommendation means may be arranged for comparing the determined user interest sequence to at least one other sequence of interests, determined into a graph of interests built from the interests of other users, to predict at least one potential future interest of this user;
 - its recommendation means may be arranged for building and updating
30 the interest graph from the stored real interests of the users;
- Its recommendation means may be arranged for building and updating an interest graph which models the evolution of interests over time for a

- plurality of users;
- in a variant, its recommendation means may be arranged for building and updating an auxiliary interest graph which models the evolution of interests over time for one user then for aggregating this auxiliary interest graph with auxiliary interest graphs built for other users to produce an interest graph;
 - its recommendation means may be arranged for building and updating a directed and weighted interest graph $G(V, W)$, where V is a set of nodes representing respectively the user interests, and W is a set of directed edges representing a transition from a user interest to another user interest;
 - its recommendation means may be arranged for assigning a weight to each of the directed edges, each weight being defined by a table establishing a correspondence between each user and an elapsed time between the appearances of first an second consecutive real interests;
 - its recommendation means may be arranged for updating the interest graph each time it is informed by the tracking means that it has determined a new real interest of a user;
 - its recommendation means may be arranged for determining at least one statistical metric from the weights assigned to the directed edges and for using each determined statistical metric with heuristics to suggest interests adapted to a chosen applicative context and then to predict at least one potential future interest for the user from these suggested interests:
 - at least one statistical metric may be representative of the relevance between two interests;
 - at least one statistical metric may be representative of the frequency of a transition between two interests;
 - its tracking means may be arranged for determining the consumption of content items of the user that are related to an interest contained into his profile and for considering that this interest is a new real interest when this determined consumption of the related content items is greater than a chosen threshold;
 - its tracking means may be arranged for considering that the first date of an interest is the date at which it detects that a content item consumption

related to this interest is greater than the chosen threshold;

- its recommendation means may be arranged for determining a favourable date for introducing the potential future interest into the profile of the user.

The invention also provides a network equipment, for at least one
5 communication network, and comprising a device such as the one above introduced, intended for working in a centralized manner to predict potential future interests for a plurality of users.

The invention also provides a user communication equipment
intended for being connected to at least one communication network, and
10 comprising a device such as the one above introduced, intended for predicting potential future interests for its user.

Other features and advantages of the invention will become apparent on examining the detailed specifications hereafter and the appended drawings, wherein:

- 15 - figure 1 schematically illustrates a communication network to which are coupled three communication equipments of users and a network equipment comprising an example of embodiment of a device according to the invention,
- figure 2 is a diagram illustrating an example of evolution of an interest
20 strength (IS) of a user over time (t),
- figure 3 schematically illustrates an example of interest graph concerning n users, and
- figure 4 schematically illustrates an example of algorithm intended for building and updating an interest graph iteratively.

25 The appended drawings may serve not only to complete the invention, but also to contribute to its definition, if need be.

The invention aims at offering a device (D) intended for providing potential interest(s) to at least one user (U_j) i) that is client of a network operator, ii) which is equipped with a communication equipment (CE) capable
30 of being connected to a communication network (CN) of this network operator, and iii) which is associated to a profile defining at least his interests.

As mentioned in the introductory part, one means here by "user

profile" a set of data (or metadata) describing the identity of a user, such as socio-demographic data and interests (or preferences or else habits) relative to one or more subjects (television programs, radio programs, news, music, advertising, entertainment, items to buy or use of services, for instance).
5 (Meta)Data describing user interests can be words or expressions or else concepts that most of the time may be found also in the descriptions that are associated to the content items.

In the following description it will be considered as example that the communication network (CN) is a wired network, for instance of an ADSL
10 type. But the invention is not limited to this type of communication network. Indeed, it concerns any type of communication network, and therefore as well wireless networks as wired networks.

Due to this assumption, it will be considered in the following description that the user communication equipments (CE) are fixed or portable
15 computers. But the invention is not limited to this type of communication equipment. Indeed, it concerns any type of communication equipment capable of being connected to a wireless network and/or a wired network. So, a communication equipment could be also a fixed or mobile phone, a personal digital assistant (or PDA), or a set-top box (STB), for instance.

20 As illustrated in the non limiting example of figure 1, a device D, according to the invention, may be localized into a network equipment SS connected to a communication network CN of a network operator. This network equipment SS may be, for instance, a server SS which is dedicated to the access to information relative to users U_j that are clients of the network
25 operator. This server SS may be a recommender system, for instance. So, in this example the device D works in a centralized manner for a plurality of users U_j (here $j = 1$ to 3). But this device D could be also coupled to a network equipment (also for working in a centralized manner), or located into, or coupled to, a user communication equipment CE for working in a distributed
30 manner for a single user U_j .

This device D can be made of a combination of electronic circuit(s) (or hardware modules) and software modules. In this case it further comprises a software interface allowing interworking between the hardware and software

modules. But it could be also made of electronic circuit(s) or of software modules (in this last case it can be stored in a memory or in any computer software product, such as a CD-ROM, for instance).

A device D according to the invention comprises a tracking module
5 TM and a recommender module RM.

This tracking module TM is intended for analyzing the profile of at least one user U_j . It is important to note that in the described example the device D works in a centralized manner for a plurality of users U_j (here $j = 1$ to 3). So it is arranged for analyzing the profiles of all the users U_j of this
10 plurality, which are stored into a first storage means SM1 which belongs to the network operator, for instance, and which are connected to (as illustrated) or comprise into the communication network CN. But in a variant in which the device D is associated to a single user communication equipment CE, the tracking module TM is arranged for analyzing the only profile of this user U_j ,
15 which can be stored into a storage means of the user communication equipment CE.

Every analysis is carried out by a sub module TSM of the tracking module TM and aims at determining each new real interest contained into the analyzed user profile. A "new real interest" is either an interest which was
20 already contained into a user profile during a preceding analysis but which was not yet considered as really important for this user, or an interest which was not contained into a user profile during the last analysis and which is immediately considered as really important for this user. So, it is not mandatory that a new real interest be a very new (or recent) interest.

To decide whether an interest (contained into a user profile) is really
25 important for this user U_j , the tracking module TM (and more precisely its sub module TSM) may be arranged for determining the consumption of content items of this user U_j that are related to this interest, and for considering that this interest is a (new) real interest when this determined consumption of the
30 related content items is greater than a chosen threshold T_{IS} . This determination of content item consumption can be carried out by the tracking module TM (via the server SS) into the communication network CN (for instance into the server(s) delivering the content items) or into the concerned

user communication equipment CE.

An example of evolution over time t of an interest strength IS , representative of the consumption by a user U_j of content items relating to an interest contained into his profile, is illustrated in the diagram of figure 2.

5 Generally speaking the interest strength IS is a function of the content consumption. In this diagram the time t is given in days (but it could be also given in months or weeks or else hours depending on the manipulated data and/or concerned application – more generally the unit (t) is chosen to be the most appropriate to describe the evolution of interest strength IS over time (t)) and the chosen threshold T_{IS} is equal to 0.72. Moreover in this example the
10 tracking module TM considers that the interest became really important at the date t_a which corresponds to the time when the IS curve became greater than the threshold T_{IS} , i.e. at $t_a = 6.4$ days. This date t_a will be called a first date hereafter.

15 Once the tracking module TM (and more precisely its sub module TSM) has considered that an interest of a user U_j is really important, it stores an identifier representative of this interest in correspondence with an identifier of this user U_j and with the first date at which it has been considered as a new real interest into his profile. The sub module TSM may store the above
20 mentioned data into a second storage means $SM2$ which may be part of the tracking module TM as illustrated. This second storage means $SM2$ may be of any type known from the man skilled in the art. So, it may be a database or a repository or else a memory, for instance.

Preferably, the tracking module TM also stores a second date t_d into
25 the second storage means $SM2$, in correspondence with an interest identifier, an user identifier and a first date t_a , when it considers that this user interest is no more a real interest for this user (i.e. when the interest strength IS of this user interest became smaller than the chosen threshold T_{IS}). In the diagram of figure 2, the second date t_d which corresponds to the time when the IS curve
30 became smaller than the threshold T_{IS} , is equal to 20.6 days.

The recommendation module RM (of the device D) is arranged for analyzing the first dates t_a of a user U_j that are stored into the second storing means $SM2$. This analysis is carried out by a sub module RSM of the

recommendation module RM and is intended for determining a time ordered sequence of interests which precede an interest that has just been considered by the tracking module TM as a new real interest for a user U_j .

5 The recommendation module RM may be informed of the appearance of a new real interest of a user U_j by the tracking module TM or by analyzing the content of the second storage means SM2 on request or automatically (for instance periodically).

10 A time ordered sequence of interests of a user U_j is a sequence which comprises a list of interests of this user U_j which are ordered according to the first date t_a that are stored into the second storage means SM2 in correspondence of their respective interest identifiers and user identifiers.

Once the sub module RSM has determined a time ordered sequence of interests for a user U_j , it compares this determined user interest sequence to at least one other sequence of interests of at least one other user $U_{j'}$ ($j' \neq j$)
15 to predict at least one potential future interest for this user U_j , in order this potential future interest could be introduced into the profile of this user U_j or at least proposed to this user U_j .

So, contrary to known methods, the invention does not recommend items, but it recommends future (or potential) interests for a user U_j , based on
20 sequence(s) of past interests of this user U_j , and on sequences of other interests of other user(s).

The invention exploits temporal dependencies between user interests, which are currently ignored in existing approaches of recommender systems, and which may be deduced from the sequence of interests of other users $U_{j'}$ if
25 one assumes that some users have similar evolution of their tastes and interests over time. For instance, a user U_j , that starts to be interested in jazz music, may be rapidly interested in a music genre related to jazz music, and/or on specific artist(s) playing notably jazz music, and/or on a sub-genre of jazz music, such as jazz manouche, and/or in concerts related to that
30 emerging interest. In an other example, an interest of a user U_j for a particular natural disaster may trigger interests in social aspects and/or economy. In still an other example, an interest of a user U_j for fashion may trigger a more general interest for online shopping.

The recommendation module RM (and more precisely its sub module RSM) may be arranged for comparing a user interest sequence, that it has just determined into the data relating to this user U_j and stored into the second storage means SM2, to at least one other sequence of interests (preferably the longest one), which can be determined into a graph of interests that has been built from the interests of other users U_j' , in order to predict at least one potential future interest of this user U_j .

Such a graph of interests can be built and updated by the recommendation module RM (and more precisely by its sub module RSM) from the data which define the real interests of the users U_j and which are stored into the second storage means SM2.

The sub module RSM may store the interest graph into a third storage means SM3, which may be part of the recommendation module RM as illustrated. This third storage means SM3 may be of any type known from the man skilled in the art. So, it may be a repository or else a memory, for instance.

For instance, the graph of interests may model the evolution of interests over time for a plurality of users U_j . It can be built and updated either directly from the stored data or by means of an aggregation of interest graphs. The last case is more particularly adapted to a situation in which devices D are distributed in the user communication equipments CE. In this case the recommendation module RM (and more precisely its sub module RSM), which belongs to the device D associated to a user U_j , may be arranged for building and updating an auxiliary interest graph, which models the evolution of interests over time for this user U_j , and then for aggregating this auxiliary interest graph with auxiliary interest graphs, built for other users U_j' (by their respective associated devices D), in order to produce an interest graph.

The interest graph may be a directed and weighted graph $G(V, W)$, where V is a set of nodes which represent respectively the user interests, and W is a set of directed edges, which each represent a transition from a user interest i_{n-1} to another user interest i_n .

A non limiting example of such a directed and weighted interest graph $G(V, W)$ is illustrated in figure 3. Six nodes A, B, C, D, E and F, corresponding

respectively to six user interests, constitute this graph $G(V, W)$ with a set of eight directed edges W in this example. More precisely there is a directed edge W_{AB} between nodes A and B, a directed edge W_{BC} between nodes B and C, a directed edge W_{BD} between nodes B and D, a directed edge W_{CF} between nodes C and F, a directed edge W_{DE} between nodes D and E, a directed edge W_{DF} between nodes D and F, and a directed edge W_{EF} between nodes E and F.

A weight is assigned to each directed edge W , for instance by the recommendation module RM (and more precisely by its sub module RSM). As illustrated in the non limiting example, each weight may be defined by a table $T(W_{AB})$ (or $T(W_{BC})$ or ... or else $T(W_{EF})$). For instance the illustrated table $T(W_{AB})$, which is associated to the directed edge W_{AB} , establishes a correspondence between each user U_j ($j = 1$ to n , for instance $n = 3$) and an elapsed time Δt_{ABj} between the appearances of the two consecutive real interests that are associated respectively to nodes A and B.

For instance, one assumes that the last known real interests that appeared for a user U_j are those represented by nodes B, D and C in the graph of figure 2. Nodes B, D and C constitutes the ordered interest sequence of user U_j . In this illustrated example of graph, node C is connected to nodes B and F, and node D is connected to node B, E and F, but node D is not connected to node C. So one possible transition is from node C to node F. However, given that this transition (C-F) relies only on the last known interest of user U_j , this transition may be a bit weak and of relative low confidence, because in the graph, neither E nor D is connected to C. So, if one ignores node C and considers the previous interest of user U_j (represented by node D), one can see that node D has node B for predecessor in the graph, which represents also a predecessor of the user interest (represented by node D). Therefore one can consider the interests, which are respectively represented by nodes E and F, as potential future interests for user U_j .

If there exists several potential future interests for user U_j (as in the above example), the recommendation module RM (and more precisely its sub module RSM) may compute one or more statistical metrics from the weights of the directed edges W , and then use each determined statistical metric to

choose the most appropriate potential future interest.

For instance the sub module RSM may compute a statistical metric such as the standard deviation to estimate the relevance of a transition between two nodes of a graph (and therefore the two corresponding interests). For instance, if the dispersion of values is very high, the transition
5 may be exploitable enough.

The sub module RSM may also compute a statistical metric such as the relative number of entries in the table (or weight) of a directed edge W to estimate the frequency of a transition between two interests, which may
10 indicate if this transition is main stream or if it is something more particular.

Based on these statistical metrics, it is possible to build heuristics that will help suggesting appropriate interests adapted to a chosen applicative context and then predicting at least one potential future interest for a user U_j from these suggested interests. For example, depending on the application
15 context, it may be more interesting to emphasize non-main stream evolutions of user interests because it could lead to "long-tail" content.

An heuristic may consist in looking into the interest graph for the longest sequence of interests $i_k, i_{k+1}, \dots, i_n$ extracted from the known sequence of interests of the considered user U_j . It is also possible to relax the search by
20 considering incomplete sequences, especially in the case where the determined relevance metric between two possible interests is low or if the frequency of the transition between two possible interests is low, which means that this is a marginal transition. So, one can select the next node i_{n+1} in the interest graph for which the frequency of transition between i_n and i_{n+1} is the
25 highest (this heuristic favors a main stream interest evolution).

The recommendation module RM (and more precisely its sub module RSM) may be also arranged for determining a favourable date for introducing a potential future interest into the profile of a user U_j . For this purpose, it may, for instance, use the weight(s) of the directed edge W between the last
30 interest of this user U_j and the predicted one(s). For instance, it may compute the average value ($\text{average}(\Delta t_{AB})$) of the table associated to the selected directed edge W and then wait until a timer, scheduled with this average value, expires before recommending the new corresponding interest to the

user U_j or before recommending this new corresponding interest in order it could be introduced into the profile of this user U_j .

To predict a future interest of a given user U_j , the recommendation module RM may implement an algorithm such as the one described hereafter
5 with reference to figure 4.

This algorithm begins with a step 10 when a new real interest i_n has been detected for a user U_j by the tracking module TM.

Then in a step 20 one (RM) carries out a first test to determine if this new real interest i_n is already present as a node in the interest graph. If this is
10 not the case, one (RM) adds a new node (representing the new real interest i_n) to the interest graph, in a step 30.

Then in a step 40 one (RM) creates a link (or directed edge W) between the two nodes representing interests i_{n-1} and i_n in the interest graph.

Then one (RM) computes a weight for the link (or directed edge W)
15 between the two nodes representing interests i_{n-1} and i_n in the interest graph, in a step 60.

Now, if the first test carried out in step 20 indicates that the new real interest i_n is already present as a node in the interest graph, one (RM) carries out a second test in step 50 to determine if a link (or directed edge W)
20 between the two nodes representing interests i_{n-1} and i_n exists in the interest graph. If this is not the case, one (RM) carries out step 40 (to create a new link) and then step 60 (to compute a weight for this new link).

If the second test indicates that the link (or directed edge W) between the two nodes representing interests i_{n-1} and i_n exists already in the interest
25 graph, one (RM) carries out step 60 to update the weight of this link. This would enable to recommend to the user U_j a content in relationship to that interest, without waiting for a long time until this user U_j would have consumed enough content related to that interest. So, thanks to the invention, the user may have access faster to content he may be interested in, even before he
30 has demonstrated a proven interest for this type of content.

The invention can provide significant advantages to content-based filtering algorithms (because it avoids over specialisation) without having the same issue(s) as the one(s) presented by collaborative filtering methods (such

as cold-start). Moreover the invention does not need user ratings.

The invention is not limited to the embodiments of device, network equipment and communication equipment described above, only as examples, but it encompasses all alternative embodiments which may be
5 considered by one skilled in the art within the scope of the claims hereafter.

CLAIMS

1. Device (D) for determining potential interest(s) of user(s) (Uj) that is/are client(s) of at least one network operator, each user (Uj) being
5 associated to a profile defining at least his interests, characterized in that it comprises i) a tracking means (TM) arranged for analyzing the profile of at least one user (Uj) to determine new real interest(s) it contains and for storing an identifier representative of a determined new real interest of said user (Uj) in correspondence with a first date at which it has been considered as a new
10 real interest into his profile, and ii) a recommendation means (RM) arranged for analyzing the first dates of a user (Uj) to determine a time ordered sequence of interests preceding a determined new real interest and for comparing this determined user interest sequence to at least one other sequence of interests of at least one other user (Uj') to predict at least one
15 potential future interest for said user (Uj), to be introduced into his profile.

2. Device according to claim 1, characterized in that said recommendation means (RM) is arranged for comparing said determined user interest sequence to at least one other sequence of interests, determined into a graph of interests built from the interests of other users (Uj'), to predict at
20 least one potential future interest of said user (Uj).

3. Device according to claim 2, characterized in that said recommendation means (RM) is arranged for building and updating said interest graph from the stored real interests of said users (Uj).

4. Device according to one of claims 1 to 3, characterized in that said
25 recommendation means (RM) is arranged for building and updating an interest graph which models the evolution of interests over time for a plurality of users (Uj).

5. Device according to one of claims 1 to 3, characterized in that said recommendation means (RM) is arranged for building and updating an
30 auxiliary interest graph, which models the evolution of interests over time for one user (Uj), then for aggregating said auxiliary interest graph with auxiliary interest graphs, built for other users (Uj'), to produce an interest graph.

6. Device according to one of claims 4 and 5, characterized in that said

recommendation means (RM) is arranged for building and updating a directed and weighted interest graph $G(V, W)$, where V is a set of nodes representing respectively said user interests, and W is a set of directed edges representing a transition from a user interest to another user interest.

5 7. Device according to claim 6, characterized in that said recommendation means (RM) is arranged for assigning a weight to each of said directed edges, each weight being defined by a table establishing a correspondence between each user and an elapsed time between the appearances of first and second consecutive real interests.

10 8. Device according to one of claims 4 to 7, characterized in that said recommendation means (RM) is arranged for updating said interest graph each time said tracking means (TM) informs it that it has determined a new real interest of a user (U_j).

15 9. Device according to one of claims 6 to 8, characterized in that said recommendation means (RM) is arranged for determining at least one statistical metric from said weights assigned to said directed edges and for using each determined statistical metric with heuristics to suggest interests adapted to a chosen applicative context and then to predict at least one potential future interest for said user (U_j) from said suggested interests.

20 10. Device according to claim 9, characterized in that at least one statistical metric is representative of the relevance between two interests.

 11. Device according to one of claims 9 and 10, characterized in that at least one statistical metric is representative of the frequency of a transition between two interests.

25 12. Device according to one of claims 1 to 11, characterized in that said tracking means (TM) is arranged for determining the consumption of content items of said user (U_j) that are related to an interest contained into his profile and for considering that this interest is a new real interest when said determined consumption of the related content items is greater than a chosen
30 threshold.

 13. Device according to claim 12, characterized in that said tracking means (TM) is arranged for considering that the first date of an interest is the date at which it detects that a content item consumption related to said

interest is greater than said chosen threshold.

14. Device according to one of claims 1 to 13, characterized in that said recommendation means (RM) is arranged for determining a favourable date for introducing said potential future interest into the profile of said user (Uj).

5 15. Network equipment (SS) for at least one communication network (CN), characterized in that it comprises a device (D) according to one of claims 1 to 14, intended for working in a centralized manner to predict potential future interests for a plurality of users.

10 16. Communication equipment (CE) for a user (Uj), intended for being connected to at least one communication network (CN), characterized in that it comprises a device (D) according to one of claims 1 to 14, intended for predicting potential future interests for said user (Uj).




FIG.1




FIG.2




FIG.3




FIG.4

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2010/064101

A. CLASSIFICATION OF SUBJECT MATTER

INV. G06Q30/00

ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G06Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2008/114756 A1 (KONIG YOCHAI [US] ET AL) 15 May 2008 (2008-05-15) page 4, paragraph 56 – page 5, paragraph 64 figure 1	1-16
X	US 2002/173971 A1 (STIRPE PAUL ALAN [US] ET AL) 21 November 2002 (2002-11-21) page 7, paragraph 88 – page 7, paragraph 92 figure 7	1-16
X	US 2009/248494 A1 (HUETER GEOFFREY J [US] ET AL) 1 October 2009 (2009-10-01) page 6, paragraph 68 – page 6, paragraph 70 figure 7	1-16



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

14 December 2010

Date of mailing of the international search report

27/12/2010

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Rachkov, Vassil

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2010/064101

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2008114756 A1	15-05-2008	US 2010122178 A1	13-05-2010
US 2002173971 A1	21-11-2002	NONE	
US 2009248494 A1	01-10-2009	US 2009248599 A1	01-10-2009
		US 2009248495 A1	01-10-2009
		US 2009248523 A1	01-10-2009
		US 2009248682 A1	01-10-2009
		US 2009248496 A1	01-10-2009
		US 2009248497 A1	01-10-2009