



(86) Date de dépôt PCT/PCT Filing Date: 2015/01/23  
(87) Date publication PCT/PCT Publication Date: 2015/08/06  
(85) Entrée phase nationale/National Entry: 2016/06/29  
(86) N° demande PCT/PCT Application No.: EP 2015/051320  
(87) N° publication PCT/PCT Publication No.: 2015/113901  
(30) Priorité/Priority: 2014/01/28 (NO20140094)

(51) Cl.Int./Int.Cl. *E21B 19/22* (2006.01)  
(71) Demandeur/Applicant:  
STIMLINE AS, NO  
(72) Inventeur/Inventor:  
BJORNENAK, MADS, NO  
(74) Agent: PERLEY-ROBERTSON, HILL & MCDOUGALL  
LLP

(54) Titre : APPAREIL TRANSPORTEUR  
(54) Title: COVEYOR APPARATUS




FIG. 5

(57) **Abrégé/Abstract:**

A conveyor apparatus (2), so-called injector head, to enable feeding of e.g. continuous tubing (7) or coiled tubing through the conveyor apparatus (2) to or from a wellhead and a well below and related to use of well tools. There is provided an apparatus frame (21) within an apparatus cage (5), and a pair of oppositely located, cooperatively movable, segmented continuous belts (28; 29) installed in the frame, each belt (28; 29) comprising a plurality of interconnected gripper shoe carriers (30) carried and movable by means of a pair of continuous belt drive chains (31; 32), and a gripper shoe (38; 52) cooperative with each carrier (30) to positively engage the tubing. The frame (21) at its lower end (21') is tiltably connected to the cage (5) so as to cause said cage (5) and frame (21) to be mutually tiltable in a tilting plane about a single tilting axis (58) which passes through a stuffing box (22') located at a lower region of the cage (5). The frame (21) has at a top region thereof a pair of rollers (24') between which the tubing (7) passes, a force imposed on one or the other of the rollers (24') causing tilting of the frame (21) relative to the cage (5).



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau

(10) International Publication Number

**WO 2015/113901 A3**(43) International Publication Date  
6 August 2015 (06.08.2015)

(51) International Patent Classification:

*E21B 19/22* (2006.01)

(21) International Application Number:

PCT/EP2015/051320

(22) International Filing Date:

23 January 2015 (23.01.2015)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

20140094 28 January 2014 (28.01.2014) NO

(71) Applicant: **STIMLINE AS** [NO/NO]; Andøyfaret 31, N-4623 Kristiansand (NO).(72) Inventor: **BJØRNENAK, Mads**; Tjuvhellereen 48E, N-4628 Kristiansand (NO).(74) Agent: **PROTECTOR IP CONSULTANTS AS**; Oscarsgate 20, N-0352 Oslo (NO).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- of inventorship (Rule 4.17(iv))

[Continued on next page]

(54) Title: COVEYOR APPARATUS




FIG. 4a




FIG. 5

(57) **Abstract:** A conveyor apparatus (2), so-called injector head, to enable feeding of e.g. continuous tubing (7) or coiled tubing through the conveyor apparatus (2) to or from a wellhead and a well below and related to use of well tools. There is provided an apparatus frame (21) within an apparatus cage (5), and a pair of oppositely located, cooperatively movable, segmented continuous belts (28; 29) installed in the frame, each belt (28; 29) comprising a plurality of interconnected gripper shoe carriers (30) carried and movable by means of a pair of continuous belt drive chains (31; 32), and a gripper shoe (38; 52) cooperative with each carrier (30) to positively engage the tubing. The frame (21) at its lower end (21') is tiltable connected to the cage (5) so as to cause said cage (5) and frame (21) to be mutually tiltable in a tilting plane about a single tilting axis (58) which passes through a stuffing box (22') located at a lower region of the cage (5). The frame (21) has at a top region thereof a pair of rollers (24') between which the tubing (7) passes, a force imposed on one or the other of the rollers (24') causing tilting of the frame (21) relative to the cage (5).

# WO 2015/113901 A3



---

**Published:**

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

**(88) Date of publication of the international search report:**  
24 September 2015

## CONVEYOR APPARATUS

### FIELD OF THE INVENTION

5 The present invention relates to a conveyor apparatus, to enable feeding of continuous elongate device (CED), such as e.g. coiled tubing, rod, wire or wireline down through the conveyor apparatus, to enable insertion of tools through the wellhead and into a well below, or up through the conveyor apparatus by pulling action enabling retrieval of such tools from the wellhead  
10 and the well below.

Such a conveyor apparatus is frequently called an "injector head" in this particular field of use.

15 The wellhead is primarily meant for oil and natural gas exploration and production operations.

Particularly, the present invention relates to a technology for inserting and retrieval of a drill tool being supported by continuous elongate device (CED), in  
20 a non-limiting example being e.g. a continuous tubing, suitably coiled tubing running through the lubricator string sections.

In the description and claims, the general term CED, i.e. Continuous Elongate Device, will be used, implying that the CED may be interpreted as being a  
25 continuous tubing (e.g. coiled tubing), continuous rod or interconnected rod sections, continuous wire or continuous wireline. In case of rods or rod sections, they could e.g. be massive rods of metal, metal alloys, carbon material, fiber reinforced plastic material.

30 However, in the discussion of the prior art and in the detailed description it will mostly be referred to the use of continuous tubing as a practical example of CED.

More particularly, the present invention relates to a conveyor apparatus

2

according to the preamble of claim 1.

## TECHNICAL BACKGROUND OF THE INVENTION

5 Use of CED's, such as e.g. coiled tubing, sourced from a hydraulically operated reel is known in oil and natural gas exploration and production operations. These tubings, generally refer to metal pipes, e.g. made from steel, with diameter ranging between 1 inch and 4 inches (2.54 - 10.12 centimeters), or suitably within the range 1.5 to 3.5 inches (3.81 - 8.89 centimeters). Such tubing may typically  
10 have a wall thickness of 5 -15% of the tubing diameter, although a different wall thickness range may applied dependent on the use of the tubing. It is also known, that coiled tubing can perform many different oil well operations, and these include use in interventions in oil and gas wells, and use as production tubing in gas wells as well.

15

Application of such coiled tubing in oil and gas operations involves deploying the tubing as support for drill tools for inserting those tools into boreholes or for retrieving those tools from boreholes. Such tools can be packers, valves, sleeves, sensors, plugs, gauges and so on, which have to be run into and retrieved from  
20 the boreholes. These tools may find use for servicing the well.

The operations as stated in the preceding paragraph are done through lubricator string sections and those sections serve as a sluice for undertaking such operations.

25

How a lubricator string functions for insertion of tools into the well and for retrieval of the same therefrom, are all common knowledge in the art and will not be elaborated on any further.

30 How to handle a tubular piping system is e.g. described in Norwegian Patent Application Nr. 20131601, filed on 03. December 2013 and entitled PIPE HANDLER, the disclosure of which is hereby incorporated by this text reference.

In the above context, telescopic injector masts are also known which extend from a base up to a substantial height and supports a coiled tubing conveyor apparatus at its top end and a lubricator string suspended from the coiled tubing conveyor apparatus. Upon insertion into the wellhead, prior thereto coiled tubing is stabbed  
5 through the coiled tubing conveyor apparatus, and thereafter conveyed through the lubricator string, which is located just above the borehole. The purpose is to insert tools into the borehole as stated before. The pulling operation of coiled tubing takes place in just the opposite direction of retrieving the tools from the borehole.

10

As stated before, injector masts for ensuring lifting of tubing conveyor apparatus (injector heads) to undertake the operation as stated in the preceding paragraph are already known. For example, US patent 7,077,209 teaches a telescopic mast having two arms, which can telescopically rise for supporting a tubing gripper  
15 conveyor apparatus at a height and positioning it above the wellhead. The mast is pivotally mounted to a vehicle.

The above document and likewise prior art known in the art does not have any teachings for rapid, accurate and safe assembling of lubricator strings below the  
20 injector head and aligning these above the well head, thereby ensuring smooth passage of the coiled tubing.

Furthermore, no teachings exist in prior art on how to precisely receive the coiled tubing from any direction and to pass it through the coiled tubing conveyor head,  
25 and simultaneously ensuring that the coiled tubing conveyor head is appropriately positioned above the well head.

A technology to meet the need of providing said teachings, which are lacking in prior art, and other associated needs, is described in Norwegian Patent  
30 Application Nr. 20131640 filed on 10.12.2013 and entitled HANDLING SYSTEM, the disclosure of which is hereby incorporated by this text reference, the handling system described therein being equipped with a telescopic mast, mounting a tubing conveyor apparatus (or an injector head) at its top end, which mast can

swivel about a vertical axis for correct injection or pulling out of the continuous tube from any direction, through the tubing conveyor apparatus and through lubricator strings. The mast also has a handling device for efficiently and rapidly assembling and disassembling lubricator strings on and from the top of the wellhead and for proper positioning and alignment of the strings beneath the tube conveyor head.

In the context of the prior art described above it has been recognized that gripping elements of the tubing conveyor apparatus should be related to a movable carrier and a gripper shoe which is removably attached to such carrier.

The disclosure of US patent US 6,173,769-B1 describes a coiled tubing conveyor apparatus exhibiting inter alia a pair of continuous, segmented drive belts, each belt with a plurality of carriers carried by a pair of drive chains, each carrier having front and back sides, and means for removably attaching a tubing gripper shoe to a front side of the carrier, an elastomeric pad with high spring rate being sandwiched between a gripper shoe base and the carrier to allow the gripper shoe to resiliently "float" on the carrier. The purpose of the elastomeric pad is to allow the gripper shoe to automatically make small adjustments in its alignment with coiled tubing as it engages the tubing, thus providing a more even distribution of gripping forces across the shoe. The elastomeric pad also accommodates manufacturing tolerances that result in slight variations in the distances between an elongate counter-force member, typically known as a "skate" in the art, on which rollers on the carriers ride, and the centerline of the tubing to be gripped. Preferably, only gripper shoes are used that have fixed shapes conforming to a normal shape of the tube or pipe, and that surround substantially half of the circumference of the tubing. As an outset, fixed shaped shoes cause the tubing to retain its normal shape when conveyed through the conveyor head and enhance the gripping ability, provided that e.g. the tubing diameter has not changed substantially.

EP 0507280 shows an injector having a load cell. The injector head is attached to the load cell on one side and a hinge on the other side. Consequently, the

5

injector head will tilt slightly about the hinge and inflict a force on the load cell. The tilting movement required to sense the load is very small. There is no indication that the hinge is adapted to allow for any significant degree of tilting beyond what is required to trigger the load cell.

5

If the hinge had allowed for larger tilting, such as beyond 1°, this would result in a sever pull and push force inflicted on the coiled tubing over the short stretch between the lowermost gripper and the lubricator. This is not desirable.

10 US 2006/081368 shows an injector where each half of the injector head is hingedly attached to a frame. Thereby the halves can be swung outward from one another so that the coiled tubing can be thread through the injector head with ease. If the halves are allowed to tilt about these hinges when the injector is operating, the grippers will be forced to glide relative to the coiled tubing, which  
15 in turn results in great wear of the coiled tubing.

US 6209634 shows an injector similar to US 2006/081368, having the same features.

## 20 **OBJECTS OF THE INVENTION**

According to an aspect of the present invention it has been observed that the counter-force members, due to strong forces acting thereon have a tendency to become "wavy" along their length, which has an adverse effect on the tubing to  
25 be gripped and conveyed through the conveyor apparatus, because the gripping forces from the gripper shoes become uneven through the apparatus, which could trigger related wavy configuration of the tubing in its longitudinal direction. The reason is that the forces, which act on the counter-force members caused by inter-space setting means substantially, only act transversely of an elongate  
30 part of the counter-force member. This will introduce along its length locations with high stresses and other locations having lower stresses causes by bending or depressions the member. There are currently no solutions to overcome this operational drawback.

It is the principal object of the present invention to provide a CED conveyor apparatus to enable a continuous elongate device to be injected into or pulled out from a borehole wellhead via an array of lubricator strings aligned below the apparatus (injector head) and above the wellhead for passage of the continuous elongate device therethrough, and in addition ensuring that the conveyor head is appropriately positioned above the well head.

More specifically, the invention is in general intended to provide remedies in order to substantially overcome the mentioned challenges which are well known from the current prior art.

## SUMMARY OF THE INVENTION

The conveyor apparatus mentioned in the introduction further comprises:  
an apparatus frame,  
a pair of oppositely located, co-operatively movable, segmented continuous belts installed in the frame, each belt comprising a plurality of interconnected device gripper shoe carriers carried and movable by means of a pair of continuous belt drive chains running over respective pairs of chain drive sprockets,  
wherein a rear side of the carrier has at least one roller configured to roll about a shaft attached to the carrier against an elongate counter-force member, a so-called skate, associated with the frame and extending between said drive sprockets,  
wherein a device gripper shoe is co-operative with each carrier to positively engage the continuous elongate device, and  
wherein a pair of said counter-force members being adapted to interact with a respective belt.

30

According to the invention, the conveyor apparatus is characterized in that the counter-force member has a) a elongate part, and b) along the length of the elongate part a plurality of pairs of substantially V shaped elements, the

7

elements of each pair extending with their V-legs laterally from oppositely located side edges of the elongate part towards an apex of the V - shaped element, that an axis of one leg of a V - element of one pair of elements, at one side edge of the elongate part, is aligned with a leg of a V - element of another and adjacent pair of elements, at the other side edge of the elongate part, and that the V- elements are integral with the elongate part and co-planar therewith.

According to an embodiment of the conveyor apparatus, the elongate part and each of said elements have substantially the same thickness.

10

According to a further embodiment of the conveyor apparatus, at least one pair of the V-shaped elements have legs, which are wider than the legs of other pairs of V-shaped elements. Suitably, said at least one pair of V - shaped elements is located at longitudinal mid-region side of the elongate part.

15

In an alternative embodiment of the conveyor apparatus, at least two pairs of the V-shaped elements have legs, which are wider than the legs of other pairs of V-shaped elements. Suitably, one pair of the at least two pairs of V-shaped elements is located upstream of longitudinal mid-region sides of the elongate part, and another pair of the at least two pairs of V-shaped elements is located downstream of longitudinal mid-region sides of the elongate part.

According to an additional embodiment of the conveyor apparatus, means are provided to adjust mutual spacing of the pair of counter-force members interact with the V- apexes of said elements.

According to a another embodiment of the conveyor apparatus, the plurality of pairs of substantially V shaped elements can be considered as substantially triangular slabs protruding laterally and integrally from either longitudinal side of the elongate part of the counter-force member, a hole being present in the slab adjacent the elongate part. Suitably, the shape of the hole is substantially triangular, circular or oval.

30

**BRIEF DESCRIPTION OF THE DRAWINGS**

Having described the main features of the invention above, a more detailed and non-limiting description of non-limiting embodiments of the conveyor apparatus according to the invention and aspects thereof is given below, with reference to the attached drawings.

Fig. **1** is an overview of a handling system in which a preferred embodiment of the conveyor apparatus of the present invention is used.

Fig. **2** is side view from one side of the apparatus, according to the invention with an associated tubing guide arch.

Fig. **3** is the side view of Fig. **2** with mutual position of apparatus frame and apparatus cage slightly changed.

Fig. **4a** is a perspective view from above and said one side of the apparatus and with the associated tubing guide arch, and Fig. **4b** is a perspective view from above and the other side of the apparatus and with the associated tubing guide arch and add-on protective cages.

Fig. **5** is a vertical cross-section through the view of Fig. **2**.

Fig. **6a** is an enlarged view of the apparatus from the other side, and Fig. **6b** is detailed top region, perspective view from above of the apparatus frame and its operational elements thereof, seen from said other side.

Fig. **7** is an enlarged view of the apparatus from said other side without the apparatus cage.

Fig. **8** is an enlarged view of the apparatus from said other side without the apparatus cage and frame shown.

Fig. **9** is a simplified vertical cross-section through the view of Fig. **8**.

Fig. **10a** is a perspective front view from one end of a conventional tubing gripper shoe installed on a novel gripper shoe carrier, according to the invention, Fig.

5 **10b** is a perspective front view from another end of the conventional tubing gripper shoe installed on the novel gripper shoe carrier, and Fig. **10ca** is a perspective front view from the another end of the novel gripper shoe carrier with the gripper shoe not present.

10 Fig. **11** is an end view of the view of Fig. **10**.

Fig. **12a** is a vertical cross-section through the perspective view of Fig. **10**.

15 Figs. **12b - 12k** illustrate variants of resilient members to provide resiliency of a gripper shoe and its carrier, and Fig. **12l** is symbolic of other resilient members.

Fig. **13** is a perspective view of a plurality of gripper shoes and their novel shoe carriers interconnected by means of pairs of drive chains.

20 Fig. **14** is an end view of a tubing gripper shoe, according to the invention.

Fig. **15** is a perspective front view and from one end of the gripper shoe, according to the invention.

25 Fig. **16** is a perspective view from above of a co-operating pair of the gripper shoe gripping a section of a continuous tubing.

Fig. **17** is a view from above of a pair of the gripper shoes in engagement with a previously not used continuous tubing.

30

Fig. **18** is a view from above of a pair of the gripper shoes in engagement with a previously used continuous tubing having a maximum ovality in the x-direction.

10

Fig. **19** is a view from above of a pair of the gripper shoes in engagement with a previously used continuous tubing having a maximum ovality in the y-direction.

5 Fig. **20** is a view from above of a pair of the gripper shoes in engagement with a previously used continuous tubing having a maximum diameter in the x and y directions due to so-called ballooning.

10 Fig. **21** is a perspective view of the conveyor apparatus shown without apparatus frame and cage, and with a pair of counter-force members, according to the invention.

Fig. **22** is a perspective view of the counter-force member.

15 Fig. **23** is a perspective view of a pair of counter-force members in interaction with means to adjust mutual space between the members.

Fig. **24** is a plan view of the counter-force member.

20 Fig. **25** is a perspective view of a slightly modified counter-force member.

Fig. **26** is a plan view of the counter-force member of Fig. **25**.

## 25 DETAILED DESCRIPTION OF THE INVENTION

The following describes preferred embodiments of the conveyor apparatus of the present invention and which is exemplary for the sake of understanding the invention and non-limiting.

30 In the present context, the term "injector head" is to be construed as being synonymous with the term conveyor apparatus as defined in the claims.

Further, the term "counter-force member" is synonymous with the term "skate"

frequently used in the art.

All throughout the specification including the claims, the words "CED", continuous elongate device", "handling system", "handling device", "continuous  
5 tubing", "coiled tubing", "borehole ", "wellhead", "lubricator strings", "bearing", "BOP", "injector head", "injector mast", "tool strings/ sections" are to be interpreted in the broadest sense of the respective terms and includes all similar items in the field, known by other terms, as may be clear to persons skilled in the art.

10

Restriction/ limitation, if any, referred to in the specification, is solely by way of example and understanding the present invention. More specifically, hereinafter, the term "coiled tubing" has been referred to for the sake of convenient understanding of the invention. It should be understood that "coiled tubing" also  
15 includes other similar continuous tubing as may be known to persons skilled in the art of the present invention. Further, it will be appreciated by the expert in the art that the invention is also applicable to other continuous elongate devices (CED's), such as rods, wires or wirelines.

20 Although the conveyor apparatus is, in a currently preferred mode of operation, primarily to be used for operation with coiled tubing, the use of the conveyor apparatus in conjunction with other CED's lies within the scope of the invention.

It should also be understood that the orientation of some the apparatus  
25 components may exhibit configurations other than those shown in the drawings, without deviating from the principle of the invention, and such different configurations which to not affect the overall operation of the apparatus are to be construed as merely technical equivalents within the scope of the present invention.

30

Figure 1 is a view of the basic layout of a handling system 1 in which the conveyor apparatus 2 or injector head 2 of the present invention is present. The handling system 1 comprises an injector carrying mast 3, which is telescopic. The injector

12

mast **3** and a tubing guide arch **4** are operatively linked to a supporting cage **5** of the apparatus **2** (the cage **5** is also shown on Figs. **2 - 6a**) at a top region of the mast **3**. This support cage **5** can be moved, e.g. rotated, to ensure alignment of the injector head **2** above a wellhead **6** and also for ensuring smooth feeding of coiled tubing **7** through a lubricator string **8**. Movement of the cage **5** can be assisted by hydraulic, pneumatic or electrical drive means.

Apart from being telescopically adjustable, the mast **3** can also be caused to swivel. The mast **3** is supported from below on a mast truck **9**. The truck **9**, at its rear end has a carrier **10** for parking a BOP (Blowout Preventer) unit **11**, when this unit is not in use. The rear portion of the injector mast truck **9** also has a rigging winch **12** and a sheave (not shown) for stabbing/ pulling coiled tubing **7** through the conveyor apparatus/ injector head **2** when it is "empty", i.e. not yet fully engaging the tubing **7** over a full conveying length of the apparatus **2**. The guide arch **4** facilitates this stabbing/ pulling operation of coiled tubing **7** through the injector head **2**, an operation where the aid from the winch **12** is highly required in view of a substantial drag force action on the tubing in the opposite direction of the pulling/ stabbing.

It should be also clear from Fig.1 that a rear face of the mast **3** is adjacent the injector head **2**. This rear face is suitably equipped with a handling device **13** for the lubricator strings **8**. The handling device **13** allows accurate, rapid and safe assembly and disassembly of the lubricator string sections **8'** on and from the top of the wellhead **6**.

25

Fig. **1** also shows a hydraulic power unit **14** located along the chassis of the truck **9**. The operations are mostly hydraulically powered and this unit supplies hydraulic pressurized fluid to numerous hydraulic motors (not shown on Fig. **1**) used in the handling system. In addition, Fig. **1** shows a reel truck **15** and the reel trailer **16** which are well known to persons skilled in the art. The coiled tubing **7** is supplied from a reel **17** located on the trailer **16**. The release from or winding of tubing onto the reel **17** is assisted and facilitated by a tubing tensioner **18** which

30

13

is hydraulically powered by an hydraulic unit **19** at the rear portion of the reel trailer **16**. The central portion of the reel truck 15 has a control room **20**.

5 The mast **3** and the reel **17** (drop-in type) can also rest on other platforms, such as fixed structures, as known to persons skilled in the art.

10 The mast **3** is of telescoping type or a combination of folding plus telescoping type. The mast has one telescope section for simplicity, however additional sections are possible if required. The mast cross section is suitably of self-centering type.

Expected maximum height from ground to the cage **5** is approximately 20 meters. The mast **3** extends from its base on the truck **9** and lifts the injector head **2** supported by the cage **5**. The injector head **2** includes the carrying cage **5** and 15 the tubing guide arch **4** is mounted onto the top of that cage **5**, and the cage **5** is attached to the top of the mast **3**.

20 The cage **5** can be tilted hydraulically relative to the mast **3** to enable the cage **5** to be positioned vertically as the mast 1 is angled, to thereby align the injector head 2 and its cage **5** with a centre line of the well head **6** and the well below (not shown).

25 The guide arch **4** can be rotated relative to the cage **5** from a first operational position through 180° to a second operational position. However, the cage **5** can be rotated relative to the mast **3** to accept coiled tubing **7** (or CED) from the reel **17** from any desired direction around the mast **3**, depending upon the location of the reel **17**.

30 The various essential aspects of the conveyor apparatus will now be described in more detail with reference to Figs. **2 - 20**.

As described above the conveyor apparatus, a so-called "injector head" **2**, enables injection of continuous tubing, e.g. coiled tubing **7**, down through the

14

conveyor apparatus **2** and then through lubricator strings **8** located between the apparatus **2** and the wellhead **6**, suitably via a BOP (blow-out-preventer) **11** to enable insertion of tools (not shown) into the wellhead **6** and further into a well below (not shown) on the drawings), or up through the conveyor apparatus **2** by  
5 pulling action enabling retrieval of the tool from the wellhead and the well below.

As mentioned above, the conveyor apparatus **2** has an apparatus cage **5**. Further, an apparatus frame **21** is located within the cage **5** as seen on Figs. **2 - 4** and **6**. At a lower end of the cage **5**, there is located a connector **22** to enable  
10 attachment of the cage **5** onto an uppermost end of the lubricator string **8**. The cage **5** is suitably provided with open sides to enable more convenient monitoring of the operation of the entire conveyor apparatus **2**. Stays **5'** are provided to provide sufficient rigidity of the cage **5**.

15 To the extent that structural elements protrude out from the frame **21** and through the circumference of the cage **5**, cage add-on's as shown on Fig. **4b** can be installed, so as to crash-protect such structural elements.

It is noted from viewing Figs. **4** and **5** that the tubing guide arch **4** has a curved  
20 tubing track **23** with a plurality of guide rollers **24** to enable the tubing **7** to follow the track **23**, so as to enter vertically into the conveyor apparatus or injector head **2** in a proper manner, as clearly seen on Fig. **5**. For stow-away purposes, the guide arch **4** can be made foldable into e.g. two parts **4'** and **4''** hinge connected at a hinge connection **25**, and kept in respective positions using a controllable  
25 ram **26**.

It is noted from Figs. **5** and **7** that there are further guide rollers **24'** between which the tubing **7** passes. If pressure is exerted on one or the other of these rollers **24'**, such pressure will cause the frame **21** to tilt relative to the cage **5**,  
30 optionally against the counter-force of spring **59** or **60**.

At the top of the cage **5** there are located a plurality of lifting lugs **27** to enable the cage **5** to be lifted from a crane. The cage **5** is conventionally attached to the

15

mast **3** at a bottom region of the cage.

The conveyor apparatus **2** has a pair of upright, oppositely located, co-operatively movable, segmented, continuous belts **28; 29** installed in the frame **21**. Each belt **28; 29** comprises a plurality of interconnected tubing gripper shoe carriers **30** and a pair continuous belt drive chains **31; 32** (see Figs. **8 - 13**) running over respective pairs of chain drive sprockets **33; 34**.

As shown on Figs. **10 - 12** each carrier **30** has a front side **30'** and a rear side **30''**.

The rear side **30''** of the carrier **30** has roller means **35** configured roll about a shaft **36** attached to the carrier **30** against an elongate counter-force member **37** associated with the frame **21** and extending between said drive sprockets **33; 34**.

The provision of the member **37** is to make sure that a gripping shoe **38** attached to the carrier **30** sufficiently engages the tubing **7** when it is forcibly driven through the injector head or apparatus **7**. Suitably, the member **37** is position adjustable transversely of its longitudinal direction, so as to be adaptable to various diameters of tubing **7** and associated gripper shoes **38**. As clearly shown on Figs. **8 and 9** there is a pair of such members **37** to operate with the respective belt **28; 29**.

Suitably, the sprockets **33** have internally a powerful torque creating motor, as symbolically indicated by reference **39**. The motor **39** is suitably a hydraulic motor, but could just as well be an electric or pneumatic motor. It is instead possible to have each motor located externally of the sprockets **33** protruding out through the cage **5**, as more clearly seen from viewing Fig. **4**. In this latter case, an add-on cage, as shown on Fig. **4b** should be provided to protect the motors and their accessories from damage in case of the cage **5** colliding with strange objects.

In order to adjust the transverse position of both counter-force members **37**, i.e. the so-called "skates" and their mutual distance, there is provided a plurality of

16

adjustment means, each such means having: at least one actuator **41**, such as e.g. a hydraulic cylinder or ram, a pair of customized, elongate rods **40**, e.g. racks or rods with threads extending on either transverse side of the belts **28; 29** and powered by the at least one actuator **41** with a sleeve **41'**, the rods **40** co-acting with nuts **42; 43** attached to the respective member **37**, yielding that turning the rod **40** in one direction causes the two members **37** to move apart, and turning the rod **40** in opposite direction causes the members **37** to have their interspace reduced. See Fig. **6** where there is used a total of eight hydraulic actuators in the operational example.

10

In an optional embodiment, the sprockets **33; 34** may be co-operative with the counter-force members **37** by being attached to an upper and lower end thereof, respectively, so as to be movable with the members **37** when interspace adjustment between the upper pair of sprockets **33** and between the lower pair of sprockets **34** is also required to adapt to a change in diameter of tubing to be conveyed and associated replacement of gripper shoes **38** to fit such diameter change.

Co-acting male means **44** and female means **45** of e.g. dove-tail configuration are provided for removably attaching a tubing gripper shoe **38** to each carrier **30** at the front side **30'** thereof. As shown on Fig. **10c**, the means **44** may not necessarily extend over the full face of the top side of the carrier **30** and correspondingly with the means **45** not over the full rear side (not shown) of the gripper shoe **38**, but instead just over a part thereof, so that the shoe **38** can be dropped onto the front face of the carrier **30**, and then just shifted a little in the direction of the means to cause mating engagement. Such co-acting means **44, 45** are well known in the art, as well as a locking spring **46** to interlock the shoe **38** and the carrier **30**, thereby preventing the shoe **38** from sliding along the male means **44** when in operational use with its front side **38'** facing the continuous tubing **7**.

Although a shoe **38** normally is removably attached to the carrier **30**, it is conceivable to have the shoe and carrier as a single unit.

It should be noted that a prior art elastomeric pad between a rear side **38''** of the shoe **38** and a front side **30'** of the carrier **30** is not used. However, in order to provide some interspace means instead of the prior art pad, e.g. the rear side **38'** of the shoe **38** or the front side **30'** of the carrier **30**, transversely of the longitudinal direction of said dovetail shaped attachment means **44** and **45**, could have a limited number of small knobs **47** (see Fig. **11**).

However, in order to retain a limited amount of resilience of the shoe **38** acting upon the tubing **7**, the shaft **36** of the roller means **35** is resiliently supported transversely of its longitudinal axis by means of a plurality of resilient members **48** fitted onto or about the shaft at spaced apart locations in the rear side **30''** of the carrier **30**. Such resilient members may be configured as conventional springs or customized metal springs or be made of resilient material, such as e.g. rubber, elastomeric material, or material having property of resiliency. Any such members will operate within their range of elasticity.

In order to prevent the shaft **36** from turning with the roller means, the shaft **36** is at either end provided with a pair of recesses **36'** spanning over an angle e.g. 60° - 120°, suitably 90 - 110° which engage the legs **36''** of a U-shaped recess on a shaft bracket **36'''** which is attached to the carrier **30** as shown on Figs. **10** and **12**. As shown on Fig. **12**, the roller means **35** have incorporated therein roller bearings **35'**, suitably of a ball bearing type, in order rotate freely on the shaft **35**, as rotation of the shaft **35** in the fitting holes **48'** of the members **48** could cause these holes to become wider and adversely affect the resilience provided by the members **48**.

Upon loading of the shoe **38** and carrier **30**, the shaft **36** will tend to move towards the shoe **38** with its recesses **36'** along the U-shaped legs **36''** and against the resilient force created by the members **48**.

As noted from Fig. **12a**, and Figs. **12b - 12k**, each member **48** may exhibit one or more of selectable configurations, e.g. one of: circular, ring-shaped, oval,

elliptical, almost triangular, oblong with curved ends, and polygonal.

It is noted that on Figs. **12b - 12k** the hole **48'** could be located eccentrically or off-center or in the center of the member **48**.

5

More specifically, Figs. **12b** and **12c** show an annular member **48** with a center-located hole **48'**. This embodiment is suitable in cases where the member is e.g. of heavy-duty elastomeric material. In other cases, it may be required to have more material "height" or amount of material between the hole **48'** and an end of the member **48** closest to the shoe **38** than at the other diametrical side of the hole, in order to let the shoe and carrier combination be more resilient in order to adapt better to structural and dimensional variations of the tubing (or CED) and any wavy configuration of the counter-force member (the skate) or when using a member **48** of a material necessitating such more material to yield required resiliency. Figs. **12d, 12e; 12f, 12g; 12j, 12k** are typical examples in this respect.

The embodiment of Figs. **12d** and **12e** as well as the embodiment of Figs. **12j** and **12k** show an oblong or elliptical member **48** with curved ends and having its hole **48'** off-center or located eccentrically. It is noted on Figs. **12j** and **12k** that there are provided a plurality of slits **48"**, implying that the member **48** could conveniently be made of a suitable metal or HD plastic material, the zig-zag configured slits providing a spring feature.

The embodiment of Figs. **12f** and **12g** is of polygonal, suitably rectangular shape with the hole **48'** located off-center.

The embodiment of Figs. **12h** and **12i** has a kind of triangular or truncated wedge shape with the hole **48'** located slightly off-center. The wider end thereof will upon compression in a wedge shaped recess in the carrier **30** contribute to increased rigidity of the member **48**, while minimizing its body "height" or amount of member material between the hole and the region thereof closest to the shoe.

Fig. **12/** indicates symbolically that in essence, the member **48** could be of any configuration and of any resilient spring configuration, even of a coiled spring or disc spring configuration.

- 5 The shaft **36** is configured to be fitted in the hole **48'** of the resilient member **48**. Further, the members **48** are each fitted into holes or cavities in the rear side **30'** of the carrier **30** adjacent the longitudinal ends of the roller means **35**.

It will be noted that the carrier **30** has two holes **49** extending through the carrier  
 10 transversely of its direction of movement, i.e. transversely of the movement direction of the belts **28; 29**. Rods **50** extend through these holes **49** and constitute pivot and connection pins at each joint of the chains **31; 32**, and are prevented from sliding out of the holes **49** and the respective chain joints **31'; 32'** by using locking wire or a U- clip **51** interacting with a hole or recess at a  
 15 respective end region of the rod **50**, as clearly illustrated on Fig. **13**.

If a conventional type of carrier is used, i.e. with no resilience members **48** associated with the shaft **36** of the roller means **35**, a novel and inventive tubing gripper shoe **52** could be used, as will now be explained with reference to Figs.  
 20 **14 - 20**. However, such shoe could of course be used with the type of carrier just described, i.e. a carrier **30** having a plurality of resilience members **48** associated with the support of the shaft **36** of the roller means **35**.

This novel tubing gripper shoe **52** comprises, according to the invention a gripper shoe base **53** having at a front **53'** thereof longitudinal first and second edge regions **53''**, **53'''**. A first leg **54** and a second leg **55** extend at one end **54'; 55'** thereof from said first and second edge regions **53''; 53'''**, respectively, said legs **54; 55** being inclined towards each other. Further, first and second tubing gripper members **56; 57** are located at the other end **54''; 55''** of said first and second  
 30 legs **54; 55**.

The gripping members **56; 57** as well as the first and second legs **54; 55** extend parallel to movement direction of the belts **28; 29** along a full length of the shoe

**52** and its base **53**. The legs thereby exhibit elasticity or resiliency as regards bending transversely of the belt movement direction, but are rigid as regards shear forces, which appear substantially in the belt movement direction.

- 5 As indicated on Fig. **14** there are spaces **56'**; **57'** between the gripping members **56**; **57** and the shoe base **53**, respectively, said spaces acting as tilt limiters for the gripping members **56**; **57**.

10 The gripper shoe base **53**, said first and second legs **54**; **55** and said first and second tubing gripper members **56**; **57** are integrally made from a metal or metal alloy.

The first and second tubing gripper members **56**; **57** are tiltable sideways upon engagement with the tubing **7** by virtue of resilience properties of the legs **54**; **55**.

15

In a practical, though non-limiting embodiment of the invention, the smallest wall thickness of said legs is in the range 0.3 - 1.5 cm.

20 Further, as a general rule, the radius of curvature of the tubing gripper shoe members **56**; **57** should be adapted to the curvature of a circular circumference of the tubing, i. e. the diameter of the tubing. This diameter could be e.g. the maximum diameter as mentioned in connection with the ballooning phenomenon.

25 The gripper shoe **52** is suitably fitted onto a carrier; either a conventional carrier or the carrier **30** by means of conventional dovetail configured attachment means **44**; **45** and locking means **46** as previously described.

30 As shown on Fig. **17** the pair of gripper shoes **52** adequately engage the tubing **7** with the gripper shoe member **56**; **57**, the tubing **7** being new and therefore substantially circular. However, when a tubing is re-coiled to thereby be subsequently re-used, its cross-section may change into an oval configuration, as shown on Figs. **18** and **19**, or its diameter may increase as shown on Fig. **20**, although the "ballooning" phenomenon shown on Fig. **20** may exhibit a circular

configuration.

On Fig. **18**, the x-diameter is at its maximum. However, due to the resilience properties of the legs **54; 55** and the location of the members **56; 57**, when the shoes **52** impose pressure on the oval tubing **7**, the members **56; 57** will attempt to exert a pressure in the x- direction, thereby attempting to let the tubing **7** regain as far as possible its circular configuration, while providing adequate gripping engagement between the members **56; 57** and the tubing **7**.

On Fig. **19**, the y-diameter is at its maximum. However, due to the resilience properties of the legs **54; 55** and the location of the members **56; 57**, when the shoes **52** impose pressure on the oval tubing **7**, the members **56; 57** will attempt to exert an extra pressure in the y-direction, thereby attempting to let the tubing **7** regain as far as possible its circular configuration, while providing adequate gripping engagement between the members **56; 57** and the tubing **7**.

As will be appreciated, the phenomenon of "ballooning" is not created in the conveyor apparatus. On Fig. **20** it is noted that the gripper shoe members **56; 57** perfectly engage most of the circumference of the ballooned tubing **7**, thereby in the process of exerting gripping pressure onto the tubing simultaneously adapting to ovality or ballooned state of the tubing **7**, thereby preventing the tubing **7** from adversely changing its ovality or ballooned configuration.

As indicated in the introduction, there is an increased risk of causing unwanted bends or dents on the tubing due to varying feed-in or feed-out speeds and/ or force conditions of the tubing to or from the conveyor apparatus. This is in particular challenge in the stabbing operation when the winch **12** is used, but could also happen when during normal conveyor operation there is excessive drag in the opposite direction of the feeding, a drag, which could even, be several tons.

According to the invention, this is solved in that the apparatus frame **21** at a lower end **21'** thereof is tiltably connected to the apparatus cage **5** so as to cause said

22

cage **5** and frame **21** to be mutually tiltable about a single tilting axis **58** being related to a pair of tilting joints **58'**; **58''** as shown on Figs. **2 - 4, 6** and **7**. Further, it is noted that the frame **21** at an upper end **21''** thereof in a tilting plane is linked to two spaced apart upper regions **5''**; **5'''** of the cage **5** via resilient members **59**; **60**. The resilient members **59**; **60** are suitable heavy duty springs, capable of withstanding heavy loading thereon, even in a range of tons. However, in certain cases said resilient members **59**; **60** may not be required due to overall rigidity exhibited by the operationally co-operative structural parts, as well as the continuous elongate device **7**.

10

The cage **5** is suitably rigidly attachable to an uppermost region of the lubricator strings **8** via the previously mentioned connector **22**.

15

The frame **21** is tiltable about the axis **58** relative to the cage **5** in one direction or the other by a tilting angle not greater than **10** degrees. In most cases, a sufficient tilting angle is not greater than **3.0** degrees. In yet another, currently preferred mode, the tilting angle is not greater than **1.5** degrees. Associated with the connector **22** there is also a stuffing box **22'** through which the tubing **7** passes. The tilting axis **58** passes through both of the tilting joints **58'**; **58''** as well as the stuffing box **22'** located between these tilting joints.

20

As indicated on Fig. **6**, at a lower region **5''''** of the cage **5** there are setting means **61**; **62** interacting with engaging means **63**; **64** on a lower region **21'** of the frame **21** for adjustably setting maximum tilting angles.

25

The cage **5** can be tilted to ensure alignment of the injector with a well center, and the springs **59**; **60** further enable the frame **21** to be aligned with the well.

30

In the description to follow, there is described improvements of the skate or counter-force member of the conveyor apparatus, with reference to Figs. **8, 9** and **21 - 24**.

As indicated, a conventional skate or counter-force member is very easily

23

subjected to deformations along its length, causing the skate **37** to exhibit along its length a wavy shape.

In order to overcome these drawbacks of the prior art, the counter-force member **37** has an elongate part **37'**, and b) along the length of the elongate part **37'** a plurality of pairs of substantially V shaped elements **37''**, the elements of each pair extending with their V-legs **37'''** laterally from oppositely located side edges of the elongate part towards an apex **37''''** of the V - shaped element.

10 An axis **61** of one leg **37'''** of a V - element of one pair of elements, at one side edge of the elongate part, is aligned with an axis **62** of a leg **37'''** of a V - element of another and adjacent pair of elements, at the other side edge of the elongate part **37'**. The V- elements **37''** are integral with the elongate part **37'** and co-planar therewith.

15

The elongate part **37'** and each of said elements **37''** have substantially the same thickness.

In order to strengthen a mid-region of the skate **37**, at least one pair of the V-shaped elements have legs **37'''** which are wider than the legs **37'''** of other pairs of V-shaped elements. Thus, said at least one pair of V - shaped elements **37''** is located at longitudinal mid-region side of the elongate part. As shown on Figs. **22** and **24**, at least two pairs **63**, **64** of the V-shaped elements **37''** have legs **37'''** which are wider than the legs **37'''** of other pairs of V-shaped elements. Thereby, one pair **63** of the at least two pairs of V-shaped elements **37''** is located upstream of longitudinal mid-region sides of the elongate part **37'**, and wherein another pair **64** of the at least two pairs of V-shaped elements **37''** is located downstream of longitudinal mid-region sides of the elongate part.

30 From viewing Figs. **21** and **23**, it is noted that the previously described means **40**, **41**, **41'**, **42**, **43** to adjust mutual spacing of the pair of counter-force members **37** interact with the V- apexes **37''''** of said elements **37''**.

24

By the arrangement of the elements **37"** as shown and described, it will be noted that the axes **61, 62** cross at a centerline of the part **37'**, thereby creating a structure which has crisscross load distribution, rather than specific load locations having high stress, i.e. a kind of structural beam.

5

Contrary to the prior art, from Fig. **24**, it is noted that the axes **61, 62** or centerlines of the legs **37""** do not cross the elongate part **37'** at right angles, but at an angle suitably in the range  $20^{\circ}$  -  $70^{\circ}$ , dependent on the angle at the apex **37""** and the number of pairs of elements **37"** provided.

10

By having such V- shaped elements **37"**, there is between the elongate part **37'** and the elements **37"** created triangular cutouts, such as cutouts **65, 66**. In the embodiment shown on Figs. **22** and **24**, the triangular cutout **65** is slightly smaller than the cutout **66**, and it is noted that the distance from the elongate part **37'** to the "valley" **67** is somewhat greater than the distance from the valley **68**, thus yielding extra strength at the mid-region of the counter-force member **37** or skate. The triangular "cut-outs" contribute to the "structural beam" configuration, thereby yielding improved overall force-vectors.

15

From Figs. **25** and **26**, it is noted that the triangular cutouts **65, 66** seen on Fig. **24** have been replaced by circular cutouts **69** and associated legs **70**. Such a configuration may affect force vector direction not to be as rectilinear as in the embodiment having triangular cutouts **65, 66** and more distinct legs **61, 62**. However, circular cutout may yield less structural stresses at the cutout region.

20

Thus, there is provided a uniform depression of the skate or counter-force member **37** by the rollers over substantially its entire length.

Hence, from the description hereinbefore it would be clear that all the objects of the invention are achieved.

25

The present invention has been described with reference to preferred embodiments and aspects thereof and related to the accompanying drawings

30

25

for the sake of understanding only and it should be obvious to persons skilled in the art that the present invention includes all legitimate modifications within the ambit of what has been described hereinbefore and claimed in the attached claims.

N e w P a t e n t C l a i m s


Date: March 9, 2016

Agent's ref.: P4487PC00

Appl. No.: PCT/EP2015/051320

- 5     **1.**           A conveyor apparatus (2), so-called injector head, to enable feeding of continuous elongate device (7; CED), e.g. continuous tubing (7) or coiled tubing, along a feeding axis down through the conveyor apparatus (2), to enable insertion of tools through the wellhead (6) and a well below, or up through the conveyor apparatus by pulling action enabling retrieval of the tool from the wellhead and the
- 10    well below,
- the conveyor apparatus (2) comprising:
- an apparatus cage (5),
- an apparatus frame (21) within the cage (5), a guide arch (4) for guiding said continuous elongate device (7; CED) into said feeding axis, said arch (4) being
- 15    attached to said cage (5), and
- a pair of oppositely located, co-operatively movable, segmented continuous belts (28; 29) installed in the frame, each belt (28; 29) comprising a plurality of interconnected device (7; CED) gripper shoe carriers (30) carried and movable by means of a pair of continuous belt drive chains (31; 32) running over respective
- 20    pairs of chain drive sprockets (33; 34), and a device (7; CED) gripper shoe (38; 52) co-operative with each carrier (30) to positively engage the continuous elongate device (7; CED),
- characterized in**
- that the frame (21) at a lower end (21') thereof is tiltably connected to the cage (5) so
- 25    as to cause frame (21) to be tiltable relative to said cage (5) in a tilting plane about a single tilting axis (58), said tilting axis (58) crossing the feeding axis of the continuous elongate device (7; CED).
- 2.**           The apparatus of claim 1, wherein the frame (21) at an upper end thereof
- 30    in the tilting plane is linked to two spaced apart upper regions (5"; 5''') of the cage (5) via resilient members (59; 60).
- 3.**           The apparatus of claim 1 or 2, wherein the tilting plane is located transversely of a rotary axis of said sprockets (33; 34).

4. The apparatus of claim 1, wherein a lubricator string (8) is located between the conveyor apparatus (2) and the wellhead (6).
5. The apparatus of claim 4, wherein a blowout preventer (11) is located between the lubricator string (8) and the wellhead (6).
6. The apparatus of claim 4 or 5, wherein the cage (5) is rigidly attachable to an uppermost region of the lubricator string (8) via a connector (22).
7. The apparatus of any one of claims 1 - 6, wherein the frame (21) is tiltable in said tilting plane relative to the cage (5) in one direction or the other by a tilting angle not greater than 10 degrees,
8. The apparatus of claim 7, wherein the tilting angle is not greater than 3.0 degrees.
9. The apparatus of claim 7, wherein the tilting angle is not greater than 1.5 degrees.
10. The apparatus of any one of claims 1 - 9, wherein at a lower region (5'') of the cage (5) there are setting means (61; 62) interacting with engaging means (63; 64) on a lower region (21') of the frame (21) for setting maximum tilting angles.
11. The apparatus of any one of claims 1 - 10, wherein the frame (21) at a top region thereof has a pair of rollers (24') between which the continuous elongate device (7; CED) passes, and wherein a force imposed on one or the other of the rollers (24') causes tilting of the frame (21) relative to the cage (5).






FIG. 2




FIG. 3




FIG. 4a




FIG. 4b




FIG. 5

7/24




FIG. 6a




FIG. 6b

9/24




FIG. 7




FIG. 8




FIG. 9

SUBSTITUTE SHEET (RULE 26)




FIG. 10a




FIG. 10b




FIG. 10c




FIG. 11




FIG. 12a




FIG. 12j




FIG. 12h




FIG. 12f




FIG. 12d




FIG. 12b




FIG. 12i




FIG. 12k



FIG. 12g




FIG. 12e




FIG. 12c




FIG. 13




FIG. 14




FIG. 15








FIG. 16






FIG. 21




FIG. 22




FIG. 24

FIG. 23

FIG. 25





FIG. 26






FIG. 4a




FIG. 5