

Feb. 8, 1966


M. E. MAYNARD

3,233,256

PROCESS FOR CONTROLLING CONDITIONS IN AN ENCLOSED FLUID MEDIUM

Original Filed July 3, 1963

3 Sheets-Sheet 1



INVENTOR.
MARVIN E. MAYNARD
BY *H. William Poley*
ATTORNEY

Feb. 8, 1966

M. E. MAYNARD

3,233,256

PROCESS FOR CONTROLLING CONDITIONS IN AN ENCLOSED FLUID MEDIUM

Original Filed July 3, 1963

3 Sheets-Sheet 3




FIG. 4-

INVENTOR.
MARVIN E. MAYNARD
BY *William T. Toney*
ATTORNEY

1

3,233,256

PROCESS FOR CONTROLLING CONDITIONS IN AN ENCLOSED FLUID MEDIUM

Marvin E. Maynard, Spartanburg, S.C., assignor to Deering Milliken Research Corporation, Spartanburg, S.C., a corporation of Delaware

Original application July 3, 1963, Ser. No. 298,514, now Patent No. 3,128,617, dated Apr. 14, 1964. Divided and this application May 29, 1964, Ser. No. 371,216 10 Claims. (Cl. 8—152)

This application is a division of application Serial No. 298,514, filed July 3, 1963, which in turn is a continuation-in-part of application Serial 118,985, filed June 22, 1961 (now U.S. Patent 3,128,617, of April 14, 1964).

This invention relates to novel processes for improved control of variables in fluid-treating process, particularly in processes for dyeing textile materials.

Fluid-treating processes generally involve the dissolution or dispersion of one material into another and the heating or cooling of the resulting system. The success of the process often hinges upon the degree of control over at least these process variables. Unfortunately, however, apparatus for providing the high degree of control required has not been developed to the same extent as the processes themselves, thereby forcing the operator to resort to alternative and less desirable practices.

These problems are particularly acute in the dyeing of textile materials, which involves the dissolution or dispersion of various dyestuffs in a suitable medium and periodically raising, lowering, and maintaining a given temperature. Some fabrics, such as those composed of wool or nylon fibers, have been extremely difficult to dye levelly because apparatus presently available is not capable of providing the control over the dyestuff concentration and temperature so necessary to level dyeing.

For example, the exhaustion of a dyestuff onto a textile material is an equilibrium reaction. In developing a dyestuff formulation to provide a desired shade, the dyer selects a group of dyestuffs which will give him the general color desired and then determines at which temperature the dyestuffs selected will exhaust onto the fabric to provide the desired shade of the general color selected. Once this temperature is selected, it is extremely important that it be controlled since variations in temperature at this point may reverse the exhaustion reaction or vary the rate of exhaustion, thereby providing a shade of color different from that desired.

In a typical situation, a blue, red, and a yellow dyestuff may be formulated to provide a grey color. The dyer then determines that the desired shade of grey, e.g., a greenish grey, will be provided at 205° F., at which temperature the requisite amounts of the various dyestuffs will exhaust onto the fabric to provide the desired shade of color. The dyer also determines that, at a temperature of 200° F., a greater amount of the blue dyestuff will exhaust onto the materials, so that a bluish-grey shade will result, whereas at a temperature of 210° F., a greater amount of yellow dyestuff will exhaust, so as to provide a yellowish-grey shade.

It becomes quite apparent that the dyestuff medium must be carefully controlled at the 205° F. equilibrium level if the desired greenish-grey shade is to be obtained. For example, the portion of the fabric which is contacted by the dyestuff medium at 200° F. will take on a bluish-grey shade, that at 205° F. the desired greenish-grey shade, that at 210° F. a yellowish-grey shade. Obviously, if the temperature varies from 200° to 210° F. across the fabric, the fabric undesirably takes on different shades.

Once this situation has arisen, the dyer may follow any one of several alternative procedures. For example, he may attempt to bring a lighter shade, if this is the case, up the desired shade by adding a sufficient amount of the

2

color dyestuff required. If the fabric has been dyed a shade darker than desired, some dyestuffs may be removed by stripping agents, although with present day equipment level stripping is as difficult as level dyeing, so that this procedure is not often feasible. On the other hand, the fabric may be dyed a still darker shade, such as black, whereby a useable fabric is obtained, though, of course, not in the desired shade. These procedures increase materially the expense involved in dyeing textile materials and numerous attempts have been made to overcome the conditions which raise these problems.

For example, a most common means of controlling the temperature of the dyestuff medium is by steam jets separated from the medium by a perforated wall. These jets are actuated when detecting devices indicate that the temperature is decreasing in the medium. This apparatus, as presently designed, frequently causes hot and cold spots in the dyestuff medium and, furthermore, often results in substantial dilution of the dyestuff medium, which in itself causes shade variations in the fabric. While this latter difficulty has been solved by more expensive closed-end steam coils extending into the dye medium, hot and cold spots varying in temperature as much as 20–30° F., are still commonplace in present day commercial apparatus.

This difficulty has also restricted the dyestuffs which can be utilized in the dyeing process. For example, a dyestuff formulation which will give its intended shade at a temperature within a fairly restricted range, e.g., 206–209° F., can not be utilized in conventional apparatus because of the wide variations in temperature throughout this equipment.

Obviously, the cost of dyeing in conventional apparatus is higher in that greater amounts of dyeing assistants and dyestuffs must be utilized to obtain level dyeings in a given shade. In addition, the dyeing cycle is longer in conventional equipment because of the add-dyeing required and the longer times required to achieve a given temperature.

The factors which prohibit a uniform temperature in conventional apparatus also contribute to non-uniform dispersion of the dyestuff throughout the apparatus, so that level dyeing is difficult to attain regardless of temperature.

It is an object of this invention to provide improved control over process variables in fluid-treating processes.

A further object of this invention is to provide novel processes for dyeing textile materials at controlled temperatures, thereby solving many of the problems associated with conventional dyeing procedures.

It is a further object of this invention to minimize temperature variations in such processes in an economical manner and without diluting the dyestuff medium.

Still a further object of this invention is to provide such processes which will allow more uniform temperature control, both heating and cooling, at increased forced rates.

It is still a further object of this invention to provide such processes wherein the dyestuff is dispersed evenly throughout the processes, greatly facilitating level dyeing.

An additional object of this invention is to provide dyeing processes which permit shorter dyeing cycles because of the reduced time required to raise uniformly the temperature of the dyestuff medium to the desired equilibrium level and because of the shorter period of exposure required at this level due to the high degree of control of the equilibrium level temperature.

Yet another object of this invention is to reduce materially or eliminate entirely add-dyeing, enabling the dyer to automate the dyeing process after establishing a dyestuff formulation and desired equilibrium temperature.

Still another object of this invention is to reduce the amount of materials required to provide the desired shade of color in a textile material, while increasing the number

of dyestuffs which can be utilized because of the more exacting control of the dyeing equilibrium temperature, as is required for many desirable dyestuffs for which no suitable apparatus has heretofore been developed.

An additional object of this invention is to provide processes suitable for the level-dyeing of textile fabrics which are presently extremely difficult to dye evenly because of temperature variations in conventional equipment.

These objects are accomplished in accordance with this invention by creating a zone of fluid turbulence in a predetermined volume of the treating fluid while it is enclosed, e.g., surrounded, in suitable equipment. The fluid is directed transversely from the turbulent zone along the depth and width thereof and then toward a plurality of predetermined areas situated in a plane displaced from and oriented at a transverse angle to the turbulent zone. This flow pattern is maintained by recirculation, continuous in most instances, of the fluid from these predetermined areas back into the turbulent zone. Most efficient flow patterns are developed in lengthwise bodies of fluid, preferably separated into at least two portions, by disposing the predetermined areas in one portion at the ends thereof and then recirculating the fluid from these areas into another portion where turbulence is developed.

The turbulence in at least one of the zones may be created in any convenient manner, but is created most simply and economically by diverting the recirculating fluid from its delivery path as it enters the zone where turbulence is to be created.

This novel process is most conveniently conducted in fluid-treating apparatus comprising a container for the treating medium, e.g., a dyestuff medium, and at least one baffle means located within the container so as to separate the container into at least a first and a second inner chamber, the baffle means having a plurality of openings along its length and width, whereby the dyestuff medium is free to pass between the first and second inner chamber. An outlet means is provided for the first chamber and is preferably adapted for removing the dyestuff medium from the dye chamber at different depths of the medium. These means, which are also preferably located at both ends of the dye chamber, are connected to an inlet means in the second chamber by a conduit system which includes a pumping means and, preferably, a heat exchange means, so that the dyestuff medium may be constantly recirculated at the desired rate from the first chamber into the second chamber and heated or cooled as desired. At least one turbulence generating means is located within the second chamber to facilitate free flow of the dyestuff medium in this chamber into the dye chamber.

A preferred turbulence generating means comprises a deflector means intersecting at a transverse angle the delivery bath of the dyestuff medium from the inlet means for the second chamber. When the recirculating dyestuff medium is directed against the deflector means, a high degree of turbulence is developed in the second chamber. The turbulent recirculating medium is preferably directed by the angle of the deflector means along the entire length of the perforated plate and downwardly across the width of the plate, thereby greatly facilitating the movement of the dyestuff medium from the turbulent second chamber into the first chamber at a rapid and uniform rate and at all strata of the dyestuff medium in the dye chamber.

Preferably, the baffle means separating the container into a dye chamber and a chamber of fluid turbulence is situated in a plane substantially parallel to and displaced from the longitudinal axis of the container, thereby providing lengthwise inner chambers.

The baffle means should be sufficiently open along its length and width to permit free flow of the fluid medium between the chambers. At the same time, the separator means should provide sufficient resistance to permit the development of fluid turbulence in the second chamber. These objectives are readily attained with a perforated

plate, although heavy gauge screens, separated baffle plates and the like are similarly useful.

The dye chamber contains textile material, which may be passed continuously into and out of the first chamber or remain immersed, as in a package dyeing operation.

While the turbulence provided in the second chamber will improve greatly the rate and uniformity of flow from the second chamber into the dye chamber so as to improve the degree of control of temperature in the dyeing chamber, this control is greatly facilitated in a preferred embodiment of this invention wherein outlets are located at each end of the dye chamber and extend substantially along its entire width preferably conforming substantially to the cross-sectional configuration of the dye chamber, so that the dyestuff medium will be removed from the dye chamber at various levels throughout the depth of the dyestuff medium, as is highly desirable.

The direction of the openings toward and upwards of the adjacent end walls of the first chamber in this embodiment seems to draw the dyestuff medium toward both end walls and downwardly along the walls toward the openings, so that the dyestuff medium is in a state of flow at each point in the container, thereby insuring adequate heat transfer and dyestuff dispersion. As a result, the textile material being dyed is confronted on all surfaces with a dyestuff medium containing the same amount of dyestuff and dyeing assistants at a substantially uniform temperature.

The outlet tubes can lead into a common outlet drain, as shown below, or have separate drains as desired. Obviously, the drain may be placed in any convenient location.

In another embodiment of this invention outlets are placed in both end walls of the dye chamber, preferably at different levels along the depth of the dyestuff medium and across the width of the dye chamber. The outlets may lead by piping to an outlet tube as described above or to a header if desired. Alternatively, tubular outlets as described above may be placed in end chambers formed by the end walls and additional baffle means as utilized to separate the container into lengthwise chambers. In these latter embodiments, screens or other lint catches are preferably placed at the outlets from the dye chamber.

In a highly preferred embodiment of this invention, the outlet means is combined with an inlet means which feeds into one end of the second chamber so that the recirculating dyestuff medium pumped therethrough will be directed lengthwise of the chamber against the deflector means. The deflector means is located in close proximity to the inlet means, preferably within the first third of the length of the second chamber from the inlet means.

The deflector means and inlet means are situated to obtain the maximum degree of turbulence along the entire length of the perforated plate. At least one plate, the preferred type deflector means, is required to provide the desired degree of turbulence, although a plurality of plates may be utilized along the entire length of the second chamber if desired. Preferably, the plate, or plates, is adjustable in two planes and is directed toward the baffle means.

The deflector means, as noted above, intersects the delivery path of the recirculating dyestuff medium from the inlet means into the second chamber to generate the desired turbulence. While it is preferred to place the inlet means at one end of the chamber, the inlet means may be placed at any desired location leading into the second chamber, for example, at approximately the middle of the second chamber so that the recirculating medium is directed toward the baffle means separating the container into two chambers. In this embodiment of the invention, a V-shaped, perforated if desired, deflector plate may be utilized to direct the recirculating dyestuff medium toward both ends of the second chamber along the perforated plate.

5

In still another embodiment, inlet means may be located at each end of the second chamber with deflector means intersecting the delivery path of either or both inlet means. In fact, some degree of turbulence is provided, particularly at the middle portion of the chamber, when both deflector means are eliminated. The flow pattern thus produced may be suitable in some processes.

The recirculating dyestuff medium is preferably continuously heated by a heat exchange means located within the conduit system connecting the outlet and inlet means, in that far more exacting temperature control is provided in this manner. Preferably, the heat exchange means is adapted for both heating and cooling, so that the dyestuff medium may be forcibly heated or cooled at a rapid rate.

A preferred heat exchange means comprises a Formee heat exchanger combined with a four-way valve and timing mechanism therefor, so that the direction of the dyestuff medium through the heater may be reversed as desired, thereby providing a flushing action to remove any entrained material from the heater. This feature is particularly desired when textile materials comprising spun yarns are being treated, in that lint and other contaminants might clog the heat exchanger. The flushing action provided by the timed four-way valve obviates this problem. Clogging of the openings of the outlet means in the dye chamber may be obviated somewhat by screens, bars or other lint catchers.

While the fullest advantages of the apparatus of this invention are accomplished when the heat exchange means is located in the recirculating conduit system, the heat exchange means may be eliminated entirely and temperature control provided by jets of steam, preferably dry steam, leading into the turbulent chamber at spaced intervals. This latter expedient is made possible only by the excellent three-dimensional fan-shaped flow pattern developed by the apparatus of this invention, whereby the recirculating dyestuff medium is forced at an increased rate from the turbulent second chamber transversely into the dye chamber and is then drawn toward each end of the dye chamber along various levels of the medium, thereby minimizing the "dead" spots or "hot" spots which generally occur in apparatus heated by steam through either open jets or closed end coils. In addition, the recirculating medium is forced downwardly as well as along the length of the perforated plate, so that the medium is fed into the dye chamber at all strata of the medium in the dye chamber, again facilitating the elimination of non-uniformities in the medium temperature and concentration.

While a non-clogging open impeller type pump is preferred for use in the apparatus of this invention, various conventional pumping means or a plurality thereof may be utilized.

FIGURE 1 is a schematic view of one apparatus suitable for practising the process of this invention.

FIGURE 2 is a cut-away view of FIGURE 1, illustrating in a more detailed manner the interior of the apparatus of FIGURE 1.

FIGURE 3 is a top view of FIGURE 2 without the fabric moving apparatus.

FIGURE 4 is a schematic, cut-away view of another embodiment of apparatus suitable for practising the process of this invention.

FIGURE 1 illustrates a preferred embodiment of this invention wherein the container 1 is separated into a dye chamber 2 and a turbulence chamber 3 by perforated plate 4. Continuous lengths of fabric 5 are passed continuously into and out of the dye chamber 2 over elliptically shaped feed roll 6 and guide roll 7 driven by a suitable motor, not shown. The plurality of fabric lengths are separated by separator bars 8 to prevent overlapping of the fabric lengths which would interfere seriously with the levelness of the dyeing operation. The dye stuff medium is withdrawn from the dye chamber from drain 9 through pump 10 driven by motor 11 and into a Formee

6

heat exchanger 12, by way of a four-way valve 13 controlled by timer 14, so that at periodic intervals the dye medium is reversed in direction through the Formee heat exchanger 12, thereby providing a flushing action. Heated or cooled fluids, for example steam or cold water, are directed in the Formee heat exchanger 12 through pipe 15. The Formee exchanger 12 is also provided, for instances when steam is utilized, with a condensate trap 16, which leads back into the boiler (not shown). The recirculation path is continued by passing the dyestuff medium through pipes 17 into inlet tube 18 leading into the turbulence chamber 3.

As shown in the cut-away view of FIGURE 2, the dye-bath medium is directed from inlet tube 18 against deflector plate 19 supported by bar 20 which is attached to the perforated plate 4 and front wall 21.

As is seen, outlet tubes 22 and 23 conform generally to the cross-sectional configuration of a dye chamber 2. Guard bars 26 are located across the end openings and perforations of the outlet tubes 22 and 23 to catch loose material, such as lint, which is drawn toward the outlet means during the operation of the recirculating system. Additional guard bars 27 are located at the end of the outlet means at back wall 28 of the container to provide additional protection from lint clogging at this higher disposed position. The outlet tubes 22 and 23 are connected by pipes 29 and 30 to the drain 9, which extends lengthwise of the dyeing chamber from outlet 23 out into the recirculating system in false bottom 33. Perforations 34 are provided in both outlet tubes through which the dye liquor is drawn for recirculation.

As shown in FIGURE 3 (a top view of FIGURE 2 without the fabric and fabric moving apparatus), the perforations of outlet tubes 22 and 23 are directed toward and upwards of the end walls 24 and 25. The location of the perforations at this point greatly enhances the flow pattern developed by this system during its operation as will be explained hereinafter.

Turbulence chamber 3 is also provided with a plurality of inlet tubes such as tubes 31 and 32, for the addition of various dyeing intermediates, dye stuffs, scouring media, water and the like. The mixing of these materials is greatly enhanced by the turbulence provided when the stream is directed against the deflector plate 19.

Operation of this apparatus is readily understood from these drawings. The container 1 is filled with the desired treating medium, e.g., a dyestuff medium, and the fabric lengths are moved into and out of the dye chamber portion 2 of the container by rotation of the feed rolls 6 and 7 in the conventional manner. As the fabric lengths move through the dye chamber, the dyestuff medium is continuously recirculated from the dye chamber 2 to the turbulence chamber 3 through tubes 22 and 23, drain 9, pump 10, heat exchanger 12 into inlet tube 18. As the dyestuff medium is pumped into the turbulence chamber 3 it strikes against deflector plate 19 whereby it is forced toward the perforated plate 4, along its length and downwardly along its depth. This turbulent action forces the dyestuff medium through the perforations of wall 4 transversely into the dye chamber at all depths of the dyestuff medium where it is then drawn along substantially the entire width and depth of the dye chamber 2 toward outlet tubes 22 and 23 located at end walls 24 and 25. Because the perforations of these outlet tubes are directed toward the end walls, the dyestuff medium is drawn down the end walls as well, thereby eliminating the "dead" spots which normally occur in those locations. When the perforations of the outlet tubes are directed inwardly from the end walls, the dyestuff medium is not necessarily drawn down the end walls, although sufficient flow is usually provided to reduce the "dead" spots which normally occur. The desired flow path, however, is most readily obtained by directing the perforation of the outlet tubes toward the end walls and this embodiment is preferred for use in accordance with this invention. The continuous

movement of the fabric lengths through the dye chamber as the dyestuff medium is being continuously recirculated in the desired flow pattern causes the dyestuff medium to be "pumped" back and forth between the dye chamber and the turbulent chamber. Consequently, the dyestuff medium is pumped continuously back and forth through the textile material also, thereby greatly facilitating the level dyeing of the textile material.

FIGURE 4 is a schematic, cut-away view of apparatus which does not employ deflectors in performing the process of this invention. As in the apparatus of FIGURES 1-3, the container 35 is separated into a dye chamber 36 and a turbulence chamber 37 by perforated plate 38. Continuous lengths of fabric 39 are passed continuously into and out of the dye chamber 36 over elliptically shaped feed roll 40 and guide roll 41 driven by a suitable motor, not shown. Separator bars 42 are also provided as before.

In this embodiment of the invention, the dyestuff medium is withdrawn from the dye chamber through outlets 43, 43', 44, 44', 45, and 45' located in the end walls and placed at different levels of the dye chamber. Instead of guard bars, the outlets are covered by perforated cover plates 46 and 46', to catch lint and other debris.

The dyestuff medium is then pumped by means of pump 47, driven by a suitable motor (not shown) into a manifold 48 connected to the pump by 5-inch tubing. The remaining tubing in the system is 4-inch diameter. From the pump, the dyestuff medium is forced through a Formee heat exchanger 49, by way of a four-way valve 50 controlled by timer 51 as before, so that at periodic intervals the dye medium is reversed in direction through the heat exchange, thereby providing a flushing action. Heated or cooled liquids, for example, steam or cold water, are directed into the heat exchange through pipe 52. The heat exchanger is also provided with a condensate trap 53, which leads back into the boiler (not shown). Inlet 54 is provided in the pump inlet-tubing for feeding various additives, e.g., additional dyestuff, into the recirculating system as desired. The recirculation path is continued by passing the dyestuff medium into another manifold wherein the dyestuff medium is divided into two substantially equal volume streams which are then fed into oppositely situated inlets 55 and 55'.

Operation of this embodiment of the invention is the same as the embodiment of FIGURES 1-3, except that the desired turbulence is created by the two streams being directed against one another in the turbulence chamber. This turbulence, in combination with the multi-level withdrawal of the dyestuff medium from the opposite side of the dye chamber inter alia provides the type of fluid flow necessary to control conditions in the dye chamber.

Example 1

Apparatus as illustrated in the drawings is utilized to dye a wool fabric. A standard Rodney Hunt Company Trushade 12 foot dye beck, separated into two chambers by a plate having 1 inch perforations across its entire area and located 16¼ inches from the front wall, is equipped at each end with 3 inch diameter U-shaped tubes, as shown in the drawings. Three perforations, 1¾ inches in diameter, are located at equal distances along the length of each tube. A 5-inch drainpipe connects both outlet tubes to a non-clog impeller type pump, Model No. 14A2, sold by the Gormon-Rupp Co., having a capacity sufficient to recirculate the dyestuff medium every minute. This pump is equipped with a 4 inch diameter outlet tube leading into the four-way valve of a standard Formee heat exchanger, heated by steam and cooled by tap water. The four-way valve is equipped with a timing device so that the direction of the material pumped therethrough may be reversed at periodic intervals to prevent clogging of the heater by lint and other contaminants from the dyebath solution. The Formee heater is connected to the dyebath chamber provided by

the perforated wall and the front wall of the dye beck by a 4 inch tube. The 4 inch inlet tube is located 18½ inches from the top and 11 inches back from the front of the dye beck. Located 12 inches from the inlet tube and directly in the path of material being pumped from the inlet tube is a solid rectangular plate (6 inches wide by 13 inches long) directed toward the perforated wall at an angle of about 20°. This plate is adjustable in two dimensions, i.e. pivotable about its major axis and also toward the end walls.

Utilizing this apparatus, the dye beck is filled with about 1050 gallons of tap water. A plurality of fabric lengths in rope form is then loaded onto the guide rolls, driven by a suitable motor, and run through the cold water for ten minutes to completely wet-out the fabric. The dye beck is then emptied, refilled and 3.06 lbs. of sodium hydroxide, 1.53 lbs. tetra-sodium pyrophosphate, 1.91 lbs. of Triton X-100, a non-ionic alkaryl polyether alcohol and 15.34 lbs. of Varsol, a refined aliphatic hydrocarbon solvent are added to the water as scouring agents. The temperature of the scouring solution is raised to 180° F. and the fabric is run therethrough for 60 minutes. The scouring solution is drained from the dye beck and the fabric is rinsed twice for 20 minutes at 160° F. and 120° F., respectively.

The dye beck is once again filled with water, raised to 120° F. as the fabric movement continues. After the addition of 5.75 lbs. of both Irgasol DA, a high molecular weight aromatic condensate and Avitone T, a sodium hydrocarbon sulfonate and 12 gallons of NaCl brine, as dyeing assistants, and 0.296 lb. of Neolan black WAN Extra, 0.245 lb. of Irgalan black RBL, 0.115 lb. of Cibalan yellow GRL, 0.92 lb. Lumicrease grey 3LR and 0.138 lb. of Lumicrease yellow 3LG, as dyestuffs, the temperature of the resulting solution is raised to 190° F. at 2° per minute intervals and held at this temperature for 45 minutes. The dyebath is then cooled at 2° per minute intervals to 160° F., by passing cold water through the Formee heat exchanger instead of steam. At this reduced temperature, 12 gallons of brine and 15.34 lbs. ammonium acetate, as exhausting agents are added to the dyebath, which is then heated to 195° F. at 2° per minute intervals and held for 60 minutes. After cooling as before to 160° F., the dyebath is drained from the dye beck and rinsed twice with water at 80° F. Swatches of the fabric so treated are removed from the fabrics throughout the dye beck and, after drying are compared with standard fabrics. The uniformity and levelness of dyeing is highly satisfactory and compares perfectly with the control so that no add-dyeing is necessary. During the entire operation, the instant treating media is recirculated through the recirculating system from the dyeing chamber into the turbulence chamber. Temperatures at equally spaced intervals along the length, width and depth of the dye beck are measured, the maximum variation being 3° F. The maximum variation at any fixed temperature level, e.g., the 190° F. equilibrium temperature, is about 1° F. The same fabric is dyed in a second Rodney Hunt Company Trushade 12 foot dye beck using the standard steam jets to increase the temperature of the dye beck at desired intervals. Cold water is utilized to cool the dye beck. Using this apparatus, however, 3.78 lbs. of caustic, 1.89 lbs. of tetra-sodium pyrophosphate, 9.46 lbs. of Triton X-100 and 18.92 lbs. of Varsol are required to provide similar scouring. In addition, greater amounts of dyestuffs and dyeing assistants are required to provide the same degree of dyeing. For example, 9.46 lbs. of Irgasol DA, 9.46 lbs. of Avitone T, and 24 gallons of brine are required as dyeing assistants, while 0.416 lb. of Neolan black WAN Extra, 0.30 lb. of Irgalan RBL, 1.41 grams of Cibalan yellow GRL, 1.13 lbs. of Lumicrease grey 3LR and 1.51 lbs. of Lumicrease yellow 3LG are required, as determined in a preliminary laboratory experiment prior to the actual dyeing operation performed, to provide dyeing equivalent to that pro-

vided by the lesser amounts utilized by the apparatus of this invention.

In addition, 28.38 lbs. of ammonium acetate is required as exhausting agent, as compared to the 15.34 lbs. required in the modified apparatus.

The above dyeing procedure is followed exactly except that the temperature is increased at 1° per minute intervals and held, after the addition of the exhausting agent, for two hours, rather than being raised at two minute intervals and being held for one hour as is possible with the modified apparatus.

The test swatches reveal that the fabrics are not dyed levelly and uniformly throughout the dye beck. To overcome this deficiency, the above dyeing cycle is repeated with the addition of 10 grams of Neolan black WAN Extra and 4 grams of Cibalan yellow GRL. The test swatches again reveal non-uniformity and the dye cycle is repeated with the addition of 0.02 lb. of Irgalan black RBL and 0.01 lb. of Cibalan yellow GRL. Once again, non-uniformity occurs and it is necessary to repeat the dyeing cycle with the addition of 0.02 lb. of Neolan black WAN Extra to obtain a fabric comaprable in quality to the fabric treated with the modified apparatus.

Thermocouples situated at the same location as on the modified apparatus indicate temperature variations of from 10° to 30° F. during the dyeing cycle.

While the apparatus of this invention if particularly adapted to the dyeing of textile fabrics, the apparatus may also be utilized in any fluid-treating apparatus wherever control over temperature, degree of dispersion, concentration or other variables is required. Most advantageous results are provided when the apparatus of this invention is utilized in the dyeing of other textile materials, such as stock, roving, top, yarn or skeins. The recirculating system and turbulence generating means may be utilized with aqueous or solvent-based systems and to modify any of the apparatus conventionally used in the dyeing of any of these various textile materials, for example, open or closed dye becks, package dyeing equipment such as the Burlington dyeing machines (with or without increased pressure) and others.

Apparatus which may be advantageously modified to include the recirculating and turbulence generating features of the apparatus of this invention includes apparatus utilized to bleach, mercerize, size or otherwise fluid-treat textile materials.

That which is claimed is:

1. Process for controlling conditions in an enclosed lengthwise fluid medium comprising creating a zone of fluid turbulence in a predetermined volume of said medium; directing the medium from the zone of fluid turbulence in a direction transverse to the longitudinal axis of said zone, along the depth and length of said zone, and then toward at least two predetermined areas displaced one from the other and situated in a plane transversely displaced from and oriented at a transverse angle to said zone of fluid turbulence, said predetermined areas being in opposing relationship and being located in substantially parallel planes; and recirculating the fluid medium from said predetermined areas into said zone of fluid turbulence.

2. The process of claim 1 wherein the fluid medium is heated as it is recirculated from the predetermined areas into the zone of fluid turbulence.

3. Process for controlling conditions in an enclosed fluid medium comprising separating said medium into at least a first and a second lengthwise fluid zone; agitating the fluid in said second zone to create a zone of fluid turbulence; directing the medium from said zone of fluid turbulence along the depth and length of said zone into the first zone, said medium being directed transversely from the longitudinal axis of said second zone toward the longitudinal axis of said first zone; then drawing the medium toward at least two predetermined areas situated in a plane transversely displaced from and oriented

at a transverse angle to said second zone, said predetermined areas being in opposing relationship and being located in substantially parallel planes; and recirculating the fluid medium from said predetermined areas of said first zone into said second zone.

4. The process of claim 3 wherein the plurality of predetermined areas are disposed along the entire width and at both ends of said first lengthwise zone.

5. The process of claim 4 wherein the fluid medium is heated as it is recirculated from the predetermined areas at the ends of the first zone into the second zone.

6. The process of claim 4 wherein the fluid medium in the second zone is agitated by diverting the recirculating medium from its path after it enters the second zone.

7. An improved process of dyeing textile materials with a dyestuff medium comprising enclosing the dyestuff medium; separating said medium into at least a first and a second lengthwise zone; recirculating said medium from a plurality of predetermined areas at the ends of said first zone into said second zone said predetermined areas being located at each end of said first lengthwise zone in opposing relationship and being located in substantially parallel planes which in turn are substantially perpendicular to the longitudinal axis of said first zone; diverting the medium as it is passed into said second zone whereby the medium in said zone is sufficiently agitated to be turbulent throughout the length and depth of said second zone; directing said medium from said second zone transversely into said first zone along the length and depth of said second zone; and then drawing said medium toward said plurality of predetermined areas disposed along the width and at the ends of said first zone.

8. The process of claim 7 wherein the dyestuff medium is heated as it is recirculated from said first chamber into said second chamber.

9. An improved process of dyeing textile materials with a dyestuff medium comprising:

(1) separating said medium into at least a lengthwise dyeing zone and a lengthwise agitation zone, the longitudinal axes of said zones being substantially parallel;

(2) removing said dyestuff medium from said dyeing zone at predetermined areas located in both ends of said dyeing zone in opposing relationship and in planes substantially parallel one to the other, said planes being perpendicular to the longitudinal axis of said dyeing zone;

(3) dividing said dyestuff medium into at least two portions;

(4) directing one of said portions into a first predetermined area in the agitation zone located in a plane substantially perpendicular to the longitudinal axis of said agitation zone;

(5) directing another of said portions into a second predetermined area in the agitation zone located in a plane substantially parallel to the first predetermined area in said agitation zone and being displaced longitudinally therefrom at the opposite end of said agitation zone, said second predetermined area also being substantially perpendicular to the longitudinal axis of said agitation zone, said predetermined areas being in opposing relationship so that the first and second portions create considerable agitation along the depth and width of said agitation zone;

(6) withdrawing the dyestuff medium from said agitation zone along the depth and length of said agitation zone in a direction transverse to, and toward, the longitudinal axis of said dyeing zone; and

(7) directing said dyestuff medium toward the predetermined areas located in both ends of said dyeing zone.

10. The process of claim 9 wherein the dyestuff medium removed from the predetermined areas located in

both ends of said dyeing zone are combined into a single stream, said stream then being heated to a predetermined temperature and then divided into two substantially equal portions.

References Cited by the Examiner

UNITED STATES PATENTS

2,482,319	9/1949	Casse	68—184
2,589,247	3/1952	Guzzetti	68—184
3,013,422	12/1961	Amidon	68—177 X

3,016,728	1/1962	Mann	68—177
3,091,109	5/1963	Clement	68—177

FOREIGN PATENTS

5	1,120,951	4/1956	France.
	1,160,578	3/1958	France.
	1,056,086	4/1959	Germany.
	257,940	3/1928	Italy.

IRVING BUNEVICH, *Primary Examiner.*