



US011182792B2

(12) **United States Patent**
Giobbi et al.

(10) **Patent No.:** **US 11,182,792 B2**
(45) **Date of Patent:** ***Nov. 23, 2021**

(54) **PERSONAL DIGITAL KEY INITIALIZATION AND REGISTRATION FOR SECURE TRANSACTIONS**

(71) Applicant: **Proxense, LLC**, Bend, OR (US)
(72) Inventors: **John J. Giobbi**, Bend, OR (US); **David L. Brown**, Jupiter, FL (US); **Fred S. Hirt**, Brookfield, IL (US)

(73) Assignee: **Proxense, LLC**, Bend, OR (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/893,155**
(22) Filed: **Jun. 4, 2020**

(65) **Prior Publication Data**
US 2020/0304301 A1 Sep. 24, 2020

Related U.S. Application Data
(63) Continuation of application No. 16/503,066, filed on Jul. 3, 2019, now Pat. No. 10,764,044, which is a (Continued)

(51) **Int. Cl.**
G06Q 20/40 (2012.01)
G06F 21/31 (2013.01)
(Continued)

(52) **U.S. Cl.**
CPC **G06Q 20/40145** (2013.01); **G06F 21/31** (2013.01); **G06F 21/32** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04L 9/0866; H04L 2209/56; H04L 2209/80; H04L 9/3231; H04L 63/0861;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,665,313 A 5/1972 Trent
3,739,329 A 6/1973 Lester
(Continued)

FOREIGN PATENT DOCUMENTS

EP 1536306 A1 6/2005
JP 10-049604 A 2/1998
(Continued)

OTHER PUBLICATIONS

Liu et al., "A Practical Guide to Biometric Security Technology," IT Pro, vol. 3, No. 1, Jan./Feb. 2001, pp. 27-32.


(Continued)

Primary Examiner — Badri Narayanan Champakesan
(74) *Attorney, Agent, or Firm* — Patent Law Works LLP

(57) **ABSTRACT**

A system and method provide efficient, secure, and highly reliable authentication for transaction processing and/or access control applications. A personal digital key (PDK) is programmed using a trusted programming device to initialize and/or register the PDK for use. In one embodiment, the initialization and registration processes are administered by a specialized trusted Notary to ensure the processes follow defined security procedures. In a biometric initialization, the programming device acquires a biometric input from a user and writes the biometric data to a tamperproof memory in the PDK. In registration, the Programmer communicates to one or more remote registries to create or update entries associated with the user PDK. Once initialized and registered, the PDK can be used for various levels of secure authentication processes.

20 Claims, 15 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/986,306, filed on Dec. 31, 2015, now Pat. No. 10,374,795, which is a continuation of application No. 14/448,891, filed on Jul. 31, 2014, now Pat. No. 9,251,326, which is a continuation of application No. 13/791,553, filed on Mar. 8, 2013, now Pat. No. 8,838,993, which is a continuation of application No. 11/744,832, filed on May 5, 2007, now Pat. No. 8,412,949.

- (60) Provisional application No. 60/798,172, filed on May 5, 2006, provisional application No. 60/798,843, filed on May 8, 2006, provisional application No. 60/838,788, filed on Aug. 17, 2006, provisional application No. 60/824,758, filed on Sep. 6, 2006, provisional application No. 60/894,608, filed on Mar. 13, 2007.

(51) **Int. Cl.**

G06F 21/32 (2013.01)
H04L 29/06 (2006.01)
G06F 21/34 (2013.01)
G06Q 20/34 (2012.01)
G07F 7/10 (2006.01)
H04L 9/32 (2006.01)
G07C 9/25 (2020.01)
G07C 9/26 (2020.01)
H04W 12/06 (2021.01)
H04L 9/08 (2006.01)

(52) **U.S. Cl.**

CPC **G06Q 20/401** (2013.01); **G06Q 20/4014** (2013.01); **H04L 63/0861** (2013.01); **G06F 21/34** (2013.01); **G06F 2221/2115** (2013.01); **G06Q 20/341** (2013.01); **G07C 9/257** (2020.01); **G07C 9/26** (2020.01); **G07C 2209/12** (2013.01); **G07F 7/1008** (2013.01); **H04L 9/0866** (2013.01); **H04L 9/3231** (2013.01); **H04L 2209/56** (2013.01); **H04L 2209/80** (2013.01); **H04W 12/06** (2013.01); **H04W 12/068** (2021.01)

(58) **Field of Classification Search**

CPC H04W 12/06; G06Q 20/341; G06Q 20/40145; G06Q 20/4014; G07F 7/1008; G06F 21/32; G06F 2221/2115; G06F 21/34; G06F 21/31; G07C 9/26; G07C 9/257
 USPC 713/183
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,761,883 A 9/1973 Alvarez et al.
 3,906,166 A 9/1975 Cooper et al.
 4,101,873 A 7/1978 Anderson et al.
 4,430,705 A 2/1984 Cannavino et al.
 4,476,469 A 10/1984 Lander
 4,598,272 A 7/1986 Cox
 4,661,821 A 4/1987 Smith
 4,759,060 A 7/1988 Hayashi et al.
 4,814,742 A 3/1989 Morita et al.
 4,871,997 A 10/1989 Adriaenssens et al.
 4,993,068 A 2/1991 Piosenka et al.
 5,043,702 A 8/1991 Kuo
 5,187,352 A 2/1993 Blair et al.
 5,224,164 A 6/1993 Elsner
 5,296,641 A 3/1994 Stelzel

5,307,349 A 4/1994 Shloss et al.
 5,317,572 A 5/1994 Satoh
 5,325,285 A 6/1994 Araki
 5,392,287 A 2/1995 Tiedemann et al.
 5,392,433 A 2/1995 Hammersley et al.
 5,410,588 A 4/1995 Ito
 5,416,780 A 5/1995 Patel
 5,422,632 A 6/1995 Bucholtz et al.
 5,428,684 A 6/1995 Akiyama et al.
 5,450,489 A 9/1995 Ostrover et al.
 5,473,690 A 12/1995 Grimonprez et al.
 5,481,265 A 1/1996 Russell
 5,506,863 A 4/1996 Meidan et al.
 5,517,502 A 5/1996 Bestler et al.
 5,541,583 A 7/1996 Mandelbaum
 5,544,321 A 8/1996 Theimer et al.
 5,552,776 A 9/1996 Wade et al.
 5,563,947 A 10/1996 Kikinis
 5,589,838 A 12/1996 McEwan
 5,594,227 A 1/1997 Deo
 5,598,474 A 1/1997 Johnson
 5,611,050 A 3/1997 Theimer et al.
 5,619,251 A 4/1997 Kuroiwa et al.
 5,623,552 A 4/1997 Lane
 5,629,980 A 5/1997 Stefik et al.
 5,644,354 A 7/1997 Thompson et al.
 5,666,412 A 9/1997 Handelman et al.
 5,689,529 A 11/1997 Johnson
 5,692,049 A 11/1997 Johnson et al.
 5,719,387 A 2/1998 Fujioka
 5,729,237 A 3/1998 Webb
 5,760,705 A 6/1998 Glessner et al.
 5,760,744 A 6/1998 Sauer
 5,773,954 A 6/1998 Vanhorn
 5,784,464 A 7/1998 Akiyama et al.
 5,799,085 A 8/1998 Shona
 5,821,854 A 10/1998 Dorinski et al.
 5,825,876 A 10/1998 Peterson, Jr.
 5,835,595 A 11/1998 Fraser et al.
 5,838,306 A 11/1998 O'Connor et al.
 5,854,891 A 12/1998 Postlewaite et al.
 5,857,020 A 1/1999 Peterson, Jr.
 5,886,634 A 3/1999 Muhme
 5,892,825 A 4/1999 Mages et al.
 5,892,900 A 4/1999 Ginter et al.
 5,894,551 A 4/1999 Huggins et al.
 5,898,880 A 4/1999 Ryu
 5,910,776 A 6/1999 Black
 5,917,913 A 6/1999 Wang
 5,923,757 A 7/1999 Hocker et al.
 5,928,327 A 7/1999 Wang et al.
 5,991,399 A 11/1999 Graunke et al.
 5,991,749 A 11/1999 Morrill, Jr.
 6,016,476 A * 1/2000 Maes G06Q 20/108
 705/18
 6,018,739 A 1/2000 McCoy et al.
 6,025,780 A 2/2000 Bowers et al.
 6,035,038 A 3/2000 Campinos et al.
 6,035,329 A 3/2000 Mages et al.
 6,038,334 A 3/2000 Hamid
 6,038,666 A 3/2000 Hsu et al.
 6,040,786 A 3/2000 Fujioka
 6,041,410 A 3/2000 Hsu et al.
 6,042,006 A 3/2000 Van Tilburg et al.
 6,055,314 A 4/2000 Spies et al.
 6,068,184 A 5/2000 Barnett
 6,070,796 A 6/2000 Sirbu
 6,076,164 A 6/2000 Tanaka et al.
 6,088,450 A 7/2000 Davis et al.
 6,088,730 A 7/2000 Kato et al.
 6,104,290 A 8/2000 Naguleswaran
 6,104,334 A 8/2000 Allport
 6,110,041 A 8/2000 Walker et al.
 6,121,544 A 9/2000 Petsinger
 6,134,283 A 10/2000 Sands et al.
 6,137,480 A 10/2000 Shintani
 6,138,010 A 10/2000 Rabe et al.
 6,148,142 A 11/2000 Anderson
 6,148,210 A 11/2000 Elwin et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,161,179	A	12/2000	Seidel	6,697,944	B1	2/2004	Jones et al.
6,175,921	B1	1/2001	Rosen	6,709,333	B1	3/2004	Bradford et al.
6,177,887	B1	1/2001	Jerome	6,711,464	B1	3/2004	Yap et al.
6,185,316	B1	2/2001	Buffam	6,714,168	B2	3/2004	Berenbaum
6,189,105	B1	2/2001	Lopes	6,715,246	B1	4/2004	Freeska et al.
6,209,089	B1	3/2001	Selitrennikoff et al.	6,728,397	B2	4/2004	McNeal
6,219,109	B1	4/2001	Raynesford et al.	6,737,955	B2	5/2004	Ghabra et al.
6,219,439	B1	4/2001	Burger	6,758,394	B2	7/2004	Maskatiya et al.
6,219,553	B1	4/2001	Panasik	6,771,969	B1	8/2004	Chinoy et al.
6,237,848	B1	5/2001	Everett	6,775,655	B1	8/2004	Peinado et al.
6,240,076	B1	5/2001	Kanerva et al.	6,785,474	B2	8/2004	Hirt et al.
6,247,130	B1	6/2001	Fritsch	6,788,640	B2	9/2004	Celeste
6,249,869	B1	6/2001	Drupsteen et al.	6,788,924	B1	9/2004	Knutson et al.
6,256,737	B1	7/2001	Bianco et al.	6,795,425	B1	9/2004	Raith
6,266,415	B1	7/2001	Campinos et al.	6,804,825	B1	10/2004	White et al.
6,270,011	B1	8/2001	Gottfried	6,806,887	B2	10/2004	Chernock et al.
6,279,111	B1	8/2001	Jensenworth et al.	6,839,542	B2	1/2005	Sibecas et al.
6,279,146	B1	8/2001	Evans et al.	6,850,147	B2	2/2005	Prokoski et al.
6,295,057	B1	9/2001	Rosin et al.	6,853,988	B1	2/2005	Dickinson et al.
6,307,471	B1	10/2001	Xydis	6,859,812	B1	2/2005	Poynor
6,325,285	B1	12/2001	Baratelli	6,861,980	B1	3/2005	Rowitch et al.
6,336,121	B1	1/2002	Lyson et al.	6,873,975	B1	3/2005	Hatakeyama et al.
6,336,142	B1	1/2002	Kato et al.	6,879,567	B2	4/2005	Callaway et al.
6,343,280	B2	1/2002	Clark	6,879,966	B1	4/2005	Lapsley et al.
6,345,347	B1	2/2002	Biran	6,886,741	B1	5/2005	Salveson
6,363,485	B1	3/2002	Adams et al.	6,889,067	B2	5/2005	Willey
6,367,019	B1	4/2002	Ansell et al.	6,891,822	B1	5/2005	Gubbi et al.
6,369,693	B1	4/2002	Gibson	6,892,307	B1	5/2005	Wood et al.
6,370,376	B1	4/2002	Sheath	6,930,643	B2	8/2005	Byrne et al.
6,381,029	B1	4/2002	Tipirneni	6,947,003	B2	9/2005	Huor
6,381,747	B1	4/2002	Wonfor et al.	6,950,941	B1	9/2005	Lee et al.
6,385,596	B1	5/2002	Wiser et al.	6,957,086	B2	10/2005	Bahl et al.
6,392,664	B1	5/2002	White et al.	6,961,858	B2	11/2005	Fransdonk
6,397,387	B1	5/2002	Rosin et al.	6,963,270	B1	11/2005	Gallagher et al.
6,401,059	B1	6/2002	Shen et al.	6,963,971	B1	11/2005	Bush et al.
6,411,307	B1	6/2002	Rosin et al.	6,973,576	B2	12/2005	Giobbi
6,424,249	B1	7/2002	Houvener	6,975,202	B1	12/2005	Rodriguez et al.
6,424,715	B1	7/2002	Saito	6,980,087	B2	12/2005	Zukowski
6,425,084	B1	7/2002	Rallis et al.	6,983,882	B2	1/2006	Cassone
6,434,403	B1	8/2002	Ausems et al.	6,999,032	B2	2/2006	Pakray et al.
6,434,535	B1	8/2002	Kupka et al.	7,012,503	B2	3/2006	Nielsen
6,446,004	B1	9/2002	Cao et al.	7,020,635	B2	3/2006	Hamilton et al.
6,446,130	B1	9/2002	Grapes	7,031,945	B1	4/2006	Donner
6,463,534	B1	10/2002	Geiger et al.	7,049,963	B2	5/2006	Waterhouse et al.
6,480,101	B1	11/2002	Kelly et al.	7,055,171	B1	5/2006	Martin et al.
6,480,188	B1	11/2002	Horsley	7,058,806	B2	6/2006	Smeets et al.
6,484,182	B1	11/2002	Dunphy et al.	7,061,380	B1	6/2006	Orlando et al.
6,484,260	B1	11/2002	Scott et al.	7,068,623	B1	6/2006	Barany et al.
6,484,946	B2	11/2002	Matsumoto et al.	7,072,900	B2	7/2006	Sweitzer et al.
6,487,663	B1	11/2002	Jaisimha et al.	7,079,079	B2	7/2006	Jo et al.
6,490,443	B1	12/2002	Freeny, Jr.	7,080,049	B2	7/2006	Truitt et al.
6,510,350	B1	1/2003	Steen et al.	7,082,415	B1	7/2006	Robinson et al.
6,522,253	B1	2/2003	Saltus	7,090,126	B2	8/2006	Kelly et al.
6,523,113	B1	2/2003	Wehrenberg	7,090,128	B2	8/2006	Farley et al.
6,529,949	B1	3/2003	Getsin et al.	7,100,053	B1	8/2006	Brown et al.
6,546,418	B2	4/2003	Schena et al.	7,107,455	B1	9/2006	Merkin
6,550,011	B1	4/2003	Sims, III	7,107,462	B2	9/2006	Fransdonk
6,563,465	B2	5/2003	Freeska	7,111,789	B2	9/2006	Rajasekaran et al.
6,563,805	B1	5/2003	Ma et al.	7,112,138	B2	9/2006	Hedrick et al.
6,564,380	B1	5/2003	Murphy	7,119,659	B2	10/2006	Bonalle et al.
6,577,238	B1	6/2003	Whitesmith et al.	7,123,149	B2	10/2006	Nowak et al.
6,593,887	B2	7/2003	Luk et al.	7,130,668	B2	10/2006	Chang et al.
6,597,680	B1	7/2003	Lindskog et al.	7,131,139	B1	10/2006	Meier
6,607,136	B1	8/2003	Atsmon et al.	7,137,008	B1	11/2006	Hamid et al.
6,628,302	B2	9/2003	White et al.	7,137,012	B1	11/2006	Kamibayashi et al.
6,632,992	B2	10/2003	Hasegawa	7,139,914	B2	11/2006	Arnouse
6,633,981	B1	10/2003	Davis	7,150,045	B2	12/2006	Koelle et al.
6,645,077	B2	11/2003	Rowe	7,155,416	B2	12/2006	Shatford
6,647,417	B1	11/2003	Hunter et al.	7,159,114	B1	1/2007	Zajkowski et al.
6,657,538	B1	12/2003	Ritter	7,159,765	B2	1/2007	Frerking
6,658,566	B1	12/2003	Hazard	7,167,987	B2*	1/2007	Angelo G06F 21/32 713/186
6,667,684	B1	12/2003	Waggamon et al.	7,168,089	B2	1/2007	Nguyen et al.
6,669,096	B1	12/2003	Saphar et al.	7,176,797	B2	2/2007	Zai et al.
6,671,808	B1	12/2003	Abbott et al.	7,191,466	B1	3/2007	Hamid et al.
6,683,954	B1	1/2004	Searle	7,209,955	B1	4/2007	Major et al.
				7,218,944	B2	5/2007	Cromer et al.
				7,225,161	B2	5/2007	Lam et al.
				7,230,908	B2	6/2007	Vanderaar et al.

(56)	References Cited						
	U.S. PATENT DOCUMENTS						
	7,231,068 B2	6/2007	Tibor	7,676,380 B2	3/2010	Graves et al.	
	7,231,451 B2	6/2007	Law et al.	7,689,005 B2	3/2010	Wang et al.	
	7,239,226 B2	7/2007	Berardi et al.	7,706,896 B2	4/2010	Music et al.	
	7,242,923 B2	7/2007	Perera et al.	7,711,152 B1 *	5/2010	Davida	G06F 21/32 382/115
	7,249,177 B1	7/2007	Miller	7,711,586 B2	5/2010	Aggarwal et al.	
	7,272,723 B1	9/2007	Abbott et al.	7,715,593 B1	5/2010	Adams et al.	
	7,277,737 B1	10/2007	Vollmer et al.	7,724,713 B2	5/2010	Del Prado Pavon et al.	
	7,278,025 B2	10/2007	Saito et al.	7,724,717 B2	5/2010	Porras et al.	
	7,283,650 B1	10/2007	Sharma et al.	7,724,720 B2	5/2010	Korpela et al.	
	7,295,119 B2	11/2007	Rappaport et al.	7,764,236 B2	7/2010	Hill et al.	
	7,305,560 B2	12/2007	Giobbi	7,765,164 B1	7/2010	Robinson et al.	
	7,310,042 B2	12/2007	Seifert	7,765,181 B2	7/2010	Thomas et al.	
	7,314,164 B2	1/2008	Bonalle et al.	7,773,754 B2	8/2010	Buer et al.	
	7,317,799 B2	1/2008	Hammersmith et al.	7,774,613 B2	8/2010	Lemke	
	7,319,395 B2	1/2008	Puzio et al.	7,780,082 B2	8/2010	Handa et al.	
	7,330,108 B2	2/2008	Thomas	7,796,551 B1	9/2010	Machiraju et al.	
	7,333,002 B2	2/2008	Bixler et al.	7,813,822 B1 *	10/2010	Hoffberg	H04N 21/44222 700/94
	7,333,615 B1 *	2/2008	Jarboe	7,865,448 B2	1/2011	Pizarro	
			H04L 9/30 380/277	7,865,937 B1	1/2011	White et al.	
	7,336,181 B2	2/2008	Nowak et al.	7,883,003 B2	2/2011	Giobbi et al.	
	7,336,182 B1	2/2008	Baranowski et al.	7,883,417 B2	2/2011	Bruzzese et al.	
	7,337,326 B2	2/2008	Palmer et al.	7,904,718 B2	3/2011	Giobbi et al.	
	7,341,181 B2	3/2008	Bonalle et al.	7,943,868 B2	5/2011	Anders et al.	
	7,342,503 B1	3/2008	Light et al.	7,957,536 B2	6/2011	Nolte	
	7,349,557 B2	3/2008	Tibor	7,961,078 B1	6/2011	Reynolds et al.	
	7,356,393 B1	4/2008	Schlatre et al.	7,984,064 B2	7/2011	Fusari	
	7,356,706 B2	4/2008	Scheurich	7,996,514 B2	8/2011	Baumert et al.	
	7,361,919 B2 *	4/2008	Setlak	8,026,821 B2	9/2011	Reeder et al.	
			G06K 9/00013 250/208.1	8,036,152 B2	10/2011	Brown et al.	
	7,363,494 B2	4/2008	Brainard et al.	8,077,041 B2	12/2011	Stern et al.	
	7,370,366 B2	5/2008	Lacan et al.	8,081,215 B2	12/2011	Kuo et al.	
	7,378,939 B2	5/2008	Sengupta et al.	8,082,160 B2	12/2011	Collins et al.	
	7,380,202 B1	5/2008	Lindhorst et al.	8,089,354 B2	1/2012	Perkins	
	7,382,799 B1	6/2008	Young et al.	8,112,066 B2	2/2012	Ben Ayed	
	7,387,235 B2	6/2008	Gilbert et al.	8,125,624 B2	2/2012	Jones et al.	
	7,401,731 B1	7/2008	Pletz et al.	8,135,624 B1	3/2012	Ramalingam et al.	
	7,404,088 B2	7/2008	Giobbi	8,171,528 B1	5/2012	Brown	
	7,424,134 B2	9/2008	Chou	8,193,923 B2	6/2012	Rork et al.	
	7,437,330 B1	10/2008	Robinson et al.	8,200,980 B1	6/2012	Robinson et al.	
	7,447,911 B2 *	11/2008	Chou	8,215,552 B1	7/2012	Rambadt	
			G06F 21/32 382/115	8,219,129 B2	7/2012	Brown et al.	
	7,448,087 B2	11/2008	Ohmori et al.	8,248,263 B2	8/2012	Shervey et al.	
	7,458,510 B1	12/2008	Zhou	8,258,942 B1	9/2012	Lanzone et al.	
	7,460,836 B2	12/2008	Smith et al.	8,294,554 B2	10/2012	Shoarinejad et al.	
	7,461,444 B2	12/2008	Deaett et al.	8,296,573 B2	10/2012	Bolle et al.	
	7,464,053 B1 *	12/2008	Pylant	8,307,414 B2	11/2012	Zerfos et al.	
			G06Q 30/06 705/35	8,325,011 B2	12/2012	Butler et al.	
	7,464,059 B1	12/2008	Robinson et al.	8,340,672 B2 *	12/2012	Brown	H04W 72/0446 455/443
	7,466,232 B2	12/2008	Neuwirth	8,352,730 B2	1/2013	Giobbi	
	7,472,280 B2	12/2008	Giobbi	8,373,562 B1 *	2/2013	Heinze	G06Q 10/06 340/572.1
	7,512,806 B2	3/2009	Lemke	8,387,124 B2	2/2013	Smetters et al.	
	7,525,413 B2	4/2009	Jung et al.	8,390,456 B2	3/2013	Puleston et al.	
	7,529,944 B2	5/2009	Hamid	8,395,484 B2	3/2013	Fullerton	
	7,533,809 B1	5/2009	Robinson et al.	8,410,906 B1 *	4/2013	Dacus	G06K 19/0701 340/10.1
	7,545,312 B2	6/2009	Kiang et al.	8,412,949 B2	4/2013	Giobbi et al.	
	7,565,329 B2	7/2009	Lapsley et al.	8,421,606 B2	4/2013	Collins et al.	
	7,573,382 B2	8/2009	Choubey et al.	8,424,079 B2	4/2013	Adams et al.	
	7,573,841 B2	8/2009	Lee et al.	8,432,262 B2	4/2013	Talty et al.	
	7,574,734 B2	8/2009	Fedronic et al.	8,433,919 B2	4/2013	Giobbi et al.	
	7,583,238 B2	9/2009	Cassen et al.	8,448,858 B1	5/2013	Kundu et al.	
	7,583,643 B2	9/2009	Smith et al.	8,457,672 B2	6/2013	Brown et al.	
	7,587,502 B2	9/2009	Crawford et al.	8,473,748 B2	6/2013	Sampas	
	7,587,611 B2	9/2009	Johnson et al.	8,484,696 B2	7/2013	Gatto et al.	
	7,594,611 B1	9/2009	Arrington, III	8,494,576 B1 *	7/2013	Bye	G07C 9/00571 455/550.1
	7,595,765 B1	9/2009	Hirsch et al.	8,508,336 B2	8/2013	Giobbi et al.	
	7,603,564 B2	10/2009	Adachi	8,511,555 B2	8/2013	Babcock et al.	
	7,606,733 B2	10/2009	Shmueli et al.	8,519,823 B2 *	8/2013	Rinkes	G06K 7/0008 340/7.32
	7,617,523 B2	11/2009	Das et al.	8,522,019 B2	8/2013	Michaelis	
	7,620,184 B2	11/2009	Marque Pucheu	8,558,699 B2 *	10/2013	Butler	G06K 7/0008 340/572.1
	7,624,073 B1	11/2009	Robinson et al.				
	7,624,417 B2	11/2009	Dua				
	7,640,273 B2	12/2009	Wallmeier et al.				
	7,644,443 B2	1/2010	Matsuyama et al.				
	7,646,307 B2	1/2010	Plocher et al.				
	7,652,892 B2	1/2010	Shiu et al.				

(56)		References Cited					
U.S. PATENT DOCUMENTS							
8,572,391	B2 *	10/2013	Golan	G06F 21/40	2001/0027439	A1	10/2001 Holtzman et al.
				713/183	2001/0044337	A1	11/2001 Rowe et al.
8,577,091	B2 *	11/2013	Ivanov	G06K 9/00013	2002/0004783	A1	1/2002 Paltenghe et al.
				382/115	2002/0007456	A1	1/2002 Peinado et al.
8,646,042	B1 *	2/2014	Brown	G06Q 20/363	2002/0010679	A1	1/2002 Felsher
				726/3	2002/0013772	A1	1/2002 Peinado
8,659,427	B2	2/2014	Brown et al.		2002/0014954	A1	2/2002 Fitzgibbon et al.
8,678,273	B2	3/2014	McNeal		2002/0015494	A1	2/2002 Nagai et al.
8,717,346	B2	5/2014	Claessen		2002/0019811	A1	2/2002 Lapsley et al.
8,738,925	B1	5/2014	Park et al.		2002/0022455	A1	2/2002 Salokannel et al.
8,799,574	B2	8/2014	Corda		2002/0023032	A1	2/2002 Pearson et al.
8,838,993	B2	9/2014	Giobbi et al.		2002/0023217	A1 *	2/2002 Wheeler G06Q 20/02
8,856,539	B2	10/2014	Weiss				713/171
8,857,716	B1	10/2014	Giobbi et al.		2002/0026424	A1	2/2002 Akashi
8,886,954	B1	11/2014	Giobbi		2002/0037732	A1	3/2002 Gous et al.
8,907,861	B2	12/2014	Hirt		2002/0052193	A1	5/2002 Chetty
8,914,477	B2	12/2014	Gammon		2002/0055908	A1	5/2002 Di Giorgio et al.
8,918,854	B1	12/2014	Giobbi		2002/0056043	A1	5/2002 Glass
8,931,698	B2	1/2015	Ishikawa et al.		2002/0059114	A1 *	5/2002 Cockrill G06Q 20/04
8,979,646	B2	3/2015	Moser et al.				705/26.81
9,020,854	B2	4/2015	Giobbi		2002/0062249	A1	5/2002 Iannacci
9,037,140	B1	5/2015	Brown		2002/0068605	A1	6/2002 Stanley
9,042,819	B2	5/2015	Dua		2002/0069364	A1	6/2002 Dosch
9,049,188	B1	6/2015	Brown		2002/0071559	A1	6/2002 Christensen et al.
9,113,464	B2	8/2015	Brown et al.		2002/0073042	A1	6/2002 Maritzen et al.
9,165,233	B2	10/2015	Testanero		2002/0080969	A1	6/2002 Giobbi
9,189,788	B1 *	11/2015	Robinson	G06Q 20/4016	2002/0083178	A1	6/2002 Brothers
9,230,399	B2	1/2016	Yacenda		2002/0083318	A1	6/2002 Larose
9,235,700	B1	1/2016	Brown		2002/0086690	A1	7/2002 Takahashi et al.
9,251,326	B2	2/2016	Giobbi et al.		2002/0089890	A1	7/2002 Fibranz et al.
9,251,332	B2	2/2016	Giobbi		2002/0091646	A1	7/2002 Lake et al.
9,265,043	B2	2/2016	Brown et al.		2002/0095586	A1 *	7/2002 Doyle G06F 21/32
9,265,450	B1	2/2016	Giobbi				713/186
9,269,221	B2	2/2016	Brown et al.		2002/0095587	A1 *	7/2002 Doyle G07F 7/1008
9,276,914	B2	3/2016	Woodward et al.				713/186
9,298,905	B1	3/2016	Giobbi		2002/0097876	A1	7/2002 Harrison
9,305,312	B2	4/2016	Kountotsis et al.		2002/0098888	A1	7/2002 Rowe et al.
9,322,974	B1	4/2016	Giobbi		2002/0100798	A1	8/2002 Farrugia et al.
9,405,898	B2	8/2016	Giobbi		2002/0103027	A1	8/2002 Rowe et al.
9,418,205	B2	8/2016	Giobbi		2002/0103881	A1	8/2002 Granade et al.
9,450,956	B1	9/2016	Giobbi		2002/0104006	A1 *	8/2002 Boate H04L 63/0853
9,542,542	B2	1/2017	Giobbi et al.				713/186
9,613,483	B2	4/2017	Giobbi		2002/0104019	A1	8/2002 Chatani et al.
9,679,289	B1	6/2017	Brown		2002/0105918	A1	8/2002 Yamada et al.
9,728,080	B1	8/2017	Giobbi et al.		2002/0108049	A1	8/2002 Xu et al.
9,807,091	B2	10/2017	Giobbi		2002/0109580	A1	8/2002 Shreve et al.
9,830,504	B2	11/2017	Masood et al.		2002/0111919	A1	8/2002 Weller et al.
9,892,250	B2	2/2018	Giobbi		2002/0112183	A1	8/2002 Baird et al.
9,904,816	B1	2/2018	Giobbi et al.		2002/0116615	A1	8/2002 Nguyen et al.
9,990,628	B2	6/2018	Giobbi		2002/0124251	A1	9/2002 Hunter et al.
10,026,253	B2	7/2018	Giobbi		2002/0128017	A1	9/2002 Virtanen
10,073,960	B1	9/2018	Brown		2002/0129262	A1	9/2002 Kutaragi et al.
10,110,385	B1	10/2018	Rush et al.		2002/0138438	A1	9/2002 Bardwell
10,171,460	B2	1/2019	Giobbi		2002/0138767	A1	9/2002 Hamid et al.
10,217,339	B1	2/2019	Giobbi		2002/0140542	A1	10/2002 Prokoski et al.
10,229,294	B1	3/2019	Giobbi et al.		2002/0141586	A1	10/2002 Margalit et al.
10,313,336	B2	6/2019	Giobbi		2002/0143623	A1	10/2002 Dayley
10,334,541	B1	6/2019	Brown		2002/0143655	A1	10/2002 Elston et al.
10,374,795	B1	8/2019	Giobbi et al.		2002/0144116	A1 *	10/2002 Giobbi H04N 21/4627
10,383,112	B2	8/2019	Brown et al.				713/188
10,403,128	B2	9/2019	Giobbi et al.		2002/0144117	A1	10/2002 Faigle
10,437,976	B2	10/2019	Giobbi		2002/0147653	A1	10/2002 Shmueli et al.
10,455,533	B2	10/2019	Brown		2002/0148892	A1	10/2002 Bardwell
10,469,456	B1	11/2019	Giobbi		2002/0150282	A1	10/2002 Kinsella
10,698,989	B2	6/2020	Giobbi		2002/0152391	A1	10/2002 Willins et al.
10,764,044	B1	9/2020	Giobbi et al.		2002/0153996	A1	10/2002 Chan et al.
10,769,939	B2	9/2020	Brown et al.		2002/0158121	A1	10/2002 Stanford-Clark
10,817,964	B2	10/2020	Guillama et al.		2002/0158750	A1	10/2002 Almalik
10,909,229	B2	2/2021	Giobbi		2002/0158765	A1	10/2002 Pape et al.
10,943,471	B1	3/2021	Giobbi et al.		2002/0160820	A1	10/2002 Winkler
2001/0000535	A1	4/2001	Lapsley et al.		2002/0174348	A1	11/2002 Ting
2001/0021950	A1	9/2001	Hawley et al.		2002/0177460	A1	11/2002 Beasley et al.
2001/0024428	A1	9/2001	Onouchi		2002/0178063	A1	11/2002 Gravelle et al.
2001/0026619	A1	10/2001	Howard et al.		2002/0184208	A1	12/2002 Kato
2001/0027121	A1	10/2001	Boesen		2002/0187746	A1	12/2002 Cheng et al.
					2002/0191816	A1	12/2002 Maritzen et al.
					2002/0196963	A1	12/2002 Bardwell
					2002/0199120	A1	12/2002 Schmidt
					2003/0022701	A1	1/2003 Gupta

(56)		References Cited						
U.S. PATENT DOCUMENTS								
2003/0034877	A1	2/2003	Miller et al.	2004/0090345	A1	5/2004	Hitt	
2003/0036416	A1	2/2003	Pattabiraman et al.	2004/0098597	A1	5/2004	Giobbi	
2003/0036425	A1	2/2003	Kaminkow et al.	2004/0114563	A1	6/2004	Shvodian	
2003/0046228	A1	3/2003	Berney	2004/0117644	A1*	6/2004	Colvin	G06F 21/121
2003/0046237	A1*	3/2003	Uberti					713/193
				2004/0123106	A1	6/2004	D'Angelo et al.	
2003/0046552	A1	3/2003	Hamid	2004/0123127	A1	6/2004	Teicher et al.	
2003/0048174	A1	3/2003	Stevens et al.	2004/0127277	A1	7/2004	Walker et al.	
2003/0051173	A1*	3/2003	Krueger	2004/0128162	A1	7/2004	Schlotterbeck et al.	
				2004/0128389	A1	7/2004	Kopchik	
2003/0054868	A1	3/2003	Paulsen et al.	2004/0128500	A1	7/2004	Cihula et al.	
2003/0054881	A1	3/2003	Hedrick et al.	2004/0128508	A1	7/2004	Wheeler et al.	
2003/0055689	A1	3/2003	Block et al.	2004/0128519	A1	7/2004	Klinger et al.	
2003/0055792	A1	3/2003	Kinoshita et al.	2004/0129787	A1	7/2004	Saito et al.	
2003/0061172	A1*	3/2003	Robinson	2004/0132432	A1	7/2004	Moore et al.	
				2004/0137912	A1	7/2004	Lin	
				2004/0153649	A1	8/2004	Rhoads et al.	
2003/0063619	A1	4/2003	Montano et al.	2004/0158746	A1	8/2004	Hu et al.	
2003/0079133	A1	4/2003	Breiter et al.	2004/0166875	A1	8/2004	Jenkins et al.	
2003/0087601	A1	5/2003	Agam et al.	2004/0167465	A1*	8/2004	Mihai	A61B 5/411
2003/0088441	A1	5/2003	McNerney					604/67
2003/0105719	A1	6/2003	Berger et al.	2004/0181695	A1	9/2004	Walker	
2003/0109274	A1	6/2003	Budka et al.	2004/0193925	A1	9/2004	Safriel	
2003/0115351	A1	6/2003	Giobbi	2004/0194133	A1	9/2004	Ikeda et al.	
2003/0115474	A1	6/2003	Khan et al.	2004/0203566	A1	10/2004	Leung	
2003/0117969	A1	6/2003	Koo et al.	2004/0203923	A1	10/2004	Mullen	
2003/0117980	A1	6/2003	Kim et al.	2004/0208139	A1	10/2004	Iwamura	
2003/0120934	A1*	6/2003	Ortiz	2004/0209690	A1	10/2004	Bruzzese et al.	
				2004/0209692	A1	10/2004	Schober et al.	
				2004/0214582	A1	10/2004	Lan et al.	
2003/0127511	A1	7/2003	Kelly et al.	2004/0215615	A1	10/2004	Larsson et al.	
2003/0128866	A1	7/2003	McNeal	2004/0217859	A1	11/2004	Pucci et al.	
2003/0137404	A1	7/2003	Bonneau et al.	2004/0218581	A1	11/2004	Cattaneo	
2003/0139190	A1	7/2003	Steelberg et al.	2004/0222877	A1	11/2004	Teramura et al.	
2003/0146835	A1	8/2003	Carter	2004/0230488	A1	11/2004	Beenau et al.	
2003/0149744	A1	8/2003	Bierre et al.	2004/0230809	A1	11/2004	Lowensohn et al.	
2003/0156742	A1	8/2003	Witt et al.	2004/0234117	A1	11/2004	Tibor	
2003/0159040	A1	8/2003	Hashimoto et al.	2004/0243519	A1	12/2004	Perttila et al.	
2003/0163388	A1	8/2003	Beane	2004/0246103	A1	12/2004	Zukowski	
2003/0167207	A1	9/2003	Berardi et al.	2004/0246950	A1	12/2004	Parker et al.	
2003/0169697	A1	9/2003	Suzuki et al.	2004/0250074	A1	12/2004	Kilian-Kehr	
2003/0172028	A1*	9/2003	Abell	2004/0252012	A1	12/2004	Beenau et al.	
				2004/0252659	A1	12/2004	Yun et al.	
				2004/0253996	A1	12/2004	Chen et al.	
2003/0172037	A1	9/2003	Jung et al.	2004/0254837	A1	12/2004	Roshkoff	
2003/0174839	A1	9/2003	Yamagata et al.	2004/0255139	A1	12/2004	Giobbi	
2003/0176218	A1	9/2003	Lemay et al.	2004/0255145	A1	12/2004	Chow	
2003/0177102	A1	9/2003	Robinson	2005/0001028	A1	1/2005	Zuili	
2003/0186739	A1	10/2003	Paulsen et al.	2005/0002028	A1	1/2005	Kasapi et al.	
2003/0195842	A1	10/2003	Reece	2005/0005136	A1	1/2005	Chen et al.	
2003/0199267	A1	10/2003	Iwasa et al.	2005/0006452	A1	1/2005	Aupperle et al.	
2003/0204526	A1	10/2003	Salehi-Had	2005/0009517	A1	1/2005	Maes	
2003/0213840	A1	11/2003	Livingston et al.	2005/0021561	A1	1/2005	Noonan	
2003/0223394	A1	12/2003	Parantainen et al.	2005/0025093	A1	2/2005	Yun et al.	
2003/0225703	A1*	12/2003	Angel	2005/0028168	A1	2/2005	Marcjan	
				2005/0035897	A1	2/2005	Perl et al.	
				2005/0039027	A1	2/2005	Shapiro	
2003/0226031	A1	12/2003	Proudler et al.	2005/0040961	A1	2/2005	Tuttle	
2003/0233458	A1	12/2003	Kwon et al.	2005/0044372	A1	2/2005	Aull et al.	
2004/0002347	A1	1/2004	Hocter et al.	2005/0044387	A1	2/2005	Ozolins	
2004/0015403	A1	1/2004	Moskowitz et al.	2005/0047386	A1	3/2005	Yi	
2004/0022384	A1	2/2004	Flores et al.	2005/0049013	A1	3/2005	Chang et al.	
2004/0029620	A1	2/2004	Karaoguz	2005/0050208	A1*	3/2005	Chatani	G06Q 20/3672
2004/0029635	A1	2/2004	Giobbi					709/229
2004/0030764	A1	2/2004	Birk et al.	2005/0050324	A1	3/2005	Corbett et al.	
2004/0030894	A1	2/2004	Labrou et al.	2005/0054431	A1	3/2005	Walker et al.	
2004/0035644	A1	2/2004	Ford et al.	2005/0055242	A1	3/2005	Bello et al.	
2004/0039909	A1	2/2004	Cheng	2005/0055244	A1	3/2005	Mullan et al.	
2004/0044627	A1	3/2004	Russell et al.	2005/0058292	A1	3/2005	Diorio et al.	
2004/0048570	A1	3/2004	Oba et al.	2005/0074126	A1	4/2005	Stanko	
2004/0048609	A1	3/2004	Kosaka	2005/0076242	A1	4/2005	Breuer	
2004/0059682	A1	3/2004	Hasumi et al.	2005/0081040	A1	4/2005	Johnson et al.	
2004/0059912	A1	3/2004	Zizzi	2005/0084137	A1	4/2005	Kim et al.	
2004/0064728	A1	4/2004	Scheurich	2005/0086115	A1	4/2005	Pearson	
2004/0068656	A1	4/2004	Lu	2005/0086515	A1	4/2005	Paris	
2004/0073792	A1	4/2004	Noble et al.	2005/0089000	A1	4/2005	Bae et al.	
2004/0081127	A1	4/2004	Gardner et al.	2005/0090200	A1	4/2005	Karaoguz et al.	
2004/0082385	A1	4/2004	Silva et al.	2005/0091338	A1	4/2005	De La Huerga	
				2005/0091553	A1	4/2005	Chien et al.	

(56)		References Cited					
		U.S. PATENT DOCUMENTS					
2005/0094657	A1	5/2005	Sung et al.	2006/0014430	A1	1/2006	Liang et al.
2005/0097037	A1*	5/2005	Tibor H04L 63/0861 705/39	2006/0022042	A1	2/2006	Smets et al.
2005/0105600	A1	5/2005	Culum et al.	2006/0022046	A1	2/2006	Iwamura
2005/0105734	A1*	5/2005	Buer H04W 4/021 380/270	2006/0022800	A1	2/2006	Krishna et al.
2005/0108164	A1	5/2005	Salafia et al.	2006/0025180	A1	2/2006	Rajkotia et al.
2005/0109836	A1	5/2005	Ben-Aissa	2006/0026673	A1	2/2006	Tsuchida
2005/0109841	A1	5/2005	Ryan et al.	2006/0030279	A1	2/2006	Leabman
2005/0113070	A1	5/2005	Okabe	2006/0030353	A1	2/2006	Jun
2005/0114149	A1	5/2005	Rodriguez et al.	2006/0034250	A1	2/2006	Kim et al.
2005/0114150	A1	5/2005	Franklin	2006/0041746	A1	2/2006	Kirkup et al.
2005/0116020	A1	6/2005	Smolucha et al.	2006/0046664	A1	3/2006	Paradiso et al.
2005/0117530	A1	6/2005	Abraham et al.	2006/0058102	A1	3/2006	Nguyen et al.
2005/0119979	A1	6/2005	Murashita et al.	2006/0063575	A1	3/2006	Gatto et al.
2005/0124294	A1	6/2005	Wentink	2006/0064605	A1	3/2006	Giobbi
2005/0125258	A1	6/2005	Yellin et al.	2006/0069814	A1	3/2006	Abraham et al.
2005/0137977	A1	6/2005	Wankmueller	2006/0072586	A1	4/2006	Callaway et al.
2005/0138390	A1	6/2005	Adams et al.	2006/0074713	A1	4/2006	Conry et al.
2005/0138576	A1	6/2005	Baumert et al.	2006/0076401	A1	4/2006	Frerking
2005/0139656	A1	6/2005	Arnouse	2006/0078176	A1*	4/2006	Abiko G06K 9/00026 382/124
2005/0141451	A1	6/2005	Yoon et al.	2006/0087407	A1	4/2006	Stewart et al.
2005/0152394	A1	7/2005	Cho	2006/0089138	A1	4/2006	Smith et al.
2005/0154897	A1	7/2005	Holloway et al.	2006/0097949	A1	5/2006	Luebke et al.
2005/0161503	A1*	7/2005	Remery G06Q 20/341 235/380	2006/0110012	A1	5/2006	Ritter
2005/0165684	A1*	7/2005	Jensen G06Q 20/40145 705/44	2006/0111955	A1	5/2006	Winter et al.
2005/0166063	A1	7/2005	Huang	2006/0113381	A1	6/2006	Hochstein et al.
2005/0167482	A1*	8/2005	Ramachandran .. G06Q 30/0609 235/379	2006/0116935	A1	6/2006	Evans
2005/0169292	A1	8/2005	Young	2006/0117013	A1	6/2006	Wada
2005/0177716	A1	8/2005	Ginter et al.	2006/0120287	A1	6/2006	Foti et al.
2005/0180385	A1	8/2005	Jeong et al.	2006/0129838	A1	6/2006	Chen et al.
2005/0182661	A1	8/2005	Allard et al.	2006/0136728	A1	6/2006	Gentry et al.
2005/0182975	A1	8/2005	Guo et al.	2006/0136742	A1	6/2006	Giobbi
2005/0187792	A1	8/2005	Harper	2006/0143441	A1	6/2006	Giobbi
2005/0192748	A1	9/2005	Andric et al.	2006/0144943	A1	7/2006	Kim
2005/0195975	A1*	9/2005	Kawakita H04L 9/0825 380/30	2006/0156027	A1	7/2006	Blake
2005/0200453	A1	9/2005	Turner et al.	2006/0158308	A1	7/2006	McMullen et al.
2005/0201389	A1	9/2005	Shimanuki et al.	2006/0163349	A1	7/2006	Neugebauer
2005/0203682	A1	9/2005	Omino et al.	2006/0165060	A1	7/2006	Dua
2005/0203844	A1	9/2005	Ferguson et al.	2006/0169771	A1	8/2006	Brookner
2005/0210270	A1	9/2005	Rohatgi et al.	2006/0170530	A1	8/2006	Nwosu et al.
2005/0212657	A1*	9/2005	Simon G06F 21/32 340/5.74	2006/0170565	A1	8/2006	Husak et al.
2005/0215233	A1	9/2005	Perera et al.	2006/0172700	A1	8/2006	Wu
2005/0216313	A1	9/2005	Claud et al.	2006/0173846	A1	8/2006	Omae et al.
2005/0216639	A1	9/2005	Sparer et al.	2006/0173991	A1	8/2006	Piikivi
2005/0218215	A1	10/2005	Lauden	2006/0183426	A1	8/2006	Graves et al.
2005/0220046	A1	10/2005	Falck et al.	2006/0183462	A1	8/2006	Kolehmainen
2005/0221869	A1	10/2005	Liu et al.	2006/0184795	A1*	8/2006	Doradla H04L 63/08 713/167
2005/0229007	A1	10/2005	Bolle et al.	2006/0185005	A1	8/2006	Graves et al.
2005/0229240	A1	10/2005	Nanba	2006/0187029	A1	8/2006	Thomas
2005/0242921	A1	11/2005	Zimmerman et al.	2006/0190348	A1	8/2006	Ofer et al.
2005/0243787	A1	11/2005	Hong et al.	2006/0190413	A1	8/2006	Harper
2005/0249385	A1	11/2005	Kondo et al.	2006/0194598	A1	8/2006	Kim et al.
2005/0251688	A1	11/2005	Nanavati et al.	2006/0195576	A1	8/2006	Rinne et al.
2005/0253683	A1	11/2005	Lowe	2006/0198337	A1	9/2006	Hoang et al.
2005/0257102	A1	11/2005	Moyer et al.	2006/0200467	A1	9/2006	Ohmori et al.
2005/0264416	A1	12/2005	Maurer	2006/0205408	A1	9/2006	Nakagawa et al.
2005/0268111	A1	12/2005	Markham	2006/0208066	A1	9/2006	Finn et al.
2005/0269401	A1*	12/2005	Spitzer G06Q 20/341 235/380	2006/0208853	A1	9/2006	Kung et al.
2005/0272403	A1	12/2005	Ryu et al.	2006/0222042	A1	10/2006	Teramura et al.
2005/0281215	A1	12/2005	Budampati et al.	2006/0226950	A1	10/2006	Kanou et al.
2005/0281320	A1	12/2005	Neugebauer	2006/0229909	A1	10/2006	Kaila et al.
2005/0282558	A1	12/2005	Choi et al.	2006/0236373	A1	10/2006	Graves et al.
2005/0284932	A1	12/2005	Sukeda et al.	2006/0237528	A1	10/2006	Bishop et al.
2005/0287985	A1	12/2005	Balfanz et al.	2006/0238305	A1	10/2006	Loving et al.
2005/0288069	A1	12/2005	Arunan et al.	2006/0268891	A1	11/2006	Heidari-Bateni et al.
2005/0289473	A1	12/2005	Gustafson et al.	2006/0273176	A1	12/2006	Audebert et al.
2006/0001525	A1	1/2006	Nitzan et al.	2006/0274711	A1	12/2006	Nelson et al.
				2006/0279412	A1	12/2006	Holland et al.
				2006/0286969	A1	12/2006	Talmor et al.
				2006/0288095	A1	12/2006	Torok et al.
				2006/0288233	A1	12/2006	Kozlay
				2006/0290580	A1	12/2006	Noro et al.
				2006/0293925	A1	12/2006	Flom
				2006/0294388	A1	12/2006	Abraham et al.
				2007/0003111	A1	1/2007	Awatsu et al.
				2007/0005403	A1	1/2007	Kennedy et al.
				2007/0007331	A1	1/2007	Jasper et al.
				2007/0008070	A1	1/2007	Friedrich

(56)

References Cited

U.S. PATENT DOCUMENTS							
2007/0008916	A1	1/2007	Haugli et al.	2007/0271194	A1	11/2007	Walker et al.
2007/0011724	A1	1/2007	Gonzalez et al.	2007/0271433	A1	11/2007	Takemura
2007/0016800	A1	1/2007	Spottswood et al.	2007/0277044	A1	11/2007	Graf et al.
2007/0019845	A1	1/2007	Kato	2007/0280509	A1	12/2007	Owen et al.
2007/0029381	A1	2/2007	Braiman	2007/0285212	A1	12/2007	Rotzoll
2007/0032225	A1	2/2007	Konicek et al.	2007/0285238	A1	12/2007	Batra
2007/0032288	A1	2/2007	Nelson et al.	2007/0288263	A1	12/2007	Rodgers
2007/0033072	A1	2/2007	Bildirici	2007/0288752	A1	12/2007	Chan
2007/0033150	A1*	2/2007	Nwosu G06Q 20/40145	2007/0293155	A1	12/2007	Liao et al.
			705/76	2007/0294755	A1	12/2007	Dadhia et al.
2007/0036396	A1	2/2007	Sugita et al.	2007/0296544	A1	12/2007	Beenau et al.
2007/0038751	A1	2/2007	Jorgensen	2008/0001783	A1	1/2008	Cargonja et al.
2007/0043594	A1	2/2007	Lavergne	2008/0005432	A1	1/2008	Kagawa
2007/0050259	A1	3/2007	Wesley	2008/0008359	A1	1/2008	Beenau et al.
2007/0050398	A1	3/2007	Mochizuki	2008/0011842	A1	1/2008	Curry et al.
2007/0051794	A1	3/2007	Glanz et al.	2008/0012685	A1	1/2008	Friedrich et al.
2007/0051798	A1	3/2007	Kawai et al.	2008/0012767	A1	1/2008	Caliri et al.
2007/0055630	A1*	3/2007	Gauthier G06Q 20/204	2008/0016004	A1	1/2008	Kurasaki et al.
			705/44	2008/0019578	A1	1/2008	Saito et al.
2007/0060095	A1	3/2007	Subrahmanya et al.	2008/0028227	A1	1/2008	Sakurai
2007/0060319	A1	3/2007	Block et al.	2008/0028453	A1	1/2008	Nguyen et al.
2007/0064742	A1	3/2007	Shvodian	2008/0046366	A1	2/2008	Bemmel et al.
2007/0069852	A1	3/2007	Mo et al.	2008/0046715	A1	2/2008	Balazs et al.
2007/0070040	A1	3/2007	Chen et al.	2008/0049700	A1	2/2008	Shah et al.
2007/0072636	A1	3/2007	Worfolk et al.	2008/0061941	A1	3/2008	Fischer et al.
2007/0073553	A1	3/2007	Flinn et al.	2008/0071577	A1	3/2008	Highley
2007/0084523	A1	4/2007	McLean et al.	2008/0072063	A1	3/2008	Takahashi et al.
2007/0084913	A1*	4/2007	Weston G06Q 20/3224	2008/0088475	A1	4/2008	Martin
			235/380	2008/0090548	A1	4/2008	Ramalingam
2007/0087682	A1	4/2007	Dacosta	2008/0095359	A1	4/2008	Schreyer et al.
2007/0087834	A1	4/2007	Moser et al.	2008/0107089	A1	5/2008	Larsson et al.
2007/0100507	A1	5/2007	Simon	2008/0109895	A1	5/2008	Janevski
2007/0100939	A1	5/2007	Bagley et al.	2008/0111752	A1	5/2008	Lindackers et al.
2007/0109117	A1	5/2007	Heitzmann et al.	2008/0127176	A1	5/2008	Lee et al.
2007/0112676	A1	5/2007	Kontio et al.	2008/0129450	A1	6/2008	Riegebauer
2007/0118891	A1	5/2007	Buer	2008/0148351	A1	6/2008	Bhatia et al.
2007/0120643	A1	5/2007	Lee	2008/0149705	A1	6/2008	Giobbi et al.
2007/0132586	A1	6/2007	Plocher et al.	2008/0150678	A1	6/2008	Giobbi et al.
2007/0133478	A1	6/2007	Armbruster et al.	2008/0156866	A1	7/2008	McNeal
2007/0136407	A1	6/2007	Rudelic	2008/0164997	A1	7/2008	Aritsuka et al.
2007/0142032	A1	6/2007	Balsillie	2008/0169909	A1	7/2008	Park et al.
2007/0152826	A1	7/2007	August et al.	2008/0186166	A1	8/2008	Zhou et al.
2007/0156850	A1	7/2007	Corrion	2008/0188308	A1	8/2008	Shepherd et al.
2007/0157249	A1	7/2007	Cordray et al.	2008/0195863	A1	8/2008	Kennedy
2007/0158411	A1	7/2007	Krieg, Jr.	2008/0201768	A1	8/2008	Koo et al.
2007/0159301	A1	7/2007	Hirt et al.	2008/0203107	A1	8/2008	Conley et al.
2007/0159994	A1	7/2007	Brown et al.	2008/0209571	A1	8/2008	Bhaskar et al.
2007/0164847	A1	7/2007	Crawford et al.	2008/0218416	A1	9/2008	Handy et al.
2007/0169121	A1	7/2007	Hunt et al.	2008/0222701	A1	9/2008	Saaranen et al.
2007/0174809	A1	7/2007	Brown et al.	2008/0223918	A1	9/2008	Williams et al.
2007/0176756	A1	8/2007	Friedrich	2008/0228524	A1	9/2008	Brown
2007/0176778	A1	8/2007	Ando et al.	2008/0235144	A1	9/2008	Phillips
2007/0180047	A1	8/2007	Dong et al.	2008/0238625	A1	10/2008	Rofougaran et al.
2007/0187266	A1	8/2007	Porter et al.	2008/0250388	A1	10/2008	Meyer et al.
2007/0192601	A1	8/2007	Spain et al.	2008/0251579	A1	10/2008	Larsen
2007/0194882	A1	8/2007	Yokota et al.	2008/0278325	A1	11/2008	Zimman et al.
2007/0198436	A1	8/2007	Weiss	2008/0289030	A1	11/2008	Poplett
2007/0204078	A1	8/2007	Boccon-Gibod et al.	2008/0289032	A1	11/2008	Aoki et al.
2007/0205860	A1	9/2007	Jones et al.	2008/0303637	A1	12/2008	Gelbman et al.
2007/0205861	A1	9/2007	Nair et al.	2008/0313728	A1	12/2008	Pandurangi et al.
2007/0207750	A1	9/2007	Brown et al.	2008/0314971	A1*	12/2008	Faith G06Q 20/322
2007/0213048	A1	9/2007	Trauberg				235/379
2007/0214492	A1	9/2007	Gopi et al.	2008/0316045	A1	12/2008	Srihartho et al.
2007/0218921	A1	9/2007	Lee et al.	2009/0002134	A1	1/2009	McAllister
2007/0219926	A1	9/2007	Korn	2009/0013191	A1	1/2009	Popowski
2007/0220272	A1	9/2007	Campisi et al.	2009/0016573	A1	1/2009	McAfee et al.
2007/0229268	A1	10/2007	Swan et al.	2009/0024584	A1	1/2009	Dharap et al.
2007/0245157	A1	10/2007	Giobbi et al.	2009/0033464	A1	2/2009	Friedrich
2007/0245158	A1	10/2007	Giobbi et al.	2009/0033485	A1	2/2009	Naevae et al.
2007/0247366	A1	10/2007	Smith et al.	2009/0036164	A1	2/2009	Rowley
2007/0258626	A1	11/2007	Reiner	2009/0041309	A1	2/2009	Kim et al.
2007/0260883	A1	11/2007	Giobbi et al.	2009/0045916	A1	2/2009	Nitzan et al.
2007/0260888	A1	11/2007	Giobbi et al.	2009/0052389	A1	2/2009	Qin et al.
2007/0266257	A1	11/2007	Camaisa et al.	2009/0070146	A1	3/2009	Haider et al.
2007/0268862	A1	11/2007	Singh et al.	2009/0076849	A1	3/2009	Diller
				2009/0081996	A1	3/2009	Duggal et al.
				2009/0096580	A1	4/2009	Paananen
				2009/0121890	A1	5/2009	Brown et al.
				2009/0125401	A1	5/2009	Beenau et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

- 2009/0140045 A1 6/2009 Evans
 2009/0157512 A1 6/2009 King
 2009/0165123 A1 6/2009 Giobbi
 2009/0176566 A1 7/2009 Kelly
 2009/0177495 A1 7/2009 Abousy et al.
 2009/0195461 A1 8/2009 Hirt
 2009/0199206 A1 8/2009 Finkenzeller et al.
 2009/0206992 A1 8/2009 Giobbi et al.
 2009/0237245 A1 9/2009 Brinton et al.
 2009/0237253 A1 9/2009 Neuwirth
 2009/0239667 A1 9/2009 Rowe et al.
 2009/0253516 A1 10/2009 Hartmann et al.
 2009/0254971 A1 10/2009 Herz et al.
 2009/0264712 A1 10/2009 Baldus et al.
 2009/0310514 A1 12/2009 Jeon et al.
 2009/0313689 A1 12/2009 Nystroem et al.
 2009/0319788 A1 12/2009 Zick et al.
 2009/0320118 A1 12/2009 Mueller et al.
 2009/0322510 A1 12/2009 Berger et al.
 2009/0328182 A1 12/2009 Malakapalli et al.
 2010/0005526 A1 1/2010 Tsuji et al.
 2010/0007498 A1 1/2010 Jackson
 2010/0022308 A1 1/2010 Hartmann et al.
 2010/0023074 A1 1/2010 Powers et al.
 2010/0037255 A1 2/2010 Sheehan et al.
 2010/0062743 A1 3/2010 Jonsson
 2010/0077214 A1 3/2010 Jogand-Coulomb et al.
 2010/0117794 A1 5/2010 Adams et al.
 2010/0134257 A1 6/2010 Puleston et al.
 2010/0169442 A1 7/2010 Liu et al.
 2010/0169964 A1 7/2010 Liu et al.
 2010/0172567 A1 7/2010 Prokoski
 2010/0174911 A1 7/2010 Isshiki
 2010/0188226 A1 7/2010 Seder et al.
 2010/0214100 A1 8/2010 Page
 2010/0277283 A1 11/2010 Burkart et al.
 2010/0277286 A1 11/2010 Burkart et al.
 2010/0291896 A1 11/2010 Corda
 2010/0305843 A1 12/2010 Yan et al.
 2010/0328033 A1 12/2010 Kamei
 2011/0072034 A1 3/2011 Sly et al.
 2011/0072132 A1 3/2011 Shafer et al.
 2011/0082735 A1 4/2011 Kannan et al.
 2011/0085287 A1 4/2011 Ebrom et al.
 2011/0091136 A1 4/2011 Danch et al.
 2011/0116358 A9 5/2011 Li et al.
 2011/0126188 A1 5/2011 Bernstein et al.
 2011/0221568 A1 9/2011 Giobbi
 2011/0227740 A1 9/2011 Wohltjen
 2011/0238517 A1 9/2011 Ramalingam et al.
 2011/0246790 A1 10/2011 Koh et al.
 2011/0266348 A1 11/2011 Denniston, Jr.
 2011/0307599 A1 12/2011 Saretto et al.
 2012/0028609 A1 2/2012 Hruska
 2012/0030006 A1 2/2012 Yoder et al.
 2012/0069776 A1 3/2012 Caldwell et al.
 2012/0086571 A1 4/2012 Scalisi et al.
 2012/0182123 A1 7/2012 Butler et al.
 2012/0212322 A1 8/2012 Idsoee
 2012/0226451 A1 9/2012 Bacot et al.
 2012/0226565 A1 9/2012 Drozd
 2012/0226907 A1 9/2012 Hohberger et al.
 2012/0238287 A1 9/2012 Scherzer
 2012/0278188 A1 11/2012 Attar et al.
 2012/0300753 A1 11/2012 Brown et al.
 2012/0310720 A1 12/2012 Balsan et al.
 2013/0019295 A1 1/2013 Park et al.
 2013/0019323 A1 1/2013 Arvidsson et al.
 2013/0044111 A1 2/2013 Vangilder et al.
 2013/0111543 A1 5/2013 Brown et al.
 2013/0135082 A1 5/2013 Xian et al.
 2013/0179201 A1 7/2013 Fuerstenberg et al.
 2013/0219186 A1 8/2013 Giobbi et al.
 2013/0276140 A1 10/2013 Coffing et al.
 2013/0297514 A1 11/2013 Giobbi
 2013/0315210 A1 11/2013 Brown et al.
 2013/0331063 A1 12/2013 Cormier et al.
 2014/0074696 A1 3/2014 Glaser
 2014/0147018 A1 5/2014 Argue et al.
 2014/0266604 A1 9/2014 Masood et al.
 2014/0266713 A1 9/2014 Sehgal et al.
 2014/0337920 A1 11/2014 Giobbi
 2015/0026480 A1 1/2015 Giobbi et al.
 2015/0039451 A1 2/2015 Bonfiglio
 2015/0294293 A1 10/2015 Signarsson
 2015/0310385 A1 10/2015 King et al.
 2015/0310440 A1 10/2015 Hynes et al.
 2016/0133123 A1 5/2016 Giobbi et al.
 2016/0171200 A1 6/2016 Giobbi
 2016/0203349 A1 7/2016 Giobbi
 2016/0205682 A1 7/2016 Brown et al.
 2016/0210614 A1 7/2016 Hall
 2016/0300236 A1 10/2016 Wiley et al.
 2016/0306956 A1 10/2016 Giobbi
 2017/0041315 A1 2/2017 Giobbi
 2017/0085564 A1 3/2017 Giobbi et al.
 2017/0091548 A1 3/2017 Agrawal et al.
 2017/0270738 A1 9/2017 Giobbi
 2017/0309165 A1 10/2017 Brown et al.
 2018/0019998 A1 1/2018 Giobbi
 2018/0129799 A1 5/2018 Giobbi
 2018/0322718 A1 11/2018 Qian et al.
 2018/0357475 A1 12/2018 Honda et al.
 2019/0065721 A1 2/2019 Giobbi
 2019/0172281 A1 6/2019 Einberg et al.
 2019/0260724 A1 8/2019 Hefetz et al.
 2019/0289562 A1 9/2019 Brown
 2020/0351873 A1 11/2020 Brown et al.

FOREIGN PATENT DOCUMENTS

- WO 99/56429 A1 11/1999
 WO 00/62505 A1 10/2000
 WO 01/22724 A1 3/2001
 WO 01/35334 A1 5/2001
 WO 01/75876 A1 10/2001
 WO 01/77790 A1 10/2001
 WO 2004/010774 A1 2/2004
 WO 2004/038563 A2 5/2004
 WO WO-2005031663 A2 * 4/2005 G06Q 20/327
 WO 2005/050450 A1 6/2005
 WO 2005/086802 A2 9/2005
 WO 2007/087558 A2 8/2007

OTHER PUBLICATIONS

- Machine translation of JPH10049604, 27 pages.
 McIver et al., "Identification and Verification Working Together," Bioscrypt, White Paper: Identification and Verification Working Together, Aug. 27, 2004, retrieved from www.ibia.org/membersadmin/whitepapers/pdf/15/Identification%20and%20Verification%20Working%20Together.pdf on Jan. 7, 2007, 5 pgs.
 Micronas, "Micronas and Thomson Multimedia Showcase a New Copy Protection System that Will Drive the Future of Digital Television," Jan. 8, 2002, retrieved from www.micronas.com/press/pressreleases/printer.php?ID=192 on Mar. 4, 2002, 3 pgs.
 Muller, "Desktop Encyclopedia of the Internet," 1999, Artech House Inc., Norwood, MA, all pages.
 National Criminal Justice Reference Service, "Antenna Types," Dec. 11, 2006, online at <http://ncjrs.gov/pdffiles1/nij/185030b.pdf>, retrieved from http://web.archive.org/web/*/http://www.ncjrs.gov/pdffiles1/nij/185030b.pdf on Jan. 12, 2011, 1 pg.
 Nel et al., "Generation of Keys for use with the Digital Signature Standard (DSS)," Communications and Signal Processing, Proceedings of the 1993 IEEE South African Symposium, Aug. 6, 1993, pp. 6-11.
 Nerd Vittles, "magicJack: Could It Be the Asterisk Killer?" Aug. 1, 2007, retrieved from <http://nerdvittles.com/index.php?p=187> on or before Oct. 11, 2011, 2 pgs.
 Nilsson et al., "Match-on-Card for Java Cards," Precise Biometrics, white paper, Apr. 2004, retrieved from www.ibia.org/membersadmin/

(56)

References Cited

OTHER PUBLICATIONS

whitepapers/pdf/17/Precise%20Match-on-Card%20for%20Java%20Cards.pdf on Jan. 7, 2007, 5 pgs.

Noore, "Highly Robust Biometric Smart Card Design." IEEE Transactions on Consumer Electronics, vol. 46, No. 4, Nov. 2000, pp. 1059-1063.

Nordin, "Match-on-Card Technology," Precise Biometrics, white paper, Apr. 2004, retrieved from www.ibia.org/membersadmin/whitepapers/pdf/17/Precise%20Match-on-Card%20technology.pdf on Jan. 7, 2007, 7 pgs.

Paget, "The Security Behind Secure Extranets," Enterprise Systems Journal, vol. 14, No. 12, Dec. 1999, 4 pgs.

Pash, "Automate proximity and location-based computer actions," Jun. 5, 2007, retrieved from <http://lifelifehacker.com/265822/automate-proximity-and-location-based-computer-actionson> or before Oct. 11, 2011, 3 pgs.

Pope et al., "Oasis Digital Signature Services: Digital Signing without the Headaches," IEEE Internet Computing, vol. 10, Sep./Oct. 2006, pp. 81-84.

SAFLINK Corporation, "SAFModule™: A Look Into Strong Authentication," white paper, retrieved from www.ibia.org/membersadmin/whitepapers/pdf/6/SAFmod_WP.pdf on Jan. 7, 2007, 8 pgs.

Sapsford, "E-Business: Sound Waves Could Help Ease Web-Fraud Woes," Wall Street Journal, Aug. 14, 2000, p. B1.

Singh et al., "A Constraint-Based Biometric Scheme on ATM and Swiping Machine," 2016 International Conference on Computational Techniques in Information and Communication Technologies (ICCTICT), Mar. 11, 2016, pp. 74-79.

Smart Card Alliance, "Contactless Technology for Secure Physical Access: Technology and Standards Choices," Smart Card Alliance, Oct. 2002, pp. 1-48.

Smart Card Alliance, "Smart Cards and Biometrics White Paper: Smart Card Alliance," May 2002, retrieved from http://www.securitymanagement.com/library/smartcard_faqte-ch0802.pdf on Jan. 7, 2007, 7 pgs.

Smart Card Alliance, "Alliance Activities: Publications: Identity Management Systems, Smart Cards and Privacy," 1997-2007, retrieved from www.smartcardalliance.org/pages/publications-identity on Jan. 7, 2007, 3 pgs.

SplashID, "SplashID—Secure Password Manager for PDA's and Smartphones," Mar. 8, 2007, retrieved from <http://www.splashdata.com/splashid/> via <http://www.archive.org/> on or before Oct. 11, 2011, 2 pgs.

Srivastava, "Is Internet security a major issue with respect to the slow acceptance rate of digital signatures," Jan. 2, 2005, Computer Law & Security Report, pp. 392-404.

Thomson Multimedia, "Thomson multimedia unveils copy protection proposal designed to provide additional layer of digital content security," retrieved from www.thomson-multimedia.com/gb/06/c01/010530.htm on Mar. 4, 2002, May 30, 2001, 2 pgs.

Unixhelp, "What is a file?" Apr. 30, 1998, retrieved from unixhelp.ed.ac.uk/editors/whatisafile.html accessed on Mar. 11, 2010, via http://waybackmachine.org/19980615000000*/http://unixhelp.ed.ac.uk/editors/whatisafile.html on Mar. 11, 2011, 1 pg.

Vainio, "Bluetooth Security," Helsinki University of Technology, May 25, 2000, 17 pgs.

Van Winkle, "Bluetooth: The King of Connectivity," Laptop Buyer's Guide and Handbook, Jan. 2000, pp. 148-153.

Wade, "Using Fingerprints to Make Payments at POS Slowly Gaining Popularity," Credit Union Journal, International Biometric Group, Apr. 21, 2003, retrieved from http://www.biometricgroup.com/in_the_news/04.21.03.html on Jan. 7, 2007, 3 pgs.

Wallace, "The Internet Unplugged," InformationWeek, vol. 765, No. 22, Dec. 13, 1999, pp. 22-24.

Weber, "In the Age of Napster, Protecting Copyright is a Digital Arms Race," Wall Street Journal, Jul. 24, 2000, B1, 2 pgs.

White, "How Computers Work," Millennium Edition, 1999, Que Corporation, Indianapolis, IN, all pages.

Yoshida, "Content Protection Plan Targets Wireless Home Networks," EE Times, Jan. 11, 2002, retrieved from www.eetimes.com/story/OEG20020111S0060 on Mar. 4, 2002, 2 pgs.

Anonymous, "Applying Biometrics to Door Access," Security Magazine, Sep. 26, 2002, retrieved from http://www.securitymagazine.com/CDA/Articles/Technologies/3ae610eaa34d8010VgnVCM100000f932a8c0_ on Jan. 7, 2007, 5 pgs.

Anonymous, "Firecrest Shows How Truly Commercially-Minded Companies Will Exploit the Internet," Computergram International, Jan. 18, 1996, 2 pgs.

Anonymous, "IEEE 802.15.4-2006—Wikipedia, the free encyclopedia," Wikipedia, last modified Mar. 21, 2009, retrieved from http://en.wikipedia.org/wiki/IEEE_802.15.4-2006 on Apr. 30, 2009, 5 pgs.

Antonoff, "Visiting Video Valley," Sound & Vision, Nov. 2001, pp. 116, 118-119.

Apple et al., "Smart Card Setup Guide," 2006, downloaded from http://manuals.info.apple.com/en_US/Smart_Card_Setup_Guide.pdf on or before May 3, 2012, 16 pgs.

Balanis, "Antenna Theory: A Review," Jan. 1992, Proceedings of the IEEE, vol. 80, No. 1, p. 13.

Beaufour, "Personal Servers as Digital Keys," Proceedings of the Second IEEE Annual Conference on Pervasive Computing and Communications (PERCOM'04), Mar. 14-17, 2004, pp. 319-328.

Biopay, LLC, "Frequently Asked Questions (FAQs) About BioPay," retrieved from <http://www.biopay.com/faqs-lowes.asp> on Jan. 7, 2007, 5 pgs.

Blueproximity, "BlueProximity—Leave it—it's locked, come back, it's back too . . ." Aug. 26, 2007, retrieved from <http://blueproximity.sourceforge.net/viahttp://www.archive.org/> on or before Oct. 11, 2011, 1 pg.

Bluetooth Sig, Inc., "Bluetooth," www.bluetooth.com, Jun. 1, 2000, 8 pgs.

Bluetooth Sig, Inc., "Say Hello to Bluetooth," retrieved from www.bluetooth.com, at least as early as Jan. 14, 2005, 4 pgs.

Blum, "Digital Rights Management May Solve the Napster 'Problem,'" Technology Investor, Oct. 2000, pp. 24-27.

Bohrsatom et al., "Automatically unlock PC when entering proximity," Dec. 7, 2005, retrieved from <http://salling.com/forums/viewtopic.php?t=3190> on or before Oct. 11, 2011, 3 pgs.

Brown, "Techniques for Privacy and Authentication in Personal Communication Systems," Personal Communications, IEEE, Aug. 1995, vol. 2, No. 4, pp. 6-10.

Chen et al., "On Enhancing Biometric Authentication with Data Protection," KES2000, Fourth International Conference on Knowledge-Based Intelligent Engineering Systems and Allied Technologies Proceedings (Cat. No. 00TH8516), vol. 1, Aug. 1, 2000, pp. 249-252.

Cisco Systems, Inc., "Antenna Patterns and Their Meaning," 1992-2007, p. 10.

Costa, "Imation USB 2.0 Micro Hard Drive," Nov. 22, 2005, retrieved from <http://www.pcmag.com/article2/0,2817,1892209,00.asp> on or before Oct. 11, 2011, 2 pgs.

Dagan, "Power over Ethernet (PoE) Midspan—The Smart Path to Providing Power for IP Telephony," Product Manager, Systems, Aug. 2005, Power Dsine Inc., 28 pgs.

Dai et al., "Toward Blockchain-Based Accounting and Assurance," Journal of Information Systems, vol. 31, No. 3, Fall 2017, pp. 5-21.

Debow, "Credit/Debit Debuts in Midwest Smart Card Test," Computers in Banking, vol. 6, No. 11, Nov. 1989, pp. 10-13.

Dennis, "Digital Passports Need Not Infringe Civil Liberties," Newsbytes, NA, Dec. 2, 1999, 2 pgs.

Derfler, "How Networks Work," Bestseller Edition, 1996, Ziff-Davis Press, Emeryville, CA, all pages.

Farouk et al., "Authentication Mechanisms in Grid Computing Environment: Comparative Study," IEEE, Oct. 2012, pp. 1-6.

Fasca, "S3, Via Formalize Agreement," Electronic News, The Circuit, 45(45, Nov. 8, 1999), p. 20.

Giobbi, Specification of U.S. Appl. No. 60/824,758, filed Sep. 6, 2006, all pages.

Govindan et al. "Real Time Security Management Using RFID, Biometric and Smart Messages." 2009 3rd International Conference

(56)

References Cited

OTHER PUBLICATIONS

on Anti-Counterfeiting, Security, and Identification in Communication, Aug. 20, 2009, pp. 282-285.

Gralla, "How the Internet works," Millennium Edition, 1999, Que Corporation, Indianapolis, IN, all pages.

Hendron, "File Security, Keychains, Encryption, and More with Mac OS X (10.3+)" Apr. 4, 2005, downloaded from http://www.johnhendron.net/documents/OSX_Security.pdf on or before May 3, 2012, 30 pgs.

IEEE Computer Society, "IEEE Std 802.15.4™-Part 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks (LR-WPANs)," The Institute of Electrical and Electronics Engineers, Inc., New York, NY, Oct. 1, 2003, 679 pgs.

International Search Report and Written Opinion for International Application No. PCT/US04/38124, dated Apr. 7, 2005, 10 pgs.

International Search Report and Written Opinion for International Application No. PCT/US05/00349, dated Mar. 19, 2008, 10 pgs.

International Search Report and Written Opinion for International Application No. PCT/US05/07535, dated Dec. 6, 2005, 6 pgs.

International Search Report and Written Opinion for International Application No. PCT/US05/43447, dated Feb. 22, 2007, 7 pgs.

International Search Report and Written Opinion for International Application No. PCT/US05/46843, dated Mar. 1, 2007, 10 pgs.

International Search Report and Written Opinion for International Application No. PCT/US07/11102, dated Oct. 3, 2008, 11 pgs.

International Search Report and Written Opinion for International Application No. PCT/US07/11103, dated Apr. 23, 2008, 9 pgs.

International Search Report and Written Opinion for International Application No. PCT/US07/11104, dated Jun. 26, 2008, 9 pgs.

International Search Report and Written Opinion for International Application No. PCT/US07/11105, dated Oct. 20, 2008, 10 pgs.

International Search Report and Written Opinion for International Application No. PCT/US08/83060, dated Dec. 29, 2008, 9 pgs.

International Search Report and Written Opinion for International Application No. PCT/US08/87835, dated Feb. 11, 2009, 8 pgs.

International Search Report and Written Opinion for International Application No. PCT/US09/34095, dated Mar. 25, 2009, 11 pgs.

International Search Report and Written Opinion for International Application No. PCT/US2009/039943, dated Jun. 1, 2009, 9 pgs.

International Search Report and Written Opinion for International Application No. PCT/US2014/037609, dated Dec. 9, 2014, 13 pgs.

International Search Report for International Patent Application No. PCT/US2001/049916, dated Apr. 25, 2002, 1 pg.

Jeyaprakash et al., "Secured Smart Card Using Palm Vein Biometric On-Card-Process," 2008 International Conference on Convergence and Hybrid Information Technology, 2008, pp. 548-551.

Katz et al., "Smart Cards and Biometrics in Privacy-Sensitive Secure Personal Identification System," May 2002, Smart Card Alliance, p. 1-29.

Kontzer, "Thomson Bets on Smart Cards for Video Encryption," www.informationweek.com, Jun. 7, 2001, 1 pg.

Lake, "Downloading for Dollars: Who said buying music off the Net would be easy?" *Sound & Vision*, Nov. 2000, pp. 137-138.

Lee et al., "Effects of dielectric superstrates on a two-layer electromagnetically coupled patch antenna," *Antennas and Propagation Society International Symposium*, Jun. 1989, AP-S. Digest, vol. 2, pp. 26-30, found at <http://ieeexplore.ieee.org/stamp/stamp.jsp?tp=&arnumber=1347>.

Lewis, "Sony and Visa in On-Line Entertainment Venture," *New York Times*, vol. 145, Thurs. Ed., Nov. 16, 1995, 1 pg.

Schneier, *Applied Cryptography, Second Edition: Protocols, Algorithms, and Source Code in C*, Jan. 1, 1996, John Wiley & Sons, Inc., 1027 pgs.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7B




FIG. 7A




FIG. 7C




FIG. 7D




FIG. 8




FIG. 9




FIG. 10

1002/1004




FIG. 11

1006




FIG. 12




FIG. 13




FIG. 14

**PERSONAL DIGITAL KEY INITIALIZATION
AND REGISTRATION FOR SECURE
TRANSACTIONS**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a continuation of and claims priority to U.S. application Ser. No. 16/503,066, entitled "Personal Digital Key Initialization and Registration for Secure Transactions," filed on Jul. 3, 2019, which is a continuation of U.S. application Ser. No. 14/986,306, entitled, "Personal Digital Key Initialization and Registration for Secure Transactions," filed on Dec. 31, 2015, which is a continuation of U.S. application Ser. No. 14/448,891, entitled, "Personal Digital Key Initialization and Registration for Secure Transactions," filed on Jul. 31, 2014, which is a continuation of U.S. application Ser. No. 13/791,553, entitled, "Personal Digital Key Initialization and Registration for Secure Transactions," filed on Mar. 8, 2013, which is a continuation of U.S. application Ser. No. 11/744,832, entitled "Personal Digital Key Initialization and Registration for Secure Transactions" filed, May 5, 2007, which claims the benefit of U.S. Provisional Application No. 60/798,172 entitled "Touch Pay" filed on May 5, 2006; U.S. Provisional Application No. 60/798,843 entitled "Touch Pay" filed on May 8, 2006; U.S. Provisional Application No. 60/838,788 entitled "Personal Digital Key Accessible Storage Device and Processor" filed on Aug. 17, 2006; U.S. Provisional Application No. 60/824,758 entitled "Truprox Touch Technology" filed on Sep. 6, 2006; and U.S. Provisional Application No. 60/894,608 entitled "TruProx Stored-Photo Extension" filed on Mar. 13, 2007, the entire contents of which are all herein incorporated by reference.

Applicants hereby notify the USPTO that the claims of the present application are different from those of the aforementioned related applications. Therefore, Applicant rescinds any disclaimer of claim scope made in the parent application or any other predecessor application in relation to the present application. The Examiner is therefore advised that any such disclaimer and the cited reference that it was made to avoid may need to be revisited at this time. Furthermore, the Examiner is also reminded that any disclaimer made in the present application should not be read into or against the parent application, the grandparent application or any other related application.

BACKGROUND

1. Field of Art

The invention generally relates to electronic authentication, and more specifically, to secure authentication using biometric verification. In particular, the present invention relates to the initialization and registration of personal digital keys.

2. Description of the Related Art

Optimizing sales transactions and providing secure access to physical and/or digital assets are challenges faced by many businesses and organizations. Ensuring these processes are safe, efficient and simple is important to merchants, providers, users and consumers alike. Conventionally, technologies such as magnetic cards (e.g., credit cards, debit cards, ATM cards, and employee badges) have been used in attempt to address these needs. More recently,

various contactless cards or tokens requiring placement near compatible readers have been used.

Each of these technologies, however, has inherent problems in providing secure transaction processing and access control. In particular, the conventional technologies fail to sufficiently ensure that individuals attempting to perform a transaction are associated with the access device and are authorized to do so. Conventional attempts to address this issue include requiring users to provide Personal Identification Numbers (PINs) or passwords in conjunction with account numbers. While in some instances, these options have helped to combat fraudulent activity, these solutions add unwanted complexity and delay to transactions. With the growing need to memorize various PINs and passwords, individuals tend to repeatedly use the same, simple phrase to protect many items, or worse, keep the written phrases in their purse/wallet or next to their computer. Thus, the use of PINs and passwords are often defeated.

A technology better suited to address the issue of authenticating users is biometrics. In biometric authentication, physical and/or behavioral characteristics of an individual are analyzed to uniquely identify the individual. For example, biometric characteristics can include fingerprint, retinal, iris, face, palm, DNA, voice or signature characteristics that can each be uniquely associated with the individual. However, traditional biometric authentication solutions also suffer from significant problems. First, traditional biometric authentication techniques typically expose the participating parties to serious liabilities, risks and inefficiencies. Conventional biometric authentication techniques nearly always require users to release personal, private and unchangeable data to a controlling-entity (e.g., a merchant or business authority) or to a third-party relied upon by the controlling-entity. This exposes an individual's personal biometric information to the possibility of theft and fraudulent use. Further, controlling entities must either assume the risks and liabilities of storing this data, or trust the data to a third-party's care.

Second, conventional biometric authentication techniques generally require an individual to submit biometric information (e.g., a fingerprint, retinal scan, facial scan, or signature) for storage in a database that can then be later used for comparison with biometric data acquired at the point of transaction. This "enrollment" process is time-consuming, risky, error-prone and considered intrusive by many individuals. Further, the enrollment process must be repeated for each individual for every intended use. For example, a user may need to enroll for biometric authentication with his/her company (e.g., for secure access to facilities or digital files), and separately enroll with various merchants using biometric authentication for transactions. Thus, the individual has to spend significant time completing each separate enrollment, and additionally must trust each entity with his/her personal biometric information. For these reasons alone many individuals do not even consider these options.

The above-defined issues represent serious roadblocks to the widespread deployment and acceptance of conventional biometric authentication options. Unless the identified deficiencies are addressed, the full potential of biometric solutions will never be realized. Therefore, a new technology is needed that provides highly reliable, safe and efficient secure authentication for transaction-processing and/or access control. Moreover, the new technology should allow for a simple and efficient enrollment process that does not put an individual's highly personal information at risk of identity theft or other fraudulent use.

SUMMARY

A system and method provide efficient, secure and highly reliable authentication for transaction processing and/or access control applications. A portable physical device, referred to herein as a Personal Digital Key or “PDK”, stores one or more profiles (e.g., a biometric profile) in a tamper-proof memory. The biometric profile is acquired in a secure trusted process and is uniquely associated with an individual that is authorized to use and is associated with the PDK. The PDK can wirelessly transmit the identification information including a unique PDK identification number and the biometric profile over a secure wireless channel for use in an authentication process. Additionally, the PDK can store other information such as credit/debit card information, bank information, or personal information in a memory for use in authorizing or completing a transaction.

Typically, a receiving device, referred to herein as a Reader, wirelessly receives the profile from the PDK in order to process a transaction or provide access to secure digital or physical assets. In one embodiment, the Reader acquires a biometric input from the individual carrying the PDK at the point of transaction. The biometric input can be acquired by, for example, a fingerprint scan, iris scan, retinal scan, palm scan, face scan, DNA analysis, signature analysis, voice analysis or any other input mechanism that provides physical or behavioral characteristics uniquely associated with the individual. The Reader compares the biometric profile received from the PDK to the biometric input obtained at the point of transaction to determine if a transaction should be authorized.

In one embodiment, the Reader is further adapted to communicate with one or more remote registries to provide an additional layer of security in the authentication process. Information transmitted from the PDK can be compared to entries stored in the registries to ensure the PDK (and its owner) have not participated in any fraudulent use and that the PDK is not invalid, lost or stolen. In yet another embodiment, one or more biometric authentications, remote registry authentications or other types of authentication are used in combination.

The PDK is programmed by a programming device referred to herein as a “Programmer” during initialization and registration processes. In one embodiment, the programming process is witnessed and authenticated by a specialized trusted Notary. In one embodiment of the initialization process, the Programmer is communicatively coupled with a PDK from the user and a PDK from the Notary. Information is read from the user PDK to determine if the PDK is authorized for initialization and Notary information is read from the Notary PDK to determine if the Notary is authorized to perform the initialization. If both the user and the Notary are authorized, the Programmer prompts the user to provide a biometric input. The Notary witnesses the biometric acquisition process either in person or remotely to ensure the information can be trusted. The Programmer then writes biometric profile data to a memory in the user PDK. In one embodiment, the Programmer does not store the personal biometric data.

In registration, the Programmer communicates to the Central Registry and/or one or more private entries to create or update entries associated with the user PDK. Registration allows the PDK owner to be authenticated for transactions requiring registry authentication. A registry entry may include, for example, a unique PDK ID, purchasing information associated with the user and personal information associated with the user.

The initialization and registration processes further enhance security by storing initialization/registration history data to both the user PDK and the Programmer memory. This data includes, for example, the user PDK ID, the Notary PDK ID, the programmer ID, a site ID, or other information associated with programming including software revisions, checksums and other metrics intended to verify the current software versions used in both the Programmer and the PDK. The history can be recalled in the future for auditing purposes.

The features and advantages described in the specification are not all inclusive and, in particular, many additional features and advantages will be apparent to one of ordinary skill in the art in view of the drawings, specification, and claims. Moreover, it should be noted that the language used in the specification has been principally selected for readability and instructional purposes, and may not have been selected to delineate or circumscribe the inventive subject matter.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a high level block diagram illustrating a system for secure electronic authentication.

FIG. 2 is a block diagram illustrating one embodiment of a Personal Digital Key (PDK).

FIG. 3 is a block diagram illustrating one embodiment of a Reader.

FIG. 4 is a flowchart illustrating one embodiment of a process for authorizing a transaction using secure authentication.

FIG. 5 is a flowchart illustrating one embodiment of a process for device authentication by a Reader.

FIG. 6 is a flowchart illustrating one embodiment of a process for profile authentication by a Reader.

FIG. 7A is a flowchart illustrating one embodiment of a process for profile testing using a biometric input.

FIG. 7B is a flowchart illustrating one embodiment of a process for profile testing using a personal identification number.

FIG. 7C is a flowchart illustrating one embodiment of a process for profile testing using a picture profile.

FIG. 7D is a flowchart illustrating one embodiment of a process for profile testing using a private or central registry.

FIG. 8 is a high level block diagram illustrating a system for initializing and registering a PDK for use in secure electronic authentication.

FIG. 9 is a block diagram illustrating one embodiment of a Programmer for programming a PDK.

FIG. 10 is a flowchart illustrating one embodiment of a process for PDK initialization.

FIG. 11 is a flowchart illustrating one embodiment of a process for validating a PDK for initialization.

FIG. 12 is a flowchart illustrating one embodiment of a process for acquiring biometric information for PDK initialization.

FIG. 13 is a flowchart illustrating one embodiment of a process for writing initialization data.

FIG. 14 is a flowchart illustrating one embodiment of a process for registering a PDK with a registry.

The figures depict various embodiments of the present invention for purposes of illustration only. One skilled in the art will readily recognize from the following discussion that alternative embodiments of the structures and methods illus-

trated herein may be employed without departing from the principles of the invention described herein.

DETAILED DESCRIPTION

FIG. 1 is a high level block diagram illustrating a system for securely authenticating an individual for transaction-processing and/or access control applications. The system 100 comprises a Personal Digital Key (PDK) 102, a Reader 108, a network 110 and one or more external databases including a validation database 112, a Central Registry 114 and one or more private registries 116. The Reader 108 is coupled to the PDK 102 by a wireless link 106 and coupled to a network 110 by either a wired or wireless link. The Reader 108 is also adapted to receive a biometric input 104 from a user and is capable of displaying status to a user. The network 110 couples the validation database 112, the Central Registry 114 and two private registries 116 to the Reader 108. In alternative embodiments, different or additional external registries or databases may be coupled to the network 110. In another embodiment, the Reader 108 operates as a standalone device without a connection to the network 110.

The system 100 addresses applications where it is important to ensure a specific individual is authorized to perform a given transaction. A transaction as used herein can include executing a purchase or financial dealing, enabling access to physical and/or digital items, verifying identification or personal information or executing other tasks where it is important to authenticate an individual for use. Generally, the Reader 108 wirelessly receives information stored in the PDK 102 that uniquely identifies the PDK 102 and the individual carrying the PDK 102. The Reader 108 can also receive a biometric input 104 from the individual. Based on the received information, the Reader 108 determines if the transaction should be authorized. Beneficially, the system 100 provides comprehensive authentication without the need for PINs or passwords. Moreover, personal biometric information need not be stored in any local or remote storage database and is only stored on the user's own PDK. Furthermore, in one embodiment, purchase transactions can be efficiently completed without requiring the use of physical credit cards, tokens or other user action beyond initiating the transaction.

The credibility of the system 100 is ensured by the use of a PDK 102 that stores trusted information. The PDK 102 is a compact, portable uniquely identifiable wireless device typically carried by an individual. The PDK 102 stores digital information in a tamper-proof format that uniquely associates the PDK 102 with an individual. Example embodiments of PDKs are described in more detail in U.S. patent application Ser. No. 11/292,330, entitled "Personal Digital Key And Receiver/Decoder Circuit System And Method" filed on Nov. 30, 2005; U.S. patent application Ser. No. 11/620,581 entitled "Wireless Network Synchronization Of Cells And Client Devices On A Network" filed on Jan. 5, 2007; and U.S. patent application Ser. No. 11/620,577 entitled "Dynamic Real-Time Tiered Client Access" filed on Jan. 5, 2007, the entire contents of which are all incorporated herein by reference.

To establish the trust, credibility and confidence of the authentication system, information stored in the PDK 102 is acquired by a process that is trusted, audited and easily verified. The process is ensured by a trusted third-party system, referred to herein as a Notary, that administers the acquisition and storage of information in the PDK 102 according to defined security protocols. In one embodiment,

the Notary is a system and/or a trusted individual that witnesses the acquisition and storage either in person or remotely. In another embodiment, the Notary comprises trusted hardware that administers the initialization process by an automated system. Thus, once initialized by the trusted process, the PDK 102 can prove that the information it stores is that of the individual. Example embodiments of the initialization process are described in more detail below with reference to FIGS. 8-14.

The Reader 108 wirelessly communicates with the PDK 102 when the PDK 102 is within a proximity zone of the Reader 108. The proximity zone can be, for example, several meters in radius and can be adjusted dynamically by the Reader 108. Thus, in contrast to many conventional RF ID devices, the Reader 108 can detect and communicate with the PDK 102 without requiring the owner to remove the PDK 102 from his/her pocket, wallet, purse, etc. Generally, the Reader 108 receives uniquely identifying information from the PDK 102 and initiates an authentication process for the individual carrying the PDK 102. In one embodiment, the Reader 108 is adapted to receive a biometric input 104 from the individual. The biometric input 104 comprises a representation of physical or behavioral characteristics unique to the individual. For example, the biometric input 104 can include a fingerprint, a palm print, a retinal scan, an iris scan, a photograph, a signature, a voice sample or any other biometric information such as DNA, RNA or their derivatives that can uniquely identify the individual. The Reader 108 compares the biometric input 104 to information received from the PDK 102 to determine if a transaction should be authorized. Alternatively, the biometric input 104 can be obtained by a biometric reader on the PDK 102 and transmitted to the Reader 108 for authentication. In additional alternative embodiment, some or all of the authentication process can be performed by the PDK 102 instead of the Reader 108.

The Reader 108 is further communicatively coupled to the network 110 in order to receive and/or transmit information to remote databases for remote authentication. In an alternative embodiment, the Reader 108 includes a non-volatile data storage that can be synchronized with one or more remote databases 112 or registries 114-116. Such an embodiment alleviates the need for a continuous connection to the network 110 and allows the Reader 108 to operate in a standalone mode and for the local data storage to be updated when a connection is available. For example, a standalone Reader 108 can periodically download updated registry entries and perform authentication locally without any remote lookup.

The network 110 provides communication between the Reader 108 and the validation database 112, Central Registry 114 and one or more private registries 116. In alternative embodiments, one or more of these connections may not be present or different or additional network connections may be present. In one embodiment, the network 110 uses standard communications technologies and/or protocols. Thus, the network 110 can include links using technologies such as Ethernet, 802.11, 802.16, integrated services digital network (ISDN), digital subscriber line (DSL), asynchronous transfer mode (ATM), etc. Similarly, the networking protocols used on the network 110 can include the transmission control protocol/Internet protocol (TCP/IP), the hypertext transport protocol (HTTP), the simple mail transfer protocol (SMTP), the file transfer protocol (FTP), etc. The data exchanged over the network 110 can be represented using technologies and/or formats including the hypertext markup language (HTML), the extensible markup language

(XML), etc. In addition, all or some of links can be encrypted using conventional encryption technologies such as the secure sockets layer (SSL), Secure HTTP and/or virtual private networks (VPNs). In another embodiment, the entities can use custom and/or dedicated data communications technologies instead of, or in addition to, the ones described above.

The validation database **112** stores additional information that may be used for authorizing a transaction to be processed at the Reader **108**. For example, in purchase transactions, the validation database **112** is a credit card validation database that is separate from the merchant providing the sale. Alternatively, a different database may be used to validate different types of purchasing means such as a debit card, ATM card, or bank account number.

The registries **114-116** are securely-accessible databases coupled to the network **110** that store, among other items, PDK, Notary, and Reader information. In one embodiment, the registries **114-116** do not store biometric information. In an alternative embodiment, a registry stores biometric information in an encoded format that can only be recovered using an algorithm or encoding key stored in the PDK **102**. Information stored in the registries can be accessed by the Reader **108** via the network **110** for use in the authentication process. There are two basic types of registries illustrated: private registries **116** and the Central Registry **114**. Private registries **116** are generally established and administered by their controlling entities (e.g., a merchant, business authority, or other entity administering authentication). Private registries **116** can be custom configured to meet the specialized and independent needs of each controlling entity. The Central Registry **114** is a single highly-secured, centrally-located database administered by a trusted third-party organization. In one embodiment, all PDKs **102** are registered with the Central Registry **114** and may be optionally registered with one or more selected private registries **116**. In alternative embodiments, a different number or different types of registries may be coupled to the network **110**.

Turning now to FIG. 2, an example embodiment of a PDK **102** is illustrated. The PDK **102** comprises a memory **210**, a programmer I/O **240**, control logic **250**, and a transceiver **260**, coupled by a bus **270**. The PDK **102** can be standalone as a portable, physical device or can be integrated into commonly carried items. For example, a PDK **102** can be integrated into a portable electronic device such as a cell phone, Personal Digital Assistant (PDA), or GPS unit, an employee identification tag, clothing, or jewelry items such as watches, rings, necklaces or bracelets. In one embodiment, the PDK **102** can be, for example, about the size of a Subscriber Identity Module (SIM) card and be as small as a square inch in area or less. In another embodiment, the PDK **102** can be easily contained in a pocket, on a keychain, or in a wallet.

The memory **210** can be a read-only memory, a once-programmable memory, a read/write memory or any combination of memory types including physical access secured and tamperproof memories. The memory **210** typically stores a unique PDK ID **212** and one or more profiles **220**. The PDK ID **212** comprises a public section and a private section of information, each of which can be used for identification and authentication. In one embodiment, the PDK ID **212** is stored in a read-only format that cannot be changed subsequent to manufacture. The PDK ID **212** is used as an identifying feature of a PDK **102** and distinguishes between PDKs **102** in private **116** or Central **114** registry entries. In an alternative embodiment, the registries can identify a PDK **102** by a different ID than the PDK ID

212 stored in the PDK **102**, or may use both the PDK ID **212** and the different ID in conjunction. The PDK ID **212** can also be used in basic PDK authentication to ensure that the PDK **102** is a valid device.

The profile fields **220** can be initially empty at the time of manufacture but can be written to by authorized individuals (e.g., a Notary) and/or hardware (e.g., a Programmer). In one embodiment, each profile **220** comprises a profile history **222** and profile data **230**. Many different types of profiles **220** are possible. A biometric profile, for example, includes profile data **230** representing physical and/or behavioral information that can uniquely identify the PDK owner. A PDK **102** can store multiple biometric profiles, each comprising a different type of biometric information. In one embodiment, the biometric profile **220** comprises biometric information transformed by a mathematical operation, algorithm, or hash that represents the complete biometric information (e.g., a complete fingerprint scan). In one embodiment, a mathematical hash is a “one-way” operation such that there is no practical way to re-compute or recover the complete biometric information from the biometric profile. This both reduces the amount of data to be stored and adds an additional layer of protection to the user’s personal biometric information. In one embodiment, the biometric profile is further encoded using a encoding key and/or algorithm that is stored with the biometric profile data. Then, for authentication, both the biometric profile data and the encoding key and/or algorithm are passed to the Reader **108**.

In one embodiment the PDK **102** also stores one or more biometric profile “samples” associated with each biometric profile. The biometric profile sample is a subset of the complete profile that can be used for quick comparisons of biometric data. In one embodiment, the profile samples can be transmitted over a public communication channel or transmitted with reduced level of encryption while the full biometric profiles are only transmitted over secure channels. In the case of fingerprint authentication, for example, the biometric profile sample may represent only small portion area of the full fingerprint image. In another embodiment, the fingerprint profile sample is data that describes an arc of one or more lines of the fingerprint. In yet another embodiment, the fingerprint profile sample can be data representing color information of the fingerprint.

In another embodiment, the stored profiles **220** include a PIN profile that stores one or more PINs or passwords associated with the PDK owner. Here, the number or password stored in the PIN profile can be compared against an input provided by the user at the point of transaction to authenticate the user. In one embodiment, a PIN profile sample is also stored with the PIN profile that comprises a subset of the full PIN. For example, a PIN profile sample can be only the first two numbers of the PIN that can be used to quickly compare the stored PIN profile to a PIN obtained at the point of transaction.

In yet another embodiment, the PDK **102** stores a picture profile that includes one or more pictures of the PDK owner. In a picture profile authentication, the picture stored in the PDK **102** is transmitted to a display at the point of transaction to allow an administrator (e.g., a clerk or security guard) to confirm or reject the identity of the individual requesting the transaction. In another embodiment, an image is captured of the individual at the point of transaction and compared to the picture profile by an automated image analysis means. Furthermore, picture profiles could be used, for example, in place of conventional passports or drivers licenses to authenticate the identity of an individual and allow for remote identification of individuals. For example,

a police officer following a vehicle could obtain an image and identity of the driver while still maintaining a safe distance from the vehicle. In the hospitality industry, a host could greet a guest at the door of a hotel, casino or restaurant and easily recognize the guest by obtaining the guest's picture profile as he/she enters.

A registry or database profile typically stores information associating the user with a registry. The registry profile can be used to determine if the individual is associated with the controlling entity for that registry and if different types of transactions are authorized for the individual. A registry profile can further include additional user information for use with the registry. For example, a private registry profile associated with a particular merchant may include a credit card number that the user has selected as a default for that merchant. In one embodiment, a profile can further include spending limits that limits the amount of purchases a user can make with a particular vendor or using a particular profile.

A profile can further include personal identification information such as name, address, phone number, etc., bank information, credit/debit card information, or membership information. This information can be useful for certain types of transactions. For example, with purchases that require delivery, a PDK 102 can automatically transmit address information to the Reader 108 at the point of transaction. In one embodiment, a profile can store multiple addresses. At the point of transaction, the Reader 108 displays the address options and allows the user to select which address to use.

Generally, some types of profile information (e.g., a biometric profile) can only be acquired during a trusted initialization process that is administered by a trusted Notary. In one embodiment, other secure information such as credit card information are also stored to the PDK in the presence of a Notary. Alternatively, certain types of low-risk information can be added by the user without a Notary, such as, for example a change of address. In another embodiment, once an initial profile has been stored to the PDK 102, a user can add information to the PDK 102 using a Programmer without a Notary through self-authentication. For example, in one embodiment, a PDK 102 that has a stored biometric profile can be "unlocked" by providing a matching biometric input. Then, once unlocked, the user can add or remove additional profiles, credit cards, personal information, etc. to the PDK 102 using a Programmer. For example, in one embodiment, a user that has unlocked his/her own PDK 102 can store additional biometric information (such as fingerprint information for other fingers) in his/her PDK 102. In another example, a user that cancels a credit card, can unlock his/her PDK 102 to remove the credit card information. In another embodiment, the user can make copies of the PDK 102 or move profiles from one PDK 102 to another once the PDK 102 is unlocked.

The profile history 222 includes a programmer ID field 224, a Notary ID 226, and a site ID field 228. The profile history 222 relates to the specific hardware, Notary, and site used at the time the profile data was created and stored to the PDK. Typically each profile 220 stores its specific profile history 222 along with the profile data 230. The profile history 222 can be recalled for auditing purposes at a later time to ensure the credibility of the stored data. In one embodiment, transaction history can also be stored to the PDK memory 210. Here, the PDK 102 stores information associated with any transactions made with the PDK 102 such as the name of the merchant, the purchase amount, credit card used, etc.

The PDK 102 also includes a programmer I/O 240 that provides an interface to a trusted Programmer (not shown). The Programmer comprises trusted hardware that is used to program the memory 210 of the PDK 102. An example embodiment of a Programmer is described in more detail below with reference to FIG. 9. The programmer I/O 240 can be, for example, a USB interface, serial interface, parallel interface, or any other direct or wireless link for transferring information between the PDK 102 and the Programmer. When coupled to the Programmer, the programmer I/O 240 receives initialization data, registration data or other information to be stored in the memory 210.

The control logic 250 coordinates between functions of the PDK 102. In one embodiment, the control logic 250 facilitates the flow of information between the programmer I/O 240, transceiver 260 and memory 210. The control logic 250 can further process data received from the memories 210, programmer I/O 240 and transceiver 260. Note that the control logic 250 is merely a grouping of control functions in a central architecture, and in other embodiments, the control functions can be distributed between the different modules of the PDK 102. The operation of the control logic will be understood to those skilled in the art based on the description below corresponding to FIGS. 4-7D.

The transceiver 260 is a wireless transmitter and receiver for wirelessly communicating with a Reader 108 or other wireless device. The transceiver 260 can send and receive data as modulated electromagnetic signals. Moreover, the data can be encrypted by the transceiver 260 and transmitted over a secure link. Further, the transceiver 260 can actively send connection requests, or can passively detect connection requests from another wireless source. In one embodiment, the transceiver 260 is used in place of a separate programmer I/O 240 and is used to wirelessly communicate with the Programmer for programming. In one embodiment, the transceiver 260 is adapted to communicate over a range of up to around 5 meters.

Optionally, a PDK 102 can also include a built in biometric reader (not shown) to acquire a biometric input from the user. The biometric input can be used to unlock the PDK 102 for profile updates, or for various types of authentication. For example, in one embodiment, a biometric input is received by the PDK 102 and compared to stored biometric information. Then, if the user is authenticated, the PDK 102 can indicate to the Reader 108 that the user is authenticated and transmit additional information (e.g., a credit card number) needed to complete a transaction.

Turning now to FIG. 3, an example embodiment of a Reader 108 is illustrated. The embodiment includes one or more biometric readers 302, a receiver-decoder circuit (RDC) 304, a processor 306, a network interface 308, an I/O port 312 and optionally a credit card terminal I/O 310. In alternative embodiments, different or additional modules can be included in the Reader 108.

The RDC 304 provides the wireless interface to the PDK 102. Generally, the RDC 304 wirelessly receives data from the PDK 102 in an encrypted format and decodes the encrypted data for processing by the processor 306. An example embodiment of an RDC is described in U.S. patent application Ser. No. 11/292,330 entitled "Personal Digital Key And Receiver/Decoder Circuit System And Method", the entire contents of which are incorporated herein by reference. Encrypting data transmitted between the PDK 102 and Reader 108 minimizes the possibility of eavesdropping or other fraudulent activity. In one embodiment, the RDC 304 is also configured to transmit and receive certain types of information in an unencrypted, or public, format.

The biometric reader **302** receives and processes the biometric input **104** from an individual at the point of transaction. In one embodiment, the biometric reader **302** is a fingerprint scanner. Here, the biometric reader **302** includes an image capture device adapted to capture the unique pattern of ridges and valleys in a fingerprint also known as minutiae. Other embodiments of biometric readers **302** include retinal scanners, iris scanners, facial scanner, palm scanners, DNA/RNA analyzers, signature analyzers, cameras, microphones, and voice analyzers. Furthermore, the Reader **108** can include multiple biometric readers **302** of different types. In one embodiment, the biometric reader **302** automatically computes mathematical representations or hashes of the scanned data that can be compared to the mathematically processed biometric profile information stored in the PDK **102**.

The processor **306** can be any general-purpose processor for implementing a number of processing tasks. Generally, the processor **306** processes data received by the Reader **108** or data to be transmitted by the Reader **108**. For example, a biometric input **104** received by the biometric reader **302** can be processed and compared to the biometric profile **220** received from the PDK **102** in order to determine if a transaction should be authorized. In different embodiments, processing tasks can be performed within each individual module or can be distributed between local processors and a central processor. The processor **306** further includes a working memory for use in various processes such as performing the method of FIGS. 4-7D.

The network interface **308** is a wired or wireless communication link between the Reader **108** and one or more external databases such as, for example, a validation database **112**, the Central Registry **114** or a private registry **116**. For example, in one type of authentication, information is received from the PDK **102** at the RDC **304**, processed by the processor **306**, and transmitted to an external database **112-116** through the network interface **308**. The network interface **308** can also receive data sent through the network **110** for local processing by the Reader **108**. In one embodiment, the network interface **308** provides a connection to a remote system administrator to configure the Reader **108** according to various control settings.

The I/O port **312** provides a general input and output interface to the Reader **108**. The I/O port **312** may be coupled to any variety of input devices to receive inputs such as a numerical or alphabetic input from a keypad, control settings, menu selections, confirmations, and so on. Outputs can include, for example, status LEDs, an LCD, or other display that provides instructions, menus or control options to a user.

The credit card terminal I/O **310** optionally provides an interface to an existing credit card terminal **314**. In embodiments including the credit card terminal I/O **310**, the Reader **108** supplements existing hardware and acts in conjunction with a conventional credit card terminal **314**. In an alternative embodiment, the functions of an external credit card terminal **314** are instead built into the Reader **108**. Here, a Reader **108** can completely replace an existing credit card terminal **314**.

In one embodiment, a Reader **108** is adapted to detect and prevent fraudulent use of PDKs that are lost, stolen, revoked, expired or otherwise invalid. For example, the Reader **108** can download lists of invalid PDKs IDs **212** from a remote database and block these PDKs **102** from use with the Reader **108**. Furthermore, in one embodiment, the Reader **108** can update the blocked list and/or send updates to remote registries **114-116** or remote Readers **108** upon

detecting a fraudulently used PDK **102**. For example, if a biometric input **104** is received by the Reader **108** that does not match the biometric profile received from the PDK **102**, the Reader **108** can obtain the PDK ID **212** and add it to a list of blocked PDK IDs **212**. In another embodiment, upon detecting fraudulent use, the Reader **108** can send a signal to the PDK **102** that instructs the PDK **102** to deactivate itself. The deactivation period can be, for example, a fixed period of time, or until the rightful owner requests re-activation of the PDK **102**. In yet another embodiment, the Reader **108** can send a signal instructing the fraudulently obtained PDK **102** to send alarm signals indicating that the PDK **102** a stolen device. Here, a stolen PDK **102** can be tracked, located and recovered by monitoring the alarm signals. In one embodiment, the Reader **108** stores biometric or other identifying information from an individual that attempts to fraudulently use a PDK **102** so that the individual's identity can be determined.

Generally, the Reader **108** is configured to implement at least one type of authentication prior to enabling a transaction. In many cases, multiple layers of authentication are used. A first layer of authentication, referred to herein as "device authentication", begins any time a PDK **102** moves within range of a Reader **108**. In device authentication, the Reader **108** and the PDK **102** each ensure that the other is valid based on the device characteristics, independent of any profiles stored in the PDK **102**. In some configurations, when fast and simple authentication is desirable, only device authentication is required to initiate the transaction. For example, a Reader **108** may be configured to use only device authentication for low cost purchases under a predefined amount (e.g., \$25). The configuration is also useful in other types of low risk transactions where speed is preferred over additional layers of authentication.

Other configurations of the Reader **108** require one or more additional layers of authentication, referred to herein as "profile authentication" based on one or more profiles stored in the PDK **102**. Profile authentication can include, for example, a biometric authentication, a PIN authentication, a photo authentication, a registry authentication, etc. or any combination of the above authentication types. Profile authentications are useful when a more exhaustive authentication process is desired, for example, for high purchase transactions or for enabling access to classified assets.

FIG. 4 illustrates an example embodiment of a process for secure authentication of a transaction. When a PDK **102** comes within range of a Reader **108**, communication is automatically established **402** between the RDC **304** of the Reader **108** and the PDK **102**. In one embodiment, the RDC **304** continually transmits beacons that are detected by the PDK **102** when it enters a proximity zone of the Reader **108**. In an alternative embodiment, the communication is instead initiated by the PDK **102** and acknowledged by the Reader **108**. Generally, initial communication between the Reader **108** and the PDK **102** is not encrypted in order to provide faster and more power efficient communication.

In step **404**, a device authentication is performed. Here, the Reader **108** establishes if the PDK **102** is a valid device and PDK **102** establishes if the Reader **108** is valid. Furthermore, device authentication determines if the PDK is capable of providing the type of authentication required by the Reader **108**.

An example embodiment of a method for performing **404** device authentication is illustrated in FIG. 5. The RDC **304** receives and analyzes **502** information from the PDK **102**; and the PDK **102** receives and analyzes **502** information received from the RDC **304**. Generally, this initial informa-

tion is transmitted over a public communication channel in an unencrypted format. Based on the received information, each device **102**, **304** determines **504** if the other is valid. As will be apparent to one of ordinary skill in the art, a number of different protocols can be used for this type of authentication such as, for example, a challenge-response authentication or a challenge handshake authentication protocol (CHAP). If either of the devices **102**, **304** is invalid **512**, the process ends. If both the PDK **102** and the RDC **304** are determined by the other to be valid, the Reader **108** requests and receives **506** authentication type information from the PDK **102** indicating the different types of authentication the PDK **102** is capable of satisfying based on the types of profiles the PDK **102** stores. The available profile types in the PDK **102** are compared against the authentication types that can be used by the Reader **108**. For example, a particular Reader **108** may be configured to perform only a fingerprint authentication and therefore any PDK without a fingerprint biometric profile cannot be used with the Reader **108**. In one embodiment, the Reader **108** can allow more than one type of profile to be used. In another embodiment, the Reader **108** requires more than one type of profile for authentication, while in yet further embodiments no profile authentications are required. Next, the method determines **508** whether the PDK **102** has one or more profiles sufficient for authentication. If the PDK **102** does not have one or more profiles sufficient for authentication with the Reader **108**, the devices **102**, **304** are determined to be invalid **512** because they cannot be used with each other. If the PDK **102** does have one or more sufficient types of profiles, the devices are valid **510**.

Turning back to FIG. 4, if either the PDK **102** or RDC **304** is not found valid during device authentication **404**, the transaction is not authorized **418** and the process ends. If the devices are valid, the RDC **304** temporarily buffers **408** the received PDK information. It is noted that in one embodiment, steps **402-408** are automatically initiated each time a PDK **102** enters the proximity zone of the Reader **108**. Thus, if multiple PDKs **102** enter the proximity zone, the Reader **108** automatically determines which PDKs **102** are valid and buffers the received information from each valid PDK **102**.

The method next determines **410** whether profile authentication is required based on the configuration of the Reader **108**, the type of transaction desired or by request of a merchant or other administrator. If the Reader **108** configuration does not require a profile authentication in addition to the PDK authentication, then the Reader **108** proceeds to complete the transaction for the PDK **102**. If the Reader **108** does require profile authentication, the profile authentication is performed **412** as will be described below with references to FIGS. 6-7D. If a required profile is determined **414** to be valid, the Reader **108** completes **416** the transaction. Otherwise, the Reader **108** indicates that the transaction is not authorized **418**. In one embodiment, completing **416** the transaction includes enabling access to secure physical or digital assets (e.g., unlocking a door, opening a vault, providing access to a secured hard drive, etc.). In another embodiment, completing **416** the transaction includes charging a credit card for a purchase. Alternatively, bank information, debit/check/ATM card information, coupon codes, or any other purchasing means information (typically stored in a profile memory field **232**) can be transmitted by the PDK **102** in place of credit card information. In one embodiment, the PDK **102** is configured with multiple purchasing means and a default is configured for different types of transactions. In another embodiment, each credit card or

other purchasing means is displayed to the customer by the Reader **108** and the customer is allowed to select which to use for the transaction.

Turning now to FIG. 6, an embodiment of a process for profile authentication is illustrated. In step **602**, a secure communication channel is established between the RDC **304** and the PDK **102**. Information sent and received over the secure channel is in an encrypted format that cannot be practically decoded, retransmitted, reused, or replayed to achieve valid responses by an eavesdropping device. The Reader **108** transmits **604** profile authentication requests to the PDK **102** requesting transmission of one or more stored profiles over the secure channel. At **608**, the process determines whether a “trigger” is required for authentication. The requirement for a trigger depends on the configuration of the Reader **108**, the specific type of transaction to be executed and the type of authentication requested.

In a first configuration, a trigger is required to continue the process because of the type of authentication being used. For example, in biometric authentication, the authentication process cannot continue until the Reader detects a biometric contact and receives biometric information. It is noted that biometric contact is not limited to physical contact and can be, for example, the touch of a finger to a fingerprint scanner, the positioning of a face in front of a facial or retinal scanner, the receipt of a signature, the detection of a voice, the receipt of a DNA sample, RNA sample, or derivatives or any other action that permits the Reader **108** to begin acquiring the biometric input **104**. By supplying the biometric contact, the user indicates that the authentication and transaction process should proceed. For example, a PDK holder that wants to make a withdrawal from an Automated Teller Machine (ATM) equipped with a Reader **108** initiates the withdrawal by touching a finger to the Reader **108**. The ATM then begins the transaction process for the withdrawal.

In a second configuration, some other user action is required as a trigger to proceed with the transaction even if the authentication process itself doesn’t necessarily require any input. This can be used for many purchasing transactions to ensure that the purchase is not executed until intent to purchase is clear. For example, a Reader **108** at a gas station can be configured to trigger the transaction when a customer begins dispensing gas. At a supermarket, a Reader **108** can be configured to trigger the transaction when items are scanned at a checkout counter.

In a third configuration, no trigger is used and the Reader **108** automatically completes the remaining authentication/transaction with no explicit action by the user. This configuration is appropriate in situations where the mere presence of a PDK **102** within range of the Reader **108** is by itself a clear indication of the PDK owner’s desire to complete a transaction. For example, a Reader **108** can be positioned inside the entrance to a venue hosting an event (e.g., a sporting event, a concert, or a movie). When a PDK owner walks through the entrance, the Reader **108** detects the PDK **102** within range, authenticates the user, and executes a transaction to purchase an electronic ticket for the event. In another embodiment, the electronic ticket can be purchased in advance, and the Reader **108** can confirm that the user is a ticket holder upon entering the venue. Other examples scenarios where this configuration is useful include boarding a transportation vehicle (e.g., a train, bus, airplane or boat), entering a hotel room, or accessing secure facilities or other assets. Thus, if no trigger is required, the process next performs **614** the requested profile authentication tests.

If a trigger is required, the Reader monitors **610** its inputs (e.g., a biometric reader, key pad, etc.) and checks for the detection **612** of a trigger. If the required trigger is detected, the process continues to perform **614** one or more profile authentication test. FIGS. 7A-7D illustrate various embodiments of profile authentication tests. According to different configurations of the Reader **108**, one or more of the illustrated authentication processes may be used. Further, in some embodiments, one or more of the processes may be repeated (e.g., for different types of biometric inputs).

Referring first to FIG. 7A, it illustrates a process for biometric authentication. In biometric authentication, a Reader **108** compares a biometric profile stored in the PDK **102** to the biometric input **104** acquired by the biometric reader **302**. Advantageously, the biometric input **104** is not persistently stored by the Reader **108**, reducing the risk of theft or fraudulent use. If **702** biometric authentication is requested, the Reader **108** scans **704** the biometric input **104** supplied by the user. In one embodiment, scanning **704** includes computing a mathematical representation or hash of the biometric input **104** that can be directly compared to the biometric profile.

Furthermore, in one embodiment, scanning **704** also includes obtaining a biometric input sample from the biometric input according to the same function used to compute the biometric profile sample stored in the PDK **102**. Optionally, the Reader **108** receives **708** a biometric profile sample from the PDK **102** and determines **710** if the biometric profile sample matches the biometric input sample. If the biometric profile sample does not match the input sample computed from the scan, the profile is determined to be invalid **718**. If the biometric profile sample matches, the full biometric profile **712** is received from the PDK **102** to determine **714** if the full biometric profile **712** matches the complete biometric input **104**. If the profile **712** matches the scan, the profile **712** is determined to be valid **720**, otherwise the profile **712** is invalid **718**. It is noted that in one embodiment, steps **708** and **710** are skipped and only a full comparison is performed. In one embodiment, the biometric profile and/or biometric profile sample is encoded and transmitted to the Reader **108** along with an encoding key and/or algorithm. Then, the Reader **108** uses the encoding key and/or algorithm to recover the biometric profile and/or biometric profile sample. In another alternative embodiment, only the encoding key and/or algorithm is transmitted by the PDK **102** and the biometric profile data is recovered from a remote database in an encoded form that can then be decoded using the key and/or algorithm.

It will be apparent to one of ordinary skill that in alternative embodiments, some of the steps in the biometric profile authentication process can be performed by the PDK **102** instead of the Reader **108** or by an external system coupled to the Reader **108**. For example, in one embodiment, the biometric input **104** can be scanned **704** using a biometric reader built into the PDK **102**. Furthermore, in one embodiment, the steps of computing the mathematical representation or hash of the biometric input and/or the steps of comparing the biometric input to the biometric profile can be performed by the PDK **102**, by the Reader **108**, by an external system coupled to the Reader **108**, or by any combination of the devices. In one embodiment, at least some of the information is transmitted back and forth between the PDK **102** and the Reader **108** throughout the authentication process. For example, the biometric input **104** can be acquired by the PDK **102**, and transmitted to the Reader **108**, altered by the Reader **108**, and sent back to the PDK **102** for comparison. Other variations of information

exchange and processing are possible without departing from the scope of the invention. The transfer of data between the PDK **102** and the Reader **108** and/or sharing of processing can provide can further contribute to ensuring the legitimacy of each device.

FIG. 7B illustrates a process for PIN authentication. If PIN authentication is requested **724**, a PIN is acquired **726** from the user through a keypad, mouse, touch screen or other input mechanism. Optionally, the Reader **108** receives **728** a PIN sample from the PDK **102** comprising a subset of data from the full PIN. For example, the PIN sample can comprise the first and last digits of the PIN. If the Reader **108** determines **730** that the PIN sample does not match the input, the profile is immediately determined to be invalid **736**. If the PIN sample matches, the full PIN profile is received **732** from the PDK and compared to the input. If the Reader **108** determines **734** that the profile matches the input, the profile is determined to be valid and is otherwise invalid **736**. It is noted that in one embodiment, steps **728** and **730** are skipped.

FIG. 7C illustrates a process for a picture authentication. If the Reader **108** determines **724** that picture authentication is requested, a picture profile is received **744** from the PDK **102** by the Reader **108** and displayed **746** on a screen. An administrator (e.g., a clerk, security guard, etc.) is prompted **748** to compare the displayed picture to the individual and confirms or denies if the identities match. If the administrator confirms that the identities match, the picture profile is determined to be valid **764** and is otherwise invalid **752**. In an alternative embodiment, the process is automated and the administrator input is replaced with a process similar to that described above with reference to FIG. 7A. Here, an image of the user is captured and face recognition is performed by comparing picture profile information received from the PDK **102** to the captured image.

FIG. 7D illustrates a process for authentication with a private registry **114** or the Central Registry **116**. If the Reader **108** determines that registry authentication is requested, a secure communication channel is established **762** over the network **110** between the Reader **108** and one or more registries (e.g., the Central Registry **114**, any private registry **116**, or other validation database **112**). If any additional information is needed to process the registry authentication (e.g., a credit card number), the Reader **108** requests and receives the additional information from the PDK **102**. Identification information is transmitted **764** from the Reader **108** to the registry **114-116** through the network interface **308**. The PDK status is received **766** from the registry to determine **768** if the status is valid **772** or invalid **770**. In one embodiment, the information is processed remotely at the registry **114-116** and the registry **114-116** returns a validation decision to the Reader **108**. In another embodiment, the Reader **108** queries the private **116** or Central registry **114** for information that is returned to the Reader **108**. The information is then analyzed by the Reader **108** and the authorization decision is made locally. In one embodiment, the process involves transmitting credit card (or other purchasing information) to a validation database **112** to authorize the purchase and receive the status of the card. Status information may include, for example, confirmation that the card is active and not reported lost or stolen and that sufficient funds are present to execute the purchase.

Turning now to FIG. 8, a system **800** is illustrated for initializing and registering a PDK **802** through secure trusted initialization and registration processes. The system **800** comprises a Programmer **810**, a user PDK **802**, a Notary PDK **806**, a network **110** and a set of external databases

including a validation database **112**, a Central Registry **114** and one or more private registries **116**. The Programmer **810** couples to the user PDK **802**, the Notary PDK **806**, and a network **110** by either wired or wireless links. The Programmer **810** is also capable of receiving a biometric input **104** from a user and a control input **808** from either the user or the Notary. The network **110** is coupled to the validation database **112**, the Central Registry **114** and two private registries **116**. In alternative embodiments, different or additional external registries or databases may be coupled to the network. In another alternative embodiment, the Programmer can operate as a standalone device without any connection to the network **110**.

Generally, the system **800** is adapted to initialize and/or register a user PDK **802** through a secure trusted process. Initialization includes configuring a user PDK **802** for at least its most basic use and can include acquiring one or more biometric profiles (or other profile) from the user according to a trusted process. The registration process registers a user PDK **802** with the Central Registry **114** and/or one or more private registries **116**. Additionally, registration can include programming profile memory fields **232** in the user PDK **802** to store, for example, credit card information, personal information or other information used for authentication or transaction purposes.

As previously mentioned, in one embodiment, the initialization process is administered and witnessed by a trusted third-party referred to as a Notary. Conceptually, a Notary can be thought of as an enhanced public notary that can be trusted to verify that an individual's identification has been properly authenticated prior to the execution of a transaction. Instead of witnessing an individual sign a legally-binding document, the Notary witnesses the acquisition and storage of an authenticated individual's biometric profile. The Notary ensures that the individual's identification and biometric profile comply with, and have been acquired and processed according to defined security protocols. In one embodiment, various requirements may be imposed on the Notary to be eligible for administering initialization and the requirements may be definable for different types of initialization. For example, in one embodiment a Notary has to pass an extensive background check, receive training, or provide signatures agreeing to fulfill the duties of a trusted Notary. Furthermore, regular audits may be performed on Notaries to ensure that they can be trusted and are not associated with any fraudulent activity. It is noted that not all types of initialization and registration require a Notary.

The initialization and registration processes are enabled by using a Programmer **810** to write initialization and registration information to a user PDK **802**. In one embodiment, the Programmer **810** also communicates with a Notary PDK **806** belonging to a Notary that verifies the processes and ensures that the initialization and registration information can be trusted. For registration, the Programmer **810** communicates to the Central Registry **114**, one or more validation databases **112** or one or more private registries **116** through the network **110**.

FIG. 9 illustrates an example embodiment of a Programmer **810**. The Programmer **810** includes one or more biometric readers **902**, an interface **904** for one or more PDKs, a storage module **910**, a processor **906**, a control interface **912**, and a network interface **908**.

It is noted that some of the modules of the Programmer **810** operate similarly to modules of the Touch Reader **108** previously described. For example, the biometric reader **902**, network interface **908** and processor **906** can be similar in architecture to the biometric reader **302**, network interface

308 and processor **306** of the Touch Reader **108**. However, the operation of these components is as described below with reference to FIGS. **10-14**. The PDK interface **904** couples the Programmer **810** to the programmer I/O **240** of one or more PDKs. In one embodiment, the PDK interface **904** simultaneously couples to a Notary PDK **806** and a user PDK **802**. In another embodiment, two or more Notary PDKs **806** can be coupled to the interface **904** in addition to the user PDK **802**. In yet another embodiment, the interface **904** only couples to one PDK at a time but allows different PDKs to be swapped in and out. In an alternative configuration, the Notary PDK **806** can couple to the PDK interface **904** from a remote location. For example, a Notary PDK **806** can couple to the Programmer through a network, allowing the Notary to perform the initialization from a remote location. In another configuration, the Notary function is performed by trusted hardware or other automated means that can be built into the Programmer, rather than by a human.

The control interface **912** receives control inputs **808** from a user or from a Notary and outputs status indicators. Control inputs **808** can include, for example, programming settings, menu selections, confirmations and so on. Outputs can include, for example, status LEDs, an LCD with or without a touchscreen interface, or other display that provides instructions, menus or programming options to the user and/or Notary.

The storage module **910** temporarily stores user information during programming. In one embodiment, the storage module **910** includes volatile and non-volatile memory. Typically, biometric information or other highly personal information is erased from the storage module **910** upon completion of programming or removal of the Notary PDK **806** or user PDK **802**. In one embodiment, the storage module **910** includes long-term storage for storing programming history information. Programming history can include, for example, the PDK ID, Notary ID, site ID, and timestamps associated with the programming of any PDK. The programming history can be recalled at a later time for auditing purposes.

Turning now to FIG. **10**, an embodiment of a high-level process for initializing a PDK is illustrated. To establish trust and credibility of data stored on the PDK, the Programmer validates **1002** a user and validates **1004** a Notary. The process for validation is described in more detail below with reference to FIG. **11**. Validation ensures that both the user and Notary are who they claim to be, that the user is eligible for PDK initialization, and that the Notary is authorized to administer the registration process. In the case of a biometric initialization, the Programmer **810** acquires **1006** biometric information from the user for storage in a biometric profile of the user PDK **802**. This process is described in more detail below with reference to FIG. **12**. The Programmer **810** can further acquire multiple types of biometric profiles, or other types of user profiles. The initialization history is then written **1008** to the PDK **802** and optionally to the Programmer **810** for future auditing. This process is described in more detail below with reference to FIG. **12**.

The steps of FIG. **10** are described in more detail with reference to FIGS. **11-13**. FIG. **11** corresponds to a process for validating **1002** a user PDK **802** and the process for validating **1004** a Notary PDK **806**. The user PDK **802** and Notary PDK **806** validation can occur in either order, or can be processed in parallel. To begin validation, the Programmer **810** detects **1102** a PDK **802/806** at the PDK interface **904**. The Programmer **810** next checks **1104** standing or status of the PDK **802/806** with the Central Registry **114**. In

the case of a user PDK **802**, the Programmer **810** confirms with the Central Registry **114** that the PDK **802** has not, for example, expired, been reported as lost or stolen, had fraudulent activity associated with the PDK **802**, or had any complaints been filed against the user for lack of payments, etc. Further, the Programmer **810** can confirm that the software internal to the user PDK **802** is valid and has not been tampered with. In many cases, the user PDK **802** has never been previously initialized or registered and automatically qualifies for good standing. The step of checking **1104** the PDK standings vary slightly for an Notary PDK **806**. Here, the check **1104** ensures that the Notary is a registered Notary, that no fraudulent activity has been associated with the Notary or any PDK initialized or registered by the Notary, that the software internal to the Notary PDK **806** is valid and has not been tampered with, and that the Notary can be trusted to administer the initialization. The process determines **1106** if the PDK (user **802** or Notary **806**) is in good standing. If the PDK (user **802** or Notary **806**) is determined to be in good standing, the initialization is allowed to continue **1110**. If the PDK (user **802** or Notary **806**) is not in good standing the initialization process ends **1108**.

In one embodiment, validation further includes the PDK **802/806** validating that the Programmer **810** is a valid trusted device. This validation ensures that the Programmer **810** has not been tampered with for fraudulent use. Various device authentication processes are possible such as, for example, a challenge-response authentication. Further, the Programmer **810** can be validated by a remote registry to ensure its software is update, the device has not been tampered with or the hardware has not been reported as lost, stolen, expired or revoked. If any fraudulent activity is detected with the Programmer, the Programmer can be automatically disabled.

Initialization optionally includes acquiring **1006** biometric information to be stored in the biometric profile of the user PDK **802** as illustrating in FIG. **12**. To begin the process, the Programmer **802** requests **1202** biometric input **804** from the user. The biometric input **804** is then scanned **1204** by the biometric reader **902**. For example, in a fingerprint-based initialization, scanning **1204** includes requesting the user to place each desired finger on the biometric reader **902** of the Programmer **810** and capturing an image representing the unique characteristics of the fingerprint. In other types of biometric initialization, scanning **1204** can include capturing a different type of image (e.g., a palm, face, retina, iris, or signature), capturing audio for a voice-based biometric profile, or capturing DNA, RNA or their derivatives as used to establish identity. The Programmer **810** checks **1206** the quality of each scan to ensure that the captured biometric input **804** is valid. If **1208** the quality is not satisfactory (due to, for example, improper positioning during the scan), the Programmer **810** repeats the request **1202** for biometric input **804**. If **1208** the quality of the scan meets the necessary standards, the biometric profile is computed from the scan results. As previously described, the biometric profile is generally computed by performing mathematical hashes on the acquired data. In addition, in one embodiment, the biometric profile can be encoded according to an encoding key and/or algorithm that is stored with the biometric profile data. This process can be repeated for any number of biometric profile types.

Additional types of profiles can also be similarly stored to the user PDK **802**. For example, a PIN profile can be added by prompting the user to enter a PIN or password. A photo

profile can be added by capturing an image of the user, checking the quality of the image and recapturing the image if necessary.

FIG. **13** illustrates an embodiment of a process for writing **1008** initialization data. In step **1302**, the Programmer **810** receives initialization approval from the Notary. By submitting the approval, the Notary indicates that he/she has witnessed the initialization process and that the user's identity has been authenticated. In one embodiment, the approval can be executed automatically if all previous steps are validated. The acquired profile information and/or registry information is then written **1304** to the user PDK **802**. Here, user data can include the profile to be written to the once-programmable memory or other information to be written to the read/write memory fields. History data is also written **1306** to the user PDK. History data includes information documenting the initialization process such as the Notary ID, the Programmer's ID, and the site ID (indicating the location of the initialization), registration date and time, and so on. Initialization history data can also be stored **1308** in the storage module **910** of the Programmer **810**. This provides an audit trail of all programming operations performed by the Programmer **810**. It should be noted that the user's biometric information is typically erased from the Programmer **810** and is therefore not at risk of theft or fraudulent use.

In one embodiment, initialization history information is also written to the Notary PDK **806**. Here, a Notary PDK **806** can store a record of every initialization performed by the Notary. This information can be used for auditing purposes in the future. For example, if a Notary's rights are revoked, any initializations performed by that Notary can be recovered from the Notary's PDK **806**. Then, user PDKs **802** initialized by that Notary may need to be disabled until re-initialized by the user.

FIG. **14** illustrates a method for registering a PDK with a Central **114** or private **116** registry. In step **1402**, the PDK initialization data is validated by the Programmer **810** to confirm that the PDK **802** has been properly initialized as described in FIGS. **10-13**. The user is validated **1404** and the Notary administering the registration is validated **1406**. In one embodiment, the validation steps can be executed by steps similar to the process of FIG. **11** used in initialization. If the user and Notary are both validated, the registry entry is added **1408** to the registry if the user is new to the registry, or a registry entry is updated **1408** if the user has already previously been registered. In this step, user information is transmitted by the network interface **908** of the Programmer **810** to the private **116** or Central Registry **114**. A registry entry can include for example, the unique user PDK, purchasing information (such as credit/debit/ATM card information or bank account information), and personal information (such as name, address, phone number, date of birth, etc.). The user PDK **802** is then updated **1410** by storing the information to the memory of the PDK. Information associated with a registry update (user PDK ID, Notary ID, programmer ID, site ID, registry ID, timestamps, etc.) can also be written to the storage module **910** of the Programmer **810** to enable future audits. In an alternative embodiment, the Programmer **810** can operate as a portable standalone device that can register a user PDK **802** in an offline mode. Then, the Programmer can be later coupled to a network to upload any new registrations to a private registry **116**, Central Registry **114**, or validation database **112**.

It is noted that although in many embodiments of the present invention, the Notary performs the initialization and registration process in person, it is also possible for the

Notary to operate from a remote location. For example, in one embodiment, a user can enter an initialization booth with a camera and a Programmer 810. The user enters the user PDK 802 into the Programmer 810 and begins the initialization session. A Notary at a remote location can monitor the operation and if necessary provide instructions to the user. Alternatively, the initialization and registration can be administered by a completely automated process that can be recalled and reviewed at a later time to ensure the user followed the appropriate procedures. In another embodiment, a human Notary is not required, and the initialization and/or registration processes are performed entirely by trusted hardware.

The order in which the steps of the methods of the present invention are performed is purely illustrative in nature. The steps can be performed in any order or in parallel, unless otherwise indicated by the present disclosure. The methods of the present invention may be performed in hardware, firmware, software, or any combination thereof operating on a single computer or multiple computers of any type. Software embodying the present invention may comprise computer instructions in any form (e.g., source code, object code, interpreted code, etc.) stored in any computer-readable storage medium (e.g., a ROM, a RAM, a magnetic media, a compact disc, a DVD, etc.). Such software may also be in the form of an electrical data signal embodied in a carrier wave propagating on a conductive medium or in the form of light pulses that propagate through an optical fiber.

While particular embodiments of the present invention have been shown and described, it will be apparent to those skilled in the art that changes and modifications may be made without departing from this invention in its broader aspect and, therefore, the appended claims are to encompass within their scope all such changes and modifications, as fall within the true spirit of this invention.

In the above description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the invention. It will be apparent, however, to one skilled in the art that the invention can be practiced without these specific details. In other instances, structures and devices are shown in block diagram form in order to avoid obscuring the invention.

Reference in the specification to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the invention. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

Some portions of the detailed description are presented in terms of algorithms and symbolic representations of operations on data bits within a computer memory. These algorithmic descriptions and representations are the means used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. An algorithm is here, and generally, conceived to be a self-consistent sequence of steps leading to a desired result. The steps are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate

physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the discussion, it is appreciated that throughout the description, discussions utilizing terms such as “processing” or “computing” or “calculating” or “determining” or “displaying” or the like, refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system’s registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

The present invention also relates to an apparatus for performing the operations herein. This apparatus can be specially constructed for the required purposes, or it can comprise a general-purpose computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program can be stored in a computer readable storage medium, such as, but is not limited to, any type of disk including floppy disks, optical disks, CD-ROMs, and magnetic-optical disks, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, magnetic or optical cards, or any type of media suitable for storing electronic instructions, and each coupled to a computer system bus.

The algorithms and modules presented herein are not inherently related to any particular computer or other apparatus. Various general-purpose systems can be used with programs in accordance with the teachings herein, or it may prove convenient to construct more specialized apparatuses to perform the method steps. The required structure for a variety of these systems will appear from the description below. In addition, the present invention is not described with reference to any particular programming language. It will be appreciated that a variety of programming languages can be used to implement the teachings of the invention as described herein. Furthermore, as will be apparent to one of ordinary skill in the relevant art, the modules, features, attributes, methodologies, and other aspects of the invention can be implemented as software, hardware, firmware or any combination of the three. Of course, wherever a component of the present invention is implemented as software, the component can be implemented as a standalone program, as part of a larger program, as a plurality of separate programs, as a statically or dynamically linked library, as a kernel loadable module, as a device driver, and/or in every and any other way known now or in the future to those of skill in the art of computer programming. Additionally, the present invention is in no way limited to implementation in any specific operating system or environment.

It will be understood by those skilled in the relevant art that the above-described implementations are merely exemplary, and many changes can be made without departing from the true spirit and scope of the present invention. Therefore, it is intended by the appended claims to cover all such changes and modifications that come within the true spirit and scope of this invention.

What is claimed is:

1. A method comprising:

determining, by a reader device, that a portable electronic device is located within a proximity zone of the reader device;

establishing a wireless communication channel between the reader device and the portable electronic device

23

responsive to determining that the portable electronic device is located within the proximity zone of the reader device;

at the reader device, receiving device identification information from the portable electronic device, the device identification information uniquely identifying the portable electronic device;

determining locally, by the reader device, that the portable electronic device is a valid device based on the device identification information without a remote lookup;

receiving a request for a transaction having a transaction amount;

determining whether the transaction amount associated with the transaction is under an amount threshold;

responsive to determining that the transaction amount associated with the transaction is under the amount threshold and the portable electronic device is located within the proximity zone of the reader device, automatically performing, by the reader device, the transaction using the transaction amount; and

responsive to determining that the transaction amount associated with the transaction is not under the amount threshold, requesting that the portable electronic device perform a profile authentication.

2. The method of claim 1, further comprising: determining whether the profile authentication was successful; and

responsive to determining that the profile authentication was successful, automatically performing, by the reader device, the transaction using the transaction amount.

3. The method of claim 2, wherein the profile authentication includes a comparison performed by the portable electronic device between a user input and a profile stored in the portable electronic device.

4. The method of claim 2, further comprising: receiving, from the portable electronic device, other information associated with the transaction responsive to determining that the profile authentication was successful; and

wherein performing the transaction uses the other information associated with the transaction.

5. The method of claim 1, further comprising: establishing a secure communication channel between the reader device and the portable electronic device; and

wherein other information associated with the transaction is received via the secure communication channel.

6. The method of claim 1, wherein other information associated with the transaction includes one or more of credit card information, debit card information, Automated Teller Machine card information, bank account information, and a code.

7. The method of claim 1, further comprising: requesting, by the reader device, validation information associated with the portable electronic device from a database using other information associated with the transaction; and

wherein automatically performing the transaction uses the validation information associated with the portable electronic device.

8. The method of claim 7, wherein the validation information is based on a spending limit associated with the other information and the transaction amount associated with the transaction.

9. The method of claim 1, wherein the reader device is an Automated Teller Machine.

24

10. The method of claim 1, wherein the portable electronic device is one of a cell phone, a personal digital assistant, a watch, and a tag.

11. A system comprising: one or more processors; and

a memory storing instructions that, when executed by the one or more processors, cause the system to perform operations including:

determining, by a reader device, that a portable electronic device is located within a proximity zone of the reader device;

establishing a wireless communication channel between the reader device and the portable electronic device responsive to determining that the portable electronic device is located within the proximity zone of the reader device;

at the reader device, receiving device identification information from the portable electronic device, the device identification information uniquely identifying the portable electronic device;

determining locally, by the reader device, that the portable electronic device is a valid device based on the device identification information without a remote lookup;

receiving a request for a transaction having a transaction amount;

determining whether the transaction amount associated with the transaction is under an amount threshold;

responsive to determining that the transaction amount associated with the transaction is under the amount threshold and the portable electronic device is located within the proximity zone of the reader device, automatically performing, by the reader device, the transaction using the transaction amount; and

responsive to determining that the transaction amount associated with the transaction is under the amount threshold, requesting that the portable electronic device perform a profile authentication.

12. The system of claim 11, wherein the instructions that, when executed by the one or more processors, further cause the system to perform the operations including:

determining whether the profile authentication was successful; and

responsive to determining that the profile authentication was successful, automatically performing, by the reader device, the transaction using the transaction amount.

13. The system of claim 12, wherein the profile authentication includes a comparison performed by the portable electronic device between a user input and a profile stored in the portable electronic device.

14. The system of claim 12, wherein the instructions that, when executed by the one or more processors, further cause the system to perform the operations including:

receiving, from the portable electronic device, other information associated with the transaction responsive to determining that the profile authentication was successful; and

wherein performing the transaction uses the other information associated with the transaction.

15. The system of claim 11, wherein the instructions that, when executed by the one or more processors, further cause the system to perform the operations including:

establishing a secure communication channel between the reader device and the portable electronic device; and

wherein other information associated with the transaction is received via the secure communication channel.

16. The system of claim 11, wherein other information associated with the transaction includes one or more of credit card information, debit card information, Automated Teller Machine card information, bank account information, and a code. 5

17. The system of claim 11, wherein the instructions that, when executed by the one or more processors, further cause the system to perform the operations including: 10

requesting, by the reader device, validation information associated with the portable electronic device from a database using other information associated with the transaction; and

wherein automatically performing the transaction uses the validation information associated with the portable electronic device. 15

18. The system of claim 17, wherein the validation information is based on a spending limit associated with the other information and the transaction amount associated with the transaction. 20

19. The system of claim 11, wherein the reader device is an Automated Teller Machine.

20. The system of claim 11, wherein the portable electronic device is one of a cell phone, a personal digital assistant, a watch, and a tag. 25

* * * * *