



- (51) International Patent Classification:
A61B 17/22 (2006.01) *A61M 25/10* (2013.01)
- (21) International Application Number:
PCT/US2013/048277
- (22) International Filing Date:
27 June 2013 (27.06.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
13/534,658 27 June 2012 (27.06.2012) US
- (71) Applicant: **SHOCKWAVE MEDICAL, INC.** [US/US];
48531 Warm Springs Boulevard, Suite 416, Fremont, CA
94539 (US).
- (72) Inventors: **ADAMS, John, M.**; 18023 Fales Road, Sno-
homish, WA 98296 (US). **GOFF, Thomas, G.**; 108 Bryant
Street #6, Mountain View, CA 94041 (US). **HAKALA,
Doug**; 19110 222 Way NE, Woodinville, WA 98077 (US).
- (74) Agents: **YANG, Hain-Ann, Hsueh** et al.; Morrison & Fo-
erster LLP, 755 Page Mill Road, Palo Alto, CA 94304-
1018 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: SHOCK WAVE BALLOON CATHETER WITH MULTIPLE SHOCK WAVE SOURCES

FIG. 12



(57) Abstract: An apparatus includes a balloon adapted to be placed adjacent a calcified region of a body. The balloon is inflatable with a liquid. The apparatus further includes a shock wave generator within the balloon that produces shock waves that propagate through the liquid for impinging upon the calcified region adjacent the balloon. The shock wave generator includes a plurality of shock wave sources distributed within the balloon.

SHOCK WAVE BALLOON CATHETER WITH MULTIPLE SHOCK WAVE SOURCES

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to U.S. Pat. Appl. No. 13/534,658, filed June 27, 2012, which is hereby incorporated by reference in its entirety.

BACKGROUND

[0002] Aortic calcification, also called aortic sclerosis, is a buildup of calcium deposits on the aortic valve in the heart. This often results in a heart murmur, which can easily be heard with a stethoscope over the heart. However, aortic calcification usually doesn't significantly affect the function of the aortic valve.

[0003] In some cases, though, the calcium deposits thicken and cause narrowing at the opening of the aortic valve. This impairs blood flow through the valve, causing chest pain or a heart attack. Doctors refer to such narrowing as aortic stenosis.

[0004] Aortic calcification typically affects older adults. But when it occurs in younger adults, it's often associated with an aortic valve defect that is present at birth (congenital) or with other illnesses such as kidney failure. An ultrasound of the heart (echocardiogram) can determine the severity of aortic calcification and also check for other possible causes of a heart murmur.

[0005] At present there is no specific treatment for aortic calcification. General treatment includes the monitoring for further developments of heart disease. Cholesterol levels are also checked to determine the need for medications to lower cholesterol in the hope to prevent progression of aortic calcification. If the valve becomes severely narrowed, aortic valve replacement surgery may be necessary.

[0006] The aortic valve area can be opened or enlarged with a balloon catheter (balloon valvuloplasty) which is introduced in much the same way as in cardiac catheterization. With balloon valvuloplasty, the aortic valve area typically increases slightly. Patients with critical aortic stenosis can therefore experience temporary improvement with this procedure. Unfortunately, most of these valves narrow over a six to 18 month period. Therefore, balloon valvuloplasty is useful as a short-term measure to temporarily relieve symptoms in patients who are not candidates for aortic valve replacement.

[0007] Patients who require urgent noncardiac surgery, such as a hip replacement, may benefit from aortic valvuloplasty prior to surgery. Valvuloplasty improves heart function and the chances of surviving non-cardiac surgery. Aortic valvuloplasty can also be useful as a bridge to aortic valve replacement in the elderly patient with poorly functioning ventricular muscle. Balloon valvuloplasty may temporarily improve ventricular muscle function, and thus improve surgical survival. Those who respond to valvuloplasty with improvement in ventricular function can be expected to benefit even more from aortic valve replacement. Aortic valvuloplasty in these high risk elderly patients has a similar mortality (5%) and serious complication rate (5%) as aortic valve replacement in surgical candidates.

[0008] Transarterial aortic valve replacement is a new procedure where the aortic valve is replaced with a self-expanding nitinol or balloon-expandable valve structure. Such procedures benefit from a smooth non-calcified circumference to attach the new valve. Large calcium deposits may induce leaks around the valve preventing a firm consistent attachment of the valve to the aorta. Thus there is a need for a calcium free valve bed to attach such self-expanding valves.

[0009] An alternative method and system for treating stenotic or calcified aortic valves is disclosed and claimed in co-pending U.S. Application Serial No. 12/611,997, filed November 11, 2009 for SHOCKWAVE VALVULOPLASTY SYSTEM. As described therein, a balloon is placed adjacent leaflets of a valve to be treated and is inflatable with a liquid. Within the balloon is a shock wave generator that produces shock waves that propagate through the liquid and impinge upon the valve. The impinging shock waves soften, break and/or loosen the calcified regions for removal or displacement to open the valve or enlarge the valve opening.

[0010] The approach mentioned above provides a more tolerable treatment for aortic stenosis and calcified aortic valves than the previously performed aortic valve replacement. It is also a more effective treatment than current valvuloplasty therapy. For patients undergoing transaortic or catheter based aortic valve replacement, this new method can soften, smooth, and open the aortic valve annulus more effectively than current valvuloplasty and prepare the area for a catheter delivered valve.

[0011] In the shock wave valvuloplasty described above, the impingement intensity of the shockwaves diminishes as a function of the distance from the shock wave origination point to the valve. More specifically, the impingement intensity of the shock waves is inversely proportional to the square of the distance from the shock wave origination point to the valve.

Hence, when applying the shock waves, it would be desirable to maximize their effectiveness by being able to minimize the distance between the shock wave source and the valve location being treated at that moment.

[0012] Similar issues are present in angioplasty. There, a calcified region of a vein or artery may extend over some longitudinal distance of the vein or artery. A point shock wave source within an angioplasty balloon, in such instances, would not be uniformly effective across the extent of the calcified region because of the varying distance from the shock wave source to the various portions of the calcified region.

[0013] The present invention addresses this and other matters of importance in providing the most efficient and effective valvuloplasty and angioplasty treatment possible.

SUMMARY

[0014] In one embodiment, an apparatus comprises a balloon adapted to be placed adjacent a calcified region of a body. The balloon is inflatable with a liquid. The apparatus further includes a shock wave generator within the balloon that produces shock waves that propagate through the liquid for impinging upon the calcified region adjacent the balloon. The shock wave generator includes a plurality of shock wave sources distributed within the balloon, wherein the plurality of shock wave sources are more than two shock wave sources. These shock wave sources can be distributed both longitudinally and circumferentially within the balloon for optimal effect.

[0015] The balloon is elongated having a longitudinal dimension along its length and the plurality of shock wave sources extend along a portion of the longitudinal dimension. The balloon has a sidewall and the shock wave sources are in non-touching relation with respect to the balloon sidewall. The shock wave generator may be an electrical arc shock wave generator and the shock wave sources may include a plurality of electrodes. The electrical arc shock wave generator may further include at least one counter electrode adapted to be in contact with the liquid and to receive a voltage polarity opposite a voltage polarity applied to the plurality of electrodes.

[0016] The shock wave generator may include an elongated conductor and an insulator overlying the elongated conductor. The insulator may have a plurality of discrete openings, each opening for exposing the elongated conductor to the fluid, to form the plurality of electrodes. An insulated wire may be employed to form the elongated conductor and the overlying insulator.

[0017] The apparatus may further include an elongated carrier. The carrier may extend through the balloon and be sealed thereto. The insulated wire may be wrapped about the carrier within the balloon. The carrier may include a guide wire lumen. The insulated wire may be wrapped about the carrier to form electrode coil turns and the apparatus may further include a conductor wire wrapped about the carrier within the balloon and in between the electrode coil turns to form the counter electrode.

[0018] The shock wave generator may include an elongated cylindrical conductor and an insulator overlying the elongated cylindrical conductor. The insulator may have a plurality of discrete openings, each opening for exposing the elongated cylindrical conductor to the fluid, to form the plurality of electrodes. The apparatus may further include an elongated carrier extending through the balloon and be in sealed relation thereto. The elongated cylindrical conductor may overlie the carrier within the balloon. The elongated carrier may include a guide wire lumen.

[0019] The shock wave generator may be an electrical arc shock wave generator, wherein the shock wave sources include a plurality of electrodes, wherein the apparatus further includes an elongated carrier having a longitudinal dimension extending through the balloon and being in sealed relation thereto, wherein the elongated carrier has a guide wire lumen extending along at least a portion of the longitudinal dimension of the elongated carrier, and wherein at least some of the plurality of electrodes are distributed along the elongated carrier within the balloon.

[0020] The elongated carrier may be formed of an insulating material. The shock wave generator may include at least one conductor extending within the elongated carrier in spaced apart relation to the guide wire lumen and along at least a portion of the longitudinal dimension of the elongated carrier and a plurality of discrete portions of the elongated carrier insulating material are removed to expose corresponding portions of the at least one conductor to form the at least some of the plurality of electrodes. At least some of the removed discrete portions of the elongated carrier insulating material may contain a conductive filling. The conductive fillings may be conductively secured to the elongated conductor.

[0021] The elongated carrier may be formed of an insulating material. The shock wave generator may include at least first and second elongated conductors extending within the elongated carrier in spaced apart relation to each other and the guide wire lumen and along at least a portion of the longitudinal dimension of the elongated carrier. A plurality of discrete portions of the elongated carrier insulating material may be removed to expose corresponding

portions of the at least first and second conductors to form the at least some of the plurality of electrodes.

[0022] The removed discrete portions of the elongated carrier insulating material that expose corresponding portions of one of the at least first and second conductors are greater in dimension than the removed discrete portions of the elongated carrier insulating material that expose corresponding portions of another one of the at least first and second conductors. The at least some of the removed discrete portions of the elongated carrier insulating material may contain a conductive filling and at least some of the conductive fillings may be conductively secured to the elongated conductors.

[0023] The plurality of electrodes are arranged in series circuit relation. Alternatively the plurality of electrodes are arranged in parallel circuit relation. The apparatus may further include a power source and a multiplexer that selectively couples the power source to the plurality of electrodes, one at a time. In another embodiment, the plurality of electrodes may be arranged in a plurality of series circuit arrangements and the apparatus may further include a multiplexer that selectively couples the power source to the series circuit arrangements, one at a time.

[0024] The plurality of shock wave sources may be arranged along a path defining a loop. The balloon may be configured to be placed adjacent leaflets of a valve, the balloon having a first chamber to be adjacent one side of the leaflets and a second chamber to be adjacent an opposite side of the leaflets. The plurality of shock wave sources may be arranged to define a loop of shock wave sources within one of the first and second chambers of the balloon.

[0025] The balloon may be configured to be placed adjacent leaflets of a valve, the balloon having a first chamber to be adjacent one side of the leaflets and a second chamber to be adjacent an opposite side of the leaflets, and wherein the plurality of shock wave sources may be arranged to define a first loop of shock wave sources within the first chamber of the balloon and a second loop of shock wave sources within the second chamber of the balloon.

[0026] In accordance with another embodiment, an apparatus comprises an elongated carrier and a balloon carried on the elongated carrier in sealed relation thereto. The balloon is adapted to be placed adjacent a calcified region of a body and is inflatable with a liquid. The apparatus further includes an electrical arc shock wave generator within the balloon. The electrical arc shock wave generator includes more than two electrodes distributed within the balloon. Each electrode is adapted to produce shock waves that propagate through the liquid for impinging

upon the calcified region adjacent the balloon. The apparatus further includes a counter electrode adapted to be in contact with the liquid and to receive a voltage polarity opposite that applied to the more than two electrodes.

[0027] In a further embodiment, a method includes the steps of inserting a balloon in a body adjacent a calcified region, inflating the balloon with a liquid to cause the balloon to contact the calcified region, placing, within the balloon, a shock wave generator including more than two shock wave sources and distributing the more than two shock wave sources within the balloon, and causing the shock wave sources to form shock waves that propagate through the liquid and impinge upon the calcified region.

[0028] The inserting step may include inserting the balloon into an artery or vein of the body. The balloon may be elongated having a longitudinal dimension and the distributing step may include distributing the shock wave sources along a portion of the longitudinal dimension.

[0029] The inserting step may include inserting the balloon into a valve of the body. The distributing step may include distributing the shock wave sources along a path defining a loop.

[0030] The balloon may be configured to be placed adjacent leaflets of the valve and to have a first chamber adapted to be adjacent one side of the leaflets and a second chamber adapted to be adjacent an opposite side of the leaflets. The inserting step may include inserting the balloon into the valve with the first chamber adjacent one side of the leaflets and the second chamber adjacent the opposite side of the leaflets. The distributing step may include distributing the shock wave sources along a path defining a loop of shock wave sources within one of the first and second chambers of the balloon.

[0031] In a still further embodiment, the balloon is configured to be placed adjacent leaflets of the valve, wherein the balloon has a first chamber to be adjacent one side of the leaflets and a second chamber to be adjacent an opposite side of the leaflets, wherein the inserting step includes inserting the balloon into the valve with the first chamber adjacent one side of the leaflets and the second chamber adjacent the opposite side of the leaflets, and wherein the distributing step includes distributing the shock wave sources to define a first loop of shock wave sources within the first chamber of the balloon and to define a second loop of shock wave sources within the second chamber of the balloon.

[0032] The balloon has a sidewall and the distributing step may include distributing the shock wave sources in non-touching relation with respect to the balloon sidewall. The shock wave generator may be an electrical arc shock wave generator, the shock wave sources may include a

plurality of electrodes, and the causing step may include applying voltage pulses between the plurality of electrodes and a counter electrode to form the shock waves.

[0033] According to a still further embodiment, a method comprises inserting a balloon in a body adjacent a calcified region, inflating the balloon with a liquid to cause the balloon to contact the calcified region, placing, within the balloon, more than two electrodes in non-touching relation to the balloon and adjacent the calcified regions, placing a counter electrode in contact with the liquid, and applying voltage pulses between the more than two electrodes and the counter electrode, wherein the voltage pulses have a first polarity applied to the two or more electrodes and a second polarity applied to the counter electrode causing the more than two electrodes to form shock waves that propagate through the liquid and impinge upon the calcified region.

BRIEF DESCRIPTION OF THE DRAWINGS

[0034] The features of the present invention which are believed to be novel are set forth with particularity in the appended claims. The various described embodiments of the invention, together with representative features and advantages thereof, may best be understood by making reference to the following description taken in conjunction with the accompanying drawings, in the several figures of which like reference numerals identify identical elements, and wherein:

[0035] FIG. 1 is a simplified drawing of an angioplasty system embodying the invention including a side view of a dilating angioplasty balloon catheter including a plurality of shock wave sources according to one embodiment;

[0036] FIG. 2 is a side view of the catheter of FIG. 1 showing an alternate electrode structure that may be employed within the dilating angioplasty balloon catheter of FIG. 1;

[0037] FIG. 3 is a side view of the catheter of FIG. 1 showing still another alternate electrode structure that may be employed within the dilating angioplasty balloon catheter of FIG. 1;

[0038] FIG. 4 is a partial sectional view illustrating alternative aspects of the electrode structure of FIG. 3 to provide the plurality of shock wave sources;

[0039] FIG. 5 is a side view of another dilating angioplasty balloon catheter including a plurality of shock wave sources according to a further embodiment of the invention;

[0040] FIG. 6 is a perspective view illustrating a manner in which an electrode structure of the catheter of FIG. 5 may be produced to provide the plurality of shock wave sources according to an embodiment of the invention;

[0041] FIG. 7 is another perspective view illustrating another aspect of the electrode structure for the of FIG. 5 according to an embodiment of the invention;

[0042] FIG. 8 is a simplified schematic diagram of a shock wave angioplasty system embodying the invention wherein the shock wave source electrodes are arranged in parallel circuit;

[0043] FIG. 9 is a simplified side view of the left ventricle, aorta, and aortic valve of a heart with a valvuloplasty treatment catheter embodying the invention within the aortic valve of the heart;

[0044] FIG. 10 is a perspective view, to an enlarged scale, of the electrode structure employed in the valvuloplasty catheter of FIG. 9;

[0045] FIG. 11 is another simplified side view of the left ventricle, aorta, and aortic valve of a heart with a dual chamber valvuloplasty treatment catheter embodying the invention within the aortic valve of the heart;

[0046] FIG. 12 is a partial side view, to an enlarged scale, of an angioplasty catheter with an electrode structure that may be employed in the embodiments herein wherein the electrodes are arranged in series circuit;

[0047] FIG. 13 is a simplified schematic diagram of a shock wave angioplasty system embodying the invention wherein the shock wave source electrodes are arranged in series circuit;

[0048] FIG. 14 is a simplified schematic diagram of a shock wave angioplasty system embodying the invention wherein the shock wave source electrodes are arranged in plural series circuits with each series circuit being individually activated;

[0049] FIG. 15 is a simplified drawing of another angioplasty system embodying the invention including a side view of a dilating angioplasty balloon catheter including a plurality of shock wave sources that are selectably coupled to a power source, one at a time, according to another embodiment; and

[0050] FIG. 16 is a timing diagram illustrating the manner in which the electrodes of FIG. 15 may be selectably coupled to a power source.

DETAILED DESCRIPTION

[0051] FIG. 1 shows an angioplasty system 10 embodying the invention including a dilating angioplasty balloon catheter 20 including a plurality of shock wave sources according to one

embodiment of the invention. The catheter 20 includes an elongated carrier 21, and a dilating balloon 26 formed about the carrier 21 in sealed relation thereto at a seal 23. The balloon 26 forms an annular channel 27 about the carrier 21 through which fluid, such as saline, may be admitted into the balloon to inflate the balloon. The carrier 21 includes a guide wire lumen 29. The guide wire lumen is arranged to receive a guide wire that may be used to direct the catheter to a desired location to locate the balloon adjacent a region of an artery or vein or to be treated.

[0052] Carried by the carrier 21 is an electrode structure 40. The electrode structure 40 includes an insulated wire 42 wound about the carrier 21. Within the insulation of the insulated wire 42 are a plurality of openings 44 that expose corresponding discrete portions of the insulated wire conductor to the saline within the balloon. Each opening 44 forms a corresponding shock wave source or electrode 46. As may be seen in FIG. 1, a plurality of more than two electrodes are formed in this manner and in non-touching relation to the sidewalls of the balloon 26.

[0053] The electrode structure 40 also includes a counter electrode 24. The counter electrode 24 is disposed in non-touching relation to the sidewalls of the balloon 26 and serves as a common electrode to cause an electrical arc to occur between each of the electrodes 46 and the common electrode 24 when a suitable high voltage is applied between the electrodes 46 and the counter electrode 24.

[0054] To that end, the electrodes 24 and 46 are attached to a source 30 of high voltage pulses through a connector 32. The electrodes 24 and 46 are formed of metal, such as stainless steel or tungsten, and are placed a controlled distance apart to allow a reproducible arc for a given voltage and current. The electrical arcs between electrode 24 and electrodes 46 in the fluid are used to generate shock waves in the fluid. The variable high voltage pulse generator 30 is used to deliver a stream of pulses across electrode 24 and electrodes 46 to create a stream of shock waves within and along the longitudinal length 25 of the balloon 26 and within the artery being treated (not shown). The magnitude of the shock waves can be controlled by controlling the magnitude of the pulsed voltage, the current, the duration and repetition rate. The insulating nature of the balloon 26 protects the patient from electrical shocks.

[0055] The balloon 26 may be filled with water or saline in order to gently fix the balloon in the walls of the artery in the direct proximity with the calcified lesion. The fluid may also contain an x-ray contrast to permit fluoroscopic viewing of the catheter during use. As previously mentioned, the carrier 21 includes a lumen 29 through which a guidewire (not shown)

may be inserted to guide the catheter into position. Once the catheter is positioned through use of the guide wire (not shown) and guide wire lumen 29, the physician or operator can start with low energy shock waves and increase the energy as needed to crack the calcified plaque. Such shockwaves will be conducted through the fluid, through the balloon, through the blood and vessel wall to the calcified lesion where the energy will break the hardened plaque without the application of excessive pressure by the balloon on the walls of the artery.

[0056] The voltage needed to produce the arcs will depend on the gap between the electrodes and is generally 100 to 3000 volts. The pulse duration will also depend on the surface area of the electrodes 24 and 46 and needs to be sufficient to generate a gas bubble at the surface of the electrodes to cause a plasma arc of electric current to jump each bubble and, upon each occurrence, create a rapidly expanding and collapsing bubble, which creates the mechanical shock wave in the balloon. Such shock waves can be as short as a few microseconds. Both the rapid expansion and the collapse of a bubble create shock waves. The pulse duration can be adjusted to favor one over the other. A large steam bubble will generate a stronger shockwave than a small one. However, more power is needed in the system to generate this large steam bubble. Traditional lithotripters try to generate a large steam bubble to maximize the collapsing bubble's shockwave. Within a balloon such large steam bubbles are less desirable due to the risk of balloon rupture. By adjusting the pulse width to a narrow pulse less than two microseconds or even less than one microsecond, a rapidly expanding steam bubble and shockwave can be generated while at the same time the final size of the steam bubble can be minimized. The short pulse width also reduces the amount of heat in the balloon to improve tissue safety.

[0057] Fig. 2 shows another electrode structure 140 that may be employed in the catheter 20 of FIG. 1. Like the electrode structure of FIG. 1, the electrode structure 140 of FIG. 2 includes an insulated wire 142 wound about the carrier 21 to form electrode coil turns 144. Within the insulation of the insulated wire 142 are a plurality of openings 146 that expose corresponding discrete portions of the insulated wire conductor to the saline within the balloon. Each opening 146 forms a corresponding shock wave source or electrode 148.

[0058] The electrode structure 140 further includes a conductor wire wrapped about the carrier 21 within the balloon 26. The conductor wire 150 is wound in between the electrode coil turns 144 to form a counter electrode 152. This provides more uniform spacings between the

electrodes 148 and the counter electrode 152. All of the electrodes 148 and 152 are disposed in non-touching relation to the sidewalls of the balloon 26.

[0059] FIG. 3 shows another electrode structure 240 that may be employed in the catheter 20 of FIG. 1. Here, the electrode structure 240 of the catheter 20 includes an elongated cylindrical conductor 242 formed of metal, such as stainless steel or tungsten, that overlies the carrier 21. The electrode structure 240 further includes an insulator 244 overlying the elongated cylindrical conductor 242. The insulator 244 has a plurality of discrete openings 246 that expose corresponding areas of the elongated cylindrical conductor to the saline within the balloon 26. Each opening 246 forms a corresponding electrode 248. Another electrode 250 forms a common electrode. All of the electrodes 248 and 250 are disposed in non-touching relation to the sidewalls of the balloon 26.

[0060] FIG. 4 is a partial sectional view illustrating alternative aspects of the electrode structure 240 of FIG. 3 to provide the plurality of shock wave sources. Here, at least some of the openings 246 are filled with a conductive material to form the electrodes 249. The conductive filler forming electrodes 249 may be of the same material forming the conductive cylinder 242 or may be of a different conductive material. It serves to raise the surface of the electrodes to above the insulator 244 which, in some cases, may result in more reliable arc formation.

[0061] Referring now to FIG. 5, it is a side view of another dilating angioplasty balloon catheter 320 including a plurality of shock wave sources according to a further embodiment of the invention. Again, the catheter 320 includes an elongated carrier 321 and an angioplasty dilating balloon 326 at the distal end thereof in sealed relation thereto. The balloon 326 and carrier 321 form a channel 327 through which the balloon may be filled with a liquid, such as water or saline. The carrier 321 also includes a guide wire lumen 329 that is adapted to receive a guide wire 330.

[0062] The catheter 320 further includes an electrode structure 340 including a first plurality of electrodes 332 and a second plurality of electrodes 342. The electrodes 332 and 342 are disposed in non-touching relation to the sidewalls of the balloon 326. During angioplasty treatment, a voltage having a first polarity is applied to the first plurality of electrodes 332 and a reversed polarity is applied to the second plurality of electrodes 342. If the voltage across electrodes 332 and 342 is applied as previously described, an arc will form between corresponding pairs of the electrodes 332 and 342 to produce corresponding shock waves. In this manner, shock waves are produced along the longitudinal dimension of the balloon 326.

[0063] It may be seen in FIG. 5 that the electrodes 332 are of larger dimension and have a greater surface area in contact with the saline in the balloon than the electrodes 342. This reduces the impedance to arc plasma formation, allowing the arc plasmas to be produced soon after the voltage is applied to the electrodes. It has also been found that this causes larger arc plasmas to be formed producing stronger shock waves. It still further assists in controlling the electrodes across which the electrical arcs will be produced.

[0064] FIG. 6 is a perspective view illustrating a manner in which an electrode structure of the catheter of FIG. 5 may be produced to provide the plurality of shock wave sources according to an embodiment of the invention. In FIG. 6 it may be seen that the electrode structure 340 includes a first conductor 344 and a second conductor 346. The conductors 344 and 346 extend along and within the carrier 321. The conductors 344 and 346 may be made to extend along and within the carrier 321 by co-extruding the conductors 344 and 346 with the elongated carrier during manufacture of the carrier 321. After the extrusion process, openings 348 and 350 may be formed in the carrier 321 to expose corresponding portions of the conductors 344 and 346. This results in the formation of electrodes 332 and 342 respectively. FIG. 7 shows that the openings, such as opening 350 formed in the carrier 321 may be filled with a conductive filler to form electrode 342.

[0065] FIG. 8 is a simplified schematic diagram of a shock wave angioplasty system 410 embodying the invention wherein the shock wave source electrodes are arranged in parallel circuit. For purposes of this description, the catheter 320 of FIG. 5 shall be used for illustration. The system includes a high voltage generator 430, a connector 432, and a catheter 320. The catheter 320 includes the first plurality of electrodes 332 and a second plurality of electrodes 342. Each electrode of the first plurality of electrodes 332 finds a corresponding electrode in the second plurality of electrodes 342. The connector 422 connects each of the electrodes of the first plurality of electrodes 332 to the plus (+) side of the voltage generator 430 through a resistance R and each of the electrodes of the second plurality of electrodes 342 to the minus (-) side of the voltage generator 430. The resistance R may be provided through individual resistive elements or through resistivity in the conductors that connect the electrodes to the connector and are provided to equalize the current available to each electrode pair. This assures that no one electrode pair will sink all of the available current precluding all other electrode pairs from producing an electrical arc.

[0066] FIG. 9 is a simplified side view of the left ventricle 500, aorta 502, and aortic valve 504 of a heart with a valvuloplasty treatment catheter 510 embodying the invention within the aortic valve of the heart. The catheter 510 includes a treatment balloon 526 placed on both sides of the aortic valve leaflets 506. Valves of the heart, such as the aortic valve 504 can become stenotic and calcified. More particularly, the opening of the valve defined by the leaflets can become stenotic and calcified. This can restrict the size of the opening as the valve leaflets 506 are thickened with calcium deposits and fibrotic tissue. The thickened leaflets 506 and smaller valve opening restrict blood flow from the heart creating excess work for the heart and poor cardiac output. Current treatment includes replacement of the valve or attempts to stretch the valve annulus with a balloon.

[0067] The treatment balloon 526 includes two longitudinally spaced chambers 528 and 530 placed on opposed sides of the aortic valve leaflets 506. The balloon 526 may be formed from a compliant or a non-compliant material. The balloon is at the distal end of a carrier 521. The catheter is placed into position by an elongated delivery tube 532.

[0068] The two longitudinally spaced chambers 530 and 528 share a common inflation lumen 534 of the carrier 521 to permit the balloon 526 to be filled with a liquid, such as saline. Alternatively the balloon chambers 530 and 528 may not share the same inflation fluid path.

[0069] The catheter 510 includes a plurality of shock wave sources that produce electrical arcs within the balloon to produce shock waves within the confined liquid. The shock waves propagate through the liquid and impinge upon the balloon wall and the valve. The impinging shock waves cause the calcified material on the valve to break and/or soften. This permits the valve opening to be widened or the calcified material to be removed.

[0070] In accordance with the embodiment of FIG. 9, the catheter 510 includes an electrode structure 540 within balloon chamber 528. The electrode structure 540 may be seen in greater detail in FIG. 10. The electrode structure generally includes a plurality of electrodes 542 distributed in a path defining a loop and a common or counter electrode 544. The plurality of electrodes may be formed in a manner as previously described by use of an insulated conductor, such as an insulated wire with discrete portion of the insulation removed to form the electrodes. Each of the electrodes 542 forms a shock wave source. As may be seen in FIG. 9, the electrodes 542 are arranged to be in non-touching relation to the sidewalls of the balloon 526.

[0071] In use, one polarity, as for example the positive polarity, of the arc forming voltage may be applied to the plurality of electrodes 542. The minus polarity may be applied to the

counter electrode 544. Because the electrodes 542 are distributed along the loop as shown, the spacing between the electrodes and the valve will remain essentially constant to enable the entire aortic valve to be treated without diminished shock wave intensities.

[0072] FIG. 11 is another simplified side view of the left ventricle 500, aorta 502, and aortic valve 504 of a heart with another valvuloplasty treatment catheter 610 embodying the invention within the aortic valve of the heart. The catheter 610 includes a treatment balloon 626 placed on both sides of the aortic valve leaflets 506. The treatment balloon 626 includes two longitudinally spaced chambers 628 and 630 placed on opposite sides of the aortic valve leaflets 506. The balloon 626 may be formed from a compliant or a non-compliant material. The balloon is at the distal end of a carrier 621. The catheter is placed into position by an elongated delivery tube 632.

[0073] The two longitudinally spaced chambers 630 and 628 share a common inflation lumen 634 of the carrier 621 to permit the balloon 626 to be filled with a liquid, such as saline. Alternatively the balloon chambers 630 and 628 may not share the same inflation fluid path.

[0074] Each of the balloon chambers 628 and 630 of the catheter 610 includes a plurality of shock wave sources that produce electrical arcs within their respective chambers of the balloon to produce shock waves within the confined liquid. The shock waves propagate through the liquid and impinge upon the balloon wall and the valve. The impinging shock waves cause the calcified material on the valve to break and/or soften. This permits the valve opening to be widened or the calcified material to be removed.

[0075] In accordance with the embodiment of FIG. 11, the catheter 610 includes an electrode structure 640A and 640B within balloon chambers 628 and 630, respectively. The electrode structures may take the form of electrode structure 540 as shown in FIG. 10. Because the electrodes are distributed in each balloon chamber 628 and 630 along a loop as shown, the spacing between the electrodes and the valve on each side of the valve will remain essentially constant to enable both sides of the entire aortic valve to be treated without diminished shock wave intensities.

[0076] FIG. 12 is a partial side view, to an enlarged scale, of an angioplasty catheter with an electrode structure that may be employed in the embodiments herein, wherein the electrodes are arranged in series circuit. The catheter 710 may be seen to include an angioplasty balloon 726 that is carried at the distal end of an elongated insulated carrier 721 in sealed relation thereto. As in previous embodiments, the carrier has a guide wire lumen 729.

[0077] Embedded within the carrier 721 is a conductor 740 that extends to the distal end of the carrier and then back toward the proximal end as shown. At points along the carrier 721 and the conductor 740, portions of the carrier 721 are removed. Corresponding portions of the conductor are also removed. Each removed conductor portion forms a pair of electrodes. For example, removed portion 742 forms an electrode pair 743. Similarly, removed portions 744 and 746 form electrode pairs 745 and 747 respectively. One side of the openings 742, 744, and 746 are coated with a conductive material to render one electrode 743a, 745a, and 747a of each electrode pair larger in surface area than the its other corresponding electrode.

[0078] Each of the electrode pairs 743, 745, and 747 forms a shock wave source. As may be noted in FIG. 13, the electrode pairs 743, 745, and 747 are arranged in series circuit. They are connected to a high voltage source 730 through a connector 732. The larger electrode 743a, 745a, and 747a of each electrode pair assures that all of the electrode pairs will reliably arc when the high voltage is applied across the string of shock wave sources.

[0079] FIG. 14 is a simplified schematic diagram of a shock wave angioplasty system 800 embodying the invention wherein the shock wave source electrodes are arranged in plural series circuits with each series circuit being individually activated. To that end, the system 800 includes series circuits 802, 804, and 806 of electrode pairs connected to a multiplexer 734 through a connector 732. The multiplexer is arranged to connect a high voltage source 730 across each series circuit 802, 804, and 806 individually, one at a time, or in any combination.

[0080] FIG. 15 is a simplified drawing of another angioplasty system 900 embodying the invention including a side view of a dilating angioplasty balloon catheter 910 including a plurality of shock wave sources that are selectably coupled to a power source, one at a time, according to another embodiment, and FIG. 16 is a timing diagram illustrating the manner in which the electrodes of FIG. 15 may be selectably coupled to a power source. The system 900 includes a catheter 920, and high voltage power source 930, and a connector 934. The catheter 920 includes an angioplasty balloon 926 carried on a carrier 921 in sealed relation thereto and arranged to be inflated by a liquid, such as saline. The catheter 920 also includes electrodes 940, 942, and 944 carried on the carrier 921 in non-touching relation to the sidewalls of the balloon 926, and a counter electrode 946, also carried on the carrier 921. The electrodes 940, 942, and 944 are each connected to a multiplexer 934 of the high voltage source 930. When an electrode is activated, a high voltage from source 930 is applied across a selected one of the electrodes and the counter electrode to create an electrical arc. The electrical arc causes a plasma to be formed.

The creation of the plasma causes a shock wave. Hence, each electrode 940, 942, and 944 forms a shock wave source. The shock waves are propagated through the liquid to impinge upon the balloon sidewall and the calcium deposit to break the calcium deposit up.

[0081] As may be seen in FIG. 16, the multiplexer 934 can activate the shock wave sources, one at a time. This reserves all of the high voltage for each shock wave source to thus form shock waves of maximum strength to be applied to the calcium deposits all along the balloon. The shock waves can be of repeatable strength. Longitudinal movement of the catheter to treat the calcium deposits is not required.

[0082] While particular embodiments of the present invention have been shown and described, modifications may be made, and it is therefore intended to cover all such changes and modifications which fall within the true spirit and scope of the invention.

CLAIMS

What is claimed is:

1. A device comprising:
a catheter having a longitudinal axis and a guide wire lumen therethrough;
a balloon that is sealably disposed over a longitudinal length of the catheter, the balloon being inflatable with a liquid; and
a plurality of shock wave electrodes carried by the catheter and enclosed within the balloon, wherein the shock wave electrodes are arranged longitudinally and configured to produce shock waves that propagate through the liquid.
2. The device of claim 1, wherein the plurality of shock wave electrodes are located along the longitudinal axis of the catheter.
3. The device of claim 2, wherein the plurality of shock wave electrodes are arranged in a series circuit configuration.
4. The device of claim 2, wherein a first set of at least two shock wave electrodes are connected in series and wherein a second set of at least two shock wave electrodes are connected in series, and the device further comprises:
a high voltage source connectable to the shock wave electrodes; and
a multiplexer selectively connecting the high voltage source to each of the first and second sets of shock wave electrodes.
5. The device of claim 4, wherein each of the electrodes include a positive and negative terminal in spaced apart relation and wherein the series connection is completed when the shock wave electrodes are activated with the high voltage source.
6. The device of claim 3, wherein the plurality of shock wave electrodes comprise a plurality of shock wave electrode pairs, wherein each shock wave electrode pair comprises a positive terminal and a negative terminal, and wherein when a positive voltage is applied to the

positive terminal, an arc capable of generating a shock wave will form between positive and negative terminals of the shock wave electrode pair.

7. The device of claim 6, wherein the positive terminal of a first shock wave electrode pair is configured to be connected to a positive voltage port of a high voltage generator, and the negative terminal of the first shock wave electrode pair is the positive terminal of a second shock wave electrode pair.

8. The device of claim 7, further comprising a third shock wave electrode pair and a fourth shock wave electrode pair, wherein the negative terminal of the second shock wave electrode pair is the positive terminal of the third shock wave electrode pair, the negative terminal of the third shock wave electrode pair is the positive terminal of the fourth shock wave electrode pair, and the negative terminal of the fourth shock wave electrode pair is configured to be connected to a negative voltage port of the high voltage generator.

9. The device of claim 8, further comprising a fifth shock wave electrode pair and a sixth shock wave electrode pair connected in series with the fifth shock wave electrode pair, wherein the positive terminal of the fifth shock wave electrode pair is configured to be connected to the positive voltage port of the high voltage generator, the negative terminal of the fifth shock wave electrode pair is the positive terminal of the sixth shock wave electrode pair, and the negative terminal of the sixth shock wave electrode pair is configured to be connected to the negative voltage port of the high voltage generator.

10. The device of claim 9, further comprising a multiplexer connected to the positive terminals of the first and fifth shock wave electrode pairs, and is configured to selectively connect the positive terminal of either the first shock wave electrode pair or the fifth shock wave electrode pair to the positive voltage port of the high voltage generator.

11. The device of claim 2, further comprising a high voltage source and a multiplexer configured to selectively connect the high voltage source to each of the plurality of shock wave electrodes.

12. The device of claim 2, wherein the plurality of shock wave electrodes comprises a first plurality of shock wave electrodes and a second plurality of shock wave electrodes

corresponding to each of the first plurality of electrodes, wherein the first and second plurality of shock wave electrodes are configured such that when a first voltage is applied to the first plurality of shock wave electrodes and a reverse voltage is applied to the second plurality of shock wave electrodes, an arc capable of generating a shock wave will form between corresponding first and second shock wave electrodes.

13. The device of claim 12, wherein the shock wave electrodes are arranged in a parallel circuit configuration.

14. The device of claim 13, wherein the first plurality of shock wave electrodes are configured to be connected to a positive terminal of a high voltage generator, and the second plurality of shock wave electrodes are configured to be connected to a negative terminal of the high voltage generator.

15. The device of claim 14, further comprising a connector configured to connect the first and second plurality of shock wave electrodes to the terminals of the high voltage generator.

16. The device of claim 13, wherein the first plurality of shock wave electrodes comprise a first conductor and the second plurality of shock wave electrodes comprise a second conductor, wherein the first and second conductors extend along and within the catheter.

17. The device of claim 2, further comprising at least one counter electrode adapted to be in contact with the liquid and to receive a voltage polarity opposite a voltage polarity applied to the plurality of shock wave electrodes.

18. The device of claim 2, further comprising a power source and a multiplexer that selectively couples the power source to the plurality of shock wave electrodes, one at a time.

19. The device of any of the preceding claims, wherein the catheter is formed of an insulating material, wherein the plurality of shock wave electrodes comprises at least one conductor extending within the catheter in spaced apart relation to the guide wire lumen and along the longitudinal axis of the catheter, and wherein a plurality of discrete portions of the catheter insulating material are removed to expose corresponding portions of the at least one conductor.

20. The device of claim 19, wherein at least some of the removed discrete portions of the catheter insulating material contain a conductive filling and wherein the conductive fillings are secured to the catheter.

21. The device of claim 1, wherein the balloon is configured to be placed adjacent leaflets of a heart valve, the balloon having a first chamber configured to be placed adjacent one side of the leaflets and a second chamber configured to be placed adjacent an opposite side of the leaflets, and wherein the plurality of shock wave electrodes are arranged to define a first loop of shock wave electrodes within the first chamber of the balloon and a second loop of shock wave electrodes within the second chamber of the balloon.

22. The device of claim 1, wherein the balloon comprises first and second longitudinally spaced chambers.

23. The device of claim 22, wherein the catheter comprises a first electrode structure having a curved distal portion, and wherein a first plurality of shock wave electrodes are located on the curved distal portion of the first electrode structure.

24. The device of claim 23, wherein the catheter further comprises a second electrode structure having a curved distal portion, and wherein a second plurality of shock wave electrodes are located on the curved distal portion of the second electrode structure.

25. The device of claim 24, wherein the first electrode structure is configured to be positioned within the first chamber of the balloon and the second electrode structure is configured to be positioned within the second chamber of the balloon.

26. The device of any one of claims 21 to 25, wherein the catheter further comprises a counter electrode configured to receive a voltage polarity opposite a voltage polarity applied to the first and second plurality of shock wave electrodes.

27. The device of any one of the preceding claims, wherein the plurality of shock wave electrodes comprises an elongated conductor and an insulator overlying the elongated conductor, and wherein the insulator has a plurality of discrete openings, each opening for exposing the elongated conductor to the fluid.

28. The device of claim 27, wherein the elongated conductor is cylindrical.

29. The device of any of the preceding claims, wherein the balloon has a sidewall and wherein the plurality of shock wave electrodes is in non-touching relation with respect to the balloon sidewall.

30. An apparatus, comprising:
a balloon adapted to be placed adjacent a calcified region of a body, the balloon being inflatable with a liquid; and
a shock wave generator within the balloon that produces shock waves that propagate through the liquid for impinging upon the calcified region adjacent the balloon,
wherein the shock wave generator comprises a plurality of shock wave sources distributed within the balloon, wherein the plurality of shock wave sources comprises more than two shock wave sources.

31. The apparatus of claim 30, wherein the balloon is elongated having a longitudinal dimension and wherein the plurality of shock wave sources extend along a portion of the longitudinal dimension.

32. The apparatus of claim 30, wherein the balloon has a sidewall and wherein the shock wave sources are in non-touching relation with respect to the balloon sidewall.

33. The apparatus of claim 32, wherein the shock wave generator is an electrical arc shock wave generator and wherein the shock wave sources include a plurality of electrodes.

34. The apparatus of claim 33, wherein the electrical arc shock wave generator further includes at least one counter electrode adapted to be in contact with the liquid and to receive a voltage polarity opposite a voltage polarity applied to the plurality of electrodes.

35. The apparatus of claim 34, wherein the shock wave generator includes an elongated conductor and an insulator overlying the elongated conductor, and wherein the insulator has a plurality of discrete openings, each opening for exposing the elongated conductor to the fluid, to form the plurality of electrodes.

36. The apparatus of claim 35, further comprising an insulated wire forming the elongated conductor and the overlying insulator.

37. The apparatus of claim 36, further comprising an elongated carrier, wherein the carrier extends through the balloon and is sealed thereto, and wherein the insulated wire is wrapped about the carrier within the balloon.

38. The apparatus of claim 37 wherein the carrier includes a guide wire lumen.

39. The apparatus of claim 37, wherein the insulated wire is wrapped about the carrier to form electrode coil turns and wherein the apparatus further includes a conductor wire wrapped about the carrier within the balloon and in between the electrode coil turns to form the counter electrode.

40. The apparatus of claim 34, wherein the shock wave generator includes an elongated cylindrical conductor and an insulator overlying the elongated cylindrical conductor, and wherein the insulator has a plurality of discrete openings, each opening for exposing the elongated cylindrical conductor to the fluid, to form the plurality of electrodes.

41. The apparatus of claim 40, further comprising an elongated carrier extending through the balloon and being in sealed relation thereto, wherein the elongated cylindrical conductor overlies the carrier within the balloon.

42. The apparatus of claim 41, wherein the elongated carrier includes a guide wire lumen.

43. The apparatus of claim 30, wherein the shock wave generator is an electrical arc shock wave generator, wherein the shock wave sources include a plurality of electrodes, wherein the apparatus further includes an elongated carrier having a longitudinal dimension extending through the balloon and being in sealed relation thereto, wherein the elongated carrier has a guide wire lumen extending along at least a portion of the longitudinal dimension of the elongated carrier, and wherein at least some of the plurality of electrodes are distributed along the elongated carrier within the balloon.

44. The apparatus of claim 43 wherein the elongated carrier is formed of an insulating material, wherein the shock wave generator includes at least one conductor extending within the elongated carrier in spaced apart relation to the guide wire lumen and along at least a portion of the longitudinal dimension of the elongated carrier, and wherein a plurality of discrete

portions of the elongated carrier insulating material are removed to expose corresponding portions of the at least one conductor to form the at least some of the plurality of electrodes.

45. The apparatus of claim 44 wherein at least some of the removed discrete portions of the elongated carrier insulating material contain a conductive filling and wherein the conductive fillings are conductively secured to the elongated conductor.

46. The apparatus of claim 43 wherein the elongated carrier is formed of an insulating material, wherein the shock wave generator includes at least first and second elongated conductors extending within the elongated carrier in spaced apart relation to each other and the guide wire lumen and along at least a portion of the longitudinal dimension of the elongated carrier, and wherein a plurality of discrete portions of the elongated carrier insulating material are removed to expose corresponding portions of the at least first and second conductors to form the at least some of the plurality of electrodes.

47. The apparatus of claim 46 wherein the removed discrete portions of the elongated carrier insulating material that expose corresponding portions of one of the at least first and second conductors are greater in dimension than the removed discrete portions of the elongated carrier insulating material that expose corresponding portions of another one of the at least first and second conductors.

48. The apparatus of claim 47 wherein at least some of the removed discrete portions of the elongated carrier insulating material contain a conductive filling and wherein at least some of the conductive fillings are conductively secured to the elongated conductors.

49. The apparatus of claim 33, wherein the plurality of electrodes are arranged in series circuit relation.

50. The apparatus of claim 33, wherein the plurality of electrodes are arranged in parallel circuit relation.

51. The apparatus of claim 33 further comprising a power source and a multiplexer that selectively couples the power source to the plurality of electrodes, one at a time.

52. The apparatus of claim 33, wherein the plurality of electrodes are arranged in a plurality of series circuit arrangements and wherein the apparatus further comprises a

multiplexer that selectively couples the power source to the series circuit arrangements, one at a time.

53. The apparatus of claim 30, wherein the plurality of shock wave sources are arranged along a path defining a loop.

54. The apparatus of claim 30, wherein the balloon is configured to be placed adjacent leaflets of a valve, the balloon having a first chamber to be adjacent one side of the leaflets and a second chamber to be adjacent an opposite side of the leaflets, and wherein the plurality of shock wave sources are arranged to define a loop of shock wave sources within one of the first and second chambers of the balloon.

55. The apparatus of claim 30, wherein the balloon is configured to be placed adjacent leaflets of a valve, the balloon having a first chamber to be adjacent one side of the leaflets and a second chamber to be adjacent an opposite side of the leaflets, and wherein the plurality of shock wave sources are arranged to define a first loop of shock wave sources within the first chamber of the balloon and a second loop of shock wave sources within the second chamber of the balloon.

56. The apparatus of claim 53, wherein the balloon has a sidewall and wherein the shock wave sources are in non-touching relation with respect to the balloon sidewall.

57. The apparatus of claim 56, wherein the shock wave generator is an electrical arc shock wave generator and wherein the shock wave sources include a plurality of electrodes.

58. The apparatus of claim 57, wherein the electrical arc shock wave generator further includes a counter electrode adapted to be in contact with the liquid and to receive a voltage polarity opposite a voltage polarity applied to the plurality of electrodes.

59. The apparatus of claim 57, wherein the shock wave generator includes an elongated conductor and an insulator overlying the elongated conductor, and wherein the insulator has a plurality of discrete openings, each opening for exposing the elongated conductor to the fluid, to form the plurality of electrodes.

60. The apparatus of claim 59, wherein the balloon is elongated having a longitudinal dimension and wherein the plurality of electrodes extend along a portion of the longitudinal dimension.

61. The apparatus of claim 60, wherein the balloon is configured to be placed adjacent leaflets of a valve, the balloon having a first chamber to be adjacent one side of the leaflets and a second chamber to be adjacent an opposite side of the leaflets, and wherein the plurality of electrodes are arranged to define a loop of electrodes within one of the first and second chambers of the balloon.

62. The apparatus of claim 60, wherein the balloon is configured to be placed adjacent leaflets of a valve, the balloon having a first chamber to be adjacent one side of the leaflets and a second chamber to be adjacent an opposite side of the leaflets, and wherein the plurality of electrodes are arranged to define a first loop of electrodes within the first chamber of the balloon and a second loop of electrodes within the second chamber of the balloon.

63. The apparatus of claim 60, further comprising an insulated wire forming the elongated conductor and the overlying insulator.

64. An apparatus, comprising:
an elongated carrier;
a balloon carried on the elongated carrier in sealed relation thereto, being adapted to be placed adjacent a calcified region of a body, and being inflatable with a liquid; and
an electrical arc shock wave generator within the balloon, the electrical arc shock wave generator comprising more than two electrodes distributed within the balloon, each electrode adapted to produce shock waves that propagate through the liquid for impinging upon the calcified region adjacent the balloon, and a counter electrode adapted to be in contact with the liquid and to receive a voltage polarity opposite that applied to the more than two electrodes.

65. A method comprising:
inserting a balloon in a body adjacent a calcified region;
inflating the balloon with a liquid to cause the balloon to contact the calcified region;
placing, within the balloon, a shock wave generator including more than two shock wave sources and distributing the more than two shock wave sources within the balloon; and

causing the shock wave sources to form shock waves that propagate through the liquid and impinge upon the calcified region.

66. The method of claim 65, wherein the inserting step includes inserting the balloon into an artery or vein of the body.

67. The method of claim 65, wherein the balloon is elongated having a longitudinal dimension and wherein the distributing step includes distributing the shock wave sources along a portion of the longitudinal dimension.

68. The method of claim 65, wherein the inserting step includes inserting the balloon into a valve of the body.

69. The method of claim 68, wherein the distributing step includes distributing the shock wave sources along a path defining a loop.




70. The method of claim 65, wherein the balloon is configured to be placed adjacent leaflets of the valve, the balloon having a first chamber to be adjacent one side of the leaflets and a second chamber to be adjacent an opposite side of the leaflets, wherein the inserting step includes inserting the balloon into the valve with the first chamber adjacent one side of the leaflets and the second chamber adjacent the opposite side of the leaflets, and wherein the distributing step includes distributing the shock wave sources along a path defining a loop of shock wave sources within one of the first and second chambers of the balloon.

71. The method of claim 65, wherein the balloon is configured to be placed adjacent leaflets of the valve, the balloon having a first chamber to be adjacent one side of the leaflets and a second chamber to be adjacent an opposite side of the leaflets, wherein the inserting step includes inserting the balloon into the valve with the first chamber adjacent one side of the leaflets and the second chamber adjacent the opposite side of the leaflets, and wherein the distributing step includes distributing the shock wave sources to define a first loop of shock wave sources within the first chamber of the balloon and to define a second loop of shock wave sources within the second chamber of the balloon.





72. The method of claim 65, wherein the balloon has a sidewall and wherein the distributing step includes distributing the shock wave sources in non-touching relation with respect to the balloon sidewall.

73. The method of claim 65, wherein the shock wave generator is an electrical arc shock wave generator, wherein the shock wave sources include a plurality of electrodes, and wherein the causing step includes applying voltage pulses between the plurality of electrodes and a counter electrode to form the shock waves.

74. A method comprising:
inserting a balloon in a body adjacent a calcified region;
inflating the balloon with a liquid to cause the balloon to contact the calcified region;
placing within the balloon more than two electrodes in non-touching relation to the balloon and adjacent the calcified regions;
placing a counter electrode in contact with the liquid; and
applying voltage pulses between the more than two electrodes and the counter electrode, the voltage pulses having a first polarity applied to the two or more electrodes and a second polarity applied to the counter electrode causing the more than two electrodes to form shock waves that propagate through the liquid and impinge upon the calcified region.



2/6



3/6

FIG. 8




FIG. 9




FIG. 10





FIG. 11



5/6

FIG. 12




FIG. 13







FIG. 14



6/6



INTERNATIONAL SEARCH REPORT

International application No
PCT/US2013/048277

A. CLASSIFICATION OF SUBJECT MATTER

INV. A61B17/22 A61M25/10
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EP0-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2009/312768 A1 (HAWKINS DANIEL [US] ET AL) 17 December 2009 (2009-12-17)	1,2
Y	paragraph [0004]; figures 2-9	3-64
Y	WO 2009/121017 A1 (UNIV CALIFORNIA [US]; ANGIODYNAMICS INC [US]; RUBINSKY BORIS [IL]; MAO) 1 October 2009 (2009-10-01) paragraphs [0109], [0110]; figures 10,12,15A,15B	3-64
Y	WO 2011/143468 A2 (SHIFAMED LLC [US]; SALAHIEH AMR [US]; LEPAK JONAH [US]; LEUNG EMMA [US]) 17 November 2011 (2011-11-17) paragraph [0146]; figures 18P-S,28A-F,32A-B,33A-D,34A-F	3-64
	-/-	



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

25 September 2013

Date of mailing of the international search report

02/10/2013

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Viidebaum, Mikk

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2013/048277

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	US 2010/114020 A1 (HAWKINS DANIEL [US] ET AL) 6 May 2010 (2010-05-06) paragraphs [0008], [0011], [0012], [0013], [0027]; figures 1-4 -----	1 2-64

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2013/048277

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2009312768 A1	17-12-2009	AU 2009257368 A1	17-12-2009
		CA 2727429 A1	17-12-2009
		EP 2300091 A2	30-03-2011
		JP 2011524203 A	01-09-2011
		US 2009312768 A1	17-12-2009
		US 2011166570 A1	07-07-2011
		US 2013030447 A1	31-01-2013
		WO 2009152352 A2	17-12-2009

WO 2009121017 A1	01-10-2009	US 2009247933 A1	01-10-2009
		US 2009248012 A1	01-10-2009
		WO 2009121009 A2	01-10-2009
		WO 2009121017 A1	01-10-2009

WO 2011143468 A2	17-11-2011	AU 2011252976 A1	08-11-2012
		CA 2797130 A1	17-11-2011
		CN 103118620 A	22-05-2013
		EP 2568905 A2	20-03-2013
		JP 2013529109 A	18-07-2013
		US 2012071870 A1	22-03-2012
		WO 2011143468 A2	17-11-2011

US 2010114020 A1	06-05-2010	AU 2009313507 A1	14-05-2010
		CA 2779600 A1	14-05-2010
		CN 102271748 A	07-12-2011
		EP 2362798 A2	07-09-2011
		JP 2012508042 A	05-04-2012
		US 2010114020 A1	06-05-2010
		US 2011295227 A1	01-12-2011
		WO 2010054048 A2	14-05-2010

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2013/048277

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 65-74
because they relate to subject matter not required to be searched by this Authority, namely:
see FURTHER INFORMATION sheet PCT/ISA/210
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

Continuation of Box II.1

Claims Nos.: 65-74

Claims 65-74 relate to a method that involves inserting a balloon in a body adjacent a calcified region and is considered to encompass an invasive step representing a substantial physical intervention on the body, which requires professional medical expertise and is therefore not in compliance with Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery.