

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
1 February 2001 (01.02.2001)

PCT

(10) International Publication Number
WO 01/07682 A1

(51) International Patent Classification⁷: **C23F 11/18**

(21) International Application Number: PCT/US00/20231

(22) International Filing Date: 25 July 2000 (25.07.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/360,768 26 July 1999 (26.07.1999) US

(71) Applicant: **A. S. INCORPORATED** [US/US]; 980 77th
Avenue, Oakland, CA 94621 (US).

(72) Inventor: **RIGGS, Olen, L., Jr.**; 4000 Stonebridge Court,
Yukon, OK 73099 (US).

(74) Agents: **GORTHEY, LeeAnn et al.**; Iota Pi Law Group,
P.O. Box 60850, Palo Alto, CA 94306-0850 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 01/07682 A1

(54) Title: CORROSION INHIBITION METHOD SUITABLE FOR USE IN POTABLE WATER

(57) Abstract: Effective corrosion inhibitors having minimal organic content, particularly suitable for use in municipal drinking water systems, are described. The preferred corrosion inhibiting additive is an aqueous solution of a stannous halide, preferably stannous chloride.

Corrosion Inhibition Method Suitable for Use in Potable Water

Field of the Invention

The present invention relates to methods for inhibiting corrosion of corrodible metals present in contact with water in distributive water systems, particularly those associated with distribution of drinking water.

Background of the Invention

In 1992, the United States Environmental Protection Agency adopted a standard for lead and copper in municipal drinking water. The standard sets action levels for lead and copper in standing samples collected from faucets with the highest risk for elevated lead and copper levels. The action level for lead is 15 μg /liter of water; the action level for copper is 1.3 mg/liter of water. The source of these and other metals in drinking water is primarily corrosion of plumbing system components, which include copper and lead-based solder as well as carbon steel and brass. Current anticorrosion additives, which include phosphate salts and/or zinc salts, have been in use for many years, but do not always provide adequate protection. There remains a need for improved corrosion inhibitors which are not themselves likely to present a health hazard when added to water.

Co-owned U.S. Patents No. 5,202,028 and No. 5,510,057 describe the use of stannous salts, such as stannous octanoate or stannous chloride, typically in combination with other additives, in an alcoholic solvent medium, for reducing metal corrosion in, for example, cooling water tower systems. However, these additional components, including the alcoholic solvent, would be undesirable or even prohibited for use in drinking water supplies. Alcoholic solvents can provide a food source for the growth of bacteria and thus impact the sterility of drinking water supplies. Reduction in microbial growth would be beneficial in industrial water supplies as well. Accordingly, there is a need for effective corrosion inhibitors which minimize organic content.

Summary of the Invention

The present invention includes, in one aspect, a method for inhibiting corrosion of corrodible metal in contact with water in a distributive water system. According to the method, stannous halide alone, a composition consisting essentially of stannous halide, or a composition consisting essentially of an aqueous stannous halide solution, is added to the water, and a concentration of the stannous halide corresponding to a tin level of about 0.01 to about 75 ppm is maintained in the water system.

The halide is preferably selected from stannous fluoride, stannous chloride, and stannous bromide, and is most preferably stannous chloride. The stannous halide is preferably added in the form of an aqueous solution. The weight percent of stannous chloride in an aqueous stannous chloride solution is preferably about 5 to 90 percent, and more preferably about 40
5 to 80 percent. The concentration of stannous chloride corresponding to a tin level of about 0.01 to about 75 ppm is about 0.016 ppm to about 120 ppm SnCl_2 ; a preferred concentration range for stannous chloride in the water system is about 0.05 to 25 ppm SnCl_2 .

The corrodible metal is typically a ferrous metal, a brass metal, a copper-containing metal, or a lead-containing metal. In a preferred embodiment of the method, the distributive
10 water system is a municipal drinking water system. Such a system may initially contain an alkali metal phosphate, such as a pyrophosphate, an orthophosphate, a hexametaphosphate, a hypophosphate, a polyphosphate, or a combination thereof, typically in an amount effective to provide a concentration of about 0.01 ppm to about 5 ppm of the alkali metal phosphate in the water system. The water system may also be treated to contain at least one component
15 selected from a dispersing agent, a chelating agent, and a biocide.

In another aspect, the invention provides a related method for inhibiting corrosion of corrodible metal in contact with water in a distributive water system. In this method, stannous halide alone, a composition consisting essentially of stannous halide, or a composition consisting essentially of an aqueous stannous halide solution, is added to the
20 water system, in combination with an alkali metal phosphate selected from a pyrophosphate, an orthophosphate, a hexametaphosphate, a hypophosphate, and a polyphosphate. A concentration of the stannous halide corresponding to a tin level of about 0.01 to about 75 ppm is maintained in the water system. Again, stannous chloride is the preferred halide, and is preferably maintained at a level of about 0.05 ppm to about 25 ppm in the water system.
25 The alkali metal phosphate, e.g. sodium hexametaphosphate or sodium orthophosphate, is typically present in an amount effective to provide a concentration of about 0.01 ppm to about 5 ppm in the water system.

In a further aspect, the invention provides a metal corrosion inhibiting composition, consisting essentially of (i) stannous halide or a an aqueous stannous halide solution and (ii)
30 an alkali metal phosphate selected from a pyrophosphate, an orthophosphate, a hexametaphosphate, a hypophosphate, and a polyphosphate. In preferred embodiments, the stannous halide is stannous chloride, and the stannous chloride and alkali metal phosphate are present in relative amounts effective to produce concentrations of about 0.05 ppm to about 25 ppm and about 0.01 ppm to about 5 ppm, respectively, in a distributive water system. The

composition may also include one or more substances typically added to a distributive water stream for purposes other than inhibition of corrosion, such as a dispersing agent, chelating agent, or biocide. In one embodiment, the composition includes an acrylate copolymer, e.g. an acrylate/sulfonate copolymer.

5 These and other objects and features of the invention will become more fully apparent when the following detailed description of the invention is read in conjunction with the accompanying drawings.

Detailed Description of the Invention

I. Definitions

10 “Corrosion” of a metal in contact with water, as used herein, refers to degradation of the metal due to chemical reaction with its environment, in this case, water and substances present in the water, including air. Such corrosion ultimately leads to dissolution or dispersion of the metal or metal compound in the water, observed as a loss of mass of the metal.

15 As used herein, “aqueous stannous halide” or “an aqueous stannous halide solution” refers to a composition of stannous halide in water, typically in fairly high concentration, i.e., about 30 weight percent or greater. The composition may include an acid, e.g. HCl, to promote dissolution of the stannous halide. There are no other components in any appreciable concentration.

20 A “composition consisting essentially of” stannous halide (or an aqueous stannous halide solution) refers to stannous halide (or an aqueous stannous halide solution) in combination with one or more optional components which do not materially affect the metal corrosion inhibiting characteristic(s) of the composition. Such components would typically be substances added to a distributive water stream for purposes other than inhibition of
25 corrosion, as defined above. For example, dispersing or chelating agents, such as soluble anionic polymers (e.g. polyacrylates or acrylate copolymers), may be employed to reduce scale formation on solid surfaces; biocides may be added to reduce microbial growth.

30 A similar definition applies to compositions consisting essentially of stannous halide (or an aqueous stannous halide solution) and an alkali metal phosphate. Such compositions may also include components present for purposes other than inhibition of corrosion.

 The “halide” in the above definitions is selected from fluoride, chloride, bromide, or iodide; the halide is preferably fluoride, chloride, or bromide, and is most preferably chloride.

 A “concentration of stannous halide which corresponds to a concentration of tin” in a

given concentration range is determined from the relative molecular weights of the components, for example:

0.010 ppm tin corresponds to approx. 0.013 ppm SnF_2 , 0.016 ppm SnCl_2 , or 0.023 ppm SnBr_2 ;

5	0.150	"	0.20	"	0.24	"	0.35	"
	1.0	"	1.32	"	1.60	"	2.34	"
	10	"	13.2	"	16.0	"	23.4	"
10	75	"	99	"	120	"	176	"

In the appended claims, water contained in a distributive water system to which a corrosion inhibitor is added is referred to as the "water system", rather than simply "water", to avoid confusion with the concentrated aqueous stannous halide solutions.

II. Preparation of Aqueous Stannous Chloride Solutions and Use in Corrosion Inhibition

To form the minimal organic content corrosion inhibitors of the invention, any stannous halide, or preferably a concentrated aqueous solution of the stannous halide, may be used. Because stannous iodide has a relatively low aqueous solubility, stannous fluoride, bromide, and chloride are preferred. For reasons of solubility and stability, stannous chloride is particularly preferred.

Highly concentrated aqueous stannous chloride solutions, i.e. up to 90 weight percent SnCl_2 , may be conveniently prepared by adding water to stannous chloride in the desired weight ratio and stirring for a brief period of time. Dissolution is enhanced by using water which is slightly acidic. Such a solution may then be added to a distributive water system in an amount needed to produce a desired concentration of SnCl_2 , e.g. about 0.05 ppm to about 25 ppm (about 0.03 to 16 ppm tin), in the water system. The concentration of SnCl_2 in the water system may then be monitored, by techniques known in the art, and adjusted as necessary to maintain the desired concentration.

Aqueous stannous chloride solutions containing 50 weight percent SnCl_2 were prepared by adding water to the solid, in the manner described above. In the following experiments, samples of these solutions were added to samples of municipal drinking water effective to provide final concentrations of 0.15 to 1.0 ppm stannous chloride in the water, as shown.

To produce the data shown in Table 1, samples of the metals shown were immersed in samples of municipal drinking water, containing about 3 ppm of the conventional corrosion inhibitor sodium hexametaphosphate (HMP), from a system located in the upper midwestern region of the U.S. The test was carried out according to the procedure described in

Materials and Methods, below. Corrosion rates, expressed in mils per year, were determined after 7 days at 120°F in aerated water samples with and without 0.25 ppm added SnCl_2 . As shown in the Table, significant decreases in corrosion were observed in the SnCl_2 -treated samples, especially with respect to carbon steel, copper and lead corrosion.

5

Table 1

Metal	No added SnCl_2 Rate, MPY	0.25 ppm SnCl_2 Rate, MPY
Carbon Steel	40.2	2.1
Brass (CDA-443)	0.43	0.15
Copper	0.71	0.00
Lead	1.80	0.09

10

To obtain the data shown in Table 2, a specimen of each metal was suspended in a sample of municipal drinking water from Oklahoma (designated OKC) in a one-liter flask equipped with a condenser, gas delivery inlet, and thermometer. The contents of each flask were heated to 120°F under a continuous air flow (1.5 cu ft/min) for seven days. Corrosion rates are again expressed as mils per year; nd = not determined. Various concentrations of SnCl_2 were used, as shown. As the data show, very low concentrations of SnCl_2 were effective in reducing corrosion.

15

Table 2

Metal	No added SnCl_2 * Rate, MPY	Treated (SnCl_2) Rates, MPY			
		0.15 ppm	0.25 ppm	0.50 ppm	1.0 ppm
Lead	1.2	nd	0.13	0.06	0.00
CDA-443 Brass	0.43	0.23	nd	0.02	nd
CDA-120 Copper	0.71	nd	0.00	nd	nd

* The water contains about 3 ppm sodium hexametaphosphate, as discussed below.

II. Corrosion Inhibition by Stannous Chloride in the Presence of Phosphate Additives

20

Currently, municipal water supplies frequently contain, as corrosion inhibiting additives, phosphates and/or zinc salts. For example, samples of OKC drinking water used in the experiments described herein contain, unless otherwise indicated, 3 ppm sodium hexametaphosphate. Therefore, experiments were carried out to examine the comparative and additive effects of aqueous stannous chloride and the phosphate additives already in use.

25

Table 3 shows corrosion rates in MPY for various metals in OKC water (aerated at 120°F, as described for Table 2) containing 3 ppm hexametaphosphate (as received) with and

without other additives. The results show that increasing the amount of phosphate had variable results, depending on the metal tested; in some cases corrosion increased (e.g. for lead). Addition of zinc chloride gave moderate improvements, except in the case of lead. Addition of stannous chloride, however, reduced corrosion significantly, as is most apparent from a comparison of the 3rd and 5th data columns.

Table 3

Metal	Additive ^a					
	3 ppm HMP (as received)	3 ppm HMP 3 ppm OP	6 ppm HMP	3 ppm HMP 3 ppm OP 0.5 ppm SnCl ₂	6 ppm HMP 0.5 ppm SnCl ₂	6 ppm HMP 0.1 ppm Zn ⁺²
1018 Carbon Steel	41.3	25.7	29.5	18.6	11.4	24.3
CDA-443 Brass	0.49	0.28	1.40	0.19	0.02	0.98
CDA-120 Copper	0.72	0.28	0.90	0.00	0.00	0.28
Lead	1.21	2.19	1.10	0.90	0.00	1.13

(a) OP = sodium orthophosphate; HMP = sodium hexametaphosphate

Table 4 gives further data for carbon steel corrosion (aerated at 120°F, as described above), showing combinations of SnCl₂ with varying amounts of phosphate. As shown in the Table, addition of SnCl₂ reduced corrosion in all cases, although it appeared to be more effective at lower levels (3 ppm vs. 6 ppm) of phosphate.

Table 4 (Carbon Steel)

ppm HMP	ppm SnCl ₂	Corrosion, MPY
3 (as received)	0	41.3
3	0.25	6.8
3	0.50	7.6
6 (3 ppm added)	0	29.5
6	0.25	13.3
6	0.50	11.4
3 (as received, plus 3 ppm OP added)	0.25	11.1

To produce the data in Table 5, a sample of OKC water was obtained which had been filtered and disinfected but not treated with phosphate. Corrosion rates were determined for carbon steel in heated, aerated water as described above.

Table 5 (Carbon Steel)

ppm HMP	ppm SnCl ₂	Corrosion, MPY
0	0	49.3
3	0	21.1
3	0.25	13.3
0	0.25	2.1

III. Copper Corrosion Inhibition by SnCl₂ in the Presence of a Polymeric Dispersant or Metal Chelator

As noted above, the present anticorrosive stannous halide compositions may be used in combination with components which do not materially affect the metal corrosion inhibiting characteristic(s) of the composition. Such components would typically be substances added to a distributive water stream for purposes other than inhibition of corrosion. For example, dispersing or chelating agents, such as soluble anionic polymers (e.g. polyacrylates or acrylate copolymers), may be employed to reduce scale formation on solid surfaces. One such polymer, Acumer® 2100 (Rohm & Haas), an acrylate/sulfonate copolymer, was added to test systems such as described above. In these tests, the metal coupons were copper (CDA-110), and the water was municipal drinking water from LaSalle, IL, which contained no phosphate additives. Test conditions were as described in Materials and Methods, below (120 °F, aerated water, 7 days duration).

As shown below, the copolymer had no adverse properties on the corrosion inhibiting properties of SnCl₂. Although larger concentrations of the copolymer alone appeared to increase corrosion, this effect was very effectively counteracted by the presence of SnCl₂.

Also shown in Table 6 is a combination of SnCl₂ with AMP (aminotris(methylenephosphonic acid); Mayoquest® 1320), which is useful in scale control by sequestering calcium and magnesium as well as ferrous ion. Again, the metal coupon showed very low corrosion in the presence of this additive and low concentrations of SnCl₂.

Table 6 (Copper)

Additive	SnCl ₂ , ppm	Corrosion Rate, MPY
Acumer® 2100, 0.25 ppm	0	1.80
Acumer® 2100, 0.25 ppm	0.25	0.0
Acumer® 2100, 3 ppm	0	29.3
Acumer® 2100, 3 ppm	0.50	0.0

AMP, 0.25 ppm	0	1.80
AMP, 0.25 ppm	0.25	0.08

IV. Lead Corrosion Inhibition at Varying pH

A series of tests was run to determine the effectiveness of conventional corrosion inhibitors and SnCl_2 on lead coupons at varying pH. Drinking water from Fall River, MA, having no phosphate additives as received, was used for the tests, using the methods described above. pH was determined using EM Reagents ColorpHast® indicator strips.

Table 7 (Lead)

pH	Treatment	Corrosion Rate, MPY
5.3	None	0.64
5.3 ^(a)	3 ppm OP	3.43
5.3	3 ppm HMP	4.60
7.2	None	2.00
7.2	3 ppm OP	3.39
7.2	3 ppm HMP	2.10
7.2	0.25 ppm SnCl_2	0.03

(a) pH prior to test; analysis after testing gave a reading of 6.9.

As shown in Table 7, corrosion was greater in untreated water at higher pH, which may be partially due to the somewhat higher solubility of lead oxide under these conditions. Both sodium orthophosphate (OP) and sodium hexametaphosphate (HMP) increased the corrosion, particularly under acidic conditions, producing a reddish-yellow corrosion product (lead oxides) on the metal.

However, corrosion was minimal in the sample containing 0.25 ppm SnCl_2 .

The above results show that aqueous stannous chloride is an extremely effective corrosion inhibitor both as a sole additive and in the presence of other substances commonly employed in municipal drinking water supplies, such as alkali metal phosphates, dispersants and metal chelators. Therefore, stannous chloride may be added to systems containing such additives, or it may be added concurrently with the additives. Although the data from the experiments above suggest that aqueous stannous chloride is in fact more effective when used without phosphates, the data also demonstrate that its addition to existing water supplies containing phosphates provides significant benefits over phosphates alone.

While the invention has been described with reference to specific methods and

embodiments, it will be appreciated that various modifications may be made without departing from the invention.

MATERIALS & METHODS

5 A typical corrosion test was carried out in the following manner. The test sample of municipal drinking water was placed in a one liter resin kettle equipped to hold (1) a jacketed water cooled condenser, (2) a mounted air-injection gas tube, and (3) a holder from which the test specimen was suspended and totally immersed in the test water. The complete assembly was placed in a constant temperature oil bath. The test water was agitated by compressed air at a flow rate of 1.5 ft³/min. The temperature was maintained at 120°F for
10 seven days.

Test coupons were generally 1" x 2" x 1/16" in size, with a 1/4" mounting hold centered 1/4" from one end. The test coupons were weighed before and after testing, and weight loss in milligrams was converted to a corrosion rate of milliinches per year (mpy).

IT IS CLAIMED:

1. A method for inhibiting corrosion of corrodible metal in contact with water in a distributive water system, comprising

5 (a) adding to said water system, stannous halide alone, a composition consisting essentially of stannous halide, or a composition consisting essentially of an aqueous stannous halide solution,

and (b) maintaining in said water system a concentration of said stannous halide which corresponds to a concentration of tin between about 0.01 ppm and about 75 ppm.

10 2. The method of claim 1, wherein said stannous halide is selected from the group consisting of stannous fluoride, stannous chloride, and stannous bromide.

3. The method of claim 2, wherein said stannous halide is stannous chloride, and the
15 concentration of stannous chloride in the water system is maintained at about 0.015 ppm to about 120 ppm.

4. The method of claim 3, wherein the concentration of stannous chloride in the water system is maintained at about 0.05 ppm to about 25 ppm.

20 5. The method of claim 3, wherein in step (i) stannous chloride is added in the form of an aqueous stannous chloride solution.

6. The method of claim 3, wherein the weight percent of stannous chloride in said
25 aqueous stannous chloride solution is from about 5 to 90 percent.

7. The method of claim 6, wherein said weight percent is from about 40 to 80 percent.

8. The method of claim 1, wherein said corrodible metal is selected from the group
30 consisting of a ferrous metal, a brass metal, a copper-containing metal, and a lead-containing metal.

9. The method of claim 1, wherein said distributive water system is a municipal drinking water system.

10. The method of claim 1, wherein said water system contains an alkali metal phosphate selected from a pyrophosphate, an orthophosphate, a hexametaphosphate, a hypophosphate, and a polyphosphate.

5 11. The method of claim 10, wherein said alkali metal phosphate is present in an amount effective to provide a concentration of about 0.01 ppm to about 5 ppm in said water system.

12. The method of claim 1, wherein said water system is treated to contain at least one component selected from a dispersing agent, a chelating agent, and a biocide.

10

13. A method for inhibiting corrosion of corrodible metal in contact with water in a distributive water system, comprising

15 a) adding to said water system, a composition consisting essentially of (i) stannous halide or an aqueous stannous halide solution and (ii) an alkali metal phosphate selected from a pyrophosphate, an orthophosphate, a hexametaphosphate, a hypophosphate, and a polyphosphate,

and (b) maintaining in said water system a concentration of said stannous halide which corresponds to a concentration of tin between about 0.01 ppm and about 75 ppm.

20

14. The method of claim 13, wherein said stannous halide is selected from the group consisting of stannous fluoride, stannous chloride, and stannous bromide.

25 15. The method of claim 14, wherein said stannous halide is stannous chloride, and the concentration of stannous chloride in the water system is maintained at about 0.015 ppm to about 120 ppm.

16. The method of claim 15, wherein said concentration of stannous chloride is maintained at about 0.05 ppm to about 25 ppm.

30

17. The method of claim 14, where in step (i) stannous chloride is added in the form of an aqueous stannous chloride solution.

18. The method of claim 13, wherein said alkali metal phosphate is added in an amount effective to provide a concentration of about 0.01 ppm to about 5 ppm in said water system.

35

19. The method of claim 13, wherein said alkali metal phosphate is sodium

hexametaphosphate or sodium orthophosphate.

20. A metal corrosion inhibiting composition consisting essentially of (i) stannous halide or a an aqueous stannous halide solution and (ii) an alkali metal phosphate selected from a
5 pyrophosphate, an orthophosphate, a hexametaphosphate, a hypophosphate, and a polyphosphate.

21. The composition of claim 20, wherein said stannous halide is stannous chloride.

10 22. The composition of claim 21, wherein said stannous chloride and said alkali metal phosphate are present in relative amounts effective to produce concentrations of about 0.05 ppm to about 25 ppm and about 0.01 ppm to about 5 ppm, respectively, in a distributive water system.

15 23. The composition of claim 20, further comprising at least one component selected from a dispersing agent, a chelating agent, and a biocide.

24. The composition of claim 23, wherein said component is an acrylate copolymer.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/20231

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C23F11/18

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C23F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, PAJ, COMPENDEX, CHEM ABS Data, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 265 723 A (KATAYAMA CHEMICAL WORKS CO) 4 May 1988 (1988-05-04) page 6, line 2-5; claims 1,3,4,8; example 1 ---	1-10, 12-17, 19-24
X	EP 0 066 347 A (METAFUSE LTD) 8 December 1982 (1982-12-08) example XIX ---	20-23
A	EP 0 006 065 A (CALGON CORP) 12 December 1979 (1979-12-12) claim 1 --- -/--	1,13



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

30 October 2000

Date of mailing of the international search report

07/11/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Torfs, F

INTERNATIONAL SEARCH REPORT

Int l Application No

PCT/US 00/20231

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	BOFFARDI B P ET AL: "ENVIRONMENTALLY SAFE POTABLE WATER TREATMENTS" MATERIALS PERFORMANCE,US,NACE. HOUSTON, vol. 34, no. 7, 1 July 1995 (1995-07-01), pages 36-39, XP000522974 ISSN: 0094-1492 page 36, line R ---	1,13
A	US 5 202 058 A (RIGGS JR OLEN L) 13 April 1993 (1993-04-13) cited in the application claim 1 ---	1
A	US 5 510 057 A (RIGGS OLEN L) 23 April 1996 (1996-04-23) cited in the application claim 1 ---	1
P,A	US 5 989 322 A (RIGGS JR OLEN LONNIE) 23 November 1999 (1999-11-23) claim 1 ---	1
P,A	US 6 001 156 A (RIGGS JR OLEN LONNIE) 14 December 1999 (1999-12-14) claim 1 -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/20231

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0265723 A	04-05-1988	JP 2608550 B	07-05-1997
		JP 63103090 A	07-05-1988
		CA 1300363 A	12-05-1992
		CN 87107003 A,B	27-04-1988
		DE 3779044 A	17-06-1992
		KR 9310996 B	19-11-1993
		US 4885136 A	05-12-1989
EP 0066347 A	08-12-1982	US 4566992 A	28-01-1986
		AT 26595 T	15-05-1987
		AT 36014 T	15-08-1988
		AT 26596 T	15-05-1987
		AU 7944782 A	22-07-1982
		AU 7944882 A	22-07-1982
		AU 7944982 A	22-07-1982
		BR 8200154 A	03-11-1982
		BR 8200155 A	03-11-1982
		BR 8200156 A	03-11-1982
		CA 1212070 A	30-09-1986
		CA 1187035 A	14-05-1985
		CA 1220160 A	07-04-1987
		DD 202456 A	14-09-1983
		DD 202312 A	07-09-1983
		DD 202313 A	07-09-1983
		DE 3276073 D	21-05-1987
		DE 3276074 D	21-05-1987
		DE 3278814 D	01-09-1988
		DK 10982 A	14-07-1982
		DK 11082 A	14-07-1982
		DK 11182 A	14-07-1982
		EP 0056331 A	21-07-1982
		EP 0057505 A	11-08-1982
		FI 820063 A	14-07-1982
		FI 820064 A	14-07-1982
		FI 820081 A	14-07-1982
		GR 75833 A	02-08-1984
		GR 75834 A	02-08-1984
		GR 77930 A	25-09-1984
		IN 161409 A	28-11-1987
		IN 161410 A	28-11-1987
		JP 1372906 C	07-04-1987
		JP 57174495 A	27-10-1982
		JP 61038272 B	28-08-1986
		JP 1372907 C	07-04-1987
		JP 57174496 A	27-10-1982
		JP 61038273 B	28-08-1986
		JP 1375754 C	22-04-1987
		JP 58042768 A	12-03-1983
		JP 61040316 B	08-09-1986
		MX 157087 A	21-10-1988
		MX 156764 A	30-09-1988
		NO 820074 A	14-07-1982
		NO 820075 A	14-07-1982
		NO 820076 A	14-07-1982
		PL 234879 A	09-05-1983
		PL 234880 A	09-05-1983
		PT 74270 A,B	01-02-1982
		PT 74271 B	23-08-1983

INTERNATIONAL SEARCH REPORT

Information on patent family members

In International Application No

PCT/US 00/20231

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0006065 A	12-12-1979	DK 231879 A JP 54159350 A	06-12-1979 17-12-1979
US 5202058 A	13-04-1993	AU 3065492 A CA 2122896 A WO 9309268 A US 5989322 A US 5510057 A	07-06-1993 13-05-1993 13-05-1993 23-11-1999 23-04-1996
US 5510057 A	23-04-1996	US 5202058 A US 6001156 A AU 3065492 A CA 2122896 A WO 9309268 A US 5989322 A	13-04-1993 14-12-1999 07-06-1993 13-05-1993 13-05-1993 23-11-1999
US 5989322 A	23-11-1999	US 6001156 A US 5202058 A AU 3065492 A CA 2122896 A WO 9309268 A US 5510057 A	14-12-1999 13-04-1993 07-06-1993 13-05-1993 13-05-1993 23-04-1996
US 6001156 A	14-12-1999	US 5510057 A US 5989322 A	23-04-1996 23-11-1999