




(86) Date de dépôt PCT/PCT Filing Date: 2007/11/28
(87) Date publication PCT/PCT Publication Date: 2008/06/05
(85) Entrée phase nationale/National Entry: 2009/05/26
(86) N° demande PCT/PCT Application No.: US 2007/085806
(87) N° publication PCT/PCT Publication No.: 2008/067412
(30) Priorité/Priority: 2006/11/28 (US11/564,084)

(51) Cl.Int./Int.Cl. *B65D 6/18* (2006.01),
A01K 1/03 (2006.01), *A01K 29/00* (2006.01)
(71) Demandeur/Applicant:
T.F.H. PUBLICATIONS, INC., US
(72) Inventeurs/Inventors:
AXELROD, GLEN S., US;
GAJRIA, AJAY, US;
TAO, ZHENGHONG, US
(74) Agent: GOWLING LAFLEUR HENDERSON LLP

(54) Titre : STRUCTURES PLIABLES/ESCAMOTABLES
(54) Title: FOLDABLE/COLLAPSIBLE STRUCTURES



(57) Abrégé/Abstract:

The present invention relates to a collapsible/foldable structure that may include a top roof and a bottom platform. A pair of sidewalls may be provided each of which may be pivotally attached to the roof. The sidewalls may include at least two side section such as an upper and middle section. The sidewalls may also include a lower side section. The upper and middle sections may be

(57) **Abrégé(suite)/Abstract(continued):**

pivotally attached to one another and the middle and lower side section may be pivotally attached to one another so that the upper and middle sidewall sections can be pivoted inwardly towards the bottom platform to provide a collapsed condition. The sidewalls may also each contain an outer and an inner surface thereof wherein the outer surface of the upper side wall and the outer surface of the adjacent middle side wall form an angle that is greater than 180 degrees when the structure is in an expanded or collapsed condition. In addition, the inner surface of the middle wall section may overlie the inner surface of the upper wall section in a collapsed condition.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
5 June 2008 (05.06.2008)

PCT

(10) International Publication Number
WO 2008/067412 A3

(51) International Patent Classification:
B65D 6/18 (2006.01)

(21) International Application Number:
PCT/US2007/085806

(22) International Filing Date:
28 November 2007 (28.11.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
11/564,084 28 November 2006 (28.11.2006) US

(71) Applicant (for all designated States except US): **T.F.H. PUBLICATIONS, INC.** [US/US]; One TFH Plaza, Third and Union Avenues, Neptune City, New Jersey 07753 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **AXELROD, Glen S.** [US/US]; 106 Cedar Drive, Colts Neck, New Jersey 07722 (US). **GAJRIA, Ajay** [US/US]; 304 Cobblestone Court, Monmouth Junction, New Jersey 08852 (US). **TAO, Zhenghong** [CN/US]; 2012 State Rt. 35, Apt. 84, Spring Lake, New Jersey 07762 (US).

(74) Agents: **GROSSMAN, Steven J.** et al.; Grossman, Tucker, Perreault & Pfleger, PLLC, 55 South Commercial Street, Manchester, New Hampshire 03101 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
31 July 2008

(54) Title: FOLDABLE/COLLAPSIBLE STRUCTURES



(57) Abstract: The present invention relates to a collapsible/foldable structure that may include a top roof and a bottom platform. A pair of sidewalls may be provided each of which may be pivotally attached to the roof. The sidewalls may include at least two side section such as an upper and middle section. The sidewalls may also include a lower side section. The upper and middle sections may be pivotally attached to one another and the middle and lower side section may be pivotally attached to one another so that the upper and middle sidewall sections can be pivoted inwardly towards the bottom platform to provide a collapsed condition. The sidewalls may also each contain an outer and an inner surface thereof wherein the outer surface of the upper side wall and the outer surface of the adjacent middle side wall form an angle that is greater than 180 degrees when the structure is in an expanded or collapsed condition. In addition, the inner surface of the middle wall section may overlie the inner surface of the upper wall section in a collapsed condition.

WO 2008/067412 A3

FOLDABLE/COLLAPSIBLE STRUCTURES

CROSS REFERENCE TO RELATED APPLICATIONS

The present application claims the benefit of the filing date of U.S. Patent Application Serial No. 11/564,084 filed November 28, 2007, the teachings of which are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to foldable/collapsible structures, and more particularly to a lightweight animal shelter having increased storage space when expanded and a compact shape when collapsed. The shelter may therefore be readily converted from an expanded to a compact condition for ease of storage and/or transport, and also may present itself as an attractive and/or classic looking doghouse design when fully deployed. This invention also relates to a pet carrier transportation device and in particular to a collapsible/foldable pet carrier or portable structure that may provide safe and sanitary temporary housing for a pet during transport. Furthermore, the present invention may also apply to collapsible storage containers, including such containers as a cooler, or ice chest, which has generally rigid walls, yet can be collapsed or folded into a configuration which takes up much less space, and can therefore be easily stored and/or transported. Finally, the invention herein also may apply to a collapsible structure in general, e.g., a collapsible consumer waste container.

BACKGROUND OF THE INVENTION

A fair amount of disclosures have been put forward in recent years, seeking to develop a foldable/collapsible structure primarily for use as an animal shelter. More specifically, a number of pet houses and enclosures have been proposed with the purpose of

providing a sleeping area for a pet and for confining a pet, when necessary, for example, when traveling.

A number of solutions have been proposed to provide improved structures, including those disclosed in United States Patent Nos. 5,950,568; 6,131,534; 7,021,242; 7,025,019 and
5 United States Patent Application Publication No. 2006/0162670, all commonly assigned to the assignee of the present invention and included herein by reference in their entirety.

Turning to a background consideration relating to pet carriers, it is noted that a variety of pet carriers have been also been reported in the prior art, all aimed in one form or another to facilitate pet transportation. Specifically, pet carriers are commonly used by pet owners for
10 carrying their pets on trips or as a means for containing the pets when the pets are shipped from one point to another. Pet carriers also commonly double as sleeping quarters for the pet as the owner may contain the pet overnight to prevent the pet from wandering and potentially damaging the home or hotel room which the owner is occupying.

BRIEF DESCRIPTION OF THE DRAWINGS

Features and advantages of the present invention will be clear from the following description of exemplary embodiments consistent with the present invention, which
20 description should be considered in conjunction with the accompanying drawings, wherein:

FIG. 1 is a perspective view of one exemplary embodiment of the collapsible/foldable structure of the present invention in an expanded condition.

FIG. 2 is a front view of the collapsible/foldable structure of the **FIG. 1** in a fully collapsed/folded condition.

FIG. 3 is a perspective view of a second exemplary embodiment of the collapsible/foldable structure of the present invention, in a partially collapsed/folded condition, illustrating a wide hinge and a carrying handle.

FIG. 4 is a perspective view of the collapsible/foldable structure of **FIG. 3** in a fully collapsed/folded condition.

FIG. 5 is a perspective view of a third exemplary embodiment of the collapsible/foldable structure of the present invention, in an expanded condition, illustrating curved upper side walls and a top access panel.

FIG. 6 is a perspective view of the exemplary embodiment of **FIG. 5** in a partially collapsed condition, illustrating the angle that the external surfaces of the upper and middle side walls pivot through.

FIG. 7 is an end view of **FIG. 6** illustrating the structure of **FIG. 5** in a fully collapsed and compact condition.

FIG. 8 is a perspective view of a fourth exemplary embodiment of the present invention, illustrating two wide hinges per side, providing additional height and storage space.

FIG 8A is another perspective view illustrating a hinge panel connecting the middle and lower side sections in a collapsed condition.

FIG. 9 is a perspective view of the structure of **FIG. 8** illustrating the structure in a fully collapsed condition.

FIG. 9A is a perspective view of a structure similar to **FIG. 8** but illustrating flexible lower sidewalls in a fully collapsed condition.

FIG. 10 is a perspective view of a fifth exemplary embodiment of the present invention, illustrating curved upper side walls, two wide hinges and a convex roof to provide additional storage space.

FIG. 11 is an end view of the structure of **FIG. 10** in a fully collapsed condition.

FIG. 12 is a partial sectional view of a living hinge connecting two side sections.

FIG. 13 is a partial sectional view of a hinge connecting the upper and middle side sections and including a stop to prevent overtravel of the hinge.

SUMMARY OF THE INVENTION

25

In exemplary embodiment the present invention relates to a collapsible/foldable structure comprising a roof and a base defining a top and bottom of said structure and a lower side section on the base. A pair of sidewalls may be provided comprising at least two sections, each which may be pivotally attached to the roof to facilitate inward collapse of the sidewalls when said sidewalls are pivoted toward the base. The sidewalls may comprise upper and middle sections wherein the upper and middle sections may be pivotally attached to one another and wherein the roof may collapse downwardly towards the base. The sidewalls may

30

include an outer and an inner surface thereof, the middle wall section being pivotally attached to the lower side section to permit folding of the middle sidewall inwardly toward the base. The upper wall section may be pivotally attached to the middle wall section to permit the middle wall section inner surface to collapse into an overlying position with the inner surface
5 of the upper wall section. The roof may be pivotally connected to the two upper sidewall sections to permit the roof to be collapsed towards the base.

In a second exemplary embodiment, a relatively wide hinge panel may pivotally attach the top roof to the upper side walls, adding height to the structure without increasing the footprint (floor area) of the structure. The relatively wide hinge panel may include two
10 hinges in a spaced apart relationship and may be of a flexible material. The structure may also include a handle for carrying the collapsed compact structure or for carrying the structure in an expanded condition containing a pet.

In a third exemplary embodiment, the structure may include curved rather than flat side walls and a curved roof. In addition, the structure may include an access door in the top
15 roof for easily accessing the pet carried inside.

In a fourth exemplary embodiment, the structure may include a relatively wide hinge panel between the upper side wall and the middle sidewall alone or in combination with a relatively wide hinge panel between the top roof and the upper side wall to provide even more height and storage space without sacrificing the footprint of the structure.

20 In a fifth exemplary embodiment, the structure may include a curved top roof and/or side walls in combination with relatively wide hinge panels attaching the upper side walls to the top roof and middle side walls.

In a sixth exemplary embodiment, the structure may include flexible lower sidewalls which are an extension of the base and are capable of bending such that the inside surface
25 may overlie the inside surface of the adjacent upper panel when the structure is in a collapsed condition.

The foldable/collapsible structure of the present invention may find uses, including but not limited to, a pet carrier, a pet shelter, a collapsible storage container or temperature conditioning device for storing, for instance, perishable and non-perishable goods.

30

DETAILED DESCRIPTION OF THE INVENTION

Turning next to a more detailed description of the various preferred embodiments of the present invention, as illustrated in **FIG. 1**, the collapsible/foldable structure of the present invention is shown generally at **10** in an expanded or use condition with the front panel removed, and comprising a pair of sidewalls **12**. Sidewalls **12** may contain at least two panels, for example an upper **16**, middle **18** and lower section **20**. Lower section **20** as illustrated may be vertically disposed on said base or bottom platform **28**. This may be understood as any lower section **20** that has a vertical component of height relative to said base or bottom platform. For example, the vertical component may be angled with respect to the base or bottom platform. The lower section **20** may also be permanently affixed to the base, separately formed and attached to the base, or even hinged to the base. As shown, lower section **20** may be hinged to middle section **18**.

As can be seen, the sidewalls may be pivotally connected, which may be accomplished by hinges **22, 24, 26**. The hinges may be disposed on the outer surfaces **16a, 18a** of the upper and middle sections **16, 18** such that when said sidewalls are collapsed the structure may convert to a compact shape for carrying or storage (see **FIG. 2**).

The upper **16** and middle **18** sections may specifically collapse inwardly and towards the base or bottom platform **28**. That is, the upper **16** and middle **18** sections of the side walls **12** may have outer surfaces **16a, 18a**, respectively, which form an angle therebetween of greater than 180 degrees when the structure is in an expanded condition as shown in **FIG. 1**. In addition, upper sidewall **16** may be pivotally attached to roof section **30** by hinge **22**. Front panel **29** has been removed for clarity in **FIG. 1**, while rear panel **34** cannot be seen. Both of these panels may fold down against the base **28** and allow the sidewalls **12** to collapse thereupon or the front and rear panels may be removed before the side walls are collapsed.

The hinges **22, 24, 26** are shown may be “piano” hinges comprising leaf sections attached to the outer surface of the side wall sections and connected by a set of knuckles engaging a pin. These hinges may be formed of metal or plastic. However, it is contemplated that any sort of pivoting mechanism that will allow the upper and middle sections to move such that the angle formed between their respective outer surfaces may increase from about 180 degrees to about 360 degrees may be used. For instance, the hinges may be friction

hinges which may independently maintain the structure in an expanded condition until sufficient force is applied to collapse the structure.

To prevent the upper section **16** and middle section **18** from collapsing inward such that the angle between their respective outer surfaces **16a**, **18a** may form an acute angle, a stop **36** (see **FIG. 13**) may be included on the outer surface of middle section **18** in the area of hinge **24**. This stop **36** may be of a type, for instance, that is attached to the lower leaf of hinge **24** and which protrudes upwards from one or more of the knuckles of the lower leaf such that it forms an interference with the upper leaf of hinge **24** and substantially prevents buckling of hinge **24** inward relative to sections **16** and **18**. One or more of these stops may be employed per side **12** as shown in **FIGS. 1** and **2**.

FIG. 13 illustrates a partial sectional view of an exemplary stop **36** which may prevent overtravel of hinge **24** between upper section **16** and middle section **18**. In other words, to prevent hinge **24** from moving inward and thus allowing the outer surfaces **16a**, **18a** of the upper and middle sections, respectively, to form an acute angle therebetween, stop **36** extends into the path of the upper leaf of hinge **24** and only allows the outer wall surfaces to form an angle greater than 180° . One example of a stop **36** is shown in the exploded view of **FIG. 13**. Other examples of stops are known in the art.

In addition, it is contemplated that at least some of the plurality of hinges connecting the sidewall sections may be “living hinges”, that is, a thin flexible molded web of material which connects two rigid bodies together and has excellent fatigue resistance. In that regard, living hinges generally comprise a polyolefin, preferably polypropylene, and may be molded as an integral part of one or more of the sidewalls. In the present invention, the living hinge may also comprise a relatively thinned section which connects the inner surfaces of the upper, middle and/or lower sidewalls to allow hinging.

FIG. 12 is a partial sectional view of a living hinge **42** connecting upper section **16** to middle section **18**, the hinge **42** formed integrally with the sections **16**, **18** and extending from the inner surfaces **16b**, **18b** of those sections. It is further contemplated that a living hinge may be formed separately and mechanically attached to the side sections, much as the hinges **22**, **24**, **26** and **32** are shown. Note that the gap **44** between the side sections **16** and **18** which overlies the living hinge **42**, may function as a stop to prevent the sides **16**, **18** from buckling inward at the hinge and allowing the respective outer surfaces **16a**, **18a** to form an acute angle to one another.

In addition, while the embodiments show that the hinges extend in one piece for the full length of the structure, it is contemplated that shorter sections of hinges may be spaced apart (discontinuous) along the length of the structure to provide the necessary pivoting action of the side sections. In all of the following embodiments, it should be noted that the sidewall sections **16**, **18** and **20** may hinge on either the inner surfaces **16b**, **18b** or the outer surfaces **16a**, **18a** of the sidewalls depending upon whether the hinge is moving outwardly or inwardly during the collapsing motion. That is, placing the hinge on the inner or outer sidewall surface may become necessary because of the thickness required for the wall construction and the amount of rotation of the side wall sections during collapse of the structure.

Attention is next directed to **FIG. 2**, which illustrates the collapsible/foldable structure of the present invention in a collapsed state. As illustrated therein, the upper **16** and middle **18** sidewall sections are collapsed and disposed inward and into the structure **10**. **FIG. 2** is a front view of the collapsed structure illustrating how the roof **30** is collapsed downwardly towards the base **28**. Due to the hinged connections of the sidewall sections, upper section **16** pivots under middle section **18** such that the angle formed by the outer surfaces **16a**, **18a** increases to nearly 360 degrees, and never forms an acute angle. This motion is generally indicated by arrows **A** in **FIG. 2**.

In addition, inner surfaces **16b**, **18b** of the upper and middle sidewall sections, respectively, now generally overlie one another in adjacent fashion. This action thus provides for relatively easy collapse or folding of the structure from an expanded condition (**FIG. 1**) wherein the roof **30** is held up by the front and rear panels **29**, **34** (not shown) to the compact condition shown in **FIG. 2**. Accordingly the roof **30** and/or side walls **12** may releasably engage the front **29** and rear **34** panels when they are in an upright and the carrier is in a non-collapsed configuration. This then may provide a measure of structural integrity to the collapsible/foldable structure of the present invention. The hinges employed may be friction hinges which may independently maintain the structure in an expanded condition until sufficient force is applied to collapse the structure. Note also that stops **36** are shown protruding from hinge **24** which may prevent the upper and middle outer surfaces **16a**, **18a**, respectively, from forming an acute angle therebetween.

FIG. 3 illustrates in perspective view a second exemplary embodiment of the present invention, in a partially collapsed condition. Here, the roof **30** has been outfitted with a

folding handle **40** for ease of carrying the structure in a collapsed or expanded condition. **FIG. 3** further illustrates the front **29** and rear **34** panels already folded into the base, overlying one another and allowing the sidewalls **12** to collapse. While preferred embodiments of the invention provide that the front and rear walls are pivotally attached to the lower sidewall section **20** so that they can be folded inwardly and beneath the side walls and roof, they may also be physically removed from the front and rear openings. When in the expanded condition, the front and rear walls may act to further support the sides and roof, and when the front and rear walls are completely removed from the structure they can be either placed on top of the structure, inside or underneath and then optionally be bound up with suitable fastening so that the complete structure can be shipped as one package. The end panels as well as the side walls may, as shown, comprise a mesh or perforated structure to allow for airflow for pets being transported.

A further feature of this exemplary embodiment is the use of a hinge panel **32** that may be located, for instance, between the upper side wall section **16** and the roof **30** as illustrated in **FIG. 3**. This hinge panel **32** may be relatively wider than a normal hinge (essentially two hinges back to back, yet spaced apart) but relatively narrower than the upper section **16**, and thus provide additional height to the structure which may then provide additional space within the structure. This additional space also will not come at the expense of the footprint (base area) as the hinge panel **32** can be allowed to collapse along the side of the roof **30** into the base **28** (see **FIG.4**).

The hinge panel **32** may comprise nearly any material, including, but not limited to, metal, plastic, cloth and leather. An additional feature may be provided by a hinge panel that is flexible, e.g. of cloth, leather, or plastic, such as thermoplastic elastomer or thermoplastic olefin, such that upon collapse, the hinge panel may bend or flex to conform to an available space. Thus, the height of the structure may be increased to allow storage of larger items, such as certain pets, yet take up relatively minimal space when collapsed.

FIG. 4 is a perspective view of the structure of **FIG.3** in a fully collapsed condition. Once again, the upper and middle sections, **16, 18** of the sidewalls **12** have rotated inwardly from a position where the outer surfaces **16a, 18a** of those walls form an angle of greater than 180 degrees to a position where the angle now may approximate 360 degrees. Of note are the hinge panels **32** which now in a folded condition may lie outboard of the roof **30**. It may therefore be appreciated that if the hinge panels were flexible, they could fold upon

themselves somewhat to take up even less space. The resultant collapsed structure may therefore provide a substantially flat, readily transportable device which is easily stored.

FIG. 5 is a perspective view of another exemplary embodiment of the present invention, illustrating in perspective view, a structure **10** in an expanded condition having a curved roof **30'**, curved sidewalls **16'** and curved hinge panels **32'**. Also shown in this view are front panel **29** and rear panel **34** in an erect position, forming a pet carrier. An additional feature of this exemplary embodiment is an access panel **14** which may be pivotally connected to the roof **30** and allow access to the contents of the structure through the roof. Although not shown, it is contemplated that the front panel **29** and/or rear panel **34** may also include access doors. By using curved panels for the roof **30'**, upper section **16'** and hinge panel **32'**, additional storage space may be created, again without increasing the relative footprint or floor area of the structure **10**.

FIG. 6 is a perspective view of the structure of **FIG. 5** in a partially collapsed condition illustrating the angular movement of upper section **16'** in relation to middle section **18'** and hinge panel **32'** in relation to upper section **16'**. In addition, the front **29** and rear **34** panels have been folded onto the base **28**.

FIG. 7 is an end view of the structure of **FIG. 5** in a fully collapsed condition.

FIG. 8 is a perspective view of another exemplary embodiment of the present invention, illustrating two relatively wide hinge panels **32** per side, providing additional height and storage space. One of the relatively wide hinge panels **32** is illustrated as connecting the roof **30** and upper section **16** and the other hinge panel connects upper section **16** and middle section **18**, respectively. **FIG 8A** illustrates that the hinge panel **32** may also connect the middle side section **18** to the base **28**. **FIG. 9** illustrates the structure of **FIG. 8** in a collapsed condition.

FIG. 9A illustrates yet another exemplary embodiment of the present invention where the middle side section may be replaced by a relatively flexible lower section **20'** which may be an extension of the base **28**. The flexible lower side section **20'** may then extend integrally from the base **28** and be pivotally connected to the upper side section **16**. It also may be separately attached to the base. The structure **10** is shown in a collapsed condition in **FIG. 9A** illustrating that the lower side section **20'** is capable of bending such that upon collapse of the roof **30** towards the base **28**, the lower side section may overlie the upper side section **16**. Or, stated another way, the upper and lower side sections include inner and outer

surfaces wherein the upper side section is pivotably attached to the lower side section and permits the lower side section inner surface to collapse into an overlying position with the inner surface of said upper side section. The lower side section may comprise a flexible plastic material, such as a polyolefin (i.e. polyethylene, polypropylene, etc.) or a thermoplastic elastomer (e.g., a polyurethane or polyester elastomer), plasticized PVC, a thermoset elastomer, a diene rubber (e.g., cis-polyisoprene), or mixtures thereof.

FIG. 10 is a perspective view of another exemplary embodiment of the present invention, illustrating curved upper side walls **16'**, two relatively wide hinge panels **32'** and a convex roof **30'** to provide additional storage space. **FIG. 11** is an end view of the structure of **FIG. 10** in a fully collapsed condition.

The structure of the present invention may comprise any of a variety of materials, including but not limited to, metal, plastic, paperboard, fabric or cloth and wood. In the case of storage for temperature conditioning of items (use as a cooler, etc.), the structure may be formed from thermally insulative materials such as polyurethane, polyolefin or polystyrene foam, optionally containing a film covering the outer surfaces that prevents weather damage to the foam layer, further providing a better or improved cosmetic appearance. In addition, other foam materials are suitable, including but not limited polyurea/urethane, polyurea, and trimer foams, etc. Accordingly, in broad embodiment, any synthetic foam material that provides thermal insulation and temperature control of the interior of the foldable/collapsible structure will be suitable for construction of the present invention. It is further contemplated that in the case of storage coolers, the front and rear end panels may be formed integrally with the base and lower side sections and the end panels connected by living hinges to provide a seal such that liquid contained within the cooler would not leak to the outside.

For use as a pet shelter or carrier, exposed surfaces of the structure may be coated with or constructed of plastic materials, including, but not limited to polyolefins, vinyl polymers, styrene based polymers, acrylonitrile-butadiene-styrene resins, vinyl polymer resins, engineering thermoplastics, and thermoset type resins or coatings which may provide the necessary barrier to chewing destruction of an animal.

The description and drawings illustratively set forth the presently preferred invention embodiment. In addition, it should be understood that all of the aforementioned features of the various embodiments are interchangeable. We intend the description and drawings to describe this embodiment and not to limit the scope of the invention. Obviously, it is

possible to modify these embodiments while remaining within the scope of the following claims. Therefore, within the scope of the claims one may practice the invention otherwise than as the description and drawings specifically show and describe.

What is claimed is:

1. A collapsible/foldable structure comprising:

a roof and a base defining a top and bottom of said structure;

5 a lower side section on said base;

a pair of sidewalls comprising at least two sections, each pivotally attached to said roof to facilitate inward collapse of said sidewalls when said sidewalls are pivoted toward said base, said sidewalls comprising upper and middle sections, wherein said upper and middle sections are pivotally attached to one another and wherein said roof can collapse downwardly toward
10 said base;

said sidewalls having an outer and an inner surface thereof, the middle wall section being pivotally attached to the lower side section to permit folding of said middle sidewall inwardly toward said base;

said upper wall section being pivotally attached to said middle wall section to permit said
15 middle wall section inner surface to collapse into an overlying position with the inner surface of said upper wall section and said roof being pivotally connected to said two upper sidewall sections to permit said roof to be collapsed towards said base.

2. The structure of claim 1 including front and rear collapsible panels each
20 movably positioned relative to said lower side section and which are configured to collapse inwardly into said collapsible/foldable structure so that said front and rear collapsible panels may overlie one another and one of said front and rear collapsible panels may overlie said base;

25 3. The structure of claim 1 wherein the outer surface of said upper side wall and the outer surface of the adjacent middle side wall form an angle that is greater than 180 degrees when the structure is in an expanded or collapsed condition.

4. The structure of claim 1 wherein said pivotal attachments comprise hinges.

30

5. The structure of claim 4 wherein one or more of said hinges comprise a living hinge.

6. The structure of claim 5 wherein said living hinge integrally extends between the inner surfaces of said upper and said middle wall sections.

7. The structure of claim 1 wherein at least one of said pivotal attachments
5 comprise hinges panels which include a pair of spaced-apart hinges.

8. The structure of claim 7 wherein said hinges panels comprise a flexible material capable of bending.

10 9. The structure of claim 8 wherein said hinges panels comprise one of leather, cloth, thermoplastic olefin or thermoplastic elastomer.

10. The structure of claim 1 wherein one or more of said roof, said upper sidewall section and said middle sidewall section are curved.

15

11. The structure of claim 7 wherein said hinge panels are curved.

12. The structure of claim 1 wherein said roof further includes an access panel for accessing items stores within said structure.

20

13. The structure of claim 1 wherein said front and rear walls are detachable from said base.

14. The structure of claim 4 wherein said hinges extend discontinuously along
25 said side sections.

15. A foldable/collapsible structure comprising:
a horizontally disposed bottom panel and a lower side section;
a top panel;
30 a pair of side walls defined by at least an upper and middle side sections including said lower side section;

wherein said upper side section is hingedly connected to said top panel and to said middle side section, said middle section is hingedly connected to said lower side section, wherein said side panels can be pivoted inwardly towards said bottom panel;

wherein said upper and said middle side sections include inner and outer surfaces and wherein the upper wall section being hingedly attached to said middle wall section permits said middle wall section inner surface to collapse into an overlying position with the inner surface of said upper wall section.

16. The structure of claim 15 including first and second end panels hingedly attached to said lower side section.

17. The structure of claim 15 wherein the outer surface of said upper side section and the outer surface of the adjacent middle side section form an angle that is greater than 180 degrees when the structure is in an expanded or collapsed condition.

18. A pet carrier for transporting or temporarily storing pets comprising:
a top roof and a bottom platform defining a top and a bottom of said carrier;
a pair of sidewalls each pivotally attached to said roof to facilitate inward collapse of said sidewalls when said sidewalls are pivoted toward said bottom platform,
said sidewalls further containing at least an upper, middle and lower section, wherein said upper and middle sections and said middle and lower sections are pivotally attached to one another so that said upper and middle sections can be pivoted inwardly towards said bottom platform,

wherein said upper and said middle sections include inner and outer surfaces and wherein the upper section being pivotally attached to said middle section permits said middle section inner surface to collapse into an overlying position with the inner surface of said upper section.

19. The structure of claim 18 wherein the outer surface of said upper side section and the outer surface of the adjacent middle side section form an angle that is greater than 180 degrees when the structure is in an expanded or collapsed condition.

20. A foldable/collapsible structure comprising:

a top panel and bottom panel;

a pair of side panels defined by at least two sections including an upper and lower side section;

5 wherein said upper side section is pivotally connected to said top panel and to said lower side section,

wherein said upper and lower side sections include inner and outer surfaces and wherein the upper side section being pivotably attached to said lower side section permits said lower side section inner surface to collapse into an overlying position with the inner surface of said
10 upper side section.

21. The structure of claim **20** wherein said lower side section comprises a material capable of bending to form said overlying condition.

1/14




FIG. 1

2/14




FIG. 2

3/14




FIG. 3

4/14




FIG. 4



5/14




FIG. 5

6/14




FIG. 6

7/14




FIG. 7

8/14




FIG. 8

9/14




FIG. 8A

10/14




FIG. 9

11/14




FIG. 9A




FIG. 10

13/14




FIG. 11

14/14

FIG. 12




FIG. 13

