




(22) Date de dépôt/Filing Date: 2004/11/30
 (41) Mise à la disp. pub./Open to Public Insp.: 2005/06/04
 (45) Date de délivrance/Issue Date: 2011/01/11
 (30) Priorité/Priority: 2003/12/04 (EP03 02 7855)

(51) Cl.Int./Int.Cl. *H04W 4/12* (2009.01),
H04M 3/533 (2006.01), *H04M 3/537* (2006.01)
 (72) Inventeurs/Inventors:
CHAUDRY, SHAHID R., CA;
ISLAM, M. KHALEDUL, CA
 (73) Propriétaire/Owner:
RESEARCH IN MOTION LIMITED, CA
 (74) Agent: MOFFAT & CO.

(54) Titre : METHODE ET SYSTEME D'ELIMINATION DES AVIS MULTIPLES POUR UN MEME MESSAGE DE BOITE VOCALE
 (54) Title: METHOD AND SYSTEM FOR ELIMINATING MULTIPLE NOTIFICATIONS FOR THE SAME VOICEMAIL MESSAGE



(57) Abrégé/Abstract:

A method and system for eliminating voicemail notifications on a wireless device for a voicemail message that a user has previously been notified of, comprising the steps of: storing information on the wireless device about the voicemail message; comparing incoming information of a new voicemail notification received by the wireless device against the information stored in the storing step; and notifying the user of the voicemail message only if the incoming information differs from the information stored in the storing step.

ABSTRACT

A method and system for eliminating voicemail notifications on a wireless device for a voicemail message that a user has previously been notified of, comprising the steps of: storing information on the wireless device about the voicemail message; comparing incoming information of a new voicemail notification received by the wireless device against the information stored in the storing step; and notifying the user of the voicemail message only if the incoming information differs from the information stored in the storing step.

METHOD AND SYSTEM FOR ELIMINATING MULTIPLE NOTIFICATIONS FOR THE SAME VOICEMAIL MESSAGE

FIELD OF THE INVENTION

The present invention relates to voicemail notifications for wireless devices and, in particular, to the elimination of multiple network-initiated notifications for the same voicemail message.

BACKGROUND TO THE INVENTION

In a wireless network, a user is notified that a voicemail message is waiting when the user receives a voicemail. This notification involves the current mobile switch that the wireless device is connected to sending a message to the wireless device indicating how many voicemail messages are waiting to be checked.

Currently, when a wireless device receives a Message Waiting or Voice Mail Notification message, it immediately sends an acknowledgement message to the network as an indication that the message was received by the wireless device and then notifies the user of the receipt of a voice mail message. It is up to the user to make a call to the Voice Mail System and listen to the pending voice mail.

In addition, it is the responsibility of the network to send a message to explicitly indicate the number of remaining pending messages, if any, if the user has listened to some or all the pending voice mails.

A problem frequently occurs with current voicemail notification when a mobile user moves from one network boundary to another (e.g. one mobile switch, system, network or registration zone to a second mobile switch system, network or registration zone). In such boundary crossings, the wireless device is usually required by the network to register with it and a notification message is sent that a voicemail message is waiting. In such instances of mobility where the wireless device is required to register with different networks, the wireless device can receive the same voicemail message repeatedly. In a data device, the same message appears multiple times in its incoming message folder. The problem gets worse at network boundaries where the user may go back and forth between two networks and each transition is accompanied by the same voicemail notification message.

Voicemail notifications can be either sent as a signalling message or as a short message service over the common paging channel or dedicated traffic channel, but

regardless of the method used to convey the voicemail notification to the wireless device, repeated notifications of the same voicemail message are annoying to the user and can lead to a negative impression by the user of the wireless service.

Prior art notification systems include U.S. Patent No. 6,032,039 to Kaplan. Kaplan teaches a voicemail notification and retrieval system for devices with no alphanumeric display. This system however suffers from the same problems as above, and does not teach the elimination of multiple notifications for the same message.

US Patent No. 6,405,035 to Singh teaches the deletion of redundant messages when a user accesses the message on one device. Singh is directed to messages that are sent to a plurality of devices and the deletion of the messages from the devices once the message has been read. It is not directed to the elimination of multiple voicemail notifications on the same device.

Other references, including US Patent No. 5,384,565 to Cannon, US Patent No. 5,347,269 to Vanden Heuvel et al, and US Patent Application No. 2002/0006783 to Akao et al, all teach methods and systems for eliminating duplicate data messages received by a mobile device such as a pager. These references teach the comparison of the data messages to look for duplicates, and various techniques for doing this. However, they are not directed to voicemail, and the elimination of multiple notifications of the same voicemail message.

SUMMARY OF THE INVENTION

The present invention seeks to overcome the deficiencies in the prior art by providing a method to eliminate multiple notifications for the same voicemail message. A voicemail notification from a mobile switch to a wireless device includes information about the number of voicemail messages that are waiting to be heard by the user. In one embodiment of the present invention, the wireless device stores the number of pending voicemail messages as directed by the most recently received message from the network. Whenever it receives a new voicemail message, it immediately sends an acknowledgement back to the network, which simply indicates that the message was successfully received by the device. The device then compares the number of voicemail messages waiting as received in the message to that stored on the wireless device. If the device detects the same number of voicemail messages as identified by the current message, the device will realize that this voicemail has

previously been brought to the user's attention and will therefore avoid notifying the user a second time.

In an alternative embodiment of the present invention, the network itself registers that the wireless device has acknowledged the receipt of voicemail notification message corresponding to particular unheard voicemail messages and will thus refrain from sending further voicemail notification messages for same unheard voicemail messages. Voicemail notifications are stored at a voice mail system, which communicates with the mobile switch the wireless device is currently connected to. When a wireless device moves into a network, the mobile switch receives a message from voice mail system that a voicemail message is waiting and sends this to the wireless device. In this embodiment, when the wireless device acknowledges the voicemail message, the mobile switch sends this acknowledgement to the voice mail system. The voice mail system then registers that the present voicemail message has been acknowledged and will not require any mobile switch subsequently connected to by the wireless device to notify the user of this voicemail message. In this way, a single acknowledgement prevents further voicemail notifications for the same message. New messages will however still be forwarded to wireless device and the user notified of the new message.

The present invention therefore provides a method for eliminating voicemail notifications on a wireless device for a voicemail message that a user has previously been notified of, comprising the steps of: storing information on said wireless device about said voicemail message; comparing incoming information of a new voicemail notification received by said wireless device against said information stored in said storing step; and notifying the user of said voicemail message only if said incoming information differs from said information stored in said storing step.

The present invention further provides a method for eliminating repeat voicemail notifications on a wireless device for a voicemail message that said wireless device has previously acknowledged, comprising the steps of: adding a flag on said voicemail message at a voicemail system once said wireless device has acknowledged said voicemail message; and notifying the wireless device of said voicemail message only if said voicemail message does not have said flag.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is best understood with reference to the drawings, in which: FIGURE 1 is a process diagram of the method of one embodiment of the present invention; and

FIGURE 2 is a process diagram of the method of an alternative embodiment of the present invention.

DETAILED DESCRIPTION OF THE DRAWINGS

Reference is now made to Figure 1. A mobile switch 10 is connected to a wireless device 12 through a radio link. Wireless device 12 registers with mobile switch 10 and mobile switch 10 knows that it is servicing wireless device 12.

Mobile switch 10 receives a message 20 that it should notify the wireless device 12 that the wireless device has a specific number of voicemail messages waiting. The notification message 20 includes the number of voicemail messages that are waiting.

Mobile switch 10, through the wireless link 14, sends the notification message to wireless device 12 and in step 22 wireless device 12 receives the notification message.

In step 23, wireless device 12 automatically acknowledges that it has received the notification in step 22. This is to ensure that mobile switch 10 does not repeatedly send notification message 20, which will occur if mobile switch 10 does not receive an acknowledgement.

After sending the acknowledgement, wireless device 12 checks the received voicemail notification for the number of voicemail messages that are waiting. In step 24, the wireless device compares the number of voicemail messages waiting as indicated in the voicemail notification with the number of voicemail messages that the wireless device knows about. If the number of voicemail messages indicated in the voicemail notification is different from the number of voicemail messages the wireless device knows about, the wireless device moves to step 26 in which the user is notified that he or she has a voicemail message waiting.

A notification can be in the form of an audio signal, such as a tone being played, or a visual signal such as a pop-up window opening or a message indicator icon being displayed. Depending on the device, the message indicator icon could include a display with the number of messages waiting. Further, in some devices with

message centres on the device, a visual notification can be a message in the message centre indicating the type of message and the time when the notification was sent. It is also possible to use both audio and visual notifications at the same time, and one skilled in the art will appreciate that other audio and visual notifications are possible.

The wireless device further, in step 28, updates the number of voicemail messages that it knows about and in step 30 the process ends.

If, in step 24, the number of messages indicated in the notification message is the same as the number of voicemail messages known to the wireless device, the wireless device skips steps 26 and 28 by going through step 32. In step 32 the wireless device 12 knows that it has previously notified a user of the voicemail message and thus does not notify the user again.

The process moves from step 32 to step 30 and ends.

In operation, when a new voicemail message is received, mobile switch 10 is told to notify the device of the new voicemail. A voicemail notification is received at step 22 and the device compares the incoming information in the voicemail notification, which includes the total number of voicemail messages waiting, with the number of voicemail messages the device knows about. The result of this comparison is that the number of voicemail messages waiting in the voicemail notification is different than the number of voicemail messages the device knows about. The device thus notifies the user and updates the number of voicemail messages it knows about.

Conversely, if the device moves from one network to another and a new mobile switch 10 is told to notify the device that there are voicemail messages waiting, where these voicemail messages have previously been acknowledged with the old mobile switch, the wireless device 12 will receive the voicemail notification in step 22 and will realize in step 24 that the voicemail notification has the same number of voicemail messages waiting as the wireless device currently knows about. In this case, the wireless device will realize that it has previously notified the user of these voicemail messages and will not notify the user again.

As is known to those skilled in the art, when a user eventually listens to and/or deletes a voicemail message, the network will reduce the number of pending

voicemail messages and notify the device of the reduced number of pending voicemail messages via voicemail notification message.

The above examples illustrate one embodiment of the invention. One skilled in the art will realize that the wireless device may have other means of identifying whether it has previously notified the user of the voicemail message.

Reference is now made to Figure 2. A voicemail system 40 stores information about voicemail messages waiting for various wireless devices. As one skilled in the art will realize, voicemail system 40 is located within the wireless network but generally remotely from a mobile switch 10.

In step 42 voicemail system 40 checks whether any voicemail messages are waiting for a particular wireless device 12. Step 42 may be initiated based on notification that the wireless device 12 has entered a new mobile switch 10 or based on other factors that are known to those skilled in the art. If no voicemail message is waiting in step 42 the process ends. Conversely, if any voicemail messages are waiting, the method next moves to step 44. In step 44 the voicemail system 40 checks whether all the voicemail messages have previously been delivered. Delivery as used herein indicates that a voicemail message notification was sent to wireless device 12 and was acknowledged by the wireless device.

Preferably a flag exists for voicemail messages that have been previous delivered and step 44 knows of said previous deliveries based on said flag. If a previous delivery has been sent voicemail system 40 next moves to step 46, which stops the process.

Conversely, if any voicemail messages for wireless device 12 have not been previously delivered, voicemail system 40 moves to step 48 in which a voicemail notification is sent to mobile switch 10.

Mobile switch 10 receives the voicemail notification in step 50 and forwards it to the wireless device in step 52. As in the method of the present invention described above, wireless device 12 receives the voicemail notification in step 22, acknowledges it in step 23, and moves to step 26 to notify the user.

As one skilled in the art will appreciate steps 24 and 28 are no longer required in this alternative method since the voicemail system controls the notifications being sent.

When wireless device 12 acknowledges the voicemail notification in step 23, this acknowledgement is sent to mobile switch 10, and in step 60 the acknowledgement is forwarded to voicemail system 40.

Voicemail system 40 received the acknowledgement from mobile switch 10 and in step 62 marks the voicemail message or messages as being delivered. Voicemail system 40 will thereafter not send voicemail notifications to wireless device 12 unless a new voicemail message is received.

In operation, the alternative method of Figure 2 will therefore only send a voicemail notification that the voicemail message is waiting a single time. After this first notification has been sent and an acknowledgment received, the voicemail message is marked to indicate that it has been delivered and thereafter its notification will not be re-sent.

The present invention therefore overcomes the disadvantages of the prior art by providing a method on a wireless device to check whether a voicemail message has previously been received. Alternatively, a voicemail system 40 stores information whether the voicemail message has previously been delivered. In both cases the user is not notified repeatedly of the same message, thereby solving a problem with current wireless devices.

Although the present invention has been described with regard to the preferred embodiments thereof, one skilled in the art will easily realize that other variations are possible, and that the invention is only intended to be limited in scope by the following claims.

**THE EMBODIMENTS OF THE INVENTION IN WHICH AN
EXCLUSIVE PROPERTY OR PRIVILEGE IS CLAIMED ARE
DEFINIED AS FOLLOWS:**

1. A method for eliminating repeat voicemail notifications on a wireless device
5 initially connected to a first wireless network and subsequently connected to
a second wireless network, the repeat voicemail notifications being for a
voicemail message that said wireless device has previously acknowledged
after receiving notification of the voicemail message when connected to the
first wireless network, comprising the steps of:
10 storing a flag on a voicemail system once said wireless device has acknowl-
edged notification of the voicemail message when the wireless device is
connected to the first network, the flag indicating acknowledgement of noti-
fication;
checking the flag on the voicemail system to see whether to send a notifica-
15 tion, upon said wireless device has been connected to the second wireless
network; and
notifying the wireless device if the checking step indicates said notification
should be sent, otherwise preventing notifying the wireless device.
- 20 2. The method of claim 1, wherein said flag is added to said voicemail mes-
sage at the voicemail system once said wireless device has acknowledged
said voicemail message.
3. The method of claim 2, wherein the notifying step notifies the wireless de-
25 vice of said voicemail message only if said voicemail message does not
have said flag.
4. The method of any of claims 1 to 3, wherein said voicemail system commu-
nicates with said wireless device through a mobile switch.
- 30 5. The method of claim 4, wherein the mobile switch receives an acknowl-
edgement from said wireless device when said wireless device receives said

voicemail notification, said mobile switch forwarding said acknowledgement to said voicemail system.

- 5 6. The method of any of claims 1 to 5, wherein said notifying step includes sending a number representing voicemail messages waiting.
7. The method of claim 5, wherein said notification step occurs upon connection by said wireless device to the mobile switch.
- 10 8. The method of claim 1, wherein the method further comprises receiving an acknowledgement from the wireless device at the voicemail system prior to the checking step.
- 15 9. The method of claim 8, wherein the receiving step includes a number representing the number of voicemails waiting that the wireless device has acknowledged.
- 20 10. The method of claim 9, wherein the checking step further compares whether the number of voicemails waiting is equivalent to the number of voicemails previously acknowledged, the notifying step only notifying the wireless device if the comparison step finds the number of voicemails waiting is different from the number of voicemails previously acknowledged.
- 25 11. A wireless device system for eliminating repeat voicemail notifications on a wireless device initially connected to a first wireless network and subsequently connected to a second wireless network, the repeat voicemail notifications being for a voicemail message that said wireless device has previously acknowledged after receiving notification of the voicemail message when connected to the first wireless network, the system comprising:
 - 30 a voicemail system having a storage means for storing the voicemail message, said storage means including memory for storing a flag at the voicemail system once said wireless device has acknowledged notification of the

voicemail message when the wireless device is connected to the first network, the flag indicating acknowledgement of notification;

a checking means adapted for checking the flag to see whether a voicemail notification should be sent, upon said wireless device has been connected to the second wireless network; and

a notification means adapted to notify the wireless device of said voicemail message only if the checking means finds said voicemail notification should be sent and otherwise to prevent notifying the wireless device.

- 5
- 10 12. The system of claim 11, wherein the flag is stored for each voicemail message.
13. The system of claim 12, wherein the checking means is adapted to check whether the voicemail message has said flag.
- 15
14. The system of claim 11, further comprising a mobile switch on a communications path between said voicemail system and said wireless device.
- 20 15. The system of claim 14, wherein the mobile switch adapted to receive an acknowledgement from said wireless device when said wireless device receives said voicemail notification, said mobile switch forwarding said acknowledgement to said voicemail system.
- 25 16. The system of claim 15, wherein said notification means includes said voicemail system sending a number representing voicemail messages waiting to said wireless device.
- 30 17. The system of claim 16, wherein said notification means is adapted to notify said wireless device upon connection of said wireless device to said mobile switch.




Figure 1




Figure 2

