FIBER COUPLING EFFICIENCY OF DIODE LASERS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This Application claims rights under 35 USC §119(e) from U.S. Application Serial No. 61/886,696 filed 4 Oct 2013, the contents of which are incorporated herein by reference.

TECHNICAL FIELD

[0002] The present disclosure relates generally to diode lasers. Embodiments of the disclosure are related to systems and methods of constructing diode lasers to increase the fiber coupling efficiency.

BACKGROUND

[0003] High power laser diodes have become a staple pump source for both solid state and fiber optic lasers due to their high brightness, spectral versatility, environmental robustness and high efficiency. Typical high power fiber coupled diode lasers are focused into the large core of a glass-cladded multimode fiber.

[0004] **FIG. 1** is an illustration of a schematic diagram of a prior art laser system **100** utilized for coupling a diode laser **102** to a double clad fiber **118** through a multimode fiber **116**. The core multimode fiber **116** by which the diode laser **102**, used to pump the double clad fiber laser, is coupled into is generally smaller than the glass cladding of the double clad fiber **118,** it is pumping. This results in an aperture mis-match and a loss in efficiency because the double clad fiber **118** is capable of receiving lower brightness light than the multimode fiber **116** for comparable numerical apertures.

[0005] Thus, connecting the pump diode 102 to multimode fiber **116** a portion of the available laser power from the pump diode lost. Invariably power is launched into the cladding of multimode fiber **116**. When multimode fiber **116** is built into a connector a cladding mode stripper is required to remove light coupled into the cladding of multimode fiber **116**. Double clad fiber **118** typically provides a larger aperture to couple light from pump diode **102** to the fiber laser oscillator comprised of **118, 118*, 108, 110, 110*** and associated splices **105** and **121**. The larger aperture provided by double clad fiber **118** increases pump diode coupling efficiency and removes the necessity for a cladding stripper at the pump-diode to fiber connector interface. Higher diode-coupling efficiencies and a simplified laser construction process are realized when coupling light into double-clad fiber **118** compared to using multimode fiber **116**.

[0006] A result of higher diode coupling efficiencies is the removal of the cladding stripper built into the connector built into multimode fiber **116**. For a laser system coupling pump diode **102** into double clad fiber **118** a cladding stripper is not needed at the diode to fiber interface as was the case when coupling into multimode fiber **116**. Constructing the connector with double clad fiber **118** adhesive or other bonding materials must not come into contact with the bare glass of **118** so as to not unintentionally create a cladding stripper.

[0007] The highly reflective fiber Bragg grating **118*** is fabricated from the same double clad fiber **118**. For pump diode **102** coupled into multimode fiber **116** splice **104** is required to transmit the light coupled into multimode fiber **116** to the fiber laser comprised of **118, 118* 108, 110, 110*** and associated splices **105** and **121.** Splice **104** becomes unnecessary when coupling pump diode **102** into double clad fiber **118**. The pump light is now coupled directly into the fiber laser comprised of **118, 118*, 108, 110, 110*** and associated splices **105** and **121** without the need for an intermediate multimode fiber **116**. The removing splice **104** from the laser increases efficiency as all splices present some finite amount of loss (decrease in efficiency).

[0008] A need, therefore, exists for an improved coupling method that overcomes the above drawbacks.

SUMMARY

[0009] The following summary is provided to facilitate an understanding of some of the innovative features unique to the disclosed embodiment and is not intended to be a full description. A full appreciation of the various aspects of the embodiments disclosed herein can be gained by taking into consideration the entire specification, claims, drawings, and abstract as a whole.

[0010] It is, therefore, one aim of the disclosed embodiments to provide for a diode laser comprising a diode pump source for generating a force to pump a laser and a double clad fiber directly coupled to the diode pump source instead of coupling to the multimode fiber. The pumped laser is transmitted directly through the double clad fiber thereby increasing the coupling efficiency of the diode pump source.

[0011] It is, therefore, one aim of the disclosed embodiments to provide for a diode laser in which at least one connector for connecting the double clad fiber and the diode pump source.

[0012] It is, therefore, one aim of the disclosed embodiments to provide for a diode laser comprising the connector having at least one adhesive in contact with an acrylate coating of the double clad fiber.

[0013] It is, therefore, one aim of the disclosed embodiments to provide for a diode laser in which the adhesive is not in contact with a glass cladding of the double clad fiber and thus the adhesive does not act as a cladding stripper.

[0014] It is, therefore, one aim of the disclosed embodiments to provide for a fiber-coupled diode laser in which the double clad fiber comprises no cladding stripper and hence the need for thermal management system for the cladding strippers is avoided.

[0015] It is, therefore, one aim of the disclosed embodiments to provide for a fiber-coupled diode laser in which the double clad fiber may be the same fiber as thehigh-reflector fiber Bragg grating.

[0016] It is, therefore, one aim of the disclosed embodiments to provide for a fiber laser oscillator that comprises a fiber-coupled diode laser. The diode laser has a diode pump source for generating a force to pump a laser and a double clad fiber directly coupled to the diode pump source instead of coupling to the multimode fiber. The pumped laser is transmitted directly through the double clad fiber thereby increasing the coupling efficiency of the diode pump source. At least one connector is utilized for connecting the double clad fiber and the diode pump source. The connector comprises at least one adhesive in contact with an acrylate coating of the double clad fiber and not in contact with a glass cladding of the double clad. The double clad fiber comprises no cladding stripper and hence the need for thermal management system for the cladding strippers can be avoided. The double clad fiber may be the same as the high-reflector fiber Bragg grating.

[0017] It is, therefore, one aim of the disclosed embodiments to provide for a laser system that comprises a diode laser. The diode laser has a diode pump source for generating a force to pump a laser and a double clad fiber directly coupled to the diode pump source instead of coupling to the multimode fiber. The pumped laser is transmitted directly through the double clad fiber thereby increasing the coupling efficiency of the diode pump source. At least one connector is utilized for connecting the double clad fiber and the diode pump source. The connector comprises at least one adhesive in contact with an acrylate coating of the double clad fiber and not in contact with a glass cladding of the double clad. The double clad fiber comprises no cladding stripper and hence the need for thermal management system for the cladding strippers can be avoided. The double clad fiber may be the same as the high-reflector fiber Bragg grating.

[0018] It is, therefore, one aim of the disclosed embodiments to provide for a method for constructing a double clad fiber connector. This method would include placing at least one adhesive in contact with an acrylate coating and avoiding at least one adhesive in contact with a glass cladding.

[0019] It is, therefore, yet another aim of the disclosed embodiments to provide for a method for constructing a double clad fiber connector comprising avoiding cladding strippers due to adhesive in contact with the glass cladding and avoiding thermal management system for the cladding strippers.

[0020] It is, therefore, one aim of the disclosed embodiments to provide for a method for constructing a double clad fiber comprising eliminating at least one fiber splice in the double clad fiber.

[0021] It is, therefore, one aim of the disclosed embodiments to provide for a method for eliminating a fiber splice when mating a fiber-coupled pump diode to a double-clad fiber laser.

[0022] It is, therefore, yet another aim of the disclosed embodiments to provide for a system and method for increasing the fiber coupling efficiency of diode lasers in which the environmental robustness of fiber coupled diode lasers is increased. Increasing the total usable aperture available for coupling of the diode laser mitigates damaging effects of beam degradation associated with high power operation and operation in strenuous environments, such as those on military platforms.

[0023] It is, therefore, yet another aim of the disclosed embodiments to provide for a system and method for increasing the fiber coupling efficiency of diode lasers which is more tolerant of beam blooming, diode smile, and beam wandering exhibited by diode lasers because there is a greater area available for fiber coupling.

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] The summary above, as well as the following detailed description of illustrative embodiments, is better understood when read in conjunction with the appended drawings. For the purpose of illustrating the present disclosure, exemplary constructions of the disclosure are shown in the drawings. However, the disclosure is not limited to specific methods and instrumentalities disclosed herein. Moreover, those in the art will understand that the drawings are not to scale. Wherever possible, like elements have been indicated by identical numbers.

[0025] **FIG. 1** is an illustration of a schematic diagram of a prior art laser system comprising a diode pump coupled to a double clad fiber through a multimode fiber;

[0026] **FIG. 2** is an illustration of a schematic diagram of a laser system comprising a diode pump directly coupled to a double clad fiber, in accordance with the disclosed embodiments;

[0027] **FIG. 3** is an illustration of a configuration of a double clad fiber utilized in **FIG. 2**, in accordance with the disclosed embodiments; and

[0028] **FIG. 4** is an illustration of a flowchart showing a method of coupling diode pump and the double clad fiber of depicted in **FIG. 3**, in accordance with the disclosed embodiments.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

[0029] The particular configurations discussed in the following description are non-limiting examples that can be varied and are cited merely to illustrate at least one embodiment and are not intended to limit the scope thereof.

[0030] A system and method for increasing the fiber coupling efficiency of diode lasers is disclosed. The diode-fiber interface connector has at least one adhesive placed in contact with an acrylate coating and not in contact with a glass cladding of the double clad fiber to avoid creating a cladding stripper.

[0031] **FIG. 2** is an illustration of a schematic diagram of a laser system **200** utilized for coupling a diode laser **202** directly to a double clad fiber **218** without connecting to a multimode fiber **116** as depicted in prior art system **100** of **FIG. 1**. The pumped laser is transmitted directly through the double clad fiber **218**, thereby increasing the coupling efficiency of the diode laser **202**. The diode laser **202** has at least one connector (not shown) for connecting the double clad fiber **218** and the diode laser **202**. The connector comprises at least one adhesive in contact with an acrylate coating of the double clad fiber **218** and not in contact with a glass cladding of the double clad fiber **218**. Adhesive in contact with an acrylate coating does not act as a cladding stripper and hence avoids the light loss. As there is no light loss hence there is no heat generation. Thus, the double clad fiber does not need a thermal management system for the cladding strippers.

[0032] As shown in **FIG. 2**, for example, coupling the highly reflective double clad fiber **218** with a REDF **208** and coupling the REDF **208** with partial reflective double-clad fiber **210** results in splices **206** and **221** respectively. Coupling partial reflective double-clad fiber **210** to a terminator **214** results in the splices **223** and **225** and a cladding stripper **212**.

[0033] It should be noted, in prior art system **100** depicted in **FIG. 1**, the multimode fibers **116** unnecessarily choke the total power potentially coupled into double clad fiber laser. The system **200** increases the coupling efficiency of the diode laser **202** into a fiber by eliminating the multimode fiber **116** depicted in **FIG. 1** and using a double clad fiber **218** in its place. The system **200** enables more power to be transported to the pumped laser medium without significant sacrifice in brightness or alteration of existing design. Additionally, the system **200** simplifies the use of fiber coupled diode laser **202** by removing the cladding mode stripper responsible for removing the light coupled into the glass cladding of a multimode fiber. This cladding

mode stripper is a heat source and requires some form of thermal dissipation via air or water. The system **200**, by leveraging the ability of a double clad fiber **218** to propagate light in the polymer clad glass cladding, eliminates the need to design and engineer a thermal management system for these cladding mode strippers, thus greatly simplifying laser architecture.

[0034] **FIG. 3** is an illustration of a configuration of a double clad fiber **218** utilized in **FIG. 2**, in accordance with the disclosed embodiments. When the diode laser **202** and double clad fiber **218** are bonded with connectors, the adhesive is placed directly on the acrylate coating **304** and not on the glass cladding **306** to bond the fiber to the ferrule **302**, which holds the fiber **218**. The glass cladding 306 of the fiber **218** carries the laser pumped from the diode laser **202.** Numeral **308** in **FIG. 3** is an arbitrary pattern intended to represent the diode light being coupled into the cladding of the double-clad fiber. Directly connecting the double clad fiber **218** with the diode laser **202** increases environmental robustness and also increases the total usable aperture available for coupling of the diode laser **202.** This method mitigates damaging effects of beam degradation associated with high power operation and operation in strenuous environments, such as those on military platforms.

[0035] The system **200** is more tolerant of beam blooming, diode smile, and beam wandering exhibited by diode laser **202** because there is a greater area available for fiber coupling. This is a very critical attribute for high reliability lasers, particularly in demanding applications where regular maintenance or repair is not an option, like on a satellite of a military platform actively deployed.

[0036] In **FIG. 4** a method **400** of coupling a diode laser **202** and the double clad fiber **218** of depicted in **FIG. 3**. As said at the block **402** and **404**, the adhesive for connecting diode laser and the double clad fiber is placed on the acrylate coating on the fiber and not in contact with glass cladding. As depicted at blocks **406** and **408**, adhesive in contact with acrylate coating avoids cladding strippers created by adhesive in contact with glass cladding and thermal management system for the cladding strippers. This increase the coupling efficiency of the laser diode.

[0037] It should be noted that, there is also a significant simplification in fiber laser architecture associated with the present system. The system, when implemented in a fiber laser oscillator, eliminates a splice in the fiber laser by allowing the diode light to be directly coupled into the double clad fiber that the high-reflector fiber Bragg grating is written into. For a company producing large numbers of these lasers, this has several implications such as eliminating a splice decreases assembly time by an amount proportional to the total number of splices needed to build the laser, laser reliability increases by eliminating that splice, and laser efficiency is increased by eliminating a potential source for loss and increased the coupling efficiency of the laser diode. Furthermore, packaging of such a laser is simplified since the design does not need to consider the placement and protection of an additional critical element in the laser architecture.

[0038] Finally, in the system, a diode-fiber interface cladding stripper is unnecessary and unwanted. In addition, the construction of the fiber connector must change to ensure it survives. This requires the connector be made such that no optical adhesives are in contact with the glass cladding. Any optical adhesive in contact with the glass cladding would act as a cladding stripper and remove the diode light. This could also result in heating of the connector which could lead to catastrophic optical damage. To eliminate this effect when making the connector, any optical adhesive must be placed in contact with the acrylate coating only, rather than the bare glass. By adhering to the acrylate, no out-coupling of cladding light can occur, as the waveguide interface (the acrylate-cladding interface) is in-tact. This enables the coupling of diode light into the double clad fiber while ensuring the connector adhesive does not act as a cladding stripper.

[0039] While the present invention has been described in connection with the preferred embodiments of the various Figures, it is to be understood that other similar embodiments may be used or modifications or additions may be made to the described embodiment for performing the same function of the present invention without deviating therefrom. Therefore, the present invention should not be limited to any single embodiment, but rather construed in breadth and scope in accordance with the recitation of the appended claims.

[0040] It will be appreciated that variations of the above disclosed and other features and functions, or alternatives thereof, may be desirably combined into many other different systems or applications. Also, various presently unforeseen or unanticipated alternatives, modifications, variations or improvements therein may be subsequently made by those skilled in the art which are also intended to be encompassed by the following claims.

[0041] Although embodiments of the current disclosure have been described comprehensively in considerable detail to cover the possible aspects, those skilled in the art would recognize that other versions of the disclosure are also possible.

CLAIMS

What is claimed is:

1. A diode laser comprising:

a diode pump source for generating a force to pump a laser; and

a double clad fiber directly coupled to the diode pump source instead of coupling to the multimode fiber, wherein the pumped laser is transmitted directly through the double clad fiber, thereby increasing the coupling efficiency of the diode pump source.

2. The diode laser of claim 1 further comprises at least one connector for connecting the double clad fiber and the diode pump source.

3. The diode laser of claim 2, wherein the connector comprises at least one adhesive in contact with an acrylate coating of the double clad fiber.

4. The diode laser of claim 3, wherein the adhesive is not in contact with a glass cladding of the double clad fiber.

5. The diode laser of claim 3, wherein the adhesive does not act as a cladding stripper.

6. The diode laser of claim 1, wherein the double clad fiber comprises no cladding stripper.

7. The diode laser of claim 1, wherein the double clad fiber comprises no thermal management system for the cladding strippers.

8. The diode laser of claim 1, wherein the double clad fiber comprises high-reflector fiber Bragg grating.

9. A fiber laser oscillator comprising a diode laser, wherein the diode laser comprises:

a diode pump source for generating a force to pump a laser; and

a double clad fiber directly coupled to the diode pump source instead of coupling to the multimode fiber, wherein the pumped laser is transmitted through the double clad fiber, thereby increasing the coupling efficiency of the diode pump source.

10. The fiber laser oscillator of claim 9, wherein the double clad fiber comprises high-reflector fiber Bragg grating.

ABSTRACT

A system and method for increasing the fiber coupling efficiency of diode lasers is disclosed. The diode laser has a diode pump source for generating a force to pump a laser and a double clad fiber directly coupled to the diode pump source instead of coupling to the multimode fiber. The pumped laser is transmitted directly through the double clad fiber thereby increasing the coupling efficiency of the diode pump source. At least one connector is utilized for connecting the double clad fiber and the diode pump source. The connector has at least one adhesive placed in contact with an acrylate coating and not in contact with a glass cladding of the double clad fiber to avoid cladding stripper and fiber splice thereby increasing the fiber coupling efficiency.

FIBER COUPLING EFFICIENCY OF DIODE LASERS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This Application claims rights under 35 USC §119(e) from U.S. Application Serial No. 61/886,696 filed 4 Oct 2013, the contents of which are incorporated herein by reference.

TECHNICAL FIELD

[0002] The present disclosure relates generally to diode lasers. Embodiments of the disclosure are related to systems and methods of constructing diode lasers to increase the fiber coupling efficiency.

BACKGROUND

[0003] High power laser diodes have become a staple pump source for both solid state and fiber optic lasers due to their high brightness, spectral versatility, environmental robustness and high efficiency. Typical high power fiber coupled diode lasers are focused into the large core of a glass-cladded multimode fiber.

[0004] **FIG. 1** is an illustration of a schematic diagram of a prior art laser system **100** utilized for coupling a diode laser **102** to a double clad fiber **118** through a multimode fiber **116**. The core multimode fiber **116** by which the diode laser **102**, used to pump the double clad fiber laser, is coupled into is generally smaller than the glass cladding of the double clad fiber **118,** it is pumping. This results in an aperture mis-match and a loss in efficiency because the double clad fiber **118** is capable of receiving lower brightness light than the multimode fiber **116** for comparable numerical apertures.

[0005] Thus, connecting the pump diode 102 to multimode fiber **116** a portion of the available laser power from the pump diode lost. Invariably power is launched into the cladding of multimode fiber **116**. When multimode fiber **116** is built into a connector a cladding mode stripper is required to remove light coupled into the cladding of multimode fiber **116**. Double clad fiber **118** typically provides a larger aperture to couple light from pump diode **102** to the fiber laser oscillator comprised of **118, 118*, 108, 110, 110*** and associated splices **105** and **121**. The larger aperture provided by double clad fiber **118** increases pump diode coupling efficiency and removes the necessity for a cladding stripper at the pump-diode to fiber connector interface. Higher diode-coupling efficiencies and a simplified laser construction process are realized when coupling light into double-clad fiber **118** compared to using multimode fiber **116**.

[0006] A result of higher diode coupling efficiencies is the removal of the cladding stripper built into the connector built into multimode fiber **116**. For a laser system coupling pump diode **102** into double clad fiber **118** a cladding stripper is not needed at the diode to fiber interface as was the case when coupling into multimode fiber **116**. Constructing the connector with double clad fiber **118** adhesive or other bonding materials must not come into contact with the bare glass of **118** so as to not unintentionally create a cladding stripper.

[0007] The highly reflective fiber Bragg grating **118*** is fabricated from the same double clad fiber **118**. For pump diode **102** coupled into multimode fiber **116** splice **104** is required to transmit the light coupled into multimode fiber **116** to the fiber laser comprised of **118, 118* 108, 110, 110*** and associated splices **105** and **121.** Splice **104** becomes unnecessary when coupling pump diode **102** into double clad fiber **118**. The pump light is now coupled directly into the fiber laser comprised of **118, 118*, 108, 110, 110*** and associated splices **105** and **121** without the need for an intermediate multimode fiber **116**. The removing splice **104** from the laser increases efficiency as all splices present some finite amount of loss (decrease in efficiency).

[0008] A need, therefore, exists for an improved coupling method that overcomes the above drawbacks.

SUMMARY

[0009] The following summary is provided to facilitate an understanding of some of the innovative features unique to the disclosed embodiment and is not intended to be a full description. A full appreciation of the various aspects of the embodiments disclosed herein can be gained by taking into consideration the entire specification, claims, drawings, and abstract as a whole.

[0010] It is, therefore, one aim of the disclosed embodiments to provide for a diode laser comprising a diode pump source for generating a force to pump a laser and a double clad fiber directly coupled to the diode pump source instead of coupling to the multimode fiber. The pumped laser is transmitted directly through the double clad fiber thereby increasing the coupling efficiency of the diode pump source.

[0011] It is, therefore, one aim of the disclosed embodiments to provide for a diode laser in which at least one connector for connecting the double clad fiber and the diode pump source.

[0012] It is, therefore, one aim of the disclosed embodiments to provide for a diode laser comprising the connector having at least one adhesive in contact with an acrylate coating of the double clad fiber.

[0013] It is, therefore, one aim of the disclosed embodiments to provide for a diode laser in which the adhesive is not in contact with a glass cladding of the double clad fiber and thus the adhesive does not act as a cladding stripper.

[0014] It is, therefore, one aim of the disclosed embodiments to provide for a fiber-coupled diode laser in which the double clad fiber comprises no cladding stripper and hence the need for thermal management system for the cladding strippers is avoided.

[0015] It is, therefore, one aim of the disclosed embodiments to provide for a fiber-coupled diode laser in which the double clad fiber may be the same fiber as thehigh-reflector fiber Bragg grating.

[0016] It is, therefore, one aim of the disclosed embodiments to provide for a fiber laser oscillator that comprises a fiber-coupled diode laser. The diode laser has a diode pump source for generating a force to pump a laser and a double clad fiber directly coupled to the diode pump source instead of coupling to the multimode fiber. The pumped laser is transmitted directly through the double clad fiber thereby increasing the coupling efficiency of the diode pump source. At least one connector is utilized for connecting the double clad fiber and the diode pump source. The connector comprises at least one adhesive in contact with an acrylate coating of the double clad fiber and not in contact with a glass cladding of the double clad. The double clad fiber comprises no cladding stripper and hence the need for thermal management system for the cladding strippers can be avoided. The double clad fiber may be the same as the high-reflector fiber Bragg grating.

[0017] It is, therefore, one aim of the disclosed embodiments to provide for a laser system that comprises a diode laser. The diode laser has a diode pump source for generating a force to pump a laser and a double clad fiber directly coupled to the diode pump source instead of coupling to the multimode fiber. The pumped laser is transmitted directly through the double clad fiber thereby increasing the coupling efficiency of the diode pump source. At least one connector is utilized for connecting the double clad fiber and the diode pump source. The connector comprises at least one adhesive in contact with an acrylate coating of the double clad fiber and not in contact with a glass cladding of the double clad. The double clad fiber comprises no cladding stripper and hence the need for thermal management system for the cladding strippers can be avoided. The double clad fiber may be the same as the high-reflector fiber Bragg grating.

[0018] It is, therefore, one aim of the disclosed embodiments to provide for a method for constructing a double clad fiber connector. This method would include placing at least one adhesive in contact with an acrylate coating and avoiding at least one adhesive in contact with a glass cladding.

[0019] It is, therefore, yet another aim of the disclosed embodiments to provide for a method for constructing a double clad fiber connector comprising avoiding cladding strippers due to adhesive in contact with the glass cladding and avoiding thermal management system for the cladding strippers.

[0020] It is, therefore, one aim of the disclosed embodiments to provide for a method for constructing a double clad fiber comprising eliminating at least one fiber splice in the double clad fiber.

[0021] It is, therefore, one aim of the disclosed embodiments to provide for a method for eliminating a fiber splice when mating a fiber-coupled pump diode to a double-clad fiber laser.

[0022] It is, therefore, yet another aim of the disclosed embodiments to provide for a system and method for increasing the fiber coupling efficiency of diode lasers in which the environmental robustness of fiber coupled diode lasers is increased. Increasing the total usable aperture available for coupling of the diode laser mitigates damaging effects of beam degradation associated with high power operation and operation in strenuous environments, such as those on military platforms.

[0023] It is, therefore, yet another aim of the disclosed embodiments to provide for a system and method for increasing the fiber coupling efficiency of diode lasers which is more tolerant of beam blooming, diode smile, and beam wandering exhibited by diode lasers because there is a greater area available for fiber coupling.

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] The summary above, as well as the following detailed description of illustrative embodiments, is better understood when read in conjunction with the appended drawings. For the purpose of illustrating the present disclosure, exemplary constructions of the disclosure are shown in the drawings. However, the disclosure is not limited to specific methods and instrumentalities disclosed herein. Moreover, those in the art will understand that the drawings are not to scale. Wherever possible, like elements have been indicated by identical numbers.

[0025] **FIG. 1** is an illustration of a schematic diagram of a prior art laser system comprising a diode pump coupled to a double clad fiber through a multimode fiber;

[0026] **FIG. 2** is an illustration of a schematic diagram of a laser system comprising a diode pump directly coupled to a double clad fiber, in accordance with the disclosed embodiments;

[0027] **FIG. 3** is an illustration of a configuration of a double clad fiber utilized in **FIG. 2**, in accordance with the disclosed embodiments; and

[0028] **FIG. 4** is an illustration of a flowchart showing a method of coupling diode pump and the double clad fiber of depicted in **FIG. 3**, in accordance with the disclosed embodiments.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

[0029] The particular configurations discussed in the following description are non-limiting examples that can be varied and are cited merely to illustrate at least one embodiment and are not intended to limit the scope thereof.

[0030] A system and method for increasing the fiber coupling efficiency of diode lasers is disclosed. The diode-fiber interface connector has at least one adhesive placed in contact with an acrylate coating and not in contact with a glass cladding of the double clad fiber to avoid creating a cladding stripper.

[0031] **FIG. 2** is an illustration of a schematic diagram of a laser system **200** utilized for coupling a diode laser **202** directly to a double clad fiber **218** without connecting to a multimode fiber **116** as depicted in prior art system **100** of **FIG. 1**. The pumped laser is transmitted directly through the double clad fiber **218**, thereby increasing the coupling efficiency of the diode laser **202**. The diode laser **202** has at least one connector (not shown) for connecting the double clad fiber **218** and the diode laser **202**. The connector comprises at least one adhesive in contact with an acrylate coating of the double clad fiber **218** and not in contact with a glass cladding of the double clad fiber **218**. Adhesive in contact with an acrylate coating does not act as a cladding stripper and hence avoids the light loss. As there is no light loss hence there is no heat generation. Thus, the double clad fiber does not need a thermal management system for the cladding strippers.

[0032] As shown in **FIG. 2**, for example, coupling the highly reflective double clad fiber **218** with a REDF **208** and coupling the REDF **208** with partial reflective double-clad fiber **210** results in splices **206** and **221** respectively. Coupling partial reflective double-clad fiber **210** to a terminator **214** results in the splices **223** and **225** and a cladding stripper **212**.

[0033] It should be noted, in prior art system **100** depicted in **FIG. 1**, the multimode fibers **116** unnecessarily choke the total power potentially coupled into double clad fiber laser. The system **200** increases the coupling efficiency of the diode laser **202** into a fiber by eliminating the multimode fiber **116** depicted in **FIG. 1** and using a double clad fiber **218** in its place. The system **200** enables more power to be transported to the pumped laser medium without significant sacrifice in brightness or alteration of existing design. Additionally, the system **200** simplifies the use of fiber coupled diode laser **202** by removing the cladding mode stripper responsible for removing the light coupled into the glass cladding of a multimode fiber. This cladding

mode stripper is a heat source and requires some form of thermal dissipation via air or water. The system **200**, by leveraging the ability of a double clad fiber **218** to propagate light in the polymer clad glass cladding, eliminates the need to design and engineer a thermal management system for these cladding mode strippers, thus greatly simplifying laser architecture.

[0034] **FIG. 3** is an illustration of a configuration of a double clad fiber **218** utilized in **FIG. 2**, in accordance with the disclosed embodiments. When the diode laser **202** and double clad fiber **218** are bonded with connectors, the adhesive is placed directly on the acrylate coating **304** and not on the glass cladding **306** to bond the fiber to the ferrule **302**, which holds the fiber **218**. The glass cladding 306 of the fiber **218** carries the laser pumped from the diode laser **202.** Numeral **308** in **FIG. 3** is an arbitrary pattern intended to represent the diode light being coupled into the cladding of the double-clad fiber. Directly connecting the double clad fiber **218** with the diode laser **202** increases environmental robustness and also increases the total usable aperture available for coupling of the diode laser **202.** This method mitigates damaging effects of beam degradation associated with high power operation and operation in strenuous environments, such as those on military platforms.

[0035] The system **200** is more tolerant of beam blooming, diode smile, and beam wandering exhibited by diode laser **202** because there is a greater area available for fiber coupling. This is a very critical attribute for high reliability lasers, particularly in demanding applications where regular maintenance or repair is not an option, like on a satellite of a military platform actively deployed.

[0036] In **FIG. 4** a method **400** of coupling a diode laser **202** and the double clad fiber **218** of depicted in **FIG. 3**. As said at the block **402** and **404**, the adhesive for connecting diode laser and the double clad fiber is placed on the acrylate coating on the fiber and not in contact with glass cladding. As depicted at blocks **406** and **408**, adhesive in contact with acrylate coating avoids cladding strippers created by adhesive in contact with glass cladding and thermal management system for the cladding strippers. This increase the coupling efficiency of the laser diode.

[0037] It should be noted that, there is also a significant simplification in fiber laser architecture associated with the present system. The system, when implemented in a fiber laser oscillator, eliminates a splice in the fiber laser by allowing the diode light to be directly coupled into the double clad fiber that the high-reflector fiber Bragg grating is written into. For a company producing large numbers of these lasers, this has several implications such as eliminating a splice decreases assembly time by an amount proportional to the total number of splices needed to build the laser, laser reliability increases by eliminating that splice, and laser efficiency is increased by eliminating a potential source for loss and increased the coupling efficiency of the laser diode. Furthermore, packaging of such a laser is simplified since the design does not need to consider the placement and protection of an additional critical element in the laser architecture.

[0038] Finally, in the system, a diode-fiber interface cladding stripper is unnecessary and unwanted. In addition, the construction of the fiber connector must change to ensure it survives. This requires the connector be made such that no optical adhesives are in contact with the glass cladding. Any optical adhesive in contact with the glass cladding would act as a cladding stripper and remove the diode light. This could also result in heating of the connector which could lead to catastrophic optical damage. To eliminate this effect when making the connector, any optical adhesive must be placed in contact with the acrylate coating only, rather than the bare glass. By adhering to the acrylate, no out-coupling of cladding light can occur, as the waveguide interface (the acrylate-cladding interface) is in-tact. This enables the coupling of diode light into the double clad fiber while ensuring the connector adhesive does not act as a cladding stripper.

[0039] While the present invention has been described in connection with the preferred embodiments of the various Figures, it is to be understood that other similar embodiments may be used or modifications or additions may be made to the described embodiment for performing the same function of the present invention without deviating therefrom. Therefore, the present invention should not be limited to any single embodiment, but rather construed in breadth and scope in accordance with the recitation of the appended claims.

[0040] It will be appreciated that variations of the above disclosed and other features and functions, or alternatives thereof, may be desirably combined into many other different systems or applications. Also, various presently unforeseen or unanticipated alternatives, modifications, variations or improvements therein may be subsequently made by those skilled in the art which are also intended to be encompassed by the following claims.

[0041] Although embodiments of the current disclosure have been described comprehensively in considerable detail to cover the possible aspects, those skilled in the art would recognize that other versions of the disclosure are also possible.

CLAIMS

What is claimed is:

1. A diode laser comprising:

a diode pump source for generating a force to pump a laser; and

a double clad fiber directly coupled to the diode pump source instead of coupling to the multimode fiber, wherein the pumped laser is transmitted directly through the double clad fiber, thereby increasing the coupling efficiency of the diode pump source.

2. The diode laser of claim 1 further comprises at least one connector for connecting the double clad fiber and the diode pump source.

3. The diode laser of claim 2, wherein the connector comprises at least one adhesive in contact with an acrylate coating of the double clad fiber.

4. The diode laser of claim 3, wherein the adhesive is not in contact with a glass cladding of the double clad fiber.

5. The diode laser of claim 3, wherein the adhesive does not act as a cladding stripper.

6. The diode laser of claim 1, wherein the double clad fiber comprises no cladding stripper.

7. The diode laser of claim 1, wherein the double clad fiber comprises no thermal management system for the cladding strippers.

8. The diode laser of claim 1, wherein the double clad fiber comprises high-reflector fiber Bragg grating.

9. A fiber laser oscillator comprising a diode laser, wherein the diode laser comprises:

a diode pump source for generating a force to pump a laser; and

a double clad fiber directly coupled to the diode pump source instead of coupling to the multimode fiber, wherein the pumped laser is transmitted through the double clad fiber, thereby increasing the coupling efficiency of the diode pump source.

10. The fiber laser oscillator of claim 9, wherein the double clad fiber comprises high-reflector fiber Bragg grating.

ABSTRACT

A system and method for increasing the fiber coupling efficiency of diode lasers is disclosed. The diode laser has a diode pump source for generating a force to pump a laser and a double clad fiber directly coupled to the diode pump source instead of coupling to the multimode fiber. The pumped laser is transmitted directly through the double clad fiber thereby increasing the coupling efficiency of the diode pump source. At least one connector is utilized for connecting the double clad fiber and the diode pump source. The connector has at least one adhesive placed in contact with an acrylate coating and not in contact with a glass cladding of the double clad fiber to avoid cladding stripper and fiber splice thereby increasing the fiber coupling efficiency.

Applicant: BAE SYSTEMS Information & Electronic Systems Integration Inc.

1/4




FIG. 1

PRIOR ART

Applicant: BAE SYSTEMS Information & Electronic Systems Integration Inc.




FIG. 2

Applicant: BAE SYSTEMS Information & Electronic Systems Integration Inc.




FIG. 3

Applicant: BAE SYSTEMS Information & Electronic Systems Integration Inc.




FIG. 4