



(86) Date de dépôt PCT/PCT Filing Date: 2014/07/21

(87) Date publication PCT/PCT Publication Date: 2015/11/19

(45) Date de délivrance/Issue Date: 2021/01/12

(85) Entrée phase nationale/National Entry: 2016/10/28

(86) N° demande PCT/PCT Application No.: IB 2014/063278

(87) N° publication PCT/PCT Publication No.: 2015/173612

(30) Priorité/Priority: 2014/05/12 (IT TO2014A000371)

(51) Cl.Int./Int.Cl. *A61M 39/10* (2006.01)

(72) Inventeur/Inventor:

GUALA, GIANNI, IT


(73) Propriétaire/Owner:

INDUSTRIE BORLA S.P.A., IT

(74) Agent: BERESKIN & PARR LLP/S.E.N.C.R.L., S.R.L.

(54) Titre : RACCORD TUBULAIRE POUR VOIES DE FLUIDE MEDICAL

(54) Title: TUBULAR FITTING FOR MEDICAL FLUID LINES



(57) Abrégé/Abstract:

A tubular fitting for medical fluid lines comprising a hollow body (1) within which a male connector (2) and an opposite female connector (3) are coaxially housed. The male connector (2) is coupled in rotation with respect to the body (1) in the direction (F) corresponding to the screwing with a female connector of the line, while it is normally freely rotatable in the unscrewing direction, in the same way as the female connector (3) is coupled in rotation with respect to the body (1) in the direction (G) corresponding to the screwing with a male connector of the line, while it is normally freely rotatable in the unscrewing direction. The male connector (2) and/or the female connector (3) can possibly be locked in rotation with respect to the body (1) in the unscrewing direction, only following a positive command.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau

(43) International Publication Date
19 November 2015 (19.11.2015)



(10) International Publication Number
WO 2015/173612 A1

(51) International Patent Classification:
A61M 39/10 (2006.01)

(21) International Application Number:
PCT/IB2014/063278

(22) International Filing Date:
21 July 2014 (21.07.2014)

(25) Filing Language: Italian

(26) Publication Language: English

(30) Priority Data:
TO2014A000371 12 May 2014 (12.05.2014) IT

(71) Applicant: **INDUSTRIE BORLA S.P.A.** [IT/IT]; Via G. Di Vittorio, 7bis, I-10024 Moncalieri (Torino) (IT).

(72) Inventor: **GUALA, Gianni**; Strada Villa Zanetti, 28/18, I-10133 Torino (IT).

(74) Agent: **BUZZI, Franco**; Buzzi, Notaro & Antonielli d'Oulx S.r.l., Via Maria Vittoria, 18, I-10123 Torino (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: TUBULAR FITTING FOR MEDICAL FLUID LINES

FIG. 3



(57) Abstract: A tubular fitting for medical fluid lines comprising a hollow body (1) within which a male connector (2) and an opposite female connector (3) are coaxially housed. The male connector (2) is coupled in rotation with respect to the body (1) in the direction (F) corresponding to the screwing with a female connector of the line, while it is normally freely rotatable in the unscrewing direction, in the same way as the female connector (3) is coupled in rotation with respect to the body (1) in the direction (G) corresponding to the screwing with a male connector of the line, while it is normally freely rotatable in the unscrewing direction. The male connector (2) and/or the female connector (3) can possibly be locked in rotation with respect to the body (1) in the unscrewing direction, only following a positive command.

"Tubular fitting for medical fluid lines"

Field of the invention

The present invention relates, in general, to
5 medical fluid lines, for example, hemodialysis lines,
chemotherapy lines and the like.

State of the art

Such fluid lines are normally fitted along their
path with connectors for the connection between the
10 various components of the line: typically male and
female luer lock connectors and the like. Accidental
disengagement or due to incorrect maneuvers between
these connectors can result in possible serious
consequences for the patients connected during the use
15 of the line.

Summary of the invention

The object of the present invention is to provide
a safe and effective solution to this problem, whilst
at the same time being practical and functional.

20 According to the invention, this object is
achieved thanks to a fitting for medical fluid lines
comprising a hollow body within which a male connector
accessible at one end of the body and a female
connector accessible at the other end of the body, are
25 coaxially housed. The fitting comprises first
unidirectional coupling means for locking in rotation
the male connector with respect to the body in the
direction corresponding to the screwing between said
male connector and a complementary female connector of
30 the line, and to enable free rotation of the male
connector in the opposite direction, and second
unidirectional coupling means for locking in rotation
the female connector with respect to the body in the
direction corresponding to the screwing between said
35 female connector and a complementary male connector of

the line, and to enable free rotation of the female connector in the opposite direction.

Thanks to this solution idea, the fitting according to the invention is advantageously usable in the form of an intermediate element for a secure connection between a male connector and a female connector of medical fluid lines. In practice, these connectors, instead of being connected directly to each other, are thus connected indirectly, by means of the fitting according to the invention, which ensures the necessary degree of safety against risks of undesired openings of the medical line due to accidental decoupling or a wrong maneuver between the connectors of the line.

According to a further advantageous characteristic of the invention, first and/or second locking means can also be provided, designed to be positively operated to lock in rotation the male connector and/or the female connector, respectively, with respect to the body in the aforesaid opposite direction of rotation.

In the fitting according to the invention, the male and female connectors can be in communication with each another to define a flow passage through the fitting, or the communication between the male and female connectors can be obstructed.

Furthermore, according to a particularly advantageous embodiment of the invention, the female connector can be a valve connector and the male connector can also be a valve connector.

Brief description of the drawings

The invention will now be described in detail with reference to the accompanying drawings, provided purely by way of non-limiting example, in which:

- Figure 1 is a schematic perspective view of a fitting for medical fluid lines according to a first

embodiment of the invention,

- Figure 2 is an elevational side view of the fitting,

5 - Figure 3 is an axial section view along the line
III-III of Figure 2,

- Figure 4 is a cross sectional view along the line IV-IV of Figure 2,

- Figure 5 is a cross sectional view along the line V-V of Figure 3,

10 - Figure 6 is a cross sectional view along the line VI-VI of Figure 2,

- Figure 7 is a cross sectional view along the line VII-VII of Figure 3,

15 - Figure 8 is an elevational side view of a second embodiment of the fitting according to the invention,

- Figure 9 is an axial section view according to the line C-C of Figure 8,

- Figure 10 is a cross sectional view along line B-B of Figure 8,

20 - Figure 11 is a cross sectional view along line A-A of Figure 8,

- Figure 12 is a cross sectional view along line D-D of Figure 9,

25 - Figure 13 is a cross sectional view along line E-E of Figure 9,

-Figure 14 is an elevational side view of a third embodiment of the fitting according to the invention,

- Figure 15 is an axial section view according to the line C-C of Figure 14,

30 - Figure 16 is a cross sectional view along line B-B of Figure 14,

- Figure 17 is a cross sectional view along line A-A of Figure 14,

35 - Figure 18 is a cross sectional view along line D-D of Figure 15,

- Figure 19 is a cross sectional view along line E-E of Figure 15,

- Figure 20 is an elevational side view of a fourth embodiment of the fitting according to the invention,

- Figure 21 is an axial section view according to the line C-C of Figure 20,

- Figure 22 is a cross sectional view along line B-B of Figure 20,

10 - Figure 23 is a cross sectional view along line A-A of Figure 20,

- Figure 24 is a cross sectional view along line D-D of Figure 21,

15 - Figure 25 is a cross sectional view along line E-E of Figure 21,

- Figure 26 is a schematic perspective view of a fifth embodiment of the fitting according to the invention,

20 - Figure 27 is an end view of the fitting of Figure 26,

- Figure 28 is a sectional view along the line A-A of Figure 27, and

- Figure 29 is a sectional view along the line B-B of Figure 28.

25 Detailed description of the invention

Referring initially to Figures 1 to 7, the fitting according to a first embodiment of the invention is indicated with I and is tubular. It comprises an outer hollow body 1 of generally cylindrical shape, within which a male connector 2 of the luer lock type and analogues, and a female fitting 3 of the luer lock type and analogues are coaxially housed in an opposite condition.

35 The connectors 2 and 3 are rotatably mounted relative to the body 1 and to each another, with the

limitations which will be discussed, and have a generally conventional shape. In detail, the male connector 2 comprises an inner tubular element 4 with a conical outer surface protruding from one end of the body 1, and an internally threaded outer hollow element 5, which extends towards the inside of the body 1 with a hollow appendage 6.

The female connector 3 consists of an externally threaded tubular element 7 with a conical inner surface, protruding from the other end of the body 1 and integrally formed with an appendage 8 terminating with a shank 9 rotatably inserted within the hollow appendage 6 of the male connector 2.

The connectors 2 and 3 are locked axially within the body 1, which is conveniently formed from two half-shells coupled together in an interlocking manner, and an O-ring seal 10 is interposed between the shank 9 and the hollow appendage 6.

The male and female connectors 2, 3 define a free flow passage through the connector according to the invention, and during use are intended to be respectively coupled to a complementary female connector and to a complementary male connector of a medical line.

The hollow appendage 6 of the male connector 2 and the appendage 8 of the female connector 3 are locked axially within the hollow body 1 and are coupled with this in rotation in one direction and normally freely rotatable in the opposite direction. However, as will become evident, the rotation in the opposite direction may also possibly be locked, but only following a positive command imparted manually.

In detail, and referring now to Figures 4 and 5, the hollow body 1 is formed internally, on the side of the male connector 2, of a crown of elastically

yielding ratchet teeth 12 cooperating by unidirectional coupling with corresponding projecting teeth 13 formed on the outside of the hollow element 5 of the male connector 2. The arrangement is such so that the hollow element 5, and therefore the entire male connector 2, is coupled in rotation with the hollow body 1 in the direction indicated by the arrow F in Figure 5, due to the effect of the engagement between the teeth 12 and 13. The direction of rotation F corresponds to the screwing between the male connector 2 and a complementary female connector, assuming the hollow body 1 is kept stationary, and then the complementary female connector is rotated to screw it into the male connector 2. In the opposite direction of rotation, or rather, the unscrewing direction, the male connector 2 is freely rotatable relative to the hollow body 1 due to the bounce of the yielding teeth 12 on the teeth 13, so that the complementary female connector cannot unscrew itself.

Obviously, in the case in which the hollow body 1 rotates and the complementary female connector is kept stationary, the situation is reversed, i.e. the direction of screwing is opposite to that of the arrow F, and the unscrewing direction is that of the arrow F.

In this way, during use, an accidental disengagement or wrong maneuver between the male connector 2 and the complementary female connector is prevented. The unscrewing may, however, possibly be allowed, but, as mentioned, only a result of a positive maneuver. To this effect, the wall of the hollow body 1 may also be formed with a pair of elastically yielding locking segments 14 whose free ends 15 are suitable for engaging, as a result of a thrust applied to the segments 14, respective peripheral teeth formations 16 of the hollow appendage 6 (Figure 4), so as to lock the

rotation of the male connector 2 with respect to the body 1.

Similarly, and with reference to Figures 6 and 7, the female connector 3 is coupled in rotation with the hollow body 1 in the direction indicated by the arrow G in Figure 7, corresponding to the screwing of this female connector 3 with a complementary male connector, maintaining the hollow body 1 stationary, while it is normally freely rotatable in the opposite direction, i.e. the unscrewing direction. To this effect, the hollow body 1 is formed with a further series of elastically yielding ratchet teeth 17, analogous to the yielding teeth 12, cooperating by unidirectional coupling with corresponding projecting teeth 18 formed on the outside of an initial portion of the appendage 8. For possible locking of the female connector 3 in rotation with respect to the hollow body 1, in the direction opposite to that indicated by the arrow G, a positive command manual should also be imparted in this case, and to this effect, the hollow body 1 can be formed with a further pair of elastically yielding locking segments 19, analogous to the yielding locking segments 14, the free ends 20 of which are suitable for engaging respective peripheral teeth formations 21 of the appendage 8 (Figure 6).

During use, the fitting according to the invention advantageously operates in the manner of an intermediate safety element for the coupling of the female connector with the male connector of a medical fluid line, which as already mentioned are connected, instead of directly to each other, to the male connector 2 and the female connector 3, respectively. Following this connection, an accidental opening or due to incorrect operation of the medical line is thus reliably prevented, as the separation between the

female connector of the line and the male connector 2 cannot be operated, or if at all, can only be operated voluntarily by applying a manual pressure on the elastically yielding segments 14, if present, and
5 similarly, the separation between the male connector of the line and the female connector 3 can possibly be achieved only by pressing the elastically yielding segments 19, if present.

The further embodiments of the fitting according
10 to the invention differ from the one already described only in the differences that will now be described in detail, using the same numerical references (partly omitted for simplicity of illustration) for the identical or similar parts.

15 In the variant shown in Figures 8-13, the fitting, indicated as a whole with II, tubular in this case as well, to define an open flow line, essentially differs from the fitting I of Figures 1-7 only in the fact that the outer body 1 is devoid of yielding locking segments
20 14 and/or 19. Therefore, the fitting II does not allow the voluntary unscrewing of the male connector 2 and/or the female connector 3 from the relative complementary female and male connectors.

In the variant shown in Figures 14-19, the
25 fitting, indicated as a whole with III, is analogous to the fitting II and only differs from it in the fact that it is not tubular, or rather it does not define an open flow passage between the two connectors 2 and 3. The communication between the two connectors is
30 permanently obstructed: to this effect, the female connector 3 has a transverse obstructive partition 20 (Figure 21).

In the variant shown in Figures 20-25, the
fitting, indicated as a whole with IV, is analogous to
35 the connection I and only differs from it in the fact

that it also does not define an open flow passage between the two connectors 2 and 3, whose communication is thus obstructed. In this case, the inner element 4 of the male connector 2 is closed by a transverse partition 21 (Figure 21).

In the variant shown in Figures 26-29, the fitting, indicated as a whole with V, is tubular and the male 2 and female 3 connectors are valve connectors of the cleanable ("swabbable") type.

10 In particular, the male valve connector 2 generally corresponds to that described in the document US-2012/0271246 by the same Applicant: briefly, it comprises a tubular member 22 having an inlet 23 protruding from one end of the hollow body 1, an
15 elastic hollow element 24 which surrounds the tubular member 22 and has an end wall 25 which normally closes the inlet 23 and is formed with a pre-cut 26. A collar 27 surrounds part of the elastic hollow element 24 and is axially movable due to the effect of the coupling of
20 the valve connector 2 with a complementary female connector, inducing a tensile strain of the elastic hollow element 24 and opening the pre-cut 26 and therefore the flow passage through the tubular member 22.

25 The female connector valve 3 generally corresponds to that described in the document US-2009/0292274 by the same Applicant: briefly, it comprises an inner hollow pin 28 arranged axially within an intermediate sealing member 29, which is formed with an elastic head
30 30 having a pre-cut 31, with an elastic hollow element 32 in sealing contact with the hollow pin 28, and with an elastic thrust part 33 tending to maintain the elastic head 30 in a closed condition of the pre-cut 31. When the female connector 3 is coupled with a
35 complementary male connector, the elastic head 30 is

deformed so as to open the pre-cut 31, and therefore the flow passage through the hollow pin 28.

With this arrangement, the flow passage through the fitting V is normally closed, and only opens
5 following the opening of one and/or the other of the valve connectors 2 and 3.

In this embodiment as well, the male valve fitting 2 and the female valve fitting 23 are each coupled in rotation with the casing 1 only in the screwing
10 direction, through the respective unidirectional ratchets 12, 13 and 17, 18, and are freely rotatable in the opposite unscrewing direction. They may also possibly be rendered voluntarily integral in rotation with the body 1 in the unscrewing direction as well,
15 acting on the elastically yielding segments 14, 19 of the body 1, if present, similarly to the other embodiments described above.

Of course, the details of construction and the embodiments may be varied widely with respect to those
20 described and illustrated, without departing from the scope of the present invention as defined in the following claims. For example, in the case of the fitting V, one or the other of the valve connectors 2, 3 could be replaced by a non-valvular fitting.

Claims:

1. A tubular fitting for medical fluid lines, comprising:

a hollow body within which a male connector accessible at one end of the body and a female connector accessible at another end of the body, are coaxially housed,

first ratchet teeth of the body engageable with projecting teeth of the male connector to lock the body in rotation in a direction corresponding to a screwing of said male connector and a complementary female connector to be coupled therewith, and to enable free rotation of the male connector in an opposite direction, and

second ratchet teeth of the body engageable with projecting teeth of the female connector lock the body in rotation in a direction corresponding to a screwing of said female connector and a complementary male connector to be coupled therewith, and to enable free rotation of the female connector in an opposite direction,

said body comprising a first plurality of elastically yielding segments engageable with corresponding peripheral teeth of said male connector to lock the male connector in rotation relative to the body, and

said body comprising a second plurality of elastically yielding segments engageable with corresponding peripheral teeth of said female connector to lock the female connector in rotation relative to the body.

2. A fitting according to claim 1, wherein said male and female connectors are coupled together in a mutually rotary fashion with the interposition of an O-ring.

3. A fitting according to claim 1, wherein said male and female connectors are in communication with each another to define an open flow passage through the fitting.

4. A fitting according to claim 1, wherein the communication between said male and female connectors is obstructed.

5. A fitting according to claim 4, wherein at least one of said male or female connectors has a transverse partition for closing the flow through said fitting.
6. A fitting according to claim 1, wherein the male connector is a valve connector.
7. A fitting according to claim 6, wherein the male connector comprises a tubular member having an inlet, an elastic hollow element that surrounds said tubular member and has an end wall that closes said inlet of the tubular member and is formed with a pre-cut, and a collar axially displaceable to cause a tensile strain of the elastic hollow element elastic so as to open said pre-cut.
8. A fitting according to claim 1, wherein the female connector is a valve connector.
9. A fitting according to claim 8, wherein the female connector comprises an inner hollow pin arranged axially within an intermediate sealing member having an elastic head formed with a pre-cut, an elastic hollow element in sealing contact with the hollow pin and an elastic thrust part tending to maintain the elastic head in a closed condition of said pre-cut.




FIG. 2




FIG. 6




FIG. 3




FIG. 7

FIG. 5




FIG. 4




FIG. 8




FIG. 9




FIG. 11




FIG. 10




FIG. 13




FIG. 12




FIG. 14




FIG. 15




FIG. 17




FIG. 16




FIG. 19




FIG. 18




FIG. 20




FIG. 21




FIG. 23




FIG. 22




FIG. 25




FIG. 24




FIG. 26




FIG. 27




FIG. 28




FIG. 29

