



(11)

EP 4 570 927 A1

(12)

EUROPEAN PATENT APPLICATION
published in accordance with Art. 153(4) EPC

(43) Date of publication:

18.06.2025 Bulletin 2025/25

(51) International Patent Classification (IPC):

C21D 9/46 (2006.01) **C22C 38/00** (2006.01)
C22C 38/06 (2006.01) **C22C 38/60** (2006.01)

(21) Application number: **23865031.1**

(52) Cooperative Patent Classification (CPC):

C21D 9/46; C22C 38/00; C22C 38/06; C22C 38/60

(22) Date of filing: **29.06.2023**

(86) International application number:

PCT/JP2023/024254

(87) International publication number:

WO 2024/057669 (21.03.2024 Gazette 2024/12)

(84) Designated Contracting States:

**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC ME MK MT NL
NO PL PT RO RS SE SI SK SM TR**

Designated Extension States:

BA

Designated Validation States:

KH MA MD TN

- **KIMURA, Hideyuki**
Tokyo 100-0011 (JP)
- **HONDA, Yuma**
Tokyo 100-0011 (JP)
- **MATSUI, Yoichiro**
Tokyo 100-0011 (JP)
- **NOGUCHI, Kotomi**
Tokyo 100-0011 (JP)
- **OZONO, Shuto**
Tokyo 100-0011 (JP)

(30) Priority: **15.09.2022 JP 2022146742**

(71) Applicant: **JFE Steel Corporation**
Tokyo 100-0011 (JP)

(74) Representative: **Haseltine Lake Kempner LLP**
Bürkleinstrasse 10
80538 München (DE)

(72) Inventors:

- **CHIBA, Tadachika**
Tokyo 100-0011 (JP)

(54) **STEEL SHEET, MEMBER, AND METHOD FOR MANUFACTURING THE FOREGOING**

(57) A steel sheet is provided that has a tensile strength of 780 MPa or more, excels in press formability, ductility, and stretch flange formability, and has excellent quality stability in the width direction. A related member, and methods for manufacturing them are also provided.

The steel sheet has a specific chemical composition and a specific steel microstructure and is such that the total area fraction of quenched martensite and retained

austenite each having an aspect ratio of 3 or less and an equivalent circular diameter of 2.0 μm or more is 20% or less relative to the total area fraction of quenched martensite and retained austenite, and the area fraction of a C-enriched region with a C concentration of **0.5 mass%** or more ($S_{C \geq 0.5}$) is 20% or less relative to the entire microstructure.

EP 4 570 927 A1

Description

Technical Field

5 **[0001]** The present invention relates to a steel sheet, a member, and methods for manufacturing them. More specifically, the present invention relates to a steel sheet that has a tensile strength (TS) of 780 MPa or more and excels in formability and quality stability, to a related member, and to methods for manufacturing them. The present invention pertains to a steel sheet for use in various applications including automobiles, to a related member, and to methods for manufacturing them.

10 Background Art

[0002] In recent years, CO₂ emissions from automobiles are regulated more strictly within an international framework from the point of view of the protection of the global environment. The most effective approach to improving the fuel efficiency of automobiles is to reduce the weight of automobile bodies by the thinning of steel sheets used for automobile frame members. For this reason, high strength steel sheets are increasingly used for the purpose of contributing to lowering the fuel consumption of automobiles. In general, increasing the strength of steel sheets tends to result in cracking at the time of press forming due to low ductility and low stretch flange formability. Thus, steel sheets enhanced in ductility and stretch flange formability compared with the conventional level are desired. Furthermore, steel sheets increased in strength also have a high yield ratio YR (YR = yield strength YS/tensile strength TS) and exhibit large springback after forming. As a result, the dimensional accuracy after press forming is problematically lowered. Thus, low-YR steel sheets are desired from the point of view of press formability.

[0003] The amount of CO₂ emissions from all the processes of manufacturing materials and products is an important index from the point of view of carbon neutrality. An increase in the amount of scrap from product manufacturing adds to the total amount of CO₂ emissions and causes a concern that the environmental burden will be increased. For this reason, materials should be used up in the production process (thereby improving the yield). This requires that steel sheets are highly stable in quality in the width direction. However, steel sheets that are increased in strength are noticeably variable in formability, such as ductility and stretch flangeability, in the width direction. Such variations lead to easy occurrence of cracking during press forming. Thus, the blanking positions are necessarily limited to ensure quality, and the yield is lowered as a result.

30 **[0004]** TRIP steel sheets in which retained austenite is dispersed in the microstructure are developed by a technique aimed for improving the formability of high strength steel sheets. For example, Patent Literature 1 discloses that a steel containing C: 0.04 to 0.12%, Si: 0.8 to 2.5%, and Mn: 0.5 to 2.0% is annealed and is held at 300 to 500°C for 10 to 900 seconds. This austempering (carbon partitioning by bainite transformation) gives rise to 2 to 10% retained γ , and the steel sheet that is obtained has high ductility with TS $\times$ EI $\geq$ 21000 MPa $\cdot$ % and a high stretch flange formability of 70% or more.

35 **[0005]** DP steels (dual phase steels) have been developed as steel sheets that have a low YR and excellent ductility and are effective in achieving small springback. General DP steels are multiphase steels in which martensite is dispersed in main phase ferrite microstructure. However, DP steels have a drawback in that stretch flange formability is poor and cracks occur easily due to stress concentration at interfaces between ferrite and martensite. Techniques for improving the stretch flange formability of DP steels are described in, for example, Patent Literature 2 and Patent Literature 3.

40 **[0006]** Patent Literature 2 discloses that ductility and stretch flange formability are improved by controlling the space factor of ferrite to 5 to 30% and the space factor of martensite to 50 to 95% relative to the whole microstructure, and by designing ferrite into fine particles with an average grain size of 3 μ m or less in terms of equivalent circular diameter and martensite into particles with an average grain size of 6 μ m or less in terms of equivalent circular diameter.

45 **[0007]** Furthermore, Patent Literature 3 discloses a technique that eliminates deterioration in stretch flange formability by controlling the space factor of ferrite to 50% or more and the space factor of martensite to 3 to 30% relative to the whole microstructure, and by controlling the average crystal grain size of ferrite to 10 μ m or less and the average crystal grain size of martensite to 5 μ m or less.

Citation List

50

Patent Literature

[0008]

55

PTL 1: Japanese Patent No. 5515623

PTL 2: Japanese Unexamined Patent Application Publication No. 2008-297609

PTL 3: Japanese Patent No. 3936440

Summary of Invention

Technical Problem

[0009] However, while Patent Literature 1 and Patent Literature 2 disclose methods for manufacturing a steel sheet with excellent ductility and stretch flange formability, the techniques require that soft ferrite phases be formed in a large amount and therefore encounter difficulties in increasing the tensile strength further to, for example, 780 MPa or more. Patent Literature 3 discloses a method for manufacturing a DP steel sheet with low YR and excellent ductility and stretch flange formability. However, steel sheets with a DP microstructure come to exhibit low ductility when their strength is increased, because the strengthening results in an increased area fraction of martensite microstructure. The manufacturing of difficult-to-form parts, such as center pillars, requires that ductility be exhibited at ridge portions that are bent. However, it has been shown that high-strength DP steel sheets are not necessarily satisfactory in ductility and are fractured when formed into such portions. Furthermore, these patent literatures do not disclose a technique that reduces variations in ductility and stretch flange formability in the width direction. Thus, the development is demanded of a high strength steel sheet that has low YR and excellent ductility and stretch flange formability from the point of view of press formability and also has excellent quality stability in the width direction from the point of view of material yield improvements.

[0010] In view of the circumstances discussed above, an object of the present invention is to provide a steel sheet that has a tensile strength (TS) of 780 MPa or more, excels in press formability, ductility, and stretch flange formability, and has excellent quality stability in the width direction. Another object of the present invention is to provide a related member and manufacturing methods.

[0011] Here, tensile strength means tensile strength (TS) obtained in accordance with JIS Z2241 (2011).

[0012] Excellent press formability means that the yield ratio YR obtained in accordance with JIS Z2241 (2011) is 0.8 or less.

[0013] Excellent ductility means that the total elongation EL obtained in accordance with JIS Z2241 (2011) satisfies any of (A) to (C) below.

(A) When TS is 780 MPa or more and less than 980 MPa, EL is 16.0% or more.

(B) When TS is 980 MPa or more and less than 1180 MPa, EL is 14.0% or more.

(C) When TS is 1180 MPa or more, EL is 12.0% or more.

[0014] Excellent stretch flange formability means that the hole expansion ratio λ (%) ($= \{(d - d_0)/d_0\} \times 100$) obtained by a hole expansion test in accordance with the provisions of JFST 1001 is 30% or more.

[0015] Excellent quality stability in the width direction means that when EL and λ are measured with respect to positions X along the width direction, the width of region A that continuously satisfies the following expressions (1) and (2) represents 80% or more of the total width of the sheet.

$$-10 \leq 100 \times [(EL (\%) \text{ at measurement position X within region A} - EL (\%) \text{ at center of sheet width})/EL (\%) \text{ at center of sheet width}] \leq 10 \quad (1)$$

$$-10 \leq 100 \times [(\lambda (\%) \text{ at measurement position X within region A} - \lambda (\%) \text{ at center of sheet width})/\lambda (\%) \text{ at center of sheet width}] \leq 10 \quad (2)$$

(In expressions (1) and (2), the measurement positions X are a total of 23 locations that divide the width W of the steel sheet into 24 portions (23 locations which occur when the width W is divided into 24 equal widths and at each of which adjacent widths are in contact with each other).

[0016] Specifically, the measurement positions X are a total of 23 locations along the width of the sheet that are indicated by $W/24$, $2W/24$, $3W/24$, $4W/24$, $5W/24$, $6W/24$, $7W/24$, $8W/24$, $9W/24$, $10W/24$, $11W/24$, $12W/24$, $13W/24$, $14W/24$, $15W/24$, $16W/24$, $17W/24$, $18W/24$, $19W/24$, $20W/24$, $21W/24$, $22W/24$, and $23W/24$.)

[0017] When, for example, the measurement positions X that continuously satisfy expressions (1) and (2) are $2W/24$ to $20W/24$, the width of region A that continuously satisfies expressions (1) and (2) is $100 \times (20 - 2 + 1)/23 = 83\%$ of the total width of the sheet.

Solution to Problem

[0018] In order to achieve the above objects, the present inventors carried out extensive studies on various steel sheets with a tensile strength of 780 MPa or more from the points of view of chemical composition, microstructures, and manufacturing conditions of the steel sheets to identify factors that would affect press formability, ductility, stretch flange

formability, and quality stability. As a result, the present inventors have found that a high strength cold rolled steel sheet that has excellent press formability, ductility, and stretch flange formability and excels in quality stability (has small variations in material quality) in the width direction can be obtained by designing the steel so that it contains, in mass%, C: 0.05 to 0.20%, Si: 0.40 to 1.50%, Mn: 1.9 to 3.5%, P: 0.02% or less, S: 0.01% or less, sol. Al: 1.00% or less, and N: less than 0.015%, and by designing the steel microstructure so that the area fraction of polygonal ferrite is 10% or more and 80% or less, the total area fraction of upper bainite, tempered martensite, and lower bainite is 10% or more and 70% or less, the area fraction of retained austenite (retained γ) is 3% or more and 15% or less, and the area fraction of quenched martensite is 15% or less (including 0%), and further so that the total area fraction (space factor) of quenched martensite and retained γ each having an aspect ratio of 3 or less and an equivalent circular diameter of 2.0 μm or more is 20% or less relative to the total area of quenched martensite and retained γ , and the area fraction of C-enriched regions with a C concentration of 0.5 mass% or more ($S_{c \geq 0.5}$) is 20% or less relative to the entire microstructure.

[0019] The present invention has been made based on the above findings. A gist of the present invention is as follows.

[1] A steel sheet having a chemical composition including, in mass%,

C: 0.05 to 0.20%,
Si: 0.40 to 1.50%,
Mn: 1.9 to 3.5%,
P: 0.02% or less,
S: 0.01% or less,
sol. Al: 1.00% or less, and
N: less than 0.015%,
the balance being iron and incidental impurities,
the steel sheet including a steel microstructure in which:

the area fraction of polygonal ferrite is 10% or more and 80% or less,
the total area fraction of upper bainite, tempered martensite, and lower bainite is 10% or more and 70% or less,
the volume fraction of retained austenite is 3% or more and 15% or less,
the area fraction of quenched martensite is 15% or less (including 0%), and
the steel microstructure further includes a remaining microstructure,
the steel sheet being such that:

the total area fraction of quenched martensite and retained austenite each having an aspect ratio of 3 or less and an equivalent circular diameter of 2.0 μm or more is 20% or less relative to the total area fraction of quenched martensite and retained austenite, and
the area fraction of a C-enriched region with a C concentration of 0.5 mass% or more ($S_{c \geq 0.5}$) is 20% or less relative to the entire microstructure.

[2] The steel sheet according to [1], wherein the chemical composition further includes, in mass%, one or two selected from:

Ti: 0.1% or less, and
B: 0.01% or less.

[3] The steel sheet according to [1] or [2], wherein the chemical composition further includes, in mass%, one, or two or more selected from:

Cu: 1% or less,
Ni: 1% or less,
Cr: 1% or less,
Mo: 0.5% or less,
V: 0.5% or less, and
Nb: 0.1% or less.

[4] The steel sheet according to any one of [1] to [3], wherein the chemical composition further includes, in mass%, one, or two or more selected from:

Mg: 0.0050% or less,
 Ca: 0.0050% or less,
 Sn: 0.1% or less,
 Sb: 0.1% or less, and
 REM: 0.0050% or less.

[5] The steel sheet according to any one of [1] to [4], which has a galvanized layer on a surface.

[6] A member obtained using the steel sheet described in any one of [1] to [5].

[7] A method for manufacturing a steel sheet, including hot rolling, pickling, and cold rolling a steel slab having the chemical composition described in any one of [1] to [4], and annealing the resultant cold rolled steel sheet, the annealing including:

a holding step of heating the cold rolled steel sheet to an annealing temperature of 750 to 880°C and holding the cold rolled steel sheet at the annealing temperature for 10 to 500 seconds;

a first cooling step of cooling the steel sheet to a first cooling stop temperature of 350 to 550°C at a first average cooling rate in a range of temperatures from the annealing temperature to the first cooling stop temperature of 2 to 50°C/s;

a second cooling step of causing the steel sheet to reside at a residence temperature of 350 to 550°C for 10 seconds or more and 60 seconds or less and cooling the steel sheet to a second cooling stop temperature of 150 to 360°C at a second average cooling rate of 3 to 50°C/s; and

a third cooling step of cooling the steel sheet at a third average cooling rate in a range of temperatures from the second cooling stop temperature to 50°C of 0.05 to 1.0°C/s.

[8] The method for manufacturing a steel sheet according to [7], wherein the second cooling step causes the steel sheet to reside at a residence temperature of 350 to 550°C for 10 seconds or more and 60 seconds or less while performing a hot-dip galvanizing treatment or a hot-dip galvannealing treatment on a surface of the steel sheet.

[9] The method for manufacturing a steel sheet according to [7], further including performing an electrogalvanizing treatment on a surface of the steel sheet after the annealing.

[10] A method for manufacturing a member, including a step of subjecting the steel sheet described in any one of [1] to [5] to at least one working of forming or joining to produce a member.

Advantageous Effects of Invention

[0020] According to the present invention, a steel sheet can be obtained that has high strength with a tensile strength TS of 780 MPa or more, has excellent press formability, ductility, and stretch flange formability, and has excellent quality stability in the width direction.

[0021] The steel sheets of the present invention are applicable to frame members of automobile bodies. In this case, difficult-to-form members with a complex shape can be manufactured by cold pressing, and a significant contribution can be made to reducing the weight of automobile bodies. Furthermore, the steel sheets have small variations in quality in the width direction. Thus, the blanking positions on the steel sheets are not limited, and the material yield can be markedly improved.

Description of Embodiments

[0022] The present invention will be described in detail below. The present invention is not limited to the following embodiments.

[0023] A steel sheet of the present invention has a chemical composition including, in mass%, C: 0.05 to 0.20%, Si: 0.40 to 1.50%, Mn: 1.9 to 3.5%, P: 0.02% or less, S: 0.01% or less, sol. Al: 1.00% or less, and N: less than 0.015%, the balance being iron and incidental impurities. The steel sheet includes a steel microstructure in which the area fraction of polygonal ferrite is 10% or more and 80% or less, the total area fraction of upper bainite, tempered martensite, and lower bainite is 10% or more and 70% or less, the volume fraction of retained austenite is 3% or more and 15% or less, the area fraction of quenched martensite is 15% or less (including 0%), and the steel microstructure further includes a remaining microstructure. The steel sheet is such that the total area fraction of quenched martensite and retained austenite each having an aspect ratio of 3 or less and an equivalent circular diameter of 2.0 μm or more is 20% or less relative to the total area fraction of quenched martensite and retained austenite, and the area fraction of a C-enriched region with a C concentration of 0.5 mass% or more ($S_{C \geq 0.5}$) is 20% or less relative to the entire microstructure.

[0024] The steel sheet of the present invention will be described below in the order of its chemical composition and its steel microstructure. First, the reasons as to why the chemical composition of the present invention is thus limited will be

described. In the following description, references to % in the steel composition indicate mass% unless otherwise specified.

<C: 0.05 to 0.20%>

[0025] Carbon is added in order to ensure predetermined strength through transformation strengthening, and to enhance ductility by ensuring a predetermined amount of retained austenite (retained γ). When the C content is less than 0.05%, these effects cannot be ensured sufficiently. When, on the other hand, the C content is more than 0.20%, the martensite start temperature (the M_s temperature) is lowered. As a result, martensite transformation and subsequent martensite tempering do not occur sufficiently in the third cooling step in which the steel sheet is cooled at a third average cooling rate of 0.05 to 1.0°C/s in a range of temperatures from the second cooling stop temperature to 50°C. This promotes the formation of quenched martensite and C-enriched regions with 0.5 mass% or more carbon concentration ($S_{c \geq 0.5}$), resulting in deterioration in stretch flange formability and quality stability in the width direction.

[0026] Thus, the C content is limited to 0.05% or more and 0.20% or less. The C content is preferably 0.08% or more. Furthermore, the C content is preferably 0.18% or less.

<Si: 0.40 to 1.50%>

[0027] Silicon is added in order to offer high strength by strengthening ferrite and to enhance ductility by suppressing the formation of carbides in martensite and bainite and thereby ensuring a predetermined amount of retained γ . When the Si content is less than 0.40%, these effects cannot be ensured sufficiently.

[0028] When, on the other hand, the Si content is more than 1.50%, carbon is partitioned to non-transformed austenite in an excessively promoted manner to increase the formation of C-enriched regions with 0.5 mass% or more carbon concentration ($S_{c \geq 0.5}$), thus causing deterioration in stretch flange formability and quality stability in the width direction.

Thus, the Si content is limited to 0.40% or more and 1.50% or less. The Si content is preferably 0.60% or more.

[0029] Furthermore, the Si content is preferably 1.20% or less.

<Mn: 1.9 to 3.5%>

[0030] Manganese is added in order to enhance the hardenability of the steel sheet so that the strength will be increased in a promoted manner through transformation strengthening, and also in order to enhance ductility by, similarly to silicon, suppressing the formation of carbides in bainite and thereby promoting the occurrence of retained austenite that contributes to ductility. In order to obtain these effects, the Mn content needs to be 1.9% or more. When, on the other hand, the Mn content is more than 3.5%, bainite transformation is significantly delayed and a predetermined amount of retained austenite cannot be ensured, with the result that ductility is lowered.

[0031] When the Mn content is more than 3.5%, furthermore, it is difficult to suppress the formation of coarse quenched martensite, and stretch flange formability is deteriorated. Thus, the Mn content is limited to 1.9% or more and 3.5% or less. The Mn content is preferably 2.1% or more. Furthermore, the Mn content is preferably 3.3% or less.

<P: 0.02% or less>

[0032] Phosphorus is an element that strengthens steel, but much phosphorus deteriorates spot weldability. Thus, the P content is limited to 0.02% or less and is preferably 0.01% or less. The P content may be nil. Dephosphorization to less than 0.001% entails a significant cost. Thus, the P content is preferably 0.001% or more.

<S: 0.01% or less>

[0033] Sulfur is an element that is effective in improving scale exfoliation in hot rolling and effective in suppressing nitridation during annealing, but sulfur adversely affects spot weldability, bendability, and stretch flangeability. To reduce these adverse effects, the S content is at least limited to 0.01% or less, and is preferably 0.0020% or less.

[0034] The S content may be nil. Desulfurization to less than 0.0001% entails a significant cost. From the point of view of manufacturing costs, the S content is preferably 0.0001% or more. The S content is more preferably 0.0005% or more, and even more preferably 0.0015% or more.

<sol. Al: 1.00% or less>

[0035] Aluminum is added for the purpose of deoxidization or obtaining retained γ . The lower limit of sol. Al is not particularly limited. For stable deoxidization, however, the sol. Al content is preferably 0.005% or more. The sol. Al content

is more preferably 0.010% or more, and even more preferably 0.020% or more.

[0036] When, on the other hand, the sol. Al content is more than 1.00%, Al-containing coarse inclusions are formed in large amounts to cause a decrease in stretch flange formability. Thus, the sol. Al content is limited to 1.00% or less.

<N: less than 0.015%>

[0037] Nitrogen is an element that forms nitrides, such as BN, AlN, and TiN, in steel, and lowers stretch flange formability. The content thereof should be limited. The N content is thus limited to less than 0.015%. The N content is preferably 0.010% or less, and more preferably 0.005% or less.

[0038] The N content may be nil. Denitrification to less than 0.0001% entails a significant cost. From the point of view of manufacturing costs, the N content is preferably 0.0001% or more. The N content is more preferably 0.0010% or more, and even more preferably 0.0020% or more.

[0039] The chemical composition of the steel sheet in the present invention includes the above elements as the basic components, and the balance includes iron (Fe) and incidental impurities. In the chemical composition of the steel sheet in the present invention, it is preferable that the balance consist of Fe and incidental impurities.

[0040] In addition to the components described above, the chemical composition of the steel sheet of the present invention may appropriately contain one, or two or more optional elements selected from the following (A) to (C).

(A) One or two selected from Ti: 0.1% or less, and B: 0.01% or less.

(B) One, or two or more selected from Cu: 1% or less, Ni: 1% or less, Cr: 1% or less, Mo: 0.5% or less, V: 0.5% or less, and Nb: 0.1% or less.

(C) One, or two or more selected from Mg: 0.0050% or less, Ca: 0.0050% or less, Sn: 0.1% or less, Sb: 0.1% or less, and REM: 0.0050% or less.

<Ti: 0.1% or less>

[0041] Titanium fixes nitrogen in steel as TiN to produce an effect of enhancing hot ductility and an effect of allowing boron to produce its effect of enhancing hardenability. Furthermore, titanium has an effect of reducing the size of the microstructure through TiC precipitation. In order to obtain these effects, the Ti content is desirably 0.002% or more. In order to fix nitrogen sufficiently, the Ti content is more preferably 0.008% or more. The Ti content is even more preferably 0.010% or more.

[0042] On the other hand, more than 0.1% titanium causes an increase in rolling load and a decrease in ductility by an increased amount of precipitation strengthening. Thus, when titanium is added, the Ti content is limited to 0.1% or less. The Ti content is preferably 0.05% or less, and more preferably 0.03% or less.

<B: 0.01% or less>

[0043] Boron is an element that enhances the hardenability of steel and advantageously facilitates the formation of a predetermined area fraction of tempered martensite and/or bainite. Thus, the B content is preferably 0.0005% or more. The B content is more preferably 0.0010% or more.

[0044] When, on the other hand, the B content is more than 0.01%, the effects are saturated, and further hot ductility is significantly lowered to invite surface defects. Thus, when boron is added, the B content is limited to 0.01% or less. The B content is preferably 0.005% or less, and more preferably 0.003% or less.

<Cu: 1% or less>

[0045] Copper enhances the corrosion resistance in automobile use environments. Furthermore, corrosion products of copper cover the surface of the steel sheet and effectively suppress penetration of hydrogen into the steel sheet. Copper is an element that is mixed when scraps are used as raw materials. By accepting copper contamination, recycled materials can be used as raw materials and thereby manufacturing costs can be reduced. From these points of view, the Cu content is preferably 0.005% or more, and, further from the point of view of enhancing delayed fracture resistance, the Cu content is more preferably 0.05% or more. The Cu content is even more preferably 0.10% or more. The Cu content is further preferably 0.25% or more, and even further preferably 0.50% or more.

[0046] However, too much copper invites surface defects. Thus, when copper is added, the Cu content is limited to 1% or less.

<Ni: 1% or less>

[0047] Similarly to copper, nickel is an element that enhances corrosion resistance. Furthermore, nickel eliminates or reduces the occurrence of surface defects that tend to occur when the steel contains copper. Thus, it is desirable to add 0.01% or more nickel. The Ni content is more preferably 0.04% or more, and even more preferably 0.06% or more. However, adding too much nickel can instead cause surface defects because scales are formed nonuniformly in a heating furnace, and also increases the cost. Thus, when nickel is added, the Ni content is limited to 1% or less. The Ni content is preferably 0.5% or less, and more preferably 0.3% or less.

<Cr: 1% or less>

[0048] Chromium may be added to produce an effect of enhancing the hardenability of steel and an effect of suppressing the formation of carbides in martensite and upper/lower bainite. In order to obtain these effects, the Cr content is preferably 0.01% or more. The Cr content is more preferably 0.03% or more, and even more preferably 0.06% or more. However, too much chromium deteriorates pitting corrosion resistance. Thus, when chromium is added, the Cr content is limited to 1% or less.

<Mo: 0.5% or less>

[0049] Molybdenum may be added to produce an effect of enhancing the hardenability of steel and an effect of suppressing the formation of carbides in martensite and upper/lower bainite. In order to obtain these effects, the Mo content is preferably 0.01% or more. The Mo content is more preferably 0.03% or more, and even more preferably 0.06% or more. The Mo content is further preferably 0.1% or more, and even further preferably 0.2% or more.

[0050] However, molybdenum significantly deteriorates the chemical convertibility of the cold rolled steel sheet. Thus, when molybdenum is added, the Mo content is limited to 0.5% or less.

<V: 0.5% or less>

[0051] Vanadium may be added to produce an effect of enhancing the hardenability of steel, an effect of suppressing the formation of carbides in martensite and upper/lower bainite, an effect of reducing the size of the microstructure, and an effect of improving delayed fracture resistance through the precipitation of carbide. In order to obtain these effects, the V content is preferably 0.003% or more. The V content is more preferably 0.005% or more, and even more preferably 0.010% or more. The V content is further preferably 0.020% or more, and even further preferably 0.050% or more. However, much vanadium significantly deteriorates castability. Thus, when vanadium is added, the V content is limited to 0.5% or less. The V content is preferably 0.3% or less, and more preferably 0.2% or less.

<Nb: 0.1% or less>

[0052] Niobium may be added to produce an effect of reducing the size of the steel microstructure and thereby increasing the strength, and, through grain size reduction, an effect of promoting bainite transformation, an effect of improving bendability, and an effect of enhancing delayed fracture resistance. In order to obtain these effects, the Nb content is preferably 0.002% or more. The Nb content is more preferably 0.004% or more, and even more preferably 0.010% or more.

[0053] However, adding much niobium results in excessive precipitation strengthening and low ductility. Furthermore, the rolling load is increased and castability is deteriorated. Thus, when niobium is added, the Nb content is limited to 0.1% or less. The Nb content is preferably 0.05% or less, and more preferably 0.03% or less.

<Mg: 0.0050% or less>

[0054] Magnesium fixes oxygen as MgO and contributes to improving formability, such as bendability. Thus, the Mg content is preferably 0.0002% or more. The Mg content is more preferably 0.0004% or more, and even more preferably 0.0006% or more.

[0055] On the other hand, much magnesium deteriorates surface quality and bendability. Thus, when magnesium is added, the Mg content is limited to 0.0050% or less. The Mg content is preferably 0.0040% or less.

<Ca: 0.0050% or less>

[0056] Calcium fixes sulfur as CaS and contributes to improvements in bendability and delayed fracture resistance.

Thus, the Ca content is preferably 0.0002% or more. The Ca content is more preferably 0.0005% or more, and even more preferably 0.0010% or more.

[0057] On the other hand, much calcium deteriorates surface quality and bendability. Thus, when calcium is added, the Ca content is limited to 0.0050% or less. The Ca content is preferably 0.0040% or less.

<Sn: 0.1% or less>

[0058] Tin suppresses oxidation and nitridation of a surface layer portion of the steel sheet and thereby eliminates or reduces the consequent loss of the C and B contents in the surface layer portion. These effects lead to suppressed formation of ferrite in the surface layer portion of the steel sheet, thus increasing strength and improving fatigue resistance. From these points of view, the Sn content is preferably 0.002% or more. The Sn content is more preferably 0.004% or more, and even more preferably 0.006% or more. The Sn content is further preferably 0.008% or more, and even further preferably 0.010% or more. The Sn content is preferably 0.030% or more, and more preferably 0.060% or more.

[0059] When, on the other hand, the Sn content is more than 0.1%, castability is deteriorated. Furthermore, tin is segregated at prior γ grain boundaries to deteriorate delayed fracture resistance. Thus, when tin is added, the Sn content is limited to 0.1% or less.

<Sb: 0.1% or less>

[0060] Antimony suppresses oxidation and nitridation of a surface layer portion of the steel sheet and thereby eliminates or reduces the consequent loss of the C and B contents in the surface layer portion. These effects lead to suppressed formation of ferrite in the surface layer portion of the steel sheet, thus increasing strength and improving fatigue resistance. From these points of view, the Sb content is preferably 0.002% or more. The Sb content is more preferably 0.004% or more, and even more preferably 0.006% or more. The Sb content is further preferably 0.008% or more, and even further preferably 0.010% or more. The Sb content is preferably 0.025% or more, and more preferably 0.050% or more.

[0061] When, on the other hand, the Sb content is more than 0.1%, castability is deteriorated and segregation occurs at prior γ grain boundaries to deteriorate delayed fracture resistance. Thus, when antimony is added, the Sb content is limited to 0.1% or less.

<REM: 0.0050% or less>

[0062] Rare earth metals are elements that spheroidize the shape of sulfides and thereby eliminate or reduce adverse effects of sulfides on stretch flange formability, thus improving stretch flange formability. In order to obtain this effect, the REM content is preferably 0.0005% or more. The REM content is more preferably 0.0010% or more, and even more preferably 0.0020% or more.

[0063] When, on the other hand, the REM content is more than 0.0050%, the effect of improving stretch flange formability is saturated. Thus, when rare earth metals are added, the REM content is limited to 0.0050% or less.

[0064] In the present invention, the rare earth metals indicate scandium (Sc) with atomic number 21, yttrium (Y) with atomic number 39, and lanthanoid elements from lanthanum (La) with atomic number 57 to lutetium (Lu) with atomic number 71. The REM concentration in the present invention is the total content of one, or two or more elements selected from the above rare earth metals.

[0065] The steel sheet preferably contains, but not limited to, Sc, Y, Ce, and La as the rare earth metals.

[0066] When the content of any of the above optional components is below the lower limit, the optional element present below the lower limit does not impair the advantageous effects of the present invention. Thus, such an optional element below the lower limit content is regarded as an incidental impurity.

[0067] Next, mechanical properties of the steel sheet of interest in the present invention (the cold rolled steel sheet with excellent quality stability) will be described.

[0068] The steel sheet of the present invention has a tensile strength (TS) of 780 MPa or more. The upper limit of the tensile strength is not particularly limited. From the point of view of the balance with other characteristics, the tensile strength is preferably 1300 MPa or less.

[0069] In the steel sheet of the present invention, significantly enhanced press forming stability is obtained by ensuring a total elongation EL of 16.0% or more when TS is 780 MPa or more, by ensuring a total elongation EL of 14.0% or more when TS is 980 MPa or more, or by ensuring a total elongation EL of 12.0% or more when TS is 1180 MPa or more.

[0070] Ensuring a hole expansion ratio λ of 30% or more makes it possible to suppress the occurrence of cracking at the time of press forming. Thus, λ is 30% or more.

[0071] When EL and λ are measured on the steel sheet of the present invention with respect to positions X along the width direction, the width of region A that continuously satisfies the following expressions (1) and (2) represents 80% or more of the total width of the sheet.

$$-10 \leq 100 \times [(EL (\%) \text{ at measurement position X within region A} - EL (\%) \text{ at center of sheet width})/EL (\%) \text{ at center of sheet width}] \leq 10 \quad (1)$$

$$-10 \leq 100 \times [(A (\%) \text{ at measurement position X within region A} - \lambda (\%) \text{ at center of sheet width})/\lambda (\%) \text{ at center of sheet width}] \leq 10 \quad (2)$$

[0072] In expressions (1) and (2), the measurement positions X are a total of 23 locations that divide the width W of the steel sheet into 24 portions (23 locations which occur when the width W is divided into 24 equal widths and at each of which adjacent widths are in contact with each other).

[0073] Specifically, the measurement positions X are a total of 23 locations along the width of the sheet that are indicated by W/24, 2W/24, 3W/24, 4W/24, 5W/24, 6W/24, 7W/24, 8W/24, 9W/24, 10W/24, 11W/24, 12W/24, 13W/24, 14W/24, 15W/24, 16W/24, 17W/24, 18W/24, 19W/24, 20W/24, 21W/24, 22W/24, and 23W/24.

[0074] When, for example, the measurement positions X that continuously satisfy expressions (1) and (2) are 2W/24 to 20W/24, the width of region A that continuously satisfies expressions (1) and (2) is $100 \times (20 - 2 + 1)/23 = 83\%$ of the total width of the sheet.

[0075] In the steel sheet of the present invention, the region A has a length in the width direction that is 80% or more of the total width of the sheet.

[0076] That is, in the region that represents 80% or more of the region over the total width of the sheet, the deviations of EL in the width direction are 10% or less relative to the value measured with respect to the center of the sheet width, and the deviations of λ in the width direction are 10% or less relative to the value measured with respect to the center of the sheet width. Unsteadiness may be present in the range of up to 20% combining both sides in the width direction.

[0077] The end portions of the steel sheet are brought into contact with other structures during the transportation of the steel sheet and the process of operation. Thus, the end portions are excluded from use in order to ensure quality. Therefore, the effective width of the sheet that can be used does not reach 100%. Thus, the effective width of the sheet is preferably less than 100%.

[0078] Because a region with the deviation of EL in the width direction is 10% or less relative to the value measured at the center of the sheet width and the deviation of λ is 10% or less is within a region that represents 80% or more of the total width of the sheet, the yield can be significantly improved. Thus, in the present invention, the region where the deviation of EL in the width direction is 10% or less relative to the value measured at the center of the sheet width and the deviation of λ is 10% or less is limited to 80% or more of the region over the total width of the sheet. The proportion is preferably 85% or more.

[0079]

<YR $\leq$ 0.8, TS $\geq$ 780 MPa, EL $\geq$ 16.0%>

<YR $\leq$ 0.8, TS $\geq$ 980 MPa, EL $\geq$ 14.0%>

<YR $\leq$ 0.8, TS $\geq$ 1180 MPa, EL $\geq$ 12.0%>

[0080] Tensile properties are evaluated by a tensile test (in accordance with JIS Z2241 (2011)) with respect to JIS No. 5 test pieces for tensile test sampled from the center of the sheet width. N = 3. Each of the properties is evaluated based on the average of the three test pieces. The steel sheet is evaluated as being of high strength when the tensile strength is 780 MPa or more. The steel sheet is evaluated as excellent in press formability when the yield ratio YR is 0.8 or less. The steel sheet is evaluated as excellent in ductility when TS is 780 MPa or more and the total elongation EL is 16.0% or more, when TS is 980 MPa or more and the total elongation EL is 14.0% or more, or when TS is 1180 MPa or more and the total elongation EL is 12.0% or more.

< $\lambda \geq 30\%$ >

[0081] Stretch flange formability is evaluated by a hole expansion test conforming to the provisions of The Japan Iron and Steel Federation Standard JFST 1001 with respect to test specimens sampled from the center of the sheet width. N = 3. Specifically, a 100 mm $\times$ 100 mm square sample is punched with a punching tool having a punch diameter of 10 mm and a clearance of 13%, and a conical punch having an apex angle of 60 degrees is inserted into the hole in such a manner that the burr produced at the time of punching will be directed to the outside. The hole is expanded until the sheet is cracked through the thickness. The hole expansion ratio λ (%) = $\{(d - d_0)/d_0\} \times 100$ is calculated where d_0 : initial hole diameter (mm), and d: hole diameter (mm) at the occurrence of cracking. The values of λ measured of the three test specimens are averaged. The steel is evaluated as excellent in hole expandability and stretch flangeability when λ is 30% or more. λ is preferably 40% or more.

<Evaluation of quality stability in the width direction>

[0082] To evaluate the quality stability in the width direction, 23 evaluation pieces (23 pieces including a piece located at the center of the sheet width) are sampled at intervals of 100 mm or less from the center of the sheet width (the position 12W/24 described hereinabove) toward both ends in the width direction, and EL and λ at each of the positions (measurement positions X) are determined. The difference between the values measured at the center of the sheet width and at each measurement position is expressed as a ratio to the value measured at the center of the sheet width, and thereby the quality stability in the width direction is evaluated. The group of continuous measurements where the differences in EL and λ are each 10% or less relative to EL and λ at the center of the sheet width is obtained as the region with 10% or less differences in EL and λ . The steel is evaluated as excellent in quality stability when this region represents 80% or more of the total width of the sheet.

[0083] Incidentally, the width of the steel sheet in the present invention is preferably 600 mm or more. The width of the steel sheet in the present invention is preferably 1700 mm or less.

[0084] Next, the steel microstructure of the steel sheet of the present invention will be described.

<Area fraction of polygonal ferrite: 10% or more and 80% or less>

[0085] In order to ensure low YR and high ductility, the area fraction of polygonal ferrite is limited to 10% or more. In order to obtain higher ductility, the area fraction of polygonal ferrite is preferably 20% or more.

[0086] When, on the other hand, polygonal ferrite represents more than 80%, the desired strength cannot be obtained. Thus, the area fraction of polygonal ferrite is limited to 80% or less, and is preferably 75% or less, and more preferably 70% or less.

<Total area fraction of upper bainite, tempered martensite, and lower bainite: 10% or more and 70% or less>

[0087] In order to obtain the desired strength, the total area fraction of upper bainite, tempered martensite, and lower bainite is limited to 10% or more. In order to obtain higher strength, the total area fraction is preferably 15% or more.

[0088] When, however, the total area fraction of upper bainite, tempered martensite, and lower bainite is more than 70%, the steel sheet is excessively strengthened and is lowered in ductility. Thus, the area fraction is limited to 70% or less, and is more preferably 65% or less, and even more preferably 60% or less.

<Volume fraction of retained austenite (retained γ): 3% or more and 15% or less>

[0089] When the volume fraction of retained austenite is less than 3%, the desired ductility cannot be ensured.

[0090] From the point of view of ductility, the volume fraction of retained austenite is limited to 3% or more, and is preferably 5% or more. When, on the other hand, retained austenite represents more than 15%, stretch flange formability is deteriorated. Thus, retained austenite is limited to 15% or less, and is more preferably 13% or less.

<Area fraction of quenched martensite: 15% or less (including 0%) >

[0091] Quenched martensite microstructure is hard and lowers λ , and therefore the area fraction thereof should be low. In order to obtain the desired λ , the area fraction of quenched martensite is limited to 15% or less. In order to obtain λ more stably, the area fraction of quenched martensite is preferably 12% or less, and more preferably 10% or less.

<Remaining microstructures>

[0092] The balance of the steel microstructure after the above microstructures is remaining microstructures. The area fraction of the remaining microstructures is preferably 5% or less. The remaining microstructures may be carbides and pearlite. These microstructures may be identified by SEM observation as will be described later.

<Total area fraction of quenched martensite and retained austenite each having an aspect ratio of 3 or less and an equivalent circular diameter of 2.0 μm or more: 20% or less relative to the total area fraction of quenched martensite and retained austenite>

[0093] Retained austenite is transformed into hard martensite microstructure by the TRIP effect induced by, for example, press forming or tensile working. In the present invention, quenched martensite and retained austenite are controlled together from the point of view of stretch flangeability. Quenched martensite or retained austenite with an equivalent circular diameter of 2.0 μm or more forms voids at interfaces with other microstructures upon stress concentration and

thereby may deteriorate stretch flange formability.

[0094] When the aspect ratio of quenched martensite or retained austenite is 3 or less, stress concentration tends to occur at interfaces with other microstructures. This promotes void formation and may result in deterioration in stretch flange formability. Thus, the total area fraction of quenched martensite and retained austenite each having an aspect ratio of 3 or less and an equivalent circular diameter of 2.0 μm or more is limited to 20% or less relative to the total area fraction of quenched martensite and retained austenite. The total area fraction is preferably 18% or less, and more preferably 16% or less. There is no lower limit for the total area fraction of quenched martensite and retained austenite each having an aspect ratio of 3 or less and an equivalent circular diameter of 2.0 μm or more relative to the total area fraction of quenched martensite and retained austenite. Because controlling the total area fraction to 0% is difficult for operation reasons, the total area fraction is preferably 2% or more, and more preferably 4% or more. The equivalent circular diameter is preferably 20.0 μm or less.

<Area fraction of C-enriched regions with a C concentration of 0.5 mass% or more ($S_{c \geq 0.5}$): 20% or less relative to the entire microstructure>

[0095] The hardness of quenched martensite is determined by the amount of carbon dissolved in the quenched martensite. A large difference in hardness between quenched martensite and other microstructures promotes the formation of voids at their interfaces upon stress concentration. Microstructures containing a large amount of solute carbon are quenched martensite and retained austenite. Retained austenite is a microstructure that contributes to high ductility, and has a C concentration of 0.5 mass% or more. When the area fraction of microstructures with a C concentration of 0.5 mass% or more is 20% or less relative to all the constituent microstructures, stretch flange formability can be ensured while ductility is enhanced; furthermore, variations in quality in the width direction can also be reduced, and steel sheets with excellent quality stability can be manufactured. Thus, the area fraction (the space factor) of C-enriched regions with a C concentration of 0.5 mass% or more ($S_{c \geq 0.5}$) is limited to 20% or less. The area fraction is preferably 15% or less, and more preferably 12% or less. The area fraction is preferably 3% or more, and more preferably 5% or more.

[0096] Next, a method for measuring the steel microstructure will be described.

[0097] To measure the area fractions of polygonal ferrite, upper bainite, tempered martensite, lower bainite, and quenched martensite (fresh martensite), the steel sheet is cut to expose a through-thickness cross section that is parallel to the rolling direction. The cross section is mirror-polished and is etched with 1 vol% Nital. Portions at 1/4 thickness are observed with SEM in 10 fields of view at a magnification of 5000 times. The microstructure images obtained are analyzed to quantify the microstructures. Polygonal ferrite discussed here is relatively equiaxed ferrite containing almost no internal carbides. This region looks blackest in SEM.

[0098] Upper bainite is a ferrite microstructure containing internal carbides that looks white in SEM or retained austenite. When it is difficult to distinguish between upper bainite and polygonal ferrite, the area fractions are calculated assuming that ferrite regions with an aspect ratio ≤ 2.0 are polygonal ferrite and regions with an aspect ratio > 2.0 are upper bainite. Here, the aspect ratio is determined by a/b where a is the length of the major axis that gives the longest particle length, and b is the length of the minor axis that cuts across the particle with the longest length in the direction perpendicular to the major axis.

[0099] Tempered martensite and lower bainite are regions that contain lath-like submicrostructures and carbide precipitates according to SEM.

[0100] Quenched martensite (fresh martensite) is massive regions that look white and do not contain any visible submicrostructures according to SEM.

[0101] The remaining microstructures are carbide and/or pearlite microstructures and can be identified as white contrast according to SEM. These microstructures can be distinguished based on the fact that carbides are microstructures with a particle size of 1 μm or less and pearlite is lamellar (layered) microstructures.

[0102] The quantitative evaluation of the microstructures described above, and the measurements of the aspect ratio and the equivalent circular diameter of quenched martensite and retained austenite may be performed using an image analysis software, for example, Image J (Fiji).

[0103] The steel sheet is cut to expose a through-thickness cross section that is parallel to the rolling direction. The cross section is mirror-polished and is etched with 1 vol% Nital. Portions at 1/4 thickness are observed with SEM in 10 fields of view at a magnification of 5000 times. The microstructures are identified and quantified by the Trainable Weka segmentation method of Image J (Fiji) that is capable of segmentation by machine learning. Furthermore, the aspect ratio and the equivalent circular diameter of quenched martensite and retained austenite may be measured using a particle analysis program that is another function of Image J. Quenched martensite and retained austenite identified as described above are exclusively extracted and analyzed.

[0104] The volume fraction of retained austenite is determined by chemically polishing the steel sheet to a location at 1/4 thickness from the surface and analyzing the cross section by X-ray diffractometry. Co-K α radiation source is used as the incident X-ray, and the volume fraction of retained austenite is calculated from the intensity ratio of (200), (211), and (220)

planes of ferrite and (200), (220), and (311) planes of austenite. Because retained austenite is randomly distributed, the volume fraction of retained austenite obtained by X-ray diffractometry may be regarded as the area fraction of retained austenite.

[0105] The area fraction $S_{C \geq 0.5}$ of C-enriched regions with a C concentration of 0.5 mass% or more is measured by mapping analysis of the C concentration distribution with respect to positions at 1/4 thickness of a through-thickness cross section parallel to the rolling direction, using field emission electron probe microanalyzer (FE-EPMA) JXA-8500F manufactured by JEOL Ltd., at an acceleration voltage of 6 kV and an illumination current of 7×10^{-8} A with the minimum beam diameter. The area fraction of regions where the C concentration is 0.5 mass% or more is thus calculated. In order to eliminate the influence of contamination, the background is subtracted so that the average value of carbon obtained by the analysis will be equal to the amount of carbon in the base material. Specifically, when the average of the measured amounts of carbon is greater than the amount of carbon in the base material, the excess is understood as contamination, and the excess is subtracted from each of the values analyzed at the respective positions. The values thus obtained are taken as the true amounts of carbon at the respective positions.

[0106] Next, a method for manufacturing a steel sheet of the present invention will be described.

[0107] A method for manufacturing a steel sheet of the present invention includes hot rolling, pickling, and cold rolling a steel slab having the chemical composition described hereinabove, and annealing the resultant cold rolled steel sheet. The annealing includes a holding step of heating the cold rolled steel sheet to an annealing temperature of 750 to 880°C and holding the cold rolled steel sheet at the annealing temperature for 10 to 500 seconds; a first cooling step of cooling the steel sheet to a first cooling stop temperature of 350 to 550°C at a first average cooling rate in a range of temperatures from the annealing temperature to the first cooling stop temperature of 2 to 50°C/s; a second cooling step of causing the steel sheet to reside at a residence temperature of 350 to 550°C for 10 seconds or more and 60 seconds or less and cooling the steel sheet to a second cooling stop temperature of 150 to 360°C at a second average cooling rate of 3 to 50°C/s; and a third cooling step of cooling the steel sheet at a third average cooling rate in a range of temperatures from the second cooling stop temperature to 50°C of 0.05 to 1.0°C/s.

<Hot rolling>

[0108] For example, the steel slab may be hot rolled in such a manner that the slab is heated and then rolled, that the slab from continuous casting is subjected to hot direct rolling without heating, or that the slab from continuous casting is quickly heat-treated and then rolled. The hot rolling may be performed in accordance with a conventional procedure. For example, the slab heating temperature may be 1100 to 1300°C; the soaking time may be 20 to 300 minutes; the finish rolling temperature may be A_{r3} transformation temperature to A_{r3} transformation temperature + 200°C; and the coiling temperature may be 400 to 720°C. In order to eliminate or reduce thickness variations and to ensure high strength stably, the coiling temperature is preferably 430 to 530°C.

[0109] The A_{r3} transformation temperature may be calculated from the composition of the steel sheet and the following empirical formula (A).

$$A_{r3} = 910 - 203 \times [C] + 44.7 \times [Mn] - 30 \times [Si] + 700 \times [P] + 400 \times [\text{sol. Al}] - 20 \times [B] + 31.5 \times [Mo] + 104 \times [V] + 400 \times [Ti] \quad (A)$$

[0110] In formula (A), [element] means the content (mass%) of the element. (When the element is absent, the content is 0 (zero) mass%.)

<Pickling>

[0111] Pickling may be performed in a conventional manner.

<Cold rolling>

[0112] Cold rolling may be performed in a conventional manner, and the cumulative rolling reduction ratio may be 30 to 85%. In order to ensure high strength stably and to reduce anisotropy, the rolling reduction ratio is preferably 35 to 85%. When a high rolling load is incurred, a softening annealing treatment may be performed on CAL (a continuous annealing line) or in BAF (a box annealing furnace) at 450 to 730°C.

<Annealing>

[0113] After cold rolling is carried out in a conventional manner, the steel sheet (the cold rolled steel sheet) is annealed

under the following conditions. The annealing facility is not particularly limited, but a continuous annealing line (CAL) or a continuous galvanizing line (CGL) is preferable from the points of view of productivity and ensuring the desired heating rate and cooling rate.

- 5 [Holding step: The steel sheet is heated to an annealing temperature in the annealing temperature range of 750 to 880°C and is held at the annealing temperature for 10 to 500 seconds.]

10 **[0114]** Annealing temperatures (soaking temperatures) below 750°C do not allow recrystallization to proceed sufficiently, and the microstructures deformed by the cold rolling remain and lower formability. Furthermore, when the annealing temperature (the soaking temperature) is below 750°C, polygonal ferrite occurs excessively and consequently increased amounts of carbon and manganese are concentrated in reverse transformed austenite. As a result, upper bainite, tempered martensite, lower bainite, and retained austenite cannot be obtained sufficiently and consequently the desired strength and ductility cannot be ensured. Thus, the annealing temperature (the soaking temperature) is limited to 750°C or above.

15 **[0115]** On the other hand, annealing temperatures (soaking temperatures) above 880°C are austenite single phase temperatures and do not give predetermined polygonal ferrite, causing an increase in YR and a decrease in ductility. Thus, the annealing temperature (the soaking temperature) is limited to 880°C or below. The annealing temperature (the soaking temperature) is preferably 850°C or below, and more preferably 830°C or below.

20 **[0116]** When the holding time (the soaking time) at the above annealing temperature is less than 10 seconds, austenite formation at the annealing temperature (the soaking temperature) does not take place sufficiently and polygonal ferrite comes to represent an increased amount. Thus, the predetermined amount of upper bainite, tempered martensite, and lower bainite cannot be obtained to cause a failure to obtain the desired strength. In addition, retained austenite cannot be obtained sufficiently to cause a failure to ensure the desired ductility.

25 **[0117]** When, on the other hand, the holding time (the soaking time) at the above annealing temperature is more than 500 seconds, the microstructures are significantly coarsened and the desired strength cannot be ensured.

[0118] Thus, the holding time (the soaking time) at the above annealing temperature is limited to 10 to 500 seconds. The holding time (the soaking time) at the annealing temperature is preferably 80 seconds or more, and more preferably 100 seconds or more. The holding time (the soaking time) at the annealing temperature is preferably 400 seconds or less, and more preferably 300 seconds or less.

30 [First cooling step: The steel sheet is cooled to a first cooling stop temperature of 350 to 550°C at a first average cooling rate in a range of temperatures from the annealing temperature to the first cooling stop temperature of 2 to 50°C/s.]

35 **[0119]** After being held at the soaking temperature of 750°C to 880°C (after the holding step), the steel sheet is cooled at a first average cooling rate of 2 to 50°C/s in a range of temperatures from the annealing temperature to a first cooling stop temperature of 350 to 550°C. When the first average cooling rate is less than 2°C/s, operation is impeded. Thus, the first average cooling rate is limited to 2°C/s or more. The first average cooling rate is preferably 5°C/s or more.

40 **[0120]** When, on the other hand, the first average cooling rate is excessively high, the shape of the sheet is deteriorated. Thus, the first average cooling rate is limited to 50°C/s or less. The first average cooling rate is preferably 40°C/s or less, and more preferably less than 30°C/s.

[0121] Here, the first average cooling rate is determined by "(annealing temperature (°C) - first cooling stop temperature (°C))/cooling time (seconds) from annealing temperature to first cooling stop temperature".

- 45 [Second cooling step (1): The steel sheet is caused to reside at a residence temperature of 350 to 550°C for 10 seconds or more and 60 seconds or less.]

50 **[0122]** Upper bainite is formed in the range of temperatures (residence temperatures) that are from 350°C to 550°C and are equal to or lower than the first cooling stop temperature. As a result, predetermined retained austenite can be obtained and the desired ductility can be achieved. Bainite transformation has an incubation period and the steel sheet should be allowed to reside at the above temperatures for a certain amount of time. When the residence temperature range that includes a residence start temperature (= the first cooling stop temperature) and a residence finish temperature is outside the range from 350 to 550°C and/or when the time for which the steel sheet is caused to reside at the residence temperatures (hereinafter, also written as the residence time) is less than 10 seconds, the desired amount of bainite cannot be obtained and the formation of retained austenite is impeded, with the result that the desired ductility cannot be obtained.

55 **[0123]** When, on the other hand, the residence time is more than 60 seconds, the partitioning of carbon from bainite to massive non-transformed γ proceeds to result in an increase in the amount of massive microstructures that remain. As a result, the desired λ cannot be obtained. Thus, the residence time is limited to 10 seconds or more and 60 seconds or less.

[Second cooling step (2): The steel sheet is cooled to a second cooling stop temperature of 150 to 360°C at a second average cooling rate of 3 to 50°C/s.]

[0124] After the above residence, the steel sheet needs to be cooled rapidly to avoid excessive partitioning of carbon into non-transformed austenite. When the average cooling rate in the temperature range from the residence finish temperature to the cooling stop temperature of 150°C or above and 360°C or below is less than 3°C/s, carbon is partitioned into massive non-transformed γ and the final cooling results in an increased amount of quenched martensite, with the result that λ is lowered. Thus, the second average cooling rate in the temperature range from the residence finish temperature to the second cooling stop temperature of 150°C or above and 360°C or below is limited to 3°C/s or more from the point of view of enhancing λ . The second average cooling rate is preferably 5°C/s or more, and more preferably 8°C/s or more. When the cooling rate in the above temperature range is excessively high, the shape of the sheet is deteriorated. Thus, the cooling rate in the above temperature range (the second average cooling rate) is limited to 50°C/s or less and is preferably 40°C/s or less. When the second cooling stop temperature is above 360°C, tempered martensite or lower bainite does not reach the predetermined area fraction, and the annealing results in an increased area fraction of quenched martensite, with the result that stretch flange formability is deteriorated. Thus, the second cooling stop temperature is limited to 360°C or below.

[0125] When, on the other hand, the second cooling stop temperature is below 150°C, martensite tempering effects cannot be obtained sufficiently during the next step of cooling to 50°C. As a result, the amount of quenched martensite is increased and, in addition, the amount of C-enriched regions ($S_{c \geq 0.5}$) is excessively increased. Stretch flange formability is thus deteriorated. Furthermore, the volume fraction of retained austenite does not reach the desired range, and sufficient ductility cannot be obtained.

[0126] Thus, the second cooling stop temperature is limited to 150°C or above.

[0127] Here, the second average cooling rate is determined by "(residence finish temperature (°C) - second cooling stop temperature (°C))/cooling time (seconds) from residence finish temperature to second cooling stop temperature".

[Third cooling step: The steel sheet is cooled at a third average cooling rate in a range of temperatures from the second cooling stop temperature to 50°C of 0.05 to 1.0°C/s.]

[0128] When the cooling rate in the temperature range from the second cooling stop temperature to 50°C is more than 1.0°C/s, martensite tempering effects cannot be obtained sufficiently and the desired amount of retained austenite cannot be obtained.

[0129] Furthermore, C-enriched regions with 0.05 mass% or more carbon concentration ($S_{c \geq 0.5}$) are increased to cause deterioration in stretch flange formability and quality stability in the width direction.

[0130] Thus, the cooling rate in the temperature range from the second cooling stop temperature to 50°C (the third average cooling rate) is limited to 1.0°C/s or less. Cooling in the temperature range from the second cooling stop temperature to 50°C at a cooling rate (a third average cooling rate) of 1.0°C/s or less reduces temperature variations in the width direction and offers further enhancements in quality stability in the width direction.

[0131] When, on the other hand, the cooling rate in the temperature range from the cooling stop temperature to 50°C is low, the processing time is extended and operability is deteriorated. Thus, the cooling rate in the temperature range from the cooling stop temperature to 50°C (the third average cooling rate) is limited to 0.05°C/s or more.

[0132] The third average cooling rate is preferably 0.08°C/s or more, and more preferably 0.10°C/s or more. The third average cooling rate is preferably 0.80°C/s or less, and more preferably 0.60°C/s or less.

[0133] Here, the third average cooling rate is determined by "(second cooling stop temperature (°C) - 50°C)/cooling time (seconds) from second cooling stop temperature (°C) to 50°C".

[0134] The surface of the steel sheet may be galvanized to form a galvanized layer on the surface of the steel sheet. The type of galvanization is not particularly limited and may be any of hot-dip galvanization or electrogalvanization. Furthermore, the galvanization may be hot-dip galvannealing treatment in which hot-dip galvanization is followed by alloying treatment.

[0135] For example, hot-dip galvanization is performed on automobile steel sheets. Hot-dip galvanization may be performed after the holding step and the first cooling step of the annealing in a continuous annealing furnace at an anterior stage of a continuous hot-dip galvanization line, by immersing the steel sheet into a hot-dip galvanizing bath to form a hot-dip galvanized layer on the surface of the steel sheet. Furthermore, alloying treatment may be performed to manufacture a hot-dip galvannealed steel sheet. Specifically, the surface of the steel sheet may be hot-dip galvanized or hot-dip galvannealed when the steel sheet is caused to reside at a residence temperature of 350 to 550°C for 10 seconds or more and 60 seconds or less in the second cooling step. The galvanization step may be performed on a different line from the soaking and cooling steps.

[0136] The electrogalvanization may be performed after the annealing, that is, after the third cooling step.

[0137] The thickness of the steel sheet of the present invention obtained as described above is preferably 0.5 mm or more. The thickness of the steel sheet of the present invention is preferably 2.0 mm or less.

[0138] The width is preferably 600 mm or more. The width of the steel sheet of the present invention is preferably 1700 mm or less.

[0139] Next, a member and a method for manufacture thereof according to the present invention will be described.

[0140] The member of the present invention is obtained by subjecting the steel sheet of the present invention to at least one working of forming or joining. The method for manufacturing a member of the present invention includes a step of subjecting the steel sheet of the present invention to at least one working of forming or joining to produce a member.

[0141] The steel sheet of the present invention has a tensile strength of 780 MPa or more, excels in press formability, ductility, and stretch flange formability, and is also excellent in quality stability in the width direction.

[0142] Thus, the member that is obtained using the steel sheet of the present invention also has high strength, excels in press formability, ductility, and stretch flange formability, and is also excellent in quality stability in the width direction. Furthermore, weight can be reduced by using the member of the present invention. Thus, for example, the member of the present invention may be suitably used in automobile body frame parts. The member of the present invention also includes a welded joint.

[0143] The forming may be performed using any common working process, such as press working, without limitation. Furthermore, the joining may be performed using common welding, such as spot welding or arc welding, or, for example, riveting or caulking without limitation.

EXAMPLES

[0144] Slabs manufactured by continuous casting of steels having a chemical composition described in Table 1 were heated to 1200°C and were hot rolled in such a manner that the soaking time was 200 minutes, the finish rolling temperature was 900°C, and the coiling temperature was 550°C. Subsequently, the steel sheets were cold rolled with a rolling reduction ratio of 50%. Cold rolled steel sheets with a thickness of 1.4 mm were thus produced. The cold rolled steel sheets were treated under annealing conditions described in Table 2. Steel sheets of the present invention and steel sheets of Comparative Examples were thus manufactured.

[0145] All the steel sheets obtained had a width of 1500 mm.

[Table 1]

Steel No.	Chemical composition (mass%)								Remarks
	C	Si	Mn	P	S	sol.Al	N	others	
A	0.133	0.45	2.43	0.008	0.0012	0.022	0.0028	Ti:0.042, B:0.0029, Nb:0.014	Inventive steel
B	0.185	1.42	2.05	0.007	0.0022	0.033	0.0033	-	Inventive steel
C	0.141	0.89	2.82	0.008	0.0019	0.041	0.0021	Cu: 0.51, Cr:0.024, Ca:0.0022	Inventive steel
D	0.089	1.22	3.22	0.007	0.0022	0.025	0.0036	Ti:0.011	Inventive steel
E	0.177	0.79	2.67	0.006	0.0034	0.322	0.0029	V:0.110	Inventive steel
F	0.081	0.63	2.54	0.003	0.0032	0.188	0.0028	Sb:0.060	Inventive steel
G	0.123	1.16	2.33	0.004	0.0022	0.033	0.0033	Mo:0.4, Mg:0.0022, Sn:0.070	Inventive steel
H	0.062	0.88	2.29	0.003	0.0052	0.331	0.0041	Ni:0.22, Cr:0.720, REM:0.0023	Inventive steel
I	<u>0.033</u>	1.22	2.56	0.005	0.0044	0.032	0.0019	-	Comparative steel
J	<u>0.223</u>	0.89	2.44	0.009	0.0043	0.024	0.0038	-	Comparative steel
K	0.121	<u>0.33</u>	2.42	0.006	0.0036	0.029	0.0042	-	Comparative steel
L	0.164	<u>1.58</u>	2.66	0.007	0.0071	0.033	0.0052	-	Comparative steel

(continued)

Steel No.	Chemical composition (mass%)								Remarks
	C	Si	Mn	P	S	sol.Al	N	others	
<u>M</u>	0.139	1.21	<u>1.77</u>	0.009	0.0039	0.024	0.0032	-	Comparative steel
<u>N</u>	0.102	1.43	<u>3.64</u>	0.004	0.0024	0.122	0.0028	-	Comparative steel
•The balance after the above components is Fe and incidental impurities. *Underlines indicate being outside the range of the present invention.									

[0146] Some of the steel sheets (the cold rolled steel sheets: CR) were obtained as hot-dip galvanized steel sheets (GI) by being hot-dip galvanized when the steel sheet was caused to reside at a residence temperature of 350 to 550°C for 10 seconds or more and 60 seconds or less. Here, the steel sheets were hot-dip galvanized by being immersed into a galvanizing bath at a temperature of 440°C or above and 500°C or below, and the coating weight was adjusted by, for example, gas wiping. The galvanizing bath used in the hot-dip galvanization had an Al content of 0.10% or more and 0.22% or less. Furthermore, some of the hot-dip galvanized steel sheets were alloyed after the hot-dip galvanizing treatment and obtained as hot-dip galvanized steel sheets (GA). Here, the alloying treatment was performed in a range of temperatures of 460°C or above and 550°C or below. Furthermore, some of the steel sheets (the cold rolled steel sheets: CR) were obtained as electrogalvanized steel sheets (EG) by electroplating.

[0147] The steel microstructure was measured in the following manner. The measurement results are described in Table 3.

[0148] To measure the area fractions of polygonal ferrite, upper bainite, tempered martensite, lower bainite, and quenched martensite (fresh martensite), the steel sheet was cut to expose a through-thickness cross section that was parallel to the rolling direction. The cross section was mirror-polished and was etched with 1 vol% Nital. Portions at 1/4 thickness were observed with SEM in 10 fields of view at a magnification of 5000 times. The microstructure images obtained were analyzed to quantify the microstructures. Polygonal ferrite discussed here is relatively equiaxed ferrite containing almost no internal carbides. This region looks blackest in SEM.

[0149] Upper bainite is a ferrite microstructure containing internal carbides that looks white in SEM or retained austenite. When it was difficult to distinguish between upper bainite and polygonal ferrite, the area fractions were calculated assuming that ferrite regions with an aspect ratio ≤ 2.0 were polygonal ferrite and regions with an aspect ratio > 2.0 were upper bainite. Here, the aspect ratio was determined by a/b where a was the length of the major axis that gave the longest particle length, and b was the length of the minor axis that cut across the particle with the longest length in the direction perpendicular to the major axis.

[0150] Tempered martensite and lower bainite are regions that contain lath-like submicrostructures and carbide precipitates according to SEM.

[0151] Quenched martensite (fresh martensite) is massive regions that look white and do not contain any visible submicrostructures according to SEM.

[0152] The remaining microstructures are carbide and/or pearlite microstructures and can be identified as white contrast according to SEM. These microstructures can be distinguished based on the fact that carbides are microstructures with a particle size of 1 μm or less and pearlite is lamellar (layered) microstructures.

[0153] The quantitative evaluation of the microstructures described above, and the measurements of the aspect ratio and the equivalent circular diameter of quenched martensite and retained austenite were performed using image analysis software Image J (Fiji).

[0154] The steel sheet was cut to expose a through-thickness cross section that was parallel to the rolling direction. The cross section was mirror-polished and was etched with 1 vol% Nital. Portions at 1/4 thickness were observed with SEM in 10 fields of view at a magnification of 5000 times. The microstructures were identified and quantified by the Trainable Weka segmentation method of Image J (Fiji) that was capable of segmentation by machine learning. Furthermore, the aspect ratio and the equivalent circular diameter of quenched martensite and retained austenite were measurable using a particle analysis program that was another function of Image J. Quenched martensite and retained austenite identified as described above were exclusively extracted and analyzed.

[0155] The volume fraction of retained austenite was determined by chemically polishing the steel sheet to a location at 1/4 thickness from the surface and analyzing the cross section by X-ray diffractometry. $\text{Co-K}\alpha$ radiation source was used as the incident X-ray, and the volume fraction of retained austenite was calculated from the intensity ratio of (200), (211), and (220) planes of ferrite and (200), (220), and (311) planes of austenite.

[0156] The area fraction $S_{\text{C}\geq 0.5}$ of C-enriched regions with a C concentration of 0.5 mass% or more was measured by

mapping analysis of the C concentration distribution with respect to positions at 1/4 thickness of a through-thickness cross section parallel to the rolling direction, using field emission electron probe microanalyzer (FE-EPMA) JXA-8500F manufactured by JEOL Ltd., at an acceleration voltage of 6 kV and an illumination current of 7×10^{-8} A with the minimum beam diameter. The area fraction of regions where the C concentration was 0.5 mass% or more was thus calculated.

[0157] In order to eliminate the influence of contamination, the background was subtracted so that the average value of carbon obtained by the analysis would be equal to the amount of carbon in the base material. Specifically, when the average of the measured amounts of carbon was greater than the amount of carbon in the base material, the excess was understood as contamination, and the excess was subtracted from each of the values analyzed at the respective positions. The values thus obtained were taken as the true amounts of carbon at the respective positions.

[0158] JIS No. 5 test pieces for tensile test and test specimens for hole expansion test were sampled from the steel sheet, and a tensile test was carried out (in accordance with JIS Z2241 (2011)). $N = 3$. Each of the properties was evaluated based on the average of the three test pieces. The steel sheet was evaluated as being of high strength when the tensile strength was 780 MPa or more. The steel sheet was evaluated as excellent in press formability when the yield ratio YR was 0.8 or less. The steel sheet was evaluated as excellent in ductility when TS was 780 MPa or more and the total elongation EL was 16.0% or more, when TS was 980 MPa or more and the total elongation EL was 14.0% or more, or when TS was 1180 MPa or more and the total elongation EL was 12.0% or more.

[0159] Stretch flange formability was evaluated by a hole expansion test conforming to the provisions of The Japan Iron and Steel Federation Standard JFST 1001 with respect to test specimens sampled from the center of the sheet width. $N = 3$. Specifically, a 100 mm $\times$ 100 mm square sample was punched with a punching tool having a punch diameter of 10 mm and a clearance of 13%, and a conical punch having an apex angle of 60 degrees was inserted into the hole in such a manner that the burr produced at the time of punching would be directed to the outside. The hole was expanded until the sheet was cracked through the thickness. The hole expansion ratio λ (%) = $\{(d - d_0)/d_0\} \times 100$ was calculated where d_0 : initial hole diameter (mm), and d : hole diameter (mm) at the occurrence of cracking. The values of λ measured of the three test specimens were averaged. The steel was evaluated as excellent in hole expandability and stretch flangeability when λ was 30% or more.

[0160] To evaluate the quality stability in the width direction, 23 evaluation pieces (23 pieces including a piece located at the center of the sheet width) were sampled at intervals of 100 mm or less from the center of the sheet width (the position 12W/24 (W: width of the sheet)) toward both ends in the width direction, and EL and λ at each of the positions (measurement positions X) were determined. The difference between the values measured at the center of the sheet width and at each measurement position was expressed as a ratio to the value measured at the center, and thereby the quality stability in the width direction was evaluated.

[0161] The group of continuous measurements where the differences in EL and λ were each 10% or less relative to EL and λ at the center of the sheet width was obtained as the region with 10% or less differences in EL and λ . The steel was evaluated as excellent in quality stability when this region represented 80% or more of the total width of the sheet.

[0162] The quality stability in the width direction was evaluated as excellent when the width of region A that satisfied the following expressions (1) and (2) represented 80% or more of the total width of the sheet.

$$-10 \leq 100 \times [(EL (\%) \text{ at measurement position X within region A} - EL (\%) \text{ at center of sheet width})/EL (\%) \text{ at center of sheet width}] \leq 10 \quad (1)$$

$$-10 \leq 100 \times [(\lambda (\%) \text{ at measurement position X within region A} - \lambda (\%) \text{ at center of sheet width})/\lambda (\%) \text{ at center of sheet width}] \leq 10 \quad (2)$$

[0163] (In expressions (1) and (2), the measurement positions X are a total of 23 locations that divide the width W of the steel sheet into 24 portions. Specifically, the measurement positions X are a total of 23 locations along the width of the sheet that are indicated by W/24, 2W/24, 3W/24, 4W/24, 5W/24, 6W/24, 7W/24, 8W/24, 9W/24, 10W/24, 11W/24, 12W/24, 13W/24, 14W/24, 15W/24, 16W/24, 17W/24, 18W/24, 19W/24, 20W/24, 21W/24, 22W/24, and 23W/24.)

[0164] The measurement results are described in Table 3.

[Table 2]

No.	Steel No.	Holding step		First cooling step		Second cooling step				Third cooling step	Galvanization (*1)	Remarks
		Annealing temp. T (°C)	Soaking time (s)	First average cooling rate (°C/s)	First cooling stop temp. (residence start temp.) (°C)	Residence finish temp. (°C)	Residence time during cooling to residence finish temp. (sec)	Second cooling stop temp. (°C)	Second average cooling rate (°C/s)	Third average cooling rate (°C/s)		
1	A	760	200	15	450	400	38	240	15	0.14	No	Inv. Ex.
2	A	780	200	15	450	400	38	240	15	0.15	EG	Inv. Ex.
3	A	800	200	1	450	400	38	220	15	0.10	No	Comp. Ex.
4	B	830	200	12	360	350	12	320	15	0.30	EG	Inv. Ex.
5	B	800	200	15	<u>570</u>	480	19	300	15	0.35	No	Comp. Ex.
6	B	<u>740</u>	200	15	520	370	24	160	15	0.77	No	Comp. Ex.
7	C	850	200	40	400	370	24	200	15	0.54	GI	Inv. Ex.
8	C	850	200	15	<u>330</u>	<u>310</u>	24	200	15	0.22	GI	Comp. Ex.
9	C	870	200	15	420	360	55	180	15	0.25	No	Inv. Ex.
10	C	830	200	15	380	350	<u>75</u>	180	15	<u>1.21</u>	GI	Comp. Ex.
11	D	800	200	10	380	350	11	180	15	0.92	No	Inv. Ex.
12	D	<u>890</u>	200	10	480	420	35	250	28	0.16	No	Comp. Ex.
13	D	850	200	10	480	<u>340</u>	35	<u>120</u>	28	0.33	No	Comp. Ex.
14	E	810	200	40	480	470	<u>7</u>	300	28	0.23	GA	Comp. Ex.

(continued)

No.	Steel No.	Holding step		First cooling step		Second cooling step				Third cooling step	Galvanization (*1)	Remarks
		Annealing temp. T (°C)	Soaking time (s)	First average cooling rate (°C/s)	First cooling stop temp. (residence start temp.) (°C)	Residence finish temp. (°C)	Residence time during cooling to residence finish temp. (sec)	Second cooling stop temp. (°C)	Second average cooling rate (°C/s)	Third average cooling rate (°C/s)		
15	E	810	200	40	450	360	66	300	28	0.34	GA	Comp. Ex.
16	E	860	200	20	420	380	33	300	28	0.44	No	Inv. Ex.
17	F	790	200	20	470	400	41	380	28	0.80	GA	Comp. Ex.
18	F	850	200	20	450	400	32	140	28	0.08	No	Comp. Ex.
19	F	830	200	10	450	400	32	160	28	0.64	No	Inv. Ex.
20	F	800	200	5	420	380	32	250	33	0.64	GA	Inv. Ex.
21	G	780	200	20	380	400	35	350	2	0.55	No	Comp. Ex.
22	G	810	200	20	380	400	35	350	5	0.25	No	Inv. Ex.
23	H	810	7	15	480	450	33	350	13	0.33	No	Comp. Ex.
24	H	830	200	15	480	450	33	350	13	1.15	GA	Comp. Ex.
25	H	840	200	15	480	450	33	350	13	0.11	No	Inv. Ex.
26	H	820	200	15	480	450	33	350	13	0.87	GA	Inv. Ex.
27	I	800	200	15	450	420	25	250	15	0.22	GA	Comp. Ex.
28	J	800	200	15	450	420	25	250	15	0.13	GA	Comp. Ex.

(continued)

No.	Steel No.	Holding step		First cooling step		Second cooling step				Third cooling step	Galvanization (*1)	Remarks
		Annealing temp. T (°C)	Soaking time (s)	First average cooling rate (°C/s)	First cooling stop temp. (residence start temp.) (°C)	Residence finish temp. (°C)	Residence time during cooling to residence finish temp. (sec)	Second cooling stop temp. (°C)	Second average cooling rate (°C/s)	Third average cooling rate (°C/s)		
29	<u>K</u>	860	200	10	450	420	40	320	15	0.25	No	Comp. Ex.
30	<u>L</u>	800	200	10	450	400	40	300	15	0.52	No	Comp. Ex.
31	<u>M</u>	820	200	20	450	400	20	180	15	0.76	No	Comp. Ex.
32	<u>N</u>	820	200	20	450	400	20	160	15	0.56	GA	Comp. Ex.
*Underlines indicate being outside the range of the present invention. *1) No: no galvanization (cold rolled steel sheet: CR), GI: hot-dip galvanized, GA: hot-dip galvanized, EG: electrogalvanized												

[Table 3]

No.	Steel No.	Microstructure						Properties					Remarks
		Area fraction of polygonal ferrite (%)	Total area fraction of upper B, tempered M, and lower B (%) (*1)	Volume fraction of retained γ (%) (*1)	Area fraction of quenched M (%) (*1)	*2 (%)	Area fraction of $S_{\geq 0.5}$ (%)	Strength	Ductility	Stretch flangeability	Press formability	Quality stability in width direction	
1	A	49	36	7	8	13	8	812	16.7	34	○	87	Inv. Ex.
2	A	56	24	9	11	12	11	822	17.2	42	○	91	Inv. Ex.
3	A	83	14	1	2	67	2	766	15.5	28	○	87	Comp. Ex.
4	B	52	43	4	1	12	3	805	24.5	35	○	87	Inv. Ex.
5	B	54	36	2	8	18	8	822	14.7	35	○	83	Comp. Ex.
6	B	82	13	2	3	43	3	754	15.9	27	○	78	Comp. Ex.
7	C	17	69	8	6	14	11	1198	13.5	36	○	91	Inv. Ex.
8	C	22	63	2	13	16	12	1189	10.1	39	○	87	Comp. Ex.
9	C	22	65	8	5	16	9	1260	14.3	42	○	83	Inv. Ex.
10	C	18	56	2	17	16	22	1244	11.1	25	○	48	Comp. Ex.
11	D	45	42	7	6	11	11	1037	15.3	36	○	83	Inv. Ex.
12	D	8	73	7	12	4	4	1322	10.2	24	×	87	Comp. Ex.
13	D	34	54	2	10	5	24	1024	13.6	22	○	91	Comp. Ex.
14	E	27	64	2	7	17	8	1207	10.3	34	○	87	Comp. Ex.

(continued)

No.	Steel No.	Microstructure						Properties					Remarks
		Area fraction of polygonal ferrite (%)	Total area fraction of upper B, tempered M, and lower B (%) (*1)	Volume fraction of retained γ (%) (*1)	Area fraction of quenched M (%) (*1)	*2 (%)	Area fraction of $S_{\geq 0.5}$ (%)	Strength	Ductility	Stretch flangeability	Press formability	Quality stability in width direction	
15	E	7	62	4	15	<u>22</u>	11	1233	14.2	<u>22</u>	<u>x</u>	<u>65</u>	Comp. Ex.
16	E	20	59	7	14	17	12	1211	13.3	42	○	83	Inv. Ex.
17	F	30	49	8	13	27	12	1005	15.3	27	○	87	Comp. Ex.
18	F	36	60	<u>1</u>	3	19	<u>21</u>	1225	<u>10.6</u>	<u>25</u>	○	<u>65</u>	Comp. Ex.
19	F	26	52	9	13	15	11	999	16.4	42	○	83	Inv. Ex.
20	F	34	38	14	14	10	12	1033	15.7	34	○	83	Inv. Ex.
21	G	44	33	12	11	<u>31</u>	10	1066	15.6	<u>24</u>	○	<u>70</u>	Comp. Ex.
22	G	39	40	10	11	8	9	1024	15.9	36	○	83	Inv. Ex.
23	H	<u>82</u>	<u>5</u>	<u>1</u>	12	7	7	<u>682</u>	<u>15.9</u>	32	○	<u>65</u>	Comp. Ex.
24	H	52	31	<u>2</u>	15	11	<u>24</u>	799	<u>14.7</u>	<u>33</u>	○	<u>57</u>	Comp. Ex.
25	H	46	35	14	5	9	7	810	19.2	46	○	87	Inv. Ex.
26	H	61	21	11	7	8	9	812	18.1	44	○	83	Inv. Ex.
27	I	53	41	<u>2</u>	4	12	2	<u>742</u>	<u>14.3</u>	36	○	87	Comp. Ex.
28	J	47	19	12	<u>22</u>	13	<u>25</u>	1234	14.8	12	<u>x</u>	<u>70</u>	Comp. Ex.

(continued)

No.	Steel No.	Microstructure						Properties					Remarks
		Area fraction of polygonal ferrite (%)	Total area fraction of upper B, tempered M, and lower B (%) (*1)	Volume fraction of retained γ (%) (*1)	Area fraction of quenched M (%) (*1)	*2 (%)	Area fraction of $S_{\geq 0.5}$ (%)	Strength	Ductility	Stretch flangeability	Press formability	Quality stability in width direction	
29	<u>K</u>	22	68	2	8	10	7	1012	<u>11.4</u>	38	○	83	Comp. Ex.
30	<u>L</u>	36	30	<u>16</u>	<u>18</u>	8	19	1221	16.9	18	× <u> </u>	74	Comp. Ex.
31	<u>M</u>	32	50	<u>1</u>	7	10	8	766	<u>15.3</u>	36	○	83	Comp. Ex.
32	<u>N</u>	29	48	<u>2</u>	<u>18</u>	9	3	822	<u>14.9</u>	22	× <u> </u>	87	Comp. Ex.

*1) B: bainite, M: martensite, retained γ : retained austenite
 *2) Total area fraction of quenched M and retained γ each having an aspect ratio of 3 or less and an equivalent circular diameter of 2.0 μm or more relative to the total area of quenched M and retained γ
 *3) Proportion of the width of region A satisfying expressions (1) and (2) to the total width of the sheet. $-10 \leq 100 \times [(\text{EL} \text{ (\%)} \text{ at measurement position X within region A-EL (\%)} \text{ at center of sheet width}) / \text{EL (\%)} \text{ at center of sheet width}] \leq 10 \cdots (1)$ $-10 \leq 100 \times [(\lambda \text{ (\%)} \text{ at measurement position X within region A-A (\%)} \text{ at center of sheet width}) / \lambda \text{ (\%)} \text{ at center of sheet width}] \leq 10 \cdots (2)$ (In expressions (1) and (2), the measurement positions X are a total of 23 locations that divide the width W of the steel sheet into 24 portions.)
 *Underlines indicate being outside the range of the present invention.

[0165] Inventive Examples described in Tables 2 and 3 achieved excellent strength, press formability, ductility, stretch flange formability, and quality stability in the width direction. In contrast, Comparative Examples were unsatisfactory in at least one of these properties.

[0166] The steel sheets of Inventive Examples have high strength and excellent press formability, ductility, stretch flange formability, and quality stability in the width direction. This has shown that members obtained by forming of the steel sheets of Inventive Examples, members obtained by joining of the steel sheets of Inventive Examples, and members obtained by forming and joining of the steel sheets of Inventive Examples will have high strength and excellent press formability, ductility, stretch flange formability, and quality stability in the width direction similarly to the steel sheets of Inventive Examples.

Claims

1. A steel sheet having a chemical composition comprising, in mass%,

C: 0.05 to 0.20%,
Si: 0.40 to 1.50%,
Mn: 1.9 to 3.5%,
P: 0.02% or less,
S: 0.01% or less,
sol. Al: 1.00% or less, and
N: less than 0.015%,
the balance being iron and incidental impurities,
the steel sheet comprising a steel microstructure in which:

the area fraction of polygonal ferrite is 10% or more and 80% or less,
the total area fraction of upper bainite, tempered martensite, and lower bainite is 10% or more and 70% or less,
the volume fraction of retained austenite is 3% or more and 15% or less,
the area fraction of quenched martensite is 15% or less (including 0%), and
the steel microstructure further comprises a remaining microstructure,
the steel sheet being such that:

the total area fraction of quenched martensite and retained austenite each having an aspect ratio of 3 or less and an equivalent circular diameter of 2.0 μm or more is 20% or less relative to the total area fraction of quenched martensite and retained austenite, and
the area fraction of a C-enriched region with a C concentration of 0.5 mass% or more ($S_{c \geq 0.5}$) is 20% or less relative to the entire microstructure.

2. The steel sheet according to claim 1, wherein the chemical composition further comprises, in mass%, one or two selected from:

Ti: 0.1% or less, and
B: 0.01% or less.

3. The steel sheet according to claim 1 or 2, wherein the chemical composition further comprises, in mass%, one, or two or more selected from:

Cu: 1% or less,
Ni: 1% or less,
Cr: 1% or less,
Mo: 0.5% or less,
V: 0.5% or less, and
Nb: 0.1% or less.

4. The steel sheet according to any one of claims 1 to 3, wherein the chemical composition further comprises, in mass%, one, or two or more selected from:

Mg: 0.0050% or less,
 Ca: 0.0050% or less,
 Sn: 0.1% or less,
 Sb: 0.1% or less, and
 REM: 0.0050% or less.

5. The steel sheet according to any one of claims 1 to 4, which has a galvanized layer on a surface.
6. A member obtained using the steel sheet described in any one of claims 1 to 5.
7. A method for manufacturing a steel sheet, comprising hot rolling, pickling, and cold rolling a steel slab having the chemical composition described in any one of claims 1 to 4, and annealing the resultant cold rolled steel sheet, the annealing comprising:
 - a holding step of heating the cold rolled steel sheet to an annealing temperature of 750 to 880°C and holding the cold rolled steel sheet at the annealing temperature for 10 to 500 seconds;
 - a first cooling step of cooling the steel sheet to a first cooling stop temperature of 350 to 550°C at a first average cooling rate in a range of temperatures from the annealing temperature to the first cooling stop temperature of 2 to 50°C/s;
 - a second cooling step of causing the steel sheet to reside at a residence temperature of 350 to 550°C for 10 seconds or more and 60 seconds or less and cooling the steel sheet to a second cooling stop temperature of 150 to 360°C at a second average cooling rate of 3 to 50°C/s; and
 - a third cooling step of cooling the steel sheet at a third average cooling rate in a range of temperatures from the second cooling stop temperature to 50°C of 0.05 to 1.0°C/s.
8. The method for manufacturing a steel sheet according to claim 7, wherein the second cooling step causes the steel sheet to reside at a residence temperature of 350 to 550°C for 10 seconds or more and 60 seconds or less while performing a hot-dip galvanizing treatment or a hot-dip galvannealing treatment on a surface of the steel sheet.
9. The method for manufacturing a steel sheet according to claim 7, further comprising performing an electrogalvanizing treatment on a surface of the steel sheet after the annealing.
10. A method for manufacturing a member, comprising a step of subjecting the steel sheet described in any one of claims 1 to 5 to at least one working of forming or joining to produce a member.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP2023/024254

A. CLASSIFICATION OF SUBJECT MATTER

C21D 9/46(2006.01)i; C22C 38/00(2006.01)i; C22C 38/06(2006.01)i; C22C 38/60(2006.01)i

FI: C22C38/00 301S; C21D9/46 G; C21D9/46 J; C22C38/00 301T; C22C38/06; C22C38/60

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

C21D9/46; C22C38/00-C22C38/60

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Published examined utility model applications of Japan 1922-1996

Published unexamined utility model applications of Japan 1971-2023

Registered utility model specifications of Japan 1996-2023

Published registered utility model applications of Japan 1994-2023

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 2009/096596 A1 (JFE STEEL CORP.) 06 August 2009 (2009-08-06) entire text	1-10
A	WO 2022/019209 A1 (NIPPON STEEL CORP.) 27 January 2022 (2022-01-27) entire text	1-10
A	WO 2017/150117 A1 (KOBE STEEL, LTD.) 08 September 2017 (2017-09-08) entire text	1-10
A	WO 2017/002883 A1 (NIPPON STEEL & SUMITOMO METAL CORP.) 05 January 2017 (2017-01-05) entire text	1-10
A	JP 2020-100894 A (JFE STEEL CORP.) 02 July 2020 (2020-07-02) entire text	1-10

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier application or patent but published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

29 August 2023

Date of mailing of the international search report

12 September 2023

Name and mailing address of the ISA/JP

Japan Patent Office (ISA/JP)
3-4-3 Kasumigaseki, Chiyoda-ku, Tokyo 100-8915
Japan

Authorized officer

Telephone No.

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/JP2023/024254

5	Patent document cited in search report	Publication date (day/month/year)	Patent family member(s)	Publication date (day/month/year)
10	WO 2009/096596 A1	06 August 2009	US 2011/0030854 A1 entire text EP 2246456 A1 KR 10-2010-0101697 A CN 101932746 A JP 2009-203550 A	
15	WO 2022/019209 A1	27 January 2022	EP 4183892 A1 entire text CN 115698359 A KR 10-2023-0012028 A	
20	WO 2017/150117 A1	08 September 2017	US 2019/0085426 A1 entire text EP 3412786 A1 CN 108699653 A KR 10-2018-0120712 A JP 2017-155327 A	
25	WO 2017/002883 A1	05 January 2017	US 2018/0202016 A1 entire text EP 3318652 A1 CN 107709598 A KR 10-2018-0019743 A	
30	JP 2020-100894 A	02 July 2020	(Family: none)	
35				
40				
45				
50				
55				

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 5515623 B [0008]
- JP 2008297609 A [0008]
- JP 3936440 B [0008]