



(12) **DEMANDE DE BREVET CANADIEN
CANADIAN PATENT APPLICATION**

(13) **A1**

(86) Date de dépôt PCT/PCT Filing Date: 2018/05/23
(87) Date publication PCT/PCT Publication Date: 2018/11/29
(85) Entrée phase nationale/National Entry: 2019/11/18
(86) N° demande PCT/PCT Application No.: US 2018/034184
(87) N° publication PCT/PCT Publication No.: 2018/217924
(30) Priorités/Priorities: 2017/05/23 (US62/510,065);
2017/07/25 (US62/536,876); 2017/11/10 (US62/584,441);
2018/03/16 (US62/644,098)

(51) Cl.Int./Int.Cl. *C07C 2/00* (2006.01),
C07C 11/06 (2006.01), *C07C 2/76* (2006.01),
C07C 2/82 (2006.01), *C07C 2/84* (2006.01),
C07C 7/00 (2006.01)
(71) Demandeur/Applicant:
LUMMUS TECHNOLOGY LLC, US
(72) Inventeurs/Inventors:
MCCORMICK, JAROD, US;
RADAELLI, GUIDO, US;
RAFIQUE, HUMERA ABDUL, US;
HIDAJAT, JAMES, US;
VUDDAGIRI, SRINIVAS R., US;
MILES, JOSHUA RYAN, US; ...

(54) Titre : INTEGRATION DE PROCEDES DE COUPLAGE OXYDANT DU METHANE
(54) Title: INTEGRATION OF OXIDATIVE COUPLING OF METHANE PROCESSES




FIG. 1

(57) **Abrégé/Abstract:**
The present disclosure provides methods and systems for producing an olefin, such as ethylene and propylene. A method for producing an olefin can comprise injecting an oxidizing agent and methane into an oxidative coupling of methane (OCM) reactor to generate ethylene. The methane and/or additional feedstocks for the OCM reactor can be derived from a thermal cracking or fluidized catalytic cracking (FCC) process. The ethylene generated in the OCM reactor can be converted to propylene through a dimerization unit and metathesis unit.

(72) Inventeurs(suite)/Inventors(continued): BLACK, RICHARD, US

(74) Agent: GOWLING WLG (CANADA) LLP

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau

(43) International Publication Date
29 November 2018 (29.11.2018)



(10) International Publication Number
WO 2018/217924 A1

(51) International Patent Classification:

C07C 2/00 (2006.01) C07C 2/84 (2006.01)
C07C 2/76 (2006.01) C07C 7/00 (2006.01)
C07C 2/82 (2006.01) C07C 11/06 (2006.01)

(21) International Application Number:

PCT/US2018/034184

(22) International Filing Date:

23 May 2018 (23.05.2018)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/510,065	23 May 2017 (23.05.2017)	US
62/536,876	25 July 2017 (25.07.2017)	US
62/584,441	10 November 2017 (10.11.2017)	US
62/644,098	16 March 2018 (16.03.2018)	US

(71) Applicant: **SILURIA TECHNOLOGIES, INC.**
[US/US]; 409 Illinois Street, San Francisco, California
94158 (US).

(72) Inventors: **MCCORMICK, Jarod**; 984 California Av-
enue, Palo Alto, California 94306 (US). **RADAELLI, Gui-**
do; 11 Oak Gate Place, Pleasant Hill, California 94523
(US). **RAFIQUE, Humera Abdul**; 25 Heligan Lane, Unit
5, Livermore, California 94551 (US). **HIDAJAT, James**;
2801 Shannon Drive, South San Francisco, California
94080 (US). **VUDDAGIRI, Srinivas R.**; 2951 Audubon

Circle, Davis, California 95618 (US). **MILES, Joshua
Ryan**; 1133 Folsom Street, San Francisco, California 94103
(US). **BLACK, Richard**; 17214 Crescent Canyon Drive,
Houston, Texas 77095 (US).

(74) Agent: **YE, Jing**; WILSON SONSINI GOODRICH &
ROSATI, 650 Page Mill Road, Palo Alto, California
94304-1050 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP,
KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,
SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

(54) Title: INTEGRATION OF OXIDATIVE COUPLING OF METHANE PROCESSES




FIG. 1

(57) Abstract: The present disclosure provides methods and systems for producing an olefin, such as ethylene and propylene. A method for producing an olefin can comprise injecting an oxidizing agent and methane into an oxidative coupling of methane (OCM) reactor to generate ethylene. The methane and/or additional feedstocks for the OCM reactor can be derived from a thermal cracking or fluidized catalytic cracking (FCC) process. The ethylene generated in the OCM reactor can be converted to propylene through a dimerization unit and metathesis unit.

WO 2018/217924 A1

TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

INTEGRATION OF OXIDATIVE COUPLING OF METHANE PROCESSES

CROSS-REFERENCE

[0001] This application claims the benefit of U.S. Provisional Patent Application No. 62/510,065, filed May 23, 2017, U.S. Provisional Patent Application No. 62/536,876, filed July 25, 2017, U.S. Provisional Patent Application No. 62/584,441, filed November 10, 2017, and U.S. Provisional Patent Application No. 62/644,098, filed March 16, 2018, each of which is incorporated herein by reference in its entirety.

BACKGROUND

[0002] Olefins, including ethylene and propylene, are important feedstocks in the chemicals industry. Olefins can be generated from the cracking of high molecular weight hydrocarbon streams into lower molecular weight streams. Additionally olefins can be interconverted among species with various numbers of carbon atoms through chemical transformations.

SUMMARY

[0003] Recognized herein is a need for efficient and commercially viable olefin production systems and methods for converting alkanes into olefins when coupled to crude to chemicals (C2C) processes such as high-severity fluidized catalytic cracking (HS-FCC) processes and processes employing dimerization and metathesis operations.

[0004] The present disclosure provides systems and methods for generating olefins, including ethylene and propylene, through the integration of an oxidative-coupling of methane (OCM) process with an additional process that can either provide the feedstock for the OCM process or can consume the products of the OCM process.

[0005] An aspect of the present disclosure provides a method for producing propylene, the method comprising: (a) injecting a first stream containing methane (CH_4) and a second stream containing an oxidizing agent into an oxidative coupling of methane (OCM) reactor at a temperature of at least about 400 °C and a pressure of at least about 3 bar(g) to produce an OCM product stream containing ethylene, hydrogen (H_2), carbon dioxide (CO_2), carbon monoxide (CO), and unconverted CH_4 ; (b) injecting at least a portion of the OCM product stream into a dimerization reactor to produce butene, wherein less than about 50% of the butene is isobutene; and (c) injecting the butene into a metathesis reactor to produce an effluent stream comprising propylene and unconverted butene.

[0006] In some embodiments, (b) and (c) are performed in a single vessel. In some embodiments, dimerization and metathesis are performed in a single reactor or over a single catalyst. In some embodiments, at least about 50% of the butene is 1-butene or 2-butene. In some

embodiments, a portion of the ethylene produced in the OCM reactor is injected into the dimerization reactor, and an additional portion of the ethylene produced in the OCM reactor is injected into the metathesis reactor. In some embodiments, about 70% of the ethylene produced in the OCM reactor is injected into the dimerization reactor, and about 30% of the ethylene produced in the OCM reactor is injected into the metathesis reactor. In some embodiments, substantially no ethylene is injected into metathesis reactor without first being injected into the dimerization reactor. In some embodiments, the butene produced in the dimerization reactor contains C_{5+} compounds, and wherein the C_{5+} compounds are removed using a de-butanizer prior to (c). In some embodiments, the ethylene is separated from C_{3+} components in the effluent stream of the metathesis reactor. In some embodiments, a portion of the separated ethylene is recycled to the metathesis reactor. In some embodiments, the propylene in the effluent stream of the metathesis reactor is separated from the unconverted butene. In some embodiments, the unconverted butene is recycled to the metathesis reactor. In some embodiments, the ethylene that is injected into the dimerization reactor has a purity of at least about 99.5 mol%. In some embodiments, at least about 95% of the ethylene is converted into butenes in the dimerization reactor. In some embodiments, the butene that is injected into the metathesis reactor further comprises un-converted ethylene, which unconverted ethylene is passed through the dimerization reactor without being converted to butene. In some embodiments, the unconverted ethylene is about the only ethylene that is injected into the metathesis reactor. In some embodiments, the unconverted methane from the OCM reactor is removed through a vacuum pressure swing adsorption (VPSA) process to produce a VPSA effluent stream that contains less than about 1% methane. In some embodiments, the VPSA effluent stream is injected into a distillation column that removes C_{3+} species to generate a distillation effluent stream that has a higher concentration of ethylene than the VPSA effluent stream. In some embodiments, the propylene generated in the metathesis reactor is also separated using the distillation column that removes the C_{3+} species. In some embodiments, the butene produced in the dimerization reactor is injected, without prior purification, into the metathesis reactor. In some embodiments, the method further comprises injecting ethane into the OCM reactor in (a). In some embodiments, the method further comprises injecting propane into the OCM reactor in (a). In some embodiments, the method further comprises separating the ethylene produced in the OCM reactor in (a) from ethane, methane, and hydrogen comprised in the OCM product stream. In some embodiments, the CO_2 is separated from the OCM product stream. In some embodiments, the CO_2 is injected into a methanation reactor to produce additional CH_4 . In some embodiments, the additional CH_4 produced in the methanation reactor is injected into the OCM reactor. In some embodiments,

distillation is used to purify the ethylene from the OCM product stream. In some embodiments, pressure swing adsorption is used to purify the ethylene from the OCM product stream. In some embodiments, a C1 splitter is used to recycle the methane back to the OCM reactor. In some embodiments, a C2 splitter is used to recycle the ethane back to the OCM reactor. In some embodiments, the methane recovered from the pressure swing adsorption is recycled to the OCM reactor. In some embodiments, the dimerization reactor contains a dimerization catalyst. In some embodiments, the OCM reactor contains an OCM catalyst. In some embodiments, the OCM catalyst comprises nanowires. In some embodiments, the method further comprises separating the effluent stream of the metathesis reactor. In some embodiments, distillation is used to purify the effluent stream. In some embodiments, ethylene and ethane are separated from C₃₊ products in a distillation column. In some embodiments, propylene and propane are separated in a distillation column. In some embodiments, the metathesis reactor reacts ethylene with butene to generate propylene. In some embodiments, butene reacts with butene to generate propylene.

[0007] Another aspect of the present disclosure provides a method for producing propylene, the method comprising: (a) injecting a first stream containing methane and a second stream containing an oxidizing agent into an oxidative coupling of methane (OCM) reactor to produce a stream containing ethylene; (b) injecting the ethylene into a dimerization reactor to produce butenes including 1-butene, 2-butene, and isobutene; and (c) injecting the butenes into a metathesis reactor to produce an effluent comprising propylene and unreacted butenes, wherein in the metathesis reactor the 1-butene and 2-butene metathesize to produce the propylene, and wherein the ethylene is not injected directly into the metathesis reactor.

[0008] In some embodiments, the method further comprises: (d) recycling a portion of the unreacted butenes to the metathesis reactor. In some embodiments, less than about 50% of the unreacted butenes are recycled to the metathesis reactor. In some embodiments, the method further comprises injecting ethane into the OCM reactor in (a). In some embodiments, the method further comprises injecting propane into the OCM reactor in (a). In some embodiments, the method further comprises separating the ethylene produced in the OCM reactor in (a) from other components comprising CO₂, CO, H₂, and unreacted CH₄ comprised in the stream. In some embodiments, the CO₂ is separated from the stream. In some embodiments, the CO₂ is injected into a methanation reactor to produce additional CH₄. In some embodiments, the additional CH₄ is injected into the OCM reactor. In some embodiments, distillation is used to purify the ethylene from the stream. In some embodiments, pressure swing adsorption is used to purify the ethylene from the stream. In some embodiments, a C1 splitter is used to recycle methane back to the OCM reactor. In some embodiments, a C2 splitter is used to recycle ethane back to the OCM

reactor. In some embodiments, methane recovered from the pressure swing adsorption is recycled to the OCM reactor. In some embodiments, a debutenizer is used to extract C_{5+} products from the dimerization reactor in (b). In some embodiments, the debutenizer is a distillation column. In some embodiments, the dimerization reactor contains a dimerization catalyst. In some embodiments, the OCM reactor contains an OCM catalyst. In some embodiments, the OCM catalyst comprises nanowires. In some embodiments, the method further comprises purifying the effluent of the metathesis reactor. In some embodiments, distillation is used to purify the effluent. In some embodiments, the purifying comprises separating ethylene and ethane from C_{3+} components in a distillation column. In some embodiments, the purifying comprises separating propylene and propane in a distillation column. In some embodiments, the butenes are not purified prior to injection in the metathesis reactor. In some embodiments, the effluent of the metathesis reactor is injected into the distillation column. In some embodiments, the separated C_{3+} components are fed into a stabilizer to remove C_{4+} components from propylene and propane. In some embodiments, the propylene is separated from the propane in the distillation column. In some embodiments, at least about 90% of the propylene generated in the metathesis reactor is included in an effluent stream of the distillation column.

[0009] Another aspect of the present disclosure provides a system for producing propylene, comprising: (a) at least one oxidative-coupling of methane (OCM) subsystem that (i) has a first input stream comprising methane (CH_4), (ii) has a second input feed stream comprising an oxidizing agent, and (iii) is configured to generate from the methane and the oxidizing agent a product stream comprising ethylene; (b) at least one first purification subsystem that is downstream of, and fluidically coupled to, the OCM subsystem, which at least one first purification subsystem is configured to use the product stream of the OCM subsystem to produce an ethylene stream having a higher concentration of ethylene than the product stream; (c) at least one dimerization subsystem downstream of, and fluidically coupled to, the at least one first purification subsystem, wherein the at least one dimerization subsystem is capable of converting the ethylene stream into a stream containing butenes; (d) at least one metathesis subsystem downstream of, and fluidically coupled to, the at least one dimerization subsystem, wherein the at least one metathesis subsystem is configured to convert the stream containing the butenes including 1-butene and 2-butene into a metathesis product stream containing propylene and unconverted butenes; and (e) at least one second purification subsystem that is downstream of, and fluidically coupled to, the at least one metathesis subsystem, which at least one second purification subsystem is configured to separate the unconverted butenes from the propylene.

[0010] In some embodiments, the system further comprises: a recycle loop that is fluidically coupled to the at least one second purification subsystem and the at least one dimerization subsystem, which recycle loop is configured to return the unconverted butenes from the at least one second purification subsystem to the at least one dimerization subsystem. In some embodiments, the recycle loop diverts at least about 50% of the unconverted butenes away from the at least one metathesis subsystem. In some embodiments, the at least one OCM subsystem contains an OCM reactor. In some embodiments, the OCM reactor contains an OCM catalyst. In some embodiments, the OCM catalyst comprises nanowires. In some embodiments, the at least one first purification subsystem is configured to remove CO₂ from the product stream of the OCM subsystem. In some embodiments, the at least one first purification subsystem is configured to feed the CO₂ into a methanation reactor. In some embodiments, the at least one first purification subsystem contains a subsystem that removes methane from the product stream of the OCM subsystem. In some embodiments, the subsystem comprises at least one demethanizer. In some embodiments, the demethanizer is a distillation column. In some embodiments, the subsystem comprises a pressure swing adsorption unit. In some embodiments, the at least one first purification subsystem contains a subsystem that removes ethane from the product stream of the OCM subsystem. In some embodiments, the subsystem comprises at least one C₂ splitter. In some embodiments, the at least one C₂ splitter comprises a distillation column. In some embodiments, the at least one second purification subsystem comprises a distillation column. In some embodiments, the at least one first purification subsystem and the at least one second purification subsystem are the same. In some embodiments, the system does not contain a purification subsystem that is capable of changing a composition of the stream of the at least one dimerization reactor prior to being injected in the at least one metathesis reactor.

[0011] Another aspect of the present disclosure provides a method for producing olefins, the method comprising: (a) injecting a feed stream containing a mixture of hydrocarbons having a first average molecular weight into a vessel operating at a temperature of at least about 500 °C, thereby producing a cracked hydrocarbon stream containing a mixture of hydrocarbons having a second average molecular weight, wherein the second average molecular weight is less than the first average molecular weight; (b) separating one or more light hydrocarbons from the cracked hydrocarbon stream; and (c) injecting the one or more light hydrocarbons separated in (b) into an oxidative coupling of methane (OCM) reactor that converts at least a portion of the one or more light hydrocarbons into ethylene.

[0012] In some embodiments, the one or more light hydrocarbons comprise hydrogen sulfide (H₂S). In some embodiments, the H₂S constitutes at least about 5 percent by weight (wt%) of the

light hydrocarbons. In some embodiments, the vessel is a thermal cracker. In some embodiments, the vessel is a fluidized catalytic cracker (FCC). In some embodiments, the FCC is operated as a high-severity fluidized catalytic cracker (HS-FCC). In some embodiments, the HS-FCC operates at a temperature of at least about 500 °C. In some embodiments, the HS-FCC contains a catalyst that moves relative to the vessel. In some embodiments, the catalyst is injected into a top portion of the vessel and falls to a bottom portion of the vessel. In some embodiments, the catalyst comprises a zeolite. In some embodiments, the zeolite is ZSM-5. In some embodiments, the HS-FCC operates with a residence time of less than about 1 second (s), and wherein the residence time is a period of time that passes between the feed stream entering the vessel and the cracked hydrocarbon stream exiting the vessel. In some embodiments, the one or more light hydrocarbons include hydrocarbons having one to three carbon atoms (C1-C3 hydrocarbons). In some embodiments, the one or more light hydrocarbons include methane. In some embodiments, the one or more light hydrocarbons include ethane. In some embodiments, the one or more light hydrocarbons include propane. In some embodiments, methane from the HS-FCC is fed into the OCM reactor. In some embodiments, ethane from the HS-FCC is fed into the OCM reactor. In some embodiments, propane from the HS-FCC is fed into the OCM reactor. In some embodiments, the ethylene is included in a product stream from the OCM reactor, and wherein the product stream is used to generate an ethylene stream that has a higher concentration of ethylene than the product stream. In some embodiments, the OCM reactor produces CO₂, which CO₂ is separated from the ethylene. In some embodiments, the CO₂ is injected into a methanation reactor to produce additional CH₄. In some embodiments, the additional CH₄ is injected into the OCM reactor. In some embodiments, pressure swing adsorption is used to generate an ethylene stream from the OCM reactor. In some embodiments, a C1 splitter is used to recycle methane back to the OCM reactor. In some embodiments, methane recovered from the pressure swing adsorption is recycled to the OCM reactor. In some embodiments, the thermal cracker is operated at a pressure of at least about 3 bar(g). In some embodiments, the FCC contains a catalyst. In some embodiments, the catalyst comprises a zeolite. In some embodiments, the zeolite comprises a high USY zeolite. In some embodiments, the zeolite comprises ZSM-5 zeolites. In some embodiments, the OCM reactor contains an OCM catalyst. In some embodiments, the OCM catalyst comprises nanowires.

[0013] Another aspect of the present disclosure provides a system for producing olefins, comprising: a fluidized catalytic cracker (FCC) unit containing a catalyst that is movable downward through the FCC unit; a first separations subsystem fluidically coupled to the FCC unit, which first separations subsystem is configured to separate components that have a boiling

point greater than that of propane from those with a boiling point lower than that of propane; a second separations subsystem fluidically coupled to the FCC unit, the second separations subsystem configured to remove hydrogen sulfide (H_2S); and an oxidative-coupling of methane (OCM) unit fluidically coupled to the FCC unit and configured to convert the components that have a boiling point lower than that of propane into ethylene.

[0014] In some embodiments, the FCC unit is a high-severity FCC (HS-FCC) unit. In some embodiments, the FCC unit operates at temperatures of at least about 500 °C. In some embodiments, the FCC unit operates with a residence time of less than about 1 second (s). In some embodiments, the catalyst in the FCC unit comprises a zeolite. In some embodiments, the system further comprises a heat recovery subsystem, which is downstream of and fluidically coupled to the OCM unit, the heat recovery system configured to transfer heat from the OCM unit to another heat transfer medium. In some embodiments, the system further comprises a process gas compressor, which is downstream of and fluidically coupled to the heat recovery subsystem, the process gas compressor configured to increase a pressure of an OCM gas exiting the OCM unit. In some embodiments, the system further comprises a CO_2 separation subsystem, which is downstream of and fluidically coupled to the process gas compressor, the CO_2 separation subsystem configured to remove CO_2 from an OCM gas exiting the OCM unit. In some embodiments, the CO_2 separation subsystem comprises an absorber unit. In some embodiments, the CO_2 separation subsystem comprises a pressure-swing adsorption unit. In some embodiments, the system further comprises a demethanation subsystem, which is downstream of and fluidically coupled to the CO_2 separation subsystem, the demethanation subsystem configured to remove methane from an OCM gas exiting the OCM unit. In some embodiments, the demethanation subsystem comprises a pressure-swing adsorption unit. In some embodiments, the system further comprises a methanation unit, which is configured to convert CO_2 to methane.

[0015] Another aspect of the present disclosure provides a method for producing propylene, comprising: (a) injecting a stream containing methane and a stream containing an oxidizing agent into an oxidative coupling of methane (OCM) unit to generate an OCM effluent stream containing ethylene, propylene, and propane; (b) fractionating the OCM effluent stream using one or more separation units to generate (i) a first stream comprising ethylene and (ii) a second stream comprising propylene and propane; (c) injecting at least a portion of the second stream into an additional separation unit to generate a propylene stream and a propane stream; and (d) injecting at least a portion of the propane stream into a propane dehydrogenation (PDH) unit to generate a PDH effluent containing propylene and hydrogen.

[0016] In some embodiments, the method further comprises injecting at least a portion of the PDH effluent into one or more additional separation units to generate a first effluent stream comprising hydrogen and C_1 - C_2 hydrocarbons, and a second effluent stream comprising C_{3+} hydrocarbons. In some embodiments, the oxidizing agent comprises oxygen. In some embodiments, the method further comprises injecting at least a portion of the first effluent stream into the one or more additional separation units to generate a hydrogen stream and an OCM feed stream. In some embodiments, the OCM feed stream contains hydrogen, methane, and ethane. In some embodiments, at least a portion of the OCM feed stream is injected into an OCM recycle loop. In some embodiments, the OCM recycle loop is comprised of any combination of i) a process gas compressor, ii) a methanation unit, iii) a CO_2 removal unit, iv) a demethanation unit, and v) the OCM unit. In some embodiments, the OCM recycle loop is comprised of i)-v). In some embodiments, the method further comprises generating heat using hydrogen from the hydrogen stream. In some embodiments, the method further comprises injecting at least a portion of the ethylene produced in the OCM unit into a dimerization unit to generate a butene-containing stream. In some embodiments, the method further comprises injecting at least a portion of the butene-containing stream into the dimerization unit to generate a propylene-containing stream. In some embodiments, the one or more additional separation units comprise include distillation towers. In some embodiments, the one or more additional separation units comprise a pressure-swing adsorption (PSA) unit.

[0017] Another aspect of the present disclosure provides a method for producing methanol ($MeOH$) and hydrocarbon compounds containing at least two carbon atoms (C_{2+} compounds), comprising: (a) separating the CO and/or CO_2 from the product stream to generate a CO and/or CO_2 stream; (b) directing the CO and/or CO_2 stream to an $MeOH$ reactor to produce $MeOH$; (c) separating the un-reacted CH_4 from the product stream to produce a CH_4 stream; and (d) directing at least a portion of the CH_4 stream to a steam methane reformer (SMR) that produces hydrogen (H_2) and CO and/or CO_2 , wherein the CH_4 stream is directed into the SMR without passing through a pre-reformer.

[0018] In some embodiments, the method further comprises directing the $MeOH$ produced in (c) to a methanol to olefins (MTO) process to produce a first olefin stream. In some embodiments, the method further comprises combining the first olefin stream and the C_{2+} compounds to produce a combined olefin stream and enriching olefins from the combined olefin stream. In some embodiments, the method further comprises directing CO and/or CO_2 produced in the SMR to the $MeOH$ reactor. In some embodiments, all of the CO and/or CO_2 from the product stream and all of the CO and/or CO_2 from the SMR is converted to $MeOH$ in the $MeOH$ reactor.

In some embodiments, the un-reacted CH_4 is provided as fuel to the SMR. In some embodiments, the un-reacted CH_4 is provided as feedstock to the SMR, and wherein the SMR converts the un-reacted CH_4 into the H_2 and the CO and/or CO_2 for conversion to MeOH in the MeOH reactor. In some embodiments, at least about 95% of the methane is converted into MeOH or C_{2+} compounds. In some embodiments, the method further comprises providing the C_{2+} compounds to a cracker that cracks or refines the C_{2+} compounds. In some embodiments, at least 80% of the methane consumed by the SMR is from the CH_4 stream. In some embodiments, the method further comprises directing a portion of the CH_4 stream to a cracker. In some embodiments, at least 80% of the methane consumed by the SMR and the cracker is from the CH_4 stream. In some embodiments, the method further comprises directing at least a portion of the CH_4 stream to a methane-consuming process. In some embodiments, at least 80% of the methane consumed by the SMR, the cracker and the methane-consuming process is from the CH_4 stream. In some embodiments, the product stream comprises CO . In some embodiments, the product stream comprises CO_2 . In some embodiments, the product stream comprises CO and CO_2 . In some embodiments, the oxidizing agent comprises oxygen.

[0019] Another aspect of the present disclosure provides a system for producing methanol (MeOH) and hydrocarbon compounds containing at least two carbon atoms (C_{2+} compounds), comprising: an oxidative coupling of methane (OCM) reactor that (i) receives methane (CH_4) and an oxidizing agent and (ii) reacts the CH_4 and the oxidizing agent to yield a product stream comprising the C_{2+} compounds, carbon monoxide (CO) and/or carbon dioxide (CO_2), and un-reacted CH_4 ; an MeOH reactor that (i) receives the CO and/or CO_2 separated from the product stream and (ii) reacts the CO and/or CO_2 to produce MeOH ; and a steam methane reformer (SMR) that (i) receives the un-reacted CH_4 separated from the product stream without use of a pre-reformer upstream of the SMR, and (ii) provides hydrogen (H_2) and at least one of carbon monoxide (CO) and CO_2 to the MeOH reactor to produce MeOH .

[0020] In some embodiments, the system further comprises a methanol to olefins (MTO) reactor that converts the MeOH to olefins. In some embodiments, the system further comprises a separations module that enriches olefins from the C_{2+} compounds and the olefins. In some embodiments, the system further comprises a separation unit downstream of the OCM reactor and upstream of the MeOH reactor, wherein the separation unit separates the CO and/or CO_2 from the product stream. In some embodiments, the system further comprises a separation unit downstream of the OCM reactor and upstream of the SMR, wherein the separation unit separates the un-reacted CH_4 from the product stream. In some embodiments, the SMR uses the un-reacted CH_4 as fuel. In some embodiments, the SMR uses the un-reacted CH_4 as a feedstock and

converts the un-reacted CH_4 into the H_2 and the at least one of CO and CO_2 for conversion to MeOH in the MeOH reactor. In some embodiments, the MeOH reactor converts all of the CO and/or CO_2 from the product stream and all of the CO and/or CO_2 from the SMR to MeOH . In some embodiments, at least about 95% of the methane is converted into MeOH or C_{2+} compounds. In some embodiments, the system further comprises a cracker that (i) receives the C_{2+} compounds and (ii) cracks or refines the C_{2+} compounds. In some embodiments, the un-reacted CH_4 directed to the SMR provides at least 80% of the methane consumed by the SMR. In some embodiments, the system further comprises a cracker that receives at least a portion of the unreacted CH_4 . In some embodiments, at least 80% of the methane consumed by the SMR and the cracker is from the unreacted CH_4 . In some embodiments, the system further comprises a methane-consuming module that receives the unreacted CH_4 . In some embodiments, at least 80% of the methane consumed by the SMR, the cracker and the methane-consuming module is from the unreacted CH_4 . In some embodiments, the product stream comprises CO . In some embodiments, the product stream comprises CO_2 . In some embodiments, the product stream comprises CO and CO_2 . In some embodiments, the oxidizing agent comprises oxygen.

[0021] Another aspect of the present disclosure provides a method for producing methanol (MeOH) and hydrocarbon compounds containing at least two carbon atoms (C_{2+} compounds), comprising: (a) directing methane (CH_4) and an oxidizing agent into an oxidative coupling of methane (OCM) reactor to produce a product stream comprising the C_{2+} compounds, carbon monoxide (CO) and/or carbon dioxide (CO_2), and un-reacted CH_4 ; (b) separating the CO and/or CO_2 from the product stream to generate a CO and/or CO_2 stream; and (c) directing the CO and/or CO_2 stream to an MeOH reactor to produce MeOH , wherein the CO and/or CO_2 stream is directed into the MeOH reactor without passing through an autothermal reformer (ATR).

[0022] In some embodiments, the method further comprises directing the MeOH produced in (c) to a methanol to olefins (MTO) process to produce a first olefin stream. In some embodiments, the method further comprises combining the first olefin stream and the C_{2+} compounds to produce a combined olefin stream and enriching olefins from the combined olefin stream. In some embodiments, all of the CO and/or CO_2 from the product stream is converted to MeOH in the MeOH reactor. In some embodiments, at least about 95% of the methane is converted into MeOH or C_{2+} compounds. In some embodiments, the method further comprises directing the C_{2+} compounds to a cracker that cracks or refines the C_{2+} compounds. In some embodiments, the product stream comprises CO . In some embodiments, the product stream comprises CO_2 . In some embodiments, the product stream comprises CO and CO_2 . In some embodiments, the oxidizing agent comprises oxygen.

[0023] Another aspect of the present disclosure provides a system for producing methanol (MeOH) and hydrocarbon compounds containing at least two carbon atoms (C_{2+} compounds), comprising: an oxidative coupling of methane (OCM) reactor that (i) receives methane (CH_4) and an oxidizing agent and (ii) reacts the CH_4 and the oxidizing agent to yield a product stream comprising the C_{2+} compounds, carbon monoxide (CO) and/or carbon dioxide (CO_2), and un-reacted CH_4 ; and an MeOH reactor that (i) receives CO and/or CO_2 separated from the product stream without use of a pre-reformer upstream of the MeOH reactor, and (ii) reacts the CO and/or CO_2 to produce MeOH.

[0024] In some embodiments, the system further comprises a methanol to olefins (MTO) reactor that converts the MeOH to olefins. In some embodiments, the system further comprises a separations module that enriches olefins from the C_{2+} compounds and the olefins. In some embodiments, the MeOH reactor converts all of the CO and/or CO_2 from the product stream to MeOH. In some embodiments, the system further comprises a separation unit downstream of the OCM reactor and upstream of the MeOH reactor, wherein the separation unit separates the CO and/or CO_2 from the product stream. In some embodiments, at least about 95% of the methane is converted into MeOH or C_{2+} compounds. In some embodiments, the system further comprises a cracker that (i) receives the C_{2+} compounds and (ii) cracks or refines the C_{2+} compounds. In some embodiments, the system further comprises a cracker that receives at least a portion of the unreacted CH_4 . In some embodiments, the product stream comprises CO. In some embodiments, the product stream comprises CO_2 . In some embodiments, the product stream comprises CO and CO_2 . In some embodiments, the oxidizing agent comprises oxygen.

[0025] Another aspect of the present disclosure provides a method for producing methanol (MeOH) and hydrocarbon compounds containing at least two carbon atoms (C_{2+} compounds), comprising: (a) directing methane (CH_4) and an oxidizing agent into an oxidative coupling of methane (OCM) reactor to produce a product stream comprising the C_{2+} compounds and un-reacted CH_4 ; (b) separating the un-reacted CH_4 from the product stream to produce a CH_4 stream; (c) directing at least a portion of the CH_4 stream to a steam methane reformer (SMR) that produces hydrogen (H_2) and CO and/or CO_2 , wherein the CH_4 stream is directed into the SMR without passing through a pre-reformer; and (d) directing the CO and/or CO_2 produced in (c) to an MeOH reactor to produce MeOH.

[0026] In some embodiments, the method further comprises directing the MeOH produced in (d) to a methanol to olefins (MTO) process to produce a first olefin stream. In some embodiments, the method further comprises combining the first olefin stream and the C_{2+} compounds to produce a combined olefin stream and enriching olefins from the combined olefin stream. In

some embodiments, all of the CO and/or CO₂ from the SMR is converted to MeOH in the MeOH reactor. In some embodiments, the un-reacted CH₄ is provided as fuel to the SMR. In some embodiments, the un-reacted CH₄ is provided as feedstock to the SMR, and wherein the SMR converts the un-reacted CH₄ into the H₂ and the CO and/or CO₂ for conversion to MeOH in the MeOH reactor. In some embodiments, at least about 95% of the methane is converted into MeOH or C₂₊ compounds. In some embodiments, the method further comprises providing the C₂₊ compounds to a cracker that cracks or refines the C₂₊ compounds. In some embodiments, at least 80% of the methane consumed by the SMR is from the CH₄ stream. In some embodiments, the method further comprises directing a portion of the CH₄ stream to a cracker. In some embodiments, at least 80% of the methane consumed by the SMR and the cracker is from the CH₄ stream. In some embodiments, the method further comprises directing at least a portion of the CH₄ stream to a methane-consuming process. In some embodiments, at least 80% of the methane consumed by the SMR, the cracker and the methane-consuming process is from the CH₄ stream. In some embodiments, the product stream comprises CO. In some embodiments, the product stream comprises CO₂. In some embodiments, the product stream comprises CO and CO₂. In some embodiments, the oxidizing agent comprises oxygen.

[0027] Another aspect of the present disclosure provides a system for producing methanol (MeOH) and hydrocarbon compounds containing at least two carbon atoms (C₂₊ compounds), comprising: an oxidative coupling of methane (OCM) reactor that (i) receives methane (CH₄) and an oxidizing agent and (ii) reacts the CH₄ and the oxidizing agent to yield a product stream comprising the C₂₊ compounds and un-reacted CH₄; a steam methane reformer (SMR) that (i) receives the un-reacted CH₄ separated from the product stream without use of a pre-reformer upstream of the SMR, and (ii) provides hydrogen (H₂) and carbon monoxide (CO) and/or CO₂; and an MeOH reactor that (i) receives the CO and/or CO₂ and (ii) reacts the CO and/or CO₂ to produce MeOH.

[0028] In some embodiments, the system further comprises a methanol to olefins (MTO) reactor that converts the MeOH to olefins. In some embodiments, the system further comprises a separations module that enriches olefins from the C₂₊ compounds and the olefins. In some embodiments, the system further comprises a separation unit downstream of the OCM reactor and upstream of the SMR, wherein the separation unit separates the un-reacted CH₄ from the product stream. In some embodiments, the SMR uses the un-reacted CH₄ as fuel. In some embodiments, the SMR uses the un-reacted CH₄ as a feedstock and converts the un-reacted CH₄ into the H₂ and the CO and/or CO₂ for conversion to MeOH in the MeOH reactor. In some embodiments, the MeOH reactor converts all of the CO and/or CO₂ from the product stream and

all of the CO and/or CO₂ from the SMR to MeOH. In some embodiments, at least about 95% of the methane is converted into MeOH or C₂₊ compounds. In some embodiments, the system further comprises a cracker that (i) receives the C₂₊ compounds and (ii) cracks or refines the C₂₊ compounds. In some embodiments, the un-reacted CH₄ directed to the SMR provides at least 80% of the methane consumed by the SMR. In some embodiments, the system further comprises a cracker that receives at least a portion of the unreacted CH₄. In some embodiments, at least 80% of the methane consumed by the SMR and the cracker is from the unreacted CH₄. In some embodiments, the system further comprises a methane-consuming module that receives the unreacted CH₄. In some embodiments, at least 80% of the methane consumed by the SMR, the cracker and the methane-consuming module is from the unreacted CH₄. In some embodiments, the product stream comprises CO. In some embodiments, the product stream comprises CO₂. In some embodiments, the product stream comprises CO and CO₂. In some embodiments, the oxidizing agent comprises oxygen.

[0029] Another aspect of the present disclosure provides a method for producing ethylene and methanol, the method comprising: (a) injecting a methane feedstream and an oxidizing agent-containing feedstream into an oxidative coupling of methane (OCM) subsystem that generates an OCM effluent stream containing ethylene, CO₂ and/or CO, and unconverted methane; (b) injecting the OCM effluent stream into a CO₂ separation subsystem that generates a stream containing CO₂ and a stream containing methane and ethylene; (c) injecting at least a portion of the stream containing CO₂ into a methanol synthesis subsystem; (d) injecting at least a portion of the stream containing methane and ethylene into a purification subsystem that generates a stream containing methane and a stream containing ethylene; and (e) injecting at least a portion of the stream containing methane into a steam methane reformer (SMR) subsystem, wherein the at least the portion of the stream containing methane is injected into the SMR subsystem without passing through a pre-reformer.

[0030] In some embodiments, the method further comprises, prior to (e), injecting the at least the portion of the stream containing methane into a hydrogenation subsystem. In some embodiments, the hydrogenation subsystem comprises a hydrogenation reactor. In some embodiments, the hydrogenation reactor hydrogenates acetylene. In some embodiments, the method further comprises injecting an oxygen-containing stream and a methane-containing stream into an autothermal reformer (ATR) that generates a stream containing CO and H₂. In some embodiments, the methane-containing stream is an effluent of the SMR subsystem. In some embodiments, the method further comprises injecting an effluent of the SMR subsystem into a heat recovery subsystem. In some embodiments, the method further comprises injecting an

effluent of the heat recovery subsystem into a syngas compressor subsystem. In some embodiments, the method further comprises injecting an effluent of the syngas compressor subsystem into the methanol synthesis subsystem. In some embodiments, the method further comprises injecting an effluent of the methanol synthesis subsystem into a product recovery subsystem. In some embodiments, the product recovery subsystem comprises one or more distillation columns. In some embodiments, the method further comprises injecting at least a portion of an effluent of the methanol synthesis subsystem into the SMR subsystem. In some embodiments, the method further comprises injecting the methane feedstream into a desulfurization subsystem prior to (a). In some embodiments, having a methanol production rate that is increased by at least about 10% relative to a method that does not comprise injecting a stream containing methane into an oxidative coupling of methane (OCM) subsystem. In some embodiments, the CO₂ that is injected into the methanol synthesis subsystem reacts with H₂ to produce methanol. In some embodiments, the method further comprises heating the SMR subsystem using at least a portion of the stream containing methane generated in (d). In some embodiments, the oxidizing agent-containing feedstream comprises oxygen.

[0031] Another aspect of the present disclosure provides a method for producing olefins, comprising: (a) directing methane (CH₄) and an oxidizing agent into an oxidative coupling of methane (OCM) reactor to produce a product stream comprising the C₂₊ compounds including olefins, carbon monoxide (CO) and/or carbon dioxide (CO₂), and un-reacted CH₄; (b) enriching the CO and/or CO₂ from the product stream to generate an enriched CO and/or CO₂ stream; (c) directing the enriched CO and/or CO₂ stream to an MeOH reactor to produce MeOH; (d) directing at least some of the MeOH to a methanol to olefins (MTO) reactor to produce a second olefins stream; (e) enriching the un-reacted CH₄ from the product stream to produce an enriched CH₄ stream; and (f) directing at least a portion of the enriched CH₄ stream to a steam methane reformer (SMR) that produces hydrogen (H₂) and CO and/or CO₂.

[0032] In some embodiments, the method further comprises recovering olefins from the product stream and the second olefins stream. In some embodiments, the method further comprises directing CO and/or CO₂ produced in the SMR to the MeOH reactor. In some embodiments, all of the CO and/or CO₂ from the product stream and all of the CO and/or CO₂ from the SMR is converted to MeOH in the MeOH reactor. In some embodiments, the un-reacted CH₄ is provided as fuel to the SMR. In some embodiments, the un-reacted CH₄ is provided as feedstock to the SMR, and wherein the SMR converts the un-reacted CH₄ into the H₂ and the at least one of CO and CO₂ for conversion to MeOH in the MeOH reactor. In some embodiments, at least about 95% of the methane is converted into MeOH or C₂₊ products. In some embodiments, the method

further comprises providing the C_{2+} compounds to a cracker that cracks or refines the C_{2+} compounds. In some embodiments, at least 80% of the methane consumed by the SMR is from the enriched CH_4 stream. In some embodiments, the method further comprises directing a portion of the enriched CH_4 stream to a cracker. In some embodiments, at least 80% of the methane consumed by the SMR and the cracker is from the enriched CH_4 stream. In some embodiments, the method further comprises directing at least a portion of the enriched CH_4 stream to a methane-consuming process. In some embodiments, at least 80% of the methane consumed by the SMR, the cracker and the methane-consuming process is from the enriched CH_4 stream. In some embodiments, the product stream comprises CO. In some embodiments, the product stream comprises CO_2 . In some embodiments, the product stream comprises CO and CO_2 . In some embodiments, the oxidizing agent comprises oxygen.

[0033] Another aspect of the present disclosure provides a system for producing olefins, comprising: an oxidative coupling of methane (OCM) reactor that (i) receives methane (CH_4) and an oxidizing agent and (ii) reacts the CH_4 and the oxidizing agent to yield a product stream comprising the C_{2+} compounds including olefins, carbon monoxide (CO) and/or carbon dioxide (CO_2), and un-reacted CH_4 ; an MeOH reactor that (i) receives CO and/or CO_2 enriched from the product stream and (ii) reacts the CO and/or CO_2 to produce MeOH; a methanol to olefins (MTO) reactor that converts at least some of the MeOH into olefins to produce a second olefins stream; and a steam methane reformer (SMR) that (i) receives un-reacted CH_4 enriched from the product stream and (ii) provides hydrogen (H_2) and at least one of carbon monoxide (CO) and CO_2 to the MeOH reactor to produce MeOH.

[0034] In some embodiments, the system further comprises a separations module that enriches olefins from the product stream and the second olefins stream. In some embodiments, the system further comprises a separation unit downstream of the OCM reactor and upstream of the MeOH reactor, wherein the separation unit enriches the CO and/or CO_2 from the product stream. In some embodiments, the system further comprises a separation unit downstream of the OCM reactor and upstream of the SMR, wherein the separation unit enriches the un-reacted CH_4 from the product stream. In some embodiments, the SMR uses the un-reacted CH_4 as fuel. In some embodiments, the SMR uses the un-reacted CH_4 as a feedstock and converts the un-reacted CH_4 into the H_2 and the at least one of CO and CO_2 for conversion to MeOH in the MeOH reactor. In some embodiments, the MeOH reactor converts all of the CO_2 from the product stream and all of the CO_2 from the SMR to MeOH. In some embodiments, at least about 95% of the methane is converted into MeOH or C_{2+} products. In some embodiments, the system further comprises a cracker that (i) receives the C_{2+} compounds and (ii) cracks or refines the C_{2+} compounds. In

some embodiments, the un-reacted CH_4 directed to the SMR provides at least 80% of the methane consumed by the SMR. In some embodiments, the system further comprises a cracker that receives at least a portion of the unreacted CH_4 . In some embodiments, at least 80% of the methane consumed by the SMR and the cracker is from the unreacted CH_4 . In some embodiments, the system further comprises a methane-consuming module that receives the enriched CH_4 . In some embodiments, at least 80% of the methane consumed by the SMR, the cracker and the methane-consuming module is from the unreacted CH_4 . In some embodiments, the product stream comprises CO. In some embodiments, the product stream comprises CO_2 . In some embodiments, the product stream comprises CO and CO_2 . In some embodiments, the oxidizing agent comprises oxygen.

[0035] Another aspect of the present disclosure provides a method for producing propylene, the method comprising: (a) feeding propane into a propane dehydrogenation (PDH) process, which PDH process converts the propane into hydrocarbon compounds with three or more carbon atoms (C_{3+} compounds) including propylene and PDH off-gas, which PDH off-gas comprises hydrocarbon compounds with one carbon atom (C_1 compounds), hydrocarbon compounds with two carbon atoms (C_2 compounds) and hydrogen (H_2); (b) feeding the PDH off-gas into an oxidative coupling of methane (OCM) process, which OCM process converts the C_1 compounds into ethylene, wherein the OCM process releases heat; and (c) providing the heat to the PDH process.

[0036] In some embodiments, the method further comprises converting the H_2 to methane in a methanation reactor in the OCM process. In some embodiments, the method further comprises generating from the C_{3+} compounds a propylene stream comprising the propylene, wherein a concentration of the propylene in the propylene stream is greater than a concentration of the propylene in a stream comprising the C_{3+} compounds. In some embodiments, the method further comprises polymerizing the propylene to produce polypropylene. In some embodiments, the method further comprises copolymerizing the propylene with the ethylene produced from the OCM process to produce poly(ethylene-co-propylene). In some embodiments, the OCM process also produces propylene or butene-1. In some embodiments, the method further comprises producing polypropylene and/or poly(propylene-co-1-butene) using the propylene or the butene-1 from the OCM process and/or the propylene from the PDH process. In some embodiments, the method further comprises diverting at least a portion of the propane from the PDH process to the OCM process. In some embodiments, the PDH process is integrated with the OCM process, and wherein the integration of reduces an amount of natural gas needed to provide heat to the PDH process as compared with an amount of natural gas needed for the PDH process in the absence of

the integration. In some embodiments, at least about 85% of carbon atoms input into the PDH and the OCM process is converted to propylene, ethylene or polypropylene.

[0037] Another aspect of the present disclosure provides a system, comprising: a cracking reactor that receives a hydrocarbon feedstream comprising feedstream hydrocarbons and, with the aid of a cracking catalyst, facilitates cracking of the feedstream hydrocarbons to produce a cracked stream comprising cracked hydrocarbons, wherein the cracked hydrocarbons have a lower molecular weight than the feedstream hydrocarbons; a separations unit in fluid communication with the cracking reactor, wherein the first separations unit receives the cracked stream and separates the cracked hydrocarbons of the cracked stream into a plurality of streams including a methane-containing stream comprising methane; and an oxidative coupling of methane (OCM) reactor in fluid communication with the separations unit, wherein the OCM reactor receives the methane-containing stream and, with the aid of an OCM catalyst, converts the methane from the methane-containing stream to higher hydrocarbon products to yield an OCM product stream comprising the higher hydrocarbon products.

[0038] In some embodiments, the system further comprises one or more additional units between the cracking reactor and the separations unit or between the separations unit and the OCM reactor.

[0039] Another aspect of the present disclosure provides a method, comprising: (a) directing a hydrocarbon feedstream comprising feedstream hydrocarbons into a cracking reactor comprising a cracking catalyst that facilitates cracking of the feedstream hydrocarbons, to produce a cracked stream comprising cracked hydrocarbons, wherein the cracked hydrocarbons have a lower molecular weight than the feedstream hydrocarbons; (b) directing the cracked stream into a separations unit that separates the cracked hydrocarbons from the cracked stream into a plurality of streams including a methane-containing stream comprising methane; and (c) directing the methane-containing stream into an oxidative coupling of methane (OCM) reactor comprising an OCM catalyst that facilitates conversion of the methane from the methane-containing stream to higher hydrocarbon products to yield an OCM product stream comprising the higher hydrocarbon products.

[0040] In some embodiments, (i) the cracked stream is directed from the cracking reactor to the separations unit through one or more additional units or (ii) the methane-containing stream is directed from the separations unit to the OCM reactor through one or more additional units.

[0041] Additional aspects and advantages of the present disclosure will become readily apparent to those skilled in this art from the following detailed description, wherein only illustrative embodiments of the present disclosure are shown and described. As will be realized, the present

disclosure is capable of other and different embodiments, and its several details are capable of modifications in various obvious respects, all without departing from the disclosure.

Accordingly, the drawings and description are to be regarded as illustrative in nature, and not as restrictive.

INCORPORATION BY REFERENCE

[0042] All publications, patents, and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication, patent, or patent application was specifically and individually indicated to be incorporated by reference.

BRIEF DESCRIPTION OF THE FIGURES

[0043] The novel features of the invention are set forth with particularity in the appended claims. A better understanding of the features and advantages of the present invention will be obtained by reference to the following detailed description that sets forth illustrative embodiments, in which the principles of the invention are utilized, and the accompanying drawings or figures (also “FIG.” and “FIGs.” herein), of which:

[0044] FIG. 1 shows an example process for converting methane into propylene using an oxidative coupling of methane (OCM), dimerization, and metathesis of ethylene and butenes;

[0045] FIG. 2 shows an example process for converting methane into propylene using an oxidative coupling of methane (OCM), dimerization, and metathesis of butenes;

[0046] FIG. 3 shows an example process for converting methane into propylene using an oxidative coupling of methane (OCM), vacuum pressure swing adsorption (VPSA), dimerization, and metathesis of butenes;

[0047] FIG. 4 shows an example process of using an offgas of a cracking unit as a feedstock for an oxidative coupling of methane (OCM) system;

[0048] FIG. 5 shows an example process of using an offgas of a cracking unit as a feedstock for an oxidative coupling of methane (OCM) system without the use of a process gas compressor;

[0049] FIG. 6 shows an example process of using an offgas of a cracking unit as a feedstock for an oxidative coupling of methane (OCM) system without the use of a process gas compressor or a pressure swing adsorption (PSA) unit;

[0050] FIG. 7 shows an example system for using an offgas of a high severity fluidized catalytic cracker (HS-FCC) subsystem in tandem with an oxidative coupling of methane (OCM) subsystem;

[0051] **FIG. 8** shows an example system for using an offgas of a high severity fluidized catalytic cracker (HS-FCC) subsystem in tandem with an oxidative coupling of methane (OCM) subsystem which uses a pressure swing adsorption (PSA) unit to purify ethylene;

[0052] **FIG. 9A** shows an example of a propane dehydrogenation process;

[0053] **FIG. 9B** shows an example of a propane dehydrogenation process integrated with an OCM process;

[0054] **FIG. 9C** shows an example system for producing propylene through dehydrogenation of propane that is generated in an oxidative coupling of methane (OCM) process;

[0055] **FIG. 10** shows an example system for producing propylene through an integration of an oxidative coupling of methane subsystem, dimerization and metathesis subsystem, and a propane dehydrogenation subsystem;

[0056] **FIG. 11** is a schematic illustration of a methanol production process;

[0057] **FIG. 12** is a schematic illustration of OCM integrated with a methanol production process;

[0058] **FIG. 13** is a schematic illustration of a petrochemical complex with a methanol production process and a cracker;

[0059] **FIG. 14** is a schematic illustration of an integration of OCM with a methanol production process and a cracker;

[0060] **FIG. 15** is a schematic illustration of an integration of OCM with a methanol production process and a cracker;

[0061] **FIG. 16** is a schematic illustration of an integration of OCM with a methanol production process and a cracker;

[0062] **FIG. 17** is a schematic illustration of an integration of OCM with a methanol production process and a synloop;

[0063] **FIG. 18** is a schematic illustration of an integration of OCM with a MTO production process;

[0064] **FIG. 19** is a schematic illustration of an example oxidative coupling of methane (OCM) process;

[0065] **FIG. 20** is a schematic illustration of addition of ethane to an example OCM reactor;

[0066] **FIG. 21A** shows an example of a fluidized catalytic cracker (FCC) unit; **FIG. 21B** shows an example of a separations train; **FIG. 21C** shows an example of treatment of FCC off-gas;

[0067] **FIG. 22** shows an example of various ways of preparing an OCM feed and performing an OCM reaction using methane and olefins from the FCC;

[0068] **FIG. 23** shows an example of a delayed coking unit (DCU); and

[0069] FIG. 24 schematically illustrates a computer system that is programmed or otherwise configured to implement systems and methods of the present disclosure.

DETAILED DESCRIPTION

[0070] While various embodiments of the invention have been shown and described herein, it will be obvious to those skilled in the art that such embodiments are provided by way of example only. Numerous variations, changes, and substitutions may occur to those skilled in the art without departing from the invention. It should be understood that various alternatives to the embodiments of the invention described herein may be employed.

[0071] The terms “C₂₊” and “C₂₊ compound,” as used herein, generally refer to a compound comprising two or more carbon atoms, e.g., two carbon atoms (C₂), three carbon atoms (C₃), etc. C₂₊ compounds include, without limitation, alkanes, alkenes, alkynes and aromatics containing two or more carbon atoms. In some cases, C₂₊ compounds include aldehydes, ketones, esters and carboxylic acids. Examples of C₂₊ compounds include ethane, ethylene, acetylene, propane, propene, butane, butene, etc.

[0072] The term “C1-C3 hydrocarbons” refers to the molecular species that include hydrocarbons with one, two, or three carbon atoms. These include methane, ethane, ethylene, acetylene, propane, propylene, and propyne.

[0073] The term “non-C₂₊ impurities,” as used herein, generally refers to material that does not include C₂₊ compounds. Examples of non-C₂₊ impurities, include nitrogen (N₂), oxygen (O₂), water (H₂O), argon (Ar), hydrogen (H₂) carbon monoxide (CO), carbon dioxide (CO₂) and methane (CH₄).

[0074] The term “apparent selectivity,” as used herein, generally refers to the extent to which an alkane species with a given number of carbons is converted to an olefin with the same number of carbons (e.g. ethane conversion to ethylene, propane conversion to propylene, butane conversion to butene, etc.), and is expressed as a percentage.

[0075] The term “residence time,” as used herein, generally refers to the average length of time during which a substance is in a given location or condition, such as inside a reactor.

[0076] The term “unit,” as used herein, generally refers to a unit operation, which is a basic step in a process. Unit operations involve a physical change or chemical transformation, such as separation, crystallization, evaporation, filtration, polymerization, isomerization, transformation, and other reactions. A given process may require one or a plurality of unit operations to obtain the desired product from the starting materials, or feedstocks.

[0077] The term “higher hydrocarbon,” as used herein, generally refers to a higher molecular weight and/or higher chain hydrocarbon. A higher hydrocarbon can have a higher molecular weight and/or carbon content than starting material(s) in a given process (e.g., OCM or ETL). A higher hydrocarbon can be a higher molecular weight and/or chain hydrocarbon product that is generated in an OCM or ETL process. For example, ethylene is a higher hydrocarbon product relative to methane in an OCM process. As another example, a C₃₊ hydrocarbon is a higher hydrocarbon relative to ethylene in an ETL process. As another example, a C₅₊ hydrocarbon is a higher hydrocarbon relative to ethylene in an ETL process. In some cases, a higher hydrocarbon is a higher molecular weight hydrocarbon.

[0078] The term “OCM process,” as used herein, generally refers to a process that employs or substantially employs an oxidative coupling of methane (OCM) reaction. An OCM reaction can include the oxidation of methane to a higher hydrocarbon and water, and can involve an exothermic reaction. In an OCM reaction, methane can be partially oxidized and coupled to form one or more C₂₊ compounds, such as ethylene. In an example, an OCM reaction is $2\text{CH}_4 + \text{O}_2 \rightarrow \text{C}_2\text{H}_4 + 2\text{H}_2\text{O}$. An OCM reaction can yield C₂₊ compounds. An OCM reaction can be facilitated by a catalyst, such as a heterogeneous catalyst. Additional by-products of OCM reactions can include CO, CO₂, H₂, as well as hydrocarbons, such as, for example, ethane, propane, propene, butane, butene, and the like.

[0079] The term “item of value,” as used herein, generally refers to money, credit, a good or commodity (e.g., hydrocarbon). An item of value can be traded for another item of value.

[0080] The term “carbon efficiency,” as used herein, generally refers to the ratio of the number of moles of carbon present in all process input streams (in some cases including all hydrocarbon feedstocks, such as, e.g., natural gas and ethane and fuel streams) to the number of moles of carbon present in all commercially (or industrially) usable or marketable products of the process. Such products can include hydrocarbons that can be employed for various downstream uses, such as petrochemical or for use as commodity chemicals. Such products can exclude CO and CO₂. The products of the process can be marketable products, such as C₂₊ hydrocarbon products containing at least about 99% C₂₊ hydrocarbons and all sales gas or pipeline gas products containing at least about 90% methane. Process input streams can include input streams providing power for the operation of the process, such as with the aid of a turbine (e.g., steam turbine). In some cases, power for the operation of the process can be provided by heat liberated by an OCM reaction.

Propylene generation from Oxidative Coupling of Methane and Metathesis

[0081] An aspect of the present disclosure provides methods for integrating an oxidative coupling of methane (OCM) system with a dimerization system and a metathesis system. In this process, methane can be converted into ethylene in the oxidative coupling of methane reactor. The ethylene can be then used as a feedstock for dimerization into butenes, which can then be metathesized into propylene. A fraction of the butenes can later be recycled to the metathesis reactor.

[0082] The methane used for any of the processes described herein can come from any suitable source. In some cases, the feedstock for OCM (including methane and optionally ethane) come from the off-gas of a fluidic catalytic cracker (FCC). In some cases, it comes from coal in a coal to olefins (CTO) process. The methane can be gathered from coal beds, or produced from coal or any process utilizing coal.

[0083] **FIG. 1** shows the integration of an oxidative coupling of methane (OCM) system with a dimerization system and a metathesis system **100**. Inputs and outputs into respective units are indicated by arrows. The process **100** shows a source of methane **101** and a source of oxidizing agent **102** that are injected into an oxidative coupling of methane (OCM) reactor **103** in which the feeds are partially converted into ethylene, hydrogen (H_2), carbon dioxide (CO_2), carbon monoxide (CO), and unconverted methane (CH_4). The OCM reactor effluent can be injected into a heat recovery system **104** that cools the effluent stream, and can be then injected into a process gas compressor **105**, wherein the gas pressure can be increased. The pressurized process gas can be then injected into a CO_2 removal system **106**. There are two effluent streams from the CO_2 removal system **106**, including one CO_2 enriched stream and one hydrocarbon enriched stream. The hydrocarbon enriched stream can be injected into a distillation column **107** which can generate a stream comprising methane, a stream comprising C_2 hydrocarbons, and a stream comprising C_{3+} hydrocarbons. The CO_2 enriched stream from the CO_2 removal system **106** and the stream comprising methane from the distillation column **107** can then be injected into a methanation reactor **108**. The methanation reactor can convert CO_2 into methane. The effluent of the methanation reactor **108** can then be injected into the oxidative coupling of methane (OCM) reactor **103**. The stream comprising C_2 hydrocarbons that can be an effluent of the distillation column **107** can then be injected into a C_2 splitter **109**, which can separate ethylene from ethane. The ethane from the C_2 splitter **109** can then be injected into the oxidative coupling of methane (OCM) reactor **103**. The ethylene from the C_2 splitter **109** can then be injected into a dimerization reactor **110** and a metathesis reactor **112**. The dimerization reactor converts ethylene into butenes and higher molecular weight hydrocarbons, including 1-butene, 2-butene,

isobutene, and C₅₊ hydrocarbons. The effluent of the dimerization reactor **110** can then be injected into a debutenizer **111**, which can separate the C₅₊ components from butenes and species lighter than butenes. The butenes can then be injected into the metathesis reactor **112**, which reacts ethylene with butenes to generate propylene. The effluent of the metathesis reactor **112** can then be injected into a de-ethanizer **113**, which can separate ethylene from C₃₊ components. The ethylene from the de-ethanizer **113** can then be injected into the metathesis reactor **112** or the dimerization reactor **110**. The C₃₊ components from the de-ethanizer **113** can then be injected into a de-propanizer **114**, which can remove C₄₊ components from C₃ components. The C₄₊ components from the de-propanizer **114** can then be injected into the debutanizer **111**. The C₃ components from the de-propanizer **114** can then be injected into a C3 splitter **115**, which can separate propylene from propane.

[0084] The oxidizing agent that is injected into the oxidative coupling of methane reactor can be oxygen (O₂).

[0085] The oxidizing agent that is injected into the oxidative coupling of methane reactor can be hydrogen peroxide (H₂O₂).

[0086] The operating temperature of the oxidative coupling of methane (OCM) reactor can be at least about 200 °C°, at least about 300 °C°, at least about 400 °C, at least about 450 °C, at least about 500 °C, at least about 550 °C, at least about 600 °C, at least about 650 °C, at least about 700 °C, at least about 750 °C, at least about 800 °C, at least about 850 °C, or more.

[0087] The operating pressure of the oxidative coupling of methane reactor can be at least about 1 bar(g), at least about 2 bar (g), at least about 3 bar (g), at least about 4 bar (g), at least about 5 bar (g), at least about 6 bar (g), at least about 7 bar (g), at least about 8 bar (g), at least about 9 bar (g), at least about 10 bar (g), at least about 11 bar (g), at least about 12 bar (g), or more.

[0088] The concentration of ethylene in the effluent of the oxidative coupling of methane reactor can be at least about 1%, at least about 2%, at least about 3%, at least about 4%, at least about 5%, at least about 6%, at least about 7%, at least about 8%, at least about 9%, at least about 10%, at least about 11%, at least about 12%, at least about 13%, at least about 14%, at least about 15%, or more.

[0089] The fraction of ethylene that is generated in the oxidative coupling of methane (OCM) reactor that is injected into the dimerization reactor can be at least about 10%, at least about 20%, at least about 30%, at least about 40%, at least about 50%, at least about 60%, at least about 70%, at least about 80%, at least about 90%, or about 100%.

[0090] The fraction of the butenes that is generated in the dimerization reactor can be less than or equal to about 90%, 80%, 70%, 60%, 50%, 40%, 30%, 20%, 10%, 5% (vol%, wt%, or mol%) or less.

[0091] Of the butenes generated in the dimerization reactor, 1-butene or 2-butene account for at least about 10%, at least about 20%, at least about 30%, at least about 40%, at least about 50%, at least about 60%, at least about 70%, at least about 80%, at least about 90% (vol%, wt%, or mol%), or more of the total butenes.

[0092] The ethylene produced in the oxidative coupling of methane (OCM) reactor can be split between the dimerization reactor and the metathesis reactor, for example, about 90% is injected into the dimerization reactor and 10% is injected into the metathesis reactor, about 80% is injected into the dimerization reactor and 20% is injected into the metathesis reactor, about 70% is injected into the dimerization reactor and 30% is injected into the metathesis reactor, about 60% is injected into the dimerization reactor and 40% is injected into the metathesis reactor, about 50% is injected into the dimerization reactor and 50% is injected into the metathesis reactor, about 40% is injected into the dimerization reactor and 60% is injected into the metathesis reactor, about 30% is injected into the dimerization reactor and 70% is injected into the metathesis reactor, about 20% is injected into the dimerization reactor and 80% is injected into the metathesis reactor, or about 10% is injected into the dimerization reactor and 90% is injected into the metathesis reactor.

[0093] **FIG. 2** shows the integration of an oxidative coupling of methane (OCM) system with a dimerization system and a metathesis system **200**. Inputs and outputs into respective units are indicated by arrows. The process **200** shows a source of methane **201** and a source of oxidizing agent **202** that are injected into an oxidative coupling of methane (OCM) reactor **203** in which the feeds are partially converted into ethylene. The OCM reactor effluent can be injected into a heat recovery system **204** that cools the effluent stream, and can be then injected into a process gas compressor **205**, wherein the gas pressure can be increased. The pressurized process gas can be then injected into a CO₂ removal system **206**. There are two effluent streams from the CO₂ removal system **206**, including one CO₂ enriched stream and one hydrocarbon enriched stream. The hydrocarbon enriched stream can be injected into a distillation column **207** which can generate a stream comprising methane, a stream comprising C₂ hydrocarbons, and a stream comprising C₃₊ hydrocarbons. The CO₂ enriched stream from the CO₂ removal system **206** and the stream comprising methane from the distillation column **207** can then be injected into a methanation reactor **208**. The methanation reactor can convert CO₂ into methane. The effluent of the methanation reactor **208** can then be injected into the oxidative coupling of methane (OCM)

reactor **203**. The stream comprising C₂ hydrocarbons that is an effluent of the distillation column **207** can then be injected into a C₂ splitter **209**, which can separate ethylene from ethane. The ethane from the C₂ splitter **209** can then be injected into the oxidative coupling of methane (OCM) reactor **203**. The ethylene from the C₂ splitter **209** can then be injected into a dimerization reactor **210**. The dimerization reactor converts ethylene into butenes and higher molecular weight hydrocarbons, including 1-butene, 2-butene, isobutene, and C₅₊ hydrocarbons. The effluent of the dimerization reactor **210** can then be injected into a debutenizer **211**, which can separate the C₅₊ components from butenes and species lighter than butenes. The butenes can then be injected into the metathesis reactor **212**, which reacts ethylene with butenes to generate propylene. The effluent of the metathesis reactor **212** can then be injected into a de-ethanizer **213**, which can separate ethylene from C₃₊ components. The ethylene from the de-ethanizer **213** can then be injected into the dimerization reactor **210**. The C₃₊ components from the de-ethanizer **213** can then be injected into a de-propanizer **214**, which can remove C₄₊ components from C₃ components. A fraction of the C₄₊ components from the de-propanizer **214** can then be injected into the debutanizer **211**, while a fraction is not injected into the debutanizer. The C₃ components from the de-propanizer **214** can then be injected into a C₃ splitter **215**, which can separate propylene from propane.

[0094] The ethylene of the C₂ splitter can be injected into the dimerization reactor, wherein substantially no ethylene is injected into the metathesis reactor.

[0095] The fraction of butenes that are in the effluent of the de-propanizer which are recycled to the metathesis reactor can be less than or equal to about 90%, 80%, 70%, 60%, 50%, 40%, 30%, 20%, 10%, 5% (vol%, wt%, or mol%), or less.

[0096] The purity of the ethylene that is injected into the dimerization reactor can be at least about 10 mol%, at least about 20 mol%, at least about 30 mol%, at least about 40 mol%, at least about 50 mol%, at least about 60 mol%, at least about 70 mol%, at least about 80 mol%, at least about 90 mol%, at least about 95 mol%, at least about 99 mol%, at least about 99.5 mol%, at least about 99.9 mol%, or more.

[0097] In some embodiments, the conversion of ethylene to butenes in the dimerization reactor can be at least about 10%, at least about 20%, at least about 30%, at least about 40%, at least about 50%, at least about 60%, at least about 70%, at least about 80%, at least about 90%, at least about 95%, at least about 99%, or more.

[0098] In some embodiments, the unconverted ethylene that is in the effluent of the dimerization reactor can comprise substantially all of the ethylene that is injected into the metathesis reactor.

[0099] FIG. 3 shows a system for generating propylene, which integrates an oxidative coupling of methane (OCM) system with a vacuum pressure swing adsorption (VPSA) system, a dimerization system, and a metathesis system **300**. The process **300** shows a source of methane **301** and a source of oxidizing agent **302** that are injected into an oxidative coupling of methane (OCM) reactor **303** in which the feeds are partially converted into ethylene. The OCM reactor effluent can be injected into a heat recovery system **304** that cools the effluent stream, and can be then injected into a process gas compressor **305**, wherein the gas pressure can be increased. The pressurized process gas can be then injected into a CO₂ removal system **306**. There are two effluent streams from the CO₂ removal system **306**, including one CO₂ enriched stream and one hydrocarbon enriched stream. The hydrocarbon enriched stream can be injected into a vacuum pressure swing adsorption unit **307** which can generate a stream comprising methane and a stream comprising C₂₊ hydrocarbons. The stream containing C₂₊ hydrocarbons that can be an effluent of the vacuum pressure swing adsorption (VPSA) can be fed into a de-ethanizer **309** that separates C₂ components from C₃₊ components. The C₃₊ components from the de-ethanizer **309** are injected into a stabilizer **310**, which separates the C₅₊ components from C₃ and C₄ components. The C₃ and C₄ components that are in the effluent of the stabilizer **310** are injected into a de-propanizer **311**, which separates the C₃ components from the C₄ components. The C₃ components are then injected into a C3 splitter **314** which separates propylene from propane. The C₂ components from the de-ethanizer **309** are injected into a dimerization reactor **312** that converts ethylene into butenes. The butenes that are generated in the dimerization reactor **312** are then injected into a metathesis reactor **313** that converts butenes into propylene. The effluent of the metathesis reactor can be then injected into the de-ethanizer **309**.

[0100] In some embodiments, the vacuum pressure swing adsorption system produces an effluent stream that contains less than about 10% methane, less than about 8% methane, less than about 5% methane, less than about 3% methane, less than about 1% methane, less than about 0.5% methane, less than about 0.1% (vol%, wt%, or mol%) methane, or less.

[0101] The effluent stream of the C3 splitter may contain at least about 50%, at least about 60%, at least about 70%, at least about 80%, at least about 90%, at least about 95%, or at least about 99% (vol%, wt%, or mol%) of the propylene that is generated in the metathesis reactor.

[0102] In some embodiments, oxidative coupling of methane reactor contains a catalyst. OCM catalysts can serve as radicalization initiators. Examples of OCM catalysts can be found in U.S. Patent Publication Serial No. 2012/0041246, U.S. Patent No. 8,921,256, U.S. Patent Publication No. US 2015/0314267 or U.S. Patent Publication No. 2016/0074844, each of which is incorporated herein by reference in its entirety.

Olefin generation from Oxidative Coupling of Methane and Cracking

[0103] An aspect of the present disclosure provides methods for integrating an oxidative coupling of methane (OCM) process with a thermal cracking process that can be used to generate olefins, including ethylene and ethane. A transformation of a high molecular weight hydrocarbon stream to a stream with a lower average molecular weight can be accomplished by holding the stream at an elevated temperature for a given time. This transformation can occur without the presence of a solid catalyst. A fraction of the stream with a reduced average molecular weight is C1-C3 hydrocarbons. These C1-C3 hydrocarbons separate from higher molecular weight components and used as a feedstock for an oxidative coupling of methane (OCM) process.

[0104] **FIG. 4** shows a system for producing ethylene, which incorporates an oxidative coupling of methane (OCM) process with a thermal cracking process **400**. The process **400** shows a source of methane **401** and a source of oxidizing agent **402** that are injected into an oxidative coupling of methane (OCM) reactor **403** in which the feeds are partially converted into ethylene. The OCM reactor effluent can be injected into a heat recovery system **404** that cools the effluent stream, and can be then injected into a process gas compressor **405**, wherein the gas pressure can be increased. The pressurized process gas can be then injected into a CO₂ removal system **406**. There are two effluent streams from the CO₂ removal system **406**, including one CO₂ enriched stream and one hydrocarbon enriched stream. The hydrocarbon enriched stream can be injected into a pressure swing adsorption unit **407** which can generate a stream comprising methane and a stream comprising C₂₊ hydrocarbons. The stream containing methane can be injected into a methanation reactor **408**. The CO₂ enriched stream from the CO₂ removal system **406** can be also injected into the methanation reactor **408**. The hydrocarbon enriched stream that can be an effluent of the pressure swing adsorption unit **407** can be injected into a cracking subsystem, which includes separations units that can further purify the ethylene from the effluent gas.

[0105] **FIG. 5** shows a system for producing ethylene, which incorporates an oxidative coupling of methane (OCM) process with a thermal cracking process **500**. The process **500** shows a source of methane **501** and a source of oxidizing agent **502** that are injected into an oxidative coupling of methane (OCM) reactor **503** in which the feeds are partially converted into ethylene. The OCM reactor effluent can be injected into a heat recovery system **504**, wherein the temperature of the OCM effluent gas can be decreased. The cooled process gas can be then injected into a CO₂ removal system **505**. There are two effluent streams from the CO₂ removal system **505**, including one CO₂ enriched stream and one hydrocarbon enriched stream. The hydrocarbon enriched stream can be injected into a pressure swing adsorption unit **506** which

can generate a stream comprising methane and a stream comprising C₂₊ hydrocarbons. The stream containing methane can be injected into a methanation reactor **507**. The CO₂ enriched stream from the CO₂ removal system **507** can be also injected into the methanation reactor **507**. The hydrocarbon enriched stream that can be an effluent of the pressure swing adsorption unit **506** can be injected into a cracking subsystem, which includes separations units that can further purify the ethylene from the effluent gas.

[0106] FIG. 6 shows a system for producing ethylene, which incorporates an oxidative coupling of methane (OCM) process with a thermal cracking process **600**. The process **600** shows a source of methane **601** and a source of oxidizing agent **602** that are injected into an oxidative coupling of methane (OCM) reactor **603** in which the feeds are partially converted into ethylene. The OCM reactor effluent can be injected into a heat recovery system **604**, wherein the temperature of the OCM effluent gas can be decreased. The cooled process gas can be then injected into a CO₂ removal system **605**. There are two effluent streams from the CO₂ removal system **605**, including one CO₂ enriched stream and one hydrocarbon enriched stream. The hydrocarbon enriched stream can be injected into cracking plant **606** that includes further ethylene purification systems. The stream containing methane can be injected into a methanation reactor **607**. The CO₂ enriched stream from the CO₂ removal system **605** can be also injected into the methanation reactor **607**.

[0107] In some embodiments, the operating temperature of the thermal cracker can be at least about 300 °C°, at least about 400 °C°, at least about 500 °C, at least about 600 °C, at least about 700 °C, at least about 800 °C, at least about 900 °C, at least about 1000 °C, or more.

Olefin generation from OCM and High-Severity Fluidized Catalytic Cracking

[0108] An aspect of the present disclosure provides methods for integrating an oxidative coupling of methane (OCM) process with a high-severity fluidized catalytic cracking system that can be used to generate olefins, including ethylene and ethane. A transformation of a high molecular weight hydrocarbon stream to a stream with a lower average molecular weight can be accomplished by holding the stream at an elevated temperature for a given time. This transformation can occur in the presence of a solid catalyst that flows down the reactor. A high C1-C3 selectivity and a high olefin selectivity can be achieved through the use of high temperatures and low residence times. A fraction of the stream with a reduced average molecular weight is C1-C3 hydrocarbons. These C1-C3 hydrocarbons separate from higher molecular weight components and used as a feedstock for an oxidative coupling of methane (OCM) process.

[0109] High severity fluid catalytic cracking (FCC) can utilize traditional FCC technology under severe conditions (higher catalyst-to-oil ratios, higher steam injection rates, higher temperatures, etc.) in order to maximize the amount of propene and other light products. A high severity FCC unit can be fed with gas oils (paraffins) and residues, and can produce about 20–25 m% propene on feedstock together with greater volumes of motor gasoline and distillate byproducts.

[0110] FIG. 7 shows a system for producing ethylene, which incorporates an oxidative coupling of methane (OCM) process with a high-severity fluidized catalytic cracking system 700. The process 700 shows a source of methane 701 and a source of oxidizing agent 702 that are injected into an oxidative coupling of methane (OCM) reactor 703 in which the feeds are partially converted into ethylene. The OCM reactor effluent can be injected into a heat recovery system 704 that cools the effluent stream, and can be then injected into a process gas compressor 705, wherein the gas pressure can be increased. The pressurized process gas can be then injected into a CO₂ removal system 706. There are two effluent streams from the CO₂ removal system 706, including one CO₂ enriched stream and one hydrocarbon enriched stream. The hydrocarbon enriched stream can be injected into a demethanizer unit 707 which can generate a stream comprising methane and a stream comprising C₂+ hydrocarbons. The stream containing methane can be injected into a methanation reactor 708. The CO₂ enriched stream from the CO₂ removal system 706 can be also injected into the methanation reactor 708. The hydrocarbon enriched stream that can be an effluent of the demethanizer unit 707 can be injected into a high-severity fluidized catalytic cracking (HS-FCC) subsystem 709, which includes separations units that can further purify the ethylene from the effluent gas. The high-severity fluidized catalytic cracking (HS-FCC) subsystem has effluent streams that are injected into the OCM reactor 703. These effluent streams include a stream comprising propane, a stream comprising ethane, and a stream comprising methane. The stream comprising methane can be injected into a desulfurization unit 710 that removes sulfur from the methane stream. The desulfurized methane can be then injected into the demethanizer 707.

[0111] FIG. 8 shows a system for producing ethylene, which incorporates an oxidative coupling of methane (OCM) process with a high-severity fluidized catalytic cracking system 800. The process 800 shows a source of methane 801 and a source of oxidizing agent 802 that are injected into an oxidative coupling of methane (OCM) reactor 803 in which the feeds are partially converted into ethylene. The OCM reactor effluent can be injected into a heat recovery system 804 that cools the effluent stream, and can be then injected into a process gas compressor 805, wherein the gas pressure can be increased. The pressurized process gas can be then injected into a CO₂ removal system 806. There are two effluent streams from the CO₂ removal system

806, including one CO₂ enriched stream and one hydrocarbon enriched stream. The hydrocarbon enriched stream can be injected into a pressure swing adsorption (PSA) unit **807** which can generate a stream comprising methane and a stream comprising C₂+ hydrocarbons. The stream containing methane can be injected into a methanation reactor **808**. The CO₂ enriched stream from the CO₂ removal system **806** can be also injected into the methanation reactor **808**. The hydrocarbon enriched stream that can be an effluent of the PSA unit **807** can be injected into a high-severity fluidized catalytic cracking (HS-FCC) subsystem **809**, which includes separations units that can further purify the ethylene from the effluent gas. The high-severity fluidized catalytic cracking (HS-FCC) subsystem has effluent streams that are injected into the OCM reactor **803**. These effluent streams include a stream comprising propane, a stream comprising ethane, and a stream comprising methane. The stream comprising methane can be injected into a desulfurization unit **810** that removes sulfur from the methane stream. The desulfurized methane can be then injected into the demethanizer **807**.

[0112] The methane effluent from the HS-FCC unit may contain hydrogen sulfide (H₂S) or hydrogen disulfide (H₂S₂). The H₂S and/or H₂S₂ may be at a concentration of at least about 0.1 wt.%, at least about 0.5 wt.%, at least about 1 wt.%, at least about 2 wt.%, at least about 3 wt.%, at least about 4 wt.%, at least about 5 wt.%, at least about 7 wt.%, at least about 10 wt.%, at least about 12 wt.% or more.

[0113] In some embodiments, the high-severity fluidized catalytic cracker (HS-FCC) operates at a temperature of at least about 400 °C, at least about 450 °C, at least about 500 °C, at least about 550 °C, at least about 600 °C, at least about 650 °C, at least about 700 °C, at least about 750 °C, at least about 800 °C, at least about 850 °C, at least about 900 °C, or more.

[0114] The high-severity catalytic cracker (HS-FCC) may contain an HS-FCC catalyst. The HS-FCC catalyst may comprise a zeolite. The HS-FCC zeolite catalyst may comprise a ZSM-5 zeolite catalyst. The HS-FCC zeolite catalyst may comprise a high USY zeolite.

[0115] In some cases, the HS-FCC contains a catalyst that aids in the decrease of molecular weight of a hydrocarbon feedstock. This cracking reaction can take place in the gas phase, in some cases homogenously.

[0116] The high-severity fluidized catalytic cracker (HS-FCC) may operate with a residence time of less than about 10 seconds (s), less than about 5 seconds (s), less than about 4 seconds (s), less than about 3 seconds (s), less than about 2 seconds (s), less than about 1 second (s), less than about 0.5 seconds (s), less than about 0.2 seconds (s), less than about 0.1 seconds (s), or less. In some cases, the residence time is a period of time that passes between the feed stream entering the vessel and the cracked hydrocarbon stream exiting the vessel.

[0117] In some cases, the HS-FCC unit has a down-comer tube in which reactant and catalyst flows, which may be followed by recovery of the catalyst. In some cases, the catalyst is not fluidized.

Integrations of Oxidative Coupling of Methane with a Propane Dehydrogenation

[0118] In some cases, an OCM process is integrated with a propane dehydrogenation (PDH) process. The PDH process can convert propane into propene and by-product hydrogen. The propene from propane yield can be about 85 mass%. Reaction by-products (mainly hydrogen) can be used as fuel for the PDH reaction. As a result, propene may tend to be the only product, unless local demand exists for hydrogen. This route can be used in various regions, such as the Middle East, where there may be an abundance of propane from oil/gas operations. In this region, the propane output may be expected to be capable of supplying not only domestic needs, but also the demand from other regions (such as China), where many PDH projects may be scheduled to go on stream. The PDH process may be accomplished through different commercial technologies. Differences between these technologies may include catalysts employed, design of the reactor and strategies to achieve higher conversion rates.

[0119] The integration of the PDH process with an OCM process as described herein can increase the capacity of a PDH process by 40-100 kta in some cases. In some instances, all carbon contained in PDH off-gas can be converted to olefins via OCM and methanation, leading to nearly 100% propane utilization. In some cases, integrating an OCM process with the PDH process can lead to a stable plant capacity over PDH catalyst lifecycle because an increase in PDH off-gas can result in an increased capacity to OCM. The OCM unit can be designed to generate ethylene and butane-1 as co-products to be used as co-monomers in a polypropylene unit, which can enable production of all grades of polypropylene. In some cases, exothermicity of OCM can be used to produce steam and reduce overall firing in the PDH heaters, leading to overall higher carbon utilization in the process.

[0120] Turning attention to **FIG. 9A**, shown here is an example PDH plant with polypropylene (PP) production. Propane **900** can be fed into a PDH unit **902**, which can produce a C₃₊ fraction **904** and off-gas **906**. The off-gas can include C₁ molecules such as methane, carbon dioxide and carbon monoxide, as well as C₂ molecules such as ethane and ethylene, and hydrogen (H₂). The off-gas can be supplemented with natural gas **908** and burned to produce heat and steam **910** for the PDH unit. The C₃₊ product can be fractionated **912** to produce propylene **914**. The propylene can be polymerized in a polypropylene plant **916** to produce polypropylene **918**. One limitation of a PDH plant may be that performance decays over the lifetime of the catalyst, leading to a

drop in plant capacity before the catalyst can be replaced. About 90% of the propane may be utilized when natural gas is available as a fuel, but may be substantially less when the only fuel is PDH off-gas. Furthermore, without an exogenous supply of ethylene, the only polymer that can be made is homo-polypropylene, which is the lowest grade of polypropylene. These limitations can be alleviated by integrating PDH with an OCM process.

[0121] For example, **FIG. 9B** shows an example of OCM integrated with PDH. Dashed lines show optional streams. Some natural gas **920** and/or some propane **922** can be diverted into an OCM process **924**. The PDH off-gas **906** can also be fed into OCM. The OCM process may be exothermic, and can produce steam **926**. The OCM process can produce C₃₊ products that can be added to the propylene product **928** or further refined **930** to propylene if needed. The OCM process can also produce ethylene and/or butene-1, which can be used as a co-monomer **932** in the production of higher grade polypropylene products.

[0122] **FIG. 9C** shows an example system for producing propylene through dehydrogenation of propane that is generated in an oxidative coupling of methane process **940**. A source containing methane **941** and a source containing oxygen **942** can be injected into an oxidative coupling of methane subsystem **943**. The source containing methane can be from the off-gas of a fluidized catalytic cracker. The source containing oxygen can come from an air separation subunit. In some embodiments, the source containing oxygen is the same as the source of methane. Additionally, the source of methane can contain other hydrocarbons, *e.g.* ethane and propane. The oxidative coupling of methane subsystem can convert methane and oxygen into ethylene. The oxidative coupling of methane subsystem may also generate propylene. The oxidative coupling of methane subsystem may comprise a single reactor or multiple reactors. The oxidative coupling of methane subsystem may comprise one or more post-bed cracking units. The effluent of the OCM subsystem **947** can be injected into a separations subsystem **944** which can generate at least one stream comprising ethylene **949** and at least one stream comprising propylene and propane **948**. The separations subsystem can include one or more distillation columns, one or more adsorption subsystems, or combinations thereof. In some embodiments, an adsorption subsystem comprising a metal–organic framework material is used. In some embodiments, an adsorption subsystem comprising a zeolite material is used. The separation subsystem **944** can also comprise one or more units for separating CO₂ gas. The stream comprising propylene and propane **948** can then be injected into a separations subsystem **945** which can separate propylene from propane to generate a stream comprising propylene **950** and a stream comprising propane **951**. The separations subsystem **945** can include one or more distillation towers, one or more adsorption units, one or more membrane units, or combinations

thereof. The stream comprising propane **951** is injected into a propane dehydrogenation (PDH) unit **946** that converts propane into propylene and H₂.

[0123] FIG. 10 shows an example system for producing propylene through the integration of an oxidative coupling of methane subsystem, dimerization and metathesis subsystem, and a propane dehydrogenation subsystem **1000**. A source containing methane **1001** and a source containing oxygen **1002** are injected into an oxygen coupling of methane (OCM) subsystem **1003**. The source containing methane may be from a recycle loop within the example system **1000**. The source containing oxygen may be from an air separation subsystem. The air separation system may include one or more distillation columns, one or more adsorption subsystems, one or more membrane subsystems, or combinations thereof. The source containing methane may come from a fluidized catalytic cracker (FCC) system. The source containing methane may come from an offgas stream within a refinery. The source containing methane may come from natural gas. The source containing methane may also contain heavier hydrocarbons, *e.g.* ethane, ethylene, propane, propylene, and may also include additional components, *e.g.* water, N₂, CO₂, or CO. The source containing methane may be the same as the source containing oxygen. The source containing oxygen and the source containing methane may be mixed within a mixing apparatus separate from or within the OCM subsystem. The OCM subsystem may include an OCM catalyst. The OCM subsystem may include a post bed cracking (PBC) unit.

[0124] The effluent of the OCM subsystem is injected into process gas compressor (PGC) subsystem **1004**. The PGC subsystem can increase the pressure of the OCM effluent gas to generate a pressurized OCM effluent gas. The PGC subsystem can pressurize the gas to greater than 1 bar, greater than 2 bar, greater than 3 bar, greater than 4 bar, greater than 5 bar, greater than 6 bar, greater than 7 bar, greater than 10 bar, or greater than 15 bar. The pressurized OCM effluent gas can be injected into a CO₂ separation subsystem **1005**. The CO₂ separation subsystem can comprise one or more absorber units, one or more desorber units, one or more adsorption units, one or more membrane units, or combinations thereof. The CO₂ separation subsystem can produce a stream containing CO₂ **1017**, a stream containing CO₂ for recycle **1018**, and a stream containing methane **1019**. The stream containing methane may contain less than 1% CO₂, less than 0.5% CO₂, less than 0.1% CO₂, or less than 0.05% CO₂. The stream containing methane is injected into a demethanizer subsystem **1006**. The demethanizer subsystem may include one or more distillation columns, one or more adsorption units, one or more membrane units, or combinations thereof. The demethanizer subsystem generates a stream containing methane **1020** and a stream containing C₂₊ hydrocarbons. The stream containing methane may contain additional gases, *e.g.* CO, CO₂, H₂, N₂, Ar, or C₂H₂. The stream containing methane can

optionally be injected into a hydrogenation unit that converts C_2H_2 into C_2H_4 . The stream containing methane **1020** and the stream containing CO_2 for recycle **1018** are injected into a methanation subsystem **1007**. The methanation subsystem can contain a methanation catalyst. The methanation subsystem can convert H_2 and CO_2 into CH_4 . The effluent of the methanation subsystem **1021** can be the same as the source of methane **1001**. The effluent of the methanation subsystem is injected into the OCM subsystem **1003**. The OCM subsystem, PGC subsystem, CO_2 removal subsystem, demethanizer subsystem, methanation subsystem, and optional hydrogenation subsystem comprise an OCM recycle loop **1016**.

[0125] The effluent of the demethanizer subsystem that contains C_{2+} hydrocarbons is injected into a deethanizer subsystem **1008** that generates a stream containing ethylene and ethane **1021**, and a stream containing C_{3+} hydrocarbons **1027**. The stream containing ethylene and ethane **1021** is injected into a C_2 splitter **1009** that generates a stream containing ethane **1022** and a stream containing ethylene **1023**. The stream containing ethane **1022** can be mixed with the source containing methane **1001**. In some embodiments, the stream containing ethane is injected into the OCM subsystem **1003**, the PGC subsystem **1004**, or both. In some embodiments, the stream containing ethane is used as a fuel gas in another unit. The stream containing ethylene **1023** is split, with a portion of the stream being injected into a dimerization subsystem **1010** and another portion of the stream being diverted into a bypass loop **1024** and injected into a metathesis subsystem **1011**. The dimerization subsystem **1010** can convert ethylene into a stream containing butenes **1025**, with some of the butenes being 1-butene. The selectivity for 1-butene may be at least 1%, at least 5%, at least 10%, at least 20%, at least 30%, at least 40%, at least 50%, at least 60%, at least 70%, at least 80%, at least 90%, at least 95%, at least 99%, or at least 100%. The selectivity for 1-butene is the flow rate of 1-butene divided by the flow rate of all C_4 hydrocarbons in the effluent of the dimerization subsystem. The dimerization subsystem can contain one or more dimerization reactors. The one or more dimerization reactors can contain a dimerization catalyst. The dimerization catalyst may be a heterogeneous catalyst or a dissolved homogeneous catalyst. Of all the ethylene in the effluent of the C_2 splitter, at least 5%, at least 10%, at least 15%, at least 20%, at least 25%, at least 30%, at least 35%, at least 40%, at least 45%, or at least 50% may be injected into the dimerization subsystem. The stream containing butenes **1025** and the ethylene bypass loop **1024** are injected into a metathesis subsystem **1011** that generates a stream containing propylene **1026**. The metathesis subsystem may include one or more metathesis reactors. The metathesis reactors may include a metathesis catalyst. The conversion of butenes to propylene in the metathesis subsystem may be at least 10%, at least

20%, at least 30%, at least 40%, at least 50%, at least 60%, at least 70%, at least 80%, at least 90%, at least 95%, or at least 99%.

[0126] The stream containing C_{3+} hydrocarbons **1027** is injected into a depropanizer subsystem **1012** that generates a stream containing propylene and propane **1028** and a stream containing C_{4+} hydrocarbons **1034**. The depropanizer subsystem can include one or more distillation columns. The stream containing propylene and propane **1028** is injected into a C3 splitter subsystem **1013** that produces a stream containing propylene **1029** and a stream containing propane **1030**. The C3 splitter subsystem can include one or more distillation columns, one or more adsorbent units, one or more membrane units, or combinations thereof. The stream containing propane **1030** is injected into a propane dehydrogenation (PDH) subsystem **1014**. The PDH subsystem can dehydrogenate propane to generate a stream containing propylene **1030**, a stream containing propane **1031**, and a stream containing hydrogen and methane **1035**. The stream containing propylene coming from the PDH subsystem **1030** can be combined with the stream containing propylene coming from the metathesis subsystem **1026**. In some embodiments, the C3 splitter subsystem is contained within the PDH subsystem. The PDH subsystem can include one or more PDH reactors. The one or more PDH reactors can contain a PDH catalyst. The stream containing hydrogen and methane **1035** can optionally be combined with the offgas of a fluidized catalytic cracking (FCC) system. The stream containing hydrogen and methane **1035** is injected into a separation subsystem **1015** that separates hydrogen from methane. The separation subsystem **1015** can comprise one or more pressure swing adsorption units, one or more membrane units, or combinations thereof. The separation subsystem **1015** generates a stream containing hydrogen **1032** and a stream containing methane **1033**. The stream containing hydrogen **1032** can be used as a source of fuel gas, injected into the methanation reactor **1007**, or both. The stream containing methane **1033** is injected into the oxidative coupling of methane (OCM) subsystem **1003**.

[0127] The generation of additional hydrogen in the PDH subsystem increases the carbon efficiency of the OCM recycle loop **1016**. The carbon efficiency of the OCM recycle loop may be greater than 10%, greater than 20%, greater than 30%, greater than 40%, greater than about 50%, greater than about 60%, greater than about 70%, greater than about 75%, greater than about 80%, greater than about 85%, greater than about 90%, greater than about 95%, or greater than about 99%.

Integration of OCM Processes with Methanol Processes

[0128] There exists an infrastructure for chemical production throughout the world. This infrastructure is deployed on virtually every continent, addresses wide ranging industries, and employs a wide variety of different implementations of similar or widely differing technologies.

[0129] The present disclosure provides systems and methods for integrating OCM systems and methods with various chemical processes, such as methanol (MeOH) production, chlorine (Cl₂) and sodium hydroxide (NaOH) production (e.g., chloralkali process), vinylchloride monomer (VCM) production, ammonia (NH₃) production, processes having syngas (e.g., mixtures of hydrogen (H₂) and carbon monoxide (CO) in any proportion), or olefin derivative production.

[0130] As will be appreciated, the capital costs associated with each of the facility types described above can run from tens of millions to hundreds of millions of dollars each. Additionally, there are inputs and outputs, of these facilities, in terms of both energy and materials, which have additional costs associated with them, both financial and otherwise that may be further optimized in terms of cost and efficiency. Further, because different facilities tend to be optimized for the particularities (e.g., products, processing conditions) of the market in which they exist, they tend to be operated in an inflexible manner, in some cases without the flexibility or option to optimize for their given market. The present inventors have recognized surprising synergies when integrating OCM with the aforementioned chemical processes which can result in improved economics and/or operational flexibility.

[0131] In some cases, the OCM processes described herein are integrated with an olefin oligomerization process, such as an ethylene-to-liquids ("ETL") process as described in U.S. Patent No. 9,598,328, and U.S. Patent Publication No. 2015/0232395, the full disclosures of each of which are incorporated herein by reference in its entirety for all purposes.

[0132] In some instances, the OCM process can be sized to fit the needs of an ethylene derivatives plant. Such a synergy can liberate the derivatives producer from being a merchant buyer of ethylene, allowing the producer more ethylene cost and supply certainty. Examples of ethylene derivatives include polyethylene, including low-density polyethylene (LDPE), linear low-density polyethylene (LLDPE), and high-density polyethylene (HDPE). Additional ethylene derivatives include ethylbenzene, styrene, acetic acid, vinylacetate monomer, ethylene dichloride, vinylchloride monomer, ethylene oxide and alpha olefins.

[0133] The OCM processes can be integrated with methanol production processes to realize unexpected synergies potentially including, but not limited to (a) additional methanol capacity with minimal or no modification to the methanol plant and (b) additional ethylene capacity with low investment and environmental footprint.

[0134] FIG. 11 shows an example of a block flow diagram of a methanol plant (e.g., a traditional methanol process, recognizing that alternate embodiments are allowed and details have been omitted for clarity). As shown, natural gas 300 can be used for feed and fuel for the process. The feed 302 (e.g., natural gas providing the carbon atoms for the methanol product) can have sulfur-containing compounds removed in a de-sulfurization module 304 before being fed into a steam methane reformer (SMR, entire gray shaded unit) 306. The SMR can also accept natural gas as fuel 308 (e.g., natural gas providing energy for the methanol plant), which does not necessarily have to be de-sulfurized. The effluent of the steam methane reformer is syngas, which can have heat recovered in a heat recovery module 310 and compressed in a compression module 312. Compressed syngas can be fed into the synthesis module 314 where conversion to methanol occurs. One suitable methanol synthesis module can have a catalyst that is a mixture of copper, zinc, and alumina, and operates at a pressure between about 50 and about 100 atmospheres and a temperature of about 250 °C. The production of syngas produces 3 moles of H₂ per mol of CH₄, while the stoichiometry of methanol formation from syngas consumes only 2 moles of H₂. Thus, excess H₂ (and un-reacted CH₄) can be purged 316 from the synthesis module and separated in a gas separation module 318 (e.g., a pressure swing adsorber). The separation module can produce additional fuel 320 for the SMR and a H₂ co-product 322. The methanol product 324 can be enriched (e.g., by a distillation module 326). In some cases, the excess H₂ is used as fuel (not shown).

[0135] A combined process that integrates OCM with methanol production is shown in FIG. 4, where like numerals represent like elements. The OCM portion of the combined process can accept the de-sulfurized natural gas feedstock 414 and include an OCM reaction module 400, a process gas compression module 402, a CO₂ removal module (e.g., process gas cleanup) 404, a drying module 406 and a separations module (e.g., a cryogenic de-methanizer) 408. In some cases, the separation module produces the C₂₊ compounds 410. The C₂₊ compounds can be further refined, and/or sent to a cracker (e.g., to the separation section of a cracker). Note that the OCM process does not require a methanation module. The OCM reaction can produce high-pressure super-heated (HPSH) steam 412 that can be used in the process and/or to produce power using a steam turbine.

[0136] Continuing with FIG. 12, the OCM portion of the process can produce a stream of methane that was not converted to C₂₊ compounds 416 in the OCM reaction. This stream 416 can have H₂ and CO in addition to methane and can be used as the feed to the methanol production process (e.g., at the SMR) and/or as fuel to the process (dashed line) 418. The stream of CO₂ 420 from the OCM process can also be used in the methanol synthesis module 314 to

produce one mole of methanol and one mole of water from one mole of CO₂ and 3 moles of H₂. The water co-product can be removed in the distillation module **326**.

[0137] The combined OCM-methanol process has considerable economic and environmental benefits. In some cases, CO₂ from OCM **420** can be used to re-balance the make-up gas to the synthesis module and convert some or all of the excess H₂ to methanol (e.g., the flow-rate of stream **322** can be zero or very small in comparison to the flow rate without OCM integration). Furthermore, the reformer **306** capacity can be automatically increased due to the "pre-formed" nature of the OCM demethanizer overhead **416** stream (e.g., already contains some H₂ and CO). This can be useful for replacing a mixed feed coil. In some instances, the only cost associated with the production of extra methanol due to OCM integration is the loss in value of the H₂ co-product **322** in situations where that stream is actually monetized or monetizable. Such integration schemes can result in improved efficiency of an existing methanol system, for example by using excess H₂ by reacting it with CO₂ produced from an OCM unit to produce a more valuable methanol product. Depending on the capacity of the OCM process, an integrated OCM-methanol system can be pushed to a low emission, high carbon efficiency process.

[0138] When retrofitting an existing methanol plant, the OCM process can be sized to the desired amount of extra methanol production. From the OCM perspective, building an OCM process to be integrated with a methanol plant can require significantly less capital than building a stand-alone OCM process, e.g., due to reducing or eliminating the need for fractionation and methanation equipment. The OCM process can also use the utilities of the existing methanol plants, such as steam. In some cases, the combined process produces zero or a minimal amount of NO_x and SO_x compounds.

[0139] The combined OCM-methanol process can be about 100% carbon efficient (e.g., with reference to **FIG. 13**, all of the carbon atoms input to the process **300** end up in the methanol **324** or the C₂₊ compounds **410**). In some cases, the combined process is less than 100% carbon efficient, e.g., greater than or equal to about 99%, greater than or equal to about 98%, greater than or equal to about 97%, greater than or equal to about 96%, greater than or equal to about 95%, greater than or equal to about 93%, greater than or equal to about 90%, greater than or equal to about 85%, greater than or equal to about 80%, or greater than or equal to about 75% carbon efficient.

[0140] In some cases, with reference to **FIG. 5**, methanol plants **500** are located in proximity to crackers **502** and/or other processes **504** that use natural gas (e.g., within 1, 5, 10, 20, 50, 100, 200 miles or more). In some cases, these processes share a piping infrastructure and/or can access a piping infrastructure for transporting natural gas, ethylene, hydrogen and other

chemicals. These processes can convert the natural gas **506** into a combination of methanol **508**, hydrogen **510**, ethylene **512**, and other products **514**. OCM can be integrated with any combination of these processes (e.g., **500**, **502** and **504**) in a number of ways as shown in **FIG. 6**, **FIG. 7** and **FIG. 8**.

[0141] **FIG. 14** shows a "minimum revamp case" where an OCM process **600** accepts natural gas **506** and provides CO₂ **602** to a methanol process **500** and crude ethylene **604** to a cracker **502**. The ethylene can be refined to a finished product (e.g., polymer grade ethylene) **512** using the fractionation capacity of the cracker. In this case, the OCM process can be sized to accept an amount of natural gas that is substantially equivalent to the methanol plant natural gas input (e.g., about 60 to 70 MMSCFD). This OCM capacity can result in about 25-30 kTa additional ethylene and about 15% to 20% additional methanol produced. In some cases, for the minimum revamp case, the only capital investment is for the OCM unit **600** and in some cases mixed feed coil replacement in the SMR.

[0142] **FIG. 15** shows a "medium revamp case" where an OCM process **700** accepts natural gas **506** and provides CO₂ **702** to a methanol process **500** and crude ethylene **704** to a cracker **502**. In this case, the OCM process can be sized to accept an amount of natural gas that is substantially equivalent to the methanol plant natural gas input **706** and cracker fuel input **708** (e.g., about 140 to 150 MMSCFD). This OCM capacity can result in about 60-80 kTa additional ethylene and about 30% to 40% additional methanol produced. In some cases, for the medium revamp case, capital investment is needed for the OCM unit **700** and methanol debottlenecking (e.g., reformer, syngas compressor, synthesis module and topping column).

[0143] **FIG. 16** shows a "maximum efficiency revamp case" where the size of the OCM process is not constrained. For example, all of the natural gas entering an entire petrochemical complex can be skimmed. An OCM process **800** accepts natural gas **506** and provides CO₂ **802** to a new methanol synthesis module **804**. In some cases, the new methanol synthesis module **804** accepts H₂ **806** from various sources including an existing methanol process **500** and/or a cracker **502**. The new methanol synthesis module **804** can provide crude methanol **808** to the existing methanol process for refining to a methanol product **508**. As in the other revamp scenarios, crude ethylene **810** can be refined in a cracker **502**. In some cases, the OCM results in about 150-200 kTa additional ethylene, the integration results in about 60% to 70% additional methanol produced. In some cases, for the maximum efficiency revamp case, capital investment is needed for the OCM unit, a new methanol synthesis module (fed with the excess H₂ across the entire complex and CO₂ from OCM) and in some cases debottlenecking of methanol distillation. The various revamp cases are not mutually exclusive and can be designed as successive project

phases. In addition, larger capacity plants can be combined with larger methanol production plants.

[0144] FIG 17 shows a schematic illustration of an integration of OCM with a methanol production process and a synloop 1700. A stream containing methane 1701 is injected into a desulfurization subsystem 1702 that removes sulfur from the stream containing methane. The stream containing methane can be natural gas. The desulfurization subsystem can include one or more hydrodesulfurization reactors. The desulfurization subsystem can include one or more adsorbent units. The effluent of the desulfurization subsystem and a stream containing oxygen 1703 is injected into an oxidative coupling of methane (OCM) subsystem 1704. The oxidative coupling of methane subsystem can contain an oxidative coupling of methane (OCM) catalyst. The oxidative coupling of methane subsystem can comprise one or more post-bed cracking (PBC) units. The oxidative coupling of methane (OCM) subsystem can generate an OCM effluent stream containing ethylene, CO₂ and/or CO, and unconverted methane. The OCM effluent stream is injected into a process gas compressor (PGC) subsystem 1705 that elevates the pressure of the gas to produce a pressurized oxidative coupling of methane (OCM) effluent. The pressurized OCM effluent is injected into a separation subsystem 1706 that removes CO₂ from the pressurized OCM effluent to generate a stream containing CO₂ and a stream containing ethylene and methane. The separation subsystem can comprise one or more absorber units, one or more adsorber units, one or more distillation columns, or combinations thereof. The stream containing ethylene and methane is injected into a purification subsystem 1707 that generates a stream containing methane and a stream containing ethylene. The purification subsystem can comprise one or more distillation columns, one or more adsorbent units, one or more membrane units, or combinations thereof. The stream containing ethylene can also include ethane and hydrocarbons with three or more carbon atoms (C₃₊ hydrocarbons). The stream containing ethylene is injected into a separation subsystem 1708 that generates a stream containing ethylene 1713.

[0145] The stream containing methane that is the effluent of the purification subsystem 1707 is injected into a hydrogenation subsystem 1715. The hydrogenation subsystem can contain one or more hydrogenation reactors. The one or more hydrogenation reactors can contain a hydrogenation catalyst. The hydrogenation subsystem can hydrogenate acetylene. The effluent of the hydrogenation subsystem contains CO and/or CO₂. The effluent of the hydrogenation subsystem is injected into a steam methane reformer (SMR) subsystem 1709, without be injected into a pre-reformer. The pre-reformer may otherwise generate CO and H₂ from hydrocarbons before entering the steam methane reformer (SMR) subsystem. The steam methane reformer

subsystem can convert water and methane into a syngas stream that comprises CO and H₂. The syngas stream is injected into a heat recovery subsystem 1710 that removes heat from the syngas stream. The effluent of the heat recovery subsystem is injected into a syngas compressor subsystem 1711 that increases the pressure of the syngas stream to produce a pressurized syngas stream. The pressurized syngas stream is injected into a methanol synthesis subsystem 1712 that at least partially converts CO and H₂ into methanol. The CO₂ that is generated in the separation subsystem 1706 is also injected into the methanol synthesis subsystem. The methanol synthesis subsystem can also include one or more water gas shift reactors. The one or more water gas shift reactors can convert CO₂ and H₂ into CO and water. The methanol synthesis subsystem can produce an offgas. The offgas can be comprised of methane, CO, CO₂, H₂ or combinations thereof. The offgas is injected into the steam methane reformer subsystem. The offgas can be used as a fuel to heat the steam methane reformer subsystem, or can be used as a feedstock for the steam methane reformer subsystem, or both. The methanol synthesis subsystem can also produce non-methanol impurities. At least a portion of the effluent of the methanol synthesis subsystem is injected into a product recovery subsystem 1712 to produce a methanol stream 1714. The product recovery subsystem can include one or more distillation columns.

[0146] The source of oxygen 1703 can also be used in an autothermal reformer (ATR) subsystem that converts methane and oxygen into CO and H₂. The ATR subsystem can use the effluent of the steam methane reformer (SMR) subsystem as a source of methane, or can use a separate source of methane, or both.

Integration of OCM Processes with Methanol to Olefins (MTO) Processes

[0147] Methanol-to-Olefins/Methanol-to-Propene may convert synthesis gas (syngas) to methanol, and then convert the methanol to ethylene and/or propene. The process may produce water as by-product. Synthesis gas may be produced from the reformation of natural gas or by the steam-induced reformation of petroleum products such as naphtha, or by gasification of coal.

[0148] Application of an MTO process may use acidic zeolite catalysts. The conversion of methanol to olefins on acidic zeolites may take place through a complex network of chemical reactions. The distribution of products and thus the “selectivity” may depend on the temperature, among other factors. Selectivity may be a measure of the amount of one product produced relative to others when the possibility to form multiple products exists. Selectivity may depend on temperature through the Arrhenius law for the different rate constants.

[0149] In some cases, at lower temperatures methanol reacts to form dimethyl ether (DME). At higher temperatures, the desired products (olefins) may be produced and the selectivity for DME may decrease.

[0150] In some cases, the methanol can be converted to olefins using a methanol to olefins (MTO) process. The OCM process can be integrated with an MTO process to realize certain synergies. The carbon efficiency of the combined process can be greater than either of the processes individually. For example, in the combined process, at least about 80%, at least about 85%, at least about 90%, at least about 95%, at least about 98%, at least about 99%, at least about 99.5%, or at least about 99.9% of the feedstock carbon can be converted to final products. In some cases, a single air separations unit (ASU) can be used for both the methanol/MTO and the OCM processes. In some cases, a single separations and/or olefin purification train can be used for both the methanol/MTO and the OCM processes. In some cases, a single utility train can be used for both the methanol/MTO and the OCM processes (*i.e.*, with tight energy integration).

[0151] In some embodiments, the combined OCM and methanol/MTO process can share a separations train (*e.g.*, cryogenic distillation). Because of this synergy, the combined process can achieve increased capacity with essentially the same equipment. In MTO, the syngas train represents the most capital intensive area of the process. Combo-reforming can be used to achieve the ideal syngas composition for methanol synthesis. In some cases, combo-reforming is needed to achieve greater than 5,000 metric ton per day (MTD) methanol capacity on a single train. In some instances, olefin conversion technology (OCT), which involves converting C₄₊ into ethylene and propylene, can be used to increase the carbon yield of light olefins.

[0152] Referring to **FIG. 18**, natural gas **1800** and oxygen **1802** can be fed into an OCM reactor **1804**, optionally with additional C₂-C₄ feed **1806**. Some of the oxygen can also be fed into the methanol process, *e.g.*, at the ATR or SMR **1808**. A first separation module **1810** can separate light gasses **1812** (having, *e.g.*, CH₄, CO and H₂) from an ethylene-rich stream **1814**. The first separation module does not need to produce purity or enriched ethylene. In some cases, the first separation module includes a PSA. The separations module can also produce a CO₂ stream **1816**, that can be sent to the MeOH synthesis module **1818**. The MeOH can then be fed to a MTO unit **1820** to produce olefins **1822**. The olefins from the MTO process **1822** and from the OCM process **1814** can be combined and recovered in an olefin recovery module **1824**. The olefin recovery module can produce an ethylene product stream **1826**, a propylene product stream **1828**, and fuel gas **1830**. In some cases, C₄₊ products can be sent to an olefin conversion

technology unit **1832** to be converted to additional ethylene and propylene, and in some cases a byproduct **1834**.

[0153] In another aspect, provided herein is a method for producing olefins, comprising: (a) directing methane (CH₄) and oxygen (O₂) into an oxidative coupling of methane (OCM) reactor to produce a product stream comprising the C₂₊ compounds including olefins, carbon monoxide (CO) and/or carbon dioxide (CO₂), and un-reacted CH₄; (b) enriching the CO and/or CO₂ from the product stream to generate an enriched CO and/or CO₂ stream; (c) directing the enriched CO and/or CO₂ stream to an MeOH reactor to produce MeOH; (d) directing at least some of the MeOH to a methanol to olefins (MTO) reactor to produce a second olefins stream; (e) enriching the un-reacted CH₄ from the product stream to produce an enriched CH₄ stream; and (f) directing at least a portion of the enriched CH₄ stream to a steam methane reformer (SMR) that produces hydrogen (H₂) and CO and/or CO₂. In some embodiments, the method further comprises (g) recovering olefins from the product stream and the second olefins stream.

In another aspect, provided herein is a system for producing olefins, comprising: (a) an oxidative coupling of methane (OCM) reactor that (i) receives methane (CH₄) and oxygen (O₂) and (ii) reacts the CH₄ and O₂ to yield a product stream comprising the C₂₊ compounds including olefins, carbon monoxide (CO) and/or carbon dioxide (CO₂), and un-reacted CH₄; (b) an MeOH reactor that (i) receives CO and/or CO₂ enriched from the product stream and (ii) reacts the CO and/or CO₂ to produce MeOH; (c) a methanol to olefins (MTO) reactor that converts at least some of the MeOH into olefins to produce a second olefins stream; and (d) a steam methane reformer (SMR) that (i) receives un-reacted CH₄ enriched from the product stream and (ii) provides hydrogen (H₂) and at least one of carbon monoxide (CO) and CO₂ to the MeOH reactor to produce MeOH. In some embodiments, the system further comprises a separations module that enriches olefins from the product stream and the second olefins stream.

Oxidative Coupling of Methane Process

[0154] In an OCM process, methane (CH₄) may react with an oxidizing agent over a catalyst bed to generate C₂₊ compounds. For example, methane can react with oxygen over a suitable catalyst to generate ethylene, e.g., $2 \text{CH}_4 + \text{O}_2 \rightarrow \text{C}_2\text{H}_4 + 2 \text{H}_2\text{O}$ (See, e.g., Zhang, Q., *Journal of Natural Gas Chem.*, **12**:81, 2003; Olah, G. "Hydrocarbon Chemistry", Ed. 2, John Wiley & Sons (2003)). This reaction may be exothermic ($\Delta H = -280 \text{ kJ/mol}$) and occur at very high temperatures (e.g., $>450^\circ\text{C}$ or $>700^\circ\text{C}$). Non-selective reactions that can occur include (a) $\text{CH}_4 + 2\text{O}_2 \rightarrow \text{CO}_2 + 2 \text{H}_2\text{O}$ and (b) $\text{CH}_4 + 1/2 \text{O}_2 \rightarrow \text{CO} + 2 \text{H}_2$. These non-selective reactions may also be exothermic,

with reaction heats of -891 kJ/mol and -36 kJ/mol respectively. The conversion of methane to CO_x products may be undesirable due to both heat management and carbon efficiency concerns. [0155] Experimental evidence suggests that free radical chemistry may be involved. (Lunsford, *J. Chem. Soc., Chem. Comm.*, 1991; H. Lunsford, *Angew. Chem., Int. Ed. Engl.*, **34**:970, 1995). In the reaction, methane (CH₄) may be activated on the catalyst surface, forming methyl radicals which then couple on the surface or in the gas phase to form ethane (C₂H₆), followed by dehydrogenation to ethylene (C₂H₄). The OCM reaction pathway can have a heterogeneous/homogeneous mechanism, which involves free radical chemistry. Experimental evidence has shown that an oxygen active site on the catalyst activates the methane, removes a single hydrogen atom and creates a methyl radical. Methyl radicals may react in the gas phase to produce ethane, which may be either oxidative or non-oxidatively dehydrogenated to ethylene. The main reactions in this pathway can be as follows: (a) CH₄ + O⁻ → CH₃^{*} + OH⁻; (b) 2 CH₃^{*} → C₂H₆; (c) C₂H₆ + O⁻ → C₂H₄ + H₂O. In some cases, to improve the reaction yield, ethane can be introduced downstream of the OCM catalyst bed and thermally dehydrogenated via the following reaction: C₂H₆ → C₂H₄ + H₂. This reaction is endothermic (ΔH = 144 kJ/mol), which can utilize the exothermic reaction heat produced during methane conversion. Combining these two reactions in one vessel can increase thermal efficiency while simplifying the process.

[0156] Catalysts for OCM, may include, e.g., various forms of iron oxide, V₂O₅, MoO₃, Co₃O₄, Pt-Rh, Li/ZrO₂, Ag-Au, Au/Co₃O₄, Co/Mn, CeO₂, MgO, La₂O₃, Mn₃O₄, Na₂WO₄, MnO, ZnO, and/or combinations thereof, on various supports. A number of doping elements may be used in combination with the above-mentioned catalysts.

[0157] Various limitations of the conventional approach to C-H bond activation may limit the yield of OCM reaction under practical operating conditions. For example, publications from industrial and academic labs have shown characteristic performance of high selectivity at low conversion of methane, or low selectivity at high conversion (J.A. Labinger, *Cat. Lett.*, **1**:371, 1988). Limited by this conversion/selectivity threshold, no OCM catalyst has been able to exceed 20-25% combined C₂ yield (*i.e.*, ethane and ethylene). In addition, almost all such reported yields required extremely high reactor inlet temperatures (> 800°C). Catalysts and processes adapted for performing OCM reaction at substantially more practicable temperatures, pressures and catalyst activities have been described in U.S. Patent Publication Nos. 2012/0041246, 2013/0023709, 2013/0165728, 2013/0158322, 2014/0121433, 2014/0274671, and 2015/0314267, each of which is incorporated herein by reference in its entirety for all purposes.

[0158] An OCM reactor can include a catalyst that facilitates an OCM process. The catalyst may include a compound including at least one of an alkali metal, an alkaline earth metal, a transition

metal, and a rare-earth metal. The catalyst may be in the form of a honeycomb, packed bed, or fluidized bed. In some embodiments, at least a portion of the OCM catalyst in at least a portion of the OCM reactor can include one or more OCM catalysts and/or nanostructure-based OCM catalyst compositions, forms and formulations. Examples of OCM reactors, separations for OCM, and OCM process designs are described in U.S. Patent Publication Nos. 2013/0225884, 2014/0107385, 2014/0012053, and 2015/0152025, , each of which is incorporated herein by reference in its entirety for all purposes. An OCM reactor can be adiabatic or substantially adiabatic (including, for example, a post-bed cracking unit). An OCM reactor can be isothermal or substantially isothermal.

[0159] With reference to **FIG. 19**, natural gas **1900** and ethane **1902** can enter the process through a de-sulfurization module (or unit) **1904**, which can flow into a process gas compression module **1906** where water can be removed. OCM product gas can be added to the process gas compression module **1906** as well. A process gas cleanup module **1908** can remove carbon dioxide (CO₂), some or all of which can be taken to a methanation module **1910**. Following cleanup, the process gas can flow into a first separations module **1912** that removes C₂₊ compounds from the process gas stream. The remaining process gas can flow to the methanation module **1910** and/or a fired heater (e.g., to heat incoming OCM gas streams **1914**). The C₂₊ compounds can be fractionated in a second separations module **1916** to produce ethylene (C₂H₄) **1918**, C₃ compounds **1920**, and C₄₊ compounds **1922** for example. The second separations module **1916** can produce an ethane (C₂H₆) stream **1926** that can be returned to the OCM reactor **1928**. At the OCM reactor **1928**, oxygen **1930** can be reacted with methane from the methanation module **1932**. Outside boundary limits (OSBL) systems may include a steam system, a boiler feed water system and a cooling water system.

[0160] The OCM reactor can perform the OCM reaction and a post-bed cracking (PBC) reaction, as described in U.S. Patent Publication No. 2015/0152025, which is incorporated herein by reference in its entirety. With reference to **FIG. 20**, the OCM reactor **2000** can have an OCM reaction section **2002** and a PBC section **2004**. Methane **2006** (e.g., from natural gas) and oxygen **2008** can be injected (via a mixer) into the OCM reaction region (which comprises an OCM catalyst). The OCM reaction may be exothermic and the heat of reaction can be used to crack additional ethane **2010** that can be injected into the PBC region **2004**. In some cases, yet more ethane **2012** can also be injected into the OCM reaction region **2002** and/or the methane feed is supplemented with ethane or other C₂₊ alkanes (e.g., propane or butane). The OCM reactor may produce an OCM effluent **2014**.

[0161] The relative amounts of supplemental ethane **2010** and **2012** can be varied to achieve a range of product outcomes from the system. In some cases, no ethane is injected into the OCM reaction region **2002** (referred to herein as Case-1). Another example presented herein has 3.5 mol% ethane injected into the OCM region (referred to herein as Case-2). Some process design results are presented in **Table 1**.

Table 1: Examples of various amounts of ethane in OCM feed

	Case-1	Case-2
Natural gas consumed (MMSCFD)	15.5	16
Ethane consumed (MMSCFD)	2.2	8.3
[Ethane] at inlet (mol%)	0.07	3.5
[Ethylene] at outlet (mol%)	3.6	4.9
C ₂ products (kTa)	85	115
C ₃ products (kTa)	10.3	21.1
C ₄₊ products (kTa)	2.7	2.5
O ₂ consumed (ton/ton ethylene)	2.2	1.8
CO ₂ produced from OCM (ton/ton ethylene)	0.9	0.7
CO ₂ produced from fired heater (ton/ton ethylene)	0.6	0.4

[0162] In some cases, an amount of hydrogen (H₂) exiting the OCM reactor is relatively higher for cases having relatively more ethane injection (e.g., 8% H₂ for Case-1 and about H₂ 10% for Case-2). The amount of ethane that can be injected can be limited by the desired temperature exiting the OCM reaction region **2002** or the OCM reactor **2014**.

[0163] Methane can be combined with a recycle stream from downstream separation units prior to or during introduction into an OCM reactor. In the OCM reactor, methane can catalytically react with an oxidizing agent to yield C₂₊ compounds. The oxidizing agent can be oxygen (O₂), which may be provided by way of air or enriched air. Oxygen can be extracted from air, for example, in a cryogenic air separation unit.

[0164] To carry out an OCM reaction in conjunction with some catalytic systems, the methane and oxygen containing gases may need to be brought up to appropriate reaction temperatures, e.g., in excess of 450°C for some catalytic OCM processes, before being introduced to the catalyst, in order to allow initiation of the OCM reaction. Once that reaction begins or “lights off,” then the heat of the reaction may be sufficient to maintain the reactor temperature at

appropriate levels. Alternatively or additionally, these processes may operate at a pressure above atmospheric pressure, such as in the range of about 1 to 30 bars (absolute).

[0165] Once formed, C₂₊ compounds can be subjected to further processing to generate one or more desired or otherwise predetermined chemicals. In some situations, alkane components of the C₂₊ compounds are subjected to cracking in an OCM reactor or a reactor downstream of the OCM reactor to yield other compounds, such as alkenes (or olefins). *See, e.g.*, U.S. Patent Publication No. 2015/0152025, which is entirely incorporated herein by reference.

[0166] The OCM effluent can be cooled after the conversion to ethylene has taken place. The cooling can take place within a portion of the OCM reactor and/or downstream of the OCM reactor (e.g., using at least about 1, 2, 3, 4, 5 or more heat exchangers). In some cases, a heat exchanger is a heat recovery steam generator (HRSG), such as the apparatus described herein. Cooling the OCM effluent suitably rapidly and to a suitably low temperature can prevent undesirable reactions from occurring with the OCM effluent, including, but not limited to the formation of coke or other by-products.

[0167] In some embodiments, the OCM effluent is cooled to a target temperature of less than or equal to about 700 °C, 650 °C, 600 °C, 550 °C, 500 °C, 450 °C, 400 °C, 350 °C, 300 °C, °C, 200 °C, or less. In some cases, the OCM effluent is cooled to the target temperature less than or equal to about 1 second, 900 milliseconds (ms), 800 ms, 700 ms, 600 ms, 500 ms, 400 ms, 300 ms, 200 ms, 100 ms, 80 ms, 60 ms, 40 ms, 20 ms, or less of the production of the desired or otherwise predetermined concentration of a compound (e.g., ethylene) in the OCM reaction.

[0168] In some situations, an OCM system generates ethylene that can be subjected to further processing to produce different hydrocarbons with the aid of one or more conversion processes (or systems). Such a process can be part of an ethylene to liquids (ETL) process flow comprising one or more OCM reactors, separations units, and one or more conversion processes for generating higher molecular weight hydrocarbons. The conversion processes can be integrated in a switchable or selectable manner in which at least a portion or all of the ethylene containing product can be selectively directed to at least about 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more different process paths to yield as many different hydrocarbon products. An example OCM and ETL (collectively “OCM-ETL” herein) is provided in U.S. Patent Publication No. 2014/0171707, which is entirely incorporated herein by reference.

[0169] An aspect of the present disclosure provides OCM processes that are configured to generate olefins (or alkenes), such as ethylene, propylene (or propene), butylenes (or butenes), etc. An OCM process can be a standalone process or can be integrated in a non-OCM process, such as a natural gas liquid(s) (NGL or NGLs) or gas processing system.

[0170] Reference will now be made to the figures, wherein like numerals refer to like parts throughout. It will be appreciated that the figures and features therein are not necessarily drawn to scale. In the figures, the direction of fluid flow between units is indicated by arrows. Fluid may be directed from one unit to another with the aid of valves and a fluid flow system. In some examples, a fluid flow system can include compressors and/or pumps, as well as a control system for regulating fluid flow, as described elsewhere herein.

[0171] In some cases, the process equipment is sized to accommodate a range of amounts of additional ethane such that the process is flexible. For example, more ethane can be injected into the process when the price of ethane is relatively cheap in comparison to the price of natural gas (e.g., low frac spread).

[0172] The ethane can be mixed with the natural gas and recycled to the OCM unit. The ethane can go straight to the OCM reactor, optionally through a separate de-sulfurization module.

Injection of ethane through a separate de-sulfurization module can reduce the load in the recycle loop of the process and/or give additional production capacity keeping the same recirculation rate. The purge gas from the process can be used for fuel gas to the fired heater or sales gas.

[0173] The concentration of ethane in the feed to the OCM reactor can be any suitable value, including greater than or equal to about 0.0 mol%, 0.25 mol%, 0.5 mol%, 0.75 mol%, 1.0 mol%, 1.25 mol%, 1.5 mol%, 1.75 mol%, 2.0 mol%, 2.25 mol%, 2.5 mol%, 2.75 mol%, 3.0 mol%, 3.25 mol%, 3.5 mol%, 3.75 mol%, 4.0 mol%, 4.25 mol%, 4.5 mol%, 4.75 mol%, 5.0 mol%, 5.25 mol%, 5.5 mol%, 5.75 mol%, 6.0 mol%, 7.0 mol%, 8.0 mol%, 9.0 mol%, 10.0 mol% or more. In some cases, the concentration of ethane in the feed to the OCM reactor is less than or equal to about 25 mol%, 20 mol%, 15 mol%, 10 mol%, 9 mol%, 8 mol%, 7 mol%, 6 mol%, 5 mol%, 4 mol%, 3 mol%, 2 mol%, 1 mol%, 0.8 mol%, 0.6 mol%, 0.4 mol%, 0.2 mol%, 0.1 mol% or less. In some cases, the concentration of ethane in the feed to the OCM reactor is between any of the two values described above, for example, between about 0.01 mol% to about 5 mol%.

[0174] The systems and methods of the present disclosure can be carbon-efficient and/or energy-efficient. In some cases, the systems or methods of the present disclosure have a carbon efficiency of at least about 50%, at least about 55%, at least about 60%, at least about 65%, at least about 70%, at least about 75%, at least about 80%, at least about 85%, at least about 90%, or more. In some cases, a system of the present disclosure or method for use thereof has a ratio of all carbon atoms output from the system as hydrocarbons to all carbon atoms input to the system of at least about 0.40, at least about 0.50, at least about 0.55, at least about 0.60, at least about 0.65, at least about 0.70, at least about 0.75, at least about 0.80, at least about 0.85, at least about 0.90, at least about 0.95, or more.

[0175] In some cases, the systems or methods of the present disclosure have a carbon efficiency of between about 50% and about 85%, between about 55% and about 80%, between about 60% and about 80%, between about 65% and about 85%, between about 65% and about 80%, or between about 70% and about 80%. In some cases, a system of the present disclosure or method for use thereof has a ratio of all carbon atoms output from the system as hydrocarbons to all carbon atoms input to the system of between about 0.50 and about 0.85, between about 0.55 and about 0.80, between about 0.60 and about 0.80, between about 0.65 and about 0.85, between about 0.65 and about 0.80, or between about 0.70 and about 0.80.

[0176] In some cases, the systems and methods combine OCM reaction, post-bed cracking (PBC), separations and methanation reactions. The separations can include oligomerization of ethylene to C₃₊ compounds, which are more easily separated as described in PCT Patent Publication No. WO/2015/105911, which is incorporated herein by reference in its entirety. Additional details of OCM reactor and process design can be found in PCT Patent Publication Nos. WO/2015/081122 and WO/2015/106023, each of which is incorporated herein by reference in their entirety.

[0177] In an aspect, provided herein is a method for performing oxidative coupling of methane (OCM). The method can comprise (a) reacting oxygen (O₂) with methane (CH₄) to form heat, ethylene (C₂H₄) and optionally ethane (C₂H₆), hydrogen (H₂), carbon monoxide (CO) or carbon dioxide (CO₂); (b) reacting the heat produced in (a) with ethane (C₂H₆) to form ethylene (C₂H₄) and hydrogen (H₂); (c) performing at least one of (i) enriching the ethylene (C₂H₄) produced in (a) and (b) or (ii) oligomerizing the ethylene (C₂H₄) produced in (a) and (b) to produce C₃₊ compounds and enriching the C₃₊ compounds; and (d) reacting the hydrogen (H₂) produced in (a) and (b) with carbon monoxide (CO) and/or carbon dioxide (CO₂) to form methane (CH₄).

[0178] In another aspect, provided herein is a system for performing oxidative coupling of methane (OCM). The system can comprise an OCM reactor that permits oxygen (O₂) and methane (CH₄) to react in an OCM process to form heat, ethylene (C₂H₄) and optionally ethane (C₂H₆), hydrogen (H₂), carbon monoxide (CO) or carbon dioxide (CO₂). The system can further comprise a cracking vessel in fluid communication with the OCM reactor, which cracking vessel may utilize the heat produced in the OCM reactor to convert ethane (C₂H₆) into ethylene (C₂H₄) and hydrogen (H₂). The system can further comprise a separations module in fluid communication with the cracking vessel. The separations module may (i) enrich the ethylene (C₂H₄) produced in the OCM reactor and the cracking vessel or (ii) oligomerize the ethylene (C₂H₄) produced in the OCM reactor and the cracking vessel to produce C₃₊ compounds and enriches the C₃₊ compounds. The system can further comprise a methanation reactor in fluid

communication with the separations module. The methanation reactor may permit the hydrogen (H_2) produced in the OCM reactor and the cracking vessel to react with carbon monoxide (CO) and/or carbon dioxide (CO_2) to form methane (CH_4).

[0179] In some cases, the ethane (C_2H_6) that is cracked in the cracking vessel is produced in the OCM reactor. In some instances, at least some of the ethane (C_2H_6) that is cracked is in addition to the ethane (C_2H_6) that was produced in the OCM reactor. In some cases, the OCM reactor produces ethane (C_2H_6), hydrogen (H_2), carbon monoxide (CO) and carbon dioxide (CO_2). In some cases, the carbon monoxide (CO) and carbon dioxide (CO_2) produced in the OCM reactor is methanated. The separations module can separate ethylene (C_2H_4) or C_{3+} compounds from methane (CH_4), ethane (C_2H_6), hydrogen (H_2), carbon monoxide (CO) or carbon dioxide (CO_2). In some instances, the cracking vessel is a portion of the OCM reactor.

[0180] The methane formed in the methanation reactor can be returned to the OCM reactor or sold as sales gas. In some embodiments, the OCM reactor has an OCM catalyst. In some embodiments, the methanation reactor has a methanation catalyst. In some embodiments, the separations module comprises an ethylene-to-liquids (ETL) reactor comprising an oligomerization catalyst. At least some of the heat produced in the OCM reactor can be converted to power.

[0181] In another aspect, described herein is a method for producing C_{2+} compounds from methane (CH_4). The method can comprise: (a) performing an oxidative coupling of methane (OCM) reaction which converts methane (CH_4) and oxygen (O_2) into ethylene (C_2H_4) and optionally ethane (C_2H_6); (b) optionally oligomerizing the ethylene (C_2H_4) to produce C_{3+} compounds; and (c) isolating the C_{2+} compounds, wherein the C_{2+} compounds may comprise the ethylene (C_2H_4), the ethane (C_2H_6) and/or the C_{3+} compounds. In some cases, the method has a carbon efficiency of at least about 50%, 60%, 70%, 80%, 90%, 95%, or more. In some cases, the isolated the C_{2+} compounds are not pure. In some cases, the isolated the C_{2+} compounds comprise methane, CO, H_2 , CO_2 and/or water.

[0182] In some cases, the systems or methods of the present disclosure consume less than or equal to about 150, 140, 130, 120, 110, 100, 95, 90, 85, 80, 75, 70, 65, 60, 55, or 50, or less million British Thermal Units (MMBtu) of energy per ton of ethylene (C_2H_4) or C_{3+} compounds enriched. In some cases, the amount of energy consumed by the system includes the energy content of the feedstock used to make the ethylene (C_2H_4) or C_{3+} compounds.

[0183] In some cases, the systems or methods of the present disclosure have consume between about 65 and about 100, between about 70 and about 110, between about 75 and about 120, between about 85 and about 130, between about 40 and about 80, or between about 50 and about

80 MMBtu of energy per ton of ethylene (C_2H_4) or C_{3+} compounds enriched. In some cases, the amount of energy consumed by the system includes the energy content of the feedstock used to make the ethylene (C_2H_4) or C_{3+} compounds.

[0184] In some cases, the systems or methods of the present disclosure have a specific oxygen consumption of greater than or equal to about 1.2, about 1.3, about 1.4, about 1.5, about 1.6, about 1.7, about 1.8, about 1.9, about 2.0, about 2.1, about 2.2, about 2.3, about 2.4, about 2.5, about 2.6, about 2.7, about 2.8, about 2.9, about 3, about 3.2, about 3.4, about 3.6, about 3.8, about 4.0, or more.

[0185] In some cases, the systems or methods of the present disclosure have a specific oxygen consumption of between about 1.2 and about 2.7, between about 1.5 and about 2.5, between about 1.7 and about 2.3 or between about 1.9 and about 2.1.

[0186] In some cases, the systems or methods of the present disclosure have a specific CO_2 emission of greater than or equal to about 0.5, about 0.6, about 0.7, about 0.8, about 0.9, about 1.0, about 1.1, about 1.2, about 1.3, about 1.4, about 1.5, about 1.6, about 2.0, about 2.2, about 2.4, about 2.6, about 2.8, about 3.0, about 3.2, about 3.4, about 3.6, or more.

[0187] In some cases, the systems or methods of the present disclosure have a specific CO_2 emission of between about 0.5 and about 1.7, between about 0.7 and about 1.4, between about 0.8 and about 1.3 or between about 0.9 and about 1.1.

[0188] In some cases, the systems or methods of the present disclosure produces C_{2+} products, and the C_{2+} products comprise at least about 1%, 2.5%, 5%, 7.5%, 10%, 12.5%, 15%, 17.5%, 20% (wt% or mol%) or more C_{3+} hydrocarbons.

[0189] In some cases, the systems or methods of the present disclosure produces C_2 products and C_{3+} products, and a molar ratio of the C_2 products to the C_{3+} products is at least or equal to about 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20 or more. In some cases, the molar ratio of the C_2 products to the C_{3+} products is less than or equal to about 50, 45, 40, 35, 30, 25, 20, 18, 16, 14, 12, 10, 8, 6, 4, 2, or less. In some cases, the molar ratio of the C_2 products to the C_{3+} products is between any of the two values described above, for example, from about 5 to about 20.

[0190] In another aspect, provided herein is a method for producing C_{2+} compounds from methane (CH_4), the method comprising: (a) performing an oxidative coupling of methane (OCM) reaction which may convert methane (CH_4) and oxygen (O_2) into ethylene (C_2H_4) and optionally ethane (C_2H_6); (b) optionally oligomerizing the ethylene (C_2H_4) to produce C_{3+} compounds; and (c) isolating the C_{2+} compounds, wherein the C_{2+} compounds may comprise the ethylene (C_2H_4), the ethane (C_2H_6) and/or the C_{3+} compounds. In some cases, the amount of energy consumed by

the system includes the energy content of the feedstock used to make the isolated C_{2+} compounds. In some cases, the isolated the C_{2+} compounds are not pure. In some cases, the isolated the C_{2+} compounds comprise methane, CO, H_2 , CO_2 and/or water.

[0191] In some cases, the method consumes less than or equal to about 150, 140, 130, 120, 110, 100, 95, 90, 85, 80, 75, 70, 65, 60, 55, 50, or less MMBtu of energy per ton of C_{2+} compounds isolated. In some cases, the method consumes greater than or equal to about 20, 30, 40, 50, 60, 70, 80, 90, 100, or more MMBtu of energy per ton of C_{2+} compounds isolated. In some cases, the method consumes between about 65 and about 100, between about 70 and about 110, between about 75 and about 120, between about 85 and about 130, between about 40 and about 80, or between about 50 and about 80 MMBtu of energy per ton of C_{2+} compounds isolated.

[0192] In another aspect, provided herein is a method for producing C_{2+} compounds from methane (CH_4). The method may comprise performing an oxidative coupling of methane (OCM) reaction using an OCM catalyst. The OCM reaction may be performed at a set of reaction conditions to convert a quantity of methane (CH_4) into ethylene (C_2H_4) at a carbon efficiency. The OCM catalyst may have a C_{2+} selectivity at the set of reaction conditions that is less than the carbon efficiency at the set of reaction conditions. The set of reaction conditions can include a temperature, a pressure, a methane to oxygen ratio and a gas hourly space velocity (GHSV).

[0193] In another aspect, provided herein is a method for producing C_{2+} compounds from methane (CH_4). The method may comprise (a) performing an oxidative coupling of methane (OCM) reaction using an OCM catalyst at a set of reaction conditions to convert a quantity of methane (CH_4) into ethylene (C_2H_4) and ethane (C_2H_6); and (b) cracking the ethane (C_2H_6) to produce additional ethylene (C_2H_4). The combined carbon efficiency of (a) and (b) may be greater than the C_{2+} selectivity of the OCM catalyst at the set of reaction conditions. The set of reaction conditions can include a temperature, a pressure, a methane to oxygen ratio and a gas hourly space velocity (GHSV).

[0194] In some instances, the C_{2+} selectivity is less than or equal to about 70%, 65%, 60%, 55%, 50%, 45%, 40%, 35%, 30% or less. In some instances, the C_{2+} selectivity is greater than or equal to about 20%, 25%, 30%, 35%, 40%, 50%, 60%, 70%, 80%, or more. In some cases, the C_{2+} selectivity is between any of the two values described herein, for example, from about 25% to about 50%.

[0195] In another aspect, provided herein is a method for producing C_{2+} compounds. The method may comprise a) providing a first feedstock comprising methane (CH_4) and optionally a first amount of ethane (C_2H_6); (b) performing an OCM reaction on the first feedstock to produce an OCM product comprising a first amount of ethylene (C_2H_4); (c) combining the OCM product

with a second feedstock comprising a second amount of ethane (C_2H_6) to produce a third feedstock; and (d) cracking the third feedstock to produce a second amount of ethylene (C_2H_4). In some cases, the second amount of ethylene includes ethylene produced in (b) and (d).

[0196] In some cases, the fraction of the second amount of ethylene (C_2H_4) that is derived from the first or the second amounts of ethane (C_2H_6) is at least about 1%, at least about 3%, at least about 5%, at least about 7%, at least about 10%, at least about 15%, at least about 20%, at least about 25%, at least about 30%, at least about 35%, at least about 40%, at least about 45%, at least about 50%, at least about 55%, or more.

[0197] In some cases, the combined moles of the first amount and second amount of ethane (C_2H_6) divided by the combined moles of the first feedstock and the second feedstock is greater than or equal to about 1%, 3%, 5%, 7%, 10%, 15%, 20%, 25%, 30%, 35%, 40%, 45%, 50%, 55%, 60%, or more. In some cases, the combined moles of the first amount and second amount of ethane (C_2H_6) divided by the combined moles of the first feedstock and the second feedstock is less than or equal to about 90%, 80%, 70%, 60%, 50%, 40%, 30%, 20%, 10% or less.

[0198] In some cases, the combined moles of the first amount and second amount of ethane (C_2H_6) divided by the combined moles of the first feedstock and the second feedstock is between about 1% and about 50%, between about 1% and about 40%, between about 1% and about 30%, between about 1% and about 20%, between about 1% and about 15%, between about 1% and about 10%, or between about 10% and about 50%.

[0199] In some cases, the first feedstock is natural gas. In some cases, the first feedstock is natural gas supplemented with the first amount of ethane (C_2H_6). In some cases, the first feedstock is natural gas having passed through a separations system to substantially remove the hydrocarbons other than methane.

[0200] In some cases, the molar percent of ethane (C_2H_6) in methane (CH_4) in the first feedstock is greater than or equal to about 1%, 3%, 5%, 7%, 10%, 15%, 20%, or more.

[0201] In some cases, some or all of a methane-containing feed stream (e.g., natural gas) can be processed in a separation system prior to being directed into an OCM reactor. Directing a methane-containing feed stream into an OCM reactor via a separation system or subsystem rather than into an OCM reactor directly can provide advantages, including but not limited to increasing the carbon efficiency of the process, optimizing the OCM process for methane processing, and optimizing the post-bed cracking (PBC) process for ethane processing. Such a configuration can result in higher back-end sizing for the system. In some cases (e.g., when using high pressure pipeline natural gas as a feedstock, high recycle ratio), the back-end sizing increase can be reduced or moderated. The separation system or subsystem can comprise a variety of

operations including any discussed in the present disclosure, such as CO₂ removal via an amine system, caustic wash, dryers, demethanizers, deethanizers, and C₂ splitters. In some cases, all of the methane and ethane in the methane-containing feed stream (e.g., natural gas) passes through a separations system or separations subsystem prior to passing through an OCM reactor. Some or all of the ethane from the feed stream can be directed from the separation system or subsystem into the inlet of an OCM reactor or into a post-bed cracking (PBC) unit.

[0202] In some configurations, an OCM system can be operated in a cycle, with at least some of the products from one unit or subsystem being processed or reacted in the next unit or subsystem. For example, oxygen (O₂) and methane (CH₄) feed can be provided to an OCM reactor, which produces an OCM product stream comprising ethane (C₂H₆), ethylene (C₂H₄), carbon monoxide (CO) and/or carbon dioxide (CO₂), and heat. The OCM product stream can then be fed into an ethane conversion subsystem (e.g., a cracking vessel or an ethane cracker) in fluid communication with the OCM reactor. The ethane conversion subsystem can also receive an additional C₂H₆ stream. The ethane conversion subsystem can convert C₂H₆ (e.g., crack C₂H₆ to C₂H₄) with the aid of the heat liberated by the OCM reaction. The heat can also be used to crack the C₂H₆ in the additional C₂H₆ stream. A C₂H₄ product stream can then be directed from the ethane conversion subsystem into a separations module in fluid communication with the ethane conversion subsystem. The separations module can enrich products such as C₂H₄ in the product stream. The separations module can also oligomerize C₂H₄ to form compounds comprising three or more carbon atoms (C₃₊ compounds). An enriched product stream enriched in C₂H₄ and/or C₃₊ compounds can be recovered from the separations module. A lights stream comprising components such as hydrogen (H₂) (e.g., hydrogen generated from the cracking of C₂H₆) and CO and/or CO₂ can be recovered from the separations module and directed into a methanation reactor in fluid communication with the separations module. The methanation reactor can react H₂ with CO and/or CO₂ to form a methanated stream comprising CH₄. The methanated stream can then be directed into the OCM reactor to provide additional methane for the OCM process. In some cases, energy generated in the methane conversion section in the form of high pressure steam, high temperature steam, heat, electricity, heat transferred via gas-gas heat exchanger, heat transferred via gas-liquid heat exchanger, or other forms, can be used to provide all of the energy and power required to run the entire plant or system.

[0203] In some cases, a cyclical system or process can operate with a carbon efficiency such as those discussed in this disclosure. For example, such a system or process can operate with a carbon efficiency of greater than or equal to about 50%, 55%, 60%, 65%, 70%, 75%, 80%, 85%, 90%, or more. In some cases, such a system or process can operate with a carbon efficiency of

between about 50% and about 85%, between about 55% and about 80%, between about 60% and about 80%, between about 65% and about 85%, between about 65% and about 80%, or between about 70% and about 80%.

[0204] In some cases, such a system or process (or method) can operate such that a ratio of all carbon atoms output from the system as hydrocarbons to all carbon atoms input to the system is greater than or equal to about 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, or more. In some cases, such a system or process can operate such that a ratio of all carbon atoms output from the system as hydrocarbons to all carbon atoms input to the system is between about 0.50 and about 0.85, between about 0.55 and about 0.80, between about 0.60 and about 0.80, between about 0.65 and about 0.85, between about 0.65 and about 0.80, or between about 0.70 and about 0.80.

[0205] An example process can comprise an OCM unit, a process gas compressor, a process gas cleanup unit, a cryogenic separations unit, a fractionation unit, a methanation unit, and a sulfur-removal unit. An oxygen stream may be fed into the OCM unit, along with a C₁ recycle stream from the methanation unit and a C₂ recycle stream from the fractionation unit. A natural gas stream and an ethane stream may be fed into the sulfur removal unit. Output from the OCM unit and the sulfur removal unit may be directed into the process gas compressor, and then into the process gas cleanup unit, which removes a CO₂ stream. The remaining product stream may be directed into the cryogenic separations unit, where light components including H₂ and CO or CO₂ may be directed into the methanation unit, and the remaining product stream, including ethylene and other C₂₊ compounds, may be directed into the fractionation unit. The fractionation unit may be configured to separate an ethylene stream and a C₃₊ compound stream comprising C₃ compounds, C₄ compounds, and C₅₊ compounds, as well as the C₂ recycle which may be directed back to the OCM unit. The methanation unit may convert the light components into methane, a first portion of which may be recycled to the OCM unit and a second portion of which may be output as sales gas. The operating flow rates for the input streams may be as follows: 20.3 MT/h of oxygen, 16.0 MT/h of natural gas, and 2.9 MT/h of ethane. The operating flow rates for the output streams may be as follows: 9.0 MT/h of ethylene, 1.4 MT/h of C₃₊ compounds, 4.3 MT/h of sales gas, and 8.2 MT/h of CO₂. The corresponding carbon content of the input streams may be 972 kmol/h of carbon in the natural gas stream, and 194 kmol/h of carbon in the ethane stream. The corresponding carbon content of the output streams may be 642 kmol/h of carbon in the ethylene stream, 96 kmol/h of carbon in the C₃₊ compounds stream, 247 kmol/h of carbon in the sales gas stream, and 181 kmol/h of carbon in the CO₂ stream. The amount of carbon input to the system may be 1166 kmol/h, and the amount of carbon output

from the system in hydrocarbon products (e.g., excluding CO₂) is 985 kmol/h, for a resulting carbon efficiency of 84.5%.

[0206] Reaction heat (e.g., OCM reaction heat) can be used to supply some, most, or all of the energy used to operate systems and perform processes of the present disclosure. In some examples, reaction heat can be used to supply greater than or equal to about 50%, 55%, 60%, 65%, 70%, 75%, 80%, 85%, 90%, 95%, 96%, 97%, 98%, 99%, or 100% of energy for operating systems and performing processes of the present disclosure. For example, the reaction heat can be used to supply at least about 80% or 90% of all of the energy for operating systems or processes of the present disclosure. This can provide for an efficient, substantially self-contained system with reduced or even minimum external energy input.

Integration of OCM with an FCC

[0207] The systems and methods described herein can be implemented in a number of scenarios, including using feedstocks from refineries (e.g., FCC offgas).

[0208] **FIGs. 21A-21C** shows a refinery system comprising a fluid catalytic cracking (FCC) unit **2101** and a separations unit **2130**. The FCC unit can comprise an FCC reactor **2102**, and in some cases a catalyst regeneration unit **2114**, as shown for example in **FIG. 21A**. In the FCC reactor, a hydrocarbon feed stream (e.g., raw oil) can be contacted with a regenerated cracking catalyst entering from a regenerated catalyst standpipe **2104**. The hydrocarbon feed stream can contact the catalyst in a riser, which can extend to the bottom of a reactor vessel. The feed and catalyst can be fluidized, for example by gas from a fluidizing line **2107**.

[0209] In some cases, heat from the catalyst vaporizes the hydrocarbon feed, and which is then cracked in the presence of the catalyst to produce lighter molecular weight hydrocarbon products as the catalyst and hydrocarbon feed are transferred up the riser into the reactor vessel. Side reactions can occur in the riser, depositing coke on the catalyst and lowering catalyst activity.

[0210] The light hydrocarbon products can then be separated from the coked catalyst, for example using cyclonic separators. Cyclonic separators can include a primary separator and one, two, or more stages of cyclones in the reactor vessel. After separation from the catalyst, gaseous cracked light hydrocarbon products exit the reactor vessel through a product outlet along a stream **2111** and are transported downstream to the separations unit **2130**, as shown in **FIG. 21B**.

[0211] Spent or coked catalyst can be regenerated for further use. For example, coked cracking catalyst, after separation from the gaseous product hydrocarbons, can be sent into a stripping section, where steam is injected (e.g., through a nozzle) to purge residual hydrocarbon vapor. After the stripping operation, the coked catalyst can be transported to the catalyst regeneration

unit **2114** through a spent catalyst standpipe **2113**. The catalyst regeneration unit can comprise a combustor or other types of regenerators. In the catalyst regeneration unit, a stream of oxygen-containing gas, such as air, can be introduced through an air distributor to contact the coked catalyst, thereby combusting the coke from the coked catalyst to yield regenerated catalyst and flue gas. The catalyst regeneration process can add heat to the catalyst, which can provide energy for the endothermic cracking reactions.

[0212] Catalyst and air can flow together up a combustor riser located within the catalyst regenerator. After regeneration, the catalyst and air can be initially separated by discharge through a disengager. Additional recovery of regenerated catalyst and flue gas exiting the disengager can be achieved using first and second stage separator cyclones within the catalyst regeneration unit. Catalyst separated from flue gas can be dispensed through diplegs from the first and second stage separator cyclones. Regenerated catalyst can be carried back to the riser through the regenerated catalyst standpipe. Flue gas, relatively lighter in catalyst, can sequentially exit the cyclones and the regenerator vessel through a flue gas outlet along flue gas stream **2121**. The flue gas can contain components including CO, CO₂, N₂ and H₂O, and other species.

[0213] The separations unit **2130** can be in downstream communication with the product outlet **2110**. In the separations unit **2130**, the gaseous cracked light FCC products in line **2111** can be directed to a lower section of a main fractionation column **2131**, which can be in downstream communication with the product outlet **2110**. Several different fractions of FCC product can be separated and taken from the main fractionation column, including but not limited to a heavy slurry oil stream **2132** from the bottoms, a heavy cycle oil stream **2133**, a light cycle oil stream **2134**, and a heavy naphtha stream **2135**. Any or all of streams **2132**, **2133**, **2134**, and **2135** may be cooled and pumped back to the main fractionation column **2131**, typically at a higher location, to cool the main column.

[0214] Gasoline and gaseous light hydrocarbons can be removed in overhead stream **2136** from the main fractionation column **2131** and condensed before entering a main column receiver **2137**. The main column receiver **2137** can be in downstream communication with the product outlet **2110**, and the main column **2131** can be in upstream communication with the main column receiver **2137**. An aqueous stream can be removed from a boot in the main column receiver **2137**. A condensed light naphtha stream can be removed in stream **2138** and an overhead stream **2139** can also be removed. The overhead stream **2139** can contain gaseous light hydrocarbons, which can comprise a dilute ethylene stream.

[0215] The streams **2138** and **2139** can be directed to a vapor recovery section **2142** of the separations unit. The vapor recovery section **2142** can comprise an absorption based system, or any other vapor recovery system such as a cold box system. The gaseous stream **2139** can be compressed in a compressor **2140**, which can improve separation of light gas components. More than one compressor stage can be used, such as a dual stage compression. The compressed light hydrocarbon stream **2141** can be joined by streams **2121** and **2144**, then chilled and delivered to a high pressure receiver **2145**. An aqueous stream from the high pressure receiver **2145** can then be routed to the main column receiver **2137**. A gaseous hydrocarbon stream **2146** comprising the dilute ethylene stream can be routed from the high pressure receiver to a primary absorber **2147** in which it can be contacted with unstabilized gasoline **2138** from the main column receiver **2137** to effect a separation between C_{3+} and C_2 hydrocarbons. The primary absorber **2147** can be in downstream communication with the main column receiver **2137**. A liquid C_{3+} stream **2143** can be returned to the compressed hydrocarbon stream **2141** prior to chilling.

[0216] A primary off-gas stream **2148** from the primary absorber **2147** can comprise the dilute ethylene stream. To concentrate the ethylene stream further and recover heavier components, the primary off-gas stream **2148** can be directed to a secondary absorber **2149**, where a circulating stream of light cycle oil **2150** diverted from stream **2134** can absorb most of the remaining C_{5+} and some C_3 - C_4 material in the primary off-gas stream. The secondary absorber **2149** can be in downstream communication with the primary absorber **2147**. Light cycle oil from the bottom of the secondary absorber **2151**, richer in C_{3+} material, can be returned to the main fractionation column **2131** via the pump-around for stream **2134**. The overhead of the secondary absorber **2149** can comprise a dry gas of predominantly C_2 hydrocarbons with hydrogen sulfide, ammonia, carbon oxides, and hydrogen, and can be removed in a secondary off-gas stream **2152** to comprise a dilute ethylene stream. A product stream containing ethylene from the separations unit **2130**, such as stream **2152**, can be processed by various techniques, including those discussed further herein.

[0217] Liquid **2153** from the high pressure receiver **2145** can be sent to a stripper **2154**. Most of the C_2 can be removed in the overhead of the stripper **2154** and returned the compressed hydrocarbon stream **2141** via overhead stream **2144**. A liquid bottoms stream **2155** can be sent from the stripper **2154** to a debutanizer column **2156**. An overhead stream **2157** from the debutanizer can comprise C_3 - C_4 olefinic product, while a bottoms stream **2158** can comprise stabilized gasoline and can be further treated and sent to gasoline storage.

[0218] The dilute ethylene stream and/or FCC dry gas stream can be used as a feedstock for OCM as described herein, including OCM integrated with another process. The dilute ethylene

stream can comprise an FCC dry gas stream, comprising between 5 weight-percent (wt%) and 50 wt% ethylene (in some cases, 10 wt% to 30 wt% ethylene). The dilute ethylene stream can comprise methane, for example at a concentration between 25 wt% and 55 wt%. The dilute ethylene stream can comprise ethane, for example at a concentration between 5 wt% and 45 wt%. The dilute ethylene stream can comprise propylene, for example at a concentration of between 0.1 wt% and 20 wt% propylene (in some cases, 0.5 wt% to 6 wt%). The dilute ethylene stream can comprise hydrogen and/or nitrogen, for example at a concentration between 1 wt% and 25 wt% each (in some cases, between 5 wt% and 20 wt% each). Saturation levels of water can also be present in the dilute ethylene stream. In some cases, if a secondary absorber **2149** is used, no more than 5 wt% of C₃₊ compounds can be present, with typically less than 0.5 wt% propylene. Besides hydrogen, other impurities such as hydrogen sulfide, ammonia, carbon oxides and acetylene can also be present in the dilute ethylene stream.

[0219] Many impurities in a dry gas ethylene stream can poison a catalyst. The secondary off-gas stream **2152**, comprising a dilute ethylene stream, can be introduced into an amine absorber unit **2160** to lower concentrations of hydrogen sulfide (see, e.g., **FIG. 21C**). A lean aqueous amine solution **2161**, for example comprising monoethanol amine or diethanol amine, can be introduced the amine absorber unit **2160** and contacted with the flowing secondary off-gas stream to absorb hydrogen sulfide, and a rich aqueous amine absorption solution **2162** containing hydrogen sulfide can be removed from the amine absorber unit **2160**, recovered, and in some cases further processed.

[0220] The amine-treated dilute ethylene stream **2163** can be introduced into a water wash unit **2164** to remove residual amine from the amine absorber **2160** and reduce the concentration of ammonia and carbon dioxide in the dilute ethylene stream **2167**. Water **2165** can be introduced to the water wash unit. The water can be slightly acidified to enhance capture of basic molecules such as the amine. An aqueous stream **2166** rich in amine, and potentially ammonia and carbon dioxide, can leave the water wash unit **2164** and may be further processed, for example as discussed herein.

[0221] **FIG. 22** shows several approaches for preparing an OCM feed and performing an OCM reaction using methane and paraffins from an FCC. A methane-containing or paraffin-containing stream **2200** can be the product of the separations unit. The methane-containing or olefin-containing stream **2200** can be the FCC overhead gas with H₂S and CO₂ removed or methanated and can be compressed in a compressor **2201**. Additional compressors may be used. The methane-containing or paraffin-containing stream **2200** can be the FCC overhead gas with H₂S and CO₂ removed and further reduced in a water wash unit. The methane-containing or paraffin-

containing stream **2200** can be compressed in a compressor **2201**. In such cases this can result in the same methane-containing or paraffin-containing stream (a first product stream) with the same composition but at a higher pressure. In some cases, one or more guard beds **2205** are located upstream and/or downstream of the compressor. In some cases, streams having methane or light paraffins (e.g., ethane and/or propane) can be added to the FCC overhead stream **2200**. Examples of such methane-containing or paraffin-containing stream can be from a cumene unit, from a de-ethanizer, or from a de-propanizer in an unsaturated plant. In some cases. The methane-containing or paraffin-containing stream can be mixed with the FCC overhead before the compressor **2210** or after the compressor **2215**. The methane-containing or paraffin-containing stream can be mixed with the FCC overhead before **2215** or after **2220** the guard bed(s) **2205**.

[0222] One or more recycle streams can be added to the OCM feed **2225**. The recycle streams can be added upstream of the compressor **2230** or downstream of the guard beds **2235**. The composition of stream **2225** can be different than the composition of stream **2200**. This compositional difference can be the result of removing components in the guard bed(s) **2205**, addition of streams **2210**, **2215**, **2220**, **2230**, **2235**, **2240**, **2245**, **2250**, or combinations thereof. This compositional difference can be the result of removing components in the guard bed(s) **2205**, addition of streams **2210**, **2215**, **2220**, **2230**, **2235**, **2240**, **2245**, **2250**, or combinations thereof.

[0223] The OCM feed stream **2225** can be sent to an OCM process **2260** and converted to olefins as described herein.

Integration of OCM with a DCU

[0224] A delayed coker unit (DCU) is a type of coker whose process comprises heating a residual oil feed to its thermal cracking temperature in a furnace with multiple parallel passes. This can crack the heavy, long chain hydrocarbon molecules of the residual oil into coker gas oil and petroleum coke. The DCU is one of the unit operations used in many oil refineries. A world scale DCU can have 1, 2, 3, 4, 5, 6, 7, 8, or more drums (e.g., each having diameters of up to about 10 meters and overall heights of up to about 43 meters). In some cases, the yield of coke from the DCU process ranges from about 18% to about 30% by weight of the feedstock residual oil. Some refineries produce as much as 2,000 to 3,000 tons or more of petroleum coke per day. Bitumen (e.g., from oil sands) is an example of a residual oil. Therefore, the present disclosure provides systems and methods for converting oil sands into olefins by OCM reactions of DCU off-gas.

[0225] With reference to **FIG. 23**, residual oil **2300** (e.g., from the vacuum distillation unit, sometimes including high-boiling oils from other sources within the refinery) can be pumped into the bottom of the distillation column called the main fractionator **2302**. From there, it can be pumped, along with some injected steam **2304**, into the fuel-fired furnace **2306** and heated to its thermal cracking temperature (e.g., about 480 °C). Thermal cracking can begin in the pipe between the furnace **2306** and the coke drums **2308**, and finishes in the coke drum(s) that are on-stream (the coke drums are alternately filled and emptied of coke). The injected steam **2304** can help to minimize the deposition of coke within the furnace tubes.

[0226] Pumping the incoming residual oil into the bottom of the main fractionator, rather than directly into the furnace, can preheat the residual oil by having it contact the hot vapors in the bottom of the fractionator. At the same time, some of the hot vapors can condense into a high-boiling liquid, which can be recycled back into the furnace along with the hot residual oil.

[0227] As cracking takes place in the drum, gas oil and lighter components **2310** can be generated in vapor phase and separated from the liquid and solids. The drum effluent is vapor except for any liquid or solids entrainment, and can be directed to main fractionator where it is separated into the desired boiling point fractions (e.g., heavy gas oil **2312**, light gas oil **2314**, coker naptha **2316**, and DCU off-gas **2318**).

[0228] The solid coke may be deposited and remain in the coke drum in a porous structure that may allow flow through the pores. Depending upon the overall coke drum cycle being used, a coke drum can fill in about 16 to 24 hours.

[0229] After the drum is full of the solidified coke, the hot mixture from the furnace may be switched to another drum. While the other drum is filling, the full drum may be steamed out **2320** to reduce the hydrocarbon content of the petroleum coke, and then quenched with water **2322** to cool it. The top and bottom heads of the full coke drum may be removed, and the solid petroleum coke may then be cut from the coke drum with a high-pressure water nozzle **2324**, where it may fall into a pit, pad, or sluiceway for reclamation to storage **2326**. In some embodiments, the coke drums **2308** operate at a pressure of about 3 to about 8 bar, the coke cutting water **2324** is injected at about 140 bar, and the DCU off-gas **2318** is withdrawn at about 2 to 3 bar (pressures absolute).

[0230] In order to simplify the present disclosure, the processing of DCU off-gas to OCM feed is described with reference to the embodiments described for FCC off-gas. Without limitation, the DCU off-gas stream **2318** can be compressed, have various streams or components added and/or have various streams or components removed prior to olefin oligomerization according to the

ETL systems and methods described in **FIG. 22**. For example, the FCC off-gas stream **2200** of **FIG. 22** can be substituted for or combined with the DCU off-gas stream **2318** of **FIG. 23**.

Control Systems

[0231] The present disclosure also provides computer control systems that can be employed to regulate or otherwise control the methods and systems provided herein. A control system of the present disclosure can be programmed to control process parameters, for example, temperatures, pressures in a given system such as OCM, ATR and/or or SMR subsystems.

[0232] **FIG. 24** shows a computer system **2401** that is programmed or otherwise configured to regulate reactions or reaction conditions in various systems/subsystems such as OCM, hydrogenation, ATR, and/or SMR subsystems. The computer system **2401** can regulate, for example, fluid stream (“stream”) flow rates, stream temperatures, stream pressures, reaction unit temperatures, reactor unit pressures, molar ratio between reactants, contact time of the reactant (or compounds) and reaction catalyst(s), and the quantity of products that are recycled, or directed into or out of a given system/unit.

[0233] The computer system **2401** includes a central processing unit (CPU, also “processor” and “computer processor” herein) **2405**, which can be a single core or multi core processor, or a plurality of processors for parallel processing. The computer system **2401** also includes memory or memory location **2410** (e.g., random-access memory, read-only memory, flash memory), electronic storage unit **2415** (e.g., hard disk), communication interface **2420** (e.g., network adapter) for communicating with one or more other systems, and peripheral devices **2425**, such as cache, other memory, data storage and/or electronic display adapters. The memory **2410**, storage unit **2415**, interface **2420** and peripheral devices **2425** are in communication with the CPU **2405** through a communication bus (solid lines), such as a motherboard. The storage unit **2415** can be a data storage unit (or data repository) for storing data.

[0234] The CPU **2405** can execute a sequence of machine-readable instructions, which can be embodied in a program or software. The instructions may be stored in a memory location, such as the memory **2410**. Examples of operations performed by the CPU **2405** can include fetch, decode, execute, and writeback. The CPU **2405** can be part of a circuit, such as an integrated circuit. One or more other components of the system **2401** can be included in the circuit. In some cases, the circuit is an application specific integrated circuit (ASIC).

[0235] The storage unit **2415** can store files, such as drivers, libraries and saved programs. The storage unit **2415** can store programs generated by users and recorded sessions, as well as output(s) associated with the programs. The storage unit **2415** can store user data, e.g., user

preferences and user programs. The computer system **2401** in some cases can include one or more additional data storage units that are external to the computer system **2401**, such as located on a remote server that is in communication with the computer system **2401** through an intranet or the Internet. The computer system **2401** can communicate with one or more remote computer systems through the network **2430**.

[0236] Methods as described herein can be implemented by way of machine (e.g., computer processor) executable code stored on an electronic storage location of the computer system **2401**, such as, for example, on the memory **2410** or electronic storage unit **2415**. The machine executable or machine readable code can be provided in the form of software. During use, the code can be executed by the processor **2405**. In some cases, the code can be retrieved from the storage unit **2415** and stored on the memory **2410** for ready access by the processor **2405**. In some situations, the electronic storage unit **2415** can be precluded, and machine-executable instructions are stored on memory **2410**.

[0237] The code can be pre-compiled and configured for use with a machine have a processor adapted to execute the code, or can be compiled during runtime. The code can be supplied in a programming language that can be selected to enable the code to execute in a pre-compiled or as-compiled fashion.

[0238] Aspects of the systems and methods provided herein, such as the computer system **2401**, can be embodied in programming. Various aspects of the technology may be thought of as “products” or “articles of manufacture” in some cases in the form of machine (or processor) executable code and/or associated data that is carried on or embodied in a type of machine readable medium. Machine-executable code can be stored on an electronic storage unit, such memory (e.g., read-only memory, random-access memory, flash memory) or a hard disk.

“Storage” type media can include any or all of the tangible memory of the computers, processors or the like, or associated modules thereof, such as various semiconductor memories, tape drives, disk drives and the like, which may provide non-transitory storage at any time for the software programming. All or portions of the software may at times be communicated through the Internet or various other telecommunication networks. Such communications, for example, may enable loading of the software from one computer or processor into another, for example, from a management server or host computer into the computer platform of an application server. Thus, another type of media that may bear the software elements includes optical, electrical and electromagnetic waves, such as used across physical interfaces between local devices, through wired and optical landline networks and over various air-links. The physical elements that carry such waves, such as wired or wireless links, optical links or the like, also may be considered as

media bearing the software. As used herein, unless restricted to non-transitory, tangible “storage” media, terms such as computer or machine “readable medium” refer to any medium that participates in providing instructions to a processor for execution.

[0239] Hence, a machine readable medium, such as computer-executable code, may take many forms, including but not limited to, a tangible storage medium, a carrier wave medium or physical transmission medium. Non-volatile storage media include, for example, optical or magnetic disks, such as any of the storage devices in any computer(s) or the like, such as may be used to implement the databases, etc. shown in the drawings. Volatile storage media include dynamic memory, such as main memory of such a computer platform. Tangible transmission media include coaxial cables; copper wire and fiber optics, including the wires that comprise a bus within a computer system. Carrier-wave transmission media may take the form of electric or electromagnetic signals, or acoustic or light waves such as those generated during radio frequency (RF) and infrared (IR) data communications. Common forms of computer-readable media therefore include for example: a floppy disk, a flexible disk, hard disk, magnetic tape, any other magnetic medium, a CD-ROM, DVD or DVD-ROM, any other optical medium, punch cards paper tape, any other physical storage medium with patterns of holes, a RAM, a ROM, a PROM and EPROM, a FLASH-EPROM, any other memory chip or cartridge, a carrier wave transporting data or instructions, cables or links transporting such a carrier wave, or any other medium from which a computer may read programming code and/or data. Many of these forms of computer readable media may be involved in carrying one or more sequences of one or more instructions to a processor for execution.

[0240] The computer system **2401** can include or be in communication with an electronic display **2435** that comprises a user interface (UI) **2440** for providing, for example, signals from a chip with time. Examples of UI's include, without limitation, a graphical user interface (GUI) and web-based user interface.

[0241] Methods and systems of the present disclosure can be implemented by way of one or more algorithms. An algorithm can be implemented by way of software upon execution by the central processing unit **2405**.

[0242] It will be appreciated that systems and methods described herein are provided as examples and that various alternatives may be employed. It will be further appreciated that components of systems described herein are interchangeable.

[0243] It should be understood from the foregoing that, while particular implementations have been illustrated and described, various modifications can be made thereto and are contemplated herein. It is also not intended that the invention be limited by the specific examples provided

within the specification. While the invention has been described with reference to the aforementioned specification, the descriptions and illustrations of the preferable embodiments herein are not meant to be construed in a limiting sense. Furthermore, it shall be understood that all aspects of the invention are not limited to the specific depictions, configurations or relative proportions set forth herein which depend upon a variety of conditions and variables. Various modifications in form and detail of the embodiments of the invention will be apparent to a person skilled in the art. It is therefore contemplated that the invention shall also cover any such modifications, variations and equivalents. It is intended that the following claims define the scope of the invention and that methods and structures within the scope of these claims and their equivalents be covered thereby.

CLAIMS

WHAT IS CLAIMED IS:

1. A method for producing propylene, the method comprising:
 - (a) injecting a first stream containing methane (CH_4) and a second stream containing an oxidizing agent into an oxidative coupling of methane (OCM) reactor at a temperature of at least about 400°C and a pressure of at least about 3 bar(g) to produce an OCM product stream containing ethylene, hydrogen (H_2), carbon dioxide (CO_2), carbon monoxide (CO), and unconverted CH_4 ;
 - (b) injecting at least a portion of the OCM product stream into a dimerization reactor to produce butene, wherein less than about 50% of said butene is isobutene; and
 - (c) injecting said butene into a metathesis reactor to produce an effluent stream comprising propylene and unconverted butene.
2. The method of Claim 1, wherein (b) and (c) are performed in a single vessel.
3. The method of Claim 1, wherein dimerization and metathesis are performed in a single reactor or over a single catalyst.
4. The method of Claim 1, wherein at least about 50% of said butene is 1-butene or 2-butene.
5. The method of Claim 1, wherein a portion of the ethylene produced in the OCM reactor is injected into the dimerization reactor, and an additional portion of the ethylene produced in the OCM reactor is injected into the metathesis reactor.
6. The method of Claim 5, wherein about 70% of the ethylene produced in the OCM reactor is injected into the dimerization reactor, and about 30% of the ethylene produced in the OCM reactor is injected into the metathesis reactor.
7. The method of Claim 1, wherein substantially no ethylene is injected into metathesis reactor without first being injected into the dimerization reactor.
8. The method of Claim 1, wherein the butene produced in the dimerization reactor contains C_{5+} compounds, and wherein said C_{5+} compounds are removed using a de-butanizer prior to (c).
9. The method of Claim 1, wherein the ethylene is separated from C_{3+} components in the effluent stream of the metathesis reactor.
10. The method of Claim 9, wherein a portion of the separated ethylene is recycled to the metathesis reactor.
11. The method of Claim 1, wherein the propylene in the effluent stream of the metathesis reactor is separated from the unconverted butene.
12. The method of Claim 11, wherein the unconverted butene is recycled to the metathesis reactor.

13. The method of Claim 7, wherein the ethylene that is injected into the dimerization reactor has a purity of at least about 99.5 mol%.
14. The method of Claim 13, wherein at least about 95% of the ethylene is converted into butenes in the dimerization reactor.
15. The method of Claim 1, wherein the butene that is injected into the metathesis reactor further comprises un-converted ethylene, which unconverted ethylene is passed through the dimerization reactor without being converted to butene.
16. The method of Claim 15, wherein the unconverted ethylene is about the only ethylene that is injected into the metathesis reactor.
17. The method of Claim 1, wherein the unconverted methane from the OCM reactor is removed through a vacuum pressure swing adsorption (VPSA) process to produce a VPSA effluent stream that contains less than about 1% methane.
18. The method of Claim 17, wherein the VPSA effluent stream is injected into a distillation column that removes C₃₊ species to generate a distillation effluent stream that has a higher concentration of ethylene than the VPSA effluent stream.
19. The method of Claim 18, wherein the propylene generated in the metathesis reactor is also separated using the distillation column that removes the C₃₊ species.
20. The method of Claim 1, wherein the butene produced in the dimerization reactor is injected, without prior purification, into the metathesis reactor.
21. The method of Claim 1, further comprising injecting ethane into the OCM reactor in (a).
22. The method of Claim 1, further comprising injecting propane into the OCM reactor in (a).
23. The method of Claim 1, further comprising separating the ethylene produced in the OCM reactor in (a) from ethane, methane, and hydrogen comprised in the OCM product stream.
24. The method of Claim 23, wherein the CO₂ is separated from the OCM product stream.
25. The method of Claim 24, wherein the CO₂ is injected into a methanation reactor to produce additional CH₄.
26. The method of Claim 25, wherein the additional CH₄ produced in the methanation reactor is injected into the OCM reactor.
27. The method of Claim 23, wherein distillation is used to purify the ethylene from the OCM product stream.
28. The method of Claim 23, wherein pressure swing adsorption is used to purify the ethylene from the OCM product stream.
29. The method of Claim 27, wherein a C1 splitter is used to recycle the methane back to the OCM reactor.

30. The method of Claim 27, wherein a C2 splitter is used to recycle the ethane back to the OCM reactor.
31. The method of Claim 28, wherein the methane recovered from the pressure swing adsorption is recycled to the OCM reactor.
32. The method of Claim 1, wherein the dimerization reactor contains a dimerization catalyst.
33. The method of Claim 1, wherein the OCM reactor contains an OCM catalyst.
34. The method of Claim 33, wherein the OCM catalyst comprises nanowires.
35. The method of Claim 1, further comprising separating the effluent stream of the metathesis reactor.
36. The method of Claim 35, wherein distillation is used to purify the effluent stream.
37. The method of Claim 36, wherein ethylene and ethane are separated from C₃₊ products in a distillation column.
38. The method of Claim 36, wherein propylene and propane are separated in a distillation column.
39. The method of Claim 1, wherein the metathesis reactor reacts ethylene with butene to generate propylene.
40. The method of Claim 1, wherein butene reacts with butene to generate propylene.
41. A method for producing propylene, the method comprising:
- (a) injecting a first stream containing methane and a second stream containing an oxidizing agent into an oxidative coupling of methane (OCM) reactor to produce a stream containing ethylene;
 - (b) injecting said ethylene into a dimerization reactor to produce butenes including 1-butene, 2-butene, and isobutene; and
 - (c) injecting said butenes into a metathesis reactor to produce an effluent comprising propylene and unreacted butenes, wherein in the metathesis reactor the 1-butene and 2-butene metathesize to produce the propylene, and wherein said ethylene is not injected directly into the metathesis reactor.
42. A system for producing propylene, comprising:
- (a) at least one oxidative-coupling of methane (OCM) subsystem that (i) has a first input stream comprising methane (CH₄), (ii) has a second input feed stream comprising an oxidizing agent, and (iii) is configured to generate from said methane and said oxidizing agent a product stream comprising ethylene;
 - (b) at least one first purification subsystem that is downstream of, and fluidically coupled to, said OCM subsystem, which at least one first purification subsystem is configured to use

the product stream of the OCM subsystem to produce an ethylene stream having a higher concentration of ethylene than the product stream;

- (c) at least one dimerization subsystem downstream of, and fluidically coupled to, said at least one first purification subsystem, wherein said at least one dimerization subsystem is capable of converting said ethylene stream into a stream containing butenes;
- (d) at least one metathesis subsystem downstream of, and fluidically coupled to, said at least one dimerization subsystem, wherein said at least one metathesis subsystem is configured to convert said stream containing said butenes including 1-butene and 2-butene into a metathesis product stream containing propylene and unconverted butenes; and
- (e) at least one second purification subsystem that is downstream of, and fluidically coupled to, said at least one metathesis subsystem, which at least one second purification subsystem is configured to separate said unconverted butenes from said propylene.

43. A method for producing olefins, the method comprising:

- (a) injecting a feed stream containing a mixture of hydrocarbons having a first average molecular weight into a vessel operating at a temperature of at least about 500 °C, thereby producing a cracked hydrocarbon stream containing a mixture of hydrocarbons having a second average molecular weight, wherein the second average molecular weight is less than the first average molecular weight;
- (b) separating one or more light hydrocarbons from the cracked hydrocarbon stream; and
- (c) injecting said one or more light hydrocarbons separated in (b) into an oxidative coupling of methane (OCM) reactor that converts at least a portion of said one or more light hydrocarbons into ethylene.

44. The method of Claim 43, wherein the one or more light hydrocarbons comprise hydrogen sulfide (H₂S).

45. The method of Claim 44, wherein the H₂S constitutes at least about 5 percent by weight (wt%) of the light hydrocarbons.

46. The method of Claim 43, wherein the vessel is a thermal cracker.

47. The method of Claim 43, wherein the vessel is a fluidized catalytic cracker (FCC).

48. The method of Claim 47, wherein the FCC is operated as a high-severity fluidized catalytic cracker (HS-FCC).

49. The method of Claim 48, wherein the HS-FCC operates at a temperature of at least about 500 °C.

50. The method of Claim 48, wherein the HS-FCC contains a catalyst that moves relative to the vessel.

51. The method of Claim 50, wherein the catalyst is injected into a top portion of the vessel and falls to a bottom portion of the vessel.
52. The method of Claim 50, wherein the catalyst comprises a zeolite.
53. The method of Claim 52, wherein the zeolite is ZSM-5.
54. The method of Claim 48, wherein the HS-FCC operates with a residence time of less than about 1 second (s), and wherein the residence time is a period of time that passes between the feed stream entering the vessel and the cracked hydrocarbon stream exiting the vessel.
55. The method of Claim 43, wherein the one or more light hydrocarbons include hydrocarbons having one to three carbon atoms (C1-C3 hydrocarbons).
56. The method of Claim 43, wherein the one or more light hydrocarbons include methane.
57. The method of Claim 43, wherein the one or more light hydrocarbons include ethane.
58. The method of Claim 43, wherein the one or more light hydrocarbons include propane.
59. The method of Claim 48, wherein methane from the HS-FCC is fed into the OCM reactor.
60. The method of Claim 48, wherein ethane from the HS-FCC is fed into the OCM reactor.
61. The method of Claim 48, wherein propane from the HS-FCC is fed into the OCM reactor.
62. The method of Claim 43, wherein said ethylene is included in a product stream from said OCM reactor, and wherein said product stream is used to generate an ethylene stream that has a higher concentration of ethylene than said product stream.
63. The method of Claim 62, wherein the OCM reactor produces CO₂, which CO₂ is separated from the ethylene.
64. The method of Claim 63, wherein the CO₂ is injected into a methanation reactor to produce additional CH₄.
65. The method of Claim 64, wherein the additional CH₄ is injected into the OCM reactor.
66. The method of Claim 61, wherein pressure swing adsorption is used to generate an ethylene stream from the OCM reactor.
67. The method of Claim 65, wherein a C1 splitter is used to recycle methane back to the OCM reactor.
68. The method of Claim 66, wherein methane recovered from the pressure swing adsorption is recycled to the OCM reactor.
69. The method of Claim 46, wherein the thermal cracker is operated at a pressure of at least about 3 bar(g).
70. The method of Claim 47, wherein the FCC contains a catalyst.
71. The method of Claim 70, wherein the catalyst comprises a zeolite.
72. The method of Claim 71, wherein the zeolite comprises a high USY zeolite.

73. The method of Claim 71, wherein the zeolite comprises ZSM-5 zeolites.

74. The method of Claim 43, wherein the OCM reactor contains an OCM catalyst.

75. The method of Claim 74, wherein the OCM catalyst comprises nanowires.

76. A system for producing olefins, comprising:

a fluidized catalytic cracker (FCC) unit containing a catalyst that is movable downward through the FCC unit;

a first separations subsystem fluidically coupled to said FCC unit, which first separations subsystem is configured to separate components that have a boiling point greater than that of propane from those with a boiling point lower than that of propane;

a second separations subsystem fluidically coupled to the FCC unit, said second separations subsystem configured to remove hydrogen sulfide (H₂S); and

an oxidative-coupling of methane (OCM) unit fluidically coupled to the FCC unit and configured to convert the components that have a boiling point lower than that of propane into ethylene.

77. A method for producing propylene, comprising:

(a) injecting a stream containing methane and a stream containing an oxidizing agent into an oxidative coupling of methane (OCM) unit to generate an OCM effluent stream containing ethylene, propylene, and propane;

(b) fractionating the OCM effluent stream using one or more separation units to generate (i) a first stream comprising ethylene and (ii) a second stream comprising propylene and propane;

(c) injecting at least a portion of the second stream into an additional separation unit to generate a propylene stream and a propane stream; and

(d) injecting at least a portion of the propane stream into a propane dehydrogenation (PDH) unit to generate a PDH effluent containing propylene and hydrogen.

78. The method of Claim 77, further comprising injecting at least a portion of the PDH effluent into one or more additional separation units to generate a first effluent stream comprising hydrogen and C₁-C₂ hydrocarbons, and a second effluent stream comprising C₃+ hydrocarbons.

79. The method of Claim 77, wherein said oxidizing agent comprises oxygen.

80. The method of Claim 78, further comprising injecting at least a portion of the first effluent stream into the one or more additional separation units to generate a hydrogen stream and an OCM feed stream.

81. The method of Claim 80, wherein the OCM feed stream contains hydrogen, methane, and ethane.

82. The method of Claim 81, wherein at least a portion of the OCM feed stream is injected into an OCM recycle loop.
83. The method of Claim 82, wherein the OCM recycle loop is comprised of any combination of i) a process gas compressor, ii) a methanation unit, iii) a CO₂ removal unit, iv) a demethanation unit, and v) the OCM unit.
84. The method of Claim 83, wherein the OCM recycle loop is comprised of i)-v).
85. The method of Claim 80, further comprising generating heat using hydrogen from the hydrogen stream.
86. The method of Claim 77, further comprising injecting at least a portion of the ethylene produced in the OCM unit into a dimerization unit to generate a butene-containing stream.
87. The method of Claim 86, further comprising injecting at least a portion of the butene-containing stream into the dimerization unit to generate a propylene-containing stream.
88. The method of Claim 80, wherein the one or more additional separation units comprise include distillation towers.
89. The method of Claim 80, wherein the one or more additional separation units comprise a pressure-swing adsorption (PSA) unit.
90. A method for producing methanol (MeOH) and hydrocarbon compounds containing at least two carbon atoms (C₂₊ compounds), comprising:
- (a) directing methane (CH₄) and an oxidizing agent into an oxidative coupling of methane (OCM) reactor to produce a product stream comprising the C₂₊ compounds, carbon monoxide (CO) and/or carbon dioxide (CO₂), and un-reacted CH₄;
 - (b) separating the CO and/or CO₂ from the product stream to generate a CO and/or CO₂ stream;
 - (c) directing the CO and/or CO₂ stream to an MeOH reactor to produce MeOH;
 - (d) separating the un-reacted CH₄ from the product stream to produce a CH₄ stream; and
 - (e) directing at least a portion of the CH₄ stream to a steam methane reformer (SMR) that produces hydrogen (H₂) and CO and/or CO₂, wherein the CH₄ stream is directed into the SMR without passing through a pre-reformer.
91. A system for producing methanol (MeOH) and hydrocarbon compounds containing at least two carbon atoms (C₂₊ compounds), comprising:
- an oxidative coupling of methane (OCM) reactor that (i) receives methane (CH₄) and an oxidizing agent and (ii) reacts the CH₄ and the oxidizing agent to yield a product stream comprising the C₂₊ compounds, carbon monoxide (CO) and/or carbon dioxide (CO₂), and un-reacted CH₄;

an MeOH reactor that (i) receives the CO and/or CO₂ separated from the product stream and (ii) reacts the CO and/or CO₂ to produce MeOH; and

a steam methane reformer (SMR) that (i) receives the un-reacted CH₄ separated from the product stream without use of a pre-reformer upstream of the SMR, and (ii) provides hydrogen (H₂) and at least one of carbon monoxide (CO) and CO₂ to the MeOH reactor to produce MeOH.

92. A method for producing methanol (MeOH) and hydrocarbon compounds containing at least two carbon atoms (C₂₊ compounds), comprising:

(a) directing methane (CH₄) and an oxidizing agent into an oxidative coupling of methane (OCM) reactor to produce a product stream comprising the C₂₊ compounds, carbon monoxide (CO) and/or carbon dioxide (CO₂), and un-reacted CH₄;

(b) separating the CO and/or CO₂ from the product stream to generate a CO and/or CO₂ stream; and

(c) directing the CO and/or CO₂ stream to an MeOH reactor to produce MeOH, wherein the CO and/or CO₂ stream is directed into the MeOH reactor without passing through an autothermal reformer (ATR).

93. A system for producing methanol (MeOH) and hydrocarbon compounds containing at least two carbon atoms (C₂₊ compounds), comprising:

an oxidative coupling of methane (OCM) reactor that (i) receives methane (CH₄) and an oxidizing agent and (ii) reacts the CH₄ and the oxidizing agent to yield a product stream comprising the C₂₊ compounds, carbon monoxide (CO) and/or carbon dioxide (CO₂), and un-reacted CH₄; and

an MeOH reactor that (i) receives CO and/or CO₂ separated from the product stream without use of a pre-reformer upstream of the MeOH reactor, and (ii) reacts the CO and/or CO₂ to produce MeOH.

94. A method for producing methanol (MeOH) and hydrocarbon compounds containing at least two carbon atoms (C₂₊ compounds), comprising:

(a) directing methane (CH₄) and an oxidizing agent into an oxidative coupling of methane (OCM) reactor to produce a product stream comprising the C₂₊ compounds and un-reacted CH₄;

(b) separating the un-reacted CH₄ from the product stream to produce a CH₄ stream;

(c) directing at least a portion of the CH₄ stream to a steam methane reformer (SMR) that produces hydrogen (H₂) and CO and/or CO₂, wherein the CH₄ stream is directed into the SMR without passing through a pre-reformer; and

(d) directing the CO and/or CO₂ produced in (c) to an MeOH reactor to produce MeOH.

95. A system for producing methanol (MeOH) and hydrocarbon compounds containing at least two carbon atoms (C₂₊ compounds), comprising:

an oxidative coupling of methane (OCM) reactor that (i) receives methane (CH₄) and an oxidizing agent and (ii) reacts the CH₄ and the oxidizing agent to yield a product stream comprising the C₂₊ compounds and un-reacted CH₄;

a steam methane reformer (SMR) that (i) receives the un-reacted CH₄ separated from the product stream without use of a pre-reformer upstream of the SMR, and (ii) provides hydrogen (H₂) and carbon monoxide (CO) and/or CO₂; and

an MeOH reactor that (i) receives the CO and/or CO₂ and (ii) reacts the CO and/or CO₂ to produce MeOH.

96. A method for producing ethylene and methanol, the method comprising:

(a) injecting a methane feedstream and an oxidizing agent-containing feedstream into an oxidative coupling of methane (OCM) subsystem that generates an OCM effluent stream containing ethylene, CO₂ and/or CO, and unconverted methane;

(b) injecting the OCM effluent stream into a CO₂ separation subsystem that generates a stream containing CO₂ and a stream containing methane and ethylene;

(c) injecting at least a portion of the stream containing CO₂ into a methanol synthesis subsystem;

(d) injecting at least a portion of the stream containing methane and ethylene into a purification subsystem that generates a stream containing methane and a stream containing ethylene; and

(e) injecting at least a portion of the stream containing methane into a steam methane reformer (SMR) subsystem, wherein the at least the portion of the stream containing methane is injected into the SMR subsystem without passing through a pre-reformer.

97. A method for producing olefins, comprising:

(a) directing methane (CH₄) and an oxidizing agent into an oxidative coupling of methane (OCM) reactor to produce a product stream comprising the C₂₊ compounds including olefins, carbon monoxide (CO) and/or carbon dioxide (CO₂), and un-reacted CH₄;

(b) enriching the CO and/or CO₂ from the product stream to generate an enriched CO and/or CO₂ stream;

(c) directing the enriched CO and/or CO₂ stream to an MeOH reactor to produce MeOH;

- (d) directing at least some of said MeOH to a methanol to olefins (MTO) reactor to produce a second olefins stream;
- (e) enriching the un-reacted CH₄ from the product stream to produce an enriched CH₄ stream; and
- (f) directing at least a portion of the enriched CH₄ stream to a steam methane reformer (SMR) that produces hydrogen (H₂) and CO and/or CO₂.

98. A system for producing olefins, comprising:

an oxidative coupling of methane (OCM) reactor that (i) receives methane (CH₄) and an oxidizing agent and (ii) reacts the CH₄ and the oxidizing agent to yield a product stream comprising the C₂₊ compounds including olefins, carbon monoxide (CO) and/or carbon dioxide (CO₂), and un-reacted CH₄;

an MeOH reactor that (i) receives CO and/or CO₂ enriched from the product stream and (ii) reacts the CO and/or CO₂ to produce MeOH;

a methanol to olefins (MTO) reactor that converts at least some of said MeOH into olefins to produce a second olefins stream; and

a steam methane reformer (SMR) that (i) receives un-reacted CH₄ enriched from the product stream and (ii) provides hydrogen (H₂) and at least one of carbon monoxide (CO) and CO₂ to the MeOH reactor to produce MeOH.

99. A method for producing propylene, the method comprising:

(a) feeding propane into a propane dehydrogenation (PDH) process, which PDH process converts said propane into hydrocarbon compounds with three or more carbon atoms (C₃₊ compounds) including propylene and PDH off-gas, which PDH off-gas comprises hydrocarbon compounds with one carbon atom (C₁ compounds), hydrocarbon compounds with two carbon atoms (C₂ compounds) and hydrogen (H₂);

(b) feeding said PDH off-gas into an oxidative coupling of methane (OCM) process, which OCM process converts said C₁ compounds into ethylene, wherein said OCM process releases heat; and

(c) providing said heat to said PDH process.

100. A system, comprising:

a cracking reactor that receives a hydrocarbon feedstream comprising feedstream hydrocarbons and, with the aid of a cracking catalyst, facilitates cracking of said feedstream hydrocarbons to produce a cracked stream comprising cracked hydrocarbons, wherein said cracked hydrocarbons have a lower molecular weight than said feedstream hydrocarbons;

a separations unit in fluid communication with said cracking reactor, wherein said first separations unit receives said cracked stream and separates said cracked hydrocarbons of said cracked stream into a plurality of streams including a methane-containing stream comprising methane; and

an oxidative coupling of methane (OCM) reactor in fluid communication with said separations unit, wherein said OCM reactor receives said methane-containing stream and, with the aid of an OCM catalyst, converts said methane from said methane-containing stream to higher hydrocarbon products to yield an OCM product stream comprising said higher hydrocarbon products.



101. A method, comprising:

(a) directing a hydrocarbon feedstream comprising feedstream hydrocarbons into a cracking reactor comprising a cracking catalyst that facilitates cracking of said feedstream hydrocarbons, to produce a cracked stream comprising cracked hydrocarbons, wherein said cracked hydrocarbons have a lower molecular weight than said feedstream hydrocarbons;



(b) directing said cracked stream into a separations unit that separates said cracked hydrocarbons from said cracked stream into a plurality of streams including a methane-containing stream comprising methane; and

(c) directing said methane-containing stream into an oxidative coupling of methane (OCM) reactor comprising an OCM catalyst that facilitates conversion of said methane from said methane-containing stream to higher hydrocarbon products to yield an OCM product stream comprising said higher hydrocarbon products.



1/23

**FIG. 1****FIG. 2**



2/23

300**FIG. 3**400**FIG. 4**

3/23

**FIG. 5****FIG. 6**

4/23

**FIG. 7****FIG. 8**

5/23




FIG. 9A





FIG. 9B

6/23

940***FIG. 9C***




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16

1700




FIG. 17




FIG. 18






FIG. 19


17/23

2000**FIG. 20**

18/23

***FIG. 21A***

20/23

***FIG. 21C***




FIG. 22




FIG. 23

23/23




FIG. 24

100




FIG. 1