



(22) Date de dépôt/Filing Date: 1996/11/05

(41) Mise à la disp. pub./Open to Public Insp.: 1998/05/05

(45) Date de délivrance/Issue Date: 2002/06/25

(51) Cl.Int.⁶/Int.Cl.⁶ E21B 33/138

(72) Inventeur/Inventor:
Loree, Dwight N., CA

(73) Propriétaire/Owner:
ENERCHEM INTERNATIONAL INC., CA

(74) Agent: THOMPSON LAMBERT LLP

(54) Titre : LIQUIDE POUR LE TRAITEMENT DE PUITES

(54) Title: WELL TREATMENT FLUID

(57) **Abrégé/Abstract:**

A well treatment fluid comprising a mixture of (A) a major amount of a first hydrocarbon fluid, the first hydrocarbon fluid being composed predominantly of diaromatics and triaromatics having more than 16 hydrocarbons, and (B) a minor amount of a second hydrocarbon fluid, the second hydrocarbon fluid being composed predominantly of hydrocarbons having from 7 to 12 carbon atoms, wherein the mixture has a density greater than 1000 kg/m³ at 15°C and a viscosity lower than 30 centiStokes at 20°C. In a method according to the invention, a kill fluid is formed by mixing the first and second hydrocarbon fluids to produce a hydrocarbon mixture having a viscosity of less than 30 centiStokes at 20°C and a density above 1000 kg/m³ at 15°C



2189610

ABSTRACT OF THE DISCLOSURE

A well treatment fluid comprising a mixture of
(A) a major amount of a first hydrocarbon fluid, the first
5 hydrocarbon fluid being composed predominantly of
diaromatics and triaromatics having more than 16
hydrocarbons, and (B) a minor amount of a second
hydrocarbon fluid, the second hydrocarbon fluid being
composed predominantly of hydrocarbons having from 7 to 12
10 carbon atoms, wherein the mixture has a density greater
than 1000 kg/m³ at 15°C and a viscosity lower than 30
centiStokes at 20°C. In a method according to the
invention, a kill fluid is formed by mixing the first and
second hydrocarbon fluids to produce a hydrocarbon mixture
15 having a viscosity of less than 30 centiStokes at 20°C and
a density above 1000 kg/m³ at 15°C

5 TITLE OF THE INVENTION:
Well Treatment Fluid

NAME(S) OF INVENTOR(S):
Dwight N. Loree

10

FIELD OF THE INVENTION

This invention relates to hydrocarbon fluids used to treat oil and gas wells, and to a method of making such a fluid.

15

BACKGROUND OF THE INVENTION

The ideal kill fluid has density above 1000 kg/m^3 at 15°C , low viscosity, high flash point, is non-aqueous, has a pour point that is suitable for winter use, and is compatible with a wide variety of geologic formations.

Such fluids are difficult to obtain. Aqueous saline fluids have high flash point and low viscosity, but tend to be damaging to formations. Condensates and light petroleum distillates typically have densities much lower than 1000 kg/m_3 . Heavier hydrocarbon fluids are often not suitable due to low viscosity and may be formation damaging, particularly if they contain wax and asphaltene components. On the other hand, hydrocarbon fluids that are high in aromatics are preferred for use in wells since they tend to be compatible with a wide range of reservoirs.

30

SUMMARY OF THE INVENTION

There is therefore provided in accordance with a first aspect of the invention, a well treatment fluid comprising a mixture of (A) a major amount of a first hydrocarbon fluid, the first hydrocarbon fluid being composed predominantly of polycyclic aromatics having more than 16 carbon atoms, and (B) a minor amount of a second

35

hydrocarbon fluid, the second hydrocarbon fluid being composed predominantly of hydrocarbons having from 7 to 12 carbon atoms, wherein the mixture has a density greater than 1000 kg/m^3 at 15°C and a viscosity lower than 30 centiStokes at 20°C .

In a further aspect of the invention, there is provided a method of producing a well treatment fluid, comprising the steps of:

obtaining a first hydrocarbon fluid, the first hydrocarbon fluid being composed predominantly of polycyclic aromatics and having a density greater than 1000 kg/m^3 at 15°C and a viscosity at 20°C greater than 30 centiStokes;

obtaining a second hydrocarbon fluid, the second hydrocarbon fluid being composed predominantly of hydrocarbons having from 7 to 12 carbon atoms and having a density less than 1000 kg/m^3 at 15°C ; and

mixing the second hydrocarbon fluid with the first hydrocarbon fluid to produce a hydrocarbon mixture having a viscosity of less than 30 centiStokes at 20°C and a density above 1000 kg/m^3 at 15°C .

The second hydrocarbon fluid is a diluent, and preferably has more than 50 LV% aromatics, and comprises 15 LV% or more of the mixture. The resultant mixture preferably has a viscosity lower than 15 centiStokes at 20°C .

The first hydrocarbon fluid is preferably a light cycle oil that comprises at least 80 LV% of aromatics.

The fluid according to the invention may be used to treat a well by injecting it into a well according to known methods.

In a further aspect of the invention, a method of treating a well with a hydrocarbon fluid mixture in association with a target fluid that has a known density

involves selecting the proportions of a first fraction composed predominantly of polycyclic aromatics having more than 16 carbon atoms and a second fraction composed predominantly of hydrocarbons having from 7 to 12 carbon atoms such that the mixture has a density matching the known density of the target fluid. This hydrocarbon fluid mixture is then injected into the well.

In a further aspect of the invention, there is provided a method of treating a well, the method comprising the step of:

injecting into the well a hydrocarbon fluid mixture composed predominantly of polycyclic aromatics having more than 16 carbon atoms.

These and other aspects of the invention are described in the detailed description of the invention and claimed in the claims that follow.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The preferred kill fluid according to the invention is a 100% hydrocarbon kill fluid with density greater than 1000 kg/m^3 and viscosity less than 30 cSt at 20° . In this patent document, "predominantly" in relation to a fluid component means 50% or more by volume of that component in the fluid.

This preferred kill fluid is formed by first obtaining a light cycle oil having a density greater than 1000 kg/m^3 and a viscosity greater than 30 cSt (cSt designates centiStokes). The preferred fluid is predominantly composed of polycyclic aromatics having more than 16 carbon atoms, preferably having 20 or more carbon atoms, preferably has more than about 80 LV% aromatics, and more particularly preferably comprises (all

figures show LV% as determined by mass spectrometry per ASTM D-2549, 2786 and 3239) the following components:

Summary:

	Paraffins	4.0
5	Naphthenes	6.3
	Aromatics	89.7

The Naphthenic Distribution of the preferred fluid is:

	1 Ring	1.6
	2 Ring	1.8
10	3 Ring	2.1
	4 Ring	0.8

The Aromatic Distribution of the preferred fluid is:

	Monoaromatics	10.9
	___Naphthenebenzenes	5.8
15	---Dinaphthenebenzenes	5.1
	Diaromatics	42.4
	---Naphthalenes	19.9
	---Acenaphthenes/Dibenzofurans	11.1
	---Fluorenes	11.4
20	Triaromatics	27.5
	---Phenenanthrenes	22.9
	---Naphthenephenanthrenes	4.6
	Tetraaromatics	4.8
	---Pyrenes	4.8
25	Thiopheno Aromatics	4.1
	---Benzothiophenes	2.1
	---Dibenzothiophenes	2.0

30 The polycyclic aromatics are preferably predominantly diaromatics and triaromatics, however, providing a formulation of the light cycle oil remains formation compatible and not too viscous for practical use, the polycyclic aromatics may include various amounts of tetraaromatics.

This fluid contains the following constituents according to gas chromatography:

	Heptanes	0.13
	Octanes	0.28
5	Nonanes	0.37
	Decanes	2.27
	Tetradecanes	1.49
	Pentadecanes	3.78
	Hexadecanes	5.02
10	Heptadecanes	5.44
	Octadecanes	6.99
	Nonadecanes	9.62
	Eicosanes	17.63
	Heneicosanes	13.55
15	Docasanes	20.72
	Tricosanes	10.47
	Tetracosanes	2.24

From this it can be seen that the fluid is predominantly composed of diaromatics, triaromatics and other hydrocarbons having more than 16 carbon atoms, and is more than 50 LV% hydrocarbons having 20 or more carbon atoms. Diaromatics and triaromatics are important components of the well treatment fluid of the invention since they are heavy components and yet when added to a well, particularly with a diluent high in aromatics, tend not to be formation damaging.

Such a fluid is available from Koch Refining Company, L.P. of St. Paul, Minnesota. This light cycle oil has an initial density of approximately 1045 kg/m³, a pour point of -21°C, a flashpoint of 146°C (PMCC) and a viscosity at 20°C of 40.62 cSt.

The light cycle oil may be injected into a well directly in conditions that maintain the fluid with a suitable viscosity, preferably lower than 50 cSt at the

ambient conditions, that allows it to flow and be injected into the well. If the fluid is not warm enough to flow, it may be heated and kept warm for injection into a well.

The light cycle oil is, however, for most applications, mixed with a diluent hydrocarbon fluid, preferably a condensate or light petroleum distillate, that has a sufficiently low viscosity that the mixture has a density greater than 1000 kg/m^3 at 15°C and a viscosity lower than 30 centiStokes at 20°C , while the mixture remains formation compatible. The light cycle oil is preferably the major component (more than 50 LV%) and the diluent is preferably the minor component (less than 50 LV%).

A preferred diluent with which the light cycle oil may be mixed is known by the trademark WAXSOL™, may be obtained from Trysol Canada Ltd. of Calgary, Alberta, Canada and has the following properties:

	Aromatics	59	LV%
	Flashpoint (PMCC)	12	deg.C
20	Flashpoint (COC)	15	deg.C
	Absolute Density	785	kg/m ³ @ 15 deg.C
	API Gravity	48	deg.C
	Cloud Point	-22	deg.C
	Pour Point	<-60	deg.C
25	Reid Vapour Pressure	4	kPa @ 37.8 deg.C

WAXSOL™ fluid is composed approximately of the following hydrocarbons (LV% according to gas chromatography):

	iso-Pentane	0.39
30	n-Hexanes	0.31
	Heptanes	11.07
	Octanes	14.90
	Nonanes	8.30
	Decanes	10.66

2189610

7

	Undecanes	6.15
	Dodecanes	3.62
	Tridecanes	2.30
	Tetradecanes	1.21
5	Pentadecanes	0.50
	Hexadecanes	0.30
	Heptadecanes	0.17
	Octadecanes	0.13
	Nonadecanes	0.08
10	Eicosanes	0.02
	Heneicosanes	0.01
	Docosanes	0.02
	Benzene	0.46
	Toluene	11.40
15	Ethyl Benzene, m+p-xylene	14.53
	o-Xylene	2.61
	1,2,4-trimethylbenzene	2.14
	Cyclopentane	0.02
	Methylcyclopentane	0.46
20	Cyclohexane	1.21
	Methylcyclohexane	7.01

As used in this patent document, LV means liquid volume. It is preferred that the WAXSOL™ fluid be added in an amount of about 15 LV% of the mixture to yield the mixture having the properties defined above.

The resultant fluid mixture, when the light cycle oil fraction constitutes 85 LV% and the diluent WAXSOL™ fraction constitutes 15 LV%, has a density of approximately 1006 kg/m³, a pour point of -37°C, a flashpoint of 28°C (PMCC), a viscosity at 20°C of 12.36 cSt, contains 89 LV% aromatics, has a Reid vapour pressure of 4 kPa @ 37.8 deg.C, Flashpoint (COC) 37°C, API Gravity 9 deg., Cloud Point -16°C and a Pour Point of -37°C. Viscosity at -20°C is 211.6 cSt, at 0° is 35.82 cSt, and at 5°C is 25.83 cSt.

2189610

8

Mixtures according to the invention that have a viscosity less than 16 cSt at 20°C are believed particularly useful. For a blend of 95 LV% light cycle oil and 5 LV% WAXSOL™ diluent, the fluid at -20°C is frozen, at 0°C has a viscosity of 103.9 cSt, at 5°C has a viscosity of 70.14 cSt and at 20°C has a viscosity of 25.87 cSt. While the 95/5 blend has a density higher than that of the 85/15 blend, it is not pumpable at -20°C, which limits its utility for winter use.

The resultant mixture has a bimodal carbon distribution in that the mixture has a minor peak in the gas chromatographic analysis between C₇ and C₁₀, due to the diluent fraction, and another peak centered at about C₂₀ to C₂₂, due to the diaromatic and triaromatic fraction. The C₇ to C₁₀ components provide low viscosity, while the C₂₀ to C₂₂ components provide weight.

Depending on the proposed use, other formation compatible light hydrocarbons (predominantly composed of C₇ - C₁₂ hydrocarbons) may be mixed with the light cycle oil in place of or in addition to the WAXSOL™ fluid.

A further exemplary diluent is FRACSOL™ hydrocarbon fluid available from Trysol Canada Ltd. of Calgary, Alberta, Canada, whose properties are as follows:

	Aromatics	63	LV%
25	Reid Vapour Pressure	<1	kPa @ 37.8 deg.C
	Flashpoint (PMCC)	30	deg.C
	Flashpoint (COC)	35	deg.C
	Absolute Density	815	kg/m ³ @ 15 deg.C
	API Gravity	42	deg.C
30	Surface Tension (Oil to Air)	25	dynes/cm @ 22 deg.C
	Interfacial Tension (Water to Oil)	27	dynes/cm @ 22 deg.C
	Cloud Point	8	deg.C
	Pour Point	-13	deg.C
	Aniline Point	56	deg.C

2189610

9

The composition of FRACSOL™ fluid is approximately as follows (LV% as determined by gas chromatography):

	Heptanes	1.85
5	Octanes	8.77
	Nonanes	7.81
	Decanes	9.29
	Undecanes	8.44
	Dodecanes	6.00
10	Tridecanes	5.74
	Tetradecanes	5.42
	Pentadecanes	3.80
	Hexadecanes	3.78
	Heptadecanes	3.28
15	Octadecanes	3.28
	Nonadecanes	3.74
	Eicosanes	2.40
	Heneicosanes	2.75
	Docasanes	2.19
20	Tricosanes	1.62
	Tetracosanes	1.76
	Pentacosanes	1.21
	Hexacosanes	1.11
	Heptacosanes	0.86
25	Octacosanes	0.80
	Nonacosanes	0.67
	Triacontanes	3.10
	Toluene	1.32
	Ethyl Benzene, m=p-xylene	3.68
30	o-Xylene	1.68
	1,2,4-trimethylbenzene	1.72
	Methylcyclopentane	0.01
	Cyclohexane	0.04
	Methylcyclohexane	1.89

2189610

10

Up to 19.56 LV% FRACSOL™ diluent may be added to the light cycle oil with the density of the mixture remaining above 1000 kg/m³ at 15°C.

5 A further example diluent is XYSOL™ blend hydrocarbon fluid available from Trysol Canada Ltd. of Calgary, Alberta, Canada, whose properties are as follows:

	Aromatics	51	LV%
	Flashpoint (PMCC)	24	deg.C
	Flashpoint (COC)	23	deg.C
10	Absolute Density	800	kg/m ³ @ 15 deg.C
	PI Gravity	45	deg.C
	Cloud Point	-48	deg.C
	Pour Point	<-60	deg.C
	Reid Vapour Pressure	2	kPa @ 37.8 deg.C

15 The composition of XYSOL™ blend fluid is approximately as follows (LV% as determined by mass spectrometry per ASTM D-2789):

	Paraffins	49.00
	Monocycloparaffins	16.60
20	Dicycloparaffins	3.59
	Alkylbenzenes	30.20
	Indanes/Tetrains	0.03
	Naphthalenes	0.58
	Alkanes (summary)	49.00
25	Aromatics (summary)	51.00

XYSOL™ blend composition as determined by gas chromatography is as follows (LV%):

	Heptanes	0.83
	Octanes	13.85
30	Nonanes	14.29
	Decanes	11.52
	Undecanes	4.46
	Dodecanes	1.56
	Tridecanes	0.63

2189610

11

	Tetradecanes	0.54
	Pentadecanes	0.20
	Hexadecanes	0.44
	Heptadecanes	0.16
5	Octadecanes	0.18
	Nonadecanes	0.11
	Eicosanes	0.11
	Heneicosanes	0.05
	Docosanes	0.05
10	Tricosanes	0.02
	Benzene	0.01
	Toluene	4.97
	Ethylbenzene, p+m-Xylene	20.91
	o-Xylene	5.39
15	1,2,4 Trimethylbenzene	2.47
	Complex Aromatics	15.02
	Cyclohexane	0.02
	Methylcyclohexane	2.21

20 A further example of a diluent is SOLUENE™ 24 hydrocarbon fluid available from Trysol Canada Ltd. of Calgary, Alberta, Canada, whose properties are as follows:

	Aromatics	50	LV%
	Flashpoint (PMCC)	24	deg.C
	Flashpoint (COC)	23	deg.C
25	Absolute Density	780	kg/m ³ @ 15 deg.C
	API Gravity	49.8	deg.
	Cloud Point	<-60	deg.C
	Pour Point	<-60	deg.C
	Reid Vapour Pressure	2	kPa @ 37.8 deg.C

30 The composition of SOLUENE 24™ fluid is approximately as follows (LV% as determined by mass spectrometry per ASTM D-2789):

	Paraffins	53.08
	Monocycloparaffins	17.01

2189610

12

	Dicycloparaffins	3.05
	Alkylbenzenes	26.37
	Indanes/Tetrains	0.03
	Naphthalenes	0.46
5	Alkanes (summary)	53.08
	Aromatics (summary)	46.92
	Heptanes	0.84
	Octanes	14.05
	Nonanes	19.22
10	Decanes	14.64
	Undecanes	3.06
	Dodecanes	0.65
	Tridecanes	0.22
	Tetradecanes	0.08
15	Pentadecanes	0.07
	Hexadecanes	0.11
	Heptadecanes	0.04
	Octadecanes	0.04
	Nonadecanes	0.03
20	Eicosanes	0.03
	Toluene	2.00
	Ethylbenzene, p+m-Xylene	23.70
	o-Xylene	6.81
	1,2,4 Trimethylbenzene	2.98
25	Complex Aromatics	9.76
	Cyclohexane	0.02
	Methylcyclohexane	1.65

30 A further example of a diluent is FX-2 hydrocarbon fluid available from Amoco Canada of Calgary, Alberta, Canada, whose composition is approximately as follows (LV% as determined by gas chromatography):

	iso-Pentane	0.04
	n-Pentane	0.06
	n-Hexanes	1.22

	Heptanes	18.19
	Octanes	20.60
	Nonanes	11.48
	Decanes	8.43
5	Undecanes	4.69
	Dodecanes	2.25
	Tridecanes	1.52
	Tetradecanes	0.65
	Pentadecanes	0.38
10	Hexadecanes	0.28
	Heptadecanes	0.24
	Octadecanes	0.20
	Nonadecanes	0.09
	Eicosanes	0.07
15	Heneicosanes	0.06
	Docosanes	0.06
	Tricosanes	0.13
	Tetracosanes	0.07
	Pentacosanes	0.06
20	Hexacosanes	0.06
	Heptacosanes	0.04
	Octacosanes	0.09
	Benzene	0.19
	Toluene	5.04
25	Ethyl Benzene, m+p-xylene	4.89
	o-Xylene	1.84
	1,2,4-trimethylbenzene	0.14
	Cyclopentane	0.02
	Methylcyclopentane	0.46
30	Cyclohexane	1.14
	Methylcyclohexane	13.04

A mixture of 12% FX-2™ and light cycle oil has density of 1087 kg/m³ at 15°C, viscosity of 12.95 cSt at

20°C, cloud point of -18°C, pour point of -39°C and a flash point of 27°C.

While each of the hydrocarbon fluids WAXSOL™, XYSOL™, SOLUENE 24™ and FRACSOL 30™ with which the light cycle oil may be mixed has more than 50 LV% aromatics, and this is preferred, it is believed possible to use a condensate or light petroleum distillate having as low as 30 LV% aromatics.

A further example of a diluent is SOLUENE™ HAD hydrocarbon fluid available from Trysol Canada Limited of Calgary, Alberta, Canada, whose composition is approximately as follows (LV% as determined by gas chromatography):

	Nonanes	0.18
15	Decanes	11.16
	Undecanes	60.35
	Dodecanes	16.59
	Tridecanes	1.62
	Tetradecanes	0.39
20	Pentadecanes	0.33
	Hexadecanes	0.11
	Heptadecanes	0.17
	Octadecanes	0.11
	Nonadecanes	0.03
25	Eicosanes	0.01
	Heneicosanes	0.01
	Toluene	0.06
	Ethyl Benzene, m+p-xylene	5.75
	o-Xylene	1.15
30	1,2,4-trimethylbenzene	1.99

When a mixture of 10 LV% SOLUENE™ HAD is mixed with 90 LV% light cycle oil (density 1040), the fluid had a pour point of -42°C, a density of 1030 kg/m₃ at 15°C, and

a viscosity of 20 cSt at 20°C. The density of SOLUENE™ HAD is 924 kg/m₃ at 15°C.

After mixing the light cycle oil with one or more of the diluents as outlined above, the fluid may be injected into a well to kill the well in accordance with known techniques.

A further example of a fluid believed to have utility for providing high density components is a light cycle oil available from Koch Refining Company that has the following characteristics:

	Absolute Density @ 15.0 deg C	1090 kg/m ³	ASTM D-4052
	Pour Point	-15 deg C	ASTM D-97
	Flash Point (PMCC)@ 101.325 kPa	201 deg C	ASTM D-93
	Color	orange	
15	Cloud Pt: Fluid gelled with no apparent crystal formation		
	Reid Vapour Pressure @ 37.8 deg C: Fluid is too viscous @ 0 deg C for measurement		
	Kinematic Viscosity @ 0 deg C	>150,000	ASTM D-445
	Kinematic Viscosity @ 20 deg C	3323	
20	Kinematic Viscosity @ 40 deg C	209.9	
	Kinematic Viscosity @ 60 deg C	40.10	

Fluid composition of this high density fluid as determined by mass spectrometry is as follows (LV%):

	Paraffins	0.8
25	Naphthenes	9.2
	Aromatics	90.0
	Naphthenic Distribution-Caps	
	1 Ring	1.1
	2 Ring	1.9
30	3 Ring	2.3
	4 Ring	1.9
	5 Ring	1.3
	6 Ring	0.7

	Aromatic Distribution	
	Monoaromatics	5.0
	___Alkylbenzenes	0.0
	___Naphthenebenzenes	1.8
5	---Dinaphthenebenzenes	3.2
	Diaromatics	8.8
	---Naphthalenes	0.5
	---Acenaphthenes/Dibenzofurans	3.4
	---Fluorenes	4.9
10	Triaromatics	25.0
	---Phenenanthrenes	14.1
	---Naphthenephenanthrenes	10.9
	Tetraaromatics	40.9
	---Pyrenes	33.1
15	___Chyrsenes	7.8
	Pentaaromatics	0.5
	___Perylenes	0.5
	___Dibenzanthracenes	0.0
	Thiopheno Aromatics	6.1
20	---Benzothiophenes	3.1
	---Dibenzothiophenes	3.0
	___Naphthabenzothiophenes	0.0
	Unidentifies Aromatics	3.7
	___Class I(See Naph.Phen.)	Inc W/NPA
25	___Class II	0.0
	___Class III	0.0
	___Class IV	3.6
	___Class V	0.0
	___Class VI	0.0
30	___Class VII	0.1

The invention also permits matching the density of the fluid mixture to another fluid. For example, in the case of a squeeze in a heavy oil reservoir, it is desirable

to match the squeeze fluid density to the density of the heavy oil. A mixture is selected according to the formula: $(D_{lco} \cdot x + D_{diluent} \cdot (1-x)) = D_{heavy\ oil}$, where D_{lco} is the density of the light cycle oil, eg from Koch Refining Company, $D_{diluent}$ is the density of the diluent, $D_{heavy\ oil}$ is the density of the heavy oil, and x is the fraction of light cycle oil and $1-x$ is the fraction of the diluent. This mixture then has a density that matches the density of the heavy oil.

10 In a further example, during acidizing of a well, it is beneficial to add a solvent that has a density equal to the density of the acid, since this is believed to assist in forming a stable emulsion of acid and solvent. A mixture is formed by adding an amount of diluent and the
15 light cycle oil that has a density that matches the density of the acid according to the formula $(D_{lco} \cdot y + D_{diluent} \cdot (1-y)) = D_{acid}$, where D_{acid} is the density of the acid. y is the fraction of light cycle oil. An exemplary acid is HCl, which is typically used in acidizing with a density of 1070
20 kg/m₃ (15% solution). Mixture of the heavy light cycle oil (1090 density) with one of the diluents may be used to achieve this density. The fluid whose density is to be matched may be referred to as the target fluid.

The fluid may be used during squeezing, where
25 pressure is applied to the fluid in a well at lower than frac pressures, during fracs or minifrac where pressure above or just above frac pressure is applied to the fluid in the well, during acidizing, killing the well and other well treatment applications where high or variable density
30 solvents are beneficial.

A person skilled in the art could make immaterial modifications to the invention described in this patent document without departing from the essence of the

2189610

18

invention that is intended to be covered by the scope of the claims that follow.

5 THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

1. A well treatment fluid, comprising:
a mixture of (A) a major amount of a first
10 hydrocarbon fluid, the first hydrocarbon fluid being
composed predominantly of polycyclic aromatics having more
than 16 carbon atoms, and (B) a minor amount of a second
hydrocarbon fluid, the second hydrocarbon fluid being
composed predominantly of hydrocarbons having from 7 to 12
15 carbon atoms; and
wherein the mixture has a density greater than
1000 kg/m³ at 15°C and a viscosity lower than 30
centiStokes at 20°C.
- 20 2. The well treatment fluid of claim 1 in which the
second hydrocarbon fluid comprises at least 30 LV%
aromatics.
3. The well treatment fluid of claim 1 in which the
25 second hydrocarbon fluid comprises at least 50 LV%
aromatics.
4. The well treatment fluid of any of claim 1, 2 or
3 in which the mixture has a viscosity lower than 15
30 centiStokes at 20°C.
5. The well treatment fluid of claims 1-4 in which
the second hydrocarbon fluid comprises at least 15 LV% of
the mixture.
- 35 6. The well treatment fluid of claims 1-5 in which
the first hydrocarbon fluid comprises at least 80 LV% of

5 aromatics.

7. The well treatment fluid of any of claims 1-6 in which the polycyclic aromatics are comprised predominantly of diaromatics and triaromatics.

10

8. A method of producing a well treatment fluid, comprising the steps of:

obtaining a first hydrocarbon fluid, the first hydrocarbon fluid being composed predominantly of polycyclic aromatics and having a density greater than 1000 kg/m³ at 15°C and a viscosity at 20°C greater than 30 centiStokes;

obtaining a second hydrocarbon fluid, the second hydrocarbon fluid being composed predominantly of hydrocarbons having from 7 to 12 carbon atoms and having a density less than 1000 kg/m³ at 15°C; and

mixing the second hydrocarbon fluid with the first hydrocarbon fluid to produce a hydrocarbon mixture having a viscosity of less than 30 centiStokes at 20°C and a density above 1000 kg/m³ at 15°C.

9. The method of claim 8 in which the second hydrocarbon fluid comprises at least 30 LV% aromatics.

30 10. The method of claim 8 in which the second hydrocarbon fluid comprises at least 50 LV% aromatics.

11. The method of claims 8, 9 or 10 in which the mixture has a viscosity lower than 15 centiStokes at 20°C.

35

12. The method of claims 8, 9, 10 or 11 in which the

5 second hydrocarbon fluid comprises at least 15 LV% of the mixture.

13. The method of claims 8-12 in which the first hydrocarbon fluid comprises at least 80 LV% aromatics.

10

14. The method of any of claims 8-13 in which the polycyclic aromatics are comprised predominantly of diaromatics and triaromatics.

15 15. A method of treating a well, the method comprising the step of:

injecting into the well a hydrocarbon fluid comprising mixture comprising a first fraction composed predominantly of polycyclic aromatics having more than 16 carbon atoms and a second fraction composed predominantly of hydrocarbons having from 7 to 12 carbon atoms, wherein the mixture has a density greater than 1000 kg/m³ at 15°C and a viscosity lower than 30 centiStokes at 20°C.

25 16. A method of treating a well with a hydrocarbon fluid mixture in association with a target fluid that has a known density, the method comprising the step of:

forming the hydrocarbon fluid mixture by mixing together a first fraction composed predominantly of polycyclic aromatics having more than 16 carbon atoms and a second fraction composed predominantly of hydrocarbons having from 7 to 12 carbon atoms, wherein the mixture has a density matching the known density of the target fluid;

30 and injecting the hydrocarbon fluid mixture into the well.

35

17. The method of claim 16 in which the target fluid

5 is acid.

18. The method of claim 16 in which the target fluid is the reservoir fluid.

10 19. The method of claim 17 or 18 in which the hydrocarbon fluid mixture is squeezed in the well.