




(72) LAPORTA, Thomas F., US
(72) SABNANI, Krishan Kumar, US
(72) WOO, Thomas Yat Chung, US
(73) LUCENT TECHNOLOGIES INC., US

(51) Int.Cl.⁶ H04Q 7/12

(30) 1996/07/24 (686,074) US

(54) **SYSTEME DE MESSAGERIE BIDIRECTIONNEL SANS FIL**

(54) **TWO-WAY WIRELESS MESSAGING SYSTEM**



(57) A two-way wireless messaging system includes a messaging network having at least one user agent corresponding to a subscriber of a two-way wireless messaging service. The subscriber receives messages from the messaging network along a first communication channel. The user agent includes a plurality of messages stored therein wherein a predetermined message is stored in the user agent and forwarded to a desired destination in response to an originating message code that is received from a two-way messaging device of the subscriber along a second communication return channel. The originating message code can be expanded by the user agent. The messages stored by the user agent can be modified so that different messages can be forwarded to the predetermined destination. The user agent also maintains location information of the two-way messaging device of the subscriber.

Abstract

A two-way wireless messaging system includes a messaging network having at least one user agent corresponding to a subscriber of a two-way wireless messaging service. The subscriber receives messages from the messaging network along a first communication channel. The user agent includes a plurality of messages stored therein wherein a predetermined message is stored in the user agent and forwarded to a desired destination in response to an originating message code that is received from a two-way messaging device of the subscriber along a second communication return channel. The originating message code can be expanded by the user agent. The messages stored by the user agent can be modified so that different messages can be forwarded to the predetermined destination. The user agent also maintains location information of the two-way messaging device of the subscriber.

TWO-WAY WIRELESS MESSAGING SYSTEM

This application is related to commonly assigned, copending application entitled Two-Way Wireless Messaging System, filed on the same date as the present application by
5 the same inventors.

Field of the Invention

This invention relates to a two-way wireless messaging system and method using a messaging network having at least one subscriber user agent that stores messages that
10 are forwarded to predetermined destinations.

Background of the Invention

Wireless messaging, such as wireless paging, is a popular consumer wireless service and will grow because of the availability of new narrowband Personal Communication
15 Services (PCS) frequencies. Wireless communication and messaging provides the foundation for many different types of services. One popular service is one-way paging, which is now very successful. Its popularity has been contributed by numerous factors, including:

- 20 (1) the small form factor of the pager device, making it portable;
- (2) the low cost of the paging service;
- (3) easy maintenance of the pager
25 device; and
- (4) ease of use for both message senders and receivers.

One-way paging, however, has no reply capability. A subscriber to a one-way paging service must rely on an
30 alternate method to respond to any messages that are received. For example, after receiving a page from the one-way paging service, a subscriber often has to find a

telephone and make a call to respond to the message.

Recently, some ideas have been proposed to design a "two-way paging system" while preserving the benefits of one-way paging, i.e., the small paging device, low cost service, easy maintenance and ease of use. These two-way
5 paging systems include return channels, but they are used only for fixed and limited replies.

In commonly assigned, copending patent application entitled Two-Way Wireless System, the disadvantages of the
10 prior art wireless messaging systems are overcome through the use of a messaging network and two-way wireless messaging device which originates, receives and replies to messages having dynamic message components to and from the messaging network.

15 **Summary of the Invention**

The present invention allows even greater control over message delivery and expansion by the use of proxy agents in the message network.

Limitations of existing wireless paging systems
20 are resolved and technical advances are achieved in the present invention by a method and system for transmitting messages on a wireless messaging network with a plurality of user agents and other intelligent servers such as transaction servers, distribution servers and batch servers.
25 The benefits of the present invention are set forth below.

In accordance with one aspect of the present invention there is provided a two-way messaging systems comprising: a messaging network; and a two-way wireless messaging device, including means in the two-way wireless
30 messaging device for generating a message having a dynamic message component the message including at least one multiple message destination address that includes a plurality of destination addresses; the messaging network including means for limiting replies from one or more one
35 destination address of the multiple message destination address.

In accordance with another aspect of the present invention there is provided a two-way messaging system, comprising: a distribution server distributing a message to at least one destination address, the message having a dynamic message component and at least one multiple message destination address; and a transaction server limiting replies to the message from at least one selected address of the multiple message destination address.

In accordance with yet another aspect of the present invention there is provided a method for message delivery in a two-way messaging system, the method comprising the steps of: distributing a message to at least one destination address, the message having a dynamic message component and at least one multiple message destination address; and limiting replies to the message from at least one selected address of the multiple message destination address.

In accordance with an exemplary embodiment of the present invention, a wireless messaging device can originate new messages or reply to previously received messages along a first communication channel (uplink), and receive messages along a second communication channel (downlink). Each such message is coded in a predetermined manner and includes, among other things, a message number that uniquely identifies a message stored both locally at the device and at the user agent, a modifier representing the customization to be applied to the message, and personalized address aliases.

A user agent inside the two-way messaging network, corresponding to a subscriber of a two-way message system, stores among other things, a plurality of messages and destination addresses. When a user agent receives a coded message from its associated subscriber, it expands the message back to the desired full message and destinations by selecting from the stored messages and destination addresses according to the code.

The message that can be transmitted is highly flexible. In addition to fixed pre-canned components, it can include dynamic components such as embedded replies, choices, predefined variables, etc. As an example, consider
5 a stock trading application. A subscriber is notified via two-way messaging when a stock he or she is interested in has reached a particular value. The notification message can embed a reply with choices to buy or sell and predefined variables for entering the number of shares and share price.

10 The dynamic components allow customization of messages by message senders and recipients, thus greatly increasing the practical applicability of the system. The particular values of the dynamic components are encoded in the message modifier, and are recovered and applied by the
15 user agent.

The coded message is much shorter than the corresponding full-text message, thus allowing reduced bandwidth usage in a wireless communication environment. Together with user agents, the use of coded message is
20 especially suited for communication scenarios in which the bandwidth in the uplink and downlink directions are asymmetric, or the end device is limited by either processing power, memory storage, or battery capacity.

The method and system of the present invention can
25 be implemented on top of any two-way messaging transport. This includes dedicated paging networks (e.g., narrowband PCS), cellular short messaging service (e.g., IS-95, IS-136 and GSM), or wireless data transport (e.g., ARDIS).

The servers can be implemented on specialized network servers or intermediate switches.

The messaging device can be a dedicated paging device similar to existing alphanumeric pagers, a unit that
5 attaches to a computing device (e.g., PDAs, laptops), or integrated as part of a communication device (e.g., cellular/PCS phones) or a computing device (e.g., PDAs, laptops).

Brief Description of the Drawings

10 The foregoing features and advantages of the present invention can be appreciated more fully from the following description, with references to the accompanying drawings in which:

Figure 1 is a block schematic diagram of a system
15 and method of the two-way wireless messaging system of the present invention showing its use in association with a public switched telephone network, data network, cellular network and a two-way messaging device.

Figure 2 is another schematic diagram of the two-
20 way wireless messaging system of the present invention.

Figure 3 is a more detailed view of the two-way wireless messaging system showing various user agents, the messaging network, and examples of messages that can be forwarded among the different subscribers.

25 Figure 4 is a schematic view showing the network architecture of the two-way wireless messaging system of the present invention.

Figure 5 shows an example of the control architecture for the two-way wireless messaging system of
30 the present invention.

Figure 6 is a block diagram showing an example of the protocol architecture used between the messaging device and the batch server of the two-way wireless messaging system of the present invention.

Figure 7 is a detailed flow chart showing an example of the protocol flow for new message delivery used with the two-way wireless messaging system of the present invention.

5 Figure 8 is a detailed flow diagram showing an example of the reply delivery in the two-way wireless messaging system of the present invention.

Figure 9 is a schematic diagram of a two-way messaging device in the form of a two-way pager that can be used with the two-way wireless messaging system of the present invention.

10 Figure 10 is a schematic diagram of an example of the batch server structure that can be used with the two-way wireless messaging system of the present invention.

15 Figure 11 is a schematic diagram showing an example of the functional parts of the user agent that can be used with the two-way wireless messaging system of the present invention.

20 Figure 12 is a schematic diagram showing an example of the various functions of the transaction server that can be used with the two-way wireless messaging system of the present invention.

Figure 12a depicts the open and closed states of the conversation manager.

25 Figure 12b depicts the state transition diagram for the recipient states of the transaction server.

Figure 13 shows a schematic illustration of a two-way messaging device where a simulated keyboard is displayed for entering a message.

30 **Detailed Description of the Invention**

Referring to Figure 1, there is shown at **10** a two-way wireless messaging system of the present invention, which allows an originating message code from a two-way messaging device **11** to be received in a user agent **12** of a

two-way messaging network **14**. The two-way messaging device **11** is illustrated throughout many of the drawings as a dedicated two-way pager. The two-way messaging device can also be an attachment to a communication device, or even
5 integrated as part of a communication or computing device. A message can be delivered through a public switched telephone network **16** that includes a network access switch **18** connected to a telephone **22** by a first communication coupling **20** through a twisted pair line, co-axial cable,
10 fiber optic line, wireless link or any other type of communication coupling. The messaging network **14** can also be connected to a cellular network **24** or data network **26** for transporting E-mail messages **27** to a desired destination such as a personal computer at a desired time.
15 Additionally, messages could be forwarded to a destination through the world-wide web **27a**.

In accordance with the present invention, a second communication coupling **28** connects the network access switch **18** to a Network Control Point (NCP) **30** that is coupled to a
20 database **32** via a third communication coupling **36**. The network **16** is coupled to the messaging network **14** via a fourth communication coupling **38**. The communication coupling between the two-way messaging device **11** and two-way messaging network **14** is an air interface. The messaging
25 network **14** also may have at least one user agent **12** corresponding to a subscriber **40** (Figure 2) of the two-way wireless messaging service. The subscriber **40** receives a message from the messaging network **14** along a first communication channel **42**. These messages can include
30 transmitted messages or replies. Messages forwarded by the two-way messaging device **11** to the messaging network **14** are forwarded along a communication return channel **43**. In the case in which messages and addresses of recipients are

coded, messages received by the two-way messaging network **14** are forwarded to a user agent **12**.

In accordance with the present invention, the user agent **12** includes a plurality of stored messages. A
5 predetermined message is forwarded to a desired destination such as a data network **26**, public switched telephone network **16** or a cellular network **24** in response to an originating message code that is received from a two-way messaging device **11** of the subscriber **40** along the second
10 communication return channel **43**. This originating message code is expanded by the user agent **12** so that the downlink message to the desired destination can include full information. Also, the selected destination could be a second two-way messaging device **44** (Figure 1).

15 As shown in Figures 1 and 2, the services which can use the two-way wireless messaging system **10** vary, and can include services for sending messages to 1) a telephone **22**, 2) a computer as E-Mail **27**, and another second messaging device, such as a pager **44**. The second communication return
20 channel **43** used by the two-way messaging device **11** and any other device not only carries new messages or replies, but also enhances the system **10** capabilities. It can be used for acknowledgements, thus allowing reliable messaging, and for signaling such as registration or location information,
25 if available. Because the message expands in the user agent **12**, the channel bandwidth in the forward and reverse directions differs significantly, as much as a ratio of 100 (or more) to 1. This asymmetry also can exist in terms of processing power, memory storage and battery capacity
30 between the messaging device **11** and the network **14**.

For purposes of discussion, a short two-way messaging scenario is first described, followed by a more detailed description of various messaging system elements and their functions.

Referring now to Figure 3, there is illustrated the two-way wireless messaging system having four user agents for Thomas, Dan, Mary and Paul, referred respectively as UAT **50**, UAD **52**, UAM **54** and UAP **56**.

5 Thomas can originate through his pager **50a** a message to his lunch group members, Dan, Mary and Paul, and inquire about lunch choices. The message is delivered via the two-way wireless messaging network **14** along message delivery channels **57a** (air interface), **57b** (Data network
10 interface), **57c** (telephone network interface) as a page to a two-way messaging device in the form of a pager **58** belonging to Dan, an electronic mail to a computer **60** belonging to Mary, and a phone call to telephone **62** belonging to Paul respectively. The reply from each
15 recipient is collected by the two-way messaging network **14** along a respective message return communication channel **64a**, **b**, **c** and forwarded back to Thomas via the first communication channel **42** as a page. The type of message return communication channel **64a**, **b**, **c** and message delivery
20 channels **57a**, **b**, **c** vary depending on the device, such as a pager **58**, computer **60** or phone **62**.

In accordance with the present invention, the uplink messages are kept short because of the use of the user agents **50-56**. The user agents mirror the state and
25 context (e.g., any address and message tables in the user agent) of their messaging devices **11** (Figure 1), **50a**, **58**. In the above example, the uplink message contains a short group identifier and a message number. These are used by the user agents as indices to respective data tables in
30 message expansion. For message reply, the uplink message contains only a reply code. This is expanded back to the full reply inside the network. By using group addressing, Thomas sends only one message uplink and the network automatically "copies" the message to the multiple

recipients at the predetermined destinations.

Dan, Mary and Paul each receive the message in a different format, which could have been proposed by Thomas during message origination or specified as part of the filtering/forwarding criteria of the respective user agents of the recipients.

The criteria for filtering/forwarding can be very general. It could be based on the message originator, time of day, or any other commonly available forwarding options. Messages can also be formed in a variety of techniques. For example, Thomas can send the message as a pre-canned message with an embedded response. Thus, the message would include not only the text of the request, but would also include a list of responses to be selected and returned by the recipient.

Any user agent, e.g., those depicted as items **50-56**, typically maintains, among other things, an identical copy of the address and message tables as the messaging devices. The address and message information stored in the messaging device and respective user agent should always be consistent with each other. Typically, to change these address and message tables, a subscriber needs to change one copy first and the system will propagate the changes to the other.

There are various methods a subscriber to the messaging system can use to enter new messages or addresses. There are chiefly two main categories, i.e., through the messaging device itself, or through the messaging system.

For example, as illustrated in Figure 13, the messaging device **11**, e.g., a two-way pager, can include a simulated keyboard **69** displayed on the LCD screen **88**. A subscriber uses the pager buttons **84** to navigate around the simulated keyboard and select characters to compose a message. This method is tedious and applicable more to

short, fixed messages. This method is not practical for making flexible messages that contain dynamic components.

A subscriber can also elect to add an incoming message sent by others to its own set of messages. For example, the subscriber will receive an incoming message from another individual. The subscriber may like that particular message and through an appropriate selection of buttons on the messaging device **11**, add that message to his or her own message list.

10 In still another method, many existing messaging devices such as pagers, have an input/output (i/o) port. This port could be used to connect to a laptop or a Personal Digital Assistant. A subscriber uses the laptop or PDA to edit messages and download them to the messaging device **11** 15 via the input/output port. An appropriate protocol could be used.

The other major category is to use the messaging system for updating any new messages and addresses to the subscriber user agent. For example, new messages and addresses are directed to the user agent. This is one way to customize a subscriber's message and address set. The copy in the subscriber user agent is updated such as by using a dial-up program, an internet connection, a world-wide web page or even an operator to change the messages and 25 addresses directly via wireline.

In still another method, the subscriber signs up for a new third-party service. When the subscriber initially signs for that service, the subscriber is given a set of messages and addresses that are used to access the 30 service. These messages and addresses are then loaded directly into the subscriber's user agent by the service provider.

In the following, a more detailed description of a user agent **12** (Figure 1) and its function relative to the

two-way wireless messaging system **10** (Figure 1) is set forth.

In accordance with the present invention, each subscriber of the two-way wireless messaging system **10** is represented by a user agent **12** that resides inside the messaging network **14**. The user agent **12** expands coded originating messages received from a two-way messaging device and provides pointers to the last known location of the two-way messaging device **11**. It also maintains the status of the two-way messaging device **11**, i.e., if it is on-line, and a profile of the subscriber. The user agent **12** also can provide some value-added functions such as message screening and selective message forwarding. The user agent **12** may also be customized by its subscriber **40**. Thus, the user agent **12** acts as a personal server for the subscriber **40**.

The user agent **12** also provides other benefits. Because messages are expanded inside the messaging network **14**, the bandwidth on the uplink can be reduced, allowing bandwidth asymmetry on the wireless link. By performing intelligent processing in the network instead of at the end device **11**, the enhanced power of the network is utilized. The user agent **12** manages mobility by tracking the location of the subscriber. Finally, the user agent **12** serves as a proxy for the two-way messaging device **11** when it is out of range, allowing the system **10** to account for disconnected users.

As shown in Figure 11, the user agent **12** can have respective fixed and extensible parts **70**, **72**. The fixed part **70** implements basic messaging functions that are generic for all user agents. It can mimic the context of a messaging device, (e.g., the address table and the message table) and maintains information about ongoing message delivery. The extensible part **72** includes user agent

programs **72a**, **72b**, it can be programmed to perform specific tasks as desired by the subscriber **40** (Figure 1), e.g., maintaining a personal calendar, retrieving specific information from a world wide web page **27a**, a database **73**,
5 where data can be input **73a**, or other similar functions. The software **74**, is associated with the user agent program to provide run time support for the system.

These basic functions include registration/deregistration, message delivery and message
10 status query.

In registration the current location of the two-way messaging device is updated to the system as shown in Figure 4. Registration can be explicit or implicit. Explicit registration occurs when a messaging device is
15 powered-up or when it moves into a new cluster **78** (Figure 4). Implicit registration occurs when a message is received or delivered to a messaging device. During power-up the user agent **12** can also download messages that have been received in the messaging network **14** since the last power-
20 down of the two-way messaging device.

The user agent **12** allows message delivery:

- (1) when the device originates a new message;
- (2) when the device receives a
25 message;
- (3) when the device replies to a message; and
- (4) when the device receives a reply.

Processing for groups 3 and 4 closely resembles
30 that of groups 1 and 2.

When a messaging device **11** originates a new message, the user agent **12** translates the destination and reply address aliases sent by the device into the full address and expands the supplied message number and modifier
35 into full message text and creates a record for the message.

This record can be used as a basis for any subsequent message query. When a messaging device **11** receives a message, the user agent **12** returns the current status (on/off) and location of its device. Certain personal
5 messaging functions, e.g., forwarding or filtering can also be performed.

For message status query, the query request is answered by the user agent by consulting its message record and if necessary, a transaction server is consulted about
10 current delivery status, as will be explained later.

The extensible portion of the user agent specifies a framework in which additional functions can be added as user agent program modules **72a**, **72b** (Figure 11). This collection of programs contain codes to handle messages of
15 a specific pattern. The extensible part **72** follows an event-driven model and provides a kernel that pattern-matches incoming messages and dispatches them to an appropriate program module. Also, the extensible part **72** can be used for signaling by addressing a message to the
20 user agent itself. For example, a message status query can be implemented as a signaling function in the extensible part.

Referring now to Figure 4, there is illustrated a basic architecture of the two-way wireless messaging system
25 **10** of the present invention. As illustrated, the system **10** includes a three-tier hierarchy. The highest is a domain **80**; the cluster **78** is the middle; and the cell **82** is the lowest. The coverage area of a base station **76** defines a cell **82**. A collection of adjacent cells **82** form a cluster
30 **78** and a collection of clusters form a domain **80**. Three domains are illustrated. A domain **80** is an administrative unit and each subscriber is associated with a unique domain called the "home domain". The various servers of the present invention **10** are replicated in each domain **80** and
35 the user agent of a subscriber resides and is managed by its

home domain. For purposes of description only one single domain is described. This hierarchy is designed for several important principles in the present invention:

- 5 (1) limiting the control information transmission;
- (2) limiting the size of transmitted messages; and
- (3) distributing functions in a modular manner.

10 To limit the transmission of control information by a two-way messaging device **11**, the amount of periodic signaling is reduced. For example, location updates can be minimized by defining the registration area to be a cluster **78**. Thus, the two-way messaging device **11** only re-registers
15 with the system **10** when it crosses cluster boundaries. This can reduce the amount of signaling traffic, especially in a microcell infrastructure with high subscriber mobility. Thus, the messaging network only knows the location of a messaging device to the resolution of a cluster **78**, and a
20 limited search is necessitated to locate a device **11** before message delivery.

A small cluster **78** size provides better precision of device location and a smaller messaging delay at the expense of more frequent updates. A larger cluster size, on
25 the other hand, increases average messaging delay but requires less frequent updates. To obtain an optimal cluster size, both message arrival rate and mobility pattern should be considered.

Referring now to Figure 9 there is illustrated one
30 example of a messaging device that can be used with the present invention. It is illustrated as a dedicated, stand alone two-way pager **11**. In this example, the messaging device **11** generates, receives and displays messages to the subscriber user. The design of the messaging devices must
35 take into account important hardware limitations, such as

the need for minimum power consumption. As illustrated, the messaging device **11** should be business card size to provide the portability required of "any time, anywhere" service. The power consumption should be minimum, requiring
5 infrequent battery change.

Figure 9 shows a representative schematic of a pager **11** having four function buttons **84** at the bottom serving as soft keys, i.e. keys whose functions vary with the contexts, and two buttons **86** on the side, used mainly
10 for scrolling purposes. The two-way pager includes a 5-line LCD screen **88** in which the top four lines are used for text while the bottom line shows current bindings for soft keys. The pager contains computing hardware, e.g., a processor and memory for user interface code and pager protocol. A low
15 power general purpose microprocessor can be used for the pager. Memory should be adequate enough to contain these various messages and associated data.

As shown in Figures 2 and 4, a base station **76** terminates the air interface and a link layer protocol with
20 the pager **11**. It manages the air interface resources. Base stations **76** can be deployed as cellular base stations, packet radios or other types of transceivers as required for any wireless messaging and paging systems.

Referring now to the general overview of Figures
25 4 and 5, there now follows a description of the various servers used with the two-way wireless messaging system of the present invention.

A batch server **100** provides intelligence to base stations **76**. A single batch server **100** connects to one or
30 more base stations **76**, and receives and acknowledges messages from the messaging device **11**. It also receives messages destined to a messaging device, forwards them to the proper base station **76** for delivery, and receives acknowledgements that the messages have been correctly
35 received. The batch server **100** may batch downlink pages

into groups for scheduled delivery to allow sleep mode operation of pagers. In essence, a batch server **100** acts as a point of transfer between the wired (network) and the wireless (subscriber and base station) portions of the system **10**. It is responsible for relaying uplink messages from subscriber devices (via base station **76**) to the network and downlink messages from the network to subscriber devices (via base stations **76**).

A protocol structure that can be used for interactions between the pager **11**, base station **76**, and batch server **100** is shown in Figure 6. The Message Layer Protocol (MLP) **102** is responsible for ensuring reliable message delivery between the batch server **100** and a messaging device. Each MLP **102** data unit contains one user-level message. At most one message per messaging device may be outstanding at a time. The sending entity of a message maintains a retransmission timer for the outstanding message, and retransmits the message until it receives an acknowledgement. Acknowledgments are generated by the receiving MLP entity when a message is correctly received.

The Airlink Specific Convergence Sublayer (ASCS) **104** operates peer-to-peer between the batch server **100** and the messaging device **11**. The ASCS **104** is responsible for segmenting MLP **102** data units into the appropriate size for transmission over the air interface, and re-assembling air interface frames into MLP data units at the receiver. ASCS **104** passes only correctly received data units to an MLP; any corrupted data units are silently discarded. The ASCS protocol specification is dependent on the air interface protocol, and as a result, many different ASCS's will exist.

Two link layer protocols **106**, **108** are illustrated. LINK1 **106** operates between the batch server **100** and the base station **76**. LINK2 **108** operates over the air interface and

is specified by the particular air interface used in the system **10**.

The high-level structure of a batch server is shown in Figure 10. It maintains a number of data structures for its operation such as a registered messaging device table, which maintains a record for each messaging device currently being served by the batch server. The record includes both information about the messaging device (i.e., last base station visited) as well as traffic statistics (e.g., number of uplink/downlink messages from/to a messaging device). The wireline (network) side is indicated generally at **109**, and the wireless (subscriber and base station) side is indicated generally at **109a**.

A record is created in the registered messaging device table under two circumstances: an explicit registration or an implicit registration. An explicit registration in turn is performed under two conditions: power up initialization or cluster boundary crossing. The former is a new registration while the latter is a re-registration. A re-registration requires the additional step of deleting the state information kept in the old batch servers. An implicit registration, on the other hand, occurs when a base station receives a data message from a messaging device not currently registered. This is often the result of an active messaging device moving between cells in a cluster, and then sending or receiving a message. The record is deleted when a power-down deregistration is received.

Another data structure is Unacknowledged Message Queues (UMQs) **110**, which contain messages that are to be delivered on the downlink. They are logically organized on a per messaging device basis, though the actual implementation may be based on separate queues or a common message pool. The batch server **100** uses a stop-and-go strategy in delivering the messages, i.e., it will not

deliver a new message to a messaging device **11** until the previous message to the messaging device has been acknowledged. Thus, at any particular time, there is at most one outstanding unacknowledged message.

5 When an acknowledgement is received from a messaging device, the acknowledged message (i.e., the message at the head of the queue) is moved to the Acknowledged Message Queue (AMQs) **112**. The acknowledgement is designed to be short; it contains only a so called
10 *receive buffer index* (rbi), which is a locally unique (relative to the destination pager) identifier. The rbi is used later to correlate the reply to the original message.

 Another data structure is the Acknowledged Message Queues **112**, which contain messages whose delivery has been
15 acknowledged by the destination messaging devices and are currently awaiting their replies. A reply contains an rbi together with a reply code. The rbi is used to retrieve the original request; it serves essentially as a local message id, thus eliminating the need to send the system message id
20 uplink. The reply code encodes the desired response, and is to be expanded by the replier's user agent.

 Generally, the length of these queues is small because replies tend to follow the acknowledgements closely, in the order of about 30 minutes. A procedure could exist
25 and be implemented by one skilled in the art to migrate the state back to the user agent if a reply does not come within a certain time limit. Thus, the AMQs behave like a cache for storing message information needed in processing a reply.

30 Depending on the air interface, the batch server **100** may also be responsible for other low-level tasks. These include the delivery of packets using a multicast operation. There are two possible forms of multicast delivery: 1) true and 2) ad-hoc. In a true multicast,
35 messaging devices belonging to a multicast group share a

single multicast address and messages are delivered using the multicast address. In an ad-hoc multicast, an address header message containing a list of destination device ID's is first sent to alert the receiving messaging devices. 5 This is then followed by the actual body of the message.

Referring again to Figures 4 and 5, there is illustrated a messaging server **114**, which enhances the modularity of the system by coordinating activities of individual servers. The messaging server **114** receives 10 originating messages, coordinates with other servers to determine their location and format in which the message should be delivered, invokes value-added services and finally routes the messages to a server which can deliver them. The messaging server **114** functionality is required in 15 all messaging systems and its operation varies depending on the intelligence and value-added services available from the messaging system.

The distribution server **116** is responsible for delivering messages to their final destinations in the 20 proper format. For messages to be delivered to a wireless device such as a pager **11**, the distribution server **116** executes a direct paging algorithm based on location information provided by a user agent **12**. For messages that are to be translated into a different format, the 25 distribution server **116** routes the message to a translator. The distribution server functions are basically required in the system **10**. If the system **10** does not make use of location information, but floods the air interfaces with messages to be delivered (true broadcast), the distribution 30 server function is minimal.

The distribution server **116** works in conjunction with a user agent **12** that supplies location information, and manages user mobility in the present invention. The distribution server **116** forwards any message to be delivered 35 to the batch server **100** that was last known to have been

5 serving the messaging device, such as a pager **11** or other wireless device. If the batch server **100** successfully delivers the message, the distribution server **116** receives an acknowledgment and the algorithm terminates. If the batch server times-out, the distribution server **116** will forward the message to all batch servers **100** which neighbor the original target batch server. This increases the coverage area in which the message delivery is attempted. The message is not sent to the original batch server on the
10 second delivery attempt. If the message is still not delivered, the coverage area is increased again, sending to neighboring batch servers **100** of the latest subset until the message is delivered.

This algorithm has several benefits. First, no
15 single batch server **100** is included twice in the search. Second, while the distribution server **116** performs directed paging on a cluster area, the batch servers **100** may execute a directed paging algorithm among the base stations **76** within the cluster **78**. This distributed control allows base
20 stations **76** to be added to clusters without requiring the distribution server **116** to change its directed paging algorithm search lists. The directed paging algorithms of the system **10** are designed to reduce both the air and network traffic in the paging system **10** when compared to the
25 flooding techniques employed by many paging systems in operation today. Many variations of this basic algorithm are possible to those skilled in the art.

The transaction server **118** (Figures 4, 5 and 12) tracks the transactions between messaging subscribers. This
30 involves correlating messages, replies, and acknowledgments. The transaction server **118** supports several transaction types, reports the status of transactions when requested, and closes transactions when complete. It supports one-to-one and one-to-many transactions. For example, a subscriber

40 (Figure 2) may send a message to three endpoints and request that it be only notified of the first response. In this case, the transaction server **118** will open a transaction when the message is sent, and close it when the
5 first reply is received. Any further replies will be discarded. If a system does not support transactions, the transaction server **118** is not a required element.

In the system of the present invention, the transaction server **118** supports the following basic
10 transaction types which may be combined to form a more enhanced set of transaction services:

1. All-reply
2. N-reply
3. Timed-reply

15 The all-reply transaction remains open until a reply has been received by every message recipient. The N-reply transaction remains open until a reply has been received by N message recipients. The timed-reply transaction remains open until a user specified time has
20 expired. Once a transaction is closed, further replies are not accepted and not forwarded to the transaction originator. For example, in a transaction in which only the first three replies are accepted within five minutes, if either five minutes elapses, or three replies are received,
25 the transaction is closed. This is an example of combining the N-reply and Timed-reply transaction types. All transactions are subject to a system timer which is used to close transactions that have not been completed within a reasonable amount of time.

30 A schematic diagram of one example of the structure of the transaction server is shown in Figure 12. As noted before, the transaction server **118** supports three basic transaction types: all-reply, N-reply, and timed-reply.

As shown in Figure 12, the transaction server has two levels of hierarchy: a conversation manager **120** and a transaction manager **122**. The conversation manager **120** maintains a simple two-state machine as either open **124** or closed **126** (Figure 12a). If a transaction is open, replies to the original message are expected and accepted. If the transaction is closed, no replies are accepted. The transaction manager **122** is responsible for tracking the state of each recipient involved in the transaction, and thus determine if a transaction should be closed. The transaction manager makes this decision based on the number of replies that are being accepted for a transaction, and the number of recipients **128** that have reached the done state as shown in Figure 12b. When the proper number of recipients are in the done state, the transaction manager informs the conversation manager **120** to close the transaction.

Consider a simple transaction with three recipients. The transaction server receives an OPENTX (open transaction) request from the messaging server **114**, and assigns a unique transaction ID to the transaction. It then initiates a conversation manager **120** to handle this request. The conversation manager **120** is indexed by the transaction ID. The conversation manager **120** transitions into its open state and initiates a transaction manager **122**. The transaction manager **122** creates three records, one for each recipient, to reflect the recipient states. The records are indexed by the recipient address. The initial states are the states labeled by "sent", signifying that the message is being sent to all three recipients.

The transaction server **118** also stores information concerning the transaction type. For example, the transaction server **118** determines from the transaction type how many replies should be accepted for the transaction.

The transaction server also sets a deadline timer by which time the transaction must be closed. If the transaction is not a timed transaction, a default system timer, typically on the order of a day, is used. At this time, the transaction server **118** replies to the messaging server with the transaction id.

As acknowledgements and replies are received from the message recipients, the conversation manager **120** maintains the transaction in its open state. The transaction manager **122** modifies the state of each corresponding recipient. As acknowledgements are received for the replies, the transaction manager **122** will transition the appropriate recipients to the done state. Depending on the number of replies allowed for the transaction, the transaction server **116** determines if more replies should be accepted. When the reply limit is reached, i.e., the required number of recipients have reached the done state, the transaction manager **122** instructs the conversation manager **120** to close the transaction. The transaction manager **122** may also instruct the conversation manager **120** to close the transaction if the transaction time has expired. After this time, any replies received by the transaction server **118** are rejected. The transaction server sets a record timer. Until the timer expires, the state of the conversation manager is frozen in the closed state, and recipient states are frozen. During this time, the transaction server **118** may be queried as to the state of the transaction. When the record timer expires, the transaction server **118** deletes the conversation manager **120** and transaction manager **122** for the transaction. Any queries to the transaction server **118** after this time will result in an invalid transaction ID message.

A simple routine flow chart is shown in Figure 12b and illustrates message transmission and acknowledgements.

A message is sent **130** and acknowledgement received **132**. A reply is received from the recipient **134** and then the sequence is done **136** when the acknowledgement is received for a reply.

5 The two-way wireless messaging system **10** with the present invention allows various types of messages. Unlike many existing paging and messaging systems which support primarily static messages, or require dictations, the present invention supports flexible message types. The
10 design of these message types is strongly influenced by the capability of the messaging device. For example, the lack of a keyboard implies that free form messages are impractical. Also, as many of the advanced features are processed locally by the messaging device, the device must
15 be sophisticated enough to handle the processing logic.

 The most basic type of supported message is *fixed pre-canned* messages. This is identical to what is currently available under one-way alphanumeric paging. A simple extension of fixed pre-canned messages is the so-called
20 *richtext* messages. It adds text attributes, e.g., bold face, inverse video, etc., to the plaintext of a fixed pre-canned messages. Fixed pre-canned messages suffer from a major limitation, namely, they cannot be dynamically customized. To overcome this, the present invention
25 introduces three types of *dynamic components*: 1) *optional components*, 2) *selections* and 3) *pre-defined variables*. Optional components delineate message parts that can be dynamically included or excluded. A selection provides a list of items from which to choose. For example, a
30 selection labeled "location" may expand into the list of choices: a) home, b) office, or c) lab. The set of available selections are defined by the individual subscribers. Pre-defined variables represent specific commonly used entries that can be customized by a user.

Typical examples of pre-defined variables are time, phone number, etc. Dynamic components can be nested as needed.

To facilitate a reply, a message can include *reply components*. A reply component embeds the desired replies, typically making use of dynamic components. This is useful in applications where the possible replies are agreed upon a priori.

The most general message type includes *conditional components*. A conditional component can be conditionally included or excluded based on the values of previous dynamic components. It can be used to chain multiple messages together, thus eliminating the roundtrip delay. They are intended only for the most advanced messaging applications.

Described below is an example of a protocol flow for a multicast message delivery with replies. Focus is directed on the salient features of the system.

In the example, presented in Figures 7 and 8, a subscriber S **200** sends a message to three recipients, R1 **202**, R2 **204**, and R3 (not shown). In this example, R1 last registered at BS-R1, **222** and is still currently in BS-R1. R2 last registered in BS-R21, **230**, and has since moved to BS-R22, **232**. R3 is currently inactive, i.e., power off. R1 **202** receives the message on its messaging device in the first delivery attempt. R2 **204** receives messages on its messaging device on the second delivery attempt. R3 requests that the message be forwarded to a message storage server for subsequent retrieval. In the following, we illustrate the function of each entity, the location management procedures of the system, and a direct paging algorithm. The interaction with individual base stations is not included in this example. It is assumed that there is a one-to-one mapping between base stations and batch servers for simplicity.

Figure 7 shows a highly schematic depiction of message delivery procedures. The originator of the message,

S **200**, transmits its message into the network through its serving batch server, BS-S **208**, via a PG2BS-NEW message. This PG2BS-NEW contains the address of S, an array of recipient addresses, an array of reply-to-addresses, and the
5 coded message. In this example, the recipients listed are R1 **202**, R2 **204**, and R3 **206**, and the reply-to-address is the address of the message originator, S **200**. The message is coded by indicating a message number and any dynamic component values. BS-S **208** receives the message, and
10 generates an acknowledgment back to S **200**, BS2PG-ACK (shown by the reversed arrow), signifying that the network has accepted the message for delivery.

The batch server **208** forwards the message to the messaging server, MS **210**, in a BS2MS-NEW message. In
15 addition to the information contained in the PG2BS-NEW message, this message contains a message identifier (mid), which uniquely identifies this message throughout the system.

The messaging server **210** contacts the user agent
20 of the message originator, UA-S **212**, with a MS2UA-NEW message. UA-S **212** performs the message expansion function. It expands the message body depending on the message number and dynamic component values received and expands any address aliases into the full system addresses. UA-S **212**
25 responds to the messaging server **210** with the message body and the message type, i.e., an indication if this message requires a reply, if it is part of a transaction, or if it is a simple one-way page. In this example the message is classified as a transaction in which replies from all
30 recipients are required. This information is sent in the UA2MS-NEW message.

As this point, the messaging server **210** contacts the user agents of the message recipients to determine the location of their corresponding messaging devices, the

format in which they wish to receive the message, and their status. It does this by sending HDR messages to the user agents. The user agents respond with the status and last known location of the messaging devices. In this example,
5 UA-R1 **214** responds that the messaging device is active, and that its last known location is BS-R1. UA-R2 **216** responds that the messaging device is active, and that its last known location is BS-R21. UA-R3 **218** responds that its pager is off, and that the message should be forwarded to a message
10 storage server.

The messaging server **210** receives these replies, and then requests that the transaction server **220** open a transaction for this message exchange via the OPENTX message. The transaction server **220** opens the transaction,
15 and returns a transaction ID in the TXRSP message. The transaction ID uniquely identifies this transaction throughout the network, and furthermore, identifies the transaction server **220** managing this transaction. The transaction ID is forwarded to the user agent **212** of the
20 message originator (TXUPDATE) so that it may access the transaction record if it later receives any queries as to the status of the transaction.

The messaging server **210** then forwards the full message body, along with the list of recipients, their
25 desired message formats, and last known locations to the distribution server **221** (MS2DS). The distribution server **221**, based on the location information provided, and the desired format of the message, determines how to deliver the message to the recipients. It forwards the message to R1
30 **202** via BS-R1 **222**, and the message to R2 **204** via BS-R21, **230** as instructed by the location information received. It forwards the message for R3 to the message storage server, MSS **224**.

BS-R1 **222** delivers the message to R1 **202** (MSG), and eventually receives an acknowledgement (ACK). The batch BS-R1 **222** server forwards this acknowledgement to the distribution server **221**, which forwards the acknowledgement to the transaction server **220**. The transaction server **220** updates its transaction record.

Likewise, an acknowledgement is received from the message storage server **224** on behalf of R3. This acknowledgement is also forwarded to the distribution server **221** and transaction server **220**. In addition, the distribution server **221** updates UA-R3 **218**, notifying it of the retrieval ID by which the user may retrieve the message from storage at a later time (UPDATE). The retrieval ID is downloaded by UA-R3 **218** to R3 when R3 powers on.

The batch server BS-R21 **230** does not receive an acknowledgement for R2 **204**, and therefore times-out. It generates a negative acknowledgement to the distribution server **221** (NAK). The distribution server **221** executes the directed paging algorithm in which it expands the message delivery area to all batch servers neighboring the original target. In this example, these are BS-R22 **232** and S-R23 **234**. BS-R22 **232** successfully delivers the message and receives the acknowledgement. The acknowledgement is forwarded to the distribution server **221** and transaction server **220**. The distribution server **221** updates UA-R2 **216** so that it may reflect the current location information of R2 **204**. It is through this interaction between the distribution server and user agents that the approximate location of the wireless messaging devices is learned, and the direct paging algorithm is executed.

At this time, the message has been delivered to all recipients, and the transaction is open.

Figure 8 shows the flow for the reply to a message generated above. At a high level, the reply flow is

symmetrical to the message origination flow. In this example, the recipient, R **240** generates the reply (REPLY), which is received by batch server BS-R **242**. The reply is again a coded message, with an identifier to associate it with the original message. The batch server **242** caches information about messages it delivers for a finite time. If the reply is received by the batch server **242** within that time period, it can determine the full message ID, transaction ID, and other ID's, from a local identifier. If the information has been removed from the cache, or if the wireless messaging device has moved to a different batch server area before sending its reply, the batch server **242** must fetch the information from the user agent of the wireless messaging device sending the reply.

As in the message origination case, the batch server forwards the message to the messaging server **244** which contacts the user agent of the replying device **246**. The user agent **246** expands the reply, and returns the message to the messaging server. The messaging server **244** then contacts the transaction server **248** to notify it that a reply has been generated. If the transaction is still open, and more replies are still being accepted, the transaction server **248** instructs the messaging server **244** to continue delivering the reply, as in this example. The remaining portion of the reply delivery flow is similar to the message delivery flow: the user agent **246** of the device receiving the reply is contacted to determine where to deliver the reply, and the reply is sent to the distribution server **250** for delivery.

When the acknowledgement for the reply is received by the distribution server **250**, it is forwarded to the transaction server **248**.

The two-way wireless messaging system with the present invention can be used with more than the above-

illustrated examples. For example, it is conducive for dispatching where a dispatcher may transmit a message to a group of recipients in order to assign a task. For example, a maintenance supervisor can send a message to all shift workers if an outage occurs. The message recipients respond upon receiving the message indicating their availability. The supervisor may then assign a job to one or more members of the group.

Additionally, the two-way messaging system can be used as a calendar reminder service where reminders and alarms are generated by a network-based calendar server with the help of subscriber user agents. The messaging devices are portable, and messages can be delivered to a pager, E-mail and other messaging device. The calendar can act somewhat as an "alarm" and notify a user at any time of scheduled appointments, anniversaries and important dates. Appointments can be entered into the calendar as part of the user agent.

Additionally, the system can be used for emergency signaling and sending a S.O.S. message. In an emergency signaling system, a person in distress can send an S.O.S. message. This message is routed to an emergency command center. The network can indicate the location of the sender of the message using a location-based service system. The emergency command center may send messages to the person in distress to perform an initial evaluation of their condition through the use of query messages. For example, messages such as "Are you injured?", "Are you bleeding?", or "Can you move?" may be sent with reply choices. Answers collected from the initial evaluation can be extremely useful in dispatching the proper emergency response units.

Upon finishing dispatching (via a separate two-way message multicast as described earlier), an acknowledgment such as "Help is coming" or "Please meet the ER people at

the next block" can be relayed back to the person requesting emergency help.

Depending on the subscriber's profile, a follow-up notification via two-way messaging could be sent to the
5 family members of the subscriber.

This service takes advantage of the reliability, bidirectionality, multicast, and transaction support of the two-way messaging system.

10 Additionally, messages may be directed to subscribers in a certain location. For example, if the trains in New York are not running, all people in New York may be sent a message. This service is similar to current simple paging services except that it is location dependent.

15 While the best mode for carrying out the invention has been described in detail, those familiar with the art which the invention relates will recognize various alternative designs and embodiments practicing the invention as defined by the following claims.

Claims:

1. A two-way messaging systems comprising:
a messaging network; and
a two-way wireless messaging device, including
5 means in the two-way wireless messaging device for generating
a message having a dynamic message component the message
including at least one multiple message destination address
that includes a plurality of destination addresses;
the messaging network including means for limiting
10 replies from one or more one destination address of the
multiple message destination address.
2. A two-way messaging system according to claim
1, where said messaging network includes a plurality of
stored messages and message destination addresses, and
15 wherein said dynamic message component includes one of an
optional component, a user-defined selection, a pre-defined
variable and a conditional component.
3. A two-way messaging system according to claim
1, wherein the message includes an embedded reply formed
20 using the dynamic message component.
4. A two-way messaging system according to claim
1, wherein a message transmitted from the two-way wireless
messaging device includes a coded message corresponding to
an expanded message stored within the messaging network.
- 25 5. A two-way messaging system, comprising:
a messaging network;
a two-way wireless messaging device, including
means in the two-way wireless messaging device for generating
a message having a dynamic message component and at least one
30 multiple message destination address, the multiple message
destination address including a plurality of destination
addresses;

a plurality of intelligent servers located within said messaging network for receiving, routing, tracking and forwarding messages through the messaging network to intended destination addresses; and

5 means located within the messaging network for limiting replies from one or more destination address of the multiple message destination address.

6. A two-way messaging system according to claim 5 including a plurality of base stations acting as relays 10 between the messaging network and a two-way wireless messaging device, and including at least one batch server for receiving and acknowledging messages from a two-way wireless messaging device and forwarding the message to a desired destination within the messaging network.

15 7. A two-way messaging system according to claim 5 including a messaging server for coordinating the activity of the plurality of intelligent servers.

8. A two-way messaging system according to claim 5 including a transaction server for tracking message 20 transactions among various users of the two-way messaging system.

9. A two-way messaging system according to claim 5 including a distribution server for delivering messages to their desired destinations in a variety of final formats.

25 10. A two-way messaging system according to claim 5 wherein said messaging network includes a plurality of stored messages and message destination addresses, and wherein said dynamic message components include optional components, user-defined selections, predefined variables and 30 conditional components.

11. A two-way messaging system according to claim 5 including messages having embedded replies formed using dynamic message components.

12. A two-way messaging system according to claim 5, wherein a message transmitted from the two-way wireless messaging device includes a coded message corresponding to an expanded message stored within the messaging network.

13. A two-way messaging system, comprising:
a messaging network storing full messages and
10 address destinations; and

a two-way wireless messaging device originating a message along a first communication channel to the messaging network, and receiving a message from the messaging network along a second communication channel, a message including a
15 coded identifier message formed locally within the two-way wireless messaging device and within the messaging network, wherein said coded identifier message is expanded within the messaging network into a full message and at least one multiple message destination address having a plurality of
20 destination addresses;

the messaging network including means for limiting replies from one or more destination address of the multiple message destination address.

14. A two-way messaging system according to claim 25 13, wherein said means for expanding a message comprises a user agent located within the messaging network, and wherein said user agent stores a plurality of messages corresponding to a respective coded identifier message.

15. A two-way messaging system according to claim 30 13 including a plurality of intelligent servers located within said messaging network for receiving, routing, tracking and forwarding messages through the messaging network to intended message destination addresses.

16. A two-way messaging system according to claim 15 including a plurality of base stations acting as relays between the messaging network and a two-way wireless messaging device, and including at least one batch server for receiving and acknowledging messages from a two-way wireless messaging device and forwarding the message to a desired message destination address within the messaging network.

17. A two-way messaging system according to claim 15 including a messaging server for coordinating the activity of the plurality of servers.

18. A two-way messaging system according to claim 15 including a transaction server for tracking transactions between various users of the two-way messaging system.

19. A two-way messaging system according to claim 15 including a distribution server for routing messages to a desired destination in a final format.

20. A two-way messaging system, comprising:
a distribution server distributing a message to at least one destination address, the message having a dynamic message component and at least one multiple message destination address; and

a transaction server limiting replies to the message from at least one selected address of the multiple message destination address.

21. The two-way messaging system according to claim 20, wherein the dynamic message component includes one of an optional component, a user-defined selection, a pre-defined variable and a conditional component.

22. The two-way messaging system according to claim 20, wherein the message includes an embedded reply formed using the dynamic message component.

23. The two-way messaging system according to claim 20, wherein the message is a coded message corresponding to an expanded message,

5 the two-way messaging system further comprising a user agent having a plurality of stored expanded messages and message destination addresses.

24. A method for message delivery in a two-way messaging system, the method comprising the steps of:

10 distributing a message to at least one destination address, the message having a dynamic message component and at least one multiple message destination address; and

limiting replies to the message from at least one selected address of the multiple message destination address.

25. The method according to claim 24, wherein the dynamic message component includes one of an optional component, a user-defined selection, a predefined variable and a conditional component.


26. The method according to claim 24, wherein the message includes an embedded reply formed using the dynamic message component.

27. The method according to claim 24, wherein the message is a coded message corresponding to an expanded message,

25 the method further comprising the steps of: storing a plurality of expanded messages and message destination addresses; and

expanding the message to be the corresponding expanded message.

FIG. 1



2/8

FIG. 2





FIG. 3



Kirby, Eades, Gale, Baker

3/8
FIG. 4






FIG. 5



Kirby, Eades, Gale, Baker



5/8

FIG. 6





FIG. 8



6/8

FIG. 9





FIG. 10



7/8
FIG. 11




FIG. 12




FIG. 12A





FIG. 12B



Kirby, Eades, Gale, Baker

8/8

FIG. 13

