

(12) **United States Patent**
Giuliano

(10) **Patent No.:** **US 12,176,815 B2**
(45) **Date of Patent:** ***Dec. 24, 2024**

(54) **SWITCHED-CAPACITOR CIRCUIT CONTROL IN POWER CONVERTERS**

(71) Applicant: **pSemi Corporation**, San Diego, CA (US)

(72) Inventor: **David Giuliano**, Bedford, NH (US)

(73) Assignee: **pSemi Corporation**, San Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/743,046**

(22) Filed: **Jun. 13, 2024**

(65) **Prior Publication Data**

US 2024/0339932 A1 Oct. 10, 2024

Related U.S. Application Data

(63) Continuation of application No. 18/606,319, filed on Mar. 15, 2024, which is a continuation of application (Continued)

(51) **Int. Cl.**
H02M 3/07 (2006.01)
H02M 1/00 (2007.01)
H02M 3/158 (2006.01)

(52) **U.S. Cl.**
CPC **H02M 3/1584** (2013.01); **H02M 1/0043** (2021.05); **H02M 3/07** (2013.01); (Continued)

(58) **Field of Classification Search**

CPC H02M 1/0043; H02M 1/007; H02M 3/07-3/078; H02M 3/1584; H02M 3/1586

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,370,215 A 2/1968 Light, Jr.
3,745,437 A 7/1973 Brown

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1132959 10/1996
CN 1483204 3/2004

(Continued)

OTHER PUBLICATIONS

Jiang, Jun et al., "Development and Production of ZCS Soft Switching Converter-based Gate Driver IC," 2009 IEEE 8th International Conference on ASIC, Changsha, China, 2009, pp. 1058-1061.

(Continued)


Primary Examiner — Fred E Finch, III

(74) *Attorney, Agent, or Firm* — Haynes and Boone, LLP

(57) **ABSTRACT**

An apparatus for power conversion comprises a voltage transformation element, a regulating element, and a controller; wherein, a period of the voltage transformation element is equal to a product of a coefficient and a period of the regulating circuit, and wherein the coefficient is selected from a group consisting of a positive integer and a reciprocal of said integer.

30 Claims, 14 Drawing Sheets



Related U.S. Application Data

No. 17/491,983, filed on Oct. 1, 2021, now Pat. No. 11,936,300, which is a continuation of application No. 16/872,207, filed on May 11, 2020, now Pat. No. 11,165,350, which is a continuation of application No. 14/857,141, filed on Sep. 17, 2015, now Pat. No. 10,686,380, which is a continuation of application No. 14/309,003, filed on Jun. 19, 2014, now Pat. No. 9,143,037, which is a continuation of application No. PCT/US2012/070555, filed on Dec. 19, 2012.

(60) Provisional application No. 61/577,271, filed on Dec. 19, 2011.

(52) **U.S. Cl.**

CPC H02M 1/0058 (2021.05); H02M 1/007 (2021.05); H02M 3/1586 (2021.05)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,818,306	A	6/1974	Marini	6,411,531	B1	6/2002	Nork et al.
3,818,360	A	6/1974	Boutmy	6,429,632	B1	8/2002	Forbes
4,214,174	A	7/1980	Dickson	6,476,666	B1	11/2002	Palusa
4,408,268	A	10/1983	Peters	6,486,728	B2	11/2002	Kleveland
4,415,959	A	11/1983	Vinciarelli	6,501,325	B1	12/2002	Meng
4,513,364	A	4/1985	Nilssen	6,504,422	B1	1/2003	Rader
4,812,961	A	3/1989	Essaff	6,507,503	B2	1/2003	Norrga
4,903,181	A	2/1990	Seidel	6,512,411	B2	1/2003	Meng et al.
5,006,782	A	4/1991	Pelly	6,515,612	B1	2/2003	Abel
5,057,986	A	10/1991	Henze	6,563,235	B1	5/2003	McIntyre
5,119,283	A	6/1992	Steigerwald	6,650,552	B2	11/2003	Takagi
5,132,606	A	7/1992	Herbert	6,657,875	B1	12/2003	Zeng et al.
5,159,539	A	10/1992	Koyama	6,657,876	B2	12/2003	Satoh
5,198,970	A	3/1993	Kawabata	6,700,803	B2	3/2004	Krein
5,268,832	A	12/1993	Kandatsu	6,738,277	B2	5/2004	Odell
5,301,097	A	4/1994	McDaniel	6,738,432	B2	5/2004	Pehlke
5,331,303	A	7/1994	Shiota	6,759,766	B2	7/2004	Hiratsuka
5,345,376	A	9/1994	Nourbakhsh	6,791,298	B2	9/2004	Shenai
5,402,329	A	3/1995	Wittenbreder, Jr.	6,798,177	B1	9/2004	Liu
5,504,418	A	4/1996	Ashley	6,927,441	B2	8/2005	Pappalardo
5,548,206	A	8/1996	Soo	6,934,167	B2	8/2005	Jang
5,557,193	A	9/1996	Kajimoto	6,980,181	B2	12/2005	Sudo
5,661,348	A	8/1997	Brown	6,995,995	B2	2/2006	Zeng
5,717,581	A	2/1998	Canclini	7,071,660	B2	7/2006	Xu
5,737,201	A	4/1998	Meynard	7,072,195	B2	7/2006	Xu
5,761,058	A	6/1998	Kanda	7,091,778	B2	8/2006	Gan
5,793,626	A	8/1998	Jiang	7,103,114	B1	9/2006	Lapierre
5,801,987	A	9/1998	Dinh	7,135,847	B2	11/2006	Taurand
5,812,017	A	9/1998	Golla	7,145,382	B2	12/2006	Ker
5,831,846	A	11/1998	Jiang	7,157,956	B2	1/2007	Wei
5,892,395	A	4/1999	Stengel	7,161,816	B2	1/2007	Shteynberg
5,907,484	A	5/1999	Kowshik	7,187,159	B2	3/2007	Katoh
5,956,243	A	9/1999	Mao	7,190,210	B2	3/2007	Azrai
5,959,565	A	9/1999	Taniuchi	7,224,062	B2	5/2007	Hsu
5,959,585	A	9/1999	Militz	7,236,542	B2	6/2007	Matero
5,978,283	A	11/1999	Hsu	7,239,194	B2	7/2007	Azrai
5,982,645	A	11/1999	Levrana	7,250,810	B1	7/2007	Tsen
6,107,864	A	8/2000	Fukushima	7,259,974	B2	8/2007	Donaldson
6,133,788	A	10/2000	Dent	7,269,036	B2	9/2007	Deng
6,140,807	A	10/2000	Vannatta	7,307,338	B1	12/2007	Mandell
6,154,380	A	11/2000	Assow	7,330,070	B2	2/2008	Väisänen
6,157,253	A	12/2000	Sigmon	7,362,251	B2	4/2008	Jensen
6,178,102	B1	1/2001	Stanley	7,375,992	B2	5/2008	Mok
6,198,645	B1	3/2001	Kotowski	7,382,113	B2	6/2008	Wai
6,255,906	B1	7/2001	Eidson	7,382,634	B2	6/2008	Buchmann
6,275,018	B1	8/2001	Telefus	7,408,330	B1	8/2008	Zhao
6,316,956	B1	11/2001	Oglesbee	7,443,705	B2	10/2008	Ito
6,327,462	B1	12/2001	Loke	7,511,978	B2	3/2009	Chen
6,339,538	B1	1/2002	Handleman	7,521,914	B2	4/2009	Dickerson
6,362,608	B1	3/2002	Ashburn et al.	7,521,914	B2	4/2009	Dickerson
6,377,117	B2	4/2002	Oskowsky	7,535,133	B2	5/2009	Perreault
6,396,341	B1	5/2002	Pehlke	7,589,605	B2	9/2009	Perreault
6,400,579	B2	6/2002	Cuk	7,595,682	B2	9/2009	Lin
				7,612,603	B1	11/2009	Petricek et al.
				7,616,467	B2	11/2009	Mallwitz
				7,633,778	B2	12/2009	Mok
				7,696,735	B2	4/2010	Oraw
				7,705,681	B2	4/2010	Ilkov
				7,724,551	B2	5/2010	Yanagida
				7,728,651	B2	6/2010	Nakai
				7,746,041	B2	6/2010	Xu et al.
				7,768,800	B2	8/2010	Mazumder
				7,777,459	B2	8/2010	Williams
				7,782,027	B2	8/2010	Williams
				7,786,712	B2	8/2010	Williams
				7,807,499	B2	10/2010	Nishizawa
				7,812,579	B2	10/2010	Williams
				7,889,519	B2	2/2011	Perreault
				7,907,429	B2	3/2011	Ramadass
				7,907,430	B2	3/2011	Kularatna
				7,928,705	B2	4/2011	Hooijschuur
				7,940,038	B2	5/2011	Da Silva
				7,952,418	B2	5/2011	McDonald
				7,956,572	B2	6/2011	Zane
				7,977,921	B2	7/2011	Bahai
				7,999,601	B2	8/2011	Schlueter
				8,000,117	B2	8/2011	Petricek
				8,018,216	B2	9/2011	Takehi
				8,026,763	B2	9/2011	Dawson
				8,031,003	B2	10/2011	Dishop

(56)	References Cited					
	U.S. PATENT DOCUMENTS					
	8,040,174 B2	10/2011	Likhterov	10,424,564 B2	9/2019	Giuliano
	8,048,766 B2	11/2011	Joly	10,476,395 B2	11/2019	Dai
	8,076,915 B2	12/2011	Nakazawa	10,483,352 B1	11/2019	Mokhti
	8,085,524 B2	12/2011	Roozeboom	10,541,611 B2	1/2020	Giuliano
	8,089,788 B2	1/2012	Jain	10,549,373 B2	2/2020	Madsen
	8,106,597 B2	1/2012	Mednik	10,601,324 B1	3/2020	Kudva
	8,111,052 B2	2/2012	Glovinsky	10,680,515 B2	6/2020	Giuliano
	8,111,054 B2	2/2012	Yen	10,686,367 B1	6/2020	Low
	8,130,518 B2	3/2012	Fishman	10,686,380 B2	6/2020	Giuliano
	8,159,091 B2	4/2012	Yeates	10,693,387 B2	6/2020	Nakahata
	8,164,384 B2	4/2012	Dawson	10,720,913 B1	7/2020	Leong
	8,169,797 B2	5/2012	Coccia	10,749,434 B2	8/2020	Giuliano et al.
	8,193,604 B2	6/2012	Lin	10,756,624 B2	8/2020	Mauri
	8,212,541 B2	7/2012	Perreault	10,756,643 B2	8/2020	Chen
	8,276,002 B2	9/2012	Dennard	10,797,660 B2	10/2020	Delano
	8,330,436 B2	12/2012	Oraw	10,917,007 B2	2/2021	Giuliano
	8,339,184 B2	12/2012	Kok	10,926,649 B2	2/2021	Nagashima
	8,350,549 B2	1/2013	Kitabatake	10,938,299 B2	3/2021	Low et al.
	8,354,828 B2	1/2013	Huang	10,938,300 B2	3/2021	Giuliano
	8,384,467 B1	2/2013	O'Keefe	11,038,418 B2	6/2021	Low et al.
	8,395,914 B2	3/2013	Klootwijk	11,936,300 B2*	3/2024	Giuliano H02M 1/0043
	8,423,800 B2	4/2013	Huang	2002/0008567 A1*	1/2002	Henry H02M 3/073
	8,451,053 B2	5/2013	Perreault			327/536
	8,456,874 B2	6/2013	Singer	2002/0060914 A1	5/2002	Porter
	8,503,203 B1	8/2013	Szczeszynski	2002/0130704 A1	9/2002	Myono
	8,542,169 B2	9/2013	Senda	2002/0158660 A1	10/2002	Jang
	8,582,333 B2	11/2013	Oraw	2003/0169096 A1	9/2003	Hsu
	8,629,666 B2	1/2014	Carroll	2003/0227280 A1	12/2003	Vinciarelli
	8,643,347 B2	2/2014	Giuliano	2004/0004851 A1	1/2004	Itoh
	8,659,353 B2	2/2014	Dawson	2004/0041620 A1	3/2004	D'Angelo
	8,670,254 B2	3/2014	Perreault	2004/0170030 A1	9/2004	Duerbaum
	8,699,248 B2	4/2014	Giuliano	2004/0222775 A1	11/2004	Muramatsu
	8,718,188 B2	5/2014	Balteanu	2005/0007184 A1	1/2005	Kamijo
	8,723,491 B2	5/2014	Giuliano	2005/0024125 A1	2/2005	McNitt
	8,729,819 B2	5/2014	Zhao	2005/0047181 A1	3/2005	Yumamoto et al.
	8,737,093 B1	5/2014	Baker	2005/0067711 A1	3/2005	Opheim
	8,743,553 B2	6/2014	Giuliano	2005/0088865 A1	4/2005	Lopez
	8,760,219 B2	6/2014	Chao	2005/0102798 A1	5/2005	Kato
	8,803,492 B2	8/2014	Liu	2005/0207133 A1	9/2005	Pavier
	8,824,978 B2	9/2014	Briffa	2005/0213267 A1	9/2005	Azrai
	8,829,993 B2	9/2014	Briffa	2005/0213280 A1	9/2005	Azrai
	8,830,709 B2	9/2014	Perreault	2005/0219878 A1	10/2005	Ito et al.
	8,830,710 B2	9/2014	Perreault	2005/0254272 A1	11/2005	Vinciarelli
	8,854,019 B1	10/2014	Levesque	2005/0286278 A1	12/2005	Perreault
	8,856,562 B2	10/2014	Huang	2006/0139021 A1	6/2006	Taurand
	8,860,396 B2	10/2014	Giuliano	2006/0153495 A1	7/2006	Wynne
	8,957,727 B2	2/2015	Dawson	2006/0213890 A1	9/2006	Kooken
	9,048,727 B2	6/2015	Giuliano	2006/0226130 A1	10/2006	Kooken
	9,143,037 B2	9/2015	Giuliano	2006/0244513 A1	11/2006	Yen et al.
	9,209,758 B2	12/2015	Briffa	2007/0013448 A1	1/2007	Azuhata et al.
	9,209,787 B2	12/2015	Shelton	2007/0024346 A1	2/2007	Takahashi et al.
	9,350,234 B2	5/2016	Verma	2007/0035977 A1	2/2007	Odell
	9,362,826 B2	6/2016	Giuliano	2007/0051712 A1	3/2007	Kooken
	9,413,257 B2	8/2016	Wang	2007/0066224 A1	3/2007	d'Hont
	9,450,506 B2	9/2016	Perreault	2007/0066250 A1	3/2007	Takahashi
	9,497,854 B2	11/2016	Giuliano	2007/0069818 A1	3/2007	Bhatti
	9,577,590 B2	2/2017	Levesque	2007/0085187 A1	4/2007	Sun
	9,584,024 B2	2/2017	Manthe	2007/0091655 A1	4/2007	Oyama
	9,634,577 B2	4/2017	Perreault	2007/0123184 A1	5/2007	Nesimoglu
	9,640,445 B1	5/2017	Hwang	2007/0146020 A1	6/2007	Williams
	9,712,051 B2	7/2017	Giuliano	2007/0146090 A1	6/2007	Carey
	9,755,672 B2	9/2017	Perreault	2007/0159257 A1	7/2007	Lee
	9,825,545 B2	11/2017	Chen	2007/0161266 A1	7/2007	Nishizawa
	9,853,637 B1	12/2017	Meiser	2007/0171680 A1	7/2007	Perreault
	9,862,052 B2	1/2018	Vogel	2007/0182390 A1	8/2007	Ishii et al.
	9,865,729 B1	1/2018	Pendharkar	2007/0210774 A1	9/2007	Kimura
	9,882,471 B2	1/2018	Giuliano	2007/0230221 A1	10/2007	Lim
	10,083,947 B2	9/2018	Giuliano	2007/0247222 A1	10/2007	Sorrells
	10,128,745 B2	11/2018	Low	2007/0247253 A1	10/2007	Carey
	10,326,358 B2	6/2019	Giuliano	2007/0281635 A1	12/2007	McCallister
	10,340,794 B1	7/2019	Zhang	2007/0290747 A1	12/2007	Traylor
	10,381,924 B2	8/2019	Giuliano	2007/0291718 A1	12/2007	Chan
	10,389,235 B2	8/2019	Giuliano	2007/0296383 A1	12/2007	Xu
	10,389,236 B1	8/2019	Low	2008/0001660 A1	1/2008	Rasmussen
	10,404,162 B2	9/2019	Giuliano	2008/0003960 A1	1/2008	Zolfaghari
				2008/0003962 A1	1/2008	Ngai
				2008/0007333 A1	1/2008	Lee
				2008/0008273 A1	1/2008	Kim
				2008/0009248 A1	1/2008	Rozenblit

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO2016149105	9/2016
WO	WO2017161368	9/2017
WO	WO2017196826	11/2017

OTHER PUBLICATIONS

W. Ng, Vincent et al., "Minimum PCB Footprint Point-of-Load DC-DC Converter Realized with Switched-Capacitor Architecture," 2009 IEEE Energy Conversion Congress and Exposition, San Jose, CA, USA, 2009, pp. 1575-1581.

Yeung, Y.P. Benny et al., "Unified Analysis of Switched-Capacitor Resonant Converters," Aug. 2004, IEEE Transactions on Industrial Electronics, vol. 51, No. 4, pp. 864-873.

Abutbul et al. "Step-Up Switching-Mode Converter With High Voltage Gain Using a Switched-Capacitor Circuit" IEEE Transactions on Circuits and Systems I. vol. 50 pp. 1098-1102 Aug. 2003.

Andreassen—"Digital Variable Frequency Control for Zero Voltage Switching and Interleaving of Synchronous Buck Converters" 12th Intl. Power Electronics and Motion Control Conference IEEE Aug. 2006 pp. 184-188 5 pages.

Axelrod et al. "Single-switch single-stage switched-capacitor buck converter" Proc. of NORPIE 2004 4th Nordic Workshop on Power and Industrial Electronics Jun. 2004.

Cao—"Multiphase Multilevel Modular DC-DC Converter for High-Current High-Gain TEG Application" IEEE Transactions on Industry Applications vol. 47 No. 3 May/June. 1991 pp. 1400-1408 9 pages.

Cheng "New generation of switched capacitor converters" PESC 98 Record. 29th Annual IEEE Power Electronics Specialists Conference (Cat. No. 98CH36196) Fukuoka Japan May 22, 1998 pp. 1529-1535 vol. 2 doi: 10.1109/PESC.1998.703377.

Dong Cao et al: "Multiphase Multilevel Modular DC-DC Converter for High-Current High-Gain TEG Application" IEEE Transactions on Industry Applications IEEE Service Center Piscataway NJ US vol. 47 No. 3 May 1, 2011 (May 1, 2011) pp. 1400-1408 XP011477763 ISSN: 0093-9994 DOI: 10.1109/TIA.2011.2125771.

Giuliano—"Architectures and Topologies for Power Delivery" Biannual Review of MIT Center for Integrated Circuits; Power Point Presentation May 9, 2007 17 slides.

Han et al. "A New Approach to Reducing Output Ripple in Switched-Capacitor-Based Step-Down DC-DC Converters" IEEE Transactions on Power Electronics vol. 21 No. 6 pp. 1548-1555 Nov. 2006.

Lei et al. "Analysis of Switched-capacitor DC-DC Converters in Soft-charging Operation" 14th IEEE Workshop on Control and Modeling for Power Electronics pp. Jun. 1-7, 23 2013.

Linear Technology data sheet for part LTC3402 "2A 3MHz Micropower Synchronous Boost Converter" 2000.

Luo—"Investigation of Switched-Capacitorized DCDC Converters" 2009 IEEE 6th Intl. Power Electronics and Motion Control Conference Wuhan China May 17-20, 2009 pp. 1270-1276 7 pages.

Ma et al. "Design and Optimization of Dynamic Power System for Self-Powered Integrated Wireless Sensing Nodes" ACM ISLPED 2005 conference (published at pp. 303-306 of the proceedings).

Markowski "Performance Limits of Switched-Capacitor DC-DC Converters" IEEE PESC'95 Conference 1995.

Meynard et al. "Multi-Level Conversion: High Voltage Choppers and Voltage-Source Inverters" IEEE Power Electronics Specialists Conference pp. 397-403 1992.

Middlebrook "Transformerless DC-to-DC Converters with Large Conversion Ratios" IEEE Transactions on Power Electronics vol. 3 No. 4 pp. 484-488 Oct. 1988.

Ng et al. "Switched Capacitor DC-DC Converter: Superior where the Buck Converter has Dominated" PHD Thesis UC Berkeley Aug. 17, 2011.

O. Abutbul et al. "Step-Up Switching-Mode Converter With High Voltage Gain Using a Switched-Capacitor Circuit" IEEE Transactions on Circuits and Systems I. vol. 50 pp. 1098-1102 Aug. 2003.

Ottman et al. "Optimized Piezoelectric Energy Harvesting Circuit using Step-Down Converter in Discontinuous Conduction Mode" IEEE Power Electronics Specialists Conference pp. 1988-1994 2002.

Pilawa-Podgurski et al. "Merged Two-Stage Power Converter Architecture with Soft Charging Switched-Capacitor Energy Transfer" 39th IEEE Power Electronics Specialists Conference 2008.

Starzyk et al. "A DC-DC Charge Pump Design Based on Voltage Doublers" IEEE Transactions on Circuits and Systems-I: Fundamental Theory and Applications vol. 48 No. Mar. 3, 2001 pp. 350-359.

Sun et al. "High Power Density High Efficiency System Two-Stage Power Architecture for Laptop Computers" Power Electronics Specialists Conference pp. Jun. 1-7, 2006.


Texas Instruments data sheet for part TPS54310 "3-V to 6-V input 3-A output synchronous-buck PWM switcher with integrated FETs" dated 2002-2005.

Umeno et al. "A New Approach to Low Ripple-Noise Switching Converters on the Basis of Switched-Capacitor Converters" IEEE International Symposium on Circuits and Systems vol. 2 pp. 1077-1080 Jun. 1991.

Wood et al. "Design Fabrication and Initial Results of a 2g Autonomous Glider" IEEE Industrial Electronics Society pp. 1870-1877 Nov. 2005.

Xu et al. "Voltage Divider and its Application in Two-stage Power Architecture" IEEE Twenty-First Annual IEEE Applied Power Electronics Conference and Exposition pp. 499-504 Mar. 2006.

* cited by examiner



PRIOR ART
FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B

SWITCHED-CAPACITOR CIRCUIT CONTROL IN POWER CONVERTERS

RELATED APPLICATIONS

This application is continuation of U.S. application Ser. No. 18/606,319, filed on Mar. 15, 2024, which is a continuation of U.S. application Ser. No. 17/491,983, filed on Oct. 1, 2021 and issued as U.S. Pat. No. 11,936,300 on Mar. 19, 2024, which is a continuation of U.S. application Ser. No. 16/872,207, filed on May 11, 2020 and issued as U.S. Pat. No. 11,165,350 on Nov. 2, 2021, which is a continuation of U.S. application Ser. No. 14/857,141, filed on Sep. 17, 2015 and issued as U.S. Pat. No. 10,686,380 on Jun. 16, 2020, which is a continuation of U.S. application Ser. No. 14/309,003, filed on Jun. 19, 2014 and issued as U.S. Pat. No. 9,143,037 on Sep. 22, 2015, which is a continuation of PCT/US2012/070555, filed on Dec. 19, 2012 which claims the benefit of the priority date of U.S. Provisional Application No. 61/577,271 filed on Dec. 19, 2011, the contents of which for all of the noted applications are herein incorporated by reference in their entirety.

FIELD OF DISCLOSURE

This disclosure relates to the control of power converters that utilize capacitors to transfer energy.

BACKGROUND

Power converters may generally include switches and one or more capacitors. Such converters can be used, for example, to power portable electronic devices and consumer electronics.

A switch-mode power converter is a specific type of power converter that regulates an output voltage or current by switching energy storage elements (i.e. inductors and capacitors) into different electrical configurations using a switch network.

A switched capacitor converter is a type of switch-mode power converter that primarily utilizes capacitors to transfer energy. In such converters, the number of capacitors and switches increases as the transformation ratio increases.

Typical power converters perform voltage transformation and output regulation. In many power converters, such as buck converters, both functions take place in a single stage. However, it is also possible to split these two functions into two specialized stages. Such two-stage power converter architectures feature a separate transformation stage and a separate regulation stage. The transformation stage transforms one voltage into another voltage, while the regulation stage ensures that the output voltage and/or output current of the power converter maintains desired characteristics.

For example, referring to FIG. 1, in one known power converter 10, a switched capacitor element 12A is electrically connected, at an input end thereof, to a voltage source 14. An input of a regulating circuit 16A is electrically connected to an output of the switched capacitor element 12A. A load 18A is then electrically connected to an output of the regulating circuit 16A. Such a converter is described in US Patent Publication 2009/0278520, filed on May 8, 2009, the contents of which are herein incorporated by reference.

Furthermore, a modular multi-stage power converter architecture is described in PCT Application PCT/2012/36455, filed on May 4, 2012, the contents of which are also incorporated herein by reference. The switched capacitor

element 12A and the regulating circuit 16A can be mixed and matched in a variety of different ways. This provides a transformative integrated power solution (TIPS™) for the assembly of such power converters. As such, the configuration shown in FIG. 1 represents only one of multiple ways to configure one or more switched capacitor elements 12A with one or more regulating circuits 16A.

SUMMARY

In one aspect, the invention features an apparatus for power conversion. Such an apparatus includes a first element configured to accept an input signal having a first voltage and to output an intermediate signal having a second voltage, and a second element configured to receive the intermediate signal from the first element and to output an output signal having a third voltage. The first element is either a voltage transformation or a regulating element. The second element is a regulating element when the first element is a voltage transformation element and a voltage transformation element otherwise. A controller is configured to control a period of the voltage transformation element and a period of the regulating element. The controller is configured to synchronize the period of the voltage transformation element with a product of a coefficient and the period of the regulating element. This coefficient can be either a positive integer or a reciprocal of the integer.

In some embodiments, the coefficient is a positive integer, whereas in others, it is a reciprocal of the positive integer.

Embodiments also include those in which the controller receives the intermediate signal from the first element and the output signal from the second element. Among these are those in which the controller receives the input signal, and also those in which the controller generates a first control signal based on the output signal and sends the first control signal to the regulating element. This embodiment also includes within its scope alternative embodiments in which the controller generates a second control signal based on the intermediate signal and the first control signal, and sends the second control signal to the voltage transformation element.

Also included within the scope of the invention are those embodiments in which the controller provides linear voltage-mode control, and those in which it provides peak current-mode control.

In some embodiments, regulating element passes continuous current therethrough, whereas in others, the regulating element passes discontinuous current therethrough.

In other embodiments, the voltage transformation element includes voltage transformation sub-elements and the regulating element includes regulating sub-elements, and each voltage transformation sub-element is associated with a corresponding one of the regulating sub-elements.

Embodiments also include those in which the first element includes a voltage transformation element and those in which the first element includes a regulating element.

In another aspect, the invention features an apparatus for power conversion, such an apparatus includes a voltage transformation element, a regulating element, and a controller. A period of the voltage transformation element is equal to a product of a coefficient and a period of the regulating circuit. The coefficient is either a positive integer or a reciprocal of the integer.

Embodiments include those in which the regulating element passes continuous current therethrough, and also those in which the regulating element passes discontinuous current therethrough.

In some embodiments, the controller controls multiple phases present in the regulating element and the voltage transformation element.

Other embodiments include a data processing unit and a memory unit, at least one of which is configured to consume power provided by the power converter circuit.

Additional embodiments include data processing unit, a display, and a wireless transmitter and receiver, at least one of which is configured to consume power provided by the power converter circuit.

DESCRIPTION OF THE FIGURES

The foregoing features of the circuits and techniques described herein, may be more fully understood from the following description of the figures in which:

FIG. 1 shows a known power converter architecture;

FIG. 2 shows a particular implementation of the power converter architecture in FIG. 1;

FIG. 3 shows a controller coupled to the power converter in FIG. 2;

FIG. 4 shows a particular implementation of the controller in FIG. 3;

FIG. 5 shows a timing diagram of relevant signals from the embodiment in FIG. 4.

FIG. 6 shows a close-up of selected signals in FIG. 5;

FIG. 7 shows a DC model of a switched capacitor element;

FIGS. 8A-8B show the relationship between the load current and the intermediate voltage ripple;

FIG. 9 shows a controller that synchronizes a regulating circuit that precedes a switched capacitor element;

FIG. 10 shows a three-phase controller that synchronizes a three-phase switched capacitor element that precedes a three-phase regulating circuit;

FIG. 11 shows a particular implementation of the three-phase controller in FIG. 10; and

FIGS. 12A-12B show timing diagrams of relevant signals from the embodiment in FIG. 11.

DETAILED DESCRIPTION

The apparatus described herein provides a way to control the switched capacitor element 12A and the regulating circuit 16A in a modular multi-stage power converter architecture.

Before describing several exemplary embodiments of controllers for power converters that utilize capacitors to transfer energy, it should be appreciated that in an effort to promote clarity in explaining the concepts, references are sometimes made herein to specific controllers for power converters that utilize capacitors to transfer energy. It should be understood that such references are merely exemplary and should not be construed as limiting. After reading the description provided herein, one of ordinary skill in the art will understand how to apply the concepts described herein to provide specific controllers for power converters that utilize capacitors to transfer energy.

It should be appreciated that reference is also sometimes made herein to particular frequencies as well as to particular transformation voltage ratios. It should be understood that such references are merely exemplary and should not be construed as limiting.

Reference may also sometimes be made herein to particular applications. Such references are intended merely as exemplary and should not be taken as limiting the concepts described herein to the particular application.

Thus, although the description provided herein explains the inventive concepts in the context of particular circuits or a particular application or a particular frequency, those of ordinary skill in the art will appreciate that the concepts equally apply to other circuits or applications or frequencies.

FIG. 2 illustrates a power converter 10A that receives an input voltage VIN from the voltage source 14 and produces an output voltage VO that is lower than the input voltage VIN.

The power converter 10A is a particular embodiment of the power converter architecture illustrated in FIG. 1. The switched capacitor element 12A features a 2:1 dual-phase series-parallel switched capacitor network that includes power switches S1-S8 and pump capacitors C1-C2. In contrast, the regulating circuit 16A features a buck converter that includes a low-side switch SL, a high-side switch SH, a filter inductor L1, and a driver stage 51.

In the operation of the switched capacitor element 12A, the power switches S1, S3, S6, S8 and the power switches S2, S4, S5, S7 are always in complementary states. Thus, in a first network state, the power switches S1, S3, S6, S8 are open and the power switches S2, S4, S5, S7 are closed. In a second network state, the power switches S1, S3, S6, S8 are closed and the power switches S2, S4, S5, S7 are open. The switched capacitor element 12A cycles through the first network state and the second network state, resulting in an intermediate voltage VX that is one-half of the input voltage VIN.

Referring to FIG. 2, the switched capacitor element 12A is in the first network state when a first phase voltage VA is low and a second phase voltage VB is high. In contrast, the switched capacitor element 12A is in the second network state when the first phase voltage VA is high and the second phase voltage VB is low. The two phase voltages VA, VB are non-overlapping and have approximately a fifty percent duty cycle.

In the operation of the regulating circuit 16A, the low-side switch SL and the high-side switch SH chop the intermediate voltage VX into a switching voltage VLX. A LC filter receives the switching voltage VLX and generates the output voltage VO that is equal to the average of the switching voltage VLX. To ensure the desired output voltage VO, a regulation control voltage VR controls the duty cycle of the low-side switch SL and the high-side switch SH. Additionally, the driver stage 51 provides the energy to open and close the low-side and high-side switches SL, SH.

Previous disclosures treat the control of the switched capacitor element 12A and regulating circuit 16A separately. This has numerous disadvantages, one of which is that the intermediate voltage VX ripple will feed through to the output voltage VO. A possible solution to this problem is to create a feed-back control loop that is fast enough to attenuate the effect of the intermediate voltage VX ripple on the output voltage VO. To achieve this goal, the frequency of the regulating circuit 16A must be at a significantly higher frequency than the frequency of the switched capacitor element 12A.

Another possible solution to this problem would be to add a feed-forward control loop to the regulating circuit 16A. However, as was the case with the fast feed-back solution, the feed-forward solution will only be effective if the frequency of the regulating circuit 16A is significantly higher than the frequency of the switched capacitor element 12A. Therefore, both solutions place a severe frequency constraint on the switched capacitor element 12A and the regulating circuit 16A.

Furthermore, there is typically a dead-time interval DT between the first network state and the second network state of the switched capacitor element 12A. During the dead-time interval DT, all of the switches in the switched capacitor element 12A are open. This ensures a clean transition between the first network state and the second network state of the switched capacitor element 12A, and vice versa. If the regulating circuit 16A tries to draw current during the dead-time interval DT, a voltage ‘glitch’ will occur at the node between the switched capacitor element 12A and the regulating circuit 16A.

The voltage ‘glitch’ can be reduced through the use of a glitch capacitor CX. Unfortunately, a portion of the energy stored on the glitch capacitor CX is thrown away each time the switched capacitor element 12A transitions between the first network state and the second network state, and vice versa. The energy loss is a result of the glitch capacitor CX being shorted to capacitors at a different voltage, such as pump capacitors C1, C2. Therefore, the use of a glitch capacitor CX to supply energy during the dead-time interval DT is an effective solution, but requires one additional capacitor and reduces the efficiency of the power converter 10A.

Embodiments described herein rely at least in part on the recognition that by synchronizing the switched capacitor element 12A and the regulating circuit 16A, the intermediate voltage VX ripple effect on the output voltage VO and the voltage “glitch” can be minimized.

FIG. 3 illustrates a first generic controller 20 that synchronizes the switched capacitor element 12A and the regulating circuit 16A within the power converter 10A shown in FIG. 2. The first generic controller 20 receives five input signals and provides three output signals. The input signals include the input voltage VIN, the output voltage VO, the intermediate voltage VX, a reference voltage VREF, and a clock voltage VCLK. The output signals include the regulation control voltage VR, the first phase voltage VA, and the second phase voltage VB. The clock voltage VCLK sets the period of the regulation control voltage VR and the reference voltage VREF sets the desired output voltage VO.

Synchronizing the switched capacitor element 12A with the regulating circuit 16A causes the intermediate voltage VX ripple to be in phase with the switching voltage VLX. In this scenario, feed-forward control is effective if the frequency of the regulating circuit 16A is greater than or equal to the frequency of the switched capacitor element 12A, thereby relieving the severe frequency constraint of separately controlled stages.

Additionally, the glitch capacitor CX, shown in FIG. 2, can be removed altogether if the dead-time interval DT of the switch capacitor element 12A occurs when the regulating circuit 16A is not drawing input current. Synchronizing the switched capacitor element 12A and the regulating circuit 16A ensures the proper timing between the dead-time interval DT and the interval during which the regulating circuit 16A is not drawing input current.

One more benefit of synchronizing the switched capacitor element 12A and the regulating circuit 16A is the ability to open and close the power switches S1-S8 in the switched capacitor element 12A when zero-current is flowing through the power switches S1-S8. This technique is often referred to as zero-current switching. To achieve zero-current switching, the dead-time interval DT must occur when the regulating circuit 16A is not drawing input current.

FIG. 4 illustrates a controller 20A that is a preferred embodiment of the first generic controller 20. The controller 20A can be separated into a first control section and a second

control section. The control circuitry for the regulating circuit 16A is in the first control section and includes first, second, third, and fourth control blocks 30, 31, 32, 33. In contrast, the control circuitry for the switched capacitor element 12A is in the second control section and includes fifth, sixth, and seventh control blocks 34, 35, 36. The “link” between the fourth control block 33 and the fifth control block 34 enables synchronization of the first and second control sections.

In an effort to promote clarity in explaining the operation of the controller 20A, FIG. 5 illustrates some relevant signals generated by the controller 20A. The relevant signals include the clock voltage VCLK, a saw-tooth voltage VSAW, the regulation control voltage VR, the switching voltage VLX, a filter inductor current IL, the intermediate voltage VX, the first phase voltage VA, and the second phase voltage VB. Furthermore, FIG. 6 illustrates a close-up of some of the waveforms in FIG. 5, where the regulation control voltage period TSW is the inverse of the regulation control voltage VR frequency.

Referring back to FIG. 4, the first control section within the controller 20A uses a linear voltage-mode control scheme to control the regulating circuit 16A. The controller 20A compares the output voltage VO with the reference voltage VREF, thereby producing a residual voltage that is conditioned by the second control block 31. A resulting error voltage VERR is then fed into the third control block 32 where it is compared with the saw-tooth voltage VSAW. Lastly, the output of the third control block 32 is further conditioned by the fourth control block 33, resulting in the regulation control voltage VR.

The first control block 30 sets the frequency of the regulation control voltage VR by generating the saw-tooth voltage VSAW from the clock voltage VCLK. Additionally, the first control block 30 provides feed-forward control of the regulating circuit 16A by adjusting the peak voltage of the saw-tooth voltage VSAW based upon the intermediate voltage VX. Alternatively, feed-forward control can be implemented by adjusting the error voltage VERR with respect to the input voltage VIN or the intermediate voltage VX in the second control block 31.

The second control section within the controller 20A uses a hysteretic control scheme to control the switched capacitor element 12A. The controller 20A causes the first and second phase voltages VA, VB to cycle the switched capacitor element 12A back and forth between the first network state and the second network state based upon a hysteresis band.

During operation, the sixth control block 35 continuously compares the intermediate voltage VX with a trigger voltage VXL. When the intermediate voltage VX drops below the trigger voltage VXL, the fifth control block 34 is triggered and then waits for a confirmation signal. Once the fourth control block 33 sends a signal informing the fifth control block 34 that it is acceptable to make a state change, the dead-time interval DT, shown in FIG. 6, is initiated. During the dead-time interval DT, the first and second phase voltages VA, VB are set low. Following the dead-time interval DT, either the first phase voltage VA is set high and the second phase voltage VB is left low or the first phase voltage VA is left low and the second phase voltage VB is set high, depending upon the initial state. After the state change, the fifth control block 34 is reset and the sequence repeats.

The controller 20A thus forces the frequency of the switched capacitor element 12A to be submultiples of the frequency of the regulating circuit 16A. This constraint is illustrated in FIG. 5, where the frequencies of the first phase voltage VA and the second phase voltage VB are much lower

than the frequency of the regulation control voltage VR. In some practices, the frequency of the second phase voltage VB is as little as a tenth that of the control voltage VR.

Since the switched capacitor element 12A is loaded down by a non-capacitive regulating circuit 16A, the voltage ripple on the intermediate voltage VX is a piecewise linear approximation of a saw-tooth waveform. As used herein, an intermediate peak-peak voltage ripple AVX is equal to the maximum intermediate voltage minus the minimum intermediate voltage under steady state conditions. Typically, the intermediate voltage VX comprises a high frequency component from the regulating circuit 16A superimposed on the lower frequency saw-tooth waveform from the switched capacitor element 12A.

Unfortunately, while the fifth control block 34 is waiting to change states, the intermediate voltage VX drops a delta voltage AVD below the trigger voltage VXL, as shown by the intermediate voltage VX curve in FIG. 5. Typically, the delta voltage AVD is small, especially if the frequency of the switched capacitor element 12A is much lower than the frequency of the regulating circuit 16A. The delta voltage AVD at most can be equal to one-half of the intermediate peak-peak voltage ripple AVX and this occurs when the frequency of the switched capacitor element 12A is equal to the frequency of the regulating circuit 16A.

FIG. 7 illustrates a DC model of the switched capacitor element 12A coupled between the voltage source 14 and the regulating circuit 16A. The DC model includes a transformer with a finite output resistance RO. Assuming the switched capacitor element 12A delivers an intermediate current IX, the average of the intermediate voltage VX can be calculated using

$$\overline{VX} = VIN \frac{N2}{N1} - IX \times RO$$

The configuration of the switches and capacitors in the switched capacitor element 12A sets a voltage transformation ratio N1:N2. Meanwhile, the output resistance RO of the switched capacitor element 12A accounts for the energy loss in charging/discharging the pump capacitors.

Based upon the waveforms in FIG. 5, the average of the intermediate voltage VX can be calculated using

$$\overline{VX} = VXL - AVD + AVX/2$$

By equating the previous two equations, the intermediate peak-peak voltage ripple ΔVX can be expressed as

$$\Delta VX = 2 \left[VIN \frac{N2}{N1} - IX \times RO - VXL + \Delta VD \right]$$

Consequently, the intermediate peak-peak voltage ripple ΔVX is function of operating parameters such as the intermediate current IX and the input voltage VIN. Additionally, due to the synchronization constraint, the intermediate peak-peak voltage ripple ΔVX is also a function of the delta voltage ΔVD.

Unfortunately, large variations in the intermediate peak-peak voltage ripple ΔVX can overstress the regulating circuit 16A. To minimize variations of the intermediate peak-peak voltage ripple ΔVX, the trigger voltage VXL, shown in FIG. 4, can be adjusted on the fly. For example, the seventh control block 36 utilizes the input voltage VIN and the intermediate voltage VX to make a decision on the

appropriate value of the trigger voltage VXL. Therefore, when the input voltage VIN rises, the trigger voltage VXL rises in step.

One key idea illustrated in FIG. 6 is that the dead-time interval DT occurs during the off state of the high-side power switch SH in FIG. 2. To ensure this outcome, there is an upper bound on the duty cycle of the regulating circuit 16A, where a maximum duty cycle DMAX is determined using

$$DMAX = \frac{TSW - DT}{TSW}$$

As illustrated by the equation above, the dead-time interval DT sets the maximum duty cycle DMAX. It is often desirable to minimize the dead-time interval DT, thereby widening the duty cycle range of the regulating circuit 16A.

It is not uncommon to have a duty cycle limit, specifically if constant frequency operation of the regulating circuit 16A is required for electromagnetic compatibility reasons. In these cases, the maximum duty cycle DMAX constraint is not overly burdensome because the feed-back control loop for the regulating circuit 16A would otherwise have a duty cycle limit.

FIG. 8A illustrates the period of the switched capacitor element 12A and the intermediate peak-peak voltage ripple ΔVX as a function of the output current. As the output current decreases, the slope of the voltage ripple on the intermediate voltage VX decreases. This reduces the frequency of the first and second phase voltages VA, VB. Due to synchronization, the reduction in frequency occurs abruptly and only at specific output current values. The change in frequency takes place whenever the intermediate peak-peak voltage ripple ΔVX is equal to a maximum peak-peak voltage ripple ΔVMAX divided by two. Consequently, the intermediate peak-peak voltage ripple ΔVX follows a saw-tooth waveform with a fixed valley voltage. Furthermore, as the output current approaches zero, the intermediate peak-peak voltage ripple ΔVX approaches one-half of the maximum peak-peak voltage ripple ΔVMAX.

With a few modifications to the controller 20A, it is also possible to get the intermediate peak-peak voltage ripple ΔVX to follow a saw-tooth waveform with a fixed peak voltage as illustrated in FIG. 8B. In this scenario, as the output current approaches zero, the intermediate peak-peak voltage ripple ΔVX approaches the maximum peak-peak voltage ripple ΔVMAX. The main difference between the first approach in FIG. 8A and second approach in FIG. 8B is the distribution of frequencies and intermediate peak-peak voltage ripple ΔVX across the output current range.

The controller 20A depicted in FIG. 4 and described above is one of many possible implementations of the first generic controller 20 that can synchronize the power converter 10A or any power converter that includes a switched capacitor element 12A that precedes a regulating circuit 16A. In the modular multi-stage power converter architecture, the switched capacitor element 12A and the regulating circuit 16A can be mixed and matched in a variety of different ways. For example, FIG. 9 illustrates an alternative power converter 10B, wherein a regulating circuit 16A precedes a switched capacitor element 12A.

In FIG. 9, a second generic controller 21 synchronizes the regulating circuit 16A and the switched capacitor element 12A. The input and output signals of the second generic controller 21 are the same as that of the first generic

controller 20. In the power converter 10B, the regulating circuit 16A may include various types of switch-mode power converters, such as a boost converter, a resonant converter, and a fly-back converter. Similarly, the switched capacitor element 12A may include various types of switched capacitor converters, such as a series-parallel charge pump, a voltage doubler, and a cascade multiplier. Regardless of the selection of either the regulating circuit 16A or the switched capacitor element 12A, if the two stages are synchronized, the frequency of the switched capacitor element 12A will change in discrete steps as the output current of the power converter 10B is varied.

In addition to alternative modular multi-stage power converter architectures, it is also possible to synchronize multi-phase implementations. FIG. 10 illustrates a three-phase power converter 10C and a generic three phase-controller 22 that synchronizes the various stages. The three-phase power converter 10C includes three regulating sub-elements: a first regulating circuit 16A, a second regulating circuit 16B, a third regulating circuit 16C and three voltage transformation sub-elements: a first switched capacitor element 12A, a second switched capacitor element 12B, and a third switched capacitor element 12C. The first, second, and third switched capacitor elements 12A, 12B, 12C provide first, second, and third intermediate voltages VX1, VX2, VX3, respectively.

First, second, and third regulation control voltages VR1, VR2, VR3 control the first, second, and third regulating circuits 16A, 16B, 16C, respectively. Furthermore, first and second phase voltages VA1, VB1 control the first switched capacitor element 12A; third and fourth phase voltages VA2, VB2 control the second switched capacitor element 12B; and fifth and sixth phase voltages VA3, VB3 control the third switched capacitor element 12C. Additionally, a regulation control bus BVR includes the first, second, and third regulation control voltages VR1, VR2, VR3. A first phase bus BVA includes the first, third, and fifth phase voltages VA1, VA2, VA3. Lastly, a second phase bus BVB includes the second, fourth, and sixth phase voltages VB1, VB2, VB3.

FIG. 11 illustrates a three-phase controller 22A that is a preferred embodiment of the generic three-phase controller 22. The three-phase controller 22A can be separated into a first control section and a second control section. The control circuitry for the first, second, and third regulating circuits 16A, 16B, 16C is in the first control section and includes first, second, third, fourth, fifth, and sixth control blocks 30, 31, 32A, 32B, 32C, 33. In contrast, the control circuitry for the first, second, and third switched capacitor elements 12A, 12B, 12C is in the second control section and includes seventh, eighth, ninth, tenth, and eleventh control blocks 34, 35A, 35B, 35C, 36.

The three-phase controller 22A looks very similar to the controller 20A in FIG. 4, but with additional input and output signals. In the three-phase controller 22A, a linear voltage-mode control scheme is used to control the regulating circuits 16A-16C and a hysteretic control scheme is used to control the switched capacitor elements 12A-12C. Consequently, the operation of the first and second control sections in the three-phase controller 22A is similar to that described in connection with FIG. 4.

In the first control section, the first control block 30 sets the frequency and phase of the first, second, and third regulation control voltages VR1, VR2, VR3. The first control block 30 generates first, second, and third saw-tooth voltages VSAW1, VSAW2, VSAW3 that are compared to an error voltage VERR by the third, fourth, and fifth control blocks 32A, 32B, 32C, respectively. The resulting three

outputs are further conditioned by the sixth control block 33 that produces the regulation control bus BVR.

In the second control section, the first, second, and third intermediate voltages VX1, VX2, VX3 are compared to a trigger voltage VXL produced by the eleventh control block 36. The output of the eighth, ninth, tenth control blocks 35A, 35B, 35C are further conditioned by the seventh control block 34 resulting in the first and second phase buses BVA, BVB. The 'link' between the sixth control block 33 and the seventh control block 34 enables synchronization of the first and second control sections.

In an effort to promote clarity, FIG. 12A illustrates some relevant signals generated by the three-phase controller 22A. The first, second, and third regulation control voltages VR1, VR2, VR3 are one hundred and twenty degrees out of phase with each other. Meanwhile, the phase voltages VA1, VA2, VA3 are shifted in time with respect to each other the same amount as their corresponding regulation control voltages VR1, VR2, VR3 are shifted in time with respect to each other. Furthermore, the second, fourth, and sixth phase voltages VB1, VB2, VB3 are one hundred and eighty degrees out of phase with the first, third, and fifth phase voltages VA1, VA2, VA3, respectively.

For example, if the frequency of the first, second, and third regulating circuits 16A, 16B, 16C is one megahertz, then the rising and/or falling edges of the first, second, and third regulation control voltages VR1, VR2, VR3 are separated by one-third of a microsecond. Consequently, the rising and/or falling edges of the first, third, and fifth phase voltages VA1, VA2, VA3 are separated by one-third of a microsecond and the rising and/or falling edges of the second, fourth, and sixth phase voltages VB1, VB2, VB3 are separated by one-third of a microsecond.

With a few modifications to the three-phase controller 22A, it is possible to further shift the first, third, and fifth phase voltages VA1, VA2, VA3 by one or more whole periods of the regulating circuits 16A-16C as illustrated in FIG. 12B.

For example, if the frequency of each of the regulating circuits 16A-16C is one megahertz, then the period of each of the regulating circuits 16A-16C is one microsecond. Assuming a shift of one period, then the rising and/or falling edges of the first, third, and fifth phase voltages VA1, VA2, VA3 are separated by one and one-third of a microsecond and the rising and/or falling edges of the second, fourth, and sixth phase voltages VB1, VB2, VB3 are separated by one and one-third of a microsecond. Among other benefits, the more uniform spacing of the first intermediate voltage VX1 ripple, the second intermediate voltage VX2 ripple, and the third intermediate voltage VX3 ripple reduces their effect on the output voltage VO.

As in the single-phase case, the glitch capacitor CX can be removed altogether if the dead-time interval DT of each of the switched capacitor elements 12A, 12B, 12C occurs when their corresponding regulating circuits 16A, 16B, 16C are neither sinking nor sourcing current through an inductive element. For example, in a buck converter, the filter inductor is sinking current from the input only a portion of the time, whereas, in a boost converter, the filter inductor is sourcing current to the output only a portion of the time. These power converters have a discontinuous current interval during which current is either sunk or sourced. Therefore, the glitch capacitor CX is unnecessary if the dead-time interval DT of each of the switched capacitor elements 12A, 12B, 12C occurs during the discontinuous input current interval.

Both the controller 20A in FIG. 4 and the three-phase controller 22A in FIG. 11 utilize linear voltage-mode con-

trol. However, other control techniques such as non-linear voltage-mode control, peak current-mode control, and average current-mode control are applicable as well.

The control circuitry described herein synchronizes the switched capacitor elements 12A with the regulating circuits 16A in the modular multi-stage power converter architecture. Among other advantages, the control circuitry described herein provides a way to minimize the effect of the intermediate voltage VX ripple on the output voltage VO and minimize the production of a voltage 'glitch' during the dead-time internal DT of the switched capacitor element 12A.

Various features, aspects, and embodiments of control techniques for power converters that utilize capacitors to transfer energy have been described herein. The features, aspects, and numerous embodiments described are susceptible to combination with one another as well as to variation and modification, as will be understood by those having ordinary skill in the art. The present disclosure should, therefore, be considered to encompass such combinations, variations, and modifications. Additionally, the terms and expression which have been employed herein are used as terms to description and not of limitation, and there is no intention, in the use of such terms and expression, of excluding any equivalents of the features shown and described (or portions thereof), and it is recognized that various modifications are possible within the scope of the claims. Other modifications, variations, and alternatives are also possible. Accordingly, the claims are intended to cover all such equivalents.

Having described the invention, and a preferred embodiment thereof, what is claimed as new and secured by letters patent is:

What is claimed is:

1. A power converter, comprising:

a voltage converting circuit configured to provide an output voltage regulated based on a first signal; and
 a switched capacitor circuit coupled to the voltage converting circuit, wherein the switched capacitor circuit is a multiple phase circuit comprising a first switched capacitor element and a second switched capacitor element each configured to change between a first network state and a second network state and each configured to provide, to an output node, an output voltage of the switched capacitor circuit in both the first network state and the second network state, wherein the first switched capacitor element comprises a first capacitor, a first set of switches configured to be switched substantially in accordance with a switching frequency and based on a first phase voltage, and a second set of switches configured to be switched substantially in accordance with the switching frequency and based on a second phase voltage out of phase with the first phase voltage, wherein the second switched capacitor element comprises a second capacitor, a third set of switches configured to be switched substantially in accordance with the switching frequency and based on the second phase voltage, and a fourth set of switches configured to be switched substantially in accordance with the switching frequency and based on the first phase voltage out of phase with the second phase voltage; and

a controller coupled to the voltage converting circuit and the switched capacitor circuit, wherein the controller is configured to provide one or more control signals to the voltage converting circuit and to the switched capacitor

circuit and configured to coordinate operation of the voltage converting circuit and the switched capacitor circuit based on the one or more control signals such that the first switched capacitor element operates simultaneously and in an out of phase relationship with the second switched capacitor element.

2. The power converter of claim 1, wherein the first switched capacitor element and the second switched capacitor element are configured to operate simultaneously and in the out of phase relationship such that:

in the first network state, each switch of the first and fourth sets of switches is in a closed state based on the first phase voltage and each switch of the second and third sets is in an open state based on the second phase voltage; and

in the second network state, each switch of the first and fourth sets of switches is in the open state based on the first phase voltage and each switch of the second and third sets is in the closed state based on the second phase voltage.

3. The power converter of claim 1, wherein each switch of the first, second, third, and fourth set of switches is configured to be in an open state or a closed state, wherein, in both the first network state and the second network state, each switch of the first set of switches is in an opposite state relative to its corresponding switch of the third set of switches and each switch of the second set of switches is in an opposite state relative to its corresponding switch of the fourth set of switches.

4. The power converter of claim 1, wherein:

in the first network state:

the first capacitor of the first switched capacitor element is configured to charge; and

the second capacitor of the second switched capacitor element is configured to discharge to the output node; and

in the second network state:

the first capacitor of the first switched capacitor element is configured to discharge to the output node; and

the second capacitor of the second switched capacitor element is configured to charge.

5. The power converter of claim 1, wherein the controller is configured to compare the output voltage of the voltage converting circuit with a trigger voltage to trigger an initiation of a dead-time interval, wherein the controller is configured to coordinate the operation of the switched capacitor circuit and the voltage converting circuit by setting a period of the switched capacitor circuit at least in part based on a period of the voltage converting circuit, wherein the controller is configured to coordinate the operation of the voltage converting circuit and the switched capacitor circuit such that the voltage converting circuit and the switched capacitor circuit are synchronized based, at least in part, on the dead-time interval, and wherein the trigger voltage is adjustable on the fly.

6. The power converter of claim 1, wherein the first switched capacitor element and the second switched capacitor element are coupled to a voltage source.

7. The power converter of claim 1, wherein the controller is configured to generate the first signal and the one or more control signals in response to one or more voltage signals associated with the switched capacitor circuit and the voltage converting circuit, and wherein the one or more voltage signals comprise a reference voltage, an output voltage, an intermediate voltage, an input voltage, or any combination thereof.

13

8. The power converter of claim 1, wherein the power converter is configured to provide power to a load, and wherein the controller is configured to coordinate the operation of the switched capacitor circuit and the voltage converting circuit to facilitate power consumption by the load.

9. The power converter of claim 1, wherein each switch of the first and second sets of switches of the first switched capacitor element is configured to be in an open state during a dead-time interval of the first switched capacitor element between the first network state and the second network state of the first switched capacitor element.

10. A power converter, comprising:

a regulating circuit configured to receive an input voltage and configured to provide, in response to the input voltage, a regulating circuit output voltage regulated based on a first signal; and

a switched capacitor circuit coupled to the regulating circuit, the switched capacitor circuit being a multiple phase circuit having multiple paths associated with corresponding voltages out of phase with each other, the switched capacitor circuit comprising at least a first capacitor and a second capacitor and a plurality of switches configured to be switched substantially in accordance with a switching frequency to change between a first network state and a second network state to alternatively charge or discharge the first and second capacitors simultaneously and in an out of phase relationship with each other and such that an output voltage is provided to an output node of the switched capacitor circuit in both the first network state and the second network state;

wherein the plurality of switches is configured to be controlled by a controller such that:

the switching frequency varies in response to an output current of the power converter,

the switching frequency is switched from a first frequency to a second frequency greater than the first frequency when the output current reaches a first threshold, and

the switching frequency is switched from the second frequency to a third frequency greater than the second frequency when the output current reaches a second threshold greater than the first threshold.

11. The power converter of claim 10, wherein the plurality of switches comprises:

a first set of switches associated with the first capacitor and configured to be switched based on a first phase voltage;

a second set of switches associated with the first capacitor and configured to be switched based on a second phase voltage out of phase with the first phase voltage;

a third set of switches associated with the second capacitor and configured to be switched based on the second phase voltage; and

a fourth set of switches associated with the second capacitor and configured to be switched based on the first phase voltage.

12. The power converter of claim 11, wherein the plurality of switches are configured to be switched substantially in accordance with the switching frequency to:

in the first network state, simultaneously charge the first capacitor and discharge the second capacitor; and

in the second network state, simultaneously discharge the first capacitor and charge the second capacitor.

13. The power converter of claim 11, wherein one switch of the first set of switches and one switch of the third set of switches are coupled to a voltage source.

14

14. The power converter of claim 10, wherein the power converter is configured to be controlled by the controller such that operation of the regulating circuit and the switched capacitor circuit are coordinated.

15. The power converter of claim 10, wherein the plurality of switches is configured to be controlled by the controller such that the switching frequency changes in discrete steps as the output current of the power converter is varied.

16. The power converter of claim 10, further comprising: the controller coupled to the regulating circuit and the switched capacitor circuit, wherein the controller is configured to generate the first signal and configured to generate one or more second signals to adjust the switching frequency.

17. The power converter of claim 16, wherein the controller is configured to provide one or more control signals to the regulating circuit and to the switched capacitor circuit and configured to coordinate operation of the regulating circuit and the switched capacitor circuit based on the one or more control signals.

18. The power converter of claim 16, wherein the controller is further configured to compare the regulating circuit output voltage with a trigger voltage to trigger an initiation of a dead-time interval, wherein the plurality of switches are configured to be switched based, at least in part, on the dead-time interval, and wherein the trigger voltage is adjustable on the fly.

19. The power converter of claim 10, wherein the power converter is configured to be controlled by the controller such that the first signal is generated in response to one or more voltage signals associated with the regulating circuit, and wherein the one or more voltage signals comprise a reference voltage, an output voltage, the regulating circuit output voltage, an input voltage, or any combination thereof.

20. The power converter of claim 10, wherein the power converter is configured to provide power to a load, and wherein the power converter is configured to be controlled by the controller such that operation of the switched capacitor circuit and the regulating circuit are coordinated, at least in part, to facilitate power consumption by the load.

21. The power converter of claim 10, wherein a first time period of the first network state and a second time period of the second network state in one cycle vary in response to the output current.

22. The power converter of claim 10, wherein the switches of the switched capacitor circuit comprising a plurality of first switches configured to be in a closed state in the first network state and a plurality of second switches configured to be in a closed state in the second network state, and wherein the first switches and the second switches are configured to be in an open state during a dead-time interval between the first network state and the second network state.

23. An integrated circuit of a switched capacitor circuit, the switched capacitor circuit being a multiple phase circuit having multiple paths associated with corresponding voltages out of phase with each other, the switched capacitor circuit having at least a first capacitor and a second capacitor and the switched capacitor circuit being coupled to a regulating circuit configured to provide, in response to an input voltage, a regulating circuit output voltage regulated based on a first signal, the integrated circuit comprising:

a plurality of switches configured to be switched substantially in accordance with a switching frequency to change between a first network state and a second network state to alternatively charge or discharge the first and second capacitors simultaneously and in an out of phase relationship with each other and such that an

15

output voltage is provided to an output node of the switched capacitor circuit in both the first network state and the second network state, wherein the plurality of switches are configured to be coupled to the first capacitor and the second capacitor, wherein the plurality of switches is configured to be controlled by a controller such that:

- the switching frequency varies in response to an output current of the integrated circuit;
- the switching frequency is switched from a first frequency to a second frequency greater than the first frequency when the output current reaches a first threshold; and
- the switching frequency is switched from the second frequency to a third frequency greater than the second frequency when the output current reaches a second threshold greater than the first threshold.

24. The integrated circuit of claim 23, further comprising the controller, wherein the controller is configured to control the plurality of switches such that the switching frequency changes in discrete steps as the output current is varied.

25. The integrated circuit of claim 23, wherein the plurality of switches comprises a plurality of first switches configured to be closed in the first network state and a plurality of second switches configured to be closed in the second network state, and wherein the first switches and the second switches are configured to be open during a dead-time interval between the first network state and the second network state.

26. An apparatus comprising the integrated circuit of claim 23, further comprising the switched capacitor circuit and the controller, wherein the controller is configured to

16

control the integrated circuit such that operation of the regulating circuit and the switched capacitor circuit are coordinated based on one or more control signals.

27. The apparatus of claim 26, wherein the controller is coupled to the regulating circuit and the switched capacitor circuit, and wherein the integrated circuit is configured to be controlled by the controller such that the first signal is generated by the controller and one or more second signals are generated by the controller to adjust the switching frequency.

28. The apparatus of claim 27, wherein the controller is configured to compare the regulating circuit output voltage with a trigger voltage to trigger an initiation of a dead-time interval, wherein the plurality of switches are configured to be switched based, at least in part, on the dead-time interval, and wherein the trigger voltage is adjustable on the fly.

29. The apparatus of claim 26, wherein the integrated circuit is configured to be controlled by the controller such that the first signal is generated in response to one or more voltage signals associated with the regulating circuit, and wherein the one or more voltage signals comprise a reference voltage, an output voltage, the regulating circuit output voltage, an input voltage, or any combination thereof.

30. An apparatus comprising the integrated circuit of claim 23, wherein the integrated circuit is configured to provide power to a load, and wherein the integrated circuit is configured to be controlled by the controller such that operation of the switched capacitor circuit and the regulating circuit are coordinated, at least in part, to facilitate power consumption by the load.

* * * * *