



US007721375B2

(12) **United States Patent**
Harr

(10) **Patent No.:** **US 7,721,375 B2**
(45) **Date of Patent:** **May 25, 2010**

(54) **DRAINAGE STRUCTURE CLEANING TOOL**

(75) Inventor: **Robert E. Harr**, Pritchett, CO (US)

(73) Assignee: **Harr Technologies, LLC**, Mosca, CO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/906,922**

(22) Filed: **Oct. 4, 2007**

(65) **Prior Publication Data**

US 2008/0028566 A1 Feb. 7, 2008

Related U.S. Application Data

(63) Continuation of application No. 11/375,886, filed on Mar. 15, 2006, now abandoned, which is a continuation-in-part of application No. 10/857,411, filed on May 27, 2004, now abandoned.

(60) Provisional application No. 60/476,568, filed on Jun. 6, 2003, provisional application No. 60/476,937, filed on Jun. 9, 2003, provisional application No. 60/492,422, filed on Aug. 4, 2003.

(51) **Int. Cl.**

B08B 9/02 (2006.01)

E02F 3/96 (2006.01)

E02F 3/76 (2006.01)

(52) **U.S. Cl.** **15/104.31**; 37/403; 37/407; 37/411; 37/444; 37/903; 172/684.5; 172/765

(58) **Field of Classification Search** 15/104.09, 15/104.095, 104.16, 104.05, 104.31, 104.32; 37/234, 341, 379, 443, 264, 403, 407, 444, 37/398, 465, 901, 903, 908, 411; 134/6, 134/166 R, 166 C, 22.1, 22.12; 172/811, 172/821, 825, 666, 684.5, 765, 771

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

293,261	A *	2/1884	Matcham	428/581
795,971	A *	8/1905	Hanaford	15/104.31
1,344,249	A *	6/1920	Stewart	15/104.31
1,599,307	A *	9/1926	Erwin	15/104.16
2,402,314	A *	6/1946	Crane	15/104.31
2,634,517	A *	4/1953	Zink	37/441
3,319,367	A *	5/1967	Lewis	37/444
3,916,471	A *	11/1975	Maze	15/104.31
6,000,152	A *	12/1999	Tate	37/405

* cited by examiner


Primary Examiner—Gary K Graham

(74) *Attorney, Agent, or Firm*—Phillip G. Meyers

(57) **ABSTRACT**

A tool for cleaning a drainage structure comprises a rod having a center longitudinal axis, a barrel housing having a proximal opening and a distal opening, the barrel housing having a center longitudinal axis and coupled coaxially to the rod, the barrel housing having an outside dimension that can be accommodated within the drainage structure, the distal opening of the barrel housing having a sinusoidal tearing contour. The tool further comprises a plurality of cutting implements radially coupled to and between the rod and the barrel housing, the cutting implements having a distal cutting edge and being angularly oriented to facilitate sweeping debris in a selected direction, and the barrel housing and cutting implements operable to rotate about the center longitudinal axis of the rod to dislodge and loosen debris inside the drainage structure.

12 Claims, 17 Drawing Sheets






Fig. 1a




Fig. 1b




Fig. 1c




Fig. 2a

Fig. 2b




Fig. 3a




Fig. 3b




Fig. 3c




Fig. 4




Fig. 5




Fig. 6b

Fig. 6a




Fig. 7




Fig. 6c




Fig. 8a




Fig. 8b




Fig. 9







Fig. 10








Fig. 12a




Fig. 12b




Fig. 12c




Fig. 13a




Fig. 13b




Fig. 14

DRAINAGE STRUCTURE CLEANING TOOL

This application is a continuation of U.S. Ser. No. 11/375, 886, filed Mar. 15, 2006, now abandoned, which is a continuation-in-part of U.S. Non-Provisional patent application Ser. No. 10/857,411, filed on May 27, 2004, now abandoned, and further claims the benefit of U.S. Provisional Patent Application Ser. No. 60/476,568, filed Jun. 6, 2003, U.S. Provisional Patent Application Ser. No. 60/476,937, filed Jun. 9, 2003, and U.S. Provisional Patent Application Ser. No. 60/492,422, filed Aug. 4, 2003, all of which are incorporated herein by reference.

BACKGROUND

Culverts, pipes, ditches, and other drainage structures are in wide use for such reasons as preventing soil erosion and controlling runoff. Drainage structures may be installed under roadways and railroads to prevent flooding or to prevent water damage to the surrounding area. In other locations, drainage structures may be used to prevent alteration of the landscape by erosion, or shifting of the soil, for example. In some areas, controlling runoff from snowmelt is another issue that may be addressed, in part, by the use of drainage structures.

In some cases, a drainage structure may lose its function because it is clogged with debris. Drainage structures may become obstructed by soil, rocks, sand, intrusion of plant roots, snow, ice, or other debris. The location of some drainage structures may make them particularly susceptible to blockage. One way to address these problems is to place a covering or grating over the openings of the drainage structure. However, these coverings may require extensive and frequent cleaning and may still allow smaller objects such as sand, silt, and gravel to enter the drainage structure. Additionally, coverings and gratings may not prevent plant roots from clogging the drainage structure. Drainage structures can be removed and replaced periodically but this often involves disturbing existing roadways and other structures. The resultant disruption to roadway or railroad traffic is costly and causes great inconvenience to travelers.

BRIEF DESCRIPTION OF THE DRAWINGS

Aspects of the present disclosure are best understood from the following detailed description when read with the accompanying figures. It is emphasized that, in accordance with the standard practice in the industry, various features may not be drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.

FIG. 1a is a cutaway view of an embodiment of a drainage structure cleaning tool.

FIG. 1b is an end view of an embodiment of a the drainage structure cleaning tool of FIG. 1a.

FIG. 1c is a side view, partly in section, of the culvert cleaning tool of FIG. 1a.

FIG. 2a is a cutaway view of an embodiment of another drainage structure cleaning tool.

FIG. 2b is an end view of an embodiment of the drainage structure cleaning tool of FIG. 2a.

FIG. 3a is a perspective view of an embodiment of another drainage structure cleaning tool.

FIG. 3b is a side view of an embodiment of the drainage structure cleaning tool of FIG. 3a.

FIG. 3c is a side view of an embodiment of the drainage structure cleaning tool of FIG. 3a with alternate cutting implement placement.

FIG. 4 is a perspective view of an embodiment of another drainage structure cleaning tool.

FIG. 5 is a perspective view of an embodiment of another drainage structure cleaning tool.

FIG. 6a is a side view of an embodiment of a drainage structure cleaning brush.

FIG. 6b is an end view of an embodiment of the drainage structure cleaning brush of FIG. 6a.

FIG. 6c is a partially disassembled view of an embodiment of the drainage structure cleaning brush of FIG. 6a.

FIG. 7 is a top view of an embodiment of a brush section.

FIG. 8a is a transparent view of an embodiment of another drainage structure cleaning brush.

FIG. 8b is an end view of an embodiment of the drainage structure cleaning brush of FIG. 8a.

FIG. 9 is a view of one possible environment in drainage structure cleaning tools of the present disclosure may operate.

FIG. 10 is a flowchart illustrating a method for cleaning a drainage structure.

FIG. 11a is a perspective view of another embodiment of a drainage structure cleaning tool.

FIG. 11b is an end view of another embodiment of the drainage structure cleaning tool of FIG. 11a.

FIG. 11c is another perspective view of the drainage structure cleaning tool of FIG. 11a.

FIG. 12a is a perspective view of another embodiment of a drainage structure cleaning tool.

FIG. 12b is a top plan view of the drainage structure cleaning tool of FIG. 12a.

FIG. 12c is a side view of the drainage structure cleaning tool of FIG. 12a.

FIG. 13a is a perspective view of another embodiment of a drainage structure cleaning tool.

FIG. 13b is a top plan view of the drainage structure cleaning tool of FIG. 13a.

FIG. 14 is a flowchart illustrating a method for cleaning and post-clean preparation of a drainage structure.

DETAILED DESCRIPTION

It is to be understood that the following disclosure provides many different embodiments, or examples, for implementing different features of various embodiments. Specific examples of components and arrangements are described below to simplify the present disclosure. These are merely examples and are not intended to be limiting. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed. Moreover, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed interposing the first and second features, such that the first and second features may not be in direct contact.

Referring to FIGS. 1a-b, a drainage cleaning tool 100 comprises a drill rod 101 having a proximal end 105 and a distal end 107 and is couple to a substantially cylindrical housing 108 at its distal end 107. The drill rod 101 may have a length that is compatible for cleaning the length of a drainage structure to be cleaned. In one embodiment, the rod 101 may range between about 5 feet and 10 feet length and ranges

from about 2 inches to about 2.5 inches in diameter. The rod **101** may be a commercially available drill rod section or may be custom made depending upon the needs of the user. The rod **101** may also be a commercially available pipe section or may be made from solid stock of steel, aluminum, or other metals or other suitable alloys thereof. In some applications plastics, polymers, fiberglass, or carbon fibers may also be used. The rod **101** comprises a coupler **102** at its proximal end **105** for coupling with an extension rod, a drilling rig or machine, or other available device, which is capable of performing horizontal or directional drilling. The coupler **102** may comprise a standard tapered threaded joint or some other type of coupling suitable for releasably attaching the rod **101** to an extension rod or to the drilling device. The coupling **102** may be integral with the rod **101** or attached as a separate component, by welding for example, and may be composed of similar materials as the rod **101**. The rod **101** and the coupling **102** may have a fluid-conducting channel **103** defined therein to provide a means for introducing pressurized water, gases or other solutions into the drainage structure. One or more openings, nozzles or sprayers **104** in fluid communication with the channel **103** are formed in the distal end of the rod **101** to direct the pressurized fluids to the debris blocking the drainage structure.

The longitudinal central axis **109** of the drill rod **101** preferably coincides with the central longitudinal axis of the housing **108**. The housing **108** may be substantially matched in diameter to the interior of the drainage structure being cleaned. For example, a cylindrical housing **108** may be chosen to approximately match the circular cross-section of certain drainage structures thus allowing a thorough cleaning in one pass. In some instances, however, with a large drainage structure, the housing **108** may be chosen to be smaller than the interior of the drainage structure to allow only portion of the drainage structure to be cleaned with each pass. In one embodiment, the diameter of the housing **108** may range from about 31 inches to about 48 inches and the length from about 14 inches to about 16 inches. The housing **108** may be made from a section of pipe of the appropriate diameter or may be custom made and may be composed of steel, iron, aluminum, or alloys thereof. If needed the housing **108** may also be made from plastic, polymers, or carbon fiber, for example.

The housing **108** may be coupled to the rod **101** by one or more supports **106**. The supports **106** may extend radially from the rod **101** to the housing **108**. Varying numbers of supports **106** may be used depending upon the application and needs of the user. The supports **106** may span the length of the tubular housing **108** but may also be shorter or longer. The supports **106** may be composed of similar or different materials than the housing **108** and rod **101**. The supports may be coupled to the rod **101** and housing **108** by welds or by other means. As best seen in FIG. **1b**, the housing **108** is secured to the rod **101** by two supports **106** spaced approximately 180.degree. apart from one another. Other configurations varying in position and number of supports are contemplated.

A plurality of cutting implements **110** are coupled to the inner surface of the housing **108**. The cutting implements **110** may be bolted or welded to the housing **108**, or secured by some other means. The tubular housing **108** may serve as an anchor point and partial covering for the cutting implements **110**. In this way, the cutting implements **108** are kept safely away from the walls of the drainage structure or pipe as well as any liner that may be in place. The housing **108** may also serve to cover and protect nozzles **104** and to keep them from becoming stopped up or clogged. The cutting implements **110** may remain within the housing **108** or extend beyond the

distal end of the housing **108** as shown in FIG. **1a**. The cutting implements **110** coupled to the inner surface of the housing **108** rotate as the housing **108** rotates. The cutting implements **110** may also be coupled to the rod **101** and rotate with the rod **101** while the housing **108** remains stationary. For example as shown in FIG. **1c**, the cutting implements **110** are coupled to the drill rod **102** by radial supports **116**. The cutting implements **110** may be paddles designed to sweep debris in a particular direction in coordination with the direction of rotation of the housing **108**. In other embodiments, the implements **110** may comprise a narrower or sharpened cutting edge **112**. The cutting edge **112** may also be serrated or equipped with teeth as the needs of the user dictate. The cutting implements or paddles **110** may have cutting edges **112** pointing inwardly toward the drill rod **101**.

The cutting implements **110** may be constructed of similar or different material than the housing **108** and rod **101**. The cutting implements **110** may also comprise high carbon steel or another durable material. For example, the cutting edge **112** may be constructed of high strength material such as high carbon steel or other suitable materials. The shape and position of the cutting implements **110** may dictate whether debris is swept forward (e.g., out from the distal end **107**) or rearward, toward the proximal end of the rod, as the needs of the application dictate. The design of the cutting implements **110** may also be such that debris may be swept either forward or rearward depending upon the direction of rotation of the housing **108** if the coupler **102** is designed to enable rotation in either direction. In FIG. **1a**, the drainage structure cleaning tool **100** is shown with two cutting implements **110**, but more or fewer implements may be utilized in other embodiments.

The jets, nozzles, or sprayers **104** may be coupled to the distal end **107** of the rod **101** at various points. The positions as shown in FIG. **1a** include a plurality of nozzles **104** within the housing **108** pointing radially outward from the rod **101** and one nozzle **104** point axially away from the distal end **107** of the rod **101**. This configuration illustrates one possible arrangement of the nozzles **104** but other configurations are contemplated. Similarly, other embodiments may have more or fewer nozzles **104**, or none at all. The nozzles **104** may be configured to provide a high pressure fluid stream in a desired direction. The nozzles **104** may be attached to the rod **101** by gluing, welding, or other means, and may be composed of similar or different materials than the rod **101**. The nozzles **104** may also be configured to provide a specific spray pattern such as a narrow stream or a wide angle spray. The nozzles **104** may be configured to spray only in a desired direction, for example, into the housing **108**, away from the housing **108**, or in some other direction from the rod **101**, which may increase the debris removal efficiency of the cleaning tool **100**.

In operation, the drainage structure cleaning tool **100** may be used to clean a drainage structure, drainage structure pipe, drainage ditch, or other elongated and confined area that has become clogged with debris. The cleaning tool **100** (FIG. **1a**) may be attached to a horizontal drilling device (not shown) by coupler **102** and, optionally, one or more extension rods. If the tool **100** is equipped with nozzles **104**, a high pressure supply of cleaning fluid may be attached to the rod **101**. A water tank with a pump may be used as the water supply. In some cases, the directional drilling machine may supply water to the nozzles **104** by pressurizing the water inside the rod **101** as previously described. The water nozzles may be checked for proper function and to ensure there is no blockage.

The cleaning tool **100** having been selected for size and for direction of debris removal may be inserted into the drainage structure. The drilling machine rotates the tool **100** within the drainage structure while injecting the pressurized water. The

5

cutting implements **110** rotate with the housing **108** or rod **101** in a predetermined direction. In certain implementations where the coupler **102** is a threaded coupling, the housing **108** may be rotated clockwise to prevent the threaded coupling from loosening. Debris that is cut or dislodged will be deflected in the appropriate direction by cutting implements **110**. The process may be repeated such that the device **100** is worked within the drainage structure in a “back and forth” motion until the drainage structure has been sufficiently cleaned. The nozzles **104** may be activated to assist with loosening of the debris and with debris removal by providing lubrication and pressurized force thereon. In some instances, the rod **101** may not provide sufficient length to clean the entire drainage structure. In such case, extension joints or tubing (not shown) that is compatible with the coupling **102** of the rod **101** and the drilling machine may be attached to coupling **102**.

FIG. **2a** is a cutaway view of another embodiment of a drainage structure cleaning tool **200** and FIG. **2b** provides an end view of the same. The drainage structure cleaning tool **200** comprises a drill rod **201** with a coupling **202** at a proximal end **205** thereof. The rod **201** may have a length that is compatible for cleaning the length of a drainage structure and may be joined to one or more extension rods (not shown) for elongating the reach of the tool. The rod **201** may range between about 5 feet and 10 feet length and ranges from about 2 inches to about 2.5 inches in diameter. The rod **201** may be a commercially available drill rod section or may be custom made depending upon the needs of the user. The rod **201** may also be a commercially available pipe section or may be made from solid stock of steel, aluminum, or other metals or other suitable alloys thereof. In some applications plastics, polymers, fiberglass, or carbon fibers may also be used. The rod **201** may comprise a channel **203** to allow pressurized fluids, such as water, gases, or other solutions to be conducted therethrough while the device **200** is in operation. The coupling **202** may be a tapered threaded joint or another type of coupling. The rod **201** and the coupling **202** may be integral or formed as separate pieces and attached together. The coupling **202** may also be hollow to allow the introduction of pressurized fluids into the rod **201**. One or more nozzles **204** provided at various locations on the rod **201** are in fluid communication with the channel **103** of the rod **201** to conduct pressurized fluids to aid in debris removal.

The rod **201** is coupled by radial supports **206** to a housing **208**. The rod **201** may be coupled coaxially along a center longitudinal axis **209** to the longitudinal axis of the housing **208**. The housing **208** may serve to cover and protect nozzles **204** and to keep them from becoming stopped up or clogged. The tubular housing **208** may be chosen to approximately match the circular cross-section of certain drainage structures thus allowing a thorough cleaning in one pass. In some instances, however, with a large drainage structure, the housing **208** may be chosen to be smaller than the interior of the drainage structure to allow only portion of the drainage structure to be cleaned with each pass. In one embodiment, the diameter of the housing **208** may range from about 31 inches to about 48 inches and the length from about 14 inches to about 16 inches. The housing **208** may be made from a section of pipe of the appropriate diameter or may be custom made and may be composed of steel, iron, aluminum, or alloys thereof. If needed, the housing **208** may also be made from plastic, polymers, or carbon fiber, for example.

The tool **200** also comprises a plurality of forward-pointing teeth **214** to provide cutting surfaces for clearing and cutting debris. A series of cutting teeth **214** is attached to the supports **206** to aid in loosening and removing debris. The teeth **214**

6

may be formed integrally with the supports **206** or they may be coupled thereto separately. The teeth **214** may be made of a durable material such iron, steel, aluminum, or alloys thereof. The teeth **214** may also be made from a high carbon steel, carbide, or diamond tipped for even greater durability. The teeth **214** and supports **206** may be constructed such that the teeth **214** protrude beyond the housing **208** at the distal end **207**. Thus, the teeth **214** are exposed to blockage in the drainage structure while the walls of the drainage structure remain protected by the housing **208**. The teeth **214** may attach at an angle to the supports **206** to improve cutting characteristics and to deflect debris in a desired direction as it is cut. There may be more or fewer teeth **214** than shown here as well as more or fewer supports **206**. The angle of the teeth **214** may be configured such that rotation in a specific direction by the housing **208** results in more efficient cutting and debris deflection. It is also contemplated that various characteristics of the embodiments disclosed herein may be incorporated or utilized together. For example, drainage structure cleaning tool **100** may comprise teeth **214** on its supports **106** as shown in FIGS. **1a-1b**.

In operation, the cleaning tool **200** may be coupled to a directional drilling machine and to a high pressure water source. The cleaning tool **200** may be inserted into the drainage structure into contact with debris to be removed. The drilling machine then rotates the cleaning tool **200** to commence clearing debris. The teeth **214** may cut through dirt, rocks, plants roots, animal nests, or other debris while moving forward and rotating. As before, this process may be repeated such that a back and forth motion is accomplished to ensure proper cutting of the debris and clearing of the drainage structure. One or more extension rods may be coupled to the drill rod **201** to extend the reach of the tool **200** into the drainage structure. The nozzles **214** may be activated to provide additional cleaning power or to assist in sweeping debris in a desired direction. Debris may be either pushed forward away from the device **200** or drawn towards the original opening depending upon the needs of the cleaning project. Additionally, the cleaning tool **200** may be used alternately with the cleaning tool **100** described above if needed.

FIGS. **3a-3c** presents various views of another embodiment of a drainage structure cleaning tool **300**. The cleaning tool **300** is a “pull bucket” and comprises a drill rod **301** with a proximal end **305**, a distal end **307** and a longitudinal axis **309** therethrough. The drill rod **301** may have a length that is compatible for cleaning the length of a drainage structure and may be joined to one or more extension rods (not shown) for elongating the reach of the tool. The rod **301** may range between about 5 feet and 10 feet length and may range from about 2 inches to about 2.5 inches in diameter. The rod **301** may be a commercially available drill rod section or may be custom made depending upon the needs of the user. The rod **301** may also be a commercially available pipe section or may be made from solid stock of steel, aluminum, or other metals or other suitable alloys thereof. In some applications plastics, polymers, fiberglass, or carbon fibers may also be used. The rod **301** may comprise a channel **303** to allow pressurized fluids, such as water, gases, or other solutions to be conducted therethrough while the device **300** is in operation. The coupling **302** may be a tapered threaded joint or another type of coupling. The rod **301** and the coupling **302** may be integral or formed as separate pieces and attached together. The coupling **302** may also be hollow to allow the introduction of pressurized fluids into the rod **301**.

Optionally, the drill rod **301** may comprise one or more nozzles in fluid communication with the fluid-conducting

channel **303** in the rod **301**. The nozzles **304** may direct pressurized fluids into the drainage structure to aid in debris removal.

The drill rod **301** is coupled to a c-shaped scoop or bucket **310** defined by an end portion **320**, sidewalls **325** with a plurality of catches **326**, and a rearward rim **340**. The sidewalls **325** of the bucket **301** do not meet and therefore define a side opening **312**. Further, the bucket **301** defines a rearward opening **313** opposing the end portion **320**. The end portion **320** and walls floor **325** may be made from iron, steel, or other materials. The end portion **320** and side walls **325** may also be made from other materials such as plastics or polymers if desired. The rod **301** may attach directly to the end portion **320** may pass therethrough to allow placement of an additional nozzle **304**, for example. The end portion **320** may include a substantially flat plate having an appropriate shape for the bucket **310**. The end portion **320** and/or sidewalls **325** may one or more pieces welded or otherwise joined together. In other embodiments, the rod **301** may be coupled to the bucket **310** at a different location, such as along the sidewall **325** opposite the bucket opening **312**, for example.

A support **335** may be coupled across the bucket opening **312** opposite the end portion **320** to increase the structural integrity and load capacity of the cleaning tool **300**. The support **335** may attach, by welding, for example, to the side walls **325** and pass over or under the rod **301**. The support **335** may also be secured to the rod **301** such as by welding. In other embodiments, the cleaning tool **300** may comprise different or additional supports than the support **335** as shown.

In particular, referring to FIG. *3b*, the bucket **310** may comprise sidewalls **325** that form an arc in cross-section with the lateral opening **312** formed by a chord **314** connecting the circumference of the bucket cross-section. The distal end of the bucket **310** is covered by the end portion **320** and the proximal end of the bucket **313** defines a rearward opening **313**. In one embodiment, the diameter of the bucket cross-section may range from about 14 inches to 17 inches and the length from about 20 inches to 25 inches. The sidewalls **325** may be formed from a large pipe section or may be custom made in the shape desired. The sidewalls **325** may be formed integrally or separately and then assembled, by welding, for example. There may also be a series of catches or ribs **326** along the sidewalls **325** which may serve to prevent debris captured in the bucket from sliding out easily. The catches **326** may be made from iron, steel, or another suitable material.

As more clearly seen in FIG. *3c*, the end portion **320** of the bucket **310** may have a curved profile. The curved forward profile of the bucket **310** may be advantageous for facilitating the advancement of the tool **300** into the drainage structure. It may also be seen that in this embodiment the rod **301** extends through the end portion **320**. The floor **325** of the bucket **310** is shown in this embodiment as being substantially parallel to the rod **301**. That is, the central axis **309** of the drill rod **301** is parallel to an axis **351** of the floor **325** of the bucket **310**. However, the cleaning tool **300** may also be assembled to provide a tilting of the bucket floor **325** relative to the rod axis **309** by a predetermined angle .alpha.. In this way, the rearward edge **340** of the bucket **310** is presented at an angle against the walls of the drainage structure to enhance the ability of the tool **300** to remove debris. The angle .alpha. may vary depending on the needs of the cleaning project.

FIG. *4* is a perspective view of another embodiment of a drainage structure cleaning tool **400**. Drainage structure cleaning tool **400** is a "push bucket" that is operable to push debris encountered in the drainage structure forward toward the distal end of the drainage structure. Cleaning tool **400**

comprises a bucket **410** with a forward opening **411** and a side opening **412** coupled to drill rod **401**. The push bucket **400** may comprise the same features as the pull bucket **300** described above. The floor and sides **425** of the tool **400** may also be tilted relative to the central axis **409** to increase cleaning efficiency.

FIG. *5* is a perspective view of another embodiment of a drainage structure cleaning tool **500**. The tool **500** comprises a bucket **510** with a generally rectilinear shape. The bucket **510** comprises a substantially flat plate having an appropriate shape which a drill rod **501** passes, a substantially flat floor **525**, and substantially flat sides **572**, **529**. The end portion **520**, floor **525**, and sides **527**, **529** may be formed integrally or as separate pieces joined together, by welding, for example. In one embodiment, the rod **501** may be coupled to the bucket **510** on the floor **525** or in a different location. The flat floor **525** provides a flat scooping or scraping edge **540**. The flat floor **540** and flat sides **527**, **529** may join at right angles and thus define a substantially rectilinear-shaped scoop. The floor **525** of the tool **500** may be parallel to the central axis **509**. However, in some embodiments, the floor **525** may be angled relative to the central axis **509** to provide for more efficient gathering of debris when the device **500** is pushed within a drainage structure. Supports, such as support **530** may also be provided to increase load capacity or improve stability of the tool **500**, for example. In another embodiment, the open end of the scoop will face toward the coupling **502**, so as to allow the scoop to operate by being drawn or pulled rather than pushed.

In operation, the scoop or bucket-type cleaning tools **300**, **400**, **500** may be used to clean a drainage structure, drainage structure pipe, drainage ditch, or another elongated and confined space that has become clogged with debris. The tools **300**, **400**, **500** may be used to remove rocks or other large debris as well as debris that may be very dense or heavy, or is otherwise more effectively removed with a scooping tool than a rotating tool, such as tool **100**. A tool (**300**, **400**, **500**) may be chosen based upon whether it is appropriate to push the debris out of the distal opening or draw it back out of the proximal opening of the drainage structure. Environmental concerns and the elevation and siting of the drainage structure openings may be determinative factors. The interior shape and dimensions of the drainage structure may also be considered. For example, in a drainage structure with a flat bottom, the rectilinear tool **500** may be used, whereas a round drainage structure may be most effectively cleaned with one of the cylindrical tools **300** and **400**. As before, the size of the tool **300**, **400**, **500** may be chosen to match the clearance in and around the drainage structure or based on other user preferences.

The chosen tool (**300**, **400**, or **500**) may be attached to a directional drilling machine and extension pieces or tubing may be used if needed. If water nozzles (**304**, **404**, or **504**, respectively) are provided or needed, a high pressure water supply may then be attached to the tool **300**, **400**, **500** and the water nozzles tested for blockage and proper operation. The tool **300**, **400**, **500** may then be inserted into the drainage structure to a desired location. The orientation of the tool **300**, **400**, **500** relative to the interior of the drainage structure, or relative to the debris to be removed, may be adjusted by partial rotations of the tool **300**, **400**, **500** by the drilling machine. As the tool **300**, **400**, **500** is worked into the drainage structure, partial rotations may also be used to clear obstacles or structures within the drainage structure that may not be removable.

When the tool **300**, **400**, **500** has been inserted to the proper location, the floor **325**, **525** of the tool **300**, **400**, **500** may be rotated towards the debris and the tool **300**, **400**, **500** may be

positioned to scoop or scrape the debris in a desired direction. If the tool **300, 400, 500** becomes overly full, it may be lifted from the debris and removed from the drainage structure. The tool **300, 400, 500** may then be rotated to an “upside down” position to allow the debris to fall out or be removed. The tool **300, 400, 500** may then be reinserted and the process repeated until the drainage structure has been sufficiently cleaned. Water jets **304, 404, 504** may be used to assist in debris removal, for example by softening debris, or by sweeping it in a desired direction. In some cases, the debris in the drainage structure may need to be churned or loosened to allow ease of removal. The bucket or scooping tool **300, 400, 500** may be placed on or near the debris and rotated by the drilling machine to effect the desired mixing or churning action. Water jets **304, 404, 504** may be used here also if needed to increase the effectiveness of the operation. The bucket or scooping tools **300, 400, 500** may also be used in conjunction with the rotating tools **100, 200**. One or more extension rods may be used with the tools **300, 400, and 500** to extend the reach of the tool inside the drainage structure.

FIG. **6a** is a side view of a drainage structure cleaning brush tool, or finishing brush tool **600**. FIG. **6b** is an end view of the brush tool **600**. The brush tool **600** has a drill rod **601** with a proximal end **603** and a distal end **605**. The proximal end **603** comprises a coupling **602**, which may be a tapered threaded coupling or another suitable coupling. The rod **601** may comprise a fluid conducting channel and one or more fluid nozzles **604** at or near its distal end **605**. The brush tool **600** comprises a brush assembly **611**. The brush assembly **611** may comprise a plurality of brush segments **602** arranged concentrically about the rod **601**. In one embodiment, brush segments **602** may range from about 30 inches to about 36 inches in diameter and may be about 2 inches in length. The brush segments **602** are sandwiched together by a forward end plate **606** and a rearward end plate **607**. One or more drive rails **608** may be mounted to the rearward end plate **607** and are operable to pass through one or more corresponding openings in the forward end plate, as seen in FIG. **6b**.

The forward end plate **606** may comprise steel, iron, aluminum, or another suitable material. In FIG. **6b**, it may be seen that the drive rails **608** may be rectilinear in shape, but they may be cylindrical or other shapes. Although, two drive rails **608** are shown equidistant from the rod **601** and offset 180.degree. from one another, there may be more or fewer drive rails and their positions may differ from those shown. Similarly, there are two sets of threaded bars **610** and fasteners **612**. The threaded bars **610** may be made from standard bolts if the desired length of bolt is available, or the threaded bars **610** may be made from commercially available all-thread, for example. The fasteners **612** may be threaded nuts or other devices for holding the brush segments together. In another embodiment, the fasteners **612** may be cotter pins for use with a hole (not shown) in the bolt **610**, for example. In yet another embodiment, the threaded bars **610** may not be necessary if, for example, the end plate **606** is welded directly to the mounting bars **608**.

FIG. **6c** is a partially disassembled view of the drainage structure cleaning brush **600** of FIG. **6a**. A portion of the rod **601** is shown with a nozzle **604**. The rearward end plate **607** is shown in position and may be attached to the rod **601**, for example, by welding. The end plate **607** may be substantially similar in composition and dimension as forward end plate **606**. Drive rails **608** and threaded bars **610** may be coupled to the end plate **607**, by welding, for example.

FIG. **7** is a top view of a brush segment **602**. Bristles **702** may be coupled to a mounting ring **704**. The mounting ring **704** may have a series of fingers **708** spaced around the inner

circumference of the ring **704** so as to engage the mounting bars **608**, and threaded bars **610** (FIGS. **6a-c**). The bristles **702** may be made of nylon, or some other suitable synthetic or natural material. The mounting ring **704** may be made of plastic, a metal, or another suitable material. The fingers **708** may likewise be composed of a plastic, metal, or other suitable material. The diameter of the bristled portion **702** of the brush segments **602** may range from about 18 inches to about 36 inches, while the diameter of the inner ring may range from about 8 inches to about 12 inches. The thickness of the brush segment **602** may be about one inch. In one embodiment of the device **600** (FIGS. **6a-c**), the drive rails **608** and threaded bars **610** are mounted to the end plate **607** in such a manner as to provide the proper spacing and radius that commercially available street sweeper sections may be used as the brush segments **602**.

FIG. **8a** is a transparent view of another embodiment of a drainage structure cleaning brush **800**. The brush **800** is built onto a rod **801**, which may have a length that is compatible for cleaning the length of a drainage structure and may be joined to one or more extension rods (not shown) for elongating the reach of the tool. The rod **801** may range between about 5 feet and 10 feet in length and ranges from about 2 inches to about 2.5 inches in diameter. The rod **801** may be a commercially available drill rod section or may be custom made depending upon the needs of the user. The rod **801** may also be a commercially available pipe section or may be made from solid stock of steel, aluminum, or other metals or other suitable alloys thereof. In some applications plastics, polymers, fiberglass, or carbon fibers may also be used. The rod **801** may comprise a channel **803** to allow pressurized fluids, such as water, gases, or other solutions to be conducted therethrough while the device **200** is in operation. In this embodiment, a multidirectional nozzle **805** is shown but other nozzles (e.g. **104** or FIG. **1**) may be used and may be interchangeable with nozzle **105**. The nozzle may be in fluid communication with the channel **803** in the rod **801**.

Drainage structure cleaning tool **800** may also comprise end plates **804** and **806** to hold the brush segments together. However, a rod brace **802** may be utilized as a base for mounting drive rails, mounting bars, or splines **808**. The rod brace **802** may be made of a pipe section of constructed from suitable materials such as a metal or plastic. The length and diameter of the rod brace may be selected to match the interior of the brush segments **602** described above. The drive rails **808** may be attached directly to the rod brace **608**, by welding, or bolting for example. As shown, the endplates **804, 806** in combination with the rod brace **800** may provide a solid substantially cylindrical surface, to which brush sections **602** may be mounted. The drive rails **808** may be arranged to as to interface with the fingers **708** of brush section **602** (FIG. **7**). The end plate **806** may be held in place by flange plate **804** which may be welded to the rod **801** for example. Captive nuts **830** on the flange plate **804** may be used for ease of assembly. Bolts **810** or other suitable fasteners may provide fastening on the opposite side. One or more washers may be used at various locations on the device **800**. For example, rubber washer **620** may be used to prevent leakage of mud, water, or debris into the interior of the rod brace **802** when the device **800** is assembled for use.

FIG. **8b** is an end view of the drainage structure cleaning brush **800** of FIG. **8a**. In this view, one possible configuration for the drive rails **808** can be seen but others are possible. As in previous embodiments, the drive rails may be positioned according to the design of the brush sections **802**, possibly allowing commercially available street sweeper brush sections to be used. One possible bolt pattern for bolts **810** can

also be seen here. The bolts **810** may be patterned to match the flange plate **831** (FIG. **8a**), but other configurations than shown here are possible. Multidirectional nozzle **805** is also shown here which, in this embodiment, attaches directly to the end of rod **801**. The multidirectional nozzle may allow for multiple high pressure fluid streams from a single location on rod **801**.

In operation, the drainage structure cleaning brush **600** or **800** may be coupled to a piece of equipment such as a directional drill capable of drilling horizontally. The size of the brush used may be chosen to correspond the size of the drainage structure being cleaned. As before, extension rods may be added to the drill rod to increase the effective reach of the brush. The brush may also be attached to a high pressure water source (e.g., the drilling machine) so that the water nozzles **604**, **805** may be used to aid in the cleaning. The nozzles **604**, **805** may aid by sweeping the debris in a desired direction (e.g., away from the drilling machine, or towards it) or by softening hardened debris for easier sweeping. As described in greater detail below, the brushes **600**, **800** may be used as part of a cleaning process that may involve first using other tools that have been described herein.

FIG. **9** is a view of one possible environment **900** in which embodiments of the above-described tools may operate. A drainage structure **902** may be a drainage structure passing under a roadway **904**. The drainage structure **902** has a proximal end **903** and a distal end **905**. Depending on environmental and other factors, the proximal end **903** or the distal end **905** may be selected as the debris exit point from the drainage structure **902**. Preferably the drainage structure end having the lower elevation is chosen as the debris exit point in order to take advantage of the force of gravity, but this selection is not required. The debris **906** may partially or fully block the drainage structure **902**. As shown, the proximal end **903** of the drainage structure **902** is accessible to a directional drilling machine or rig **910**. Removal of grating or other safety implements (not shown) to expose the proximal opening of the drainage structure may be necessary, as well as excavation of the immediate area to allow proper access to the drainage structure **902**. In this example, the cleaning tool **400** (as in FIG. **4**) is shown attached to a drill rod of the drilling rig **910**. One or more extension rods **912** may be used here to increase the effective reach of the tool **400**. As stated previously, a high pressure water supply **914** may also be attached to the cleaning tool **400**, via the extension rods **912**, for example. The drilling rig **910** may manipulate the cleaning tool **400** in such a manner as to effect removal of the debris **906**. The drilling rig **910** may be able to supply movement to the cleaning tool **400** along several different axes as shown by arrows D, E, F, and G. Depending upon the tool attached to the rig **910**, the debris may be pushed or pulled from the proximal end of the drainage structure.

FIG. **10** is a flow chart of one embodiment of a method for cleaning a drainage structure. The appropriate tool may first be selected at step **1001**. The cleaning tools as previously described may be chosen depending upon the type of debris in the drainage structure, the size and location of the drainage structure, and environmental factors, for example. Once an appropriate tool has been chosen, an appropriate size may be selected at step **1002**. The size of the tool needed may depend upon the size of the drainage structure and whether a portion or all of the drainage structure is to be cleaned in each pass of the tool. Additionally the type of debris may impact the choice of the size of the tool. For example, very dense debris may lead to a selection of a smaller tool to reduce weight in the tool. A drainage structure with an immovable obstacle

inside may lead to the selection of a smaller size tool to enable adequate room to maneuver the tool inside the drainage structure.

One an appropriate tool and size has been selected, the tool may be connected to a drilling machine at step **1004**, such as a horizontal drilling rig. The connection of the tool to the drilling rig may also involve the use of extension joints as previously described. If water is to be used to assist in the cleaning at step **1006**, the water supply is connected at step **1008**. In some embodiments, the drilling rig may also serve as a high pressure pump or water supply. Clean water may be used in some embodiments but waste water, water from a local body of water, or another supply of a suitable liquid may also be used. At step **1010**, the tool may be inserted into the drainage structure and the cleaning action may commence. As previously described and depending upon the tool currently in use, drilling motions, sweeping motions, or scooping motions may be used to clear debris from the drainage structure. Additionally, it may be necessary for debris to be deposited only in one area as it is removed from the drainage structure. Environmental concerns, for example, may necessitate that removed debris is placed only at one end of the drainage structure and/or that the fluids used in loosening the debris not enter an existing natural body of water.

In some environments, the cleaning of a drainage structure may require the use of more than a single tool. For example, a scooping-type tool may be used, followed by a brush. In some embodiments, two different kinds of routing or rotating tools may be used followed by a brush tool. Some drainage structures may require the use of both scooping tool and routing tools followed by the brush tool and some cleanings may not require the brush at all. At step **1012**, a decision may be made as to whether an additional tool is needed. If so, the additional tool may be selected as described beginning at step **1001**.

The cleaning of some drainage structures may require additional, optional steps. For example, a liner may be inserted into the cleaned drainage structure at step **1014**. A liner may help to prevent degradation of the drainage structure itself, or may help to slow the subsequent buildup of new debris inside the drainage structure. In some environments, the debris may have to be removed from the cleaning site at step **1016**. This may be due to environmental concerns, or concerns with keeping the area free of loose debris, for example. If the area around the end of the drainage structure was excavated to allow proper access, it may be necessary to restore the landscape to its original condition at step **1018**. Any grills, coverings, or other safety implements may also be replaced at this step.

FIGS. **11a**, **11b**, and **11c** are various views of another embodiment of a drainage structure cleaning tool **1100**, also called a barrel cleaning tool. The tool **1100** comprises a drill rod **1102** having a proximal end **1104** and a distal end **1105**. At the proximal end **1104**, a coupler **1106**, such as a splined connection of the type made by Earth Tool Corporation of Wisconsin under the model designation SPLINE-LOCK, may be used to couple tool **1100** to one or more drill string rods and to a directional boring machine or another type of equipment operable to rotate and steer the tool and drill string. The drill rod **1102** defines therein a longitudinal fluid-conducting channel **1108** to direct pressurized fluids to a plurality of nozzles **1110** disposed about the drill rod **1102** proximate its distal end **1105**.

The tool **1100** further comprises a barrel housing **1112** coupled substantially coaxially to the drill rod **1102** at its distal end. The cross-sectional shape of the barrel housing **1112** may conform to the cross-sectional shape of the drain-

13

age structure to be cleaned. For example, a tool having a having a substantially circular cross-section may be used to clean and clear out a drainage structure with a circular cross-section. On the other hand, a tool having a having a substantially square or rectangular cross-section may be used to clean and clear out a drainage structure with a square or rectangular cross-section. The distal end of barrel housing 1112 is further shaped to define a plurality of integral ripping teeth 1114. The ripping teeth 1114 are shaped and contoured to define a sinusoidal profile with a plurality of peaks and valleys, where the peaks and valleys may be pointed or blunt in profile. The ripping teeth 1114 are operable to tear through and loosen vegetation, compacted soil and other obstructions inside the drainage structure.

At the distal end of the drill rod 1102, a plurality of cutting implements or paddles 1116 couple the barrel housing 1112 to the drill rod 1102. The cutting implements 1116 may be mounted onto the drill rod 1102 at an angle α from the longitudinal axis 1118 of the drill rod 1102. The angle α is preferably less than 90 degrees. This angled mounting of the cutting implements 1116 is best seen in FIG. 11c. The angle of attack of the cutting implements 1116 is designed to cut, loosen and sweep debris in the drainage structure in a general direction toward the proximal end of the drainage structure when rotation of the barrel housing 1112 and drill rod 1102 causes rotation of the cutting implements 1116 about the longitudinal axis of the drill rod. Referring to FIG. 11b, advanced (or distal) edges 1120 of the cutting implements 1116 are further equipped with a plurality of cutting teeth 1124. The cutting teeth 1124 may be attached to cutting implements 1116 and may have tips or inserts constructed of carbide, steel, polycrystalline diamond (PCD), and other suitable materials. The cutting teeth 1124 provides the cleaning tool 1100 added capability to cut through thick vegetation and compacted debris in the drainage structure. The cutting implements 1116 may have a L-shaped configuration where the angle δ , between the two legs of the cutting implement is greater than 90 degrees.

In operation, the drainage structure cleaning tool 1100 may be used to clean a culvert, pipe, drainage ditch, drainage structure, or another elongated and confined area that has become clogged with debris. The cleaning tool 1100 may be coupled or mounted to a horizontal drilling equipment by coupler 1106 and, optionally, one or more extension rods depending on the length of the drainage structure and the location of the blockage. If the cleaning tool 1100 is equipped with nozzles 1110, a high-pressure supply of cleaning fluid may be coupled to the drill rod 1102 to conduct the cleaning fluid in the channel 1108 to the nozzles. A storage tank equipped with a pump may be used as the cleaning fluid supply. The cleaning fluid may be water, steam, or another cleaning solution. The cleaning tool 1100 is selected for size and shape to suit the size and shape of the drainage structure to be cleaned. The drilling machine rotates the tool 1100 within the drainage structure while injecting the pressurized fluid that aids in further loosening the lodged debris. The cutting implements 1116 rotate with the barrel housing 1112 and the drill rod 1102 in a predetermined direction. Debris that is cut or dislodged are thus deflected and swept in the appropriate direction by cutting implements 1116. The process may be repeated such that the tool 1100 makes more than one pass within the drainage structure until most of the debris is sufficiently cleaned.

FIGS. 12a, 12b, and 12c are various views of an embodiment of another drainage structure cleaning tool 1200. Cleaning tool 1200 comprises a "pull bucket" 1201 coupled or mounted on a distal end of a drill rod 1206. The pull bucket

14

1201 has an overall substantially cylindrical shape with a proximal opening 1202, a side opening 1203 integral with the proximal opening 1202, and a distal closed end 1204. The closed distal end of the pull bucket 1201 preferably has an angled construction having an inclined angle β shown in FIG. 12c. The proximal opening 1202 of the pull bucket 1201 has a contoured profile, including a digging lip 1212. The digging lip 1212 may have a general profile having an inclined angle γ relative to the side wall of the pull bucket as shown in FIG. 12c. The digging lip 1212 presents an advanced proximal edge of the pull bucket 1201 that is operable to provide leverage while the pull bucket 1201 is being pulled toward the horizontal drilling machine used to operate the cleaning tool 1200 and further provide a digging profile that facilitates the removal and loosening of compacted debris and soil.

The drill rod 1206 defines therein a longitudinal fluid-conducting channel 1207 that is in fluid-communication with a plurality of nozzles 1222 disposed about the distal end of the drill rod 1206. A proximal end of the drill rod 1206 comprises a splined connection that enable the drill rod to be quickly coupled to one or more drill string rods or extensions. Further, the drill rod 1206 is preferably mounted to the pull bucket 1201 along the side opening 1203 of the pull bucket 1201. This mounting location enables the drill rod 1206 and the support plate 1220 to not interfere with the loading and filling of the pull bucket 1201. The support plate 1220 are mounted so that its flat surfaces are at an angle β relative to the longitudinal axis of the rod 1206 (best seen in FIG. 12c). The support plate 1220 may be used to mount the drill rod 1206 to the bucket and provide structural reinforcement. The support plate 1220 may define an opening 1230 therein for accommodating the drill rod 1206. Similarly, the distal closed end 1204 of the pull bucket 1201 may define another opening 1232 for accommodating the distal end of the drill rod. The drill rod 1206, the support plate 1220 and the pull bucket 1201 may be secured to one another by welding or another suitable method. The support plate opening 1230 and the closed distal end opening 1232 may be connected to the side opening of the bucket to facilitate tool assembly.

In operation, the pull bucket tool 1200 may be used when the proximal end of the drainage structure has been selected as the exit site of the debris. Generally, after a tool of the type shown in FIGS. 1a-2b and 11a-11c has been used to loosen the debris compacted and lodged in the drainage structure, the pull bucket tool 1200 may be subsequently used to move and evacuate the dislodged debris toward the proximal end of the drainage structure. The digging lip 1212 of the pull bucket 1201 enables a substantial amount of the debris to be loaded and transported out of the drainage structure. On the other hand, the slanted closed distal end 1204 of the pull bucket 1201 enables some of the debris in the pull bucket tool 1200 to be pushed and spill out of the distal end of the pull bucket as to avoid overloading the bucket. Furthermore, the pull bucket tool 1200 may be advantageously used to dig into the side walls of the drainage structure to further loosen the debris therein. The pull bucket tool 1200 may be pulled to dig, using the digging lip, load the bucket, and then rotated to unload the debris collected therein, and then pulled to dig and load the bucket, rotated to unload the debris, and so on. Once most of the debris inside a segment of the drainage structure has been loosened, the pull bucket can be used to load and pull the dislodged debris out of the drainage structure.

FIGS. 13a and 13b are two views of an embodiment of another drainage structure cleaning tool 1300. The cleaning tool 1300 comprises a "push bucket" 1302 with an overall substantially cylindrical shape. The push bucket 1302 com-

15

prises a proximal closed end **1304** and a distal open end **1306**. The distal open end **1306** is integrally connected to a side opening **1308** of the push bucket **1302**. The proximal opening **1306** is contoured to have a digging lip **1310**. The digging lip **1310** has an advanced edge ahead of the rest of the push bucket that facilitates digging under or into compacted soil and debris along the sides of the drainage structure. A plurality of catches **1312** are disposed along the digging lip **1310** on the inside wall of the push bucket **1302**.

The push bucket **1302** is coupled to or mounted onto a drill rod **1320**. The drill rod **1320** defines an inner longitudinal fluid-conducting channel **1322** that is in fluid-communication with a plurality of nozzles **1324** disposed at the distal end of the drill rod **1320** inside and/or outside the push bucket **1302**. Preferably, the drill rod **1320** is accommodated in an opening **1328** in the proximal closed end **1304** of the push bucket **1302** and is welded or otherwise securely attached to the push bucket **1302**. The site of the opening **1328** is preferably near the bottom of the bucket away from the side opening of the bucket. Two support flanges **1326** further affix the drill rod **1320** to the closed proximal end **1304** of the push bucket **1302**. Preferably the distal end of the drill rod **1320** terminates well before reaching the digging lip **1310** of the push bucket. Therefore, nearly the entire volume of the push bucket is available to load and convey dislodged and loosened debris from the drainage structure. The proximal end of the drill rod **1320** may comprise a coupler **1330** such as a splined connector operable to be connected to one or more extension rods.

In operation, the push bucket tool **1300** may be used when the distal end of the drainage structure has been selected as the exit site of the debris. Generally, after a tool of the type shown in FIGS. **1a-2b** and **11a-11c** has been used to loosen the debris compacted and lodged in the drainage structure, the push bucket tool **1300** may be subsequently used to move and evacuate the dislodged debris toward the distal end of the drainage structure. The digging lip **1310** of the push bucket **1302** enables a substantial amount of the debris to be loaded and transported out of the drainage structure. Furthermore, the push bucket tool **1300** may be advantageously used to dig into the side walls of the drainage structure to further loosen the debris therein. The push bucket tool **1300** may be pushed to dig, using the digging lip, load the bucket, and then rotated to unload the debris collected therein, then pushed to dig and load the bucket, then rotated to unload the debris, and so on. Once most of the debris inside a segment of the drainage structure has been loosened, the push bucket can be used to load and push the dislodged debris out of the drainage structure.

Although the pull bucket tool **1200** and the pull bucket tool **1300** described above are shown as having substantially cylindrical cross-sections, these tools may utilize buckets of other shapes appropriate for cleaning the drainage structure at hand. For example, a cubic-shaped bucket may be used to clean a square or rectangular-cross-sectioned drainage structure.

Any machinery that is operable to controllably rotate and advance the drainage cleaning tools may be used such as a horizontal directional drill manufactured by Vermeer Manufacturing Company of Pella, Iowa. Further, a sonde may be used to enable the detection and steering of the cleaning tools in the drainage structure. In addition, sonde may also be used to determine the angular orientation of the cleaning tool so that the cleaning tools such as the push and pull buckets may be manipulated to scoop and dump the debris.

FIG. **14** is a flowchart illustrating a method **1400** for cleaning and post-clean preparation of a drainage structure step **1402**, a cleaning tool such as the tool **1100** described above is

16

first used to make multiple passes through the drainage structure to tear through compacted debris. Pressurized fluids may be used to further assist in loosening the debris lodged in the drainage structure. In step **1404**, the push or pull bucket tools are used to scrape and otherwise remove debris from the sides of the drainage structure. In steps **1406** and **1408**, the bucket tool is used to scoop and otherwise load the dislodged debris into the bucket and then guided out of the drainage structure to dump the load outside the drainage structure in step **1410**. The bucket tool is steered and rotated to direct the digging lip of the bucket tool along the sides of the drainage structure to scrape off the compacted debris and then to rotate the bucket tool so that the debris load can be emptied from the bucket. Steps **1406-1410** may be performed multiple times to thoroughly clean the drainage structure.

After the drainage structure is thoroughly cleaned, a liner may be positioned in place. In steps **1412** and **1414**, the liner is eased into place inside the drainage structure by pulling and/or pushing the liner while rotating the liner to help guiding the liner in place. In step **1416**, grout is then injected into the annular space between the liner and drainage structure.

The foregoing has outlined features of several embodiments according to aspects of the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions and alterations herein without departing from the spirit and scope of the present disclosure.

What is claimed is:

1. A tool for cleaning a drainage structure, comprising:
 - a rod having a center longitudinal axis and a proximal end and a distal end, the rod having a coupling at its proximal end;
 - an elongated bucket coupled to the distal end of the rod and having a closed distal end, a proximal end opening, and a side opening adjacent to the proximal end opening;
 - a cross member spanning the side opening of the bucket perpendicularly to a longitudinal axis of the rod, which cross member defines an opening accommodating the rod therethrough;

wherein the rod further defines a fluid-conducting channel in communication with at least one nozzle opening which directs fluid into the bucket.

2. The tool of claim **1**, wherein the closed distal end of the bucket further defines an opening secured to a distal end portion of the rod.

3. The tool of claim **1**, wherein the bucket is substantially cylindrical.

4. The tool of claim **1**, further comprising at least one extension rod releasably coupled between the proximal end of the rod and a drilling machine.

5. The tool of claim **1**, wherein the rod is secured to the cross member so that it lies substantially proximately along the side opening of the bucket.

6. The tool of claim **1**, wherein the proximal end opening of the bucket has a protruding digging lip.

7. A tool for cleaning a drainage structure, comprising:

- a rod having a center longitudinal axis, a proximal end and a distal end, the rod having a coupling at its proximal end;

17

an elongated bucket coupled to the distal end of the rod and having a closed end and an open end, an end opening at the open end, a side opening adjacent to the end opening; and
 a cross member spanning the side opening of the bucket 5
 perpendicularly to the longitudinal axis of the rod, which cross member defines an opening accommodating the rod therethrough;
 wherein the rod further defines a fluid-conducting channel in communication with at least one nozzle opening which 10
 directs fluid into the bucket.

8. The tool of claim 7, wherein the side opening is continuous with the end opening.

9. The tool of claim 7, wherein the bucket has an inwardly curved bottom wall and a pair of opposed, inwardly curving 15
 side walls.

10. The tool of claim 7, wherein the rod has a longitudinal extending channel therein which is open at the proximal end of the rod, and a distal portion of the rod which extends lengthwise through the bucket has one or more radially 20
 directed nozzles in communication with the longitudinal extending channel, which nozzles direct fluid into the bucket.

18

11. The tool of claim 7, wherein the end opening of the bucket has a digging lip which protrudes in a lengthwise direction of the bucket at a lower edge of the end opening.

12. A tool for cleaning a drainage structure, comprising:
 a rod having a center longitudinal axis, a proximal end and a distal end, the rod having a coupling at its proximal end; and
 an elongated bucket coupled to the distal end of the rod and having a closed end and an open end, an end opening at the open end, a side opening adjacent to the end opening;
 a cross member spanning the side opening of the bucket perpendicularly to the longitudinal axis of the rod, which cross member defines an opening accommodating the rod therethrough; and
 at least one extension rod releasably coupled between the proximal end of the rod and a drilling machine, whereby rotation of the extension rod upon removal of the bucket from a culvert is effective to discharge contents of the bucket through the side opening of the bucket.

* * * * *