



US010118029B2

(12) **United States Patent**
Hamilton

(10) **Patent No.:** **US 10,118,029 B2**

(45) **Date of Patent:** ***Nov. 6, 2018**

(54) **DRILL ASSEMBLY FOR ACCESSING BONE**

(71) Applicant: **K-D Instruments, Inc.**, Leawood, KS (US)

(72) Inventor: **Dennison Hamilton**, Leawood, KS (US)

(73) Assignee: **K-D Instruments, Inc.**, Leawood, KS (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 328 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/948,603**

(22) Filed: **Nov. 23, 2015**

(65) **Prior Publication Data**

US 2016/0074652 A1 Mar. 17, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/230,534, filed on Mar. 31, 2014, now Pat. No. 9,192,759.

(51) **Int. Cl.**
A61N 1/05 (2006.01)
A61B 17/16 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC *A61N 1/0551* (2013.01); *A61B 17/1622* (2013.01); *A61B 17/1626* (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 17/1604; A61B 17/1622; A61B 17/1615; A61B 17/34; A61B 17/1757;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,463,401 B2 6/2013 Jones et al.
2006/0276867 A1 12/2006 Viswanathan
(Continued)

FOREIGN PATENT DOCUMENTS

WO 2013173360 A1 11/2013

OTHER PUBLICATIONS

European Patent Application 15772303.2 extended search report dated Jan. 31, 2018.


Primary Examiner — Richard Louis

(74) *Attorney, Agent, or Firm* — Erise IP, P.A.

(57) **ABSTRACT**

A system and method for implanting and stabilizing spinal cord stimulators in an epidural space of the spinal column of a patient to prevent or limit axial movement of the stimulators once implanted in the epidural space. The system includes a drill assembly, a guide wire assembly, and a guide wire receiver. The drill assembly includes a cannula, a drill for creating access points in the patient's spinal column for implanting the stimulators, and an incremental drill adjuster for drilling into the patient's lamina a pre-set, discrete distance. The guide wire assembly includes a hollowed guide wire sleeve, a guide wire housed within the sleeve, and a magnet disposed on a proximal end of the guide wire assembly. The guide wire receiver includes a scoop for receiving and catching the magnet to assist in feeding the stimulators through the epidural space.

21 Claims, 13 Drawing Sheets



- (51) **Int. Cl.**
A61M 25/09 (2006.01)
A61B 17/17 (2006.01)
A61B 17/34 (2006.01)
A61M 25/06 (2006.01)
- (52) **U.S. Cl.**
CPC *A61B 17/1671* (2013.01); *A61B 17/1697*
(2013.01); *A61B 17/1757* (2013.01); *A61B*
17/34 (2013.01); *A61M 25/09041* (2013.01);
A61B 17/1615 (2013.01); *A61B 17/3421*
(2013.01); *A61B 17/3468* (2013.01); *A61B*
17/3472 (2013.01); *A61B 2017/3458*
(2013.01); *A61M 25/0662* (2013.01); *A61M*
2025/09125 (2013.01)
- (58) **Field of Classification Search**
CPC *A61B 17/1697*; *A61B 17/1626*; *A61B*
17/1671; *A61B 17/3472*; *A61B*
2017/3458; *A61B 17/3468*; *A61B*
17/3421; *A61N 1/0551*; *A61M 25/09041*;
A61M 25/0662; *A61M 2025/09125*
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2009/0149857 A1* 6/2009 Culbert A61B 1/018
606/80
2014/0039481 A1 2/2014 Coe et al.

* cited by examiner




Fig. 1






Fig. 2








Fig. 8




Fig. 9




Fig. 10

Fig. 11





Fig. 12

Fig. 13






Fig. 16a

Fig. 16b

Fig. 16c




Fig. 16d





Fig. 16e






Fig. 19




Fig. 20

DRILL ASSEMBLY FOR ACCESSING BONE

RELATED APPLICATION

The present application is a continuation patent application and claims priority benefit, with regard to all common subject matter, of earlier-filed U.S. patent application Ser. No. 14/230,534, filed Mar. 31, 2014, entitled "SYSTEM AND METHOD FOR STABILIZING IMPLANTED SPINAL CORD STIMULATORS," and now issued as U.S. Pat. No. 9,192,759 on Nov. 24, 2015 ("the '759 Patent"). The above-referenced patent is hereby incorporated by reference into the present application in its entirety.

BACKGROUND

1. Field

Embodiments of the invention provide a system and method for stabilizing implanted spinal cord stimulators implanted in the epidural space of a spinal cord of a patient.

2. Related Art

Spinal cord stimulators ("SCSs" or "stimulators") output electrical pulses to control chronic back pain. The stimulator generally comprises an implantable pulse generator (IPG), a plurality of implanted stimulating electrodes, and conducting lead wires connecting the electrodes to the generator. The electrodes are positioned on a lead that is implanted in the epidural space of the spinal column proximate the spinal cord, and multiple leads may be implanted. The IPG is implanted subcutaneously proximate the lumbar region of the back and includes a power supply and remote controls. The electrodes commonly come in two forms—percutaneous form and paddle form. Embodiments of the invention are primarily directed to percutaneous type electrodes. The lead wires are coupled to the percutaneous leads having an array of electrodes and are fed through the spinal column and to the IPG implanted in the lumbar region. A patient can then control an amount of voltage and current exerted by the electrodes to address chronic pain or other disorders.

Percutaneous electrodes comprise a very long, thin wire (also known as a "lead wire" or "lead line") connected to the lead(s). A plurality of leads may extend from the single wire, or multiple wires with one or more leads may be implanted in the epidural space. Because the percutaneous electrodes extend axially through the spinal column, the electrodes are susceptible to axial movement within or dislodgement from the spinal column when the patient moves. This may be undesirable if the electrodes move out of position relative to the location where the voltage should be applied.

SUMMARY

Embodiments of the invention relate to spinal cord stimulators and systems and methods for implanting the stimulators and preventing or limiting axial movement of the stimulators once implanted in a patient's epidural space of the spinal column. Embodiments of the invention are specially adapted for use with percutaneous leads, although embodiments may be used with paddle stimulators. The stimulators generally comprise at least one lead and at least one lead wire connected to the lead. The system of embodiments of the invention broadly comprises a drill assembly, a guide wire assembly, and a guide wire receiver. The drill assembly includes a cannula, a drill, and an incremental drill adjuster. The guide wire assembly includes a hollowed guide wire sleeve presenting a guide wire sleeve lumen and a guide

wire housed within the sleeve lumen. A magnet is disposed on a proximal end of the guide wire assembly.

The cannula has a handle and a hollowed cannula shaft coupled to and extending from the handle. The hollowed cannula shaft presents a cannula lumen. The drill has a drill handle and a hollowed drill shaft presenting a drill lumen, wherein the drill shaft has proximal and distal ends. A drill bit is provided on the proximal end of the shaft, and the drill shaft is configured to be inserted in the cannula lumen. The incremental drill adjuster is configured to advance the drill shaft by a pre-set distance upon rotation of the drill handle by 360 degrees or other pre-set rotation angle.

The guide wire receiver comprises a handle and an elongated shaft, and the shaft has a handle end coupled to the handle and a receiving end opposite the handle end. The guide wire receiver shaft is semi-cylindrical along a portion of its length to present an open lumen, and at least a portion of the open lumen at the receiving end of the shaft is widened to provide a scoop for receipt of the magnet on the proximal end of the guide wire assembly.

The above components, in addition to other components not discussed above in this brief summary, are utilized in the method of embodiments of the invention. The method of embodiments of the invention broadly comprises the below-discussed steps. First, a surgeon accesses the patient's epidural space at the lumbar region of the patient to create a first access point and accesses the user's epidural space at the thoracic region of the patient to create a second access point. The epidural space is accessed at the thoracic region using the drill assembly. In contrast, the epidural space at the lumbar region may be accessed using the drill assembly or, if penetrating only soft tissue and not bony lamina, a needle and stylet.

After creating the first and second access points, the surgeon then inserts the guide wire assembly through the second access point and into the epidural space at the thoracic region of the patient. The guide wire assembly has proximal and distal ends, and the proximal end of the guide wire is an end closest to the patient when the guide wire is inserted through the second access point, and the distal end of the guide wire is opposite the proximal end and closest to a surgeon when the guide wire is inserted through the second access point. The surgeon then inserts the guide wire receiver into the first access point at the lumbar region of the patient. The surgeon captures the guide wire assembly with the guide wire receiver by positioning the proximal end of the guide wire assembly within the scoop of the guide wire receiver.

Upon capturing the guide wire assembly via the guide wire receiver, the surgeon pulls, from the lumbar region, the guide wire assembly through the epidural space to expose a portion of the guide wire assembly external to the first access point at the lumbar region. The surgeon then removes the magnet from the guide wire assembly and removes the guide wire housed within the guide wire sleeve lumen. The surgeon feeds at least one monofilament through the guide wire sleeve lumen from one of the lumbar or thoracic regions and to an other of the lumbar or thoracic regions. Once the monofilament is fed through the patient's epidural space along the axial length of the patient's back, the surgeon removes the guide wire sleeve from the epidural space and leaves in place the at least one monofilament in the epidural space. A first length of the at least one monofilament is then exposed and external to the first access point, and a second length of the at least one monofilament is exposed and external to the second access point.

To insert the percutaneous leads into the epidural space, the surgeon couples one end of the at least one monofilament to an end of a percutaneous lead of a spinal cord stimulator. The surgeon pulls the percutaneous lead through at least a portion of the epidural space of the spinal cord by pulling on an other of the ends of the at least one monofilament to which the percutaneous lead is not coupled. The surgeon then positions the percutaneous lead at the desired position within the epidural space by pulling on said other end of the at least one monofilament until the lead is in said desired position. Finally, the surgeon anchors one of said first or second lengths of the at least one monofilament exposed outside of the one of said first or second access points and anchors the percutaneous lead wire exposed outside of the other of said first and second access points.

This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the detailed description. This summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter. Other aspects and advantages of the present invention will be apparent from the following detailed description of the embodiments and the accompanying drawing figures.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

Embodiments of the present invention are described in detail below with reference to the attached drawing figures, wherein:

FIG. 1 is a schematic view of a patient's posterior side, including an illustration of the patient's spinal column and indicating a lumbar region and a thoracic region on the patient;

FIG. 2 is an exploded perspective view of a cannula and a trocar of embodiments of the invention;

FIG. 3 is an exploded perspective view of a drill assembly of embodiments of the invention, particularly illustrating the cannula, a drill, and a drill stylet;

FIG. 4 is a fragmentary perspective view of the drill of FIG. 3 and particularly illustrating a cutout in a drill handle;

FIG. 5 is a perspective view of the drill and drill stylet of FIG. 3 and particularly illustrating the drill stylet seated within a notch of the drill handle;

FIG. 6 is a perspective view of a drill shaft of the drill of FIG. 3 and illustrating various segments of the shaft;

FIG. 7 is a fragmentary front end view of a cannula handle of the cannula of FIG. 3, the drill handle, and the drill stylet;

FIG. 8 is a cross-sectional view taken through line 7-7 of FIG. 7;

FIG. 9 is an exploded perspective view of a needle and a needle stylet of embodiments of the invention;

FIG. 10 is a fragmentary perspective view of a guide wire assembly of embodiments of the invention and particularly illustrating a guide wire sleeve and a guide wire housed within the sleeve;

FIG. 11 is a fragmentary exploded perspective view of the needle and needle stylet of FIG. 9 and the guide wire assembly of FIG. 10 housed within the needle stylet;

FIG. 12 is an exploded perspective view of an introducer and introducer stylet of embodiments of the invention;

FIG. 13 is a perspective view of a guide wire receiver of embodiments of the invention;

FIG. 14 is an exploded perspective view of a first angiocath of embodiments of the invention being fed over the guide wire assembly of FIG. 10;

FIG. 15 is a fragmentary perspective view of the introducer and introducer stylet combination of FIG. 12 being fed over the guide wire assembly of FIG. 10;

FIG. 16a is a first end view of a scoop located on a proximal end of the guide wire receiver of FIG. 13;

FIG. 16b is a second end view of a scoop located on a proximal end of the guide wire receiver of FIG. 13;

FIG. 16c is a third end view of a scoop located on a proximal end of the guide wire receiver of FIG. 13;

FIG. 16d is a first perspective view of the scoop and particularly illustrating the scoop in a fully-folded position;

FIG. 16e is a second perspective view of the scoop and particularly illustrating the scoop in a fully-open position;

FIG. 17 is an exploded perspective view of the guide wire receiver housed within the introducer, and the combined guide wire receiver and introducer being fed into the cannula;

FIG. 18 is a fragmentary perspective view of the scoop of the guide wire receiver catching a magnet coupled to the proximal end of the guide wire assembly;

FIG. 19 is an exploded perspective view of a second angiocath of embodiments of the invention having a magnet coupled to its proximal end and being fed through the introducer stylet and introducer; and

FIG. 20 is a perspective view of a lead wire of a percutaneous stimulator, a connector, and the monofilament of embodiments of the invention.

The drawing figures do not limit the invention to the specific embodiments disclosed and described herein. The drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the invention.

DETAILED DESCRIPTION

The following detailed description of embodiments of the invention references the accompanying drawings that illustrate specific embodiments in which the invention can be practiced. The embodiments are intended to describe aspects of the invention in sufficient detail to enable those skilled in the art to practice the invention. Other embodiments can be utilized and changes can be made without departing from the scope of the present invention. The following detailed description is, therefore, not to be taken in a limiting sense. The scope of the invention is defined only by the appended claims, along with the full scope of equivalents to which such claims are entitled.

In this description, references to "one embodiment," "an embodiment," or "embodiments" mean that the feature or features being referred to are included in at least one embodiment of the technology. Separate references to "one embodiment," "an embodiment," or "embodiments" in this description do not necessarily refer to the same embodiment and are also not mutually exclusive unless so stated and/or except as will be readily apparent to those skilled in the art from the description. For example, a feature, structure, act, etc. described in one embodiment may also be included in other embodiments but is not necessarily included. Thus, the present technology can include a variety of combinations and/or integrations of the embodiments described herein.

Turning now to the drawings, embodiments of the invention comprise a system and a method for implanting and stabilizing or otherwise securing percutaneous spinal cord stimulators 10. As shown in FIG. 20, the stimulators 10 generally comprise one or more leads 12, with the one or more leads comprising at least one electrode (not shown) that emits an electrical voltage. The leads 12 are connected

to a lead wire **14**, and the lead wire is coupled with an implantable pulse generator **16** (IPG) (see, FIG. **1**) that is implanted subcutaneously in a patient's back. Referring to FIG. **1**, the patient's back has a lumbar region or end **18** and a thoracic region or end **20** with the spinal column **22** axially positioned between the two regions. The IPG **16** is normally implanted at the flank region or the lumbar region **18**. A stabilizing system **24** of embodiments of the invention secures the lead **12** within the epidural space of the spinal column **22**. In embodiments, the system **24** broadly comprises a plurality of various medical devices that are used to perform the method of embodiments of the invention. In particular, the stabilizing system **24** comprises a drill assembly **26**, a guide wire assembly **28**, and a guide wire receiver **30**. Other components of the system will be described herein.

The following description will reference various orientations of the components of the stabilizing system. Reference to a proximal end of a particular component refers to the end closest to the patient when the component is in use. In contrast, reference to a distal end refers to the end opposite the proximal end and closest to the surgeon using the component. Reference to a vertical axis of a component refers to the axis along the component's length, and reference to a transverse axis of a component refers to the axis along the component's width. If the reference directions of "proximal" and "distal" are not suitable for a particular component, such as if the component is within the spinal column, then reference will be made to a thoracic end and a lumbar end, with the thoracic end being the end closest to the thoracic region **20** of the patient (i.e., closer to the patient's neck), and the lumbar end being the end closest to the lumbar region **18** of the patient (i.e., closer to the patient's buttocks). Finally, many of the components of the system **24** comprise medical devices that have hollowed shafts. The term "lumen" will be used herein to refer to the hollowed area or bore formed by the respective shaft, and each respective shaft's lumen will not be given a separate reference numeral.

Many, if not most, of the components described herein are radio-opaque so that they can be viewed under X-ray. Unless otherwise stated, it is to be assumed that in embodiments of the invention, a component is radio-opaque.

Turning now to FIGS. **2-8**, the drill assembly **26** of embodiments comprises a cannula **32**, a drill **34**, and an incremental drill adjuster **36**. The cannula **32** comprises a cannula handle **38** and a cannula shaft **40** that is hollowed to present a cannula lumen. A trocar **42** having a trocar cap **44** and pointed shaft **46** is configured to fit within the cannula lumen. A proximal end **48** of the pointed shaft **46** extends outside a proximal end **50** of the cannula shaft **40** when the trocar **42** is housed within the cannula **32**.

The cannula handle **38** includes grasping bars **52** and a cutout **54** formed in a top of the handle **38** for receipt and capturing of the trocar cap **44** of the trocar **42** when the trocar **42** is coupled with the cannula **32**. The cutout **54** includes at least one horizontally-oriented channel **56** formed in a sidewall **58** of the cutout **54** for receipt of a tab **60** horizontally extending from the trocar cap **44**. A user (who is commonly a surgeon or interventional pain physician) may position the trocar shaft **46** in the cannula lumen and then rotate the trocar cap **44** to guide the tab **60** into the channel **56**. The trocar **42** will then not be easily dislodged or moved with respect to the cannula **32** until the user reverses rotation of the trocar cap **44** to expose the tab **60** from the channel **56**. In embodiments, the cutout **54** may include opposing channels formed in opposing sidewalls of

the cutout to receive two tabs extending from the trocar. The cannula handle **38** further includes a ball detent assembly that will be discussed further below and that is part of the incremental drill adjuster **36**.

In some steps of the method of embodiments of the invention, the trocar **42** will not be housed within the cannula **32**, but it is still desirable that the cannula be capped. In such instances, the cannula **32** will include a cannula cap **62** that is separate from the trocar cap **44** attached to a distal end of the trocar **42**. However, the cannula cap **62** will be substantially the same as the trocar cap **44**, except that the cannula cap **62** will include an axial cylindrical chamber **64** (see FIG. **8**) therethrough to provide a passage for accessing the cannula lumen, as described below. Additionally, the cannula cap **62** may include an axial tab (not shown) similar to the tab **60** on the trocar cap **44** to assist with interfitting the cap **62** with the cannula handle **38** via a friction fit.

The drill **34** of embodiments of the invention is illustrated in FIGS. **3-8** and comprises a drill handle **66** and a drill shaft **68** coupled to the drill handle **66** and extending therefrom. The drill shaft **68** is hollowed to present a drill lumen. A drill stylet **70** having a handle **72** and shaft **74** extending therefrom is configured to fit within the drill lumen, i.e., the hollowed drill shaft **68**. A proximal end **76** of the drill stylet shaft **74** is configured to extend outside a proximal end **78** of the drill shaft **68** when the drill stylet **70** is housed within the drill **34**, as discussed in more detail below. Similar to the cannula handle **38**, the drill handle **66** includes grasping bars **80** and a cutout **82** formed in a top of the handle for receipt and capturing of the drill stylet handle **72** when the drill stylet **70** is coupled with the drill **34**. However, the drill handle cutout **82** is shaped differently than the cutout **54** on the cannula handle **38**.

In particular, the drill handle cutout **82** includes a seat **84**, sidewalls **86** extending distally from the seat **84**, and a notch **88** extending proximally from the seat **84**. The sidewalls **86** are complementally shaped to fit and receive the drill stylet handle **72**. Referring to FIGS. **3** and **7**, the drill stylet handle **72** has a generally horizontally oriented shelf **90** and sidewalls **92** extending from the shelf **90**. Two tabs **94** extend horizontally from the shelf **90** on opposing front and rear sides of the shelf **90**. The sidewalls **92** are angled or otherwise shaped to be received within the cutout **54** formed in the drill handle **66**, such that the sidewalls **92** of the drill stylet handle **72** closely match the angle and shape of the sidewalls **58** of the drill handle cutout **54**.

To position the drill stylet **70** in the drill **34**, the user rotates the drill stylet **70**, such that a width of the stylet handle **72** is non-parallel to a width of the drill handle **66**. The user then inserts the drill stylet shaft **74** within the drill lumen. Once inserted, the user can rotate the drill stylet handle **72** to a position where the drill stylet handle width is generally parallel to the drill handle width, as best shown in FIG. **7**. Upon rotation, the sidewalls **86** of the drill stylet handle **72** will closely match with the sidewalls **58** of the drill handle cutout **54**, as shown in FIG. **7**. Moreover, the two tabs **94** extending from the drill stylet shelf **90** will overlap a portion of the drill handle **66** to prevent removal or dislodgement of the drill stylet **70** from the drill **34**, referred to as a locked position of the drill stylet **70**. In embodiments, upon rotation of the drill stylet handle **72** relative to the drill handle **66** to have the widths of the drill stylet handle and drill handle be substantially parallel, the tabs **94** may slightly catch to provide a further frictional securement. In this position, the shelf **90** of the drill stylet handle **72** sits atop the seat **84** of the drill handle **66**, as shown in FIG. **7**. To remove

the drill stylet **70** from the drill **34**, the user reverses rotation of the drill stylet handle **72**, such that the drill stylet handle width is non-parallel to the drill handle width. The user can then remove the drill stylet shaft **74** from the drill lumen.

When the drill stylet handle **72** is seated within the cutout **54** of the drill handle **66**, the drill stylet handle **72** does not fill the notch **88** that extends proximally from the seat **84**. That is, the notch **88** still presents an open cavity **96**, as best seen in FIG. 7. The purpose of the notch **88** is to allow the drill stylet shaft **74** to be advanced farther within the drill lumen. In particular, if the user reverses rotation of the drill stylet handle **72**, such that the drill stylet handle is non-parallel to the drill handle **66**, and the user continues reversal of rotation until the drill stylet handle **72** is approximately perpendicular to the drill handle **66**, the user can then set a portion of the shelf **90** of the drill stylet handle **72** within the notch **88**, as shown in FIG. 5. This is accomplished by the front to rear depth of the drill stylet handle **72** being less than the transverse width of the notch **88**. When the drill stylet shelf **90** is fit within the notch **88**, this in turn extends the proximal end **78** of the drill stylet shaft **74** outside of the proximal end **78** of the drill shaft **68** by an axial length of the notch **88**. In embodiments of the invention, the axial length of the notch (i.e., the length of the notch along a vertical axis) is approximately 0.5-5 mm, approximately 1-4 mm, approximately 2-3.5 mm, or approximately 3 mm. As discussed below in the method of embodiments of the invention, the user may desire to extend the drill stylet shaft **74** outside of the proximal end **78** of the drill shaft **68** to test whether the user has accessed the epidural space.

The drill shaft **68** is best illustrated in FIG. 6 and presents the proximal end **78** and a distal end **98**, a drill bit segment **100** (also referred to herein as a "drill bit") at the proximal end **78**, a straight-sided segment **102**, a detent segment **104**, and a shank segment **106** at the distal end **98**. The segments **100,102,104,106** are integral to each other, such that the drill shaft **68** is formed of a rigid, biocompatible material, such as steel, titanium, etc. The drill bit segment **100** includes a plurality of flutes **108** that assist in drilling into lamina of the patient's spinal column **22**. Upon rotation of the drill shaft **68**, as described in more detail below, the flutes **108** serve to create an access point into the spinal column **22**. The straight-sided segment **102** provides a length for the drill shaft **68**, such that the straight-sided segment **102** may be different lengths depending on the use of the drill **34** or preferences of a user of the drill. The detent segment **104** is described in more detail immediately below. The shank segment **106**, or a portion of a length of the shank segment, is mounted within the drill handle **66**.

The detent segment **104** is a component of the incremental drill adjuster **36**. The detent segment **104** provides a body **110** that is generally cylindrical along its length, except that a plurality of adjacent detents **112** or grooves is formed along at least a portion of a length of the detent segment **104**. In particular, the plurality of adjacent detents **112** is formed on one side of the generally cylindrical detent segment body **110**. The detents **112** are arranged side-by-side and are spaced approximately 0.1-0.8 mm apart, approximately 0.2-0.5 mm apart, or approximately 0.25 mm apart. That is, a length of a single detent **112** from a proximal end of the detent to a distal end of the detent is 0.1-0.8 mm, approximately 0.2-0.5 mm, or approximately 0.25 mm. The length of the detent segment **104** at the area comprising the detents generally forms a longitudinal channel in the detent segment body **110**, and the detents are formed in the longitudinal channel. The detents **112** are formed from slightly projecting walls **114**, as best illustrated in FIG. 6. Each pair of adjacent

walls **114** extends from the detent segment body **110** to form a detent **112** therebetween, and each detent **112** presents a trough for receipt of a portion of a ball of the ball detent assembly discussed in more detail below.

As noted above, the detents **112** are formed in the longitudinal channel. Extending outside the channel and circumscribing the detent segment body **110** is a plurality of flutes **116**, with each flute **116** generally corresponding and aligning with a formed detent **112**. Each flute **116** presents a flute wall **118** that extends from the detent segment body **110**. As discussed in more detail below, as the drill **34** is rotated during insertion in the lamina, the user of the drill may apply enough force to dislodge the ball from a particular detent **112**; in response to rotation of the drill handle **66**, guide the ball along a flute **116** adjacent to the detent **112** in which the ball was just located; and set the ball in one of the other detents **112**.

As shown in FIGS. 7 and 8, the drill shaft **68** is sized and configured to fit within the cannula cap **62**, through the cannula handle **38**, and through the cannula lumen. Thus, the drill stylet **70** is housed within the drill lumen, and the drill shaft **68** is housed within the cannula lumen. Each of these components collectively operates together, as described in more detail below.

Returning to the cannula handle **38**, the incremental drill adjuster **36** will now be described. The adjuster **36** allows for adjusting the drill **34** forward a set amount and in discrete movements so that the user is able to control proximal movement of the drill **34** and by the set amount. The incremental drill adjuster **36** comprises a ball detent assembly **120** and the detent segment **104**. The ball detent assembly **120** includes a ball **122** and a spring **124** that loads the ball **122** in each detent **112**. The detent segment **104**, which was described above, includes the plurality of adjacent detents **112** formed in the detent segment of the drill shaft and the corresponding flutes **116**. The ball detent assembly **120** is positioned in the cannula handle **38**, as best shown in FIG. 8. A side of the cannula handle **38** is hollowed to provide a chamber **126** to receive the ball **122** and spring **124**. A cap **128** is fitted onto the cannula handle **38** to close off the chamber **126** once the ball **122** and spring **124** are positioned in the chamber **126**. In embodiments, an end of the spring **124** may be secured to an inside of the cap, as shown in FIG. 8. In alternative embodiments, the ball **122** and spring **124** may be formed in the cannula cap **62** or one of the ball and spring may be formed in the cannula cap **62**. Therefore, it is not intended as limiting that a portion of the detent assembly **120** is described above as formed in the cannula handle **38**.

The ball **122** is spring-loaded, in that application of a force or pressure against the ball will compress or retract the spring **124** within the chamber **126**. Upon the spring **124** returning to its fully extended position within the chamber **128**, as shown in FIG. 8, the spring **124** seats a portion of the ball **122** in one of the detents **112** described above. To actuate the drill **34** forward, the user will apply sufficient force or pressure against the drill handle **66** to overcome the force of the spring **124** and push the ball **122** into the chamber **126**. Due to the ball **122** being spring-loaded, the user will be able to intuitively feel the force of the spring **124** pushing the ball forward into the adjacent detent.

To actuate proximal movement of the drill **34** (i.e., advance the drill into the lamina or other bone), the user first locates the drill stylet **70** within the drill handle **66** and in the locked position noted above. The locked position is shown in FIG. 7 and occurs when the shelf **90** of the drill stylet handle **72** sits atop the seat **84** of the drill handle **66**. The drill

shaft **68** is then positioned through the cannula cap **62** and into the cannula lumen, as shown in FIGS. 7 and 8. The user then inserts the drill shaft **68** through the cannula lumen and to the desired location and then releases any rotational force applied to the drill handle **66**. The release of the rotational force will seat the ball **122** into one of the detents **112**, as shown in FIG. 8. The user can then place the proximal end **78** of the drill shaft **68** proximate the desired location on the patient, e.g., proximate the lamina. The user will then rotate the drill handle **66** to begin drilling into the lamina. In embodiments of the invention, every 360 degree rotation of the drill handle **66** will advance the drill bit approximately 1 mm, although the drill assembly **26** can be sized to advance the drill shaft **68** less or more upon a single 360 degree rotation. At the initial stage of drilling, the user will likely be applying significant rotational force to advance the drill shaft **68** through the lamina. However, upon drilling through the lamina, not as much force is required to advance the drill shaft. At this stage, the user will take advantage of the incremental drill adjuster **36** to advance the drill shaft **68** in set amounts. In particular, the user may choose to advance the drill shaft **68** by only one detent length, such that the drill shaft **68** is advancing in relatively small but discrete amounts. This is desirable if the user is attempting to access the epidural space but without impacting the spinal cord, which is dangerous and painful for the patient. If in embodiments the drill shaft **68** advances approximately 1 mm for every 360 degree rotation, then approximately every quarter-turn or every approximately 90 degrees will seat the ball **122** in the next adjacent detent **112** and advance the drill shaft **68** by approximately 0.25 mm. The user can then incrementally adjust the drill **34** to obtain a precise drilling advancement into the access point.

The drill **34** described herein is for use in inserting the stimulators **10**. However, it should be appreciated that the drill **34** of embodiments of the invention could be used for other medical procedures and for drilling through bone on other areas of a patient (both human and animal).

In some instances the spinal column **22** can be accessed without needing to drill through the lamina. For example, in the lumbar region **18** of the patient, there is more room between adjacent lamina, which allows more room for the user to maneuver between the lamina to establish an access point within the spinal column. In this instance, the user need only penetrate soft tissue in the back to create the access point. However, in some instances in the lumbar region **18**, the patient may have arthritis or other issues that require drilling through the lamina.

In the instances where only soft tissue need be penetrated and the drill **34** is not required, embodiments of the invention use a needle **130** and needle stylet **132**, as illustrated in FIG. 9. The needle **130** presents a small handle **134** and a hollowed needle shaft **136** extending therefrom and presenting a needle lumen. The needle handle **134** has a generally cylindrical, axial opening (not shown) therethrough for the needle stylet **132**. The needle stylet **132** also includes a handle **138** and a needle stylet shaft **140**, although the needle stylet shaft **140** is not hollowed to present a lumen. A proximal end **142** of the needle stylet shaft **140** is pointed to assist in penetrating soft tissue. In operation, the needle stylet shaft **140** is fed through the opening in the needle handle **134** and through the needle lumen, and in embodiments, the pointed proximal end **142** of the needle stylet shaft **136** extends outside a proximal end **144** of the needle shaft **136**.

Turning now to FIG. 10, the guide wire assembly **28** of embodiments of the invention comprises an elongated guide

wire **146**, a wound-wire sleeve **148** surrounding the guide wire **146**, and a magnet **150** coupled to a proximal end **152** of the guide wire assembly **28**. The elongated guide wire **146** is a long, thin section of wire that in embodiments is approximately 0.1-1.0 mm in diameter, approximately 0.2-0.8 mm in diameter, or approximately 0.3 mm in diameter. The wire **146** is flexible, such that it can be bent approximately 180 degrees in any direction. A length of the wire **146** is dependent on an axial length of the patient's spinal column **22**, such that the length of the wire should be long enough to extend axially through the patient's spinal column **22** from the lumbar region **18** and to the thoracic region **20** (or vice-versa) and with a working section (discussed below) extending from each region. Given the length of the guide wire **146**, the drawings illustrate the guide wire length in fragment, such as shown in FIG. 10.

The wound-wire guide wire sleeve **148**, as shown in FIG. 10, substantially covers the guide wire **146**. The sleeve **148** is formed of wire that is tightly wound to present a lumen in which the guide wire **146** is inserted. The sleeve **148** provides rigidity to the guide wire assembly **28** that is helpful during insertion of the guide wire assembly **28** into the spinal column **22**. However, the combined guide wire **146** and sleeve **148** are still flexible enough to be bent up to 180 degrees. The sleeve **148** is sized and configured to be easily slidable along the length of the guide wire **146**, so that the user can easily insert and remove the guide wire **146** into the sleeve lumen. The combined guide wire **146** and sleeve **148** are also sized and configured to easily slide within the needle lumen, as shown in FIG. 11, the guide wire receiver, as shown in FIG. 17, or an angiocath, as shown in FIG. 13 and discussed in more detail below.

The guide wire assembly **28** further includes the magnet **150** coupled to the proximal end **152** of the guide wire assembly **28** and, in particular, the guide wire sleeve **148** (as opposed to the guide wire **146**), as best illustrated in FIG. 10. The magnet **150** may be coupled to the end of the sleeve **148** via any method that secures the magnet **150** and prevents it from becoming dislodged from the end of the sleeve **148**. An exemplary securement method is an adhesive applied to the sleeve **148** and/or the magnet **150**. In embodiments, the magnet **150** may present a hollowed chamber (not shown) at one end so that the end of the sleeve **148** may be fitted within the hollowed chamber of the magnet. In embodiments, the magnet is approximately 1-3 mm in length or approximately 2 mm in length. The magnet **150** provides sufficient magnetic attraction to a magnet on an end of an angiocath (discussed below) to draw the two magnets together when the guide wire assembly **28** and angiocath are inserted into the epidural space.

Some steps of the method of embodiments of the invention may use a combined guide wire **146** and wound-wire sleeve **148** surrounding the guide wire **146**, but in such steps, the combination guide wire **146** and sleeve **148** does not include a magnet **150**, or, at the least, a magnet is required. That is, in some steps, a combination guide wire **146** and sleeve **148** can be used that does not include a magnet. In some embodiments of the invention, a kit that is provided with the components of the invention includes a combination guide wire **146** and sleeve **148** that does not include a magnet and a combination guide wire **146** and sleeve **148** that does include a magnet **150**. But, in other embodiments of the invention, the provided kit includes two combination guide wires **146** and sleeves **148**, each with a magnet. Even though the magnet is not required for one of the steps, as described below, two combination guide wires and sleeves with a magnet may still be provided for ease of manufac-

turing and not having to source two different components. In yet further embodiments, two combination guide wires and sleeves with no magnets are provided as a component of the kit.

Turning now to FIGS. 13, 16a-e, 17, and 18, the guide wire receiver 30 will be described. The guide wire receiver 30 is inserted into the epidural space at the lumbar region 18. The guide wire assembly 28 is inserted into the epidural space at the thoracic region 20. In general but discussed in more detail below, the user feeds the guide wire assembly 28 through the spinal column 22 and to the guide wire receiver 30. The receiver 30 is then sized and configured to easily catch or receive the guide wire assembly 28 so that the guide wire assembly 28 can be pulled through the access point at the lumbar region 18 of the patient's spine.

Referring to FIG. 13, the guide wire receiver 30 broadly comprises a handle 154, a semi-cylindrical body 156 extending from the handle 154, and a receiving section 158. The handle 154 is hollowed to present a handle lumen that connects with a guide wire receiver lumen through the body 156. A distal end 160 of the body 156 is completely closed about the cylindrical body; however, a majority of a length of the body 156 is open to present a semi-cylindrical body section 162. As such, the guide wire receiver lumen at the semi-cylindrical body section 162 presents an open lumen. The receiving section 158 is integrally formed with and extends from the semi-cylindrical body section 162. The receiving section 158 is at a proximal end 164 of the guide wire receiver 30. The semi-cylindrical body section 162 widens at the receiving section 158 to present a scoop 166 comprising the receiving section and for receipt of the magnet 150 on the end of the guide wire assembly 28, as shown in FIG. 18.

In more detail, the receiving section 158 of the guide wire receiver 30, and namely, the scoop 166, is flexible and configured to be rolled from an unfolded condition to a folded condition, as illustrated in FIGS. 16a-16e. The scoop 166 extends from the distal end 160 of the semi-cylindrical body section 162 to present sidewalls 168 and a proximal-most end 170. The sidewalls 168 of the scoop 166 are angled outwards as the proximal-most end 170 of the scoop 166 is approached, such that the proximal-most end 170 of the scoop 166 is wider than the semi-cylindrical body section 162 of the guide wire receiver 30. In the scoop's fully unfolded condition, illustrated in FIG. 16a, the scoop's sidewalls 168 are generally raised as the sidewalls 168 extend from the semi-cylindrical body section 162 of the guide wire receiver 30. However, as the sidewalls 168 widen as the proximal-most end 170 of the scoop 166 is approached, the sidewalls begin to flatten out, as illustrated in FIG. 16e. As can be seen in FIG. 16a, the sidewalls 168 of the scoop 166 are not completely flat, however, even in the fully unfolded condition, so as to present a flared proximal end.

The scoop 166 is flexible and especially designed to be "rolled up." That is, the sidewalls 168 of the scoop 166 may be curved upwards from the fully unfolded position, as shown in FIGS. 16a and 16e, to a fully-folded condition, as shown in FIG. 16d. In the fully-folded condition, proximal ends of the sidewalls 168 of the scoop 166 are almost touching (see FIG. 16d), are touching (not shown), or are overlapping (not shown). The scoop 166 is thus foldable, and this foldable feature serves to capture the magnet 150 of the guide wire assembly 28 upon the magnet 150 being received in the unfolded scoop 166. In other instances, the scoop 166 may not need to be either fully folded or full unfolded, and in such instances, the scoop may be folded to

intermediate positions, as shown in FIGS. 16b and 16c. The scoop 166 thus provides sufficient flexibility to be rolled from the unfolded to the fully-folded condition but also enough rigidity to hold a particular folded incremental position during use. Use of the guide wire receiver 30 will be described in more detail below.

As described below and as shown in FIG. 17, the guide wire receiver 30 is fed through a lumen of an introducer 172 or epiducer. During insertion, the scoop 166 is operable to roll to the fully-folded condition so that it can be inserted into the introducer lumen. To insert the guide wire receiver 30 into the introducer lumen, the user simply places the scoop 166 (which is presently in its fully-unfolded condition) against a distal end 174 of the introducer 172 and begins pushing the guide wire receiver 30 through the introducer lumen. When the scoop 166 is not inserted in a lumen, it is in a rest or natural state of the fully unfolded position of FIG. 16a. However, upon the user beginning to insert the scoop 166 into the lumen, the scoop will begin to fold to the fully-folded position of FIG. 16d for placement within the lumen. A length of the guide wire receiver 30 is longer than a length of the introducer 172, such that the scoop 166 extends beyond a proximal end 176 of the introducer, as shown in FIG. 17.

The system 24 for securing spinal cord stimulators 10 also includes various other components. In particular and referring to FIGS. 12, 14, 15, and 19-21, the system 24 further comprises the introducer 172 (or epiducer), an introducer stylet 178, a first angiocath 180, a second angiocath 182 having a magnet 184 at one end, at least one monofilament 186, and a connector 188 for connecting the monofilament 186 to the lead 12 of the percutaneous stimulators 10.

The introducer 172 of embodiments of the invention may also be what is known in the art as an epiducer. Both the introducer 172 and epiducer include a handle 190 and a hollowed shaft 192 extending from the handle 190 and presenting a lumen. As is known in the art, an introducer typically has a cylindrical shaped shaft, whereas an epiducer has an oval or oblong shaped shaft when viewed in horizontal cross section. As discussed herein, the term "introducer" is defined to include both cylindrically shaped and oval or oblong shaped shafts, and as such, the term "introducer" is intended to encompass both the typical introducer and epiducer known in the art. Although not shown in the drawings, the introducer handle 190 is hollowed so that the introducer lumen and hollowed introducer handle can receive another component therethrough, as shown in FIG. 17.

As illustrated in FIG. 12, the introducer stylet 178 is configured to be inserted into the introducer lumen. The introducer stylet 178 comprises a handle 194, a luer 196 for removably coupling the introducer stylet 178 with the introducer 172, and a hollowed introducer stylet shaft 198 that includes a taper 200 at a proximal end. The introducer stylet shaft 198 extends from the handle 194 and through the luer 196, and because the shaft is hollowed, the introducer stylet has a lumen. The shaft 198, and specifically the taper 200, is slightly flexible to provide some flexing upon application of pressure. A length of the introducer stylet shaft 198 is longer than a length of the introducer shaft 192, such that when the introducer stylet 178 is housed within the introducer lumen, the taper 200 extends out from the proximal end of the introducer 172. The luer 196 serves to couple the introducer stylet 178 with the introducer 172 by fitting the luer 196 over a portion of a distal end of the introducer 172 and rotating the luer 196 to obtain a friction fit.

13

The system 24 of embodiments employs at least two and potentially additional angiocaths. In embodiments, the first angiocath 180, illustrated in FIG. 14, is a conventional angiocath having a handle 202 and a shaft 204 extending therefrom. The shaft 204 is generally flexible to allow an approximately 5-45 degree radius of movement about an axial length of the shaft. In the first angiocath 180 shown in FIG. 14, a proximal end 206 of the angiocath is substantially straight. However, the system 24 of embodiments of the invention contemplates including a plurality of angiocaths having proximal ends with various curvatures, such that the proximal end 206 is angled at a particular degree. Exemplary first angiocaths 180 include proximal ends 206 angled at 0 degrees (i.e., a straight proximal end), 5 degrees, 10 degrees, 15 degrees, 20 degrees, 25 degrees, and 30 degrees. The system may comprise a kit that includes some or all of the plurality of first angiocaths.

The second angiocath 182, which is illustrated in FIG. 19, is substantially the same as the first angiocath (like reference numerals are used to indicate like structure), except that the second angiocath 182 includes the magnet 184 coupled to the proximal end 206 of the angiocath shaft 204. The magnet 184 may be secured to the proximal end 206 via adhesive or other suitable securement method. The magnet 184 on the second angiocath 182 is configured to be attracted to the magnet 150 on the guide wire assembly 28, as discussed above. As discussed in more detail below, during the method of stabilizing the spinal cord stimulators 10 in the patient, the magnet 184 on the second angiocath 182 is positioned proximate the magnet 150 on the guide wire assembly 28 so that the magnets are magnetically attracted to each other to removably couple the guide wire assembly to the second angiocath to allow for pulling of the guide wire assembly through the epidural space.

Similar to the first angiocath 180, the system 24 may also include a plurality of second angiocaths 182, with each second angiocath having a proximal end with a different radius of curvature. In particular, the proximal ends of each of the second angiocaths may be angled at 0 degrees (i.e., a straight proximal end), 5 degrees, 10 degrees, 15 degrees, 20 degrees, 25 degrees, and 30 degrees. The system 24 may comprise a kit that includes some or all of the plurality of second angiocaths. The purpose of the angled proximal ends will be discussed in more detail below.

Referring now to FIG. 20, the monofilament 186 is shown coupled to the lead 12 of the spinal cord stimulators 10. The monofilament 186 is a single or multiple line of thin wire that is flexible and can be rolled or coiled upon itself, as shown in FIG. 20. However, the monofilament 186 also has enough rigidity to be guided into location and manipulated within the epidural space. In embodiments, the monofilament 186 is thinner in diameter than a diameter of the guide wire 146. The monofilament 186 is biocompatible, and in embodiments, the monofilament 186 is formed of carbothane. The monofilament 186 is of a length that can extend the length of the patient's back and provide additional extraneous length at both the lumbar and thoracic regions 18,20. In embodiments, a plurality of monofilaments 186 may be provided with the system 24 if multiple leads 12 are also used.

The connector 188 is also shown in FIG. 20 and is, in embodiments, a relatively small piece of carbothane tubing that is configured to couple the monofilament 186 to the percutaneous lead 12. In embodiments, the connector 188 is a cylindrical section of tubing that can receive an end of the monofilament 186 in one end of the connector 188, and an end of the lead 12 in the other end of the connector 188. The

14

respective ends of the monofilament and lead are operable to be friction fit within the connector. The user can apply adhesive or another permanent coupling solution to securely couple the monofilament with the connector and the lead with the connector. In embodiments, the connector 188 is biocompatible, as it will be permanently implanted in the patient's epidural space, as discussed in more detail below.

The method of embodiments of the invention will now be described. The method comprises steps for using the system 24 of embodiments to secure and stabilize the percutaneous spinal cord stimulators 10 in the patient's spinal column 22. The steps of the method need not be performed in the order presented below, unless expressly stated otherwise. Additionally, it should be appreciated that some steps may be combined into a single step, and some steps may be skipped altogether. Due to the nature of performing an invasive surgery on a patient, the user of the system may decide during the surgery to alter the performed steps described below.

To begin, the user (who is commonly a surgeon or other physician trained in spinal surgery and who will be referred to below as a surgeon) prepares the lumbar region 18 of the patient and creates a first access point. As noted above, the lumbar region 18 is at the tail of the patient's spine near the patient's buttocks. The surgeon will evaluate whether the drill assembly 26 is needed to access the epidural space through the patient's lamina. As noted above, in some patients the space between vertebrae is small, such as may be due to arthritis, which requires the surgeon to access the epidural space via the lamina. Because the lamina is bone, the drill assembly 26 of embodiments of the invention is required. However, for other patients, the surgeon may be able to access the epidural space through the soft tissue between adjacent lamina. In this instance, only the needle 130 and needle stylet 132 combination of embodiments of the invention is needed.

If the drill assembly 26 is needed to access the epidural space, the surgeon will locate the cannula 32 and trocar 42 combination on the lamina. The trocar 42 is then removed from the cannula 32, leaving only the cannula 32. The drill 34 and drill stylet 70 combination is then inserted into the cannula 32. To initiate drilling through the lamina, the surgeon will apply an appropriate rotational force to the drill handle 66 to rotate the drill handle. As discussed above, an approximate 360 degree rotation of the drill handle 66 will effect an approximate 1 mm advanced of the drill shaft 68 through the lamina. As can be appreciated, drilling through the bony lamina will require an appropriate force applied to the drill handle 66 from the surgeon as compared to advancing the drill shaft 68 through soft tissue, for example, or incrementally advancing the drill shaft once the epidural space is reached. Once the surgeon successfully drills through the lamina, the surgeon will then take advantage of the incremental drill adjuster 36 to advance the drill shaft 68 in set amounts, as discussed above. Once the lamina, or most of the lamina, is penetrated, the epidural space is reached to create a first access point. The surgeon must be careful to fully access the epidural space and provide a clean and open access point but also not advance the drill shaft 68 so far into the epidural space as to touch the spinal cord. The incremental drill adjuster 36 allows for this fine precision once the majority of the lamina is drilled through. The surgeon will rotate the drill handle 66 to advance the ball 122 to the next adjacent detent 112, as discussed above. Advancement by one detent length corresponds to approximately a one-quarter turn of the handle and 0.25 mm drill shaft advancement. The surgeon is normally performing the operation

15

under X-ray so that the surgeon can see where the drill bit segment **100** is in relation to the lamina and when the drill bit segment **100** penetrates the lamina and enters the epidural space. Once the lamina is fully penetrated, the surgeon uses a blunt probe (not shown) to insure a clean and fully-open access point to the epidural space.

In embodiments of the invention, the surgeon may alternatively use the drill stylet **70** to insure that the epidural space is reached. As discussed above, the drill stylet **70** is inserted into the drill lumen. The drill stylet **70** and drill handle **66** are configured to allow the drill stylet **70** to be housed within the drill lumen in two positions. A first position, shown in FIG. 7, is where the drill stylet shelf **90** is seated on the drill handle seat **84**, such that the open cavity **96** of the notch **88** notch is exposed. A second position is shown in FIG. 5 and is where the drill stylet **70** is rotated 90 degrees (from the position shown in FIG. 7), such that a portion of the drill stylet handle **72** is seated within the notch **88**. In this position, the proximal end of the stylet **76** extends outside of the proximal end of the drill shaft **78** (i.e., outside a proximal end of the drill bit segment **100**), as also shown in FIG. 5. Moving the drill stylet **70** to the second position with respect to the drill **34** allows the surgeon to insure that the epidural space is identified and accessed without touching the spinal cord, which as noted above, is dangerous and painful for the patient. Due to a length of the notch **88** in the drill handle **66**, the proximal end **76** of the drill stylet **70** is allowed to advance outside the proximal end **78** of the drill shaft **68** by approximately the length of the notch **88**. This length is enough for the surgeon to identify under X-ray that the epidural space is accessed, but not enough length to touch the spinal cord.

Once the surgeon identifies the epidural space, the surgeon then removes the drill **34** from the cannula **32**, leaving only the cannula **32**. The surgeon will then feed the guide wire assembly **28** through the cannula **32** and through first access point. The surgeon removes the cannula **32** distally, leaving only the guide wire assembly **28** penetrating the first access point. The surgeon then insures that the introducer stylet **178** is housed within the introducer lumen. As shown in FIG. 15, the combination introducer **172** and introducer stylet **178** are then fed over the guide wire assembly **28** penetrating the first access point so that the introducer and introducer stylet penetrate through the first access point. The surgeon then removes the guide wire assembly **28** from the introducer **172** and introducer stylet **178** combination by pulling the guide wire assembly **28** distally through the introducer stylet lumen. The purpose of first placing the guide wire assembly **28** through the first access point prior to placement of the introducer **172** and introducer stylet **178** combination is to provide rigidity to the introducer **172** and introducer stylet **178** combination to prevent the introducer stylet tapered end **200** from touching or penetrating the spinal cord and to further provide a guide for insertion of the introducer and introducer stylet combination.

If the drill **34** is not needed to access the epidural space at the lumbar region **18**, such as may be the case if the surgeon can access the epidural space through soft tissue, then the surgeon may optionally only use the needle **130** and needle stylet **132** illustrated in FIG. 9. The surgeon inserts the stylet **132** through the needle lumen and then uses the needle **130** and stylet **132** combination to penetrate the soft tissue to create the first access point. The surgeon then removes the stylet **132** and inserts the guide wire assembly **28** through the needle lumen, as shown in FIG. 11. Once the guide wire assembly **28** is inserted through the first access point, the surgeon removes the needle **130**, leaving only the

16

guide wire assembly **28**. The surgeon then performs the following steps, similar to if the drill **34** was used to create the first access point, as described above. In particular, the surgeon then insures that the introducer stylet **178** is housed within the introducer lumen. The combination introducer **172** and introducer stylet **178** are then fed over the guide wire assembly **28** penetrating the first access point so that the introducer and introducer stylet penetrate through the first access point, as shown in FIG. 15. The surgeon then removes the guide wire assembly **28** from the introducer **172** and introducer stylet **178** combination by pulling the guide wire assembly **28** distally through the introducer stylet lumen. The surgeon removes the introducer stylet **178**, leaving only the introducer **172** at the first access point.

The surgeon next creates a second access point at the patient's thoracic region **20**. As should be appreciated, the surgeon may first create an access point at the thoracic region and then create an access point at the lumbar region, or vice-versa. Reference to first and second access points is not intended to imply that one access point must be surgically performed before another access point.

The surgeon will prepare the surgical area on the patient at approximately T4 or T5 in the thoracic region **20**. Once the surgeon identifies a preferred second access point, the surgeon inserts the combined cannula **32** and trocar **42** onto the lamina. Similar to the lumbar region **18** and creation of the first access point with the drill **34**, the surgeon removes the trocar **42** from the cannula **32** and inserts the drill **34** and the drill stylet **70** into the cannula lumen. The surgeon then advances the drill **34** through the lamina to create the second access point. In embodiments that set the drill at advancement of 1 mm based on a single 360 degree rotation of the drill handle **66**, the surgeon will normally advance the drill in 1 mm increments. Advancement of the drill is substantially similar to the steps described above for the lumbar region. Upon drilling through, or almost through, the lamina, the surgeon may choose to advance the drill in 0.25 mm increments using the incremental drill adjuster **36**, as described above. Once the epidural space is identified, the surgeon will then use a blunt probe (not shown) to test for the epidural space or use the drill stylet **70**, as described above for the lumbar region **18**.

After the surgeon creates the second access point at the thoracic region **20**, the surgeon removes the drill **34** and drill stylet **70** from the cannula lumen, leaving the cannula **32** on the lamina. At this next step, the surgeon inserts the guide wire assembly **28** through the cannula **32**, into the second access point, and into the epidural space at the thoracic region **20**. In some circumstances, the surgeon may have difficulty in inserting the guide wire assembly **28** through the cannula **32** and into the epidural space. In particular, the angle of insertion through the second access point and into the epidural space may not allow for easy insertion. In such circumstances, the surgeon may insert one of the plurality of first angiocaths **180** through the cannula lumen. As noted above, the system **24** of embodiments of the invention includes the plurality of first angiocaths **180**, with each angiocath having a proximal end with a different angle of curvature. Under X-ray, the surgeon will be able to view the required angle of curvature. Upon inserting the first angiocath **180** into the epidural space, the surgeon inserts the guide wire assembly **28** through the angiocath lumen, as shown in FIG. 14 (note that for ease of illustration, FIG. 14 does not illustrate the first angiocath **180** into the cannula lumen, as described above). The guide wire assembly **28** is inserted with the magnet **150** at the proximal end, so that the magnet **150** is inserted first through the first angiocath **180**.

17

The first angiocath's proximal end then assists in positioning the guide wire assembly **28** into the epidural space and axially through the spinal column. The surgeon then uses the first angiocath **180** to direct the guide wire assembly **28** into the midline of the thoracic epidural space. Once the guide wire assembly **28** is in place, the surgeon removes the first angiocath **180**.

Returning to the lumbar region **18**, recall that the introducer **172** alone is positioned at the first access point. The guide wire assembly **28** has been removed from the introducer **172**. At this point, the surgeon inserts the guide wire receiver **30** through the introducer lumen and into the first access point. Operating under X-ray, the surgeon advances the guide wire assembly **28**, which is inserted through the second access point at the thoracic region **20**, towards the guide wire receiver **30** inserted through the first access point at the lumbar region **18**. The surgeon uses the guide wire receiver **30** to catch the guide wire assembly **28** being pushed from the thoracic end **20** and towards the lumbar end **18**, as shown in FIG. **18**. The sidewalls **168** of the scoop **166** of the guide wire receiver **30** surround and hold the magnet **150** of the guide wire assembly **28** within the scoop **166** as the surgeon advances the guide wire assembly **28** into the semi-cylindrical body section **162** of the guide wire receiver **30**.

In some instances, the surgeon may have difficulty catching the guide wire assembly **28** with the scoop **166** alone. In such circumstances, the surgeon inserts one of the plurality of second angiocaths **182** through the guide wire receiver lumen, as shown in FIG. **19**. Recall that the second angiocath **182** has the proximal end provided with the magnet **184**. When the proximal end of the second angiocath **182** extends outside the guide wire receiver lumen (e.g., when the magnet **184** is proximate the scoop **166**), the magnet **184** on the second angiocath **182** is magnetically attracted to the magnet **150** on the guide wire assembly **28**. Upon the two magnets **150,184** magnetically coupling, the surgeon can pull the second angiocath **182** distally from the guide wire receiver **30** to position the proximal end of the guide wire assembly **28** within the scoop **166** and into the guide wire receiver lumen. Once the guide wire assembly **28** is captured within the guide wire receiver **30**, the surgeon pulls the guide wire receiver **30** distally from the introducer lumen to pull the guide wire assembly **28** distally through the first access point. The surgeon thus removes the guide wire receiver **30** from the introducer lumen, leaving only the introducer **172** fed over the guide wire assembly **28**. At this time, the guide wire assembly **28** extends through the patient's spinal column and both of the first and second access points.

Working at the lumbar region **18**, the surgeon next cuts the proximal end **152** of the guide wire assembly **28** external to the first access point proximal the magnet **150**. In essence, the surgeon cuts the magnet **150** off of the guide wire assembly's proximal end **152**. Due to the relatively small diameter of the guide wire assembly **28**, the surgeon can easily cut through the guide wire sleeve **148** and guide wire **146** with surgical scissors or wire cutters. Once the magnet **150** is cut off the guide wire assembly **28**, the guide wire **146** internal to the guide wire sleeve **148** is exposed. The surgeon removes the guide wire **146** from the sleeve **148** to leave only the guide wire sleeve **148** extending through the patient's spinal column. Note that in embodiments of the invention, a distal end of the guide wire assembly **28** is not closed, such that the guide wire **146** within the guide wire sleeve **148** is exposed. Therefore, the surgeon may remove the guide wire **146** from either the lumbar **18** or thoracic ends **20** of the patient's back. In alternative embodiments

18

where the guide wire assembly **28** is closed at the distal end, the surgeon cuts the guide wire assembly proximate the distal end to expose the guide wire **146** within the sleeve **148**, as is done for the proximal end **152**, in the event the surgeon desires to remove the guide wire **146** from the sleeve **148** via the thoracic end **20**.

The surgeon then feeds the monofilament **186** through the guide wire sleeve **148** from the lumbar end **18** and to the thoracic end **20**. Once the monofilament **186** is fed through the guide wire sleeve **148**, the monofilament **186** extends through the patient's spinal column **22** and external both the first and second access points. The surgeon then removes the guide wire sleeve **148** from the patient's spinal column through either the first or second access point. The guide wire sleeve **148** provides a sufficient stiffness through the epidural space to allow the monofilament **186** to be positioned in the epidural space. At this time, the monofilament **186** is positioned through the first access point, through the epidural space of the patient's spinal column, and through the second access point at the thoracic region **20**.

The surgeon is now ready to insert the spinal cord stimulator **10** into the patient's epidural space. As discussed above, the stimulator **10** may have a plurality of leads **12** (otherwise known as an array of leads) that is one or more electrodes. Each lead **12** is attached to a lead wire **14** that is eventually coupled with the IPG **16**. To feed each lead **12** through the epidural space of the patient's spinal column **22**, the surgeon uses the connector **188** to connect the lead **12** with the monofilament **186**. In instances where more than one lead **12** is used, the surgeon may insert multiple monofilaments **186** through the epidural space, so that each lead **12** is individually coupled with a monofilament **186**. It should be appreciated that in embodiments of the invention, there is a one-to-one ratio of leads to monofilaments. It is common for the surgeon to place a plurality of leads through the epidural space, and therefore, embodiments of the invention contemplate positioning a plurality of monofilaments through the epidural space. Note that in alternative embodiments, one lead wire **14** may be connected to a plurality of leads **12**.

Working at the lumbar region **18**, the surgeon couples an end of each lead **12** of the stimulator **10** to the exposed end of the monofilament **186** using the connector **188**. As shown in FIG. **20**, the end of the lead **12** is inserted through one end of the connector **188** and held via a friction fit, and the end of the monofilament **186** is inserted through the other end of the connector **188** and held via a friction fit. The surgeon may choose to permanently couple the connector **188** with the lead **12** of the stimulator **10** and the monofilament **186** by applying a small amount of adhesive to each end of the connector and the coupled lead/monofilament. Once the monofilament **186** is coupled with the lead **12** via the connector **188**, the surgeon then turns to the thoracic region **20**. The surgeon pulls the exposed monofilament **186** at the thoracic end **20** distally to pull the monofilament **186** through the epidural space. This in turn pulls the lead **12** connected to monofilament **186** through the epidural space. The surgeon is able to position the lead **12** within the desired location of the spinal column **22** by pulling the monofilament **186** from the thoracic end **20**.

As noted above, there may be multiple leads with multiple wires, and therefore, multiple monofilaments. Once each monofilament is coupled to its respective lead, and each lead is positioned within the epidural space, the surgeon excises the skin at the lumbar region and removes the introducer **172** located at the first access point. The surgeon then applies a sylvastic anchor (not shown) to secure the lead wire **14** at the

19

patient's lumbar region. The surgeon prepares a pocket in the patient's lumbar region for the IPG **16**, connects the first access point and the pocket for the IPG with a tunneling instrument (not shown), pulls the lead wire **14** through the tunneling instrument, and connects the lead wire to the IPG. As discussed above, the IPG **16** controls application of voltage to the leads **12**, and the signal is sent through the lead wire **14**.

The surgeon then turns to the thoracic region **20** to secure the exposed monofilament **186**. Similar to the lead wire at the lumbar end **18**, the surgeon trims the monofilament **186** as needed. However, the surgeon leaves an exposed monofilament, referred to as a tension relief portion. The surgeon will use this exposed tension relief portion to move the lead **12** within the epidural space during the patient's ongoing use of the stimulator **10**. Prior to securing the tension relief portion within an excised portion of skin in the patient, the surgeon removes the cannula **32**. To secure the tension relief portion, the surgeon forms a loop or otherwise gathers the exposed tension relief portion. The surgeon excises the skin at the thoracic end and prepares a pocket for securing the exposed tension relief portion. The surgeon secures the tension relief portion using sylvastic anchors (not shown). Thus, the lead is secured, via the monofilament, at the thoracic end of the patient.

In embodiments of the invention, the surgeon can move the lead(s) within the epidural space by gathering or releasing either or both of the lead wire(s) **14** connected to the leads **12** at the lumbar region **18** or the monofilament(s) **186** at the thoracic region **20**. Because each percutaneous lead **12** is coupled to its respective monofilament **186** at the thoracic end **20**, and the lead wire **14** is coupled to the lead **12** at the lumbar end **18**, the leads will not move axially within the epidural space once the lead wire and monofilament are secured with the anchors. However, the surgeon can move the lead within the epidural space as desired.

Although the invention has been described with reference to the embodiments illustrated in the attached drawing figures, it is noted that equivalents may be employed and substitutions made herein without departing from the scope of the invention as recited in the claims. Having thus described various embodiments of the invention, what is claimed as new and desired to be protected by Letters Patent includes the following:

Having thus described various embodiments of the invention, what is claimed as new and desired to be protected by Letters Patent includes the following:

1. A drill assembly for accessing bone, comprising:
 - a cannula having a handle and a hollowed cannula shaft coupled to and extending from the handle, wherein the hollowed cannula shaft presents a cannula lumen;
 - a drill having a drill handle and a hollowed drill shaft presenting a drill lumen,
 - wherein the drill shaft has proximal and distal ends, wherein a drill bit is provided on the proximal end of the shaft,
 - wherein the drill shaft is configured to be inserted in the cannula lumen; and
 - an incremental drill adjuster at least partially mounted within the handle of the cannula and configured to advance the drill shaft by a pre-set distance,
 - wherein the incremental drill adjuster includes a spring-loaded ball detent having a spring and a ball positioned proximate the spring and operable to act against the spring to retract the spring.

20

2. The drill assembly of claim 1, wherein the spring and ball are located in the cannula handle.
3. The drill assembly of claim 2, wherein the distal end of the drill shaft includes a plurality of formed adjacent detents, wherein a portion of the ball of the spring-loaded ball detent is configured to rest in one of the plurality of adjacent detents, such that incremental adjustment of the drill relative to the cannula results in the ball being advanced proximally to one of the plurality of formed adjacent detents.
4. The drill assembly of claim 3, wherein the handle of the cannula includes a hollowed portion to present a chamber for receipt of the ball and the spring, wherein the chamber is covered with a cap, wherein an end of the spring is secured to an inside of the cap.
5. The drill assembly of claim 4, wherein the drill handle is configured to receive a force applied by a user to actuate the incremental drill adjuster, such that application of a sufficient adjustment force against the drill handle overcomes a force of the spring and retracts the ball into the chamber.
6. The drill assembly of claim 5, wherein upon the ball being retracted into the chamber, the drill is configured to be incrementally adjusted proximally by a length of at least one of the plurality of detents formed in the drill shaft.
7. The drill assembly of claim 1, further including a drill stylet having a drill stylet handle and a drill stylet shaft, wherein the drill stylet shaft is configured to be fed through the drill lumen, wherein the drill stylet handle includes left and right side walls.
8. The drill assembly of claim 7, wherein the drill handle has a cutout formed in the handle for receipt of a portion of the drill stylet handle, wherein the cutout includes a seat and left and right side walls extending distally from the seat, wherein the cutout further includes a notch extending proximally from the seat.
9. The drill assembly of claim 8, wherein a bottom of the drill stylet handle is complementally shaped to be received within the cutout in the drill handle and seated against the seat of the drill handle, wherein the left and right side walls of the cutout in the drill handle are complementally shaped to fit and receive the left and right side walls of the drill stylet handle.
10. The drill assembly of claim 9, wherein the drill stylet handle is rotatable approximately 90 degrees about a stylet shaft axis, wherein upon rotation of approximately 90 degrees of the drill stylet handle, a bottom of the drill stylet handle is sized and configured to be received within the notch of the drill handle, such that a length of the drill stylet shaft is external to a proximal-most end of the drill shaft.
11. A drill assembly for accessing bone, comprising:
 - a cannula having a handle and a hollowed cannula shaft coupled to and extending from the handle, wherein the hollowed cannula shaft presents a cannula lumen;
 - a drill having a drill handle and a hollowed drill shaft presenting a drill lumen,
 - wherein the drill shaft has proximal and distal ends, wherein a drill bit is provided on the proximal end of the shaft,

21

wherein the drill shaft is configured to be inserted in the cannula lumen,
 wherein the drill handle is rotatable approximately 90 degrees with respect to the cannula handle;
 a drill stylet having a drill stylet handle and a drill stylet shaft,
 wherein the drill stylet shaft is configured to be fed through the drill lumen,
 wherein the drill stylet handle is rotatable approximately 90 degrees with respect to the drill handle; and
 an incremental drill adjuster at least partially mounted within the handle of the cannula and configured to advance the drill shaft by a pre-set distance,
 wherein the incremental drill adjuster includes a spring-loaded ball detent having a spring and a ball positioned proximate the spring and operable to act against the spring to retract the spring.
 12. The drill assembly of claim 11, wherein the drill is configured to be incrementally advanced upon application of a rotational force by a user.
 13. The drill assembly of claim 11, wherein the spring and ball are located in the cannula handle.
 14. The drill assembly of claim 13, wherein the distal end of the drill shaft includes a plurality of formed adjacent detents,
 wherein a portion of the ball of the spring-loaded ball detent is configured to rest in one of the plurality of adjacent detents, such that incremental adjustment of the drill relative to the cannula results in the ball being advanced proximally to one of the plurality of formed adjacent detents.
 15. The drill assembly of claim 14, wherein the handle of the cannula includes a hollowed portion to present a chamber for receipt of the ball and the spring,
 wherein the chamber is covered with a cap,
 wherein an end of the spring is secured to an inside of the cap.
 16. The drill assembly of claim 15, wherein the drill handle is configured to receive a force applied by a user to actuate the incremental drill adjuster, such that application of a sufficient adjustment force against the drill handle overcomes a force of the spring and retracts the ball into the chamber.
 17. The drill assembly of claim 16, wherein upon the ball being retracted into the chamber, the drill is configured to be incrementally adjusted proximally by a length of at least one of the plurality of detents formed in the drill shaft.
 18. The drill assembly of claim 11, wherein the drill handle has a cutout formed in the handle for receipt of a portion of the drill stylet handle,

22

wherein the cutout includes a seat and left and right side walls extending distally from the seat,
 wherein the cutout further includes a notch extending proximally from the seat.
 19. The drill assembly of claim 18, wherein the drill stylet handle includes left and right side walls,
 wherein a bottom of the drill stylet handle is complementally shaped to be received within the cutout in the drill handle and seated against the seat of the drill handle,
 wherein the left and right side walls of the cutout in the drill handle are complementally shaped to fit and receive the left and right side walls of the drill stylet handle.
 20. The drill assembly of claim 19, wherein the drill stylet handle is rotatable approximately 90 degrees about a stylet shaft axis,
 wherein upon rotation of approximately 90 degrees of the drill stylet handle, a bottom of the drill stylet handle is sized and configured to be received within the notch of the drill handle, such that a length of the drill stylet shaft is external to a proximal-most end of the drill shaft.
 21. A drill assembly for accessing bone, comprising:
 a cannula having a handle and a hollowed cannula shaft coupled to and extending from the handle, wherein the hollowed cannula shaft presents a cannula lumen;
 a drill having a drill handle and a hollowed drill shaft presenting a drill lumen,
 wherein the drill shaft has proximal and distal ends,
 wherein a drill bit is provided on the proximal end of the shaft,
 wherein the drill shaft is configured to be inserted in the cannula lumen,
 wherein the drill handle is rotatable approximately 90 degrees with respect to the cannula handle;
 a drill stylet having a drill stylet handle and a drill stylet shaft,
 wherein the drill stylet shaft is configured to be fed through the drill lumen,
 wherein the drill stylet handle is rotatable approximately 90 degrees with respect to the drill handle,
 wherein the drill handle has a cutout formed in the handle for receipt of a portion of the drill stylet handle,
 wherein the cutout includes a seat and left and right side walls extending distally from the seat,
 wherein the cutout further includes a notch extending proximally from the seat; and
 an incremental drill adjuster associated with one of the cannula and the drill and configured to advance the drill shaft by a pre-set distance.

* * * * *