




US 20100037390A1

(19) **United States**(12) **Patent Application Publication**
Hoernig et al.(10) **Pub. No.: US 2010/0037390 A1**(43) **Pub. Date: Feb. 18, 2010**(54) **BATH SYSTEM****Publication Classification**(76) Inventors: **Victor Hoernig**, Lowell, IN (US);
Charles A. Patterson, Durango,
CO (US); **Man Ki Yoo**, Morton
Grove, IL (US)(51) **Int. Cl.**
A47K 3/00 (2006.01)(52) **U.S. Cl.** **4/613**

Correspondence Address:

Carlson, Gaskey & Olds/Masco Corporation
400 West Maple Road, Suite 350
Birmingham, MI 48009 (US)(21) Appl. No.: **12/533,094**(22) Filed: **Jul. 31, 2009****Related U.S. Application Data**(60) Provisional application No. 61/189,054, filed on Aug.
15, 2008.(57) **ABSTRACT**

According to the invention, a bathing environment, such as a shower or a tub, has an entry way that does not encumber entry or exit from a bathing environment. The bathing environment has a drain in the entry way so that the entry way remains substantially level so that a user encounters no threshold if entering or exiting said bathing environment. The drain has a channel in the entry way for collecting water that flows to it, and a cover over the channel. The environment has a floor that slopes gently to the channel so that water is directed to the channel for removal therefrom.






FIG. 1




FIG. 2




FIG. 3




FIG.4




FIG.5




FIG.6




FIG.7




FIG. 8





FIG. 8A






FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG.15

BATH SYSTEM

REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to U.S. Provisional Application No. 61/189,054 filed Aug. 15, 2008. Cross reference is made to copending U.S. patent applications Ser. No. _____ entitled “Bath System” (Attorney Docket No. 136-3125-U; 60137-581 PUS1); Ser. No. _____ entitled “Bath System” (Attorney Docket No. 136-3127-U; 60137-581 PUS3); Ser. No. _____ entitled “Bath System” (Attorney Docket No. 136-3128-U; 60137-581 PUS4); Ser. No. _____ entitled “Bath System” (Attorney Docket No. 136-3129-U; 60137-581 PUS5); Ser. No. _____ entitled “Bath System” (Attorney Docket No. 136-3130-U; 60137-581 PUS6); Ser. No. _____ entitled “Bath System” (Attorney Docket No. 136-3131-U; 60137-581 PUS7).

BACKGROUND OF THE INVENTION

[0002] Bath showers and tubs have many features. Some baths and showers include seats and benches. Some seats are fixed to the interior of tubs and showers. Other seats are arranged on slides to allow a user to, in essence, ride the seat from the exterior of a tub to the interior of the tub and back.

[0003] Showers typically have a threshold over which a user must step to enter into a shower. The threshold typically serves to keep water from escaping from the shower.

[0004] Some bath and shower fixtures attach grab bars thereto to provide hand holds for users.

[0005] Both shower and shower/bath fixtures use doors, typically glass, and curtains, typically plastic, to keep water from escaping from the shower enclosure during use.

[0006] Some bath and shower units provide shelves for storage of bath materials such as soap, shampoo, toys and the like.

SUMMARY OF THE INVENTION

[0007] According to the invention, a bathing environment, such as a shower or a tub, has an entry way that is designed to present no encumbrances to entry or exit from a bathing environment. The bathing environment has a drain in the entry way so that the entry way remains substantially level so that a user encounters no threshold if entering or exiting said bathing environment.

[0008] According to an embodiment of the invention, the drain has a channel in the entry way for collecting water that flows to it, and a cover over the channel.

[0009] According to an embodiment of the invention, the environment has a floor that slopes gently to the channel so that water is directed to the channel for removal therefrom.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] These and other features of the present invention can be best understood from the following specification and drawings, the following of which is a brief description.

[0011] FIG. 1 illustrates a plan view of a shower surround;
[0012] FIG. 2 is a schematic sectional view of a handheld showerhead mounted to a handrail;

[0013] FIG. 3 illustrates a top perspective view of a shower surround;

[0014] FIG. 4 illustrates a shower surround according to another non-limiting embodiment;

[0015] FIG. 5 illustrates an embodiment of the shower chair of FIG. 4;

[0016] FIG. 6 illustrates another schematic embodiment of the shower chair shown in FIG. 4;

[0017] FIG. 7 illustrates a plan view of another embodiment of a shower chair shown in a shower surround;

[0018] FIGS. 8, 8A and 8B illustrate a shower surround showing an embodiment of a shower bench;

[0019] FIG. 9 illustrates a top view of a shower surround of FIG. 8;

[0020] FIG. 10 illustrates a plan view of a tub surround;

[0021] FIG. 11 illustrates another plan view of a shower and tub surround;

[0022] FIG. 12 illustrates a top plan view of the shower and tub surround of FIG. 11;

[0023] FIG. 13 illustrates a perspective view of an embodiment of a shower and tub surround including a storage compartment;

[0024] FIG. 14 illustrates a perspective view of an embodiment of a the storage compartment of FIG. 13; and

[0025] FIG. 15 illustrates a phantom view of the storage compartment of FIG. 14;

DETAILED DESCRIPTION

[0026] Referring now to FIGS. 1 and 2, a shower surround 20 that includes a pair of grab bars 25(a-b) against a back wall 30 of the shower, a grab bar 35 at each end wall 40 of the shower, a floor 45 incorporating a zero threshold drain 50, a knee wall 55 in the back wall 30 of the shower and a pair of shower doors 60 is illustrated. A fixed showerhead 63 may also be provided in or above one end of the shower surround 20.

[0027] At the back wall 30 of the shower 20, there is a vertically placed grab bar 25a and a cathedral shaped grab bar 25b. Similarly, grab bars 35 are placed on end wall 40 to provide hand holds for a user. The cathedral shaped grab bar 25b is placed in a recess 70 in the back wall 30, the cathedral-shaped grab bar having a bottom portion 75, two upwardly extending leg portions 80, and an arcuate section 85 connecting the tops of the two leg portions is placed therein. The grab bars are attached to end and side walls 30, 40 by means known in the art by mounts 102 (see FIG. 2).

[0028] As may be seen in FIG. 1, a hand-held shower head is appended to the cathedral shaped grab bar 25b to enable a user to hold a shower head in the desired position and wash himself as will be described hereinbelow. The hand-held shower head may also be appended to grab bars 35 and 25a.

[0029] Referring now to FIG. 2, it is seen that the hand-held shower head 90 is held by conventional means (93) on a bracket 95 which has a clamping mechanism 100. The clamping mechanism creates a friction fit with a grab bar and be either a flexible plastic piece having legs 101 that will grasp the grab bar and be flexible enough to be removed from the grab bar and still grab the grab bar, or a screw-down mechanism 102, as is known in the art, that will hold the bracket in place on the cathedral-shaped grab bar 25b (or other grab bar 25 having a same diameter as grab bar 25b) so that the bracket may be disposed in any position a user deems necessary along that grab bar. The clamping mechanism 100 engages at least partially around handrail 25b so as to permit movement of the legs 101. That is, the handheld showerhead 90 may slide from post to post around the entirety of the handrail/grab bars 25b to thereby position the handheld showerhead 90 at any position. If a user wishes to position the handheld showerhead 90 around a second pair of posts 90, the clamping mechanism 102 must be detached and reattached therearound. By

appending the hand-held to the cathedral-shaped grab bar, a user may then place the shower head in the ideal place to wash and rinse herself. It should be understood that the handrail may be configured with particular radiuses and shapes, even in the z-axis (see FIG. 3) so as to permit this slideable movement. Furthermore, it should be understood that the handrail/grab bars 25, 35 may be of various configurations, shapes, orientations, and arrangements other than that illustrated herein to place the grab bar 25b both ideally to support a user and to place a shower head. The arcuate section 85 may extend into the shower 20 (see FIG. 3).

[0030] By integrating the shower head with the grab bars, a user may understand that he can hold the shower head support if desired while manipulating the shower head because the shower head support is the grab bar.

[0031] Referring now to FIG. 3, the shower surround 20 includes the floor 45 that inclines slightly towards the integral drain 50 that is flush with the floor 45 of the shower and the floor 105 of the bathroom. The incline is slight so a wheel chair will not be impeded by the steepness of incline if entering the shower surround. The drain 50 has a plurality of slots and grooves 110 that are roughly transverse to an axis 115 of the drain so that water flowing from the shower floor 45 does not have a straight path to the bathroom floor 105 to minimize flow from the shower to the bathroom floor 105. The drain and floor 45 create no threshold barrier that a user has to step over or that would likely impede access or egress to the shower 20. One of ordinary skill in the art will recognize that the slots 110 may have different shapes or frequency to minimize the flow of water from the floor 45 to floor 105 of the bathroom.

[0032] Referring to FIGS. 4 and 5, an embodiment of a chair 125 that is designed for use in the shower 20 are shown. The chair 125 shown in FIG. 4 is comprised of a seat 130, a seat back 135, a stabilizing bracket 140, a spring 143 attached to the stabilizing bracket 140, a pair of legs 150, a weight distribution support 155 and support arms 160.

[0033] The stabilizing bracket 140 is attached to the upper back 165 of the seat back 135 (see FIG. 5) by conventional means like screws or brads (not shown) or is integral therewith (see FIG. 6). The brackets have an arcuate portion 170 that has a diameter that is greater than a diameter of grab bars 35 and that curves less than 180° so that the bracket 140 and the chair 125 thereby are removably attached to the grab bars 25a, 25b, or 35. The brackets do not support the weight of a user but serve to prevent the chair 125 from tipping forward. The spring 143 is also attached to the bracket or is integral therewith and tends to resist force that pushes the spring back to the bracket. The weight of the user is transferred from the seat 130 to the floor 45 via legs 150 and weight distribution support 155.

[0034] The seat back is attached to the legs 150 by means of support arms 160 which attach to the seat back below the stabilizing bracket 140 by conventional means and attach to a mid portion 175 of legs 150 also by conventional means. The seat has a pair of downwardly depending flanges 180 which conventionally attach to the legs 150 while allowing the seat to pivot thereabout. The legs 150 conventionally attach at their lower end to the weight distribution support 155 that serves to distribute the weight of a user across a greater area of the shower floor 45 to minimize the ends of the legs from damaging the floor 45.

[0035] The chair 125 is made of water resistant material like plastic, wood or metal. As shown in FIG. 5, the seat has a plastic seat with a water-resistant foam top for user comfort.

The chair 125 shown in FIG. 7 is all plastic with slots 182 to allow for water run-off and quick drying. Also, the slots 182 in seat 125 are hygienically designed to allow a user to wash his or her undersides (not shown) without undue movement by directing spray from under the seat to that underside area. The slots tend to be wider at a user's underside portions to allow cleaning thereof.

[0036] To use the chair, one places the bracket 140 over a grab bar 25 while depressing the spring 143 to allow the grab bar 35 to nestle within the arcuate portion 170, locates the weight distribution support 155 and flips down the seat 130. When not in use, a user simply flips up the seat 130 and leaves the chair in place. If more space is necessary, or the chair needs cleaning, a user simply flips up the seat and, because of the dimensions of the arcuate portion 170, simply depresses the spring 143 and lifts the chair and the bracket 140 up over the bar for removal. The spring minimizes the probability that the chair will be pushed off the bracket when it is not intended to remove the chair. If the chair is lifted or pushed upwardly, the spring catches the grab bar 35 and prevents removal of the chair from the grab bar. One of ordinary skill in the art will recognize that other types of devices such as clamps, flexible over-center grips and the like may be used to prevent the removal of the chair if not desired by a user.

[0037] Referring now to FIG. 7, another embodiment of a chair is shown. Similar to FIGS. 4-6, the chair 125 is comprised of a seat 130, a seat back 135, and a stabilizing bracket 140.

[0038] However, the seat back also has: a pair of legs 150 whereby the seat back and legs are integrally formed; pair of horizontally disposed flanges 185 extending therefrom; and a plurality of horizontal slots 190 that increase in width from the top of the seat back to the bottom thereof both to allow water to drain and to present an appealing design. The legs 150 are wider at the bottom to distribute the weight of a user across a greater area of the shower floor 45 to minimize damage thereto. The seat 130 is conventionally attached to the flanges 185 to allow the seat to pivot upwardly. The stabilizing bracket 140 acts like the seat bracket as shown in FIGS. 4-6. It does not support the weight of a user and allows for easy removal of the chair from the any of the grab bars at the appropriate height, e.g., 25b, 35, because the arcuate portion 170 of the stabilizing bracket is less than 180° and has a diameter that is greater than the diameter of the grab bars as stated herein above.

[0039] Referring now to FIG. 8, a shower surround 195 according to another non-limiting embodiment is illustrated. The shower surround 195 includes a zero threshold drain 50, a knee-wall 205, a bench seat 210, and a pedestal 215 disposed at the front of the shower surround.

[0040] Referring now to FIG. 9, a top view of the shower surround of FIG. 8 is shown. The pedestal 215 is essentially a rectangular solid, but as one of ordinary skill in the art will recognize, the pedestal may have other shapes and decorative features so long as it can support the bench seat 210. The pedestal may be either permanently affixed to the shower floor 45 or may be removable therefrom to enable a user to have more room in the shower 195. The knee wall may have a longitudinal portion 220 that juts away from the back wall 225 and the rest of the knee wall so that bench seat 210 is supported by the longitudinal area 220 and the pedestal 215. The pedestal may also fit in groove 227 shown in FIG. 8. FIG. 9 also shows a slot 320 in which a shower curtain may slide to

minimize water splashing out of the shower if the hinge **222** for bench seat **210** is attached to the bench seat and a tub wall (not shown).

[0041] The bench seat may either sit on the longitudinal portion **220** of the knee wall and the pedestal **215** and thereby be easily removed from the shower surround **195** if desired, or may be fixedly hinged as shown in FIG. 9 or hinged via an integrated, arcuate portion **230** that fits into a corresponding arcuate recess **231** in pedestal **215** and knee-wall **205**. The arcuate recess **231** is less than 180° so that the parts can be easily separated. One of ordinary skill can appreciate that the arcuate portion and arcuate recess can be in either of the seat or the knee-wall and the pedestal. A user would then be able to flip the bench seat up (or down) and out of the way, or removed by separating the pieces **230** and **231** from each other, if more space is desired. As with other seats disclosed herein, the seat may be slotted to allow for hygiene and water runoff; padded for user comfort; and, have other decorative and functional features. Also as noted herein, the bench seat **210** may be manufactured of wood, metal or other suitable material.

[0042] The bench seat **205** is generally flush with a pedestal **215** when flipped down (FIG. 8) or on top of the pedestal (see FIG. 8a) to allow a user to easily slide his bottom across the pedestal and sit on the bench seat **205**.

[0043] Referring to FIGS. 8 and 8(b), there are typically shower curtains (not shown) or doors **240**, **245** to minimize splashing or other flows of water onto the bathroom floor. Door **240** is either a single panel or a bi-fold that prevents the flow of water onto the bathroom floor between the shower sidewall away from the bench seat. The other door **245** covers area at the back of the shower closest to the bench seat so that a user or an aide may have easy access to the bench seat. Door **245** typically has a narrower width than door **240**. The door **240**, if a bi-fold, facilitates access into the shower surround **195** while a swing out door **245** is located adjacent the bench seat **205**. The doors **240**, **245** are readily accessed from a seated position. For instance, a user can open door **245** and door **240** from a wheelchair, slide himself across to bench seat **205**, reach to close door **245** which is close because of its relatively short horizontal width and grasp a bar **290** disposed on the bi-fold door **240** and pull door **240** closed. The user is now free to use the close controls **295**.

[0044] According to an embodiment of this invention, the door **245** need only extend down to a top **298** of the pedestal thereby reducing the weight and cost of the door. In this embodiment, the pedestal and the shorter door cooperate to minimize water escaping from the shower surround.

[0045] Referring now to FIG. 10, a shower/bath enclosure **300** is shown. The enclosure **300** includes an integral access bench **305** which extends from an outside wall **310** of the enclosure **300**. The integral access bench is about 18" high to accommodate the usual height of wheel chairs which tend to be between 17 and 19 inches in height. The shower/bath enclosure is shown here as a shower but may also be used as a tub (see dotted lines **313** in FIG. 10). The enclosure may further include a flip-up seat **315** as is taught herein. The access bench **305** is shown as an integrally molded portion having a half-circular sitting area **325**. One of ordinary skill in the art will recognize that the access bench may be of different sizes and shapes to improve the esthetics and functionality thereof as long as the access bench allows a user to sit on the bench, pivot, and slide over to the bench seat while lifting ones legs over the surround wall, if any, and thereby be

enabled to use the shower. One of ordinary skill in the art will also recognize that the doors **240**, **245** may also be used herein instead of a shower curtain to enable a user to take advantage of the short door **245** and the door **240** and still have easy access to both as taught hereinabove. Also, the slots **182** in seat **315** are hygienically designed to allow a user to wash his or her bottom area (not shown) without undue movement by directing spray from under the seat to that bottom area.

[0046] Referring now to FIGS. 11 and 12, a tub surround **350** is illustrated and includes a transfer bench **355**, a head rest/pillow **360**, and armrests **365**. Arm rests **365** jut inwardly towards the interior of the tub surround **350** from front wall **370** and back wall **380**, and a sloping back rest **385**. The head rest/pillow **390** is attached to a top portion **395** (see FIG. 12) of the back rest **385**. A seat **400** has a pair of side arms **405** that attach to the front wall **370** and back wall **380** by conventional means **410** so that the seat **400** may pivot up and out of the way if more room is desired in the tub surround **350**. The seat **400** also has a pair of downwardly displaced flanges **403** that rest on the armrests **365**. The arm rests **365** also function as a support of the seat **400** via the flanges **403** when the seat is not pivoted up and if the user desires to sit thereupon. The arm rests and seat cooperate so that, when the seat is pivoted down, the seat is essentially flush with the front wall **370** so a user can slide across the front wall onto the seat if desired.

[0047] The arm rests **365** are contoured to mimic a comfortable position for a user's arms and, therefore, one will recognize that one of ordinary skill in the art may choose other shapes and contours as long as the arm rests conform with the seat to provide a surface that is comfortably flush with the front wall **370**. The side arms **405** of the seat **400** extend past the sides of a pillow **360** when the seat is pivoted down so that the pillow **390** can be placed in an ideal position behind the seat (see FIG. 11) to support a user's head when the seat is pivoted upwardly and not interfere with the seat when the seat is pivoted downwardly atop the arm rests **365**.

[0048] The seat **400** may be spaced from the front wall **370** by a dimension that allows a shower curtain room to pass between the front wall and the seat to minimize an amount of water from escaping from the tub surround **350** (see FIG. 9). One of ordinary skill in the art will also recognize that the doors **240**, **245** as shown in FIGS. 8 and 8(b) may also be used herein instead of a shower curtain to enable a user to take advantage of the functionality of the doors **245** and **240** and still have easy access to the shower surround as taught hereinabove.

[0049] Referring to FIGS. 13-15, a tub and shower surround **425** according to another non-limiting embodiment is illustrated. Because the front wall **430** is relatively low, about 14 inches high, as compared to a normal tub having a wall that is about 18 inches high, to allow easier access to the tub and shower surround **425**, water may not cover a user comfortably when bathing especially given the height of normal overflow drains (shown in phantom **435**) placed under a tub spout **430**. Normal overflow drains allow water to be about 13 inches deep in a full tub. According to this invention, overflowing water accesses a drain **440** through a plurality of scuppers **445** across the top of the water side of the side, front or rear walls of the tub and shower surround. Because the scuppers are at the top of the walls beginning about 13 inches from the bottom of the tub, the water in the tub and shower surround is as deep as a normal tub to give a user a comfortable and similar soak even though the front wall is only about 14 inches high. The ratio of the height of a tub wall to the depth of water

in a normal tub is 18 inches to 13 inches or about 1.38. The ratio of the height of a tub wall to the depth of water in the tub of the invention is 14 inches to 13 inches or about 1.08.

[0050] The drain **440** is disposed within a cavity **450** in the front wall **430** (or other wall) of the bath and shower surround and has enough volume to store goods such as soap, shampoo, bath toys and other items deemed necessary or preferable for the bathing experience. The bottom walls **455** of the cavity are sloped towards the drain **440** to allow for complete drainage in the event of an overflow condition. The cavity **440** may have a pivotable cover **460** that closes for esthetics and to give easy access to the tub and shower surround **425**. The cover should be flush with the top of the front wall so as not to provide an impediment to entering or exiting the tub. It should be understood that the cavity **450** may incorporate various other devices such as shower controls, separate handheld showers **455** that may be plumbed into the cavity as is known in the art, soap dispensers, as well as other devices (not shown).

[0051] The adjacent scuppers form a plurality of corbels **465** that are designed to support the cover if it is closed. The cover **465** may be relatively rigid to operate as a transfer seat or other support.

[0052] It should be understood that like reference numerals identify corresponding or similar elements throughout the several drawings. It should also be understood that although a particular component arrangement is disclosed in the illustrated embodiment, other arrangements will benefit herefrom.

[0053] The foregoing description is exemplary rather than defined by the limitations within. Various non-limiting embodiments are disclosed herein, however, one of ordinary skill in the art would recognize that various modifications and variations in light of the above teachings will fall within the scope of the appended claims. It is therefore to be understood that within the scope of the appended claims, the invention may be practiced other than as specifically described. For that reason the appended claims should be studied to determine true scope and content.

What is claimed is:

1. A bathing environment in a room having a floor, said bathing environment comprising:
 - an entry way, said entry way designed to be contiguous to and substantially flush with the floor;
 - a channel in said entry way for collecting water therein; and
 - a cover disposed over said channel such that said entry way cooperates with the floor so that entering or exiting said bathing environment is not encumbered.
2. The environment of claim **1** further comprising:
 - a floor sloping towards said channel so that water in said bathing environment is directed to said channel.
3. The environment of claim **1** further comprising:
 - a drain disposed in said channel for removing water therefrom.
4. The environment of claim **1** wherein said cover further comprises:
 - a plurality of slots that are transverse to a longitudinal axis of said cover so that water flows into said channel.
5. A bathing environment, said bathing environment comprising:
 - an entry way, said entry way being configured so as not to impede entry therethrough;
 - a channel in said entry way for collecting water therein; and
 - a cover disposed over said channel such that said entry way remains substantially level so that a user encounters no threshold if entering or exiting said bathing environment.
6. The environment of claim **5** further comprising:
 - a floor sloping towards said channel so that water in said bathing environment is directed to said channel.
7. The environment of claim **5** further comprising:
 - a drain disposed in said channel for removing water therefrom.
8. The environment of claim **5** wherein said cover further comprises:
 - a plurality of slots that are transverse to a longitudinal axis of said cover so that water flows into said channel more readily than out of said environment.

* * * * *