



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : A61M 15/00</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/45986</p> <p>(43) International Publication Date: 16 September 1999 (16.09.99)</p>
<p>(21) International Application Number: PCT/EP99/01486</p> <p>(22) International Filing Date: 8 March 1999 (08.03.99)</p> <p>(30) Priority Data: 9805102.2 10 March 1998 (10.03.98) GB</p> <p>(71) Applicant (for all designated States except AT): NOVARTIS AG [CH/CH]; Schwarzwaldallee 215, CH-4058 Basel (CH).</p> <p>(71) Applicant (for AT only): NOVARTIS-ERFINDUNGEN VERWALTUNGSGESELLSCHAFT MBH [AT/AT]; Brunner Strasse 59, A-1235 Vienna (AT).</p> <p>(72) Inventor: MOULIN, Claude; Thermenstrasse 5, CH-4310 Rheinfelden (CH).</p> <p>(74) Agent: BECKER, Konrad; Novartis AG, Corporate Intellectual Property, Patent & Trademark Dept., CH-4002 Basel (CH).</p>		<p>(81) Designated States: AL (Utility model), AM (Utility model), AT (Utility model), BG (Utility model), BR (Utility model), BY (Utility model), CN (Utility model), CZ (Utility model), DE (Utility model), DK (Utility model), EE (Utility model), FI (Utility model), GE (Utility model), GH (Utility model), HU (Utility model), JP (Utility model), KE (Utility model), KG (Utility model), KR (Utility model), KZ (Utility model), LS (Utility model), MD (Utility model), MX (Utility model), PL (Utility model), PT (Utility model), RU (Utility model), SK (Utility model), TJ (Utility model), TR (Utility model), TT, UA (Utility model), UG, UZ (Utility model), VN (Utility model), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
<p>(54) Title: POWDER INHALER</p>		
<p>(57) Abstract</p> <p>This invention relates to single dose dry powder inhalers in which medicament is stored in a capsule and is released by piercing the capsule wall with polymer-coated steel pins. Methods of preparation of polymer-coated piercing means and their use in releasing the medicament from the capsule are described.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

POWDER INHALER

This invention relates to single dose dry powder inhalers in which medicament is stored
5 in a capsule prior to release.

It is well-known to pierce capsules with a metal pin or other cutting means in an inhaler.
Capsule-cutting means are disclosed for example in DE 39 27 170 and in EP 528 764.

10 An inhaler for powdered medicaments is described in US patent 3,991,761 (hereafter
referred to as Inhaler A). Inhaler A comprises a recess for receiving a capsule, and
push buttons are provided which carry sharpened metal pins and are held in position by
biasing springs. In use the capsule is pierced by the spring-loaded pins and on release
of the push buttons, the pins retract from the perforated capsule allowing medicament
15 to pass out therefrom.

A problem encountered with known capsule-piercing mechanisms is that the cutting
means, e.g. metal pin, can become adhered to a capsule wall. This prevents complete
release of medicament for inhalation and causes frustration amongst users.

20

The present applicants have sought to overcome this problem, and have found that a
polymer coating applied to the metal pins permits complete release after capsule-
puncture.

25 In one aspect, therefore, this invention provides an inhaler comprising metal capsule-
piercing means which is coated with a polymer.

In another aspect this invention provides the use of polymer-coated metal capsule-
piercing means in an inhaler for faster, more complete and effective release of a
30 medicament.

In accordance with the present invention, piercing means are provided that may have at
least one coating of an inert polymer characterized by (i) excellent antiadhesive

properties, i.e. highly lubricating, properties, for example a polymer having a low friction coefficient, e.g. a friction coefficient (which is defined as the dimensionless quotient obtained by dividing the value of the force necessary to move one body over another at a constant speed by the weight of the body) of at least 0.1 under light loads and (ii)

5 high thermal and chemical inertness. Preferred polymers include any inert polymer, for example fluorocarbon polymers containing $-CF_2-CF_2-$ units, including copolymers thereof, having different terminal groups at the polymer chain ends, for example hydrogen, a halogen, a halogenated carbon, e.g. trichlorocarbon, a carboxylic acid, an alkylgroup, or an alcohol, depending on the method of producing the polymer.

10 Especially preferred is polytetrafluoroethylene (PTFE) also known as TEFLON[®]. The molecular weights of the polymers used for coating the piercing means may range from about 2×10^3 to about 2×10^6 Daltons. Preferably, these polymers are incorporated homogeneously, e.g. uniformly distributed, for example in an alloy matrix, at a concentration of up to 30 %, e.g. from 5 to 30 %. These alloys may contain chromium

15 and/or one or more elements of Group VIII of the Periodic Table, for example iron, cobalt, nickel, preferably nickel, and/or a noble metal, for example ruthenium, rhodium, palladium. Particularly preferred are nickel phosphorous alloys which preferably contain about 90 to 93 % by weight nickel and about 7 to 10 % by weight phosphorous.

20 Cotermious piercing of the capsule may be achieved by one or more pins at each end of the capsule. The coating or coatings may cover at least the portion of a pin or pins which come in contact and pierce the capsule, but preferably they cover the whole surface of the pin or pins. More than one alloy may be used to apply more than one coating to the pins, particularly preferred are two coatings. The polymer coating or

25 coatings may typically have a total thickness of between about 1 to about 30 microns, for example a first coating may have a thickness of about 5 to about 15 microns, and a second coating may have a thickness of about 3 to 10 microns.

Thus, in one embodiment of this invention, piercing means may be coated with PTFE or

30 an alloy matrix, e.g. a chromium or a nickel phosphorous alloy, or an alloy matrix containing PTFE particles, e.g. a PTFE-containing nickel phosphorous alloy, also known as CHENIFLON[™].

In a particularly preferred embodiment of this invention, steel pins, e.g. stainless steel pins, for use in an inhalation device are coated with a first layer of a nickel phosphorous alloy, e.g. NIPLOY™, to a thickness of between about 5 and about 15 microns and a second layer containing about 20 to 30 % by volume PTFE particles homogeneously incorporated in a nickel phosphorous alloy matrix may be applied at a thickness of between 3 and 10 microns onto the first layer.

Preferably, the composition of a plated deposit contains about 80 to 95 %, e.g. 85 % by weight nickel, 5 to 20 %, e.g. 6.6 % by weight phosphorous and up to 30 %, e.g. 8.4 % by weight PTFE. The PTFE content in a composite of 8.4 % by weight may correspond to approximately 25 % by volume in the deposit.

Polymers may be applied to the pins, e.g. steel pins, using techniques suitable to give a uniform coating. Typically, conventional coating techniques include (i) applying the polymers in form of a, preferably fine, dispersion and (ii) evaporating the liquid medium to form the coating. Such techniques include for example

- (i) dipping the pins into a dispersion of an alloy and controlling the coating thickness by polymer concentration, rate of dipping and withdrawing, and number of applications;
- (ii) wiping or brushing dilute alloy dispersions onto pin surfaces, particularly useful for partial surface coating;
- (iii) spraying, for example air spraying of an alloy dispersed in a less volatile solvent using conventional spray equipment, airless spraying using dilute alloy dispersions, or electrostatic spraying;
- (iv) depositing a coating using aerosol formulations;
- (v) by ultraviolet photopolymerization;
- (vi) by RF sputtering; or
- (vii) by electrophoresis of such a dispersion onto the pins.

Suitable liquid media to form a dispersion include aqueous solutions, freons, for example dichlorodifluoromethane, dichlorotetrafluoroethane, and the like, including mixtures of these media. The dispersion may be preferably fine such that the particles remain uniformly distributed through the solution with little or no agitation. However,

most preferably the polymer coatings are formed by depositing a coating using plating processes, particularly preferred is an electroless nickel composite coating process.

5 Typically, in an electroless nickel plating process direct reduction of the nickel onto the surface takes place in solution in the presence of reducing agents which provide the necessary energy, e.g. sodium hypophosphite, boron compounds or hydrazine. Most preferably the reduction reaction is fueled by hypophosphite, which results in co-deposition of small amounts of phosphorous, e.g. up to 10 %, e.g. from about 7 to 10 % by weight. A corresponding composite process further includes particles in the plating
10 solution, for example polymers, e.g. PTFE. Typically a chemical composition of a plating solution may contain 6 g/l nickel metal, 30 g/l sodium hypophosphite, 3-6 g/l PTFE powder, 10-30 g/l organic acids, and stabilizers in picomolar concentrations. Typical operating conditions may include a pH of about 4.7 to 5.0 and a temperature of about 183 to 193 F.

15

Thus, in a particularly preferred embodiment a coating may be applied by electroless nickel plating or composite coating, e.g. using the Cheniflon™ process from the Argos company of Italy.

The following non-limiting examples were carried out to illustrate the processes of the present invention:

Test 1.

5

50 Beclometason 400 Cyclocaps® are used successively in Inhaler A with uncoated steel pins at 20°C. After perforation of each capsule the push buttons are released and it is observed that the pins are retained in, or incompletely withdrawn from, 15 capsules.

10 This is repeated with inhaler A with Niploy™ and Cheniflon™ coated steel pins and no pin retention is observed in any capsule.

Test 2.

15

50 Salbutanol 200 Cyclocaps® are used successively in Inhaler A with uncoated pins at 20°C. After perforation of each capsule the push buttons are released and the pins are retained in, or incompletely withdrawn from, 18 capsules.

20 This is repeated with inhaler A with Niploy™ and Cheniflon™ coated pins and no pin retention by any capsule is observed.

CLAIMS

1. Use of polymer-coated metal capsule-piercing means in an inhaler device.
5
2. Use as claimed in claim 1 wherein the polymer is polytetrafluoroethylene in an alloy matrix.
3. Use as claimed in claim 1 or claim 2 wherein the capsule-piercing means is a
10 sharpened steel pin.
4. An inhaler comprising polymer-coated steel capsule-piercing means.
5. An inhaler according to claim 4 wherein said steel capsule-piercing means are
15 coated with a first coating of a nickel phosphorous alloy and a second coating of a nickel phosphorous alloy containing PTFE particles.
6. An inhaler according to claims 4 or 5 wherein the total thickness of all polymer
20 coating is 5 to 30 microns.
7. Use of electroless nickel composite coating process to coat a PTFE/nickel alloy composite layer onto capsule-piercing means for an inhaler.
8. Coated capsule-piercing means substantially as herein described.
25
9. A method of preparing polymer-coated piercing means for an inhaler comprising coating the piercing means with a first coating of a nickel phosphorous alloy and a second coating of a nickel phosphorous alloy containing PTFE particles.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 99/01486

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A61M15/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 949 751 A (DEAN DESMOND ALFRED ET AL) 13 April 1976 see column 1, line 45 - line 64 see column 2, line 20 - column 3, line 25 see column 4, line 42 - line 51 see figure 1	1, 3, 4
A	-----	2, 5-7, 9

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

³ Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

17 June 1999

Date of mailing of the international search report

14. 07. 1999

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Lakkis, A

INTERNATIONAL SEARCH REPORT

International application No.
PCT/EP 99/01486

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:

2. Claims Nos.: 8
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
obscurity

3. Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.

2. As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.

3. As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:

4. No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- The additional search fees were accompanied by the applicant's protest.
- No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/01486

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3949751 A	13-04-1976	GB 1338254 A	21-11-1973
		AT 316732 B	15-06-1974
		BE 764567 A	20-09-1971
		CA 933829 A	18-09-1973
		CH 538284 A	15-08-1973
		DE 2114038 A	18-11-1971
		DK 128982 B	05-08-1974
		FI 53926 B	31-05-1978
		FR 2085062 A	17-12-1971
		IE 35024 B	15-10-1975
		JP 54006839 B	02-04-1979
		KE 2546 A	01-08-1975
		NL 7103939 A, B,	28-09-1971
		SE 382914 B	23-02-1976
		SE 7103839 A	
		YU 73971 A, B	30-04-1981
