



US009771813B2

(12) **United States Patent**
Brooks

(10) **Patent No.:** **US 9,771,813 B2**

(45) **Date of Patent:** **Sep. 26, 2017**

(54) **CONVERGING FLOW JOINT INSERT SYSTEM AT AN INTERSECTION BETWEEN ADJACENT TRANSITIONS EXTENDING BETWEEN A COMBUSTOR AND A TURBINE ASSEMBLY IN A GAS TURBINE ENGINE**

(58) **Field of Classification Search**
CPC .. F01D 9/023; F23R 2900/00005; F23R 3/60; F23R 3/002; F02C 3/14; F02C 3/425; (Continued)

(71) Applicant: **Siemens Energy, Inc.**, Orlando, FL (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(72) Inventor: **Robert T. Brooks**, Chuluota, FL (US)

2,596,646 A 5/1952 Buchi
2,967,013 A 1/1961 Dallenbach et al.
(Continued)

(73) Assignee: **SIEMENS ENERGY, INC.**, Orlando, FL (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

EP 2660519 A1 11/2013
EP 26604227 A1 11/2013

OTHER PUBLICATIONS

(21) Appl. No.: **15/318,781**

PCT International Search Report and Written Opinion dated Oct. 21, 2014 corresponding to PCT Application PCT/US2014/044289 filed Jun. 26, 2014. (11 pages).

(22) PCT Filed: **Jun. 26, 2014**

Primary Examiner — Andrew Nguyen

(86) PCT No.: **PCT/US2014/044289**

§ 371 (c)(1),
(2) Date: **Dec. 14, 2016**

(57) **ABSTRACT**

(87) PCT Pub. No.: **WO2015/199694**

PCT Pub. Date: **Dec. 30, 2015**

A transition duct system (100) for routing a gas flow from a combustor (102) to the first stage (104) of a turbine section (106) in a combustion turbine engine (108), wherein the transition duct system (100) includes one or more converging flow joint inserts (120) forming a trailing edge (122) at an intersection (124) between adjacent transition ducts (126, 128) is disclosed. The transition duct system (100) may include a transition duct (126, 128) having an internal passage (130) extending between an inlet (132, 184) to an outlet (134, 186) and may expel gases into the first stage turbine (104) with a tangential component. The converging flow joint insert (120) may be contained within a converging flow joint insert receiver (136) and disconnected from the transition duct bodies (126, 128) by which the converging flow joint insert (120) is positioned. Being disconnected eliminates stress formation within the converging flow joint insert (120), thereby enhancing the life of the insert. The

(65) **Prior Publication Data**

US 2017/0130595 A1 May 11, 2017


(51) **Int. Cl.**
F01D 9/02 (2006.01)
F02C 3/14 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **F01D 9/023** (2013.01); **F02C 3/14** (2013.01); **F23R 3/425** (2013.01); **F23R 3/60** (2013.01);

(Continued)

(Continued)



converging flow joint insert (120) may be removable such that the insert (120) can be replaced once worn beyond design limits.

10 Claims, 21 Drawing Sheets

(51) **Int. Cl.**

F23R 3/60 (2006.01)
F23R 3/42 (2006.01)

(52) **U.S. Cl.**

CPC *F05D 2250/25* (2013.01); *F05D 2250/37* (2013.01); *F05D 2250/38* (2013.01)

(58) **Field of Classification Search**

CPC *F02C 3/52*; *F05D 2250/38*; *F05D 2250/25*; *F05D 2250/322*; *F05D 2260/941*

See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

3,184,152 A 5/1965 Bourquad
 3,333,762 A 8/1967 Vrana
 3,420,435 A 1/1969 Jarosz et al.

3,484,039 A	12/1969	Mittelstaedt	
3,657,882 A	4/1972	Hugoson	
3,743,436 A	7/1973	O'Connor	
4,164,845 A	8/1979	Exley et al.	
4,368,005 A	1/1983	Exley et al.	
4,565,505 A	1/1986	Wollenweber	
5,039,317 A	8/1991	Thompson et al.	
5,145,317 A	9/1992	Brasz	
5,320,489 A	6/1994	McKenna	
6,280,139 B1	8/2001	Romani et al.	
6,589,015 B1	7/2003	Roberts et al.	
6,845,621 B2	1/2005	Teets	
8,113,003 B2	2/2012	Charron et al.	
2006/0127827 A1	6/2006	Yoshida	
2008/0010990 A1*	1/2008	Shi	F16L 25/0072 60/772
2010/0077719 A1	4/2010	Wilson et al.	
2011/0203282 A1	8/2011	Charron et al.	
2012/0292861 A1*	11/2012	Moehrle	F01D 9/023 277/641
2013/0283818 A1*	10/2013	Flanagan	F01D 9/023 60/800
2014/0010644 A1	1/2014	Charron et al.	
2014/0109578 A1*	4/2014	Bothien	F01D 9/023 60/722
2015/0132117 A1*	5/2015	Marra	F01D 9/023 415/187

* cited by examiner




FIG. 1
(PRIOR ART)




FIG. 2
(PRIOR ART)




FIG. 3
(PRIOR ART)




FIG. 4
(PRIOR ART)




FIG. 5
(PRIOR ART)




FIG. 6
(PRIOR ART)




FIG. 7
(PRIOR ART)




FIG. 8
(PRIOR ART)




FIG. 9
(PRIOR ART)





FIG. 10
(PRIOR ART)






FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 31

PROFILE AT PLANE S




FIG. 30




FIG. 32




FIG. 34

FIG. 33








FIG. 37






FIG. 42




FIG. 43




FIG. 44

FIG. 45




FIG. 46

**CONVERGING FLOW JOINT INSERT
SYSTEM AT AN INTERSECTION BETWEEN
ADJACENT TRANSITIONS EXTENDING
BETWEEN A COMBUSTOR AND A TURBINE
ASSEMBLY IN A GAS TURBINE ENGINE**

STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH OR DEVELOPMENT

Development of this invention was supported in part by the United States Department of Energy, Advanced Turbine Development Program, Contract No. DE-FC26-05NT42644. Accordingly, the United States Government may have certain rights in this invention.

FIELD OF THE INVENTION

This invention is directed generally to gas turbine engines, and more particularly to transition ducts for routing gas flow from combustors to the turbine section of gas turbine engines.

BACKGROUND OF THE INVENTION

In conventional gas turbine engines, as shown in FIG. 1, combustion gases created within a combustor **10** are passed to a turbine assembly via a plurality of transition ducts **12**. In many conventional systems, the transition ducts **12** extended longitudinally without any offset in a circumferential direction. A row of first stage vanes **14** were used to turn the combustion exhaust gases before being passed to the row one turbine blades **16**. The use of first stage vanes **14** in a turbine assembly to accelerate and turn the longitudinal combustor exhaust gas flow in the circumferential direction presented several challenges. The vanes **14** and the associated vane support structures were required to have high strength characteristics to withstand the forces generated in changing the direction of extremely hot, high pressure gas flow over a substantial angle in a relatively short distance. The temperature of the gas flow and the heat generated by this turning process also require a vane cooling system. The forces and heat involved diminished material properties causing cracks to develop and otherwise damage the vanes and associated support structures.

To accommodate these operating conditions and to provide a more robust design, as shown in FIGS. 2-10, the transition ducts **20** directing combustion gases from a combustor **22** to a turbine assembly **24** were skewed circumferentially such that the outlets **26** of the transition ducts **20** were skewed circumferentially in the same direction of that the first row turbine vanes would otherwise skew the combustion exhaust gases in the circumferential direction. As such, row one turbine vanes were no longer needed because the exhaust gases emitted from the transition ducts **20** already included the correct circumferential vector, thereby eliminating the need for the row one turbine vanes. As shown in U.S. Pat. No. 8,113,003, filing date Aug. 12, 2008, issuance date Feb. 14, 2012, which is incorporated herein in its entirety, the outlet of each transition duct is skewed in the circumferential direction relative to the inlet of each transition duct. While the transition duct system of the U.S. Pat. No. 8,113,003 has eliminated the need for row one turbine vanes upstream of row one turbine blades within a turbine assembly, there exists a need to increase the useful life of the skewed transition duct system by eliminating areas of high stress, which are shown in FIGS. 6-10.

SUMMARY OF THE INVENTION

A transition duct system for routing a gas flow from a combustor to the first stage of a turbine section in a combustion turbine engine, wherein the transition duct system includes one or more converging flow joint inserts forming a trailing edge at an intersection between adjacent transition duct is disclosed. The transition duct system may include a transition duct having an internal passage extending between an inlet to an outlet and may expel gases into the first stage turbine with a tangential component. The converging flow joint insert may be contained within a converging flow joint insert receiver and disconnected from the transition duct bodies by which the converging flow joint insert is positioned. Being disconnected eliminates stress formation within the converging flow joint insert, thereby enhancing the life of the insert. The converging flow joint insert may be removable such that the insert can be replaced once worn beyond design limits.

For a better understanding of the invention, a coordinate system can be applied to such a turbine system to assist in the description of the relative location of components in the system and movement within the system. The axis of rotation of the rotor assembly extends longitudinally through the compressor section, the combustion section and the turbine section and defines a longitudinal direction. Viewed from the perspective of the general operational flow pattern through the various sections, the turbine components can be described as being located longitudinally upstream or downstream relative to each other. For example, the compressor section is longitudinally upstream of the combustion section and the turbine section is longitudinally downstream of the combustion section. The location of the various components away from the central rotor axis or other longitudinal axis can be described in a radial direction. Thus, for example, the blade extends in a radial direction, or radially, from the rotor disc. Locations further away from a longitudinal axis, such as the central rotor axis, can be described as radially outward or outboard compared to closer locations that are radially inward or inboard.

The third coordinate direction—a circumferential direction—can describe the location of a particular component with reference to an imaginary circle around a longitudinal axis, such as the central axis of the rotor assembly. For example, looking longitudinally downstream at an array of turbine blades in a turbine engine, one would see each of the blades extending radially outwardly in several radial directions. Thus, the radial direction can describe the size of the reference circle and the circumferential direction can describe the angular location on the reference circle.

In at least one embodiment, the transition duct system routes gas flow in a combustion turbine subsystem that includes a first stage blade array having a plurality of blades extending in a radial direction from a rotor assembly for rotation in a circumferential direction, whereby the circumferential direction may have a tangential direction component. The combustion turbine subsystem may have an axis of the rotor assembly defining a longitudinal direction and at least one combustor located longitudinally upstream of the first stage blade array and located radially outboard of the first stage blade array. The transition duct system may include a first transition duct body having an internal passage extending between an inlet and an outlet. The outlet of the first transition duct body may be offset from the inlet in the longitudinal direction and the tangential direction. The outlet of the first transition duct body may be formed from a radially outer side generally opposite to a radially inner

3

side, and the radially outer and inner sides may be coupled together with opposed first and second side walls. The transition duct system may also include a second transition duct body having an internal passage extending between an inlet and an outlet. The outlet of the second transition duct body may be offset from the inlet in the longitudinal direction and the tangential direction. The outlet of the second transition duct body may be formed from a radially outer side generally opposite to a radially inner side, and the radially outer and inner sides may be coupled together with opposed first and second side walls. A first side of the first transition duct body may intersect with a second side of the second transition duct body forming a converging flow joint. The transition duct system may include a converging flow joint insert positioned within a recess at a downstream end of the converging flow joint to form a trailing edge of the converging flow joint. The transition duct system may include a recess positioned within the converging flow joint to receive the converging flow joint insert.

The transition duct system may include an insert attachment system configured to attached the converging flow joint insert to the converging flow joint. The insert attachment system may include one or more pins extending into the converging flow joint insert and into the converging flow joint. In at least one embodiment, the insert attachment system may include one or more pins extending through the converging flow joint insert and through the converging flow joint. The insert attachment system may also include one or more collars for securing a first end of the at least one pin.

The transition duct system may also include an internal cooling system within the converging flow joint insert. The internal cooling system may include one or more internal cooling chambers in fluid communication with one or more exhaust orifices extending from an inlet in the internal cooling chamber through an outer wall forming the converging flow joint insert. The exhaust orifice of the internal cooling system may include one or more exhaust orifices extending from the internal cooling chamber to an exhaust outlet at an outer surface facing a surface forming the recess in which the converging flow joint insert resides and one or more orifices extending from the internal cooling chamber to an exhaust outlet at an outer surface facing downstream and away from the recess in which the converging flow joint insert resides. At least a portion of the cooling system may be contained within a pin forming at least a portion of an insert attachment system configured to attached the converging flow joint insert to the converging flow joint. The pin may include an inner channel having one or more inlets positioned outside of the recess at the downstream end of the converging flow joint and may include one or more exhaust outlets in fluid communication with the internal cooling chamber. The pin may include a first inlet at a first end of the pin in communication with the inner channel in the pin and may include a second inlet in a second end of the pin at an opposite end of the pin from the first end.

The converging flow joint insert may include a body formed from an outer section, an inner section and a middle section between the outer and inner sections. The body of the converging flow joint insert may include an outer section, an inner section and a middle section between the outer and inner sections, whereby the middle section has a cross-sectional area narrower in width than the outer and inner sections. The inner section may extend further downstream than the middle section and the outer section extends further downstream than the inner section. A cross-sectional area at a distal end of the outer section may be larger than a cross-sectional area at a distal end of the inner section.

4

An advantage of the transition duct system is that the converging flow joint insert replaces an area of high mechanical stress within transition duct systems with a converging flow joint insert that resides within a converging flow joint insert receiver and is exposed to minimal and possibly no mechanical stress.

Another advantage of the transition duct system is that the converging flow joint insert removes the sharp narrow geometry and the resulting stress concentrations from the converging flow joint between adjacent transition ducts and incorporates the sharp narrow geometry into the converging flow joint insert.

Yet another advantage of the transition duct system is that the converging flow joint insert is removably and replaceable, thereby enabling the converging flow joint insert to be replaced when worn due to erosion from high velocity gases.

Another advantage of the transition duct system is that the converging flow joint insert is supported by a converging flow joint insert receiver that is formed from a buildup of material at the intersection of sidewalls proximate to outlets of adjacent transition ducts that increase the strength of the walls so they can better resist the pressure loading and distributing the stresses over a larger area, thereby reducing the stress levels and increasing the design life of the transition duct system.

These and other embodiments are described in more detail below.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and form a part of the specification, illustrate embodiments of the presently disclosed invention and, together with the description, disclose the principles of the invention.

FIG. 1 is a cross-sectional view of a portion of a gas turbine engine.

FIG. 2 is an downstream facing perspective view of an upper half of a plurality of can-annular combustors coupled to transition ducts.

FIG. 3 is an upstream longitudinal view of a circular array of transition ducts.

FIG. 4 is a side view of a transition duct relative to row one turbine blades.

FIG. 5 is a top view of a circular array of transition ducts.

FIG. 6 is a top view of a fitting in which two adjacent transition ducts are positioned.

FIG. 7 is a cross-sectional view of the two adjacent transition ducts of FIG. 6 taken along section line 7-7 in FIG. 6 in which an area of high mechanical stress is identified.

FIG. 8 is a perspective detailed view of the area of high mechanical stress at the intersection between the adjacent transition ducts taken along detail line 8-8 in FIG. 7.

FIG. 9 is another perspective view of the area of high mechanical stress at the intersection between the adjacent transition ducts taken along detail line 8-8 shown in FIG. 7.

FIG. 10 is a partial perspective view of two transition ducts looking upstream into the internal passageways of the transition ducts showing how the adjacent transition ducts next together at the exhaust outlets.

FIG. 11 is an downstream facing perspective view of an upper half of a plurality of can-annular combustors coupled to transition ducts.

FIG. 12 is an upstream longitudinal view of a circular array of transition ducts.

FIG. 13 is a side view of a transition duct relative to row one turbine blades.

5

FIG. 14 is a perspective view of a plurality of transition ducts coupled together immediately upstream of row one turbine blades.

FIG. 15 is a simplified side view of a transition duct shown in FIG. 10.

FIG. 16 is a perspective view of external surfaces of two adjacent transition ducts at their downstream ends, which are coupled together and including a converging flow joint insert positioned within a converging flow joint insert receiver at an intersection between two adjacent transition ducts.

FIG. 17 is a perspective view of the converging flow joint insert positioned within a converging flow joint insert receiver at an intersection between two adjacent transition ducts.

FIG. 18 is a cross-sectional view of the converging flow joint between two adjacent transition ducts taken at section line 18-18 in FIG. 16.

FIG. 19 is a cross-sectional view of the converging flow joint between two adjacent transition ducts taken at section line 19-19 in FIG. 16.

FIG. 20 is a cross-sectional view of the converging flow joint between two adjacent transition ducts taken at section line 20-20 in FIG. 16.

FIG. 21 is a cross-sectional view of the converging flow joint between two adjacent transition ducts taken at section line 21-21 in FIG. 16.

FIG. 22 is a perspective view of internal surfaces of a converging flow joint insert receiver at a converging flow joint between two adjacent transition ducts at their downstream ends, whereby the converging flow joint insert is not contained within the converging flow joint insert receiver.

FIG. 23 is a perspective view of internal surfaces of a converging flow joint insert receiver at a converging flow joint between two adjacent transition ducts at their downstream ends with the converging flow joint insert positioned within the converging flow joint insert receiver.

FIG. 24 is perspective view a converging flow joint insert at a different angle than in FIG. 23.

FIG. 25 is a perspective view of external surfaces of a converging flow joint insert receiver at a converging flow joint between two adjacent transition ducts at their downstream ends, whereby the converging flow joint insert is not contained within the converging flow joint insert receiver and a downstream internal surface of the converging flow joint insert receiver is displayed.

FIG. 26 is another perspective view of external surfaces of a converging flow joint insert receiver, taken from a different perspective than FIG. 25, at a converging flow joint between two adjacent transition ducts at their downstream ends, whereby the converging flow joint insert is not contained within the converging flow joint insert receiver and an upstream internal surface of the converging flow joint insert receiver is displayed.

FIG. 27 is a perspective view of external surfaces of a non-insert side of the converging flow joint insert receiver at a converging flow joint between two adjacent transition ducts at their downstream ends.

FIG. 28 is a cross-sectional, top view of the converging flow joint insert taken along section lines 28-28 in FIG. 23, as shown relative to a perspective view of external surfaces of two adjacent transition ducts at their downstream ends, which are coupled together and including a converging flow joint insert positioned within a converging flow joint insert receiver at an intersection between two adjacent transition ducts.

6

FIG. 29 is a cross-sectional side view of the converging flow joint insert taken along section line 29-29 in FIG. 28.

FIG. 30 is a bottom view of the converging flow joint insert shown in FIG. 29.

FIG. 31 is a front view of the converging flow joint insert shown in FIG. 29.

FIG. 32 is a cross-sectional view of the converging flow joint insert positioned within a converging flow joint insert receiver at an intersection between two adjacent transition ducts taken along section line 32-32 in FIG. 28.

FIG. 33 is a cross-sectional side view of the converging flow joint insert with an internal cooling system together with alternative outer surface locations showing possible alternative positions of the outer surface in other embodiments.

FIG. 34 is an upstream end view of the converging flow joint insert of FIG. 33.

FIG. 35 is a cross-sectional view of the converging flow joint insert taken at section line 35-35 in FIG. 33.

FIG. 36 is a cross-sectional view of another embodiment of the converging flow joint insert with a different internal cooling system configuration taken at section line 35-35 in FIG. 33.

FIG. 37 is a cross-sectional view of the converging flow joint insert configuration taken at section line 37-37 in FIG. 16.

FIG. 38 is a perspective view of an alternative embodiment of internal surfaces of a converging flow joint insert receiver at a converging flow joint between two adjacent transition ducts at their downstream ends with an alternative embodiment of the converging flow joint insert positioned within a recess where the converging flow joint insert does not protrude through the outer wall defining the recess.

FIG. 39 is a side view of the converging flow joint insert of FIG. 38.

FIG. 40 is a right side view of the converging flow joint insert of FIG. 38.

FIG. 41 is a left side view of the converging flow joint insert of FIG. 38.

FIG. 42 is a perspective view of the converging flow joint insert of FIG. 38.

FIG. 43 is a cross-sectional side view of the converging flow joint insert of FIG. 38 taken along section line 43-43 in FIG. 42.

FIG. 44 is a perspective view of a first end of the pin extending through the converging flow joint insert of FIG. 38.

FIG. 45 is a perspective view of a second end of the pin extending through the converging flow joint insert of FIG. 38.

FIG. 46 is a cross-sectional view of the converging flow joint insert of FIG. 38 positioned within a converging flow joint insert receiver at an intersection between two adjacent transition ducts.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

As shown in FIGS. 11-46, a transition duct system 100 for routing a gas flow from a combustor 102 to the first stage 104 of a turbine section 106 in a combustion turbine engine 108, wherein the transition duct system 100 includes one or more converging flow joint inserts 120 forming a trailing edge 122 at an intersection 124 between adjacent transition duct 126, 128 is disclosed. The transition duct system 100 may include a transition duct 126 having an internal passage 130 extending between an inlet 132 to an outlet 134 and may

expel gases into the first stage turbine **114** with a tangential component. The converging flow joint insert **120** may be contained within a converging flow joint insert receiver **136** and disconnected from the transition duct bodies **126, 128** by which the converging flow joint insert **120** is positioned. Being disconnected on side surfaces eliminates stress formation within the converging flow joint insert **120**, thereby enhancing the life of the insert **120**. The converging flow joint insert **120** may be removable such that the insert **120** can be replaced once worn beyond design limits.

In at least one embodiment, the transition duct system **100** may route gas flow in a combustion turbine subsystem **138** that includes a first stage blade array **104** having a plurality of blades **142** extending in a radial direction from a rotor assembly **144** for rotation in a circumferential direction **146**, whereby the circumferential direction **146** may have a tangential direction component **148**. The combustion turbine subsystem **138** may also include an axis **150** of the rotor assembly **144** defining a longitudinal direction **152**, and at least one combustor **102** located longitudinally upstream of the first stage blade array **104** and located radially outboard of the first stage blade array **104**.

The transition duct system **100** may include a plurality of transition ducts **126, 128** coupled together such that the ducts **126, 128** exhaust combustion gases in a downstream direction together with a tangential component **148**, thereby eliminating the need for a first stage turbine vane row upstream from a first turbine blade row, as found in convention gas turbine engines. In particular, the transition duct system **100** may include a first transition duct body **126** having an internal passage **130** extending between an inlet **132** and an outlet **134**. The outlet **134** of the first transition duct body **134** is offset from the inlet **132** in the longitudinal direction **152** and the tangential direction **148**. The outlet **134** of the first transition duct body **126** may be formed from a radially outer side **168** generally opposite to a radially inner side **170**, and the radially outer and inner sides **168, 170** may be coupled together with opposed first and second side walls **172, 174**.

The transition duct system **100** may include a second transition duct body **128** having an internal passage **182** extending between an inlet **184** and an outlet **186**. The outlet **186** of the second transition duct body **128** may be offset from the inlet **184** in the longitudinal direction **152** and the tangential direction **148**. The outlet **186** of the second transition duct body **128** may be formed from a radially outer side **188** generally opposite to a radially inner side **190**, and the radially outer and inner sides **188, 190** may be coupled together with opposed first and second side walls **192, 194**. When the first transition duct **126** is positioned next to the second transition duct body **128**, a first side wall **172** of the first transition duct body **126** intersects with a second side wall **194** of the second transition duct body **128** forming a converging flow joint **196**. In at least one embodiment, the first side wall **172** of the first transition duct body **126** may be configured to be coplanar with a second side wall **194** of the second transition duct body **128** when assembled beside the first transition duct body **126**. Longitudinal axes **270, 272** of the first and second transition duct bodies **126, 128** may be offset from each other in the circumferential direction **146**.

The transition duct system **100** may also include a converging flow joint insert **120** extending through an outer wall **202** and positioned at a downstream end **204** of the converging flow joint **196** to form the trailing edge **122** of the converging flow joint **196**. The converging flow joint insert **120** is positioned in a location of high mechanical stress in

conventional systems. The converging flow joint insert **120** may be disconnected from the first side **172** of the first transition duct body **126** and the second side **194** of the second transition duct body **128**. Being disconnected, yet positioned to act as the trailing edge **122** of the converging flow joint **196** enables the converging flow joint insert **120** to function without being subjected to mechanical stress. The converging flow joint insert **120** may be contained within a converging flow joint insert receiver **136**. The converging flow joint insert receiver **136** may be positioned at the converging flow joint **196** and configured to receive the converging flow joint insert **120**. The converging flow joint insert receiver **136** may include one or more inner walls **208** defining at least one insert receiving orifice **210** that provides support to the converging flow joint insert **120**, as shown in FIGS. **22-26**. The converging flow joint insert receiver **136** may also include one or more flange contact surfaces **212** configured to support a flange **214**, as shown in FIGS. **29-37**, positioned at a first end **216** of the insert **120** to prevent the converging flow joint insert **120** from being ingested into a turbine downstream of the transition duct system **100**. The converging flow joint insert **120** may be removably attached within the transition duct system **100**. The converging flow joint insert **120** may be coupled to the converging flow joint insert receiver **136** via a weld or appropriate method already invented or yet to be invented.

The converging flow joint insert **120** may be formed from a body **218** with a flange **214** positioned at the first end **216** of the insert **120** to prevent the converging flow joint insert **120** from being ingested into a turbine downstream of the transition duct system **100**. The flange **214** of the converging flow joint insert **120** may have a larger cross-sectional area than the body **218** of the converging flow joint insert **120**. The converging flow joint insert **120** may be formed from a first side **260** that forms an extension of the first side wall **172** of the first transition duct body **126** and a second side **262** that forms an extension of the second side wall **194** of the second transition duct body **128**. The flange **214** and the body **218** may be a unitary structure. In another embodiment, the flange **214** may be coupled to the body **218** via welding, brazing or other appropriate connection mechanism.

The body **218** of the converging flow joint insert **120** may include a first section **220** with a uniform thickness from a first side **222** to a second side **224** opposite to the first side **222** and a second section **226** extending from the first section **220** and forming an outer downstream tip **228** of the converging flow joint insert **120**. The second section **226** has a nonuniform thickness with a thickness at the outer downstream tip **228** being less than a thickness at an upstream edge **230**. As shown in FIG. **20**, the first section **220** of the converging flow joint insert **120** may be positioned closer to the converging flow joint insert receiver **136** than the second section **226**. The second section **226** may include a first side **231** and a second side **233** that is on an opposite side from the first side **231**. The first and second sides **231, 233** may have a somewhat convex surface that each replicate the inner surfaces of the first side wall **172** of the first transition duct body **126** and the second side wall **194** of the second transition duct body **128**. The trailing edge **229** of the converging flow joint insert **120** may have a generally curved shape extending from the first section **220** towards a distal end **232** of the second section **226** to follow the contour of the intersection **124** between the first and second transition bodies **126, 128**.

The converging flow joint insert **120** may include an internal cooling system **234** within the converging flow joint

insert **120**, as shown in FIGS. **33-36**. The internal cooling system **234** may have any appropriate shape configured to adequately cool the converging flow joint insert **120** when extending into the hot gas path at the intersection **124** of the first and second transition ducts **126**, **128**. The internal cooling system **234** may include one or more internal cooling chambers **236** in fluid communication with one or more exhaust orifices **238** extending from an inlet **240** in the internal cooling chamber **236** through an outer wall **242** forming the second section **226** of the converging flow joint insert **120**. The second section **226** may include an outer downstream tip **228** of the converging flow joint insert **120**, and an outlet **244** of the at least one exhaust orifice **238** may be positioned at an outer surface **246** of the internal cooling chamber **236**. In at least one embodiment, the internal cooling system **234** may include a plurality of exhaust orifices **238** extending from inlets **240** in the internal cooling chamber **236** through the outer wall **242** forming the second section **226** of the converging flow joint insert **120** to outlets **244** of the exhaust orifice **238** positioned at the outer surface **246** of the internal cooling chamber **236**.

The internal cooling system **234** may include one or more impingement plates **248**, as shown in FIG. **35**, positioned in the internal cooling chamber **236** and extending from a first side **250** to a second side **252** opposite to the first side **250** forming the converging flow joint insert **120**. The impingement plate **120** may include one or more impingement orifices **254**, and, in at least one embodiment, may include a plurality of impingement orifices **254**. In another embodiment, as shown in FIG. **36**, the internal cooling system **234** may include one or more internal cooling chambers **236** having an internal volume less than one half of a volume of outer walls **242** forming the converging flow joint insert **120**. One or more exhaust orifices **238** may extend from an inlet **240** in the internal cooling chamber **236** through the outer wall **256** forming the first section **220** of the converging flow joint insert **120**. The first section **220** may have a uniform thickness from the first side **222** to the second side **224** opposite to the first side **222**. One or more exhaust orifices **238** may extend from an inlet **240** in the internal cooling chamber **236** through an outer wall **242** forming a second section **226** of the converging flow joint insert **120**. The second section **226** may extend from the first section **220** and may form an outer downstream tip **228** of the converging flow joint insert **120**. The second section **226** may have a nonuniform thickness with a thickness at the outer downstream tip **228** being less than a thickness at an upstream edge **230** of the second section **226**.

In another embodiment, as shown in FIGS. **38-46**, the transition duct system **100** may have an alternative configuration. The transition duct system **100** may include the first and second transition duct bodies **126**, **128** as previously set forth, but may include an alternative configuration for the converging flow joint insert **120**. The transition duct system **100** may include converging flow joint insert **120** positioned within a recess **300** at a downstream end **302** of the converging flow joint **196** to form a trailing edge **301** of the converging flow joint **196**. The recess **300** may be positioned within the converging flow joint **196** and may be configured to receive and house the converging flow joint insert **120**. In this embodiment, the converging flow joint insert **120** may extend through the outer wall **202** at a downstream end **204** of the converging flow joint **196**. Instead, the converging flow joint insert **120** may be contained completely within the recess **300** with a portion exposed to form the trailing edge **122** of the converging flow joint **196**.

The transition duct system **100** may be held in place within the recess **300** via an insert attachment system **303** configured to attached the converging flow joint insert **120** to the converging flow joint **196**. In at least one embodiment, the insert attachment system **303** may be formed from one or more pins **304** extending into the converging flow joint insert **120** and into the converging flow joint **196**. In at least one embodiment, the insert attachment system **303** may include one or more pins **304** extending through the converging flow joint insert **120** and through the converging flow joint **196**. The insert attachment system **303** may include one or more collars **306** for securing a first end **308** of the pin **304**. The collar **306** may be integrally formed with the pin **304** or may be attached to the pin via welding or other appropriate method. A second end **310** of the pin **304** that is generally on an opposite end of the pin **304** relative to the first end **308** may or may not include a collar **306**. The pin **304** near the second end **310** may be secured to the converging flow joint **196** via welding or other appropriate method.

The transition duct system **100** may include an internal cooling system **312** within the converging flow joint insert **120**. The internal cooling system **312** may include one or more internal cooling chambers **314** in fluid communication with one or more exhaust orifices **316** extending from an inlet **318** in the internal cooling chamber **314** through an outer wall **320** forming the converging flow joint insert **120**. The exhaust orifice **316** of the internal cooling system **312** may include one or more exhaust orifices **316** extending from the internal cooling chamber **314** to an exhaust outlet **322** at an outer surface **324** facing a surface **326** forming the recess **300** in which the converging flow joint insert **120** resides. The internal cooling system **312** may also include one or more exhaust orifices **318** extending from the internal cooling chamber **314** to exhaust outlets **330** at an outer surface **332** facing downstream and away from the recess **300** in which the converging flow joint insert **120** resides.

In at least one embodiment, a portion of the internal cooling system **312** may be contained within the pin **304** forming at least a portion of the insert attachment system **303** configured to attached the converging flow joint insert **120** to the converging flow joint **196**. The pin **304** may include an inner channel **334** having at least one inlet **336** positioned outside of the recess **300** at the downstream end **204** of the converging flow joint **196** and may include one or more exhaust outlets **338** in fluid communication with an internal cooling chamber **340**. In at least one embodiment, the pin **304** may include a first inlet **342** at a first end **344** of the pin **304** in communication with the inner channel **334** in the pin **304** and may include a second inlet **346** in a second end **348** of the pin **304** at an opposite end of the pin **304** from the first end **344**. The converging flow joint insert **120** may include a body **350** including an outer section **352**, an inner section **354** and a middle section **356** between the outer and inner sections **352**, **354**. The middle section **356** may have a cross-sectional area narrower in width than cross-sectional areas of the outer and inner sections **352**, **354**. The inner section **354** may extend further downstream than the middle section **356**, and the outer section **352** may extend further downstream than the inner section **354**. A cross-sectional area at a distal end **358** of the outer section **352** may be larger than a cross-sectional area at a distal end **360** of the inner section **354**, as shown in FIG. **43**.

In at least one embodiment, the converging flow joint insert **120** of the converging flow joint **196** may be essentially load free when positioned within the converging flow joint insert receiver **136**. In another embodiment, the con-

11

verging flow joint insert **120** of the converging flow joint **196** may be formed from a material having a larger coefficient of thermal expansion than a material forming the converging flow joint insert receiver **136**. As such, during use when the converging flow joint insert **120** and the converging flow joint insert receiver **136** are exposed to the hot combustion gases, the converging flow joint insert **120** will thermally expand at a faster rate than the converging flow joint insert receiver **136**. As such, the converging flow joint insert **120** will be placed under at least a partial load formed from a compressive load, which partially alleviates the compressive load and stress placed on the converging flow joint insert receiver **136** and surrounding structure. The load and stress created in the converging flow joint insert **120** is less than at a trailing edge in a conventional system without a converging flow joint insert **120**. This is beneficial because stresses are transferred from the permanent/high cost material forming the converging flow joint insert receiver **136** and related components to the modular, disposable converging flow joint insert **120**.

The foregoing is provided for purposes of illustrating, explaining, and describing embodiments of this invention. Modifications and adaptations to these embodiments will be apparent to those skilled in the art and may be made without departing from the scope or spirit of this invention.

I claim:

1. A transition duct system for routing gas flow in a combustion turbine subsystem that includes a first stage blade array having a plurality of blades extending in a radial direction from a rotor assembly for rotation in a circumferential direction, the circumferential direction having a tangential direction component, an axis of the rotor assembly defining a longitudinal direction, and at least one combustor located longitudinally upstream of the first stage blade array and located radially outboard of the first stage blade array, the transition duct system comprising:

a first transition duct body having an internal passage extending between an inlet of the first transition duct body and an outlet of the first transition duct body;

wherein the outlet of the first transition duct body is offset from the inlet of the first transition duct body in the longitudinal direction and the tangential direction;

wherein the outlet of the first transition duct body is formed from a radially outer side of the first transition duct body generally opposite to a radially inner side of the first transition duct body, and the radially outer and inner sides of the first transition duct body are coupled together with opposed first and second side walls of the first transition duct body;

a second transition duct body having an internal passage extending between an inlet of the second transition duct body and an outlet of the second transition duct body;

wherein the outlet of the second transition duct body is offset from the inlet of the second transition duct body in the longitudinal direction and the tangential direction;

wherein the outlet of the second transition duct body is formed from a radially outer side of the second transition duct body generally opposite to a radially inner side of the second transition duct body, and the radially outer and inner sides of the second transition duct body are coupled together with opposed first and second side walls of the second transition duct body;

wherein one of the first and second side walls of the first transition duct body intersects with a corresponding one of the first and second side walls of the second transition duct body forming a converging flow joint;

12

a recess positioned within the converging flow joint; a converging flow joint insert positioned within the recess at a downstream end of the converging flow joint to form a trailing edge of the converging flow joint, an internal cooling system within the converging flow joint insert,

wherein the internal cooling system comprises at least one internal cooling chamber in fluid communication with at least one exhaust orifice extending from at least one inlet in the internal cooling chamber through an outer wall forming the converging flow joint insert,

wherein at least a portion of the cooling system is contained within a pin forming at least a portion of an insert attachment system configured to attach the converging flow joint insert to the converging flow joint, wherein the pin includes an inner channel having a first inlet in a first end of the pin, said first inlet in the first end of the pin positioned outside of the recess at the downstream end of the converging flow joint and includes at least one pin exhaust outlet in fluid communication with the at least one internal cooling chamber.

2. The transition duct system of claim **1**, wherein the pin extends into the converging flow joint insert and into the converging flow joint.

3. The transition duct system of claim **1**, wherein the pin extends through the converging flow joint insert and through the converging flow joint.

4. The transition duct system of claim **2**, wherein the insert attachment system further comprises at least one collar for securing the first end of the pin.

5. The transition duct system of claim **1** wherein the at least one exhaust orifice of the internal cooling system comprises a first exhaust orifice extending from a first inlet of the at least one inlet in the at least one internal cooling chamber to a first exhaust outlet at a first outer surface of the outer wall forming the converging flow joint insert, said outer surface facing a surface forming the recess in which the converging flow joint insert resides, and further comprises a second exhaust orifice extending from a second inlet of the at least one inlet in the at least one internal cooling chamber to a second exhaust outlet at a second outer surface of the outer wall forming the converging flow joint insert, said second outer surface facing downstream and away from the recess in which the converging flow joint insert resides.

6. The transition duct system of claim **1**, further including a second inlet in a second end of the pin at an opposite end of the pin from the first end of the pin.

7. The transition duct system of claim **1**, further comprising a body of the converging flow joint insert includes an outer section, an inner section and a middle section between the outer and inner sections.

8. The transition duct system of claim **1**, further comprising a body of the converging flow joint insert includes an outer section, an inner section and a middle section between the outer and inner sections, wherein the middle section has a cross-sectional area narrower in width than the outer and inner sections.

9. The transition duct system of claim **8**, wherein the inner section extends further downstream than the middle section and the outer section extends further downstream than the inner section.

10. The transition duct system of claim **8**, wherein a cross-sectional area at a distal end of the outer section is larger than a cross-sectional area at a distal end of the inner section.