

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 November 2010 (04.11.2010)

PCT

(10) International Publication Number
WO 2010/124860 A1

(51) International Patent Classification:

C10M 163/00 (2006.01) *C10N 30/04* (2006.01)
C10M 169/04 (2006.01) *C10N 40/25* (2006.01)

(21) International Application Number:

PCT/EP2010/002622

(22) International Filing Date:

26 April 2010 (26.04.2010)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

09159278.2 1 May 2009 (01.05.2009) EP

(71) Applicant (for all designated States except US): **INFINEUM INTERNATIONAL LIMITED** [GB/GB]; PO Box 1, Milton Hill, Oxford OX13 6BB (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BERTRAM, Richard** [GB/GB]; Infineum UK Ltd, PO Box 1, Milton Hill, Oxford OX13 6BB (GB). **DOWDING, Peter** [GB/GB]; Infineum UK Ltd, PO Box 1, Milton Hill, Oxford OX13 6BB (GB). **HARTLEY, Joseph** [GB/GB]; Infineum UK Ltd, PO Box 1, Milton Hill, Oxford OX13 6BB (GB). **WATTS, Peter** [GB/GB]; Infineum UK Ltd, PO Box 1, Milton Hill, Oxford OX13 6BB (GB).

(74) Agents: **LEWIS, Pauline, Therese** et al.; Infineum UK Ltd, PO Box 1, Milton Hill, Oxford OX13 6BB (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- of inventorship (Rule 4.17(iv))

Published:

- with international search report (Art. 21(3))

(54) Title: MARINE ENGINE LUBRICATION

(57) Abstract: Trunk piston marine engine lubrication, when the engine is fueled by heavy fuel oil, is effected by a composition comprising a major amount of an oil of lubricating viscosity containing at least 50 mass % of a basestock containing greater than or equal to 90% saturates and less than or equal to 0.03% sulphur or a mixture thereof, and respective minor amounts of an over-based metal hydrocarbyl-substituted hydroxybenzoate detergent other than such a detergent having a basicity index of less than two and a degree of carbonation of 80% or greater and 5 to 500 mass %, based on the mass of detergent, of an oil-soluble alkyl-substituted phenol other than a hindered phenol. Asphaltene precipitation in the lubricant, caused by the presence of contaminant heavy fuel oil, is prevented or inhibited.



WO 2010/124860 A1

MARINE ENGINE LUBRICATION**FIELD OF THE INVENTION**

This invention relates to a trunk piston marine engine lubricating composition for a medium-speed four-stroke compression-ignited (diesel) marine engine and lubrication of such an engine.

BACKGROUND OF THE INVENTION

Marine trunk piston engines generally use Heavy Fuel Oil ('HFO') for offshore running. Heavy Fuel Oil is the heaviest fraction of petroleum distillate and comprises a complex mixture of molecules including up to 15% of asphaltenes, defined as the fraction of petroleum distillate that is insoluble in an excess of aliphatic hydrocarbon (e.g. heptane) but which is soluble in aromatic solvents (e.g. toluene). Asphaltenes can enter the engine lubricant as contaminants either via the cylinder or the fuel pumps and injectors, and asphaltene precipitation can then occur, manifested in 'black paint' or 'black sludge' in the engine. The presence of such carbonaceous deposits on a piston surface can act as an insulating layer which can result in the formation of cracks that then propagate through the piston. If a crack travels through the piston, hot combustion gases can enter the crankcase, possibly resulting in a crankcase explosion.

It is therefore highly desirable that trunk piston engine oils ('TPEO's) prevent or inhibit asphaltene precipitation. The prior art describes ways of doing this.

WO 96/26995 discloses the use of a hydrocarbyl-substituted phenol to reduce 'black paint' in a diesel engine. WO 96/26996 discloses the use of a demulsifier for water-in-oil emulsions, for example, a polyoxyalkylene polyol, to reduce 'black paint' in diesel engines. US-B2-7,053,027 describes use of one or more overbased metal carboxylate detergents in combination with an antiwear additive in a dispersant-free TPEO.

The problem of asphaltene precipitation is more acute at higher basestock saturate levels. WO 2008/128656 describes a solution by use of an overbased metal hydrocarbyl-substituted hydroxybenzoate detergent having a basicity index of less than 2 and a degree of

carbonation of 80% or greater in a marine trunk piston engine lubricant to reduce asphaltene precipitation in the lubricant. Mentioned, but not exemplified, are lubricants comprising Group III and Group IV basestocks, and exemplified are lubricants comprising a Group II basestock, all of which basestocks have high saturates levels.

The above-described solution is however restricted to a specific class of detergents. It is now found, in the present invention, that the problem in WO 2008/128656 is solved for a different range of overbased metal carboxylate detergents by employing, in combination therewith, an alkyl-substituted phenol other than a hindered phenol.

SUMMARY OF THE INVENTION

A first aspect of the invention is a trunk piston marine engine lubricating oil composition for improving asphaltene handling in use thereof, in operation of the engine when fuelled by a heavy fuel oil, which composition comprises or is made by admixing an oil of lubricating viscosity, in a major amount, containing 50 mass % or more of a basestock containing greater than or equal to 90% saturates and less than or equal to 0.03% sulphur or a mixture thereof, and, in respective minor amounts:

- (A) an overbased metal hydrocarbyl-substituted hydroxybenzoate detergent other than such a detergent having a basicity index of less than two and a degree of carbonation of 80% or greater, where degree of carbonation is the percentage of carbonate present in the overbased metal hydrocarbyl-substituted hydroxybenzoate detergent expressed as a mole percentage relative to the total excess base in the detergent; and
- (B) 5 to 500, preferably 15 to 90, mass % active ingredient, based on the active ingredient mass of (A), of an oil-soluble alkyl-substituted phenol other than a hindered phenol.

A second aspect of the invention is the use of a detergent (A) in combination with a component (B) as defined in, and in the amounts stated in, the first aspect of the invention in a trunk piston marine lubricating oil composition for a medium-speed compression-ignited marine engine, which composition comprises an oil of lubricating viscosity in a major amount

and contains 50 mass % or more of a basestock containing greater than or equal to 90% saturates and less than or equal to 0.03% sulphur or a mixture thereof, to improve asphaltene handling during operation of the engine, fueled by a heavy fuel oil, and its lubrication by the composition, in comparison with analogous operation when the same amount of detergent (A) is used in the absence of (B).

A third aspect of the invention is a method of operating a trunk piston medium-speed compression-ignited marine engine comprising

- (i) fueling the engine with a heavy fuel oil; and
- (ii) lubricating the crankcase of the engine with a composition as defined in the first aspect of the invention.

A fourth aspect of the invention is a method of dispersing asphaltenes in a trunk piston marine lubricating oil composition during its lubrication of surfaces of the combustion chamber of a medium-speed compression-ignited marine engine and operation of the engine, which method comprises

- (i) providing a composition as defined in the first aspect of the invention;
- (ii) providing the composition in the combustion chamber;
- (iii) providing heavy fuel oil in the combustion chamber; and
- (iv) combusting the heavy fuel oil in the combustion chamber.

In this specification, the following words and expressions, if and when used, have the meanings ascribed below:

“active ingredients” or “(a.i.)” refers to additive material that is not diluent or solvent;

“comprising” or any cognate word specifies the presence of stated features, steps, or integers or components, but does not preclude the presence or addition of one or more

other features, steps, integers, components or groups thereof; the expressions “consists of” or “consists essentially of” or cognates may be embraced within “comprises” or cognates, wherein “consists essentially of” permits inclusion of substances not materially affecting the characteristics of the composition to which it applies;

“major amount” means in excess of 50 mass % of a composition;

“minor amount” means less than 50 mass % of a composition;

“TBN” means total base number as measured by ASTM D2896.

Furthermore in this specification:

“calcium content” is as measured by ASTM 4951;

“phosphorus content” is as measured by ASTM D5185;

“sulphated ash content” is as measured by ASTM D874;

“sulphur content” is as measured by ASTM D2622;

“KV100” means kinematic viscosity at 100°C as measured by ASTM D445.

Also, it will be understood that various components used, essential as well as optimal and customary, may react under conditions of formulation, storage or use and that the invention also provides the product obtainable or obtained as a result of any such reaction.

Further, it is understood that any upper and lower quantity, range and ratio limits set forth herein may be independently combined.

DETAILED DESCRIPTION OF THE INVENTION

The features of the invention will now be discussed in more detail below.

OIL OF LUBRICATING VISCOSITY

The lubricating oils may range in viscosity from light distillate mineral oils to heavy lubricating oils. Generally, the viscosity of the oil ranges from 2 to 40 mm²/sec, as measured at 100°C.

Natural oils include animal oils and vegetable oils (e.g., castor oil, lard oil); liquid petroleum oils and hydrorefined, solvent-treated or acid-treated mineral oils of the paraffinic, naphthenic and mixed paraffinic-naphthenic types. Oils of lubricating viscosity derived from coal or shale also serve as useful base oils.

Synthetic lubricating oils include hydrocarbon oils and halo-substituted hydrocarbon oils such as polymerized and interpolymers of olefins (e.g., polybutylenes, polypropylenes, propylene-isobutylene copolymers, chlorinated polybutylenes, poly(1-hexenes), poly(1-octenes), poly(1-decenes)); alkybenzenes (e.g., dodecylbenzenes, tetradecylbenzenes, dinonylbenzenes, di(2-ethylhexyl)benzenes); polyphenyls (e.g., biphenyls, terphenyls, alkylated polyphenols); and alkylated diphenyl ethers and alkylated diphenyl sulphides and derivative, analogs and homologs thereof.

Alkylene oxide polymers and interpolymers and derivatives thereof where the terminal hydroxyl groups have been modified by esterification, etherification, etc., constitute another class of known synthetic lubricating oils. These are exemplified by polyoxyalkylene polymers prepared by polymerization of ethylene oxide or propylene oxide, and the alkyl and aryl ethers of polyoxyalkylene polymers (e.g., methyl-polyiso-propylene glycol ether having a molecular weight of 1000 or diphenyl ether of poly-ethylene glycol having a molecular weight of 1000 to 1500); and mono- and polycarboxylic esters thereof, for example, the acetic acid esters, mixed C₃-C₈ fatty acid esters and C₁₃ Oxo acid diester of tetraethylene glycol.

Another suitable class of synthetic lubricating oils comprises the esters of dicarboxylic acids (e.g., phthalic acid, succinic acid, alkyl succinic acids and alkenyl succinic acids, maleic acid, azelaic acid, suberic acid, sebacic acid, fumaric acid, adipic acid, linoleic acid dimer, malonic acid, alkylmalonic acids, alkenyl malonic acids) with a variety of alcohols (e.g., butyl alcohol, hexyl alcohol, dodecyl alcohol, 2-ethylhexyl alcohol, ethylene glycol, diethylene

glycol monoether, propylene glycol). Specific examples of such esters includes dibutyl adipate, di(2-ethylhexyl) sebacate, di-n-hexyl fumarate, dioctyl sebacate, diisooctyl azelate, diisodecyl azelate, dioctyl phthalate, didecyl phthalate, dieicosyl sebacate, the 2-ethylhexyl diester of linoleic acid dimer, and the complex ester formed by reacting one mole of sebacic acid with two moles of tetraethylene glycol and two moles of 2-ethylhexanoic acid.

Esters useful as synthetic oils also include those made from C₅ to C₁₂ monocarboxylic acids and polyols and polyol esters such as neopentyl glycol, trimethylolpropane, pentaerythritol, dipentaerythritol and tripentaerythritol.

Silicon-based oils such as the polyalkyl-, polyaryl-, polyalkoxy- or polyaryloxysilicone oils and silicate oils comprise another useful class of synthetic lubricants; such oils include tetraethyl silicate, tetraisopropyl silicate, tetra-(2-ethylhexyl)silicate, tetra-(4-methyl-2-ethylhexyl)silicate, tetra-(p-tert-butyl-phenyl) silicate, hexa-(4-methyl-2-ethylhexyl)disiloxane, poly(methyl)siloxanes and poly(methylphenyl)siloxanes. Other synthetic lubricating oils include liquid esters of phosphorous-containing acids (e.g., tricresyl phosphate, trioctyl phosphate, diethyl ester of decylphosphonic acid) and polymeric tetrahydrofurans.

Unrefined, refined and re-refined oils can be used in lubricants of the present invention. Unrefined oils are those obtained directly from a natural or synthetic source without further purification treatment. For example, a shale oil obtained directly from retorting operations; petroleum oil obtained directly from distillation; or ester oil obtained directly from an esterification and used without further treatment would be an unrefined oil. Refined oils are similar to unrefined oils except that the oil is further treated in one or more purification steps to improve one or more properties. Many such purification techniques, such as distillation, solvent extraction, acid or base extraction, filtration and percolation are known to those skilled in the art. Re-refined oils are obtained by processes similar to those used to provide refined oils but begin with oil that has already been used in service. Such re-refined oils are also known as reclaimed or reprocessed oils and are often subjected to additional processing using techniques for removing spent additives and oil breakdown products.

The American Petroleum Institute (API) publication "Engine Oil Licensing and Certification System", Industry Services Department, Fourteenth Edition, December 1996, Addendum 1, December 1998 categorizes base stocks as follows:

- a) Group I base stocks contain less than 90 percent saturates and/or greater than 0.03 percent sulphur and have a viscosity index greater than or equal to 80 and less than 120 using the test methods specified in Table E-1.
- b) Group II base stocks contain greater than or equal to 90 percent saturates and less than or equal to 0.03 percent sulphur and have a viscosity index greater than or equal to 80 and less than 120 using the test methods specified in Table E-1.
- c) Group III base stocks contain greater than or equal to 90 percent saturates and less than or equal to 0.03 percent sulphur and have a viscosity index greater than or equal to 120 using the test methods specified in Table E-1.
- d) Group IV base stocks are polyalphaolefins (PAO).
- e) Group V base stocks include all other base stocks not included in Group I, II, III, or IV.

Analytical Methods for Base Stock are tabulated below:

PROPERTY	TEST METHOD
Saturates	ASTM D 2007
Viscosity Index	ASTM D 2270
Sulphur	ASTM D 2622
	ASTM D 4294
	ASTM D 4927
	ASTM D 3120

By way of example, the present invention embraces Group II, Group III and Group IV basestocks and also basestocks derived from hydrocarbons synthesised by the Fischer-Tropsch process. In the Fischer-Tropsch process, synthesis gas containing carbon monoxide and hydrogen (or 'syngas') is first generated and then converted to hydrocarbons using a

Fischer-Tropsch catalyst. These hydrocarbons typically require further processing in order to be useful as a base oil. For example, they may, by methods known in the art, be hydroisomerized; hydrocracked and hydroisomerized; dewaxed; or hydroisomerized and dewaxed. The syngas may, for example, be made from gas such as natural gas or other gaseous hydrocarbons by steam reforming, when the basestock may be referred to as gas-to-liquid ("GTL") base oil; or from gasification of biomass, when the basestock may be referred to as biomass-to-liquid ("BTL" or "BMTL") base oil; or from gasification of coal, when the basestock may be referred to as coal-to-liquid ("CTL") base oil.


As stated, the oil of lubricating viscosity in this invention contains 50 mass % or more of the defined basestock or a mixture thereof. Preferably, it contains 60, such as 70, 80 or 90, mass % or more of the defined basestock or a mixture thereof. The oil of lubricating viscosity may be substantially all the defined basestock or a mixture thereof.

OVERBASED METAL DETERGENT (A)

A metal detergent is an additive based on so-called metal "soaps", that is metal salts of acidic organic compounds, sometimes referred to as surfactants. They generally comprise a polar head with a long hydrophobic tail. Overbased metal detergents, which comprise neutralized metal detergents as the outer layer of a metal base (e.g. carbonate) micelle, may be provided by including large amounts of metal base by reacting an excess of a metal base, such as an oxide or hydroxide, with an acidic gas such as carbon dioxide.

In the present invention, overbased metal detergents (A) are overbased metal hydrocarbyl-substituted hydroxybenzoate, preferably hydrocarbyl-substituted salicylate, detergents.

"Hydrocarbyl" means a group or radical that contains carbon and hydrogen atoms and that is bonded to the remainder of the molecule via a carbon atom. It may contain hetero atoms, i.e. atoms other than carbon and hydrogen, provided they do not alter the essentially hydrocarbon nature and characteristics of the group. As examples of hydrocarbyl, there may be mentioned alkyl and alkenyl. The overbased metal hydrocarbyl-substituted hydroxybenzoate typically has the structure shown:



wherein R is a linear or branched aliphatic hydrocarbonyl group, and more preferably an alkyl group, including straight- or branched-chain alkyl groups. There may be more than one R group attached to the benzene ring. M is an alkali metal (e.g. lithium, sodium or potassium) or alkaline earth metal (e.g. calcium, magnesium barium or strontium). Calcium or magnesium is preferred; calcium is especially preferred. The COOM group can be in the ortho, meta or para position with respect to the hydroxyl group; the ortho position is preferred. The R group can be in the ortho, meta or para position with respect to the hydroxyl group.

Hydroxybenzoic acids are typically prepared by the carboxylation, by the Kolbe-Schmitt process, of phenoxides, and in that case, will generally be obtained (normally in a diluent) in admixture with uncarboxylated phenol. Hydroxybenzoic acids may be non-sulphurized or sulphurized, and may be chemically modified and/or contain additional substituents. Processes for sulphurizing a hydrocarbonyl-substituted hydroxybenzoic acid are well known to those skilled in the art, and are described, for example, in US 2007/0027057.

In hydrocarbonyl-substituted hydroxybenzoic acids, the hydrocarbonyl group is preferably alkyl (including straight- or branched-chain alkyl groups), and the alkyl groups advantageously contain 5 to 100, preferably 9 to 30, especially 14 to 24, carbon atoms.

The term "overbased" is generally used to describe metal detergents in which the ratio of the number of equivalents of the metal moiety to the number of equivalents of the acid moiety is greater than one. The term 'low-based' is used to describe metal detergents in which the equivalent ratio of metal moiety to acid moiety is greater than 1, and up to about 2.

By an "overbased calcium salt of surfactants" is meant an overbased detergent in which the metal cations of the oil-insoluble metal salt are essentially calcium cations. Small amounts of other cations may be present in the oil-insoluble metal salt, but typically at least 80, more typically at least 90, for example at least 95, mole %, of the cations in the oil-insoluble metal salt, are calcium ions. Cations other than calcium may be derived, for

example, from the use in the manufacture of the overbased detergent of a surfactant salt in which the cation is a metal other than calcium. Preferably, the metal salt of the surfactant is also calcium.

Carbonated overbased metal detergents typically comprise amorphous nanoparticles. Additionally, there are disclosures of nanoparticulate materials comprising carbonate in the crystalline calcite and vaterite forms.

The basicity of the detergents may be expressed as a total base number (TBN). A total base number is the amount of acid needed to neutralize all of the basicity of the overbased material. The TBN may be measured using ASTM standard D2896 or an equivalent procedure. The detergent may have a low TBN (i.e. a TBN of less than 50), a medium TBN (i.e. a TBN of 50 to 150) or a high TBN (i.e. a TBN of greater than 150, such as 150-500). In this invention, Basicity Index and Degree of Carbonation may be used. Basicity Index is the molar ratio of total base to total soap in the overbased detergent. Degree of Carbonation is the percentage of carbonate present in the overbased detergent expressed as a mole percentage relative to the total excess base in the detergent.

Overbased metal hydrocarbyl-substituted hydroxybenzoates can be prepared by any of the techniques employed in the art. A general method is as follows:

1. Neutralisation of hydrocarbyl-substituted hydroxybenzoic acid with a molar excess of metallic base to produce a slightly overbased metal hydrocarbyl-substituted hydroxybenzoate complex, in a solvent mixture consisting of a volatile hydrocarbon, an alcohol and water;
2. Carbonation to produce colloidally-dispersed metal carbonate followed by a post-reaction period;
3. Removal of residual solids that are not colloidally dispersed; and
4. Stripping to remove process solvents.

Overbased metal hydrocarbyl-substituted hydroxybenzoates can be made by either a batch or a continuous overbasing process.

Metal base (e.g. metal hydroxide, metal oxide or metal alkoxide), preferably lime (calcium hydroxide), may be charged in one or more stages. The charges may be equal or

may differ, as may the carbon dioxide charges which follow them. When adding a further calcium hydroxide charge, the carbon dioxide treatment of the previous stage need not be complete. As carbonation proceeds, dissolved hydroxide is converted into colloidal carbonate particles dispersed in the mixture of volatile hydrocarbon solvent and non-volatile hydrocarbon oil.

Carbonation may be effected in one or more stages over a range of temperatures up to the reflux temperature of the alcohol promoters. Addition temperatures may be similar, or different, or may vary during each addition stage. Phases in which temperatures are raised, and optionally then reduced, may precede further carbonation steps.

The volatile hydrocarbon solvent of the reaction mixture is preferably a normally liquid aromatic hydrocarbon having a boiling point not greater than about 150°C. Aromatic hydrocarbons have been found to offer certain benefits, e.g. improved filtration rates, and examples of suitable solvents are toluene, xylene, and ethyl benzene.

The alkanol is preferably methanol although other alcohols such as ethanol can be used. Correct choice of the ratio of alkanol to hydrocarbon solvents, and the water content of the initial reaction mixture, are important to obtain the desired product.

Oil may be added to the reaction mixture; if so, suitable oils include hydrocarbon oils, particularly those of mineral origin. Oils which have viscosities of 15 to 30 mm²/sec at 38°C are very suitable.

After the final treatment with carbon dioxide, the reaction mixture is typically heated to an elevated temperature, e.g. above 130°C, to remove volatile materials (water and any remaining alkanol and hydrocarbon solvent). When the synthesis is complete, the raw product is hazy as a result of the presence of suspended sediments. It is clarified by, for example, filtration or centrifugation. These measures may be used before, or at an intermediate point, or after solvent removal.

The products are generally used as an oil solution. If the reaction mixture contains insufficient oil to retain an oil solution after removal of the volatiles, further oil should be added. This may occur before, or at an intermediate point, or after solvent removal.

In this invention, (A) may have:

- (A1) a basicity index of two or greater and a degree of carbonation of 80% or greater; or
- (A2) a basicity index of two or greater and a degree of carbonation of less than 80%; or
- (A3) a basicity index of less than two and a degree of carbonation of less than 80%.

ALKYL-SUBSTITUTED PHENOL (B)

As stated, the phenol constitutes 5 to 500, preferably 15 to 90, mass % of the mass of (A). More preferably it constitutes from 20 to 80, such as 30 to 70, for example 40 to 60, mass %.

The alkyl substituent in (B) may for example be a straight chain or branched, preferably a straight chain, single alkyl group having from 9 to 30, preferably 14 to 24, carbon atoms.

As an example of alkylphenol (B) there may be mentioned an alkyl benzenol where the alkyl substitution is, for example, in the 2-position or in the 4-position.

As a further example of alkylphenol (B) there may be mentioned an alkylnaphthol where the alkyl substitution is in the 1-position or in the 2-position.

As a further example of alkylphenol (B) there may be mentioned an alkyl phenol aldehyde condensate, preferably where the aldehyde is formaldehyde such that the condensate is a methylene-bridged alkylphenol. Examples of such condensates are known in the art such as in EP-A-1 657 292.

The treat rate of additives (A) and (B) contained in the lubricating oil composition may for example be in the range of 1 to 25, preferably 2 to 20, more preferably 5 to 18, mass %.

(A) and (B) may be provided together for the purpose of the invention by blending them together. Or, they may be provided together during the manufacture of (A) by incorporating (B) during the overbasing step to manufacture (A).

CO-ADDITIVES

The lubricating oil composition of the invention may comprise further additives, different from and additional to (A) and (B). Such additional additives may, for example include ashless dispersants, other metal detergents, anti-wear agents such as zinc dihydrocarbyl dithiophosphates, anti-oxidants and demulsifiers.

It may be desirable, although not essential, to prepare one or more additive packages or concentrates comprising the additives, whereby additives (A) and (B) can be added simultaneously to the base oil to form the lubricating oil composition. Dissolution of the additive package(s) into the lubricating oil may be facilitated by solvents and by mixing accompanied with mild heating, but this is not essential. The additive package(s) will typically be formulated to contain the additive(s) in proper amounts to provide the desired concentration, and/or to carry out the intended function in the final formulation when the additive package(s) is/are combined with a predetermined amount of base lubricant. Thus, additives (A) and (B), in accordance with the present invention, may be admixed with small amounts of base oil or other compatible solvents together with other desirable additives to form additive packages containing active ingredients in an amount, based on the additive package, of, for example, from 2.5 to 90, preferably from 5 to 75, most preferably from 8 to 60, mass % of additives in the appropriate proportions, the remainder being base oil.

The final formulations as a trunk piston engine oil may typically contain 30, preferably 10 to 28, more preferably 12 to 24, mass % of the additive package(s), the remainder being base oil. Preferably, the trunk piston engine oil has a compositional TBN (using ASTM D2896) of 20 to 60, such as 25 to 55.

EXAMPLES

The present invention is illustrated by but in no way limited to the following examples.

COMPONENTS

The following components were used:

Component (A):

- (A1) a calcium salicylate detergent having a TBN of 350 (basicity index of two or greater; a degree of carbonation of 80% or greater) and containing 6 mass % of alkylphenol;
- (A2) a calcium salicylate detergent having a TBN of 225 (basicity index of two or greater; a degree of carbonation of less than 80%) and containing 5 mass % of alkylphenol;
- (A3) a calcium salicylate detergent having a TBN of 65 (basicity index of less than two; a degree of carbonation of less than 80%) and containing 8 mass % of alkylphenol.
- (A3) and (B) a calcium salicylate detergent having a TBN of 67 (basicity index of less than two; a degree of carbonation of less than 80%), overbased in the presence of phenol B1 (see below). Two different products were made as indicated by TABLE 1 below.

Component (B):

- (B1) a mixed 2- and 4- (linear C16 alkyl) benzenol (2:1)
- (B2) a 1- (linear C16 alkyl) naphthol
- (B3) a 2-(linear C16 alkyl) naphthol

Base oil II: an API Group II 600R basestock from Chevron

Base oil III: an API Group III base oil known as XHV182

Base oil IV: an API Group IV base oil known as DURASYN82

HFO: a heavy fuel oil, ISO-F-RMK 380

LUBRICANTS

Selections of the above components were blended to give a range of trunk piston marine engine lubricants. Some of the lubricants are examples of the invention; others are reference examples for comparison purposes. The compositions of the lubricants tested when each contained HFO are shown in the tables below under the “Results” heading.

TESTING

Light Scattering

Test lubricants were also evaluated for asphaltene dispersancy using light scattering according to the Focused Beam Reflectance Method (“FBRM”), which predicts asphaltene agglomeration and hence ‘black sludge’ formation.

The FBRM test method was disclosed at the 7th International Symposium on Marine Engineering, Tokyo, 24th - 28th October 2005, and was published in ‘The Benefits of Salicylate Detergents in TPEO Applications with a Variety of Base Stocks’, in the Conference Proceedings. Further details were disclosed at the CIMAC Congress, Vienna, 21st -24th May 2007 and published in “Meeting the Challenge of New Base Fluids for the Lubrication of Medium Speed Marine Engines – An Additive Approach” in the Congress Proceedings. In the latter paper it is disclosed that by using the FBRM method it is possible to obtain quantitative results for asphaltene dispersancy that predict performance for lubricant systems based on base stocks containing greater than or less than 90% saturates, and greater than or less than 0.03% sulphur. The predictions of relative performance obtained from FBRM were confirmed by engine tests in marine diesel engines.

The FBRM probe contains fibre optic cables through which laser light travels to reach the probe tip. At the tip, an optic focuses the laser light to a small spot. The optic is rotated so that the focussed beam scans a circular path between the window of the probe and the sample. As particles flow past the window they intersect the scanning path, giving backscattered light from the individual particles.

The scanning laser beam travels much faster than the particles; this means that the particles are effectively stationary. As the focussed beam reaches one edge of the particle there is an increase in the amount of backscattered light; the amount will decrease when the focussed beam reaches the other edge of the particle.

The instrument measures the time of the increased backscatter. The time period of backscatter from one particle is multiplied by the scan speed and the result is a distance or chord length. A chord length is a straight line between any two points on the edge of a particle. This is represented as a chord length distribution, a graph of numbers of chord lengths (particles) measured as a function of the chord length dimensions in microns. As the measurements are performed in real time the statistics of a distribution can be calculated and tracked. FBRM typically measures tens of thousands of chords per second, resulting in a robust number-by-chord length distribution. The method gives an absolute measure of the particle size distribution of the asphaltene particles.

The Focused beam Reflectance Probe (FBRM), model Lasentec D600L, was supplied by Mettler Toledo, Leicester, UK. The instrument was used in a configuration to give a particle size resolution of 1 μm to 1mm. Data from FBRM can be presented in several ways. Studies have suggested that the average counts per second can be used as a quantitative determination of asphaltene dispersancy. This value is a function of both the average size and level of agglomerate. In this application, the average count rate (over the entire size range) was monitored using a measurement time of 1 second per sample.

The test lubricant formulations were heated to 60°C and stirred at 400rpm; when the temperature reached 60°C the FBRM probe was inserted into the sample and measurements made for 15 minutes. An aliquot of heavy fuel oil (10% w/w) was introduced into the lubricant formulation under stirring using a four blade stirrer (at 400 rpm). A value for the average counts per second was taken when the count rate had reached an equilibrium value (typically overnight).

RESULTS

Light Scattering

The results of the FBRM tests are summarized in TABLES 1 and 2 below. In TABLE 1, phenol B1 was incorporated into Ca salicylate during the overbasing step to produce (A)+(B).

In TABLE 2, phenols B1, B2 and B3 were each blended separately with overbased Ca salicylate (A1).

The base oil was Base Oil II.

All values in each table are mass% a.i. other than the particle count values in the right hand column. Comparative examples are designated "Ref" and examples of the invention designated "In".

TABLE 1

Ex	Salicylic acid	Phenol	Salicylic acid & Phenol	Particle counts
Ref 1	0	0	0	6000
Ref 2	0	4.0	4.0	4800
Ref 3	3.1	0.3	3.4	400
In 3	0.7	2.1	2.8	500
Ref 4	15.6	1.3	16.9	10
In 4	3.5	10.7	14.2	10

In 3 and In 4 each contain the same additive but at different treat rates. Likewise, Examples Ref 3 and Ref 4 each contain the same additive but at different treat rates.

Ref 2 shows that the phenol alone gave a very poor performance. Ref 3 shows that salicylate alone (with a small amount of inherent phenol) has a better performance. In 3 shows that, even when a much higher percentage of phenol is used, the performance remains much the same. (The expectation would be that the relative higher phenol content would

severely diminish performance). Ref 4 and In 4 illustrate the same point at higher concentrations.

TABLE 2

Ex	Salicylic acid	Phenol	Salicylic acid & Phenol	Particle counts
Ref 1	0	0	0	6000
Ref 2	0	4.0 (B1)	4.0	4800
Ref 5	8.0	0.8	8.8	2100
In 5	8.0	2.0 (B1)	10.0	900
In 6	8.0	4.0 (B1)	12.0	700
Ref 7	0	4.4 (B2)	4.4	8700
In 7	8.0	4.4 (B2)	12.4	1100
Ref 8	0	4.4 (B3)	4.4	5800
In 8	8.0	4.4 (B3)	12.4	1000

Results for In 5 and In 6 show that, as phenol B1 is added, performance improves over Ref 5. This is very surprising in view of the performance of B1 alone in Ref 2.

Results for In 7 and In 8 show the same surprising improvement for phenols B2 and B3 respectively given the very poor performance of B2 and B3 alone in Ref 7 and Ref 8 respectively.

TABLE 3 (Base oil III)

Ex	Ca Salicylate (A1) (mass % a.i.)	Component (B1) (mass % a.i.)	Particle count/s
Ref	-	12.06	38,189
Ref	17.19	-	23,969
	17.19	6.03	6,742
	17.19	12.06	14
Ref	11.46	-	26,496
	11.46	2.01	24,116
	11.46	4.02	17,517

TABLE 4 (Base oil IV)

Ex	Ca Salicylate (A1) (mass % a.i.)	Component (B1) (mass % a.i.)	Particle count/s
Ref	-	12.06	37,568
Ref	17.19	-	16,080
	17.19	6.03	10,113
	17.19	12.06	14

The results in Tables 3 and 4 show that, in both group III and Group IV base oils, combinations of (A) and (B), represented by (A1) and (B1), give better light scattering performance than (A) alone and than (B) alone.

CLAIMS

1. A trunk piston marine engine lubricating oil composition for improving asphaltene handling in use thereof, in operation of the engine when fuelled by a heavy fuel oil, which composition comprises or is made by admixing an oil of lubricating viscosity, in a major amount, containing 50 mass % or more of a basestock containing greater than or equal to 90% saturates and less than or equal to 0.03% sulphur or a mixture thereof, and, in respective minor amounts:
 - (A) an overbased metal hydrocarbyl-substituted hydroxybenzoate detergent other than such a detergent having a basicity index of less than two and a degree of carbonation of 80% or greater, where degree of carbonation is the percentage of carbonate present in the overbased metal hydrocarbyl-substituted hydroxybenzoate detergent expressed as a mole percentage relative to the total excess base in the detergent; and
 - (B) 5 to 500, preferably 15 to 90, mass % active ingredient, based on the active ingredient mass of (A) of an oil-soluble alkyl-substituted phenol other than a hindered phenol.
2. The composition as claimed in claim 1 wherein (A) has
 - (A1) a basicity index of two or greater and a degree of carbonation of 80% or greater;or
 - (A2) a basicity index of two or greater and a degree of carbonation of less than 80%;or
 - (A3) a basicity index of less than two and a degree of carbonation of less than 80%.
3. The composition as claimed in claim 1 or 2 wherein the alkyl substituent in (B) is a single alkyl group, preferably straight chain, having 9 to 30 carbon atoms.
4. The composition as claimed in any of claims 1 to 3 wherein (B) is an alkylbenzenol.
5. The composition as claimed in claim 4 wherein alkyl-substitution in the benzenol is in the 2-position or in the 4-position.

6. The composition as claimed in any of claims 1 to 3 wherein (B) is an alkyl naphthol.
7. The composition as claimed in claim 6 wherein alkyl-substitution in the naphthol is in the 1-position or in the 2-position.
8. The composition as claimed in any of claims 1 to 3 wherein (B) is a methylene-bridged alkylphenol.
9. The composition as claimed in any of claims 1 to 8 wherein (B) is provided in (A) during the overbasing step in the manufacture of (A).
10. The composition as claimed in any of claims 1 to 8 wherein (B) is blended separately with (A).
11. The composition as claimed in any of claims 1 to 10 wherein the metal in (A) is calcium.
12. The composition as claimed in any of claims 1 to 11 wherein the hydrocarbyl-substituted hydroxybenzoate in (A) is a salicylate, preferably C₉ to C₃₀ alkyl-substituted.
13. The composition as claimed in any one of claims 1 to 12 wherein the oil of lubricating viscosity contains more than 60 mass % of a basestock containing greater than or equal to 90% saturates and less than or equal to 0.03% sulphur or a mixture thereof.
14. The composition as claimed in any of claims 1 to 13 having a TBN of 20 to 60, such as 25 to 55.
15. The use of a detergent (A) as defined in claim 1 in combination with a component (B) as defined in, and in the amount stated in claim 1, in a trunk piston marine lubricating oil composition for a medium-speed compression-ignited marine engine, which composition comprises an oil of lubricating viscosity in a major amount and contains 50 mass % or more of a basestock containing greater than or equal to 90% saturates and less than or equal to 0.03% sulphur or a mixture thereof, to improve asphaltene

handling during operation of the engine, fueled by a heavy fuel oil, and its lubrication by the composition, in comparison with analogous operation when the same amount of detergent (A) is used in the absence of (B).

16. A method of operating a trunk piston medium-speed compression-ignited marine engine comprising
 - (i) fueling the engine with a heavy fuel oil; and
 - (ii) lubricating the crankcase of the engine with a composition as defined in any of claims 1 to 14.
17. A method of dispersing asphaltenes in a trunk piston marine lubricating oil composition during its lubrication of surfaces of the combustion chamber of a medium-speed compression-ignited marine engine and operation of the engine, which method comprises
 - (i) providing a composition as defined in any of claims 1 to 14;
 - (ii) providing the composition in the combustion chamber;
 - (iii) providing heavy fuel oil in the combustion chamber; and
 - (iv) combusting the heavy fuel oil in the combustion chamber.

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2010/002622

A. CLASSIFICATION OF SUBJECT MATTER

INV. C10M163/00 C10M169/04
 ADD. C10N30/04 C10N40/25

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

C10M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 96/26995 A (BP CHEMICALS ADDITIVES [GB]; COOK STEPHEN JAMES [GB]; ROBINSON PAUL KR) 6 September 1996 (1996-09-06) cited in the application paragraphs [0001], [0002], [0004], [0006], [0007]; examples -----	1-17
X	US 2007/027043 A1 (LE COENT JEAN-LOUIS [FR]) 1 February 2007 (2007-02-01) paragraphs [0121], [0127]; claims 1,11,15; table III -----	1-5,9, 11-13
X	EP 1 191 088 A (INFINEUM INT LTD [GB]) 27 March 2002 (2002-03-27) paragraphs [0076], [0083]; claims 1,3-5,12 ----- -/-	1-17



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

14 June 2010

Date of mailing of the international search report

21/06/2010

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040,
 Fax: (+31-70) 340-3016

Authorized officer

Bertrand, Samuel

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2010/002622

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2003/004069 A1 (HAMMOND STEVE [GB] ET AL) 2 January 2003 (2003-01-02) paragraphs [0075], [0079], [0086]; claims 1,4,12,15 -----	1-17
X	US 2007/117726 A1 (CARTWRIGHT STANLEY J [CA]) 24 May 2007 (2007-05-24) paragraphs [0110], [0115]; tables 1,2 -----	1-5, 10-13
A	WO 2008/128657 A2 (INFINEUM INT LTD [GB]; SKINNER PHILIP [GB]) 30 October 2008 (2008-10-30) claim 1 -----	1-17
X	WO 2008/128656 A2 (INFINEUM INT LTD [GB]; BERTRAM RICHARD DAVID [GB]; DOWDING PETER JOHN) 30 October 2008 (2008-10-30) cited in the application pages 28,34 -----	1-17

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2010/002622

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9626995	A	06-09-1996	NONE	
US 2007027043	A1	01-02-2007	CA 2551978 A1 EP 1749875 A1 JP 2007039689 A SG 129425 A1	29-01-2007 07-02-2007 15-02-2007 26-02-2007
EP 1191088	A	27-03-2002	NONE	
US 2003004069	A1	02-01-2003	AT 350435 T CA 2372478 A1 CN 1370816 A DE 60217204 T2 EP 1236791 A1 JP 4381644 B2 JP 2002275487 A SG 104959 A1	15-01-2007 16-08-2002 25-09-2002 11-10-2007 04-09-2002 09-12-2009 25-09-2002 30-07-2004
US 2007117726	A1	24-05-2007	AU 2006316648 A1 CA 2629559 A1 EP 1987116 A2 JP 2009516061 T WO 2007061698 A2	31-05-2007 31-05-2007 05-11-2008 16-04-2009 31-05-2007
WO 2008128657	A2	30-10-2008	CA 2686116 A1 CN 101668837 A CN 101668839 A EP 2150603 A2 US 2010069273 A1	30-10-2008 10-03-2010 10-03-2010 10-02-2010 18-03-2010
WO 2008128656	A2	30-10-2008	CA 2686115 A1 EP 2167620 A2 US 2010087347 A1	30-10-2008 31-03-2010 08-04-2010