### (19) World Intellectual Property Organization

International Bureau





## (43) International Publication Date 16 May 2002 (16.05.2002)

#### **PCT**

# (10) International Publication Number WO 02/38004 A1

(51) International Patent Classification<sup>7</sup>: A46B 7/06

(21) International Application Number: PCT/US01/40261

**(22) International Filing Date:** 8 March 2001 (08.03.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

09/526,679 16 March 2000 (16.03.2000) US

(63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:


US 09/526,679 (CON) Filed on 16 March 2000 (16.03.2000)

(71) Applicant (for all designated States except US):
GILLETTE CANADA COMPANY [CA/CA]; 4 Robert
Speck Parkway, Mississauga, Ontario L4Z 4C5 (CA).

- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BRAUN, Phillip, M. [IE/US]; 128 Beechwood Hill Trail, Exeter, RI 02822 (US). BREDALL, William, Alan [US/US]; 257 Marvilla Circle, Pacifica, CA 94044 (US). CLAIRE, Karen, Lynn [US/US]; 103 Liberty Ave #3, Somerville, MA 02144 (US). MASTERMAN, Thomas, Craig [US/US]; 121 Cityhomes Lane, Foster City, CA 94404 (US). MC-CONNELL, Mark, Edward [GB/US]; Unit 121, 880 Meridian Bay, Foster City, CA 94404 (US). ROBERTS, Michael, F. [IE/US]; 453 Commercial Street, Braintree, MA 02184 (US). OVERTHUN, Thomas [DE/US]; 82 Valley Street, San Francisco, CA 94110 (US).
- (74) Agent: GALLOWAY, Peter, D.; Ladas & Parry, 26 West 61st Street, New York, NY 10023 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,

[Continued on next page]

(54) Title: TOOTHBRUSH



(57) Abstract: A toothbrush includes a handle, a head extending from the handle, and a plurality of tooth cleaning elements, such as tufts of bristles, extending from the head. Each tooth cleaning element is supported for rotation about primarily only one axis. Each tooth cleaning element is rotatable independent of the other tooth cleaning element(s).



MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

#### **Published:**

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 02/38004 PCT/US01/40261

- 1 -

#### **TOOTHBRUSH**

The invention relates generally to the field of oral care, and in particular to toothbrushes.

5

10

15

20

25

30

A Japanese patent document having an application number of 3-312978 discloses a toothbrush having a multiplicity of tufts of nylon bristles. In a irst embodiment shown in Figures 1, 2 and 3, a plurality of cylindrical recessed ections in the head are set orthogonally to the longitudinal axial direction of a shank and are formed at equal intervals. Column-shaped rotary bodies 5 are respectively contained in the recessed sections. On the peripheral surfaces of the rotary bodies 5, along the axial direction, projected strip sections 5a are formed, and they are set in a state that they are positioned at the opening sections of the recessed sections. At the opening sections of the recessed sections, contact surfaces to be positioned on both the sides are formed. At both the ends of the upper surfaces of the projected strip, sections 5a, nylon bristles 6 are arranged to be vertically erected.

As shown in Figure 3, the arrangement described above allows bristles 6 to rotate during use of the brush. A problem with this brush is that two tufts of bristles are secured to each strip section 5a and thus must rotate in unison. As a result, an individual tuft of bristles cannot rotate independently of its "partner" tuft. The individual tuft may thus be prevented from achieving optimal penetration between two teeth during brushing because the partner tuft might contact the teeth in a different manner and interfere with rotation of the individual tuft.

Figures 4, 5 and 6 disclose a second embodiment in which each tuft of bristles is secured to the head by a ball and socket type arrangement. While this embodiment allows each tuft of bristles to swivel independent of the other tufts, it does have disadvantages. If a tuft of bristles is tilted out towards the side of the head and that tuft is positioned near the interface between the side and top surfaces of the teeth, chances are increased that the bristle tips will not even be in contact with the teeth during brushing. Further, random orientation in which the tufts can end up after brushing detracts from the attractiveness of the brush.

The present invention is directed to overcoming one or more of the problems set forth above. Briefly summarized, according to one aspect of the present invention, a toothbrush includes a handle, a head extending from the handle,

- 2 -

PCT/US01/40261

and a plurality of tooth cleaning elements, such as tufts of bristles, extending from the head. Each tooth cleaning element is supported for rotation about primarily only one axis. Each tooth cleaning element is rotatable independent of the other tooth cleaning element(s).

5

WO 02/38004

By having each tooth cleaning element supported for rotation about only one axis, the problems mentioned above for the ball and socket tuft support are avoided. That is, the chances are increased that the tooth cleaning element will remain in contact with teeth during brushing and the brush will be more attractive in appearance.

10

Further, as each tooth cleaning element is rotatable independent of the other tooth cleaning element(s), the problem discussed above with the first Japanese embodiment is avoided. Each tooth cleaning element can achieve optimal interdental penetration without interference from rotation by another tooth cleaning element.

15

These and other aspects, objects, features and advantages of the present invention will be more clearly understood and appreciated from a review of the following detailed description of the preferred embodiments and appended claims, and by reference to the accompanying drawings.

FIG. 1 is a perspective view of a toothbrush according to a first embodiment of the invention;

20

FIG. 2 is a partial sectional view of the head of the toothbrush of Fig. 1 and one of the tooth cleaning elements;

25

FIG. 3 is a sectional view taken along the lines 3-3 of Fig. 2; FIG. 4 is a front view of an alternative tooth cleaning element; and

FIG. 5 is a side view of the tooth cleaning element of Fig. 4.

Beginning with FIG. 1, a toothbrush 8 includes a handle 10 from which extends a head 12. Head 12 includes a first group of tooth cleaning elements 14, such as tufts of bristles, which are secured to the head in a conventional manner (e.g. by stapling or hot-tufting). Elements 14 are designed to clean the exposed surfaces of teeth.

30

A second group of tooth cleaning elements 16 are secured to head 12 such that each element can independently rotate about a single axis during use of

WO 02/38004

5

10

15


20

25

30

the brush. Each elements 16 can be a tuft of bristles or, alternatively, a single unitary fin made of plastic or rubber. Elements 16 are designed to penetrate in between teeth to clean the interdental spaces.

The interproximal residence time of elements 16 is significantly increased as compared to elements 14 which are rigidly fixed to head 12. An experiment was conducted in which the interproximal residence time was determined for fixed tufts at both a 0 degree (like element 14) and 16 degree forward angle, and for rotating tufts such as element 16. The tufts had an average of 40 bristles each with each bristle having a 7-mil diameter. Residence times were measured on a Single Filament Tester (SFT) with a load of 4g/tuft at velocities between 0.5 and 10 in/s.



The graph above shows interproximal of mobile tufts and fixed tufts in the interdental gap(s). The data are averages over 4 experiments. The error bars represent the error of the mean at the 95% confidence level. This experimental data shows that rotating tufts experience 1.6 times more interproximal residence time compared to angled fixed bristle tufts, and 2.7 times more interproximal residence time compared to vertical fixed bristle tufts. More interproximal residence time translates into better cleaning between teeth.

With reference to Figs. 2 and 3, the structure for enabling element 16

WO 02/38004 PCT/US01/40261

- 4 -

to rotate and its methods of manufacture will be described. Element 16 includes at its lower end a unitary bearing 18 which is cylindrical in shape and rounded at its ends. Bearing 18 can be formed by either melting some of the material from which element 16 is made, or by molding the bearing in a separate molding operation.

Such a molding operation would use a high flow material such as

Exxon Escorene Polypropylene PP-1105, or FINA Polypropylene 3824. It is
important to gate from both sides and to have very low pack pressure during the
molding operation. An undercut on element 16 is preferable in order to secure
bearing 18 to element 16. If bearing 18 is molded separately and then secured to
element 16, an adhesive can be used in place of the undercut to secure element 16
and bearing 18 together.

5

10

15

20

25

An example of a specific molding operation would be to use a 90 Ton Toshiba Injection Molding Machine to mold Exxon Escorene Polypropylene PP-1105. The temperature profile is a 350F barrel temperature, a 350F rear temperature, a 405F front temperature and a 390F nozzle temperature. The mold temperature is preferably about 90F, and a 1/16 inch nozzle should be used. Fill time is 0.25 seconds, screw forward time is 3.75 seconds, injection time is 4.00 seconds and cool time is 15 seconds. Peak hydraulic pressure is 250psi.

Head 12 is actually made up of a top piece 22 and a bottom piece 24. Both of these pieces are created in separate molding steps with piece 22 being integrally molded with the brush handle. Element 16 is inserted through an aperture 25 in top piece 22 bearing end last to the position shown in the figures. Aperture 25 includes a bearing socket 20 which captures bearing 18. It is preferable to insert a viscous substance, such as some food-grade grease, into socket 20 to provide some resistance to rotation of element 16 to prevent the element from loosely flopping back and forth. Finally, piece 24 is fixed to piece 22 to secure bearing 18 in socket 20. Piece 24 can be secured to piece 22 by, for example, snap features (not shown) or heat welding. Alternatively, piece 24 can be injection molded into place.

An alternative manufacturing method to using two pieces 22, 24 for the head is to injection mold the entire head (and handle) about bearing 18. A higher melting temperature material would need to be used for element 16 and bearing 18 so that they are not softened/melted during injection molding of the

WO 02/38004 PCT/US01/40261

- 5 -

head/handle. Element 16 can be exercised after completion of the brush by rotating the element back and forth to free it in the event some plastic from the head is interfering with rotation.

The arrangement described above allows element 16 to rotate back and forth about only one axis 26 which is preferably substantially perpendicular to a long axis of element 16. Preferably, element 16 can rotate about 30 degrees either side of vertical. The top of aperture 25 limits the amount of rotation that can be experienced by element 16. It should be noted that there is no spring force or other force which returns element 16 to a home position, so the element can end up at any one of an infinite number of positions along its 60 degree freedom of movement at the end of the brushing process.

5

10

15

20

25

30

Alternatively, bearing 18 could be made in a spherical shape. Use of such a spherical bearing would still only allow element 16 to rotate about only one axis because, as shown in Fig. 2, head 12 fits up against opposite sides of element 16, thereby restricting rotation to occurring about one axis only.

Turning to Figs. 4 and 5, an alternative tooth cleaning element will be described. Element 30 includes a tooth cleaning portion 32 which can be a tuft of bristles or a unitary plastic or rubber fin. A hinge 34 (e.g. a living hinge) made of a soft plastic or elastomer is injection molded onto cleaning portion 32. The material from which hinge 34 is made must be carefully selected, because if it is too soft, retention of element 16 will be poor, and if the material is too hard, the hinge will not be flexible enough. The hinge is preferably made of GLS Corp.'s DYNAFLEX thermoplastic rubber compound G2780 or G2711 and can be injection molded under the conditions outlined above. The living hinge allows cleaning portion 32 to rotate primarily only about an axis 36 which, as described above, is preferably substantially perpendicular to a long axis of portion 32. Resistance to rotation increases as portion 32 is moved away from a position vertical to the top surface of the brush head. A toothbrush head 38 with integral handle (not shown) is injection molded about a base portion of living hinge 34 to capture the living hinge in the head (see Fig. 4).

- 6 -

#### CLAIMS

A toothbrush, comprising:

a handle;

15

20

- a head extending from the handle; and
- a plurality of tooth cleaning elements extending from the head, each tooth cleaning element being supported for rotation primarily about only one axis, each tooth cleaning element being rotatable independent of the other tooth cleaning element(s).
- 2. The toothbrush of claim 1, wherein each tooth cleaning element is a tuft of bristles.
  - 3. The toothbrush of claim 1, wherein each tooth cleaning element is a fin made of a material selected from the group of materials consisting of plastic and rubber.
  - 4. The toothbrush of claim 1, wherein each tooth cleaning element has a range of rotation of about 60 degrees.
    - 5. The toothbrush of claim 1, wherein each tooth cleaning element can rotate about 30 degrees to either side of a vertical position in which the element is perpendicular to a top surface of the head.
  - 6. The toothbrush of claim 1, further including one or more stationary tooth cleaning elements which substantially cannot be rotated.
    - 7. The toothbrush of claim 1, wherein each tooth cleaning element includes at its non-brushing end a bearing which is substantially cylindrical in shape in its major portion, each bearing being secured in its own hollow space within the head, each bearing allowing rotation of its respective tooth cleaning element.
- 25 8. The toothbrush of claim 7, wherein the head is made of at least two pieces which are joined together to secure the bearing within the head.
  - 9. The toothbrush of claim 1, wherein a portion of the head limits rotation of each tooth cleaning element.
- 10. The toothbrush of claim 1, wherein there is no portion of the toothbrush itself which rotates the tooth cleaning elements.
  - 11. The toothbrush of claim 7, wherein a viscous substance is provided in each hollow space in the head to provide some resistance to rotation of the tooth

- 7 -

PCT/US01/40261


cleaning elements.

WO 02/38004


5


12. The toothbrush of claim 1, wherein each tooth cleaning element includes at its non-brushing end a living hinge, each living hinge being secured partially within the head, each living hinge allowing rotation of its respective tooth cleaning element.

. 13. The toothbrush of claim 1, wherein the axis about which each tooth cleaning element is rotatable is substantially perpendicular to a long axis of the element.




2/3





PCT/US01/40261



#### INTERNATIONAL SEARCH REPORT

PCT/US 01/40261

# A. CLASSIFICATION OF SUBJECT MATTER IPC 7 A46B7/06

According to International Patent Classification (IPC) or to both national classification and IPC

#### B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A46B A46D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

#### EPO-Internal

C. DOCUME	NTS CONSIDERED TO BE RELEVANT			
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
Х	DE 198 17 704 A (MEYER FELICITAS) 14 October 1999 (1999-10-14) column 3, line 14 - line 37 figures	1,2,4-6, 9,10		
Υ	i igui es	3,7,8, 12,13		
Α		11		
Υ	US 5 896 614 A (FLEWITT HARRY) 27 April 1999 (1999-04-27) column 4, line 27 - line 33 figure 1	3		
Υ	US 5 991 959 A (RAVEN STEPHEN JOHN ET AL) 30 November 1999 (1999-11-30) column 7, line 5 - line 13 figure 16	7,8,12		

Further documents are listed in the continuation of box C.	X Patent family members are listed in annex.
Special categories of cited documents:  A' document defining the general state of the art which is not considered to be of particular relevance  E' earlier document but published on or after the international filing date  L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  O' document referring to an oral disclosure, use, exhibition or other means  P' document published prior to the international filing date but later than the priority date claimed	<ul> <li>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</li> <li>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</li> <li>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</li> <li>"&amp;" document member of the same patent family</li> </ul>
Date of the actual completion of the international search	Date of mailing of the international search report
13 December 2001	20/12/2001
Name and mailing address of the ISA	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL – 2280 HV Rijswijk Tel. (+31–70) 340–2040, Tx. 31 651 epo nl, Fax: (+31–70) 340–3016	Ottesen, R

### INTERNATIONAL SEARCH REPORT

PCT/US 01/40261

		PC1/US 01/40261		
	ation) DOCUMENTS CONSIDERED TO BE RELEVANT			
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
Υ	US 5 269 038 A (BRADLEY TERRY G) 14 December 1993 (1993-12-14) column 2, line 12 - line 26 column 4, line 31 -column 5, line 8 column 6, line 51 - line 59 figures	13		
Х	US 2 263 802 A (ARTHUR GRUSIN) 25 November 1941 (1941-11-25) page -	1,2,4,5, 9,10,13		
A	wo 99 37181 A (SANOFI SYNTHELABO ;SOETEWEY LODE (FR); BEAUGENDRE LYDIE (FR)) 29 July 1999 (1999-07-29) figure 3			

### INTERNATIONAL SEARCH REPORT

PCT/US 01/40261

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
DE 19817704	A	14-10-1999	DE	19817704 A1	14-10-1999
US 5896614	Α	27-04-1999	AU	4172696 A	17-06-1996
			EP	0792114 A1	03-09-1997
			JP	10509884 T	29-09-1998
			WO	9615696 A1	30-05-1996
			ZA 	9509780 A	01-10-1996
US 5991959	Α	30-11-1999	AU	6398398 A	08-09-1998
			BR	9807384 A	14-03-2000
			CN	1248151 T	22-03-2000
			WO	9835584 A1	20-08-1998
			EP	1009253 A1	21-06-2000
			HU	0001484 A2	28-08-2000
			PL	335158 A1	10-04-2000
US 5269038	Α	14-12-1993	AU	2400092 A	02-11-1992
			DE	69228115 D1	18-02-1999
			EP	0585408 A1	09-03-1994
			WO	9217094 A1	15-10-1992
	. <b></b>		US	5398366 A	21-03-1995
US 2263802	Α	25-11-1941	NONE		
WO 9937181	Α	29-07-1999	FR	2773962 A1	30-07-1999
			AU	2061499 A	09-08-1999
			BR	9907247 A	31-10-2000
			EP	1051093 A1	15-11-2000
			WO	9937181 A1	29-07-1999
			HU	0101301 A2	28-08-2001
			NO	20003098 A	20-09-2000
			PL	341936 A1	07-05-2001
			SK	10882000 A3	09-04-2001
			US	6311358 B1	06-11-2001