

i
a
5 c
v
u
b
10 l
o
i
t
15 v
c
t
t
20 a
w
ti
in
25 a
t
d
30 d
tl
p
fi
ir
35 st
tl
lc
ir
p
40 7
n
is
ti
to
45 fi
is
o
is
50 p
w
10
wi
ma
55 rek
cha

imp
ter-
tom
ter- 60
nds
20,
pars
nted
wer 65
erg-
sup-
rose
rms
11 70
29,
ped
cyl-
one
cor- 75
ted
the
the
lose 80
inst
uter
s 30
l of
5 is 85
will
ned
line
90
ody,
wer
lead
der,
n, a 95
said
hed
said
and
sure 100
said
cyl-
rom
nder 105
sing
er a
said
said
one 110
hav-
ear-

ing carried by said head over which said member operates and means for supplying fluid under pressure into said fixed cylinder.

3. An elevator including a support, a vertically movable platform, a bracket on which said platform is mounted, a pair of telescopically arranged cylinders, one being fixed to and upstanding from said support and having its upper end open and the other being movable and working over said fixed cylinder, a head closing the upper end of the movable cylinder, bearings carried by said bracket and running on said movable cylinder which forms a track therefor, a frame carried by said head, sheaves carried by said frame, flexible members operating over said sheaves and connected at one end to the platform and at their other ends to an anchor and means for supplying fluid under pressure into said fixed cylinder.

4. An elevator including a portable truck body, a fluid container carried thereby, a cylinder fixed to and upstanding from said body and having its upper end open, a cylinder telescoping over the fixed cylinder and movable relative thereto and having its upper end closed, bearings carried by and movable with said movable cylinder, a platform support, a platform carried thereby, bearings carried by the platform support and movable along said movable cylinder, flexible members having connection at one end to the platform and at their other ends to a fixed anchor and operative over the bearings carried by the movable cylinder and means carried by said body for introducing fluid under pressure from said container into said fixed cylinder.

5. An elevator including a portable body, a fluid container carried thereby, a cylinder upstanding from said body and having its upper end open, a cylinder telescoping over the fixed cylinder and movable relative thereto and having its upper end closed, bearings carried by and movable with said movable cylinder, a platform support, a platform carried thereby, bearings carried by the platform support and movable along said mov-

able cylinder, flexible members having connection at one end of the platform and at their other ends to a fixed anchor and operative over the bearings carried by the movable cylinder and means carried by said body for introducing fluid under pressure from said container into said fixed cylinder, said means comprising a pump having a suction line leading from said container and a fluid pressure line leading into the fixed cylinder.

6. An elevator including a portable truck body, a fluid container carried thereby, a cylinder fixed to and upstanding from said body and having its upper end open, a cylinder telescoping over the fixed cylinder and movable relative thereto and having its upper end closed, bearings carried by and movable with said movable cylinder, a platform support, a platform carried thereby, bearings carried by the platform support and movable along said movable cylinder, flexible members having connection at one end to the platform and at the other ends to a fixed anchor and operative over the bearings carried by the movable cylinder and means carried by said body for introducing fluid under pressure from said container into said fixed cylinder, said means comprising a pump having a suction line leading from said container and a fluid pressure line leading into the fixed cylinder and a valve controlled branch line leading from the fluid pressure line into said container.

7. An elevator including a truck body, telescopically arranged cylinders, the lower end of one being fixed to said body, a head closing the upper end of the other cylinder, a frame fixed to said head, load supporting means a flexible member one end of which is attached to said body and the other end of which is attached to said means, a bearing carried by said frame and over which the flexible member operates, and means for introducing fluid under pressure into and for relieving the same from said cylinder.

In testimony whereof I have signed my name to this specification.

GRIFFIN C. THRIFT.