



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



Publication number: **0 179 607 B1**

12

## EUROPEAN PATENT SPECIFICATION

45 Date of publication of patent specification: **18.09.91** 51 Int. Cl.<sup>5</sup>: **B41J 2/17**

21 Application number: **85307373.2**

22 Date of filing: **14.10.85**

54 **Ink jet apparatus.**

30 Priority: **15.10.84 US 661029**  
**16.10.84 US 661924**

43 Date of publication of application:  
**30.04.86 Bulletin 86/18**

45 Publication of the grant of the patent:  
**18.09.91 Bulletin 91/38**

34 Designated Contracting States:  
**BE CH DE FR GB IT LI LU NL**

56 References cited:  
**EP-A- 0 097 823**  
**US-A- 3 247 519**  
**US-A- 4 106 030**

73 Proprietor: **DATAPRODUCTS CORPORATION**  
**6200 Canoga Avenue**  
**Woodland Hills California 91365(US)**

72 Inventor: **DeYoung, Thomas William**  
**Rt. 1 Box 289 Overhill Road**  
**Stormville New York 12582(US)**

74 Representative: **Stanley, David William et al**  
**APPLEYARD LEES & CO. 15 Clare Road Hali-**  
**fax**  
**West Yorkshire HX1 2HY(GB)**

**EP 0 179 607 B1**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

## Description

This invention relates to an ink jet wherein the ink employed within the jet is of the phase change type, which may be referred to as hot melt ink.

5 The phase change, or hot melt ink, of the type utilized in an ink jet is characteristically solid at room temperature. When heated, the ink will melt to a consistency so as to be jettable.

European Patent Application Number 0 097 823 describes an ink jet recording system comprising an ink jet, a reservoir, an orifice for ejecting hot melt ink in a liquid state from the reservoir, an ink inlet for supply of hot melt ink and heater means for heating hot melt ink and to maintain the ink in a liquid state.

10 It has been found that improper heating may degrade the ink and thus the performance of an ink jet. In order to avoid such degradation by extended heating, the reservoir is allowed to cool during standby and only the head is heated, thereby limiting the amount of ink heated and minimizing degradation of the ink with its adverse effects on performance.

15 It has also been found that extremely high, localized temperatures in an ink jet apparatus can subject the localized ink to undesirable conditions which will result in localized ink degradation which, of course, can also affect performance. Moreover, temperature gradients, i.e., variations in temperatures from one location to another location, in the ink jet apparatus can adversely affect performance of the ink jet. In addition to degrading performance, the above-discussed temperature effects can adversely affect reliability.

20 According to the invention there is provided a hot melt ink jet printing apparatus for ejecting droplets of phase change ink comprising at least one ink jet including a chamber, an orifice for ejecting phase change ink in a liquid state from said chamber, an ink inlet for supply of phase change ink in a liquid state to said chamber, and a reservoir containing a supply of the phase change ink, said reservoir coupled to the inlet of said at least one ink jet, characterized in that said apparatus comprises first heater means for heating phase change ink in said jet(s) so as to undergo a phase change from a solid state to a liquid state without degrading the ink, second heater means for heating ink in said reservoir so as to undergo a phase change from a solid state to a liquid state without degrading the ink, and thermal resistance barrier means between said ink jet and said reservoir, whereby said first heater means is adapted to be controlled independently of said second heater means, thereby enabling said ink jet to be maintained at a different temperature than said reservoir, said jet(s) comprising a material having a thermal conductivity of at least 0.03 g cal/sec cm<sup>2</sup> (°C/cm) [12.55 W/(m.K)].

30 With at least some embodiments of the invention, one or more of the following may be achieved:-

- minimizing the effects of heating on performance and reliability in a phase change ink jet system.
- providing a high degree of reliability in a phase change ink jet system.
- minimizing temperature gradients in such an ink jet system, including localized hot spots.
- 35 - providing an ink jet system of the phase change type which may be allowed to cool in the standby mode and be rapidly brought up to the desired operating temperature.
- providing an ink jet system of the phase change type comprising a material which will not adversely react with the ink contained within the system.
- minimizing the weight associated with the ink jet system, thereby permitting rapid movement of an ink jet relative to a surface being scanned.

40 Preferably, the ink jet material has a thermal conductivity of at least 0.2 g cal/sec cm<sup>2</sup> (°C/cm) [83.68 W/(m.K)].

Any of a plurality of highly thermally conductive materials may be utilized including stainless steel, although aluminum is preferred.

45 In accordance with a preferred embodiment of this invention, the apparatus comprises a reservoir which is also coupled to the heater means. The reservoir also comprises a material having a thermal conductivity of at least 0.03 g cal/sec cm<sup>2</sup> (°C/cm) [12.55 W/(m.K)] preferably more than 0.2 g cal/sec cm<sup>2</sup> (°C/cm) [83.68 W/(m.K)].

50 The invention will be better understood from the following description given by way of example and with reference to the accompanying drawing in which Fig. 1 is a sectional view of one form of ink jet system in accordance with this invention.

Referring to Fig. 1, an ink jet apparatus comprises an imaging head 10 including at least one ink jet 12 and a reservoir 14. The ink jet apparatus is adapted to jet droplets of hot melt or phase change ink. Substantially all of the imaging head 10 and the reservoir 14 in contact with the melted ink comprises a highly thermally conductive material so as to minimize temperature gradients and thereby avoid degradation of the ink and assure high performance and reliability of the ink jet apparatus.

As shown in Fig. 1, a block of solid state ink 16 is juxtaposed to an opening in a trough 18. When the pellet 16 drops into the trough 18, the pellet 16 proceeds to melt in response to heat generated by a heater

20 located at the base of the reservoir 14 below a sloping surface 22.

As shown in Fig. 1, the ink jet 12 includes a chamber 24 having an orifice 26 for ejecting droplets of ink and an inlet 28 extending to the lowermost extremity 30 of the reservoir 14 adjacent the sloping bottom 22.

5 The head 10 is provided with an independent heater 32 located between a thermal resistance barrier 34 comprising insulation and a head member 36. By providing the heater 32 which is independent of the heater 20, it is possible to maintain the head 10 at a different temperature from the reservoir 14. This allows the reservoir 14 and the ink within the reservoir to be cooled in the standby mode thereby avoiding cooking of and resulting degradation of a large volume of ink while at the same time maintaining the ink within the imaging head 10 in a liquid state so as to prevent depriming.

10 With respect to the prevention of depriming, it will be appreciated that inlet 28 passes through the head member 36 which is highly conductive such that heat is conducted to the end 38 which maintains a pool of ink 40 in the liquid state in the immediate vicinity of the end 38 while the remainder of the ink within the reservoir 14 is able to cool to the solid state when the system is in a standby mode. As shown in Fig. 1, the pool 40 of liquid ink is maintained in an otherwise solid state mass 42 of ink extending up to a level 44.

15 As also shown in Fig. 1, a transducer 46 is juxtaposed to the end of the chamber 24. The transducer which is provided with electrodes is energized by a signal provided through a printed circuit board 48 located above the member 36. The transducer 46 and the printed circuit board 48 are then housed within head members 50 and 52.

20 As also shown in Fig. 1, the head includes a chamber plate 54 forming the chamber 24, which is in communication with a foot 56 located at the end of the transducer 46. As the transducer changes state in response to signals applied, the position of the foot 56 varies so as to expand and compress the volume within the chamber 24. The inlet 28 supplies a manifold 58 located in a plate 60 which is coupled to restricted inlets to the jet 12. Actually, the manifold 58 serves a plurality of restricted inlets in an array of ink jets identical to the jet 12 shown in Fig. 1.

25 The reservoir 14 as shown in Fig. 1 also includes a filter 62 which is located below a port 64 which is adapted to be opened and closed by a needle valve 66. The needle valve 66 is employed to close the port 64 during the priming operation.

30 As also shown in Fig. 1, the insulating barrier 34 which provides a high thermal resistance path is sealed against portion 70 of the reservoir 14, using an O-ring 72 which is also characterized by adequate insulating properties. Preferably, the member 36 which extends down into the reservoir 14 toward the lowermost portion 30 is slightly spaced from portion 70 of the reservoir 14. This spacing assures an adequate thermal barrier and high thermal resistance path so as to permit independent heating of the ink within the head as compared to the heat within the reservoir 14.

35 Finally, Fig 1 shows redundant level sensing elements 74 and 76, which may comprise RF level sensing or other electrical sensor means. Baffles 78 are also provided in the reservoir 14.

40 As stated in the foregoing, it is preferred that the head 10 as well as the reservoir 14 have a thermal conductivity in excess of  $0.03 \text{ g cal/sec cm}^2 \text{ (}^\circ\text{C/cm)}$  [ $12.55 \text{ W/(m.K)}$ ]. Preferably, the thermal conductivity of the head 10 and the reservoir 14 is in excess of  $0.2 \text{ g cal/sec cm}^2 \text{ (}^\circ\text{C/cm.)}$  [ $83.68 \text{ W/(m.K)}$ ]. In this connection, it is preferred to utilize aluminum although stainless steel may be utilized as well as other materials having similar conductivities, e.g., metallic and plastic composites.

Various materials suitable for use are set forth in the following table:

45

50

55

	<u>MATERIAL</u>	<u>THERMAL CONDUCTIVITIES</u>	
		<u>g cal/sec cm<sup>2</sup> (°C/cm)</u>	<u>W/(m.K)</u>
5	Copper	0.92	384.93
	Aluminum - 99%	0.50	209.20
	Aluminum 7075	0.289	120.92
10	Aluminum 6061	0.409	171.13
	Aluminum 356	0.36-0.40	150.62-167.36
	Aluminum A13	0.29	121.34
	Aluminum 380	0.23-0.26	104.60-129.70
15	Brass	0.25-0.31	104.60-129.70
	400 Series		
	Stainless Steel		
20	(420)	0.0595	24.89
	300 Series		
	Stainless Steel		
25	(316)	0.0389	16.28

Where the preferred material of aluminum is utilized, the advantages associated with high thermal conductivity so as to minimize so as to minimize temperature gradients and hot spots is achieved as well as rapid heating to the desired operating temperature. In addition, aluminum by virtue of its relatively low density provides a relatively lightweight imaging head 10 and reservoir 14 so as to minimise the inertia of the head 10 and the reservoir 14, thereby permitting rapid movement of the jet with respect to a surface being scanned. Moreover, aluminum will not chemically react with ink.

Of course, it is clear that the entire imaging head 10 and entire reservoir 14 does not comprise the high thermal conductivity material. For example, thermal resistance barrier 34 may comprise a material having a thermal conductivity less than 0.005 g cal/sec cm<sup>3</sup> (°C/cm) [2.09 W/(m.K)]. The thermal barrier may also be achieved without benefit of insulation by minimising the metal contact between the head 10 and the reservoir 14. However, substantially all of the head 10 and the reservoir 14 which is in direct or indirect contact with the ink does comprise the high thermal conductivity material, a notable exception including the filter 62. Indirect contact is achieved where the material such as copper is coated so as to minimize any reaction with the ink. It is also possible to utilise more than one high thermal conductivity material in the ink jet apparatus. For example, it may be possible to make a portion of the head 10 from aluminum with a portion or all of the reservoir 14 comprises stainless steel.

#### 45 Claims

1. A hot melt ink jet printing apparatus for ejecting droplets of phase change ink comprising at least one ink jet (12) including a chamber (24), an orifice (26) for ejecting phase change ink in a liquid state from said chamber, an ink inlet (28) for supply of phase change ink in a liquid state to said chamber, and a reservoir (14) containing a supply of the phase change ink, said reservoir coupled to the inlet of said at least one ink jet, characterized in that said apparatus comprises first heater means (32) for heating phase change ink in said jet(s) so as to undergo a phase change from a solid state to a liquid state without degrading the ink, second heater means (20) for heating ink in said reservoir so as to undergo a phase change from a solid state to a liquid state without degrading the ink, and thermal resistance barrier means (34) between said ink jet and said reservoir, whereby said first heater means is adapted to be controlled independently of said second heater means, thereby enabling said ink jet to be maintained at a different temperature than said reservoir, said jet(s) comprising a material having a thermal conductivity of at least 0.03 g cal/sec cm<sup>2</sup> (°C/cm) [12.55 W/(m.K)].

2. An apparatus according to claim 1, wherein said material has a thermal conductivity of at least 0.2 g cal/sec cm<sup>2</sup> (°C/cm) [83.68 W/(m.K)].
3. An apparatus according to claim 1, wherein said material comprises stainless steel.
- 5 4. An apparatus according to claim 1, wherein said material comprises aluminum.
5. An apparatus according to any preceding claim, wherein said apparatus comprises a reservoir (14) coupled to said second heater means (20), said reservoir (14) also comprising a material having a  
10 thermal conductivity of at least 0.03 g cal/sec cm<sup>2</sup> (°C/cm) [12.55 W/(m.K)].
6. An apparatus according to claim 5, wherein said material of said reservoir (14) has a thermal conductivity of at least 0.2 g cal/sec cm<sup>2</sup> (°C/cm) [83.68 W/(m.K)].
- 15 7. An apparatus of claim 5, wherein said material of said reservoir (14) comprises stainless steel.
8. An apparatus of claim 5, wherein said material of said reservoir (14) comprises aluminum.

### Revendications

- 20 1. Un dispositif d'impression à jet d'encre liquéfiée à chaud, pour éjecter des gouttes d'encre à changement de phase comprenant, au moins, un ajutage d'encre (12) comprenant une chambre (24), un orifice (26) pour éjecter de l'encre à changement de phase à l'état liquide à partir de ladite  
25 chambre, une entrée d'encre (28) pour alimenter de l'encre à changement de phase à l'état liquide vers ladite chambre, et un réservoir (14) contenant un approvisionnement d'encre à changement de phase, ledit réservoir étant relié à l'entrée au moins dudit ajutage d'encre, caractérisé en ce que ledit dispositif comprend des premiers moyens de chauffage (32) pour chauffer l'encre à changement de phase dans le ou les ajutages d'encre, de manière à lui faire subir un changement de phase, de l'état solide à l'état liquide, sans dégradation de l'encre, des seconds moyens de chauffage (20) pour  
30 chauffer l'encre dans ledit réservoir, pour lui faire subir un changement de phase, de l'état solide à l'état liquide sans dégradation de l'encre, et des moyens formant barrière à résistance thermique (34), entre ledit ajutage d'encre et ledit réservoir, de manière que lesdits premiers moyens de chauffage soient adaptés de façon à être réglés indépendamment desdits seconds moyens de chauffage, afin de permettre de maintenir ainsi ledit ajutage d'encre à une température différente de celle dudit réservoir,  
35 le ou lesdits ajutages d'encre étant composés d'un matériau possédant une conductibilité thermique d'au moins 0,03 g cal / sec.cm<sup>2</sup> (°C/cm) {12,55 W/(m.K)}.
2. Un dispositif à jet d'encre selon la revendication 1, dans lequel ledit matériau a une conductibilité thermique d'au moins 0,2 g.cal/sec.cm<sup>2</sup> (°C/cm) {83,68 W/(m.K)}.
- 40 3. Un dispositif à jet d'encre selon la revendication 1, dans lequel ledit matériau comprend l'acier inoxydable.
4. Un dispositif à jet d'encre selon la revendication 1, dans lequel ledit matériau comprend l'aluminium.
- 45 5. Un dispositif à jet d'encre selon l'une quelconque des précédentes revendications, dans lequel ledit dispositif comprend un réservoir (14) relié auxdits seconds moyens de chauffage (20), ledit réservoir (14) comprenant également un matériau possédant une conductibilité thermique d'au moins 0,03 g.cal/sec cm<sup>2</sup> (°C/cm) {12,55 W / (m.K)}.
- 50 6. Un dispositif selon la revendication 5, dans lequel ledit matériau dudit réservoir (14) a une conductibilité thermique d'au moins 0,2 g.cal/sec cm<sup>2</sup> (°C/cm) {83,68 W / (m.K)}.
7. Un dispositif selon la revendication 5, dans lequel ledit matériau dudit réservoir (14) comprend l'acier  
55 inoxydable.
8. Un dispositif selon la revendication 5, dans lequel ledit matériau dudit réservoir (14) comprend l'aluminium.

## Patentansprüche

- 5 1. Schmelz-Tintenstrahldruckgerät zum Ausstoß von Tröpfchen phasenveränderlicher Tinte mit mindestens eine Tintenstrahldüse (12), mit einer Kamme (24), einer Öffnung zum Ausstoß phasenveränderlicher Tinte im flüssigen Zustand aus der Kammer, einem Tinteneinlaß (28) zur Versorgung der Kammer mit phasenveränderlicher Tinte im flüssigen Zustand und einem Reservoir (14) mit einem Vorrat an der phasenveränderlichen Tinte, wobei das Reservoir mit dem Einlaß der mindestens einen Tintenstrahldüse verbunden ist, **dadurch gekennzeichnet**, daß das Gerät eine erste Heizvorrichtung (32) zum Erhitzen phasenveränderlicher Tinte in der (den) Strahldüse(n) aufweist, so daß ein Phasenübergang vom festen Zustand in den flüssigen Zustand bewirkt wird, ohne die Tinte zu schädigen, einer zweiten Heizvorrichtung (20) zum Erhitzen von Tinte im Reservoir, so daß eine Phasenveränderung vom festen Zustand in den flüssigen Zustand erzielt wird, ohne die Tinte zu schädigen, und eine thermisch isolierende Trenneinrichtung (34) zwischen der Tintenstrahldüse und dem Reservoir, wodurch die erste Heizvorrichtung so ausgelegt ist, daß sie unabhängig von der zweiten Heizvorrichtung gesteuert werden kann und es somit ermöglicht, die Tintenstrahldüse auf einer von der des Reservoirs verschiedenen Temperatur zu halten, wobei die Strahldüse(n) aus einem Material bestehen, das eine Wärmeleitfähigkeit von mindestens  $0.03 \text{ g cal/sec cm}^2 (^\circ \text{C/cm})$  ( $12.55 \text{ W/(m.K)}$ ) aufweist.
- 10 2. Gerät nach Anspruch 1, wobei das Material eine Wärmeleitfähigkeit von mindestens  $0.2 \text{ g cal/sec cm}^2 (^\circ \text{C/cm})$  ( $83.68 \text{ W/(m.K)}$ ) aufweist.
- 15 3. Gerät nach Anspruch 1, wobei das Material rostfreien Stahl enthält.
- 20 4. Gerät nach Anspruch 1, wobei das Material Aluminium enthält.
- 25 5. Gerät nach einem der vorhergehenden Ansprüche, mit einem Reservoir (14), das mit der zweiten Heizvorrichtung (20) verbunden ist, wobei das Reservoir (14) ebenfalls aus einem Material mit einer Wärmeleitfähigkeit von mindestens  $0.03 \text{ g cal/sec cm}^2 (^\circ \text{C/cm})$  ( $12.55 \text{ W/(m.K)}$ ) besteht.
- 30 6. Gerät nach Anspruch 5, wobei das Material des Reservoirs (14) eine Wärmeleitfähigkeit von  $0.2 \text{ g cal/sec cm}^2 (^\circ \text{C/cm})$  ( $83.68 \text{ W/(m.K)}$ ) aufweist.
- 35 7. Gerät nach Anspruch 5, wobei das Material des Reservoirs (14) rostfreien Stahl enthält.
- 40 8. Gerät nach Anspruch 5, wobei das Material des Reservoirs (14) Aluminium enthält.
- 45
- 50
- 55

