




(86) Date de dépôt PCT/PCT Filing Date: 2006/04/26
(87) Date publication PCT/PCT Publication Date: 2006/11/02
(45) Date de délivrance/Issue Date: 2013/09/10
(85) Entrée phase nationale/National Entry: 2007/09/26
(86) N° demande PCT/PCT Application No.: US 2006/016288
(87) N° publication PCT/PCT Publication No.: 2006/116698
(30) Priorité/Priority: 2005/04/27 (US11/115,586)

(51) Cl.Int./Int.Cl. *B41J 2/175* (2006.01)
(72) Inventeurs/Inventors:
OGLE, HOLLI, US;
TAYLOR, JOHN L., US;
BALDWIN, MARC A., US
(73) Propriétaire/Owner:
HEWLETT-PACKARD DEVELOPMENT COMPANY,
L.P., US
(74) Agent: SIM & MCBURNEY

(54) Titre : COMPOSANT D'ETANCHEITE DEFINISSANT UN PREMIER, UN SECOND ET UN TROISIEME JOINTS
(54) Title: SEALING COMPONENT DEFINING FIRST, SECOND, AND THIRD SEALS



(57) Abrégé/Abstract:

A sealing component (106) includes an elastomeric material (302). An exterior side surface (304) of the elastomeric material is to define at least a first seal (306, 308) with a first external mating member (104) into which the sealing component is insertable. An interior surface (320) of the elastomeric material is to define a second seal (324) and a third seal (322) with a second external mating member (110) insertable into the sealing component.



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 November 2006 (02.11.2006)

PCT

(10) International Publication Number
WO 2006/116698 A3

(51) International Patent Classification:
B41J 2/175 (2006.01)

(21) International Application Number:
PCT/US2006/016288

(22) International Filing Date: 26 April 2006 (26.04.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
11/115,586 27 April 2005 (27.04.2005) US

(71) Applicant (for all designated States except US):
HEWLETT-PACKARD DEVELOPMENT COMPANY, L.P. [US/US]; Hewlett-Packard Company, Intellectual Property Administration, 20555 S.H. 249, Houston, Texas 77070 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **OGLE, Holli** [US/US]; 1000 NE Circle Blvd., Corvallis, Oregon 97330 (US). **TAYLOR, John L.** [US/US]; 1000 NE Circle Blvd., Corvallis, Oregon 97330 (US). **BALDWIN, Marc A.** [US/US]; 1000 NE Circle Blvd., Corvallis, Oregon 97330 (US).

(74) Agents: **JOLLY, Thomas A.** et al.; Hewlett-Packard Company, Intellectual Property Administration, P.O. Box 272400, Mail Stop 35, Fort Collins, Colorado 80527-2400 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to the identity of the inventor (Rule 4.17(i))
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))

[Continued on next page]

(54) Title: SEALING COMPONENT DEFINING FIRST, SECOND, AND THIRD SEALS



(57) Abstract: A sealing component (106) includes an elastomeric material (302). An exterior side surface (304) of the elastomeric material is to define at least a first seal (306, 308) with a first external mating member (104) into which the sealing component is insertable. An interior surface (320) of the elastomeric material is to define a second seal (324) and a third seal (322) with a second external mating member (110) insertable into the sealing component.

WO 2006/116698 A3

WO 2006/116698 A3



— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

(88) Date of publication of the international search report:
14 December 2006

Published:

— *with international search report*
— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

SEALING COMPONENT DEFINING FIRST, SECOND, AND THIRD SEALS BACKGROUND

Inkjet-printing devices, such as inkjet printers, operate by ejecting ink onto media to form images on the media. For instance, a printhead may be moved back and forth across the media, and the media advanced perpendicular to the movement of the printhead across the media. While the inkjet printhead moves across the media, it ejects ink onto the media to form an image.

At least in some types of inkjet-printing devices, traditionally the inkjet printhead and the ink have been encased in an enclosure known as an inkjet cartridge. Usually the ink of the cartridge is depleted before the inkjet printhead requires replacement. Thus, when the ink runs out, a new cartridge has to be inserted into the printer. More recently, the inkjet printhead has been separated from the ink supply as separately replaceable consumable items. An inkjet printhead may be inserted into an inkjet-printing device, and then just a supply of ink may be mated with the printhead already installed within the printing device, or before the printhead is installed.

Where the ink is encased in a supply separate from the inkjet printhead, the mating process between the printhead and the supply should ensure that there are no resulting fluid leaks. Furthermore, a supply may be later removed from the printhead before the ink therein is depleted. When the supply is so removed, as well as before the supply is first mated with the printhead, there should also be no fluid leaks.

SUMMARY

Accordingly, in one aspect there is provided a sealing component comprising an elastomeric material; an exterior side surface of the elastomeric material to define at least three first seals, including a top first seal, a middle first seal, and a bottom first seal, with a first external mating member into which the sealing component is insertable; and an interior surface of the elastomeric material to define a second seal and a third seal with a second

1a

external mating member insertable into the sealing component, the second external mating member being different than the first external mating member, wherein the exterior side surface of the elastomeric material further defines a compression region into which the elastomeric material is compressed upon insertion of the sealing component into the first external mating member, wherein the compression region is defined as a first groove between a first portion of the exterior side surface and a second portion of the exterior side surface, a side profile of the first portion being collinear with a side profile of the second portion, wherein the first groove is a top-most groove within the elastomeric material, where a top of the elastomeric material is a part of the elastomeric material at which the second external mating member is inserted into the sealing component, wherein the first groove is defined between the top first seal and the middle first seal, a second groove defined between the middle first seal and the bottom first seal, the second groove being larger than the first groove, and wherein the interior surface of the elastomeric material is at least substantially curved where the second seal is defined with the second external mating member prior to defining the second seal with the second external mating member and remains at least substantially curved where the second seal is defined with the second external mating member upon the second seal being defined with the second external mating member.

According to another aspect there is provided a supply comprising an enclosure having one or more openings; fluid encased within the enclosure; and one or more sealing components fabricated from elastomeric material and corresponding to the openings of the enclosure, each sealing component capable of defining at least three first seals, including a top first seal, a middle first seal, and a bottom first seal, with a corresponding opening of the enclosure, and a second seal and a third seal with an external mating member insertable into the sealing component, the second seal and the third seal defined by an interior surface of the elastomeric material, wherein an exterior side surface of each sealing component defines a compression region into which the elastomeric material is compressed upon insertion of the external mating member into the sealing component, wherein the

1b

compression region of the exterior side surface of each sealing component is defined as a first groove between a first portion of the exterior side surface and a second portion of the exterior side surface, a side profile of the first portion being collinear with a side profile of the second portion, wherein the first groove of each sealing component is a top-most groove within the sealing component, where a top of the sealing component is a part of the sealing component at which the external mating member is inserted into the sealing component, wherein the first groove is defined between the top first seal and the middle first seal, a second groove defined between the middle first seal and the bottom first seal, the second groove being larger than the first groove, and wherein the interior surface is at least substantially curved where the second seal is defined with the second external mating member prior to defining the second seal with the external mating member and remains at least substantially curved where the second seal is defined with the external mating member upon the second seal being defined with the external mating member.

According to another aspect there is provided a system comprising one or more enclosures, each having one or more openings and encasing fluid; one or more sealing components fabricated from elastomeric material and corresponding to the openings of the enclosures, each sealing component defining at least three first seals, including a top first seal, a middle first seal, and a bottom first seal, with a corresponding opening of one of the enclosures; and one or more mating members corresponding to the sealing components, each mating member insertable into one of the enclosures through a corresponding sealing component, each sealing component capable of defining a second seal and a third seal with a corresponding mating member, the second seal and the third seal defined by an interior surface of the elastomeric material, wherein an exterior side surface of each sealing component defines a compression region into which the elastomeric material is compressed upon insertion of the corresponding mating member into the sealing component, wherein the compression region of the exterior side surface of each sealing component is defined as a first groove between a

1c

first portion of the exterior side surface and a second portion of the exterior side surface, a side profile of the first portion being collinear with a side profile of the second portion, wherein the first groove of each sealing component is a top-most groove within the sealing component, where a top of the sealing component is a part of the sealing component at which the corresponding mating member is inserted into the sealing component, wherein the first groove is defined between the top first seal and the middle first seal, a second groove defined between the middle first seal and the bottom first seal, the second groove being larger than the first groove, and wherein the interior surface is at least substantially curved where the second seal is defined with the second external mating member prior to defining the second seal with the external mating member and remains at least substantially curved where the second seal is defined with the external mating member upon the second seal being defined with the external mating member.

According to another aspect there is provided a seal comprising an elastomeric material; an exterior surface of the elastomeric material defining first and second exterior seals with a first mating member into which the seal is inserted; and an interior surface of the elastomeric material defining first and second interior seals with a second mating member inserted into the seal, wherein the interior surface of the elastomeric material is substantially curved in a region of the first interior seal prior to the first interior seal being defined with the second mating member, and wherein the interior surface of the elastomeric material remains substantially curved in the region of the first interior seal upon the first interior seal being defined with the second mating member, wherein, upon insertion of the second mating member into the seal, the first interior seal is defined with the second mating member prior to the second interior seal being defined with the second mating member.

According to another aspect there is provided a method comprising inserting a sealing component into an opening of an enclosure, an exterior side surface of the sealing component defining at least a first exterior seal with the enclosure at the opening thereof; and inserting an external mating member into the enclosure through the sealing component, an interior

1d

surface of the sealing component defining first and second interior seals with the external mating member upon insertion of the external mating member into the enclosure through the sealing component, including defining the first interior seal with the external mating member prior to defining the second interior seal with the external mating member, wherein the interior surface of the sealing component is substantially curved in a region of the first interior seal prior to the first interior seal being defined with the external mating member, and remains substantially curved in the region of the first interior seal upon the first interior seal being defined with the external mating member.

According to another aspect there is provided a sealing component comprising an elastomeric material; an exterior side surface of the elastomeric material to define a first and a second annular seal with a first external mating member when the sealing component is inserted into the mating member; and an interior surface of the elastomeric material to define a third seal and a fourth seal with a second external mating member insertable into the sealing component, wherein the exterior side surface of the elastomeric material further defines a compression region into which the elastomeric material is able to be compressed upon insertion of the sealing component into the first external mating member, wherein the compression region is a groove formed between the first and the second annular seal within the exterior side surface.

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings referenced herein form a part of the specification. Features shown in the drawing are meant as illustrative of only some embodiments of the invention, and not of all embodiments of the invention,
5 unless otherwise explicitly indicated.

FIGs. 1A, 1B, 1C, and 1D are diagrams showing a sealing component inserted into a rudimentary enclosure of fluid, and a rudimentary printhead being inserted into and removed from the enclosure through the sealing component, according to an exemplary embodiment of the invention.

10 FIGs. 2A and 2B are diagrams depicting insertion of a printhead adapter into an enclosure of fluid through a sealing component, according to a more specific exemplary embodiment of the invention.

FIG. 2C is a diagram of a supply or enclosure into which a sealing component can be inserted, according to the same specific exemplary
15 embodiment of the invention of FIGs. 2A and 2B.

FIGs. 3A, 3B, 3C, and 3D are diagrams of a sealing component, according to one exemplary embodiment of the invention.

FIG. 4 is a graph illustrating the non-additive insertion force of a mating member being inserted into the sealing component of FIGs. 3A, 3B, 3C, and 3D,
20 according to an exemplary embodiment of the invention.

FIGs. 5A, 5B, and 5C are diagrams of a sealing component, according to the same embodiment of the invention of FIGs. 2A, 2B, and 2C.

FIG. 6 is a diagram of a mating member pressing against a bottom surface of the sealing component of FIGs. 5A, 5B, and 5C when another mating
25 member is not inserted into the sealing component, according to an exemplary embodiment of the invention.

FIG. 7 is a flowchart of a method of use, according to an exemplary embodiment of the invention.

DETAILED DESCRIPTION OF THE DRAWINGS

30 In the following detailed description of exemplary embodiments of the invention, reference is made to the accompanying drawings that form a part

hereof, and in which is shown by way of illustration specific exemplary
embodiments in which the invention may be practiced. These embodiments are
described in sufficient detail to enable those skilled in the art to practice the
invention. Other embodiments may be utilized, and logical, mechanical, and
other changes may be made without departing from the scope of the present
invention.

FIGs. 1A, 1B, 1C, and 1D show a printhead 102 being inserted into and
removed from an enclosure 104 of fluid 108 through a sealing component 106,
according to an exemplary embodiment of the invention. The printhead 102 has
a needle 110 or another mating member that is able to pierce the sealing
component 106 to access the fluid 108 encased within the enclosure 104. The
printhead 102 is more generally an external mating member, in that it is a
member that mates with the sealing component 106, and that is external to the
sealing component 106. The printhead 102 may be part of an inkjet-printing
device, such as an inkjet printer, where there may be instances of the enclosure 104
for each different color of ink used in the device for forming images on media.

The fluid 108 encased within the enclosure 104 may be ink in one
embodiment. The enclosure 104 may be considered an ink supply, or a part of
an ink supply, in one embodiment. For instance, the dotted line 107
surrounding the enclosure 104 and the sealing component 106 in FIG. 1A in
particular is indicative of an ink supply in one embodiment, which may include
the enclosure 104, the sealing component 106, and potentially the fluid 108.

The enclosure 104 is also generally a mating member, in that it is a
member that mates with the sealing component 106. When considering the
sealing component 106 alone, the enclosure 104 is an external mating member,
since the enclosure 104 is external to the sealing component 106. When
considering the sealing component 106 in conjunction with the enclosure 104,
such as two parts of an ink supply, the enclosure 104 is an internal mating
member, since the enclosure 104 is a part of the same supply of which the
sealing component 106 is a part.

In general, the sealing component 106 seals with the enclosure 104 so that the fluid 108 cannot leak or escape therefrom. The sealing component 106 is specifically inserted into a hole or other opening of the enclosure 104. In FIG. 1A, the needle 110 of the printhead 102 has not yet been inserted into the enclosure 104 through the sealing component 106. As such, the sealing component 106 seals with the enclosure 104 in FIG. 1A, and the sealing component 106 can seal with itself to ensure that the fluid 108 cannot leak or escape therefrom. It is noted that the needle 110 has an inner channel extending across its length so that when the needle 110 is inserted into the enclosure 104, it is able to access the fluid 108 encased therein. As such, the needle 110 may be considered to be a hollow needle, and is more generally a mating member.

In FIG. 1B, the needle 110 of the printhead 102 is in the process of being inserted into the enclosure 104 through the sealing component 106, as indicated by the arrow 122. As the needle 110 is inserted through the sealing component 106, the sealing component 106 seals with the needle 110 so that the fluid 108 cannot leak or escape. Thus, in FIG. 1B, there are two acts of sealing being performed by the sealing component 106: the sealing component 106 sealing with the enclosure 104, and the sealing component 106 sealing with the needle 110 of the printhead 102.

In FIG. 1C, the needle 110 of the printhead 102 has been completely inserted into the enclosure 104 through the sealing component 106. As such, the printhead 102 is now able to access the fluid 108 encased within the enclosure 104, through the needle 110 thereof. The sealing component 106 again seals with both the needle 110 and the enclosure 104 so that the fluid 108 cannot leak or escape.

In FIG. 1D, the needle 110 of the printhead 102 is in the process of being removed from the enclosure 104 through the sealing component 106, as indicated by the arrow 124. As the needle 110 is removed through the sealing component 106, the sealing component 106 still seals with the needle 110 so that the fluid 108 cannot leak or escape. Thus, in FIG. 1D, there are still two acts of sealing being performed by the sealing component 106: the sealing

component 106 sealing with the enclosure 104, and the sealing component 106 sealing with the needle 110. After performance of the process depicted in FIG. 1D, and the needle 110 is completely removed from the enclosure 104, the enclosure 104 is again in the state depicted in FIG. 1A. Thus, the sealing
5 component 106 can again seal with itself, such that the enclosure 104 prevents the escape of the fluid 108.

FIGs. 2A and 2B show a more specific implementation of an exemplary printhead adapter 201 being mated with a more specific implementation of the enclosure 104 of fluid 108 via sealing components 106A and 106B, according to
10 an embodiment of the invention. The printhead adapter 201 ultimately mates with or is coupled to the printhead 102, such as via assorted tubes and/or housings. There are two needles 110A and 110B, corresponding to the two sealing components 106A and 106B. As before, the fluid 108 encased within the enclosure 104 may be ink, and the enclosure 104 may be an ink supply or
15 a part of an ink supply.

In FIG. 2A, the printhead adapter 201 is in the process of being mated with the enclosure 104 via the needles 110A and 110B being inserted into the enclosure 104 through the sealing components 106A and 106B, as indicated by the arrows 112. In FIG. 2B, the printhead adapter 201 has been mated with the
20 enclosure 104, via the needles 110A and 110B having been inserted into the enclosure 104 through the sealing components 106A and 106B.

In the embodiment of FIGs. 2A and 2B, the top needle 110A may allow air to be released into the enclosure 104 as the bottom needle 110B draws the fluid 108 from the enclosure 104. Having two sealing components 106A and
25 106B ensures that both needles 110A and 110B are sealed. Allowing air to be released into the enclosure 104 as the fluid 108 is drawn from the enclosure 104 ensures that internal pressure within the enclosure 104 remains at least substantially constant as the fluid 108 is depleted from the enclosure 104.

FIG. 2C shows in detail a portion of the enclosure 104, according to a
30 specific embodiment of the invention. As before, the enclosure 104 is intended to encase fluid, such as the fluid 108 of FIGs. 1A, 1B, 1C, 1D, 2A, and 2B, and may be or may be part of an ink supply. FIG. 2C depicts the enclosure 104 as

having features, shown here as castellations 252, within an interior portion of the enclosure 104 wherein the sealing component 106 is to be inserted. In this example, castellations 252 are tabs, or a tabbed formation of grooves or notches, extending around the interior portion of the enclosure 104 within which
5 the sealing component 106 is to be inserted.

The castellations 252 ensure that the sealing component 106 can be inserted into the enclosure 104 in a more secure manner than if the castellations 252 were not otherwise present. In particular, when the sealing component 106 is inserted into the enclosure 104, air can be trapped such that the sealing
10 component 106 may not be able to be completely seated. For instance, there may be a solid shelf extending around the interior portion of the enclosure 104 within which the sealing component 106 is to be inserted, and against which the sealing component 106 is to be pressed. Inserting the sealing component 106 into the sealing component 106 may trap air such that the air has nowhere to go
15 except against the solid shelf, resulting in the sealing component 106 not being completely seated.

By comparison, the presence of the castellations 252 allows such air to be lodged on the notches or grooves thereof, so that the sealing component 106 is able to be more completely seated. That is, any air that is trapped during
20 insertion of the sealing component 106 can be lodged within the notches or grooves of the castellations 252. As such, the sealing component 106 may be able to be pushed inward within the enclosure 104 as far as it is supposed to go, and thus be completely seated within the enclosure 104.

FIGs. 3A, 3B, 3C, and 3D show a specific implementation of the sealing
25 component 106, according to an exemplary embodiment of the invention. FIG. 3A shows a top perspective view of the sealing component 106, whereas FIG. 3B shows a bottom perspective view of the sealing component 106. FIG. 3C shows a cross-sectional side view of the sealing component 106, where the needle 110 has not been inserted into the sealing component 106. FIG. 3D
30 shows a cross-sectional side view of the sealing component 106, where the needle 110 has been inserted into the sealing component 106. The sealing component 106 may be fabricated from an elastomeric material 302, such as

rubber or another elastomeric material. In describing the sealing component 106 of FIGs. 3A, 3B, 3C, and 3D, primary reference is made to the cross-sectional side views of FIGs. 3C and 3D, with supplemental reference as needed to the perspective views of FIGs. 3A and 3B.

5 The sealing component 106 has an exterior side surface 304. Upon insertion of the sealing component 106 into an external or internal mating member, such as the hole or opening of the enclosure 104 as depicted in FIGs. 1A, 1B, 1C, and 1D, the exterior side surface 304 defines at least one seal with this mating member. That is, the mating member mates with the
10 sealing component 106 to define at least one of the seals indicated by the reference numbers or arrows 306, 308, and 310. Where the hole or opening of the mating member and the sealing component 106 are both round in shape, these seals may be considered annular seals.

 The seals indicated by the reference numbers or arrows 306 and 308 are
15 the primary seals defined by the exterior side surface 304 with the mating member into which the sealing component 106 is inserted. That is, the exterior side surface 304 of the sealing component 106 is designed so that the seals indicated by the reference numbers or arrows 306 and 308 are defined when the sealing component 106 is inserted into the mating member. By comparison,
20 the seal indicated by the reference number or arrow 310 may or may not be defined, in that the exterior side surface 304 is not necessarily designed so that this seal is defined when the sealing component 106 is inserted into the mating member, as is described in more detail in the next two paragraphs.

 When the sealing component 106 is inserted into the mating member, the
25 seals indicated by the reference numbers or arrows 306 and 308 are defined because the elastomeric material 302 at these portions of the exterior side surface 304 are pushed or compressed into a compression region 312. The compression region 312 is a groove notched or otherwise fabricated within, and defined by, the exterior side surface 304 so that the elastomeric material 302
30 can so compress into the region 312 when these seals are being defined. By comparison, the region 314 may be a compression region defined by the exterior side surface 304 into which the elastomeric material 302 is pushed or

compressed into where the seal identified by the reference number 310 is defined.

However, the region 314, and the area identified by the reference number or arrow 310, more generally constitute a manufacturing tolerance region, the dimensions of which do not affect definition of the seals identified by the reference numbers or arrows 306 and 308. As such, the dimensions of the manufacturing tolerance region can be varied during manufacture or fabrication of the sealing component 106, without affecting the functionality of the seals identified by the reference numbers or arrows 306 and 308. In this way, the seal identified by the reference number or arrows 310 may or may not be defined, depending on the manufacture of the sealing component 106.

Furthermore, the exterior side surface 304 of the sealing component 106 is asymmetrically shaped, so that a user is able to easily determine the proper orientation of the sealing component 106 when it is inserted into the mating member. The sealing component 106 of FIGs. 3A, 3B, 3C, and 3D is to be inserted into the mating member with a specific orientation, such that the portion of the sealing component 106 indicated by the arrows 310 is first inserted into the mating member, and the portion of the sealing component 106 indicated by the arrows 306 is inserted last into the mating member. The region 314 may thus be considered an orientation region defined by the exterior side surface 304 to render the shape of the exterior side surface 304 asymmetric, so that the user is able to easily discern the proper orientation of the sealing component 106.

Another mating member, such as an external mating member like the needle 110 of the printhead 102 of FIGs. 1A, 1B, 1C, and 1D, is insertable into the sealing component 106, as indicated by the arrow 316 in FIG. 3C (as well as the arrow 122 in Fig 1B), and as specifically depicted in FIG. 3D. The sealing component 106 has an interior surface 320. When such a mating member is inserted into the sealing component 106, the interior surface 320 defines at least two seals with the mating member, one seal indicated by the arrows 322 in FIG. 3D, and another seal indicated by the arrows 324 in FIG. 3D. It is noted

that the seals indicated by the arrows 322 and 324 are not present unless the mating member has been inserted into the sealing component 106.

When the mating member is first inserted into the sealing component 106, a lead-in region 318 of the sealing component 106 guides the mating member into the sealing component 106. The lead-in region 318 is thus a downward-ramped region defined by the interior surface 320, which if contacted by the mating member as it is inserted into the sealing component 106, results in the mating member being guided further inward into the sealing component 106. As the mating member further is inserted into the sealing component 106, the interior surface 320 defines a seal with the mating member, as indicated by the arrows 324 in FIG. 3D. This seal may be considered an annular seal where the interior surface 320 and the mating member each have a round shape. To assist the mating member into and past the regions of the interior surface 320 indicated by the arrows 324 and 322 in FIG. 3D, and by the arrows 338 in FIG. 3C, lubricating fluid, lubricating grease, or another type of lubricant may be used in one embodiment.

As the mating member is further inserted into the sealing component 106, it encounters a slit 326. Generally the slit 326 is a piercing of the sealing component 106 thereat, such as resulting from inserting a round needle into the sealing component 106 to result in the slit 326. The slit 326 may thus in one embodiment be round or partially round in shape. It is noted that a slight gap is depicted between the needle 110 and the sealing component 106 in FIG. 3D so that the slit 326 can be more clearly depicted in FIG. 3D. However, in actuality, this gap may not be present.

Prior to the mating member reaching the slit 326, the interior surface 320 of the sealing component 106 defines a seal with itself as indicated by the arrows 338 in FIG. 3C. That is, elastomeric material 302 of the sealing component 106 exerts sufficient force at both sides of the slit 326 to define the seal indicated by the arrows 338 in FIG. 3C. This seal prevents fluid at the bottom side of the sealing component 106 from escaping or leaking.

Once the mating member encounters the slit 326, it pushes through and past the slit 326 to reach the fluid at the other side of the sealing component

106, to access this fluid. The interior surface 320 of the sealing component 106 defines another seal, indicated by the arrows 322 in FIG. 3D, with the mating member once the mating member has been pushed through the slit 326. Thus, there are two seals defined between the interior surface 320 of the sealing component 106 and the mating member: the seal identified by the arrows 324 in FIG. 3D, and the seal identified by the arrows 322 in FIG. 3D.

Having two seals defined between the interior surface 320 of the sealing component 106 and the mating member inserted into the sealing component 106 provides for redundancy. If one of the seals should fail, the other seal is still present to prevent fluid leakage or escape. Furthermore, the seals indicated by the arrows 322 and 324 are defined because the elastomeric material 302 at these portions of the interior surface 320 are pushed or compressed into a compression region 328. The compression region 328 is a groove or notch removed from or otherwise fabricated within, and defined by, the interior surface 320 so that the elastomeric material 302 can compress into the region 328 when these seals are being defined.

Once the mating member has been inserted into the sealing component 106, it may be removed by being pulled from the sealing component 106. As the mating member is pulled from the sealing component 106, the seal identified by the arrows 322 is first broken. However, at the same time the seal formed by the interior surface 320 with itself, identified by the arrows 338 in FIG. 3C, is defined, so that the fluid to the other side of the sealing component 106 does not leak or escape. This seal formed by the interior surface 320 with itself, at the slit 326, is formed at any time when the needle 110 is not inserted at least partially into the slit 326. Thus, after the needle 110 has been removed from the sealing component 106 past the slit 326, the seal identified by the arrows 338 is formed. Similarly, while the needle 110 is being inserted into the sealing component 106, but before it has reached the slit 326, the seal identified by the arrows 338 is formed. Likewise, when the needle 110 is not inserted at all within the sealing component 106, this seal is formed.

The protrusion of the elastomeric material 302 at the interior surface 320 indicated by the arrows 324 serve further functionality in addition to defining a

seal, when the mating member is being removed from the sealing component 106. As the mating member is being pulled from the sealing component 106, any fluid, such as ink, remaining on the sides of the mating member is at least substantially wiped off, or cleaned, by this protrusion. That is, the arrows 324
5 denote a wiping region defined by the interior surface 320 to at least partially clean the mating member as it is being removed from the sealing component 106.

Finally, once the mating member has been sufficiently removed from the sealing component 106 such that it clears the protrusion identified by the arrows
10 324, the seal defined by the interior surface 320 with the mating member, and denoted by the arrows 324, is broken. Thus, first the seal defined by the interior surface 320 with the mating member denoted by the arrows 322 is broken, and next the seal defined by the interior surface 320 with the mating member
15 denoted by the arrows 324 is broken, as the mating member is removed from the sealing component 106. The order of these seals is reversed when the seals are being defined upon insertion of the sealing component 106, where first the seal identified by the arrows 324 is defined by the interior surface 320 with the mating member, and next the seal identified by the arrows 322 is defined by the interior surface 320 with the mating member.

20 FIG. 4 shows a graph 400 depicting the relatively low insertion force needed to insert a needle, as the external member, into the exemplary sealing component 106 of FIGs. 3A, 3B, 3C, and 3D, according to an embodiment of the invention. The graph 400 depicts the force needed to insert the needle on the y-axis 404 as a function of the relative distance at which the needle has
25 been inserted into the sealing component 106 on the x-axis 402. The line 406 depicts a force-distance plot when the needle is inserted at the proper end of the sealing component 106, as indicated by the arrow 316, with the assistance of lubricating fluid to push the needle past the region of the interior surface 320 indicated by the arrows 324 and the arrows 322. The line 408, by comparison,
30 depicts a force-distance plot when the needle is inserted at the opposite, wrong end of the sealing component 106, opposite of the arrow 316, such that it encounters the slit 326 first before the region identified by the arrows 324.

The line 406 denotes that the force needed to push the needle first past the region of the interior surface 320 indicated by the arrows 324 is non-additive with the force subsequently needed to push the needle into and through the slit 326. The first hump in the line 406 is the force needed to push the needle past the region of the interior surface 320 indicated by the arrows 324. Once the region has been exceeded, the force needed to further insert the needle into the sealing component 106 drops until the slit 326 is encountered. The second hump in the line 406 is the force needed to push the needle into and through the slit 326. Because the required force drops after needle insertion past the region of the interior surface 320 indicated by the arrows 324, before rising again when the needle encounters the slit 326, it can be considered that the force needed to insert the needle through the region 320 indicated by the arrows 324 is non-additive with the force needed to insert the needle through the slit 326.

By comparison, the line 408 denotes that the force needed to push the needle first into and through the slit 326 is additive with the force subsequently needed to push the needle past or through the region of the interior surface 320 indicated by the arrows 324. That is, once the slit 326 has been encountered by the needle, the force needed to continue pushing the needle through the sealing component 106, past the region of the interior surface 320 identified by the arrows 324, continues to increase. As such, these two forces are additive. Having the forces non-additive, as in the line 406, is advantageous because ultimately less force is required in total to completely push the needle through the sealing component 106, and less force is required at any given time to continue pushing the needle through the sealing component 106.

FIGs. 5A, 5B, and 5C show a specific implementation of the sealing component 106, according to another exemplary embodiment of the invention. FIG. 5A shows a top perspective view of the sealing component 106, whereas FIG. 5B shows a bottom perspective view of the sealing component 106. FIG. 5C shows a cross-sectional side view of the sealing component 106. The sealing component 106 is again fabricated from an elastomeric material 302, such as rubber or another elastomeric material. In describing the sealing component 106 of FIGs. 5A, 5B, and 5C, primary reference is made to the

cross-sectional side view of FIG. 5C, with supplemental reference as needed to the perspective views of FIGs. 5A and 5B.

The sealing component 106 has an exterior side surface 304. Upon insertion of the sealing component 106 into an external or internal mating member, such as the hole or opening of the enclosure 104 as depicted in FIGs. 1A, 1B, 1C, and 1D, the exterior side surface 304 defines at least one seal with this mating member. That is, the mating member mates with the sealing component 106 to define at least one of the seals indicated by the reference numbers or arrows 306 and 308. Where the hole or opening of the mating member and the sealing component 106 are both round in shape, these seals may be considered annular seals.

When the sealing component 106 is inserted into the mating member, the seals indicated by the reference numbers or arrows 306 and 308 are defined because the elastomeric material 302 at these portions of the exterior side surface 304 are pushed or compressed into a compression region 312. The compression region 312 is a groove notched or otherwise fabricated within, and defined by, the exterior side surface 304 so that the elastomeric material 302 can so compress into the region 312 when these seals are being defined.

The region 314 is a manufacturing tolerance region, the dimensions of which do not affect definition of the seals identified by the reference numbers or arrows 306 and 308. As such, the dimensions of the manufacturing tolerance region can be varied during manufacture or fabrication of the sealing component 106, without affecting the functionality of the seals identified by the reference numbers or arrows 306 and 308.

The exterior side surface 304 of the sealing component 106 is asymmetrically shaped, so that a user is able to easily determine the proper orientation of the sealing component 106 when it is inserted into the mating member. The sealing component 106 of FIGs. 5A, 5B, and 5C is to be inserted into the mating member bottom end first. The region 314 may thus be considered an orientation region defined by the exterior side surface 304 to render the shape of the exterior side surface 304 asymmetric, so that the user is able to easily discern the proper orientation of the sealing component 106.

It is noted that the exterior side surface 304 of the sealing component 106 of FIGs. 5A, 5B, and 5C is oriented upside-down as compared to the exterior side surface 304 of the sealing component 106 of FIGs. 3A, 3B, 3C, and 3D. For instance, the region 314 of the exterior side surface 304 is located
5 towards one end of the sealing component 106 in FIGs. 5A, 5B, and 5C, whereas the region 314 of the exterior side surface 304 is located at the other end of the sealing component 106 in FIGs. 3A, 3B, 3C, and 3D.

Another mating member, such as an external mating member like the needle 110 of the printhead 102 of FIGs. 1A, 1B, 1C, and 1D, is insertable into
10 the sealing component 106. The sealing component 106 has an interior surface 320. The interior surface 320 defines two seals with the mating member, one seal indicated by the arrows 322, and another seal indicated by the arrows 324.

When the mating member is first inserted into the sealing component 106, a lead-in region 318 of the sealing component 106 guides the mating
15 member into the sealing component 106. The lead-in region is thus a downward-ramped region defined by the interior surface 320, which if contacted by the mating member as it is inserted into the sealing component 106, results in the mating member being guided further inward into the sealing component 106. As the mating member passes the region of the interior surface 320
20 indicated by the arrows 324, the interior surface 320 defines a seal at this region with the mating member. This seal may be considered an annular seal where the interior surface 320 and the mating member each have a round shape.

As the mating member is further inserted into the sealing component 106, it passes the region of the interior surface 320 indicated by the arrows 322. The
25 interior surface 320 defines another seal at this region with the mating member. This seal may also be considered an annular seal where the interior surface 320 and the mating member each have a round shape. Thus, there are two seals defined between the interior surface 320 of the sealing component 106 and the mating member: the seal identified by the arrows 324, and the seal identified by
30 the arrows 322.

Having two seals defined between the interior surface 320 of the sealing component 106 and the mating member inserted into the sealing component

106 provides for redundancy. If one of the seals should fail, the other seal is still present to prevent fluid leakage or escape. Furthermore, the seals indicated by the arrows 322 and 324 are defined because the elastomeric material 302 at these portions of the interior surface 320 are pushed or compressed into a
5 compression region 328. The compression region 328 is a groove or notch removed from or otherwise fabricated within, and defined by, the interior surface 320 so that the elastomeric material 302 can compress into the region 328 when these seals are being defined. In one embodiment, the seals identified by the arrows 322 and 324 are at least substantially identical.

10 Once the mating member has been inserted into the sealing component 106, it may be removed by being pulled from the sealing component 106. As the mating member is pulled from the sealing component 106, the seal identified by the arrows 322 is first broken. Next, as the member is further pulled from the sealing component 106, the seal identified by the arrows 324 is broken. It is
15 noted that the order of these seals is reversed when the seals are being defined upon insertion of the sealing component 106, where first the seal identified by the arrows 324 is defined by the interior surface 320 with the mating member, and next the seal identified by the arrows 322 is defined by the interior surface 320 with the mating member.

20 Finally, as the member is further pulled from the sealing component 106, the mating member passes the protrusion of the elastomeric material 302 at the interior surface 320 indicated by the arrows 325. As the member is being pulled from the sealing component 106, any fluid, such as ink, remaining on the sides of the mating member is at least substantially wiped off, or cleaned, by this
25 protrusion. That is, the arrows 325 denote a wiping region defined by the interior surface 320 to at least partially clean the mating member as it is being removed from the sealing component 106.

It is noted that the sealing component 106 of FIGs. 5A, 5B, and 5C does not self-seal when a mating member like a needle is removed from or has not
30 yet been inserted into the sealing component 106. This is in comparison to the sealing component 106 of FIGs. 3A, 3B, 3C, and 3D. The sealing component 106 of FIGs. 3A, 3B, 3C, and 3D features a self-seal capability, where the slit

326 thereof defines a seal with itself when a mating member is removed from or has not yet been inserted into the sealing component 106. Such sealing of the sealing component 106 is desirable to ensure that no fluid escapes or leaks from the sealing component 106 when a mating member is removed from or has not yet been inserted into the sealing component 106.

Therefore, a (third) member, such as an internal mating member like a spring-loaded ball, may be pressed against the exterior bottom surface 330 of the sealing component of FIGs. 5A, 5B, and 5C, as identified by the arrows 332. The exterior bottom surface 330 thus defines a seal with such an internal mating member, like a ball, when the other mating member, like a needle, is being removed from or has not yet been inserted into the sealing component 106 from the component 106. Further discussion of this mating member is made with reference to this member specifically being a ball, whereas further discussion of the mating member inserted into the sealing component 106 is made with reference to the member specifically being a needle, so that the distinction between these two mating members is clear. However, in general, both mating members are still mating members, and are not restricted to a ball and a needle.

Before the needle is inserted into the sealing component 106, the ball and the exterior bottom surface 330 thus define a seal indicated by the arrows 332 so that fluid cannot escape through the sealing component 106. When the needle is inserted into the sealing component 106, it pushes this ball down into the enclosure or supply into which the sealing component 106 has been inserted. Therefore, the needle is able to access the fluid. When the needle is again removed, the ball via its spring-loaded nature pushes or presses against the exterior bottom surface 330 again, to redefine the seal indicated by the arrows 332, so that fluid cannot escape through the sealing component 106.

Two other features of the sealing component 106 of FIGs. 5A, 5B, and 5C are notable. First, there is a slight indentation, or notch or groove, within the interior surface 320 of the sealing component 106, indicated by the reference numbers 329. This indentation serves to separate, or decouple, the functionality of the seal defined by the exterior bottom surface 330 with the ball, as identified by the arrows 332, with the functionality of the seals defined by the

interior surface 320 with the needle, as identified by the arrows 322 and 324. Such decoupling means that the seals afforded by elastomeric material 302 relative to the needle are not affected by the seals afforded by the elastomeric material 302 relative to the ball.

5 For instance, when the needle is being inserted into the sealing component 106, the presence of the slight indentation at least substantially reduces, if not totally eliminating, distortion or compression of the elastomeric material 302 that may otherwise affect the seal with the ball. That is, the potential for the elastomeric material 302 to distort and affect the seal with the
10 ball is reduced. Resultingly, the potential for leakage to occur at the seal with the ball during needle insertion is reduced due to the presence of the indentation identified by the reference numbers 329. It is noted that such undesirable distortion or compression of the elastomeric material 302 is further reduced or eliminated as a result of there being two seals with the needle, due
15 to the compression region 328 being present between these two seals.

 Second, there is a notch or groove 321 that separates the top of the sealing component 106 from the seals with the needle identified by the arrows 322 and 324. This notch 321 helps to define the wiping region identified by the arrows 325 within the interior surface 320. Furthermore, the notch 321 isolates
20 the seals identified by the arrows 322 and 324 from the top of the sealing component 106. Any irregular pressure on the top of the sealing component 106, such as resulting from a user pushing on the top of the sealing component 106, is thus less likely to affect the ability of the elastomeric material 302 to define and maintain the seals identified by the arrows 322 and 324.

25 FIG. 6 shows a specific implementation of an internal mating member 601 pressing against the exterior bottom surface 330 of the sealing component 106, according to an exemplary embodiment of the invention. The mating member 601 includes a ball 602, as has been described, and a spring 604. The ball 602 is spring-loaded by virtue of coupling with the spring 604. As depicted
30 in FIG. 6, the sealing component 106 has been inserted into the enclosure 104, such that its exterior side surface 304 defines seals with the enclosure 104 so

that fluid cannot escape around the sealing component 106 along the exterior side surface 304.

When a mating member such as a needle has been removed from or has not yet been inserted into the sealing component 106, the ball 602 presses
5 against the exterior bottom surface 330 of the sealing component 106, due to the force exerted by the spring 604. The exterior bottom surface 330 thus defines a seal with the mating member 601, specifically the ball 602 thereof, so that fluid cannot escape or leak through the sealing component 106 along the interior surface 320. When the needle or other mating member is inserted into
10 the sealing component 106, it pushes down against the ball 602. The seal defined by the exterior bottom surface 330 with the mating member 601 is thus broken, and the needle or other mating member can access the fluid. That is, the needle pushes the ball 602 away so that it can access the fluid. Fluid cannot escape or leak along the interior surface 320 around this needle or other
15 mating member, due to the seals defined by the interior surface 320 with the needle, as have been described.

As the needle or other mating member is removed from the sealing component 106, the spring 604 pushes the ball 602 towards or against the exterior bottom surface 330, so that a seal is again defined by the exterior
20 bottom surface with the mating member 604. Thus, at no time can fluid leak or escape through the sealing component 106 along its interior surface 320. At any given time, either the interior surface 320 is defining one or more seals with the needle, or the exterior bottom surface 330 is defining a seal with the mating member 601.

25 FIG. 7 shows a method 700, according to an embodiment of the invention. The method 700 may be performed relative to the sealing component of FIGs. 3A, 3B, 3C, and 3D that has been described, or it may be performed relative to the sealing component of FIGs. 5A, 5B, and 5C that has been described. The sealing component is first oriented by a user relative to an
30 opening of an enclosure, based on an orientation region of the sealing component (702). The sealing component can then be inserted into the opening of the enclosure since it is now properly oriented and thus inserted right

side up (704). Insertion of the sealing component into the enclosure causes elastomeric material of the sealing component to compress into a compression region of an exterior side surface of the sealing component (706), resulting in the exterior side surface defining at least one seal with the enclosure at the opening of the enclosure (708). Not shown in FIG. 7 is that the enclosure may be filled with fluid, such as ink, either before or after the sealing component has been inserted into the enclosure, although typically the enclosure is filled with fluid after the sealing component has been inserted into the enclosure.

Next, an external mating member, such as a needle, is inserted into the enclosure through the sealing component (710). A lead-in region of the sealing component may guide insertion of the needle into the enclosure (712). Insertion of the needle into the sealing component causes elastomeric material of the sealing component to compress into a compression region of an interior surface of the sealing component (714). As a result, the interior surface defines at least two seals with the needle in succession, as the needle is inserted into the sealing component (716). Furthermore, in one embodiment, where the sealing component is that of FIGs. 5A, 5B, and 5C, insertion of the needle into the sealing component causes the needle to push away a ball from the exterior bottom surface of the sealing component (718).

At some point, the needle is removed from the enclosure (720). For instance, the needle may have been used to fill the enclosure with fluid, or the needle may have been used to extract fluid from the enclosure, such that either such process is finished, and the needle removed. In one embodiment, where the sealing component is that of FIGs. 3A, 3B, 3C, and 3D, removal of the needle results in the interior surface of the sealing component defining a seal with itself via a slit (722). In another embodiment, where the sealing component is that of FIGs. 5A, 5B, and 5C, removal of the needle results in the ball pressing against the bottom exterior surface of the sealing component (724), such that the bottom exterior surface defines a seal with the ball (726). Finally, a wiping region of the sealing component at least partially cleans the needle as the needle is removed from the enclosure through the sealing component (728).

It is noted that, although specific embodiments have been illustrated and described herein, it will be appreciated by those of ordinary skill in the art that any arrangement calculated to achieve the same purpose may be substituted for the specific embodiments shown. For example, whereas some embodiments of the invention have been described in relation to a sealing component for an ink supply that then mates with an inkjet printhead or an inkjet printhead component, other embodiments of the invention can be employed in relation to applications other than inkjet-printing devices. The scope of the claims should not be limited by the embodiments set forth above, but should be given the broadest interpretation consistent with the description as a whole.

What is claimed is:

1. A sealing component comprising:
 - an elastomeric material;
 - an exterior side surface of the elastomeric material to define at least three first seals, including a top first seal, a middle first seal, and a bottom first seal, with a first external mating member into which the sealing component is insertable; and
 - an interior surface of the elastomeric material to define a second seal and a third seal with a second external mating member insertable into the sealing component, the second external mating member being different than the first external mating member,
 - wherein the exterior side surface of the elastomeric material further defines a compression region into which the elastomeric material is compressed upon insertion of the sealing component into the first external mating member,
 - wherein the compression region is defined as a first groove between a first portion of the exterior side surface and a second portion of the exterior side surface, a side profile of the first portion being collinear with a side profile of the second portion,
 - wherein the first groove is a top-most groove within the elastomeric material, where a top of the elastomeric material is a part of the elastomeric material at which the second external mating member is inserted into the sealing component,
 - wherein the first groove is defined between the top first seal and the middle first seal, a second groove defined between the middle first seal and the bottom first seal, the second groove being larger than the first groove, and
 - wherein the interior surface of the elastomeric material is at least substantially curved where the second seal is defined with the second external mating member prior to defining the second seal with the second external mating member and remains at least substantially curved where the second seal is defined with the second external mating member upon the

second seal being defined with the second external mating member.

2. The sealing component of claim 1, wherein as the second external mating member is being inserted into the sealing component, first the second seal is defined by the interior surface of the elastomeric material with the second external mating member, and next the third seal is defined by the interior surface of the elastomeric material with the second external mating member.

3. The sealing component of claim 2, wherein as the second external mating member is being removed from the sealing component, first the third seal is broken and next the second seal is broken.

4. The sealing component of any one of claims 1 to 3, wherein the exterior side surface of the elastomeric material further defines a manufacturing tolerance region, dimensions of which do not affect definition of the first seal and which are able to vary during manufacturing without affecting functionality of the first seal.

5. The sealing component of any one of claims 1 to 4, wherein the exterior side surface of the elastomeric material further defines an orientation region to indicate to a user that the sealing component is properly oriented, such that the exterior side surface of the elastomeric material is asymmetrically shaped.

6. The sealing component of any one of claims 1 to 5, wherein the interior surface further defines a lead-in region to guide the second external mating member as the second external mating member is inserted into the sealing component.

7. The sealing component of any one of claims 1 to 6, wherein the interior surface further defines a wiping region to at least partially clean the second

external mating member upon removal from the sealing component.

8. The sealing component of claim 7, wherein the interior surface defines the wiping region and the second seal at a same portion of the elastomeric material.

9. The sealing component of any one of claims 1 to 8, wherein the interior surface further defines a compression region into which the elastomeric material is able to be compressed upon insertion of the second external mating member into the sealing component.

10. The sealing component of any one of claims 1 to 9, further comprising a bottom surface to define a fourth seal with a third external mating member pressable against the bottom surface.

11. The sealing component of claim 10, wherein the fourth seal is functionally decoupled from the second and the third seals.

12. The sealing component of any one of claims 1 to 9, wherein the third seal is defined by the interior surface as a slit within the elastomeric material.

13. The sealing component of claim 12, wherein the slit further defines a fourth seal with itself when the second external mating member prior to insertion into or after removal from the sealing component.

14. The sealing component of any one of claims 1 to 13, wherein a first force needed to insert the second external mating member into the sealing component such that the second seal is defined is non-additive with a second force needed to insert the second external mating member into the sealing component such that the third seal is defined.

15. The sealing component of any one of claims 1 to 14, wherein the elastomeric material is rubber.

16. A supply comprising:

an enclosure having one or more openings;

fluid encased within the enclosure; and

one or more sealing components fabricated from elastomeric material and corresponding to the openings of the enclosure, each sealing component capable of defining at least three first seals, including a top first seal, a middle first seal, and a bottom first seal, with a corresponding opening of the enclosure, and a second seal and a third seal with an external mating member insertable into the sealing component, the second seal and the third seal defined by an interior surface of the elastomeric material,

wherein an exterior side surface of each sealing component defines a compression region into which the elastomeric material is compressed upon insertion of the external mating member into the sealing component,

wherein the compression region of the exterior side surface of each sealing component is defined as a first groove between a first portion of the exterior side surface and a second portion of the exterior side surface, a side profile of the first portion being collinear with a side profile of the second portion,

wherein the first groove of each sealing component is a top-most groove within the sealing component, where a top of the sealing component is a part of the sealing component at which the external mating member is inserted into the sealing component, wherein the first groove is defined between the top first seal and the middle first seal, a second groove defined between the middle first seal and the bottom first seal, the second groove being larger than the first groove, and wherein the interior surface is at least substantially curved where the second seal is defined with the second external mating member prior to defining the second seal with the external mating member and remains at least substantially curved where the second seal is defined with the external mating member upon the second seal being

defined with the external mating member.

17. The supply of claim 16, wherein as the external mating member is being inserted into the sealing component, first the second seal is defined by the interior surface of the elastomeric material with the external mating member, and next the third seal is defined by the interior surface of the elastomeric material with the external mating member.

18. The supply of claim 17, wherein as the external mating member is being removed from the sealing component, first the third seal is broken and next the second seal is broken.

19. The supply of any one of claims 16 to 18, wherein each sealing component further defines at least one of:

- a manufacturing tolerance region, dimensions of which do not affect definition of the first seal and which are able to vary during manufacturing without affecting functionality of the first seal;

- an orientation region to indicate to a user that the sealing component is properly oriented, such that the exterior side surface of the elastomeric material is asymmetrically shaped;

- a lead-in region to guide the external mating member as the external mating member is inserted into the sealing component;

- a wiping region to at least partially clean the external mating member upon removal from the sealing component; and

- a compression region into which the elastomeric material of the sealing component is able to be compressed upon insertion of the external mating member into the sealing component.

20. The supply of any one of claims 16 to 19, further comprising one or more internal mating members corresponding to the sealing components, each sealing component further capable of defining a fourth seal with a corresponding internal mating member pressable against a bottom surface of

the sealing component.

21. The supply of claim 20, wherein the corresponding internal mating member of each sealing component is capable of pressing against the bottom surface of the sealing component upon removal of the external mating member from the sealing component, to seal the fluid within the enclosure.

22. The supply of claim 20, wherein the corresponding internal mating member of each sealing component is capable of being pushed away from the bottom surface of the sealing component upon insertion of the external mating member into the sealing component, so that the external mating member is able to access to the fluid within the enclosure.

23. The supply of claim 20, wherein the corresponding internal mating member of each sealing component comprises:

- a ball to mate with the bottom surface of the sealing component; and
- a spring to push the ball against the bottom surface of the sealing component upon removal of the external mating member from the sealing component.

24. The supply of any one of claims 16 to 19, wherein the third seal of each sealing component is defined as a slit within the elastomeric material of the sealing component, the slit defining a fourth seal with itself when the external mating member is removed from the sealing component.

25. The supply of any one of claims 16 to 24, wherein the enclosure comprises a plurality of castellations.

26. The supply of any one of claims 16 to 25, wherein the supply is insertable into an inkjet-printing device, and the fluid within the enclosure is ink.

27. A system comprising:

one or more enclosures, each having one or more openings and encasing fluid;

one or more sealing components fabricated from elastomeric material and corresponding to the openings of the enclosures, each sealing component defining at least three first seals, including a top first seal, a middle first seal, and a bottom first seal, with a corresponding opening of one of the enclosures; and

one or more mating members corresponding to the sealing components, each mating member insertable into one of the enclosures through a corresponding sealing component, each sealing component capable of defining a second seal and a third seal with a corresponding mating member, the second seal and the third seal defined by an interior surface of the elastomeric material,

wherein an exterior side surface of each sealing component defines a compression region into which the elastomeric material is compressed upon insertion of the corresponding mating member into the sealing component,

wherein the compression region of the exterior side surface of each sealing component is defined as a first groove between a first portion of the exterior side surface and a second portion of the exterior side surface, a side profile of the first portion being collinear with a side profile of the second portion,

wherein the first groove of each sealing component is a top-most groove within the sealing component, where a top of the sealing component is a part of the sealing component at which the corresponding mating member is inserted into the sealing component,

wherein the first groove is defined between the top first seal and the middle first seal, a second groove defined between the middle first seal and the bottom first seal, the second groove being larger than the first groove, and

wherein the interior surface is at least substantially curved where the second seal is defined with the second external mating member prior to

defining the second seal with the external mating member and remains at least substantially curved where the second seal is defined with the external mating member upon the second seal being defined with the external mating member.

28. The system of claim 27, wherein each sealing component first defines the second seal with a corresponding mating member and next defines the third seal with the mating member as the mating member is inserted into one of the enclosures, such that the third seal is first broken and the second seal is next broken as the mating member is removed from the enclosure.

29. The system of claim 28, wherein the second and the third seals defined by each sealing component are at least substantially identical.

30. The system of claim 28 or 29, wherein a first force needed to insert each mating member through a corresponding sealing component such that the second seal is defined is non-additive with a second force needed to insert the mating member through the sealing component such that the third seal is defined.

31. The system of any one of claims 27 to 30, further comprising one or more additional mating members corresponding to the sealing components, each sealing component further capable of defining a fourth seal with a corresponding additional mating member pressable against a bottom surface of the sealing component.

32. The system of claim 31, wherein each additional mating member comprises:

- a ball to mate with the bottom surface of a corresponding sealing component and that is pushed away from the sealing component such that the fourth seal is broken upon insertion of a corresponding mating member into one of the enclosures; and

a spring to push the ball against the bottom surface of the sealing component upon removal of the mating member from the enclosure.

33. The system of any one of claims 27 to 30, wherein the third seal of each sealing component is defined as a slit within the elastomeric material of the sealing component, the slit defining a fourth seal with itself to seal a corresponding opening upon a corresponding mating member being removed from one of the enclosures.

34. The system of any one of claims 27 to 33, wherein the system is an inkjet-printing device, and the enclosure is at least part of a supply insertable into the inkjet-printing device.

35. A seal comprising:
an elastomeric material;
an exterior surface of the elastomeric material defining first and second exterior seals with a first mating member into which the seal is inserted; and
an interior surface of the elastomeric material defining first and second interior seals with a second mating member inserted into the seal, wherein the interior surface of the elastomeric material is substantially curved in a region of the first interior seal prior to the first interior seal being defined with the second mating member, and wherein the interior surface of the elastomeric material remains substantially curved in the region of the first interior seal upon the first interior seal being defined with the second mating member, wherein upon insertion of the second mating member into the seal, the first interior seal is defined with the second mating member prior to the second interior seal being defined with the second mating member.

36. The seal of claim 35, wherein, upon insertion of the second mating member into the seal, the second mating member contacts the first interior seal before the second mating member contacts the second interior seal.

37. The seal of claim 35, wherein the exterior surface of the elastomeric material further defines a third exterior seal with the first mating member into which the seal is inserted, and wherein the exterior surface of the elastomeric material includes a first exterior compression region defined by a first exterior groove between the first exterior seal and the second exterior seal, and includes a second exterior compression region defined by a second exterior groove between the second exterior seal and the third exterior seal, wherein the second exterior groove is larger than the first exterior groove.

38. The seal of claim 35, wherein the interior surface of the elastomeric material includes a first interior compression region defined by a first interior groove formed within the interior surface of the elastomeric material between the first interior seal and the second interior seal.

39. The seal of claim 35, wherein the second interior seal forms an interior seal with itself before insertion of the second mating member into the seal and after removal of the second mating member from the seal, wherein the second interior seal is defined by a slit formed within the elastomeric material.

40. The seal of claim 35, wherein a sealing surface of the first interior seal is collinear with a sealing surface of the second interior seal upon insertion of the second mating member into the seal.

41. The seal of any one of claims 35 to 40, wherein the interior surface further defines a lead-in region configured to guide the second mating member as the second mating member is inserted into the seal.

42. The seal of any one of claims 35 to 41, wherein the interior surface further defines a wiping region configured to at least partially clean the second mating member upon removal from the seal.

43. The seal of claim 42, wherein the interior surface defines the wiping

region and the first interior seal by a same portion of the elastomeric material.

44. The seal of any one of claims 35 to 43, further comprising:
a bottom surface of the elastomeric material defining a bottom seal with a third mating member pressed against the bottom surface.

45. The seal of any one of claims 35 to 44, wherein the elastomeric material is rubber.

46. A method comprising:
inserting a sealing component into an opening of an enclosure, an exterior side surface of the sealing component defining at least a first exterior seal with the enclosure at the opening thereof; and
inserting an external mating member into the enclosure through the sealing component, an interior surface of the sealing component defining first and second interior seals with the external mating member upon insertion of the external mating member into the enclosure through the sealing component, including defining the first interior seal with the external mating member prior to defining the second interior seal with the external mating member,
wherein the interior surface of the sealing component is substantially curved in a region of the first interior seal prior to the first interior seal being defined with the external mating member, and remains substantially curved in the region of the first interior seal upon the first interior seal being defined with the external mating member.

47. The method of claim 46, further comprising compressing the sealing component into a compression region of the exterior side surface of the sealing component upon insertion of the sealing component into the opening of the enclosure.

48. The method of claim 46 or 47, further comprising orienting the sealing

component relative to the opening of the enclosure based on an orientation region of the exterior side surface of the sealing component so that the sealing component is properly oriented within the opening of the enclosure.

49. The method of any one of claims 46 to 48, further comprising guiding insertion of the external mating member into the enclosure through the sealing component via a lead-in region of the interior surface of the sealing component.

50. The method of any one of claims 46 to 49, further comprising:
removing the external mating member from the enclosure through the sealing component, such that the second internal seal is first broken and the first internal seal is next broken as the external mating member is removed, and a wiping region of the interior surface of the sealing component at least partially cleaning the external mating member as the external mating member is removed.

51. The method of any one of claims 46 to 50, further comprising compressing the sealing component into a compression region of the interior surface upon insertion of the external mating member into the enclosure through the sealing component.

52. The method of claim 46, further comprising:
the external mating member pushing another mating member away from the sealing component upon insertion of the external mating member into the enclosure through the sealing component;
the other mating member pressing against a bottom surface of the sealing component upon removal of the external mating member from the enclosure through the sealing component; and
the bottom surface of the sealing component defining a bottom seal with the other mating member.

53. The method of claim 46, wherein the interior surface of the sealing component defines the second interior seal with the external mating member via the external mating member being pushed through a slit within the interior surface of the sealing component.

54. The method of claim 46, further comprising the interior surface of the sealing component defining an interior seal with itself via a slit that closes upon the removal of the external mating member from the enclosure through the sealing component.

55. The method of claim 46, further comprising the exterior side surface of the sealing component further defining a second exterior seal with the enclosure at the opening thereof.

56. The method of claim 46, wherein defining the first interior seal with the external mating member prior to defining the second interior seal with the external mating member includes the external mating member contacting the first interior seal before contacting the second interior seal.

57. The method of claim 46, wherein a sealing surface of the first interior seal is collinear with a sealing surface of the second interior seal upon insertion of the external mating member into the enclosure through the sealing component.

58. A sealing component comprising:

- an elastomeric material;

- an exterior side surface of the elastomeric material to define a first and a second annular seal with a first external mating member when the sealing component is inserted into the mating member; and

- an interior surface of the elastomeric material to define a third seal and a fourth seal with a second external mating member insertable into the sealing component,

wherein the exterior side surface of the elastomeric material further defines a compression region into which the elastomeric material is able to be compressed upon insertion of the sealing component into the first external mating member,

wherein the compression region is a groove formed between the first and the second annular seal within the exterior side surface.

59. The sealing component of claim 58, wherein the exterior side surface of the elastomeric material further defines an orientation region to indicate to a user that the sealing component is properly oriented, such that the exterior side surface of the elastomeric material is asymmetrically shaped.

60. The sealing component of claim 58 or 59, wherein the interior surface further defines a lead-in region to guide the second external mating member as the second external mating member is inserted into the sealing component.

61. The sealing component of any one of claims 58 to 60, wherein the interior surface further defines a wiping region to at least partially clean the second external mating member upon removal from the sealing component.



62. The sealing component of claim 61, wherein the interior surface defines the wiping region and the third seal at the same portion of the elastomeric material.



63. The sealing component of any one of claims 58 to 62, wherein the interior surface further defines a compression region into which the elastomeric material is able to be compressed upon insertion of the second external mating member into the sealing component.



64. The sealing component of any one of claims 58 to 63, further comprising a bottom surface to define a fifth seal with a third external mating member pressable against the bottom surface.


65. The sealing component of any one of claims 58 to 64, wherein the fourth seal is defined by the interior surface as a slit within the elastomeric material.



66. The sealing component of claim 65, wherein the slit further defines a fifth seal with itself prior to insertion of the second external mating member into or after removal thereof from the sealing component.

**FIG. 1A****FIG. 1B**

**FIG. 1C****FIG. 1D**

**FIG. 2A****FIG. 2B**

**FIG. 2C**

**FIG. 3A****FIG. 3B**




FIG. 3C










FIG. 3D

**FIG. 4**

**FIG. 5A**

**FIG. 5B****FIG. 5C**

**FIG. 6**



700 ↗

FIG. 7

