666035

SPRUSON & FERGUSON

AUSTRALIA

PATENTS ACT 1990

PATENT REQUEST: STANDARD PATENT

I/We, the Applicant(s)/Nominated Person(s) specified below, request I/We be granted a patent for the invention disclosed in the accompanying standard complete specification.

[70,71] Applicant(s)/Nominated Person(s):

Kyowa Hakko Kogyo Co., Ltd., of 6-1, Ohtemachi 1-chome, Chiyoda-ku, Tokyo 100, JAPAN

[54] Invention Title:

Process for Producing Compositions for Ruminants

[72] Inventor(s):

Yorozu Yokomori, Toshikazu Murayama, Tomoaki Masada, Motohiro Ohta, Masaki Azuma and Yoshio Yumiba

[74] Address for service in Australia:

Spruson & Ferguson, Patent Attorneys
Level 33 St Martins Tower
31 Market Street
Sydney New South Wales Australia (Code SF)

Details of Basic Application(s):

[31] Appl'n No(s):	[33] Country:	[32] Application Date:
243157/92	JP	11 September 1992

Basic Applicant(s): Kyowa Hakko Kogyo Co., Ltd.

DATED this TENTH day of SEPTEMBER 1993

Kyowa Hakko Kogyo Co., Ltd.

By:

S 040431 100993

Registered Patent Attorney

IRN: 249764 INSTR CODE: 57040

5845/2

SPRUSON&FERGUSON

Australia

Patents Act 1990

NOTICE OF ENTITLEMENT

I, Seiichi Yada

of 2-1-1, Hatanodai, Shinagawa-ku, Tokyo, Japan

being authorised by the Applicant(s)/Nominated Person(s) in respect of an application entitled:

Process for Producing Compositions for Ruminants

state the following:-

1. The Applicant(s)/Nominated Person(s) has/have, for the following reasons, gained entitlement from the actual inventor(s):-

The Applicant, by virtue of a Contract between the actual inventors as employees and the Applicant as employer, is a person who would be entitled to have the patent assigned to it if a patent were granted on an application made by the actual inventors.

2a.* The Applicant(s)/Nominated Person(s) is/are the applicant(s) of the of the basic application(s) listed* on the Patent Request/ ~~*in the Declaration under Article 8 of the PCT~~.

2b.* ~~The Applicant(s)/Nominated Person(s) is/are entitled to rely on the basic application(s) listed* on the Patent Request/ *in the Declaration under Article 8 of the PCT as follows:~~

3.* The basic application(s) listed *on the Patent Request/ ~~*in the Declaration under Article 8 of the PCT~~ is/are the application(s) first made in a Convention Country in respect of the invention.

4a.* ~~The Applicant(s)/Nominated Person(s) is/are the depositor(s) of the deposit(s) listed in the Schedule hereto.~~

4b.* ~~The Applicant(s)/Nominated Person(s) has/have the consent of~~ , ~~of~~

~~the depositor(s) of the deposit(s) listed in the Schedule hereto, to rely on that/those deposit(s).~~

DATED this 23rd day of August 1993

Kyowa Hakko Kogyo Co., Ltd.

Seiichi Yada

(Signature) Seiichi Yada

Executive vice-president

(Name & Title)

* Delete if not applicable.

AU9346294

(12) PATENT ABRIDGMENT (11) Document No. AU-B-46294/93
(19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. 666035

(54) Title
PROCESS FOR PRODUCING COMPOSITIONS FOR RUMINANTS

International Patent Classification(s)
(51)[5] A61K 009/113
(51)[6] A23K 001/18 A61K 009/32

(21) Application No. : 46294/93 (22) Application Date : 10.09.93

(30) Priority Data

(31) Number	(32) Date	(33) Country
4-243157	11.09.92	JP JAPAN

(43) Publication Date : 17.03.94

(44) Publication Date of Accepted Application : 25.01.96

(71) Applicant(s)
KYOWA HAKKO KOGYO CO., LTD.

(72) Inventor(s)
YOROZU YOKOMORI; TOSHIKAZU MURAYAMA; TOMOAKI MASADA; MOTOHIRO OHTA; MASAKI AZUMA; YOSHIO YUMIBA

(74) Attorney or Agent
SPRUSON & FERGUSON , GPO Box 3898, SYDNEY NSW 2001

(56) Prior Art Documents
AU 18524/92 A23K A61K
AU 78330/91 A61K A23L A23P
US 5244669

(57) Claim

1. A process for producing a composition for ruminants which comprises the steps of:

a. granulating a polymer soluble in water of pH 5.0 or below and insoluble in water of pH over 5.0 to fine particles having a diameter of less than 100μm;

b. preparing a slurry by dispersing the fine particles obtained in step a in water;

c. preparing a coating material by mixing the slurry obtained in step b with an emulsion obtained by dissolving in an organic solvent a hydrophobic sparingly water soluble substance, dispersing the resulting solution in water, with an emulsifier, and removing the organic solvent by heating; and

d. coating a nucleus containing a physiologically active substance with the coating material obtained in step c.

Process For Producing Compositions For Ruminants

Background of the Invention

The present invention relates to a novel process for producing compositions for ruminants in which an aqueous suspension is used for coating.

In ruminants, substances orally administered are stored in the rumen of pH 5.5 and then absorbed into a blood stream in the abomasum of pH 3.0.

In order to increase the absorption of physiologically active substances in the abomasum, there have been developed compositions for ruminants utilizing coating materials which have a suppressive effect on the decomposition of the active substances in the rumen, but do not have a suppressive effect on the absorption of the active substances in the abomasum.

For example, Japanese Published Unexamined Patent Application Nos. 88843/86, 88844/86 and USP 5,080,917 (EP-A-336,713) disclose compositions which comprise as a coating a substance selected from saturated fatty acids having more than 14 carbon atoms, hardened oils of animal or plant origin, natural resins and synthetic resins, and mixtures thereof, and a polymer soluble in water of pH 5.0 or below. The compositions are produced by coating a granulated physiologically active substance as a nucleus with a coating material by spraying. The coating material is prepared by dissolving a substance selected from saturated fatty acids having more than 14 carbon atoms, hardened oils of animal or plant origin, natural resins and synthetic resins, and mixtures thereof, and a polymer soluble in water of pH 5.0 or below in an organic solvent. During the spray coating, a large quantity of the organic solvent evaporates and diffuses into the air. Such process involves the danger of pollution and fire.

Therefore, it is desired to develop a process for producing compositions for ruminants which does not involve such problem.

Summary of the Invention

The present invention provides a process for producing a composition for ruminants which comprises the steps of:

a. granulating a polymer soluble in water of pH 5.0 or below and insoluble in water of pH over 5.0 to fine particles having a diameter of less than 100μm;

b. preparing a slurry by dispersing the fine particles obtained in step a in water;

c. preparing a coating material by mixing the slurry obtained in step b with an emulsion obtained by dissolving in an organic solvent a hydrophobic sparingly water soluble substance, dispersing the resulting solution in water, with an emulsifier, and removing the organic solvent by heating; and

d. coating a nucleus containing a physiologically active substance with the coating material obtained in step c.

AUSTRALIAN PATENT OFFICE LS

In the process, an aqueous suspension is used for coating instead of a material dissolved in an organic solvent.

Detailed Description of the Invention

The coating material used in the present invention may be prepared by any method so long as it is an aqueous suspension of (i) a hydrophobic sparingly water soluble substance and (ii) a polymer soluble in water of pH 5.0 or below and insoluble in water of pH over 5.0.

For example, the coating material can be prepared by suspending in water (i) an emulsion comprising water and at least one hydrophobic sparingly water soluble substance and (ii) a slurry containing at least one polymer soluble in water of pH 5.0 or below and insoluble in

AUSTRALIAN PATENT OFFICE

water of pH over 5.0, if necessary, in the presence of a filler.

The emulsion comprising water and at least one hydrophobic sparingly water soluble substance ~~substance hardly soluble in water~~ can be prepared in the following manner. The hydrophobic substance is dissolved in an appropriate quantity of an organic solvent, together with an emulsifier, and then the resulting solution is dropped and dispersed in water, followed by the removal of the organic solvent with heating at 40 to 100°C at ordinary pressure or under reduced pressure. It is preferable that the removed organic solvent is recovered by a cooler. Alternatively, the hydrophobic substance may be dissolved in an appropriate quantity of an organic solvent and then dropped and dispersed in water containing an emulsifier, followed by the removal of the organic solvent as described above.

Examples of the hydrophobic sparingly water soluble substances ~~substances hardly soluble in water~~ include saturated fatty acids containing not less than 14 carbon atoms and metal salts thereof, higher fatty alcohols containing not less than 12 carbon atoms, hardened animal and vegetable oils, and natural and synthetic polymers.

Examples of the saturated fatty acids containing not less than 14 carbon atoms include straight-chain or branched monocarboxylic acids such as myristic acid, palmitic acid and stearic acid, and examples of their metal salts include calcium, magnesium, barium and iron

AUSTRALIAN PATENT OFFICE LS

salts. Examples of the higher fatty alcohols containing not less than 12 carbon atoms include laurel alcohol, myristyl alcohol, cetyl alcohol and stearyl alcohol. Examples of the hardened animal and vegetable oils include hardened beef tallow oil and hardened castor oil. An example of the natural polymer is shellac. Examples of the synthetic polymers include copolymer resins of styrene, vinyl chloride, vinylidene chloride, acrylic esters, methacrylic esters, vinyl acetate and the like; resins such as polyesters, polyurethanes, nylons and polyacetals; and derivatives of natural polymers such as cellulose acetate, ethyl cellulose and propyl cellulose.

Examples of the organic solvents include toluene, xylene, acetone, methyl ethyl ketone, isobutyl ketone, ethyl acetate, butyl acetate and chloroform. The solvents are used in an amount of 140 to 700 wt% based on the weight of the hydrophobic substance contained in the solvents.

Examples of the emulsifiers include nonionic emulsifiers such as polyoxyethylene alkyl ethers, polyoxyethylene alkylphenol ethers, sorbitan fatty acid esters, polyoxyethylene sorbitan fatty acid esters, polyoxyethylene acyl esters, polyoxyethylene oxypropylene block copolymers and fatty acid monoglycerides; anionic emulsifiers such as salts of fatty acids, salts of sulfuric esters of higher alcohols, alkylbenzenesulfonate, alkylnaphthalenesulfonate, dialkylsulfosuccinate, salts of alkyl phosphate and salts

of polyoxyethylene sulfate; and cationic emulsifiers such as salts of alkylamines, quaternary ammonium salts and polyoxyethylene alkylamines. The emulsifiers are used in an amount of 1 to 30 parts by weight, preferably 2 to 20 parts by weight, based on 100 parts by weight of the hydrophobic substance.

The hydrophobic substance may be contained in the emulsion in an amount of 1 to 50 wt% based on the weight of the entire emulsion.

In cases where the hydrophobic sparingly water soluble substance ~~substance hardly soluble in water of pH 5.5 or above~~ is a synthetic copolymer resin, it is possible to prepare the emulsion in accordance with a known method [Soichi MUROI "Chemistry of Copolymer Latex," published by Kobunshi Kankokai (1970)]. A commercially available emulsion, for example, Ethyl Cellulose Emulsion (produced by FMC Co.) can also be used as the emulsion comprising water and a hydrophobic substance hardly soluble in water.

Examples of the polymers soluble in water of pH 5.0 or below and insoluble in water of pH over 5.0 to be contained in the slurry include cellulose derivatives such as benzylaminomethyl cellulose, dimethylaminomethyl cellulose, piperidylethyl hydroxyethyl cellulose, cellulose acetate dimethylaminoacetate, cellulose acetate diethylaminoacetate and cellulose acetate dibutylaminohydroxypropyl ethers; polyvinyl derivatives such as vinyldiethylamine-vinyl acetate copolymers, vinylbenzylamine-vinyl acetate copolymers,

AUSTRALIAN PATENT OFFICE LS

polyvinyldiethylaminoacetoacetals, vinylpiperidylacetoacetal-vinyl acetate copolymers, polyvinyl acetal diethylamino acetate, polydimethylaminoethyl methacrylate, polydiethylaminomethylstyrenes, polyvinylethylpyridines, vinylethylpyridine-styrene copolymers, vinylethylpyridine-acrylonitrile copolymers methylvinylpyridine-acrylonitrile copolymers and methylvinylpyridine-styrene copolymers; copolymers of dimethylaminoethyl methacrylate and one or more acrylic acid alkyl esters and/or methacrylic acid alkyl esters; nitrogen-containing polysaccharides such as chitosan and chitin; and metal salts of polysaccharides such as calcium alginate. These polymers can be used either individually or in combination.

The slurry can be obtained by the following method. The polymer soluble in water of pH 5.0 or below and insoluble in water of pH over 5.0 is granulated to fine particles (diameter: 100 μm or less) by a jet mill, a ball mill, a colloid mill or the like. The fine particles are dispersed in water, preferably in the presence of an emulsifier as mentioned above and, if necessary, in the presence of a coagulation inhibitor such as talc. In order to obtain a stable slurry, it is preferred to add an emulsifier in an amount of 1 to 10 parts by weight, based on 100 parts by weight of the polymer. The polymer is contained in the slurry preferably at a concentration of 10 to 30% by weight.

Commercially available polymers, for example, AEA (trademark for a polyvinylacetal diethylaminoacetate produced by Sankyo Co., Ltd.) and Eudragid E100 (trademark for a copolymer consisting of dimethylaminoethyl acrylate, a methacrylic acid alkyl ester and at least one acrylic acid alkyl ester produced by Rohm Pharm. Co.), can also be used as the polymer soluble in water of pH 5.0 or below and insoluble in water of pH over 5.0.

As the filler, there can be used inorganic substances such as talc, kaolin, mica, silica, calcium carbonate, diatomaceous earth and barium sulfate; metal salts (e.g., calcium, barium or iron salts) of water-insoluble fatty acids having at least 12 carbon atoms, such as palmitic acid, stearic acid and myristic acid; alcohols such as lauryl alcohol, myristyl alcohol and stearyl alcohol; and pulverized particles of hardened material of thermosetting polymers such as pulverized particles of hardened epoxy resin acid anhydrides and of hardened phenolic resins. These fillers can be used either individually or in combination.

Inorganic fillers are used preferably in the form of fine powders pulverized beforehand, and non-inorganic fillers are used preferably in the form of an aqueous slurry of fine particles pulverized beforehand to a size of 100 μm or less.

The hydrophobic sparingly water soluble substance ~~substance hardly soluble in water~~ (B), the polymer soluble in water of pH 5.0 or below and

AUSTRALIAN PATENT OFFICE LS

insoluble in water of pH over 5.0 (C) and the filler (D) are admixed at the following ratio:

B/(C+D) = 100/10 to 100/200

C/D = 100/2 to 100/1000

B/C = 95/5 to 20/80, preferably 90/10 to 40/60

and the resulting mixture is suspended in water to prepare the coating material. The final volume of water is 1.5 to 18 times that of (B+C+D).

Examples of the physiologically active substances include amino acids such as methionine, lysine, tryptophan, threonine, glutamic acid, glutamine and aspartic acid; vitamins such as vitamin A; proteases such as acidic protease; saccharides such as glucose; antibiotics such as penicillin; and anthelmintics such as levamisole.

The nuclei containing a physiologically active substance can be produced by pelletizing a mixture of the physiologically active substance, an excipient, a binder and, if necessary, other ingredients (e.g., inorganic substance) by the use of an extrusion granulator, and then shaping the pellets into spheres by the use of a rounder.

Examples of the binders include cellulose derivatives such as methyl cellulose, ethyl cellulose, hydroxypropyl cellulose and hydroxypropyl methyl cellulose; vinyl derivatives such as polyvinyl alcohol and polyvinyl pyrrolidone; starch; fatty acids; hardened vegetable oils; and hardened animal oils. Examples of

the excipients include starch and fine crystalline cellulose; and examples of the inorganic substances include calcium carbonate, calcium phosphate and talc.

It is preferred to produce the nuclei in the spherical or granular form. Though the size of the nuclei is not particularly limited, they are usually 0.1 to 10 mm in diameter.

Coating of the nuclei with the coating material can be carried out by spraying at a temperature of 40 to 120°C. The coating material is used in an amount of 5 to 50 parts by weight based on 100 parts by weight of the nuclei. Any usual coating method can be utilized for the coating, including the pan coating method, the fluidization coating method and the centrifugal fluidization coating method.

The compositions obtained as above can be used for feed additives, medicines, and the like for ruminants.

In the present invention, an organic solvent is used only in the preparation of the emulsion. The obtained emulsion containing the organic solvent is heated and the evaporated organic solvent is recovered. Thus the organic solvent does not diffuse into the air.

Furthermore, in the coating process of the present invention, an aqueous suspension is used instead of the material dissolved in an organic solvent. The coating process of the present invention avoids the diffusion of an organic solvent into the air.

In conclusion, the process of the present invention

AUSTRALIAN PATENT OFFICE LS

is effective for the prevention of pollution and fire.

The nucleus of a composition for ruminants should dissolve only in the abomasum. The specificity of the site of dissolution of the nucleus depends on the coating of the nucleus. In general, coating of the nucleus with an aqueous suspension has been considered to be unsuitable for getting the desired effect on the dissolution of the nucleus at the specific site.

The dissolution rate of the compositions obtained according to the process is shown below.

Test Example

Methionine Oral Administration Compositions 1 to 3 and Lysine Oral Administration Compositions 4 to 6 were prepared in accordance with the process of the present invention, and Methionine Oral Administration Composition (a) and Lysine Oral Administration Composition (b) were prepared according to a known method using an organic solvent (as shown in Reference Examples 1 and 2). The compositions were subjected to a dissolution test under the conditions set forth in Table 1.

Table 1

Test Conditions

Test Liquid:	pH = 3.0: (A model for abomasum) Primary potassium citrate - hydrochloric acid pH = 6.0: (A model for rumen) Primary potassium citrate - sodium hydroxide

Continued../

Quantity of Liquid:	500 ml
Liquid Temperature:	37°C
Sample (pills):	500 mg
Detection Method:	Methionine: HPLC method Detected at Wavelength of 210 nm Column = Nucleocil C18 (by Nippon Gas Chromatography Kogyo Co., Ltd.) Lysine: Ninhydrin reaction OD method, 565 nm
Test Method:	Japanese Pharmacopoeia No. 11, General test method, Dissolution test, Paddle method, Number of rotation = 100 r.p.m.

The rates of dissolution were measured at six points (0.5, 1, 2, 3, 4 and 5 hours from the beginning of the test). The rates of dissolution of the compositions at pH 3.0 and 6.0 are shown in Table 2.

Table 2

Composition	pH	Dissolution rate of the nucleus (%) time from the beginning of the experiment 0.5 hr	1.0 hr	2.0 hrs	3.0 hrs	4.0 hrs	5.0 hrs
1	6.0	0	0	0	0	0	0
	3.0	78	90	102	101	100	101
2	6.0	0	0	0	0	0	0
	3.0	65	91	97	102	98	99
3	6.0	0	0	0	0	0	0
	3.0	60	87	94	103	101	102
4	6.0	0	0	0	0	0	0
	3.0	55	96	98	99	97	99
5	6.0	0	0	0	0	0	0
	3.0	50	87	95	101	100	100
6	6.0	0	0	0	0	0	0
	3.0	73	92	97	100	98	101
(a)	6.0	0	0	0	0	0	0
	3.0	99	98	101	102	100	101
(b)	6.0	0	0	0	0	0	0
	3.0	96	97	101	103	100	104

AUSTRALIAN PATENT OFFICE

Table 2 shows that the compositions according to the present invention are not dissolved at pH 6.0 (rumen) and dissolved at pH 3.0 (abomasum). Though the nucleus is coated with an aqueous suspension, the present invention shows the desired effect on the dissolution of the nucleus at the specific site. Furthermore, Table 2 shows that the present invention has the same effect as the known method. That is, in spite of the general view, it is apparent that the use of an aqueous suspension for coating in the preparation of compositions for ruminants can give the same effect as given by the use of a meterial dissolved in an organic solvent.

Certain embodiments of the invention are illustrated in the following examples.

Example 1

(1) Preparation of Methionine Granules

DL-Methionine (2,000 g) was mixed with 400 g of a 20% (w/w) aqueous solution of polyvinyl alcohol as a binder. The resulting mixture was extruded through a cylindrical granulating machine having a screen (diameter: 2.0 mm) and then shaped into spheres by using a Marumerizer (produced by Fuji Powdal Co.). The resulting granules were sieved through a sieve of 8 to 10 mesh and then dried in a current of air at 60°C for one hour to obtain granules of a diameter of 1.7 to 2.4 mm.

(2) Preparation of AEA Slurry

AEA (produced by Sankyo Co., Ltd.) pulverized using a ball mill and sieved through a sieve of 200 mesh. The obtained AEA particles (290 g) was admixed and stirred with 10 g of polyoxyethylene lauryl ether (Emulgen 106; produced by Kao Corp.) and 700 g of water, and the resulting mixture was dispersed using a sand mill to obtain a slurry of AEA.

(3) Preparation of Polyvinyl Acetate Slurry

Polyvinyl acetate was pulverized using a ball mill under cooling and then sieved through a sieve of 200 mesh. In order to prevent consolidation, 10 parts by weight of talc was added to 100 parts by weight of the sieved polyvinyl acetate particles. Then, the resulting polyvinyl acetate particles (285 g) was admixed and stirred with Emulgen 106 (15 g) and water (700 g), and the resulting mixture was dispersed using a sand mill to obtain a slurry of polyvinyl acetate.

(4) Preparation of Methionine Oral Administration Composition 1

In 200 g of water were suspended 200 g of a commercially available ethyl cellulose emulsion [composition: water 70%, solids 30% (ethyl cellulose, 87%; cetyl alcohol, 9%; and lauryl sulfate, 4%); product of FMC Co.], the AEA slurry (80 g) and the polyvinyl acetate slurry (120 g), to obtain a coating liquid. By using a fluidized-bed apparatus, the methionine granules

(1,000 g) were coated with the coating liquid (600 g) by spraying to obtain Methionine Oral Administration Composition 1.

Example 2

(1) Preparation of Stearic Acid Emulsion

Stearic acid (200 g) and ammonium laurylsulfate (12 g) were dissolved in a mixture of toluene (200 g) and ethyl acetate (200 g). The solution was added dropwise to water (2 liters) with stirring, and the resulting dispersion was concentrated by removing the solvents at 80°C under reduced pressure (50 torr.) to obtain a stearic acid emulsion having a solid content of 30%.

(2) Preparation of Eudragid E100 Slurry

A slurry of Eudragid E100 was prepared according to the same method as in the preparation of the polyvinyl acetate slurry in Example 1, except that Eudragid E100 was used in place of polyvinyl acetate.

(3) Preparation of Talc Slurry

A talc slurry was prepared by admixing and stirring talc (277.5 g), Emulgen 106 (22.5 g) and water (700 g), followed by dispersion using a sand mill.

(4) Preparation of Methionine Oral Administration Composition 2

Methionine Oral Administration Composition 2 was prepared in the same manner as in Example 1, except that

the coating liquid was prepared by suspending the ethyl cellulose emulsion used in Example 1 (270 g), the stearic acid emulsion (60 g), the Eudragid E100 slurry (160 g) and the talc slurry (110 g) in water (300 g).

Example 3

(1) Preparation of Cellulose Acetate Emulsion

Cellulose acetate (acetic acid value: 52%) (200 g), 12 g of sodium lauryl sulfate and 12 g of polyoxyethylene lauryl ether (Emulgen 120 produced by Kao Corp.), were dissolved in acetone (800 g). The solution was added dropwise to water (6 liters) with stirring, and the resulting dispersion was concentrated by removing acetone at 80°C under reduced pressure (50 torr.) to obtain a cellulose acetate emulsion having a solid content of 30%.

(2) Preparation of Chitosan Slurry

A slurry of chitosan was prepared according to the same method as in the preparation of the AEA slurry in Example 1, except that chitosan was used in place of AEA.

(3) Preparation of Methionine Oral Administration Composition 3

Methionine Oral Administration Composition 3 was prepared in the same manner as in Example 1, except that the coating liquid was prepared by suspending the cellulose acetate emulsion (400 g), the chitosan slurry (160 g) and the polyvinyl acetate slurry obtained in

AUSTRALIAN PATENT OFFICE

Example 1 (240 g) in water (400 g).

Example 4

(1) Preparation of Lysine Granules

Seven hundred grams of a mixture of 6% (w/w) hydroxypropyl cellulose (binder), water and ethanol [water:ethanol = 1:1 (v/v)] was added to l sine hydrochloride (2,000 g), and the mixture was kneaded. The resulting mixture was extruded through a cylindrical granulating machine having a screen (diameter: 2.0 mm) and then shaped into spheres by using a Marumerizer. The resulting granules were sieved through a sieve of 8 to 10 mesh, and then dried in a current of air at 60°C for one hour to obtain granules of a diameter of 1.7 to 2.4 mm.

(2) Preparation of Lysine Oral Administration Composition 4

The ethyl cellulose emulsion used in Example 1 (360 g), the chitosan slurry obtained in Example 3 (120 g) and the polyvinyl acetate slurry obtained in Example 1 (120 g) were suspended in water (300 g), to prepare a coating liquid. By using a fluidized-bed apparatus, the lysine granules (1,000 g) were coated with the coating liquid (900 g) by spraying, to obtain Lysine Oral Administration Composition 4.

Example 5

Preparation of Lysine Oral Administration Composition 5

Lysine Oral Administration Composition 5 was prepared in the same manner as in Example 4, except that the coating liquid was prepared by suspending the cellulose acetate emulsion obtained in Example 3 (600 g), the stearic acid emulsion obtained in Example 2 (60 g), the chitosan slurry obtained in Example 3 (120 g) and the talc slurry obtained in Example 2 (60 g) in water (400 g).

Example 6

Preparation of Lysine Oral Administration Composition 6

Lysine Oral Administration Composition 6 was prepared in the same manner as in Example 4, except that the coating liquid was prepared by suspending 1,000 g of a mixture of the ethyl cellulose emulsion used in Example 1 (720 g), the AEA slurry obtained in Example 1 (140 g), the polyvinyl acetate slurry obtained in Example 1 (70 g) and the talc slurry obtained in Example 2 (70 g) in 500 g of water.

Reference Example 1

Preparation of Methionine Oral Administration Composition

(a) Using Solvent

A coating liquid was prepared by dissolving ethyl cellulose (66.7 g), stearic acid (33.3 g), AEA (100 g) and glycerol fatty acid ester (30 g) in 3,000 g of a mixture of isopropanol and acetone [2:1 (v/v)], followed by the addition of 25 g of magnesium stearate as a

coagulation inhibitor. By using a fluidized-bed apparatus, the methionine granules used in Example 1 (1,000 g) were coated with the coating liquid (100 g as a solid) by spraying to obtain Methionine Oral Administration Composition (a).

Reference Example 2

Preparation of Lysine Oral Administration Composition (b) Using Solvent

A coating liquid was prepared by dissolving ethyl cellulose (83.3 g), stearic acid (16.7 g) and ethanol (50 g) in 3,000 g of a mixture of dichloromethane and ethanol [3:3 (v/v)]. The lysine granules used in Example 4 (1,000 g) were coated with the coating liquid (100 g as a solid) by spraying to obtain Lysine Oral Administration Composition (b).

The claims defining the invention are as follows:

1. A process for producing a composition for ruminants which comprises the steps of:

a. granulating a polymer soluble in water of pH 5.0 or below and insoluble in water of pH over 5.0 to fine particles having a diameter of less than 100μm;

b. preparing a slurry by dispersing the fine particles obtained in step a in water;

c. preparing a coating material by mixing the slurry obtained in step b with an emulsion obtained by dissolving in an organic solvent a hydrophobic sparingly water soluble substance, dispersing the resulting solution in water, with an emulsifier, and removing the organic solvent by heating; and

d. coating a nucleus containing a physiologically active substance with the coating material obtained in step c.

2. A process for producing a composition for ruminants substantially as hereinbefore described with reference to any one of the Examples but excluding the comparative examples.

3. The product of the process of claim 1 or claim 2.

Dated 10 November, 1995
Kyowa Hakko Kogyo Co., Ltd.
Patent Attorneys for the Applicant/Nominated Person
SPRUSON & FERGUSON

AUSTRALIAN PATENT OFFICE

Process for Producing Compositions for Ruminants

Abstract

Disclosed is a process for producing a composition for ruminants, which is characterised in that a nucleus containing a physiologically active substance is coated with a coating material prepared by suspending in water (i) an emulsion comprising water and at least one hydrophobic substance hardly soluble in water and (ii) a slurry containing at least one polymer soluble in water of pH 5.0 or below and insoluble in water of pH over 5.0.

In the process, an aqueous suspension is used for coating instead of a material dissolved in an organic solvent.

The invention also provides compositions for ruminants and methods for delivering physiologically active substances to ruminants.