
CORRECTED VERSION

(19) World Intellectual Property Organization

International Bureau





(10) International Publication Number WO 2011/104516 A8

(51) International Patent Classification:

E21B 17/04 (2006.01) **E21B 34/10** (2006.01) **E21B 34/14** (2006.01) **E21B 34/14** (2006.01)

(21) International Application Number:

PCT/GB2011/000265

(22) International Filing Date:

25 February 2011 (25.02.2011)

(25) Filing Language:

(26) Publication Language: English

(30) Priority Data:

12/713,256 26 February 2010 (26.02.2010)

US

English

- (71) Applicant (for all designated States except US): HAL-LIBURTON ENERGY SERVICES, INC. [US/US]; 10200 Bellaire Boulevard, Houston, Texas 77072 (US).
- (71) Applicant (for MW only): TURNER, Craig, Robert [GB/GB]; A A Thornton & Co, 235 High Holborn, London WC1V 7LE (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): HRISCU, Iosif, Joseph [US/US]; 1721 Wilshire Drive, Duncan, Oklahoma 73533 (US). BAILEY, Michael, Brent [US/US]; 1001 Palm Drive, Duncan, Oklahoma 73533 (US). EHTE-SHAM, Muhammad, Asif [PK/US]; 1902 Meadowview Drive, Duncan, Oklahoma 73533 (US). HOWARD, Robert [US/US]; 2600 South 2nd Street, Duncan, Oklahoma 73533 (US). PIPKIN, Robert, Lee [US/—]; HC 64 Box 22D, Marlow, Oklahoma 73055 (US).

- (74) Agents: TURNER, Craig, Robert et al.; A A Thornton & Co, 235 High Holborn, London WC1V 7LE (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:


- with international search report (Art. 21(3))
- (88) Date of publication of the international search report: 10 May 2012
- (48) Date of publication of this corrected version:

27 September 2012

[Continued on next page]

(54) Title: PRESSURE-ACTIVATED VALVE FOR HYBRID COILED TUBING JOINTED TUBING TOOL STRING





(57) Abstract: Embodiments of the hybrid tool string include coiled tubing (80) and jointed tubing, as well as a means typically located at the connection of the coiled and jointed tubing for sealing the fluid flowpath through the bore of the hybrid tool string. Embodiments of the hybrid tool string may use a pressure - activated valve tool (50) attached in series between the coiled tubing and the jointed tubing, which allows for sealing of the bore by application of pressure. Embodiments of the pressure - activated valve tool may use a flapper (53) in conjunction with a sleeve (55) to seal the bore. The novel hybrid tool string may be used to service a well.





(15) Information about Correction: see Notice of 27 September 2012