

(43) International Publication Date
8 December 2016 (08.12.2016)(51) International Patent Classification:
G06F 15/16 (2006.01)(21) International Application Number:
PCT/US2016/036006(22) International Filing Date:
6 June 2016 (06.06.2016)

(25) Filing Language: English

(26) Publication Language: English



(30) Priority Data:
14/732,079 5 June 2015 (05.06.2015) US(71) Applicant: **BOVEDA INC.** [US/US]; 17613 Minnetonka
Boulevard, Minnetonka, Minnesota 55391 (US).(72) Inventors: **SCHMITZ, Jason L.**; 4586 Daylesford Drive,
Akron, Ohio 44333 (US). **ESSE, Robert L.**; 3502 134th
Street NW, Monticello, Minnesota 55362 (US). **KNUT-
SEN, Sean A.**; 6207 Cascade Pass, Chanhassen, Min-
nesota 55391 (US).(74) Agents: **DAWSON, Michelle E.** et al.; Winthrop & Wein-
stine, P.A., Capella Tower, Suite 3500, 225 S 6th Street,
Minneapolis, Minnesota 55402 (US).(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).**Declarations under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

(54) Title: SYSTEMS, METHODS AND DEVICES FOR CONTROLLING HUMIDITY IN A CLOSED ENVIRONMENT WITH AUTOMATIC AND PREDICTIVE IDENTIFICATION, PURCHASE AND REPLACEMENT OF OPTIMAL HUMIDITY CONTROLLER

**FIG. 1A****FIG. 1B**

(57) Abstract: The invention relates to systems and methods for monitoring and providing humidity control for an asset within a closed environment such as a storage container, with transmission of sensed humidity levels to at least one server that stores current and historical humidity levels and comprises a processor and stored executable instructions that, when executed by the processor, may recommend an optimal humidity controller to use for the asset, determine when the recommended humidity controller requires replacement and predictively recommend an optimal replacement humidity controller based on at least historical humidity data and trending thereof, execution of a sales transaction, that may be pre-scheduled based on asset type, asset size and/or historical data, for the optimal replacement humidity controller, and providing the proper replacement humidity controller to the user.

Systems, Methods and Devices for Controlling Humidity in a Closed Environment with Automatic and Predictive Identification, Purchase and Replacement of Optimal Humidity Controller

INVENTORS

Jason L. Schmitz, a citizen of the United States of America, resident at Akron, OH

Robert L. Esse, a citizen of the United States of America, resident at Monticello, MN

Sean A. Knutsen, a citizen of the United States of America, resident at Chanhassen, MN

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] Not Applicable

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

[0002] Not Applicable

FIELD OF THE INVENTION

[0003] The invention relates to systems and methods for monitoring and tracking while providing humidity control for an asset within a closed environment and automatic and predictive replacement of the humidity controller before reaching its end of life.

BACKGROUND OF THE INVENTION

[0004] Closed environments such as storage cases for instruments, particularly stringed instruments, cigars or other tobacco products require controlling of the relative humidity levels within the closed environments to optimally maintain the assets stored or housed therein.

[0005] In the case of musical instruments, atmospheric humidity can affect the lifespan and sound quality for stringed, woodwind, brass and percussion instruments. The presence or absence of optimal humidity levels can lead to swelling, splits, cracks, checking, movement in joins and general distortion of materials susceptible to too much

or too little humidity.

[0006] Similarly, too much or too little atmospheric humidity can adversely affect the quality and/or lifespan of stored cigars or other tobacco products. Thus, humidors are provided to assist in maintaining not only humidity levels, but also temperature levels, within a desired range.

[0007] Humidity controllers are known in the art and may be considered for use in conjunction with the present invention. Particularly effective humidity controllers are marked by Boveda, Inc., and are described in detail in US Patents 5,936,178 and 8,748,723, the full disclosures of which are hereby incorporated by reference. See also US Patent 6,209,717, also incorporated in its entirety by reference. Generally, however, any humidity controller may be suitable for operation with the present invention as described and claimed.

[0008] Also known to the skilled artisan are systems and methods for wirelessly transmitting sensed humidity data, obtained within a closed environment by known humidity sensors, via a communication system for remote viewing by a user on a computing device such as a computer, tablet, and/or a smartphone.

[0009] There are, however, no known systems or methods that provide a predictive notification and automated purchase of an optimal humidity controller designed to maintain humidity levels for a specific type of asset. Further, there are no known systems or methods that predict and automatically set a replacement frequency for identifying and purchasing an optimal humidity controller for a specific asset type.

BRIEF SUMMARY OF THE INVENTION

[0010] Various embodiments of the invention comprise systems, server(s) and methods for monitoring and providing humidity control for an asset within a closed environment such as a storage container, with transmission of sensed humidity levels to at least one server that stores current and historical humidity levels and comprises a processor and stored executable instructions that, when executed by the processor, may recommend an optimal humidity controller to use for the asset, determine when the recommended humidity controller requires replacement and predictively recommend an optimal replacement humidity controller based on at least historical humidity data and

trending thereof, execution of a sales transaction, that may be pre-scheduled based on asset type, asset size and/or historical data, for the optimal replacement humidity controller, and providing the proper replacement humidity controller to the user.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0011] The following drawings are illustrative of embodiments of the invention and are not intended or to be interpreted as limiting the scope of the invention as encompassed by the claims.

[0012] Figure 1A is a schematic diagram of one embodiment of the present invention;

[0013] Figure 1B is a schematic diagram of one embodiment of the present invention;

[0014] Figure 2 is a schematic diagram of one embodiment of the present invention;

[0015] Figure 3 is a schematic diagram of one embodiment of the present invention; and

[0016] Figure 4 is a flowchart of one embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0017] The description of the invention and its applications as set forth herein is illustrative and is not intended to limit the scope of the invention. Variations and modifications of the embodiments disclosed herein are possible, and practical alternatives to and equivalents of the various elements of the embodiments would be understood to those of ordinary skill in the art upon study of this patent document. These and other variations and modifications of the embodiments disclosed herein may be made without departing from the scope and spirit of the invention.

[0018] Generally, the present invention comprises systems, methods and servers configured to monitor and control humidity levels within a closed environment such as an instrument case or humidor or other closed environments housing assets in need of humidity control. More specifically, the invention comprises identification of an optimal humidity controller for the specific asset under consideration and/or identification of an

optimal replacement humidity controller for the specific asset. In certain embodiments, these steps are executed automatically when the system, method and/or server determines that the currently used humidity controller is nearing the end of its useful life. In still further embodiments, a replacement frequency may be established for replacing the currently used humidity controller, and subsequently used replacement humidity controllers, shortly before the presently used humidity controller reaches the end of its useful life.

[0019] As illustrated in Figures 1A and 1B, a closed environment 10 is provided which may consist of a container 12 housing an asset 14 and humidity sensor 16 therein. Humidity sensor 16 may, alternatively, be located within the asset 14. Humidity controller 18 is also disposed within closed environment 10.

[0020] Figure 1A illustrates the case where humidity controller 18 is located or disposed generally within the closed environment 10 and specifically within the container 12, but not inside the asset 14. Figure 1B provides an alternative arrangement wherein the humidity controller 18 is disposed or located generally within the closed environment 10 and specifically within the asset 14.

[0021] Figure 2 illustrates one embodiment of a system according to the present invention. There, closed environment 10 is shown as a container 12 with asset 14, humidity sensor 16 and humidity controller 18, generally configured as in Figure 1A.

[0022] As discussed above, the humidity controller 18 may comprise many alternatives or configurations. However, one highly preferred humidity controller 18 humidity controller controls the relative humidity in the container and/or asset housed within the container in the general range of 40% to 60%, the device comprising: (a) a pouch formed of a thin-walled polymeric material permeable to water vapor but not to liquid solutions; (b) a humidity control solution comprising saturated or unsaturated aqueous salt solution containing an amount of alkali metal formate selected from sodium formate, potassium formate, sodium or potassium lactate and combinations thereof sealed in said pouch wherein said salt solution contains from about 30% to 90% salt; and (c) wherein the water vapor permeability of the pouch is such that the moisture transfer capacity of the pouch transmits at least from about 1% to about 50% by weight of the initial pouch contents when exposed to an atmosphere of less than 10% relative humidity

and absorbs at least from about 1% to about 50% by weight of the initial pouch content when exposed to an atmosphere having greater than 85% relative humidity.

[0023] In some embodiments, the pouch is disposed in a fabric holder for insertion into and retraction from a “bell hole” of an instrument. In certain embodiments, the pouch may be further configured to prevent leakage of the contents thereof.

[0024] Figure 2 further provides that the humidity sensor 16 is in wireless operative communication 20, via in the illustration, a Wi-Fi bridge 22, with a cloud-based remotely located server, or set of servers 24. In addition, humidity sensor 16 is also in wireless operative communication with a computing device 26 which may also be remotely located from both the sensor 16 and the cloud-based server(s) 24. Further, the computing device 26 is in operative and wireless communication with the cloud-based server(s) 24 as well as a commerce platform 28 comprising servers and capable of an internet-based transaction. Finally, the cloud-based server(s) 25 and the commerce platform servers 28 are in wireless and operative communication.

[0025] The skilled artisan will recognize that computing device 26 may comprise a computer or a smartphone or the like.

[0026] The skilled artisan will also readily understand that the wireless communication ability of the humidity sensor to operatively communicate with the cloud-based server(s) 24 and/or the computing device 26 may be achieved in a number of ways, including but not limited to Bluetooth, RFID and/or QR code(s).

[0027] The skilled artisan will also realize that commerce platform servers 28 and the purchasing and delivery systems and methods embodied thereby are well known in the art.

[0028] Thus, Figure 2 provides for a system wherein the humidity sensor 16 periodically provides humidity data from within the closed environment, e.g., within the container 12, wirelessly via, Bluetooth to e.g., a Wi-Fi bridge 22 and ultimately to the cloud-based server(s) 24 and/or the computing device 26.

[0029] As best seen in Figures 2 and 3, the cloud-based server(s) 24 comprise a processor 30 configured to control at least some operations of the server(s) 24 and a memory 32 in operative communication with the processor 30. The memory 32 is capable of storing at least computer executable instructions, user addresses associated

with an asset that is located at a remote location and that at least part of the time is stored within a container, and a look-up table listing more than one humidity controller arranged by humidity control capacity and/or useful life under known humidity conditions and a plurality of asset types associated with at least one of the listed humidity controllers, wherein the associated listed humidity controllers are optimized for controlling the humidity of the associated asset type.

[0030] The computer executable instructions stored in the server memory 32 are configured to be executed by the processor 30 that, when executed cause the server(s) 24 to:

[0031] look up the asset located at a remote location and the at least one associated humidity controller 18 in the look-up table;

[0032] select or identify the humidity controller 18 that is optimal for the asset 14;

[0033] in response to selecting or identifying the optimal humidity controller 18 for the asset 14, retrieve stored user addresses associated with the asset 14;

[0034] transmits the optimal humidity controller selection to the user addresses; and

[0035] initiate and execute a transaction to purchase the optimal humidity controller 18 for delivery to the user.

[0036] In this way, the present invention may automatically select or identify, purchase and deliver the optimal humidity controller 18 to a user for a particular asset 14.

[0037] In addition, the present invention may be used to automatically identify/select, purchase and deliver an optimal replacement controller 18 to a user for a particular asset 14.

[0038] Thus, in addition to the above steps, the servers' processor (30) may further execute the programmed and executable instructions to:

[0039] determine the selected humidity controller's end of useful life;

[0040] identify an optimal humidity controller replacement;

[0041] automatically initiate and execute a transaction to purchase the optimal humidity controller replacement before the determined end of useful life; and

[0042] deliver the optimal humidity controller replacement to the user before the

determined end of useful life.

[0043] In some embodiments, identifying the optimal humidity controller may include one or more of:

[0044] Tracking the humidity levels over a duration. In certain embodiments, the tracking starts from when the humidity controller is first placed in service. In other embodiments, the tracking is over a pre-specified period;

[0045] Retrieving information that identifies the asset for which the humidity controller is or will be used for;

[0046] Retrieving information on the humidity controller currently in use. Such information may include one or more of the total number of humidity controllers in use and the identity of each humidity controller in use such as, but not limited to, the product model number and serial number. The retrieved information may also include information on when each humidity controller was placed into service such as, but not limited to, the installation date and/or time;

[0047] Retrieving information on where the asset is located including, but not limited, the geographic location and locale;

[0048] Determining the optimal replacement humidity controller for the housed asset based on tracked humidity levels, the retrieved asset identity, the retrieved information on the humidity controller currently in use with the asset, and the retrieved information on where the asset is located. In some embodiments, such determination may be made from a database of all the humidity controller products available. The database may include information such as, but not limited to, the performance, engineering and/or technical specifications for all the humidity controller products; and

[0049] Recommending the determined optimal replacement humidity controller for purchase. In some embodiments, the user is provided comparative information on the humidity controller currently in service and the recommended replacement humidity controller. Such comparative information may be useful to the user in understanding why the recommended humidity controller is different from that in service. In certain embodiments, if the in-service and replacement humidity controller are the same, it may not be necessary to provide the comparative information. In other embodiments, the recommendation may include information such as the performance of the humidity

controller in service.

[0050] In some embodiments, the initiation and/or execution of the transaction to purchase the humidity controller replacement may be manual or partly automated, i.e., not fully automated. In a non-limiting exemplary embodiment, the user is provided an option to select, for purchase, between the recommended and the in-service humidity controller. In some embodiments, the user may be provided an option to change the quantity and/or the type (e.g., product number) of the recommended or the in-service humidity controller being purchased. In certain embodiments, the user may be provided an option to select and/or order the desired quantity and/or the type of the humidity controller which may be different from the humidity controller currently in-service and/or the recommended humidity controller.

[0051] In some embodiments, the initiation and/or purchase of the humidity controller may include providing the user to select a payment method from a plurality of choices presented to the user. It will be appreciated that such transaction processing systems and methods are well known in the art. In a non-limiting exemplary embodiment, the purchase transaction may include a “one-click” payment option as is well known in the art. In certain embodiments, the payment transaction may further include providing the user an ability to change the payment method and/or update any previously stored payment related information.

[0052] In a non-limiting exemplary embodiment, the user is always provided an ability to cancel the transaction at any point in the process.

[0053] Still further, the present invention may be used to establish an optimal humidity controller replacement frequency, storing same within the server’s memory. In this embodiment, the processor 30 may execute computer executable instructions that cause the server to:

[0054] establish an optimal humidity controller replacement frequency based on asset type and the determined end of useful life of the selected humidity controller;

[0055] automatically initiate and execute at least one transaction to purchase a first optimal humidity controller replacement before the selected humidity controller’s determined end of useful life and in accordance with the established replacement frequency; and

[0056] deliver the first optimal humidity controller replacement to the user before the selected humidity controller's determined end of useful life.

[0057] Thus, using an established replacement frequency enables repeated automated replacement, including identification/selection, purchase and delivery of the optimal replacement humidity controllers 18.

[0058] Turning now to Figure 4, one embodiment of the inventive method is illustrated.

[0059] Initially, a closed environment 10 housing an asset 14 is provided in step 50.

[0060] Next, a humidity sensor is provided and located within the closed environment, either within a container 12 or within the asset 14 housed within the container 12 and configured to sense humidity levels therein in step 52.

[0061] A humidity controller 18 is provided within the closed environment 10 and is selected, either automatically using the invention or manually, to maintain the humidity levels within the closed environment and/or asset within a predetermined range in step 54.

[0062] A remotely located, cloud-based, server(s) 24 is provided at a location remote from the closed environment 10 is provided in step 56. The server(s) 24 are in operative and wireless communication with the humidity sensor 16. Generally, as described above, Bluetooth or similar wireless communication method may be used to facilitate wirelessly communicating the humidity data sensed within closed environment 10 to the server(s) 24 via, e.g., a Wi-Fi bridge 22.

[0063] Further, in response to selecting the optimal humidity controller for the asset, user addresses associated with the asset stored in the server(s) 24 memory are retrieved from the server(s) 24 memory 32 at step 60.

[0064] Next, a transaction to purchase the selected optimal humidity controller for delivery to the user is automatically initiated and executed, with subsequent delivery to the user addresses previously accessed in step 62.

[0065] In certain embodiments, the selected humidity controller's end of useful life is determined, accessing the relevant data from the memory 32 of server(s) 24 at step 64.

[0066] In certain embodiments, a recommended optimal humidity controller replacement may be determined and established in step 64, with subsequent automatically initiation and execution of a transaction to purchase the optimal humidity controller replacement before the determined end of useful life in step 68 and delivery of the optimal humidity controller replacement to the user before the determined end of useful life in step 70.

CLAIMS

We claim:

1. A method for automatically replacing a user's humidity controller used to maintain humidity levels within a closed environment housing an asset, comprising:
determining the humidity controller is nearing the end of its useful life;
retrieving stored user address information;
identifying the optimal replacement humidity controller for the housed asset;
initiating a purchase transaction for the optimal replacement humidity controller;
notifying the user; and
delivering the replacement humidity controller to the user address.
2. The method of claim 1, wherein identifying the optimal replacement humidity controller comprises:
tracking the humidity levels over a duration;
retrieving asset identifying information;
retrieving humidity controller information, comprising:
total number of humidity controllers in use;
identity of each humidity controller in use; and
installation date of each humidity controller in use;
retrieving asset location information;
determining the optimal replacement humidity controller for the housed asset based
on the tracked humidity levels, the retrieved asset identity, the retrieved
humidity controller information, and the retrieved asset location information;
and
recommending the determined optimal replacement humidity controller for
purchase.
3. The method of claim 2, wherein initiating the purchase transaction further
comprises providing the user an ability to change the purchase.

4. The method of claim 3, wherein initiating the purchase transaction comprises providing the user a purchasing option selected from the group consisting of the recommended optimal replacement humidity controller and the retrieved humidity controller information.
5. The method of claim 1, wherein initiating the purchase transaction comprises the user selecting a payment method comprising one of a previously provided payment method and a new payment method.
6. The method of claim 1, further comprising:
establishing a frequency for purchasing and replacing the user's humidity controller; and
automatically identifying, purchasing, replacing and delivering an optimal replacement humidity controller to the user address in accordance with the established frequency.
7. A system for monitoring and controlling humidity levels within a container that houses an asset owned or operated by a user, comprising:
a humidity sensor located within the container and/or within the asset housed within the container, wherein the humidity sensor periodically senses the humidity experienced by the asset, and wherein the humidity sensor is in operative wireless communication with at least one server located remotely from the humidity sensor, and wherein the at least one server is capable of receiving and storing sensed humidity data transmitted from the humidity sensor;
a first optimal humidity controller located within the container and/or within the asset housed within the container and capable of controlling the monitored humidity to predetermined levels and further comprising a predicted useful life with the container and the asset;

a computing device capable of wirelessly operatively communicating with the server and/or the humidity sensor to enable the user to view the stored sensed humidity data; and

the at least one server further configured to, before the end of the optimal humidity controller's predicted useful life, automatically determine an optimal replacement humidity controller, initiate a transaction to purchase the determined optimal replacement humidity controller with notification to the user's computing device, and deliver the purchased optimal replacement humidity controller to the user before the end of the predicted useful life for the humidity controller.

8. The system of claim 7, wherein the asset comprises a stringed instrument or tobacco products.
9. The system of claim 7, wherein the humidity controller controls the relative humidity in the container and/or asset housed within the container in the general range of 40% to 60%, the device comprising:
 - (a) a pouch formed of a thin-walled polymeric material permeable to water vapor but not to liquid solutions;
 - (b) a humidity control solution comprising saturated aqueous salt solution containing an amount of alkali metal formate selected from sodium formate, potassium formate, sodium or potassium lactate and combinations thereof sealed in said pouch wherein said salt solution contains from about 30% to 90% salt; and
 - (c) wherein the water vapor permeability of the pouch is such that the moisture transfer capacity of the pouch transmits at least from about 1% to about 50% by weight of the initial pouch contents when exposed to an atmosphere of less than 10% relative humidity and absorbs at least from about 1% to about 50% by weight of the initial pouch content when exposed to an atmosphere having greater than 85% relative humidity.

10. A server, comprising:
 - a processor configured to control at least some operations of the server;
 - a memory in operative communication with the processor and storing computer executable instructions, user addresses associated with an asset that is located at a remote location and that at least part of the time is stored within a container, and a look-up table listing more than one humidity controller arranged by humidity control capacity and/or useful life under known humidity conditions and a plurality of asset types associated with at least one of the listed humidity controllers, wherein the associated listed humidity controllers are optimized for controlling the humidity of the associated asset type; and
 - the computer executable instructions configured to be executed by the processor that, when executed cause the server to:
 - look up the asset located at a remote location and the at least one associated humidity controller in the look-up table;
 - select the humidity controller that is optimal for the asset;
 - in response to selecting the optimal humidity controller for the asset, retrieve user addresses associated with the asset;
 - transmits the optimal humidity controller selection to the user addresses; and
 - initiate and execute a transaction to purchase the optimal humidity controller for delivery to the user.
11. The server of claim 10, further comprising the server's computer executable instructions being configured to, upon execution by the processor, causing the server to:
 - determine the selected humidity controller's end of useful life;
 - identify an optimal humidity controller replacement;
 - automatically initiate and execute a transaction to purchase the optimal humidity controller replacement before the determined end of useful life; and
 - deliver the optimal humidity controller replacement to the user before the determined end of useful life.

12. The server of claim 11, further comprising the server's computer executable instructions being configured to, upon execution by the processor, cause the server to:
establish an optimal humidity controller replacement frequency based on asset type and the determined end of useful life of the selected humidity controller;
automatically initiate and execute at least one transaction to purchase a first optimal humidity controller replacement before the selected humidity controller's determined end of useful life; and
deliver the first optimal humidity controller replacement to the user before the selected humidity controller's determined end of useful life.
13. The server of claim 11, further comprising the server's computer executable instructions being configured to, upon execution by the processor, cause the server to:
automatically initiate and execute at least one transaction to purchase a second optimal humidity controller replacement based on the established optimal humidity controller replacement frequency; and
deliver the purchased second optimal humidity controller replacement to the user before the first optimal humidity controller replacement's end of useful life.
14. The server of claim 10, wherein the asset comprises a stringed instrument.
15. The server of claim 10, wherein the asset comprises tobacco products.
16. A method of controlling humidity in a closed environment, comprising:
providing a closed environment housing an asset;
providing a humidity sensor within the closed environment and/or asset and
configured to sense humidity levels within the closed environment and/or asset;
providing a humidity controller within the closed environment and/or asset, selected to maintain the humidity levels within the closed environment and/or asset within a predetermined range;

providing a remotely located server at a location remote from the closed environment, the server comprising:

- a processor in the remotely located server configured to control at least some operations of the server; and
- a memory in operative communication with the processor and storing computer executable instructions, user addresses associated with the asset, and a look-up table listing more than one humidity controller arranged by humidity control capacity and/or useful life under known humidity conditions and a plurality of asset types associated with an optimal humidity controller of the listed humidity controllers; and

executing the computer executable instructions to enable:

- looking up the asset located at a remote location and the at least one associated humidity controller in the look-up table;
- selecting the humidity controller that is optimal for the asset;
- in response to selecting the optimal humidity controller for the asset, retrieving user addresses associated with the asset;
- transmitting the selected optimal humidity controller selection to the user addresses; and
- initiating and executing a transaction to purchase the selected optimal humidity controller for delivery to the user.

17. The method of claim 16, further comprising:
- determining the selected humidity controller's end of useful life;
 - establishing a recommended optimal humidity controller replacement;
 - automatically initiating and executing a transaction to purchase the optimal humidity controller replacement before the determined end of useful life; and
 - delivering the optimal humidity controller replacement to the user before the determined end of useful life.

18. The method of claim 16, further comprising:

the humidity controller controlling the relative humidity in the closed environment within the general range of 40% to 60%; and

providing a humidity controller comprising:

- (a) a pouch formed of a thin-walled polymeric material permeable to water vapor but not to liquid solutions;
- (b) a humidity control solution comprising saturated aqueous salt solution containing an amount of alkali metal formate selected from sodium formate, potassium formate, sodium or potassium lactate and combinations thereof sealed in said pouch wherein said salt solution contains from about 30% to 90% salt; and
- (c) wherein the water vapor permeability of the pouch is such that the moisture transfer capacity of the pouch transmits at least from about 1% to about 50% by weight of the initial pouch contents when exposed to an atmosphere of less than 10% relative humidity and absorbs at least from about 1% to about 50% by weight of the initial pouch content when exposed to an atmosphere having greater than 85% relative humidity.




FIG. 1A




FIG. 1B






FIG. 2

**FIG. 3**

**FIG. 4**

INTERNATIONAL SEARCH REPORT		International application No. PCT/US16/36006		
A. CLASSIFICATION OF SUBJECT MATTER IPC: G06F 15/16(2006.01) USPC: 709/206 According to International Patent Classification (IPC) or to both national classification and IPC				
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 709/206 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)				
C. DOCUMENTS CONSIDERED TO BE RELEVANT				
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
Y	US 2014/0189443 A1 (Xu et al.) 03 July 2014, see entire document.	1-20		
Y	US 2009/0080428 A1 (Witkowski et al) 26 March 2009, see entire document.	1-20		
Y	US 2004/0243737 A1 (Beardsley et al.) 02 December 2004, see entire document.	6, 16		
Y	US 2002/0031142 A1 (Metin et al.) 14 March 2002, see entire document.	9, 19		
Y	US 2013/0111077 A1 (Gowravaram et al.) 02 May 2013, see entire document.	7-8, 17-18		
☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.				
<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; vertical-align: top;"> * Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed </td> <td style="width: 50%; vertical-align: top;"> "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family </td> </tr> </table>			* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family			
Date of the actual completion of the international search 28 September 2016 (28.09.2016)		Date of mailing of the international search report 07 OCT 2016		
Name and mailing address of the ISA/IJS Mail Stop PCT, Attn: ISA/IJS Commissioner for Patents P.O. Box 1450 Alexandria, Virginia 22313-1450 Facsimile No. (571) 273-8300		Authorized officer Chris Grant Telephone No. 571-272-4300		