

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
16 November 2006 (16.11.2006)

PCT

(10) International Publication Number
WO 2006/120553 A1

(51) International Patent Classification:
H04L 12/56 (2006.01) **H04L 12/28** (2006.01)

(74) Agents: **STYLE, Kelda, Camilla, Karen** et al.; Page White & Farrer, Bedford House, John Street, London WC1N 2BF (GB).

(21) International Application Number:
PCT/IB2006/001236

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 3 May 2006 (03.05.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0509429.7 9 May 2005 (09.05.2005) GB
0509530.2 10 May 2005 (10.05.2005) GB

(71) Applicant (*for all designated States except US*): **NOKIA CORPORATION** [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **UUSIKARTANO, Joanna** [FI/FI]; Puistotie 3 B2, FIN-02760 Espoo (FI). **KÄLL, Jan** [FI/FI]; Jupperinmetsä 2 B, FIN-02730 Espoo (FI). **KUORELAHTI, Seppo** [FI/FI]; Kyntäjäsentie 1, FIN-00390 Helsinki (FI).


(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: A TERMINAL, AN EMERGENCY CENTRE, A NETWORK; A NETWORK ELEMENT, A SYSTEM AND A METHOD FOR ESTABLISHING AN EMERGENCY SESSION USING A TERMINAL IDENTITY



(57) Abstract: A terminal for use with a wireless local area network, . said terminal' being arranged to use at least part of at least one of the' following pieces information as an identity: a MAC Medium Access Control address of an AP access point to which said terminal is connected to, in use; a MAC address of said terminal; a signal line identifier of a fixed line that said terminal is connected to in use either directly or via a WLAN access point AP; and a switch or router port number of a fixed line that said terminal is connected to, in use, either directly or via a WLAN access point AP.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

A TERMINAL, AN EMERGENCY CENTRE, A NETWORK; A NETWORK ELEMENT, A SYSTEM AND A METHOD FOR ESTABLISHING AN EMERGENCY SESSION USING A TERMINAL IDENTITY

Field of the Invention:

The invention relates to a terminal.

Description of the Related Art:

- 5 A communication system can be seen as a facility that enables communication sessions between two or more entities such as user equipment and/or other nodes associated with the communication system. The communication may comprise, for example, communication of voice, data, multimedia and so on.
- 10 A session may, for example, be a telephone call between users or multi-way conference session, or a communication session between user equipment and an application server (AS), for example a service provider server. The establishment of these sessions generally enables a user to be provided with
- 15 various services.

A communication system typically operates in accordance with a given standard or specification which sets out what the various entities associated with the communication system are

20 permitted to do and how that should be achieved. For example, the standard or specification may define if the user, or more precisely, user equipment is provided with a circuit switched service and/or a packet switched service. Communication protocols and/or parameters which shall be used for the

25 connection may also be defined. In other words, a specific set of "rules" on which the communication can be based on needs to be defined to enable communication by means of the system.

Communication systems providing wireless communication for user equipment are known. An example of the wireless systems is the public land mobile network (PLMN) and another example is the wireless local area network (WLAN). Fixed broadband
5 access is another type of access.

The term "service" used above and hereinafter will be understood to broadly cover any service or goods which a user may desire, require or be provided with. The term also will
10 be understood to cover the provision of complimentary services. In particular, but not exclusively, the term "service" will be understood to include Internet protocol multimedia IM services, conferencing, telephony, gaming, rich

15 An example of the services that may be offered for users such as the subscribers to a communication system are the so called multimedia services. Some of the communication systems enabled to offer multimedia services are known as Internet Protocol (IP) Multimedia networks. IP Multimedia (IM)
20 functionalities can be provided by means of an IP Multimedia Core Network (CN) subsystem, or briefly IP Multimedia subsystem (IMS). The IMS includes various network entities for the provision of the multimedia services. The IMS services are intended to offer, among other services, IP
25 connections between mobile user equipment.

IP Multimedia connections in IMS will be used more and more for voice calls in the future. To be able to provide full voice services, IMS also has to fulfil regulatory
30 requirements, and thus it needs to be possible to make IMS emergency sessions. IMS emergency sessions in turn have a requirement that emergency calls must be allowed to proceed even without a UICC (universal integrated circuit card) or a

(U)SIM (Universal Subscriber Identity Module) card or if the UICC is blocked from usage (due to unpaid bills or the like).

When there is no UICC in the terminal, there is no IMSI (International Mobile Subscriber Identity) available, but there is still a need to identify the terminal in the network. In the IMS emergency technical specification currently proposed TR [23.867v0.9.0], at least part of the IMEI International Mobile station Equipment Identity is used.

However, IMS emergency sessions also have to be made over other IP-CAN (IP-Connectivity Access Network) than GPRS. For WLAN (wireless local area network) and NGN (next generation network) access, no identity has been standardised in case there is no UICC available. For WLAN and NGN, there may not be any IMEI for the terminal that can be used as in the GPRS access case.

Embodiments of the present invention aim to address this.

SUMMARY OF THE INVENTION:

Various aspects of the present invention can be seen from the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS:

For better understanding of the invention, reference will now be made by way of example to the accompanying drawings in which:

Figure 1 shows a communication system wherein the invention may be embodied;

Figure 2 shows a signal flow in embodiments of the invention;
and

Figure 3 shows scenarios in which embodiments of the
invention may be used.

5

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS:

Embodiments of the present invention relate particularly but
not exclusively to IMS networks. Embodiments of the invention
10 may be applicable to other networks.

Reference is made to Figure 1 which shows an IP Multimedia
Network 45 for offering IP multimedia services for IP
Multimedia Network subscribers. IP Multimedia (IM)
15 functionalities can be provided by means of a Core Network
(CN) subsystem including various entities for the provision
of the service.

Base stations 31 and 43 are arranged to transmit signals to
20 and receive signals from mobile user equipment 30 and 44 of
mobile users i.e. subscribers via a wireless interface.
Correspondingly, each of the mobile user equipment is able to
transmit signals to and receive signals from the base station
via the wireless interface. In the simplified presentation of
25 Figure 1, the base stations 31 and 43 belong to different
radio access networks (RAN). In the shown arrangement each of
the user equipment 30, 44 may access the IMS network 45 via
the two access networks associated with base stations 31 and
43, respectively. It shall be appreciated that, although, for
30 clarity, Figure 1 shows the base stations of only two radio
access networks, a typical mobile communication network
usually includes a number of radio access networks.

The 3G radio access network (RAN) is typically controlled by appropriate radio network controller (RNC). This controller is not shown in order to enhance clarity. A controller may be assigned for each base station or a controller can control a plurality of base stations. Solutions wherein controllers are provided both in individual base stations and in the radio access network level for controlling a plurality of base stations are also known. It shall thus be appreciated that the name, location and number of the network controllers depends on the system.

The mobile user may use any appropriate mobile device adapted for Internet Protocol (IP) communication to connect the network. For example, the mobile user may access the cellular network by means of a Personal computer (PC), Personal Data Assistant (PDA), mobile station (MS) and so on. The following examples are described in the context of mobile stations.

One skilled in the art is familiar with the features and operation of a typical mobile station. Thus, a detailed explanation of these features is not necessary. It is sufficient to note that the user may use a mobile station for tasks such as for making and receiving phone calls, for receiving and sending data from and to the network and for experiencing e.g. multimedia content. A mobile station is typically provided with processor and memory means for accomplishing these tasks. A mobile station may include antenna means for wirelessly receiving and transmitting signals from and to base stations of the mobile communication network. A mobile station may also be provided with a display for displaying images and other graphical information for the user of the mobile user equipment. Speaker means may also be provided. The operation of a mobile station may be

controlled by means of an appropriate user interface such as control buttons, voice commands and so on.

It shall be appreciated that although only two mobile
5 stations are shown in Figure 1 for clarity, a number of mobile stations may be in simultaneous communication

The core network (CN) entities typically include various control entities and gateways for enabling the communication
10 via a number of radio access networks and also for interfacing a single communication system with one or more communication system such as with other cellular systems and/or fixed line communication systems. In Figure 1 serving GPRS support nodes 33, 42 and gateway GPRS support nodes 34,
15 40 are for provision of support for GPRS services 32, 41, respectively, in the network.

The radio access network controller is typically connected to an appropriate core network entity or entities such as, but not limited to, the serving general packet radio service support nodes (SGSN) 33 and 42. Although not shown, each SGSN typically has access to designated subscriber database configured for storing information associated with the subscription of the respective user equipment.

User equipment within the radio access network may communicate with a radio network controller. The radio access
20 network controller is in communication with the serving GPRS support node via an appropriate interface, for example on an Iu interface.

The serving GPRS support node, in turn, typically
25 communicates with a gateway GPRS support node via the GPRS

backbone network 32, 41. This interface is commonly a switched packet data interface. The serving GPRS support node and/or the gateway GPRS support node are for provision of support for GPRS services in the network.

5

The user equipment 30, 44 may connect, via the GPRS network, to application servers that are generally connected to the IMS.

10 The communication systems have developed such that services may be provided for the user equipment by means of various functions of the network that are handled by network entities known as servers. For example, in the current third generation (3G) wireless multimedia network architectures it
15 is assumed that several different servers are used for handling different functions. These include functions such as the call session control functions (CSCFs). The call session control functions may be divided into various categories such as a proxy call session control function (P-CSCF) 35 and 39,
20 interrogating call session control function (I-CSCF) 37, and serving call session control function (S-CSCF) 36 and 38. A user who wishes to use services provided by an application server via the IMS system may need to register with a serving control entity. The serving call session control function (S-
25 CSCF) may form in the 3G IMS arrangements the entity a user needs to be registered with in order to be able to request for a service from the communication system. The CSCFs may define an IMS network of a UMTS system.

30 It shall be appreciated that similar function may be referred to in different systems with different names. For example, in certain applications the CSCFs may be referenced to as the call state control functions.

It should be appreciated that while embodiments of the invention have been described in relation to user equipment such as mobile stations, embodiments of the invention are applicable to any other suitable type of user equipment. In this document the term, terminal is intended to cover all the examples of user equipment described.

Also shown in Figure 1 is a WLAN system 50. A WLAN terminal 52 is connected to a WLAN system 54 and in particular to an access point thereof. A gateway 56 is provided for connection to an external network, for example network 45. The gateway 56 may be connected to a GGSN 58 of the network 58 which will be connected to various elements as already discussed but which are omitted from the figure for clarity. The connection between the gateways 56 and 58 may be via the Internet or the like.

One possible embodiment of this invention has a WLAN terminal or a fixed broadband terminal that is used for establishing an emergency session, even though the terminal does not carry a valid user identity module, e.g. the UICC card with USIM functionality described in 3GPP or when the identity module is blocked from usage by the operator for some reason. This technique may be, where applicable, be used with GPRS terminals. A system in which various embodiments of the invention can be implemented is shown schematically in Figure 3. In this system, IMS services can be offered to terminals which are connected to a data network using WLAN access or fixed broadband access.

A first terminal 200 is a WLAN terminal and is connected to a WLAN 202 and in particular to an access point 204 thereof.

The WLAN is connected to a network 206, for example an IMS network which is in turn connected to the PSAP (public service attachment point).

5 A second terminal 210 can be connected to a fixed line 214, which may be provided as part of broadband access. The second terminal can be a WLAN terminal or a fixed broadband terminal. The connection to the fixed line may be via an access point 212 or directly. The access point may be part of
10 a WLAN. The fixed line 214 may be connected to network 206.

A third terminal 216 may be connected via an access point 218 or directly to a switch or router 220. The router may be connected to network 206.

15

It should be appreciated that the arrangement shown in Figure 3 is schematic and in practice various additional elements may be provided between the different elements shown. Different ones of the terminals may be connected to different
20 networks instead of the single network 206 shown in Figure 3. More than one network may be connected to the same PSAP. More than one PSAP may be connected to the same network.

According to an embodiment of the invention the terminal
25 shall create the temporary identifier to be used in the emergency session based on at least one of the following information elements:

- The MAC Medium Access Control address of the AP access point the terminal is connected to
- 30 - The MAC address of the terminal itself
- The xDSL digital signal line identifier of the fixed line that the terminal is connected to either directly or via a WLAN AP.

- The switch or router port number of the fixed line that the terminal is connected to either directly or via a WLAN AP.
- An identifier constructed by combining any one or more of the above information elements, the whole information element or only some part of the information element in question

Reference is made to Figure 2 which shows how embodiments of the invention may be implemented. The terminal 100 shall include this temporary identity in the SIP INVITE sent to the IMS network 102 in step S1.

The IMS network 102 in step S2 shall use this identifier when forwarding the emergency session to the appropriate emergency centre or Public Service Attachment Point (PSAP) 104.

In steps S3 and S4, the PSAP/emergency centre 104 may use this temporary identity in case the original emergency session is disconnected for some reason in order to initiate a new emergency session, in other words to re-establish the emergency session with the same terminal. In particular, the PSAP sends a message to the IMS network including the temporary identity. Based on this temporary identity, the IMS network is able to establish a connection in step S4 with the terminal.

The PSAP/emergency centre may also use the temporary identifier to request further information about the terminal from IMS (and from the access network), for example in step S5. Such information may be for example about the current location of the terminal or historical data the IMS may store regarding this terminal e.g. regarding routing history or

lost connections history. This information may be returned by the IMS network to the PSAP in step S6.

It should be appreciated that steps S3 and S4 are only
5 required if a connection needs to be established by the PSAP
104 and accordingly these steps may be carried out at any
appropriate time and not just as shown in Figure 2.

Likewise, steps S5 and S6 may be carried out only if the PSAP
10 requires certain information. The timing of these steps may
be varied and may not just be as shown in Figure 2. It should
be appreciated that several requests may be sent by the PSAP
at varying times. The requested information may be returned
in one or more responses by the IMS. Likewise the PSAP may
15 send one request and receive one or more responses from the
IMS in response to that one request.

In some embodiments of the invention, the IMS may in response
to a request from the PSAP send a request to the terminal
20 itself or a different entity in order to obtain the required
information for responding to the PSAP.

When using lower layer routing identities to identify the
user that is making the call, it to some extent breaks the
25 layered model, as a lower layer identity is used as an
identifier or part of a terminal identifier on upper layers.
The advantage is that this type of information is typically
available in the terminal and it is possible for the terminal
to construct a temporary identity, which is very likely to be
30 globally unique, using these information elements.

In one embodiment of the invention, the terminal IP address may be used at least partially or in its entirety in combination or on its own.

- 5 It is also noted herein that while the above describes exemplifying embodiments of the invention, there are several variations and modifications which may be made to the disclosed solution without departing from the scope of the invention as defined in the appended claims.

CLAIMS

1. A terminal for use with a wireless local area network,
said terminal being arranged to use at least part of a MAC
5 medium access control address as a user identity.
2. A terminal as claimed in claim 1, wherein said address
is the MAC address of at least one of the terminal and an
access point to which the terminal is connected in use.
- 10 3. A terminal for use with a wireless local area network,
said terminal being arranged to use at least part of
information identifying a fixed line to which said terminal
is coupled in use.
- 15 4. A terminal as claimed in claim 3, wherein said
information is least one of:
an DSL line identifier; a switch identifier; a router
identifier; a switch port; and a router port.
- 20 5. A terminal as claimed in claim 3 or 4, wherein said
terminal is arranged to be connected directly to said fixed
line.
- 25 6. A terminal as claimed in claim 3 or 4, wherein said
terminal is arranged to be connected to said fixed line via
an access point.
- 30 7. A terminal as claimed in claim 6, wherein said access
point comprises a WLAN access point.

8. A terminal for use with a wireless local area network, said terminal being arranged to use at least part of at least one of the following pieces information as an identity:

5 a MAC Medium Access Control address of an AP access point to which said terminal is connected to, in use;

a MAC address of said terminal;

a signal line identifier of a fixed line that said terminal is connected to in use either directly or via a WLAN access point AP; and

10 a switch or router port number of a fixed line that said terminal is connected to, in use, either directly or via a WLAN access point AP.

15 9. A terminal as claimed in any preceding claim, wherein said terminal is one of a GPRS terminal, a WLAN terminal and a fixed broadband terminal.

20 10. A terminal as claimed in claim 8 or 9, wherein said terminal is arranged to obtain said at least part of at least one of said pieces of information from one of an access point, a fixed line, a switch or a router and to use said information to determine said identity.

25 11. A system comprising a terminal as claimed in any preceding claim and a network to which said terminal is attachable.

30 12. A system as claimed in claim 11, comprising an access point to which said terminal is attachable, said access point being connectable to said network.

13. A system as claimed in any of claims 11 and 12, comprising at least one of a router and a switch to which said terminal is attachable, said at least one router and switch being connectable to said network.

5

14. A system as claimed in any of claims 11 to 13, further comprising an emergency centre which is arranged to have an emergency session with said terminal.

10 15. An emergency centre arranged to establish a session with a terminal using an identity associated with said terminal, said identity comprising at least one of the following:

a MAC Medium Access Control address of an AP access point to which said terminal is connected to, in use;

15

a MAC address of said terminal;

a signal line identifier of a fixed line that said terminal is connected to in use either directly or via a WLAN access point AP; and

20

a switch or router port number of a fixed line that said terminal is connected to, in use, either directly or via a WLAN access point AP.

16. An emergency centre arranged to request information from a terminal with which an emergency session is established, using an identity associated with said terminal, said identity comprising at least one of the following:

a MAC Medium Access Control address of an AP access point to which said terminal is connected to, in use;

a MAC address of said terminal;

30

a signal line identifier of a fixed line that said terminal is connected to in use either directly or via a WLAN access point AP; and

a switch or router port number of a fixed line that said terminal is connected to, in use, either directly or via a WLAN access point AP.

5 18. An emergency centre as claimed in claim 17, wherein said information comprises at least one of the current location of the terminal, routing history and lost connections history.

10 19. A network arranged to receive identity information associated with a terminal and to forward said information to an entity with which a session is to be established, said information comprising at least one of the following:

a MAC Medium Access Control address of an AP access point to which said terminal is connected to, in use;

15 a MAC address of said terminal;

a signal line identifier of a fixed line that said terminal is connected to in use either directly or via a WLAN access point AP; and

20 a switch or router port number of a fixed line that said terminal is connected to, in use, either directly or via a WLAN access point AP.

25 20. A network as claimed in claim 19, wherein said network is an IMS network.

21. A network as claimed in claim 19 or 20, wherein said entity is one of an emergency centre and a PSAP.

30 22. A network as claimed in any of claims 19 to 21, wherein said network is arranged to store information in association with said identity.

23. A network as claimed in claim 22, wherein said information comprises at least one of connection history, dropped connections history and location information.

5 24. A network element arranged to receive identity information associated with a terminal and to forward said information to a network with which an session is to be established, said information comprising at least one of the following:

10 a MAC Medium Access Control address of an AP access point to which said terminal is connected to, in use;

a MAC address of said terminal;

a signal line identifier of a fixed line that said terminal is connected to in use either directly or via a

15 WLAN access point AP; and

a switch or router port number of a fixed line that said terminal is connected to, in use, either directly or via a WLAN access point AP.

20 25. A network element as claimed in claim 24, wherein said network element comprises at least one of an access point, a switch, a router, and a fixed line.

25 26. A network element as claimed in claim 24 or 25, wherein said network element is arranged to provided at least part of said information used by said terminal to provide said identity information.

30 27. A method of establishing an emergency session comprising the steps of:
defining identity information associated with a terminal, said information comprising at least one of the following:

- a MAC Medium Access Control address of an AP access point to which said terminal is connected to, in use;
a MAC address of said terminal;
a signal line identifier of a fixed line that said
5 terminal is connected to in use either directly or via a WLAN access point AP; and
a switch or router port number of a fixed line that said terminal is connected to, in use, either directly or via a WLAN access point AP,
10 and forwarding said information to an entity with which an session is to be established





Fig. 1

FIGURE 2






FIGURE 3

INTERNATIONAL SEARCH REPORT

International application No
PCT/IB2006/001236

A. CLASSIFICATION OF SUBJECT MATTER
INV. H04L12/56 H04L12/28 H04L29/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2005/063519 A1 (JAMES ANTHONY W) 24 March 2005 (2005-03-24)	1-5, 8, 9, 11-16, 18, 19, 21-25, 27
Y	abstract paragraph [0010] - paragraph [0014] paragraph [0025] - paragraph [0039] paragraph [0043] - paragraph [0056] paragraph [0065] - paragraph [0079] ----- -/-	6, 7, 10, 20, 26

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

18 July 2006

Date of mailing of the international search report

25/07/2006

Name and mailing address of the ISA/
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Biyee, N

INTERNATIONAL SEARCH REPORT

International application No

PCT/IB2006/001236

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y X	WO 02/09458 A (BLUESOCKET, INC) 31 January 2002 (2002-01-31) page 6, line 25 - page 8, line 16 page 9, line 1 - line 15 page 10, line 1 - page 11, line 23 page 14, line 6 - page 16, line 31 page 18, line 3 - page 19, line 18 page 1, line 23 - page 3, line 7 -----	6,7,10, 20,26 1,2,8,9, 11-13, 19, 22-25,27
X	US 2004/203593 A1 (WHELAN ROBERT ET AL) 14 October 2004 (2004-10-14) paragraph [0047] - paragraph [0056] paragraph [0091] - paragraph [0095] -----	1,2, 8-13,19, 22,24, 25,27
X	FR 2 844 413 A (ALCATEL) 12 March 2004 (2004-03-12) page 1, line 8 - page 2, line 25 page 5, line 16 - line 32 page 8, line 11 - page 9, line 24 -----	1,2,8,9, 11-13, 19,22, 24,25,27
A	US 2002/105931 A1 (HEINONEN TOMI ET AL) 8 August 2002 (2002-08-08) paragraph [0004] - paragraph [0018] paragraph [0047] - paragraph [0048] paragraph [0056] - paragraph [0063] paragraph [0066] - paragraph [0082] -----	1-13,19, 22-27
X,P	US 2005/181805 A1 (GALLAGHER MICHAEL D) 18 August 2005 (2005-08-18) abstract paragraph [0008] - paragraph [0010] paragraph [0030] - paragraph [0048] paragraph [0061] paragraph [0065] - paragraph [0071] paragraph [0102] - paragraph [0108] paragraph [0115] - paragraph [0126] -----	1,2, 8-16, 18-27

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/IB2006/001236

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2005063519	A1	24-03-2005	NONE	
WO 0209458	A	31-01-2002	NONE	
US 2004203593	A1	14-10-2004	US 2004198319 A1	07-10-2004
FR 2844413	A	12-03-2004	CN 1489341 A	14-04-2004
			EP 1398939 A1	17-03-2004
			JP 2004104784 A	02-04-2004
US 2002105931	A1	08-08-2002	AU 1239802 A	01-07-2002
			EP 1344367 A2	17-09-2003
			WO 0251093 A2	27-06-2002
			FI 20002822 A	22-06-2002
US 2005181805	A1	18-08-2005	NONE	