



US005753884A

# United States Patent [19]

[11] Patent Number: 5,753,884

Hilgenfeldt et al.

[45] Date of Patent: May 19, 1998

- [54] **AESTHETIC ORTHODONTIC BAND AND ATTACHMENT ASSEMBLY**
- [75] Inventors: **Thorsten G. Hilgenfeldt**, Montrose; **Allen B. Amundson**, Upland; **Nicholine M. Sandoval**, Monrovia; **Fantu W. Leka**, La Verne; **Robert C. Manemann**, Huntington Beach; **Casey A. Campbell**, Arcadia, all of Calif.
- [73] Assignee: **Minnesota Mining & Manufacturing Co.**, St. Paul, Minn.

3,896,286	7/1975	Minors	219/86
3,905,111	9/1975	Kesling	32/14 A
3,955,282	5/1976	McNall	32/14 C
3,985,282	10/1976	Miller et al.	228/175
4,083,113	4/1978	Miller et al.	32/14 A
4,249,060	2/1981	Colby	219/121 LD
4,256,455	3/1981	Förster	433/8
4,842,513	6/1989	Haarmann	433/9
5,064,368	11/1991	Lavin	433/2
5,123,845	6/1992	Vassiliadis et al.	433/215
5,154,606	10/1992	Wildman	433/8
5,161,969	11/1992	Pospisil et al.	433/8
5,232,364	8/1993	Rosen	433/173
5,338,191	8/1994	Hamula	433/23

- [21] Appl. No.: 631,857
- [22] Filed: Apr. 10, 1996

### Related U.S. Application Data

- [62] Division of Ser. No. 311,349, Sep. 23, 1994, Pat. No. 5,529,491.
- [51] Int. Cl.<sup>6</sup> A61C 7/18; B23K 11/11; B23K 11/36
- [52] U.S. Cl. 219/117.1; 219/86.24; 219/87; 219/91.2; 219/159; 433/23; 433/8
- [58] Field of Search 219/86.1, 86.23, 219/86.24, 86.25, 87, 91.2, 117.1, 158-161; 433/8, 23, 32

### References Cited

#### U.S. PATENT DOCUMENTS

2,062,395	12/1936	Brusse et al.	32/14
2,527,526	10/1950	Brusse	32/14
3,521,355	7/1970	Pearlman	433/8
3,657,817	4/1972	Kesling	32/14 A

### FOREIGN PATENT DOCUMENTS

0 218 589	of 0000	European Pat. Off.	
0 384 485	of 0000	European Pat. Off.	
256283	10/1988	Japan	219/117.1

Primary Examiner—Teresa J. Walberg  
 Assistant Examiner—J. Pelham  
 Attorney, Agent, or Firm—James D. Christoff

### [57] ABSTRACT

An orthodontic assembly that includes a band and an attachment has one or more spot welds to secure the band to the attachment. The spot welds are characterized by the lack of any outer surface weld deformation that is circular in shape, or that is visible to the naked eye when viewed at a distance of twenty-four inches. Apparatus for welding the attachment to the band includes a subframe that is swingable in an arc to follow the inner contour of the band in order to provide automated welding on mesial and distal sides of the attachment.

6 Claims, 5 Drawing Sheets





FIG. 1




FIG. 3





FIG. 2




FIG. 9




FIG. 8




FIG. 4




FIG. 5




FIG. 6



## AESTHETIC ORTHODONTIC BAND AND ATTACHMENT ASSEMBLY

This is a division of application Ser. No. 08/311,349 filed Sep. 23, 1994, Now U.S. Pat. No. 5,529,491.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

This invention relates to a welded orthodontic assembly, and particularly concerns an orthodontic band that is welded to a bracket, buccal tube or other orthodontic attachment.

#### 2. Description of the Related Art

Orthodontic treatment involves movement of the teeth to desired positions. During treatment, small slotted bodies known as brackets are typically affixed to anterior, cuspid and bicuspid teeth, and small devices known as buccal tubes are secured to molar teeth. An arch wire held in slots of the brackets and channels in the buccal tubes functions as a track to guide movement of the teeth to orthodontically correct positions. The teeth are often moved by bends or twists placed in the arch wire or by elastic members connected between the brackets or buccal tubes of certain teeth.

In past years, it was common practice to weld each buccal tube and bracket to a respective orthodontic band. The orthodontic bands were selected to match the contour and circumferential dimension of the tooth, so that a close, non-loosening fit between the band and the tooth could be obtained. In more recent years, however, adhesives have been developed that usually have sufficient strength to securely affix brackets directly to the tooth surfaces.

However, buccal tubes are often subjected to relatively large forces from occluding teeth as well as forces exerted by the arch wire. As such, it is still common practice to weld buccal tubes to an metallic orthodontic band so that a stable base for the buccal tube is provided. Welded bracket and band assemblies are also still used with anterior, cuspid and bicuspid teeth in instances where a relatively strong connection to the tooth is desired.

In addition to brackets and buccal tubes, other orthodontic devices or "attachments" may also be welded to bands. Examples of such other attachments include cleats, buttons, hooks, lingual sheaths and eyelets, and such attachments may be mounted on either the buccolabial side (i.e., facing the cheeks or lips) or the lingual side (i.e., facing the tongue) of the band.

Many types of attachments are provided with welding flanges that extend in mesial and distal directions. The flanges facilitate welding the attachment to the band by providing an additional surface for electrical and physical contact with electrodes of the welder.

Past welding processes for manufacturing orthodontic attachment and band assemblies have included an initial tack welding step wherein the attachment is received in a recess of a fixture. The fixture including the recess is electrically connected to one electrode of the welder and the other electrode is brought into contact with an inner surface of the band. After completion of tack welding to temporarily affix the attachment to the band, the assembly is removed from the tack welder and taken to a finish welder for final welding.

Finish welding is often carried out by placing one electrode of the finish welder in contact with an outer surface of the attachment flanges, while contacting the inner surface of the band adjacent the attachment to the other electrode of the finish welder. The finish weld process has often been carried out by hand. Commonly, the operator grips the tack welded

assembly and places the flanges of the attachment and the adjacent area of the band between the electrodes of a higher current, finish spot welder. Oftentimes, four spot welds are provided, two in each of the two flanges.

In the step of finish welding orthodontic attachments to bands, both electrodes typically have identical cylindrical shapes of relatively small diameter. As current flows between the electrodes during the welding process, a weld is obtained at the interface of the band and the attachment along a path that represents the path of least electrical resistance, which is typically the shortest path through the assembly between the ends of the two electrodes. The small diameter of the cylindrical electrodes enables the current to be directed toward a particular area where the weld is desired.

There is a continuing need in the art to improve the aesthetics of orthodontic assemblies. Unfortunately, conventional welded assemblies are often characterized by a relatively visible deformations on the surface of the welding flanges, which may detract from the smooth appearance of remaining external surfaces of the assembly. If the deformations are sufficiently large, the deformations may function as a site that retains small food particles or bacteria or function as a site that may initiate corrosion.

In the past, it has also been known to weld a band to a bracket without flanges. In the manufacture of such assemblies, a tack weld was utilized to initially fix the bracket to the band, and a finish weld was later applied such that the substantial majority of any weld deformations appeared on the inside of the band. However, such practice has not been extended to brackets having flanges, because such brackets are wider in a mesiodistal direction and the flanges provide better anchorage locations for the finish welds.

### SUMMARY OF THE INVENTION

The present invention is directed toward an orthodontic assembly that comprises a metallic band for encircling a tooth, wherein the band has an inner surface and an outer surface. The assembly also includes a metallic orthodontic attachment that is connected to the band, wherein the attachment has at least one welding flange with an outer surface. The assembly additionally includes at least one spot weld between each flange and the outer surface of the band, and the spot weld(s) interconnect the attachment and the band with a strength sufficient for orthodontic treatment. The outer surface of each welding flange is characterized by a lack of any welding deformation that is circular in shape.

In addition, the present invention is directed toward an orthodontic assembly that comprises a metallic band for encircling a tooth, wherein the band has an inner surface and an outer surface. The assembly also includes a metallic orthodontic attachment that is connected to the band, wherein the attachment has at least one welding flange with an outer surface. The assembly additionally includes at least one spot weld between each flange and the outer surface of the band, and the spot weld(s) interconnect the attachment and the band with a strength sufficient for orthodontic treatment. The outer surface of each welding flange is characterized by a lack of any welding deformation when viewed by the naked eye at a distance of 24 inches.

The present invention is also directed toward a method of welding an orthodontic attachment to a band. The method includes the steps of placing the attachment in a holder, and electrically connecting the attachment to one electrode of an electric resistance spot welder. The band is placed in a

fixture in a certain orientation such that an outer surface of the band is directly adjacent an inner surface of the attachment. An electrode is placed in contact with an inner surface of the band, and a current is directed in a first instance along a path extending between the electrodes and through the band and the attachment to provide a first spot weld. The electrode and the band are relatively moved in an arc while retaining the band in the certain orientation relative to the attachment. A current is directed in a second instance along a path extending between the electrodes and through the band and the attachment after the aforementioned step of relatively moving the electrode and the band in order to provide a second spot weld that is spaced from the first spot weld in an arc along the inner surface of the band.

The invention in its various embodiments is advantageous, in that the welded assembly is aesthetic when viewed toward its external surfaces. The deformations are difficult to see and not pronounced as is common with conventional welded assemblies. The lack of sharp deformation edges provides comfort to the patient. Moreover, the step of tack welding the attachment to the band as was common in prior art practice may be avoided, so that alignment of the attachment to the band and finish welding of the assembly may occur in a one-step operation.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side elevational view looking toward an outer, or buccolabial, surface of an exemplary orthodontic assembly constructed in accordance with the invention;

FIG. 2 is a plan view of the assembly illustrated in FIG. 1;

FIG. 3 is an end elevational view looking toward a mesial side of the assembly illustrated in FIGS. 1 and 2;

FIG. 4 is a reduced front elevational view of an automated apparatus for manufacture of the assembly shown in FIGS. 1-3;

FIG. 5 is a reduced side elevational view of the apparatus depicted in FIG. 4;

FIG. 6 is an enlarged plan view of the apparatus illustrated in FIGS. 4 and 5;

FIG. 7 is an enlarged view of a portion of the apparatus depicted in FIG. 6;

FIG. 8 is an enlarged front elevational view of a lower electrode assembly of the apparatus shown in FIGS. 4-7; and

FIG. 9 is a plan view of the lower electrode assembly illustrated in FIG. 8, but shown with two electrode sections of the assembly in an orientation somewhat closer to each other.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIGS. 1 and 3 illustrate for exemplary purposes an orthodontic assembly 20 constructed in accordance with the principles of the present invention. The assembly includes a metallic band 22 for encircling a tooth. The band 22 has a diameter and contour to closely match the diameter and contour of the selected tooth. The band 22 has an inner surface 24 facing the encircled tooth and an outer surface 26 facing away from the tooth.

The assembly 20 also includes a metallic orthodontic attachment 28 that, in the example shown in the drawings, is a single passage buccal tube particularly adapted for use with the first molar teeth. The buccal tube attachment 28

includes a base 30 and a pair of welding flanges 32 that extend away from the base 30 in opposite, mesial and distal directions. Each welding flange 32 has an outer or buccolabial surface facing away from the tooth, and an inner or lingual surface that is in contact with the outer surface 26 of the band 22.

The attachment 28 further includes a body 34 surrounding the passage, and also a hook 36. The base 30, the welding flanges 32, the body 34 and the hook 36 are integral and made for example of stainless steel by a metal injection molding process, by a casting process or by a machining process. The passage has a shape adapted to receive an end of an orthodontic arch wire.

The buccal tube attachment 28 shown in FIGS. 1-3 is only one example of a variety of attachments that may be utilized with the assembly of the present invention. Other examples of orthodontic attachments include brackets, cleats, buttons, hooks, eyelets and other devices as may be deemed desirable by the practitioner. Bands for other teeth (such as anterior, cuspid or bicuspid teeth) may also be used in place of the molar band shown in the drawings.

The assembly 20 also includes at least one spot weld interconnecting the attachment 28 to the band 22. In FIG. 1, the numeral 38 illustrates the location of four spot welds that are provided to securely interconnect the welding flanges 32 to the band 22. Each spot weld is located in an area between the inner surfaces of the welding flanges 32 and the outer surface 26 of the band 22, and the welds together join the attachment and the band 22 with a strength sufficient for orthodontic treatment so that the attachment 28 normally does not detach from the band 22 as treatment progresses.

The location of spot welds are often highly visible in conventional welded orthodontic assemblies because of deformation of the metal due to localized high temperatures that are present in the vicinity of the joint as it is welded. The deformations typically result in areas where the electrodes contact the metallic parts, and may be enhanced due to localized arcing that occurred during welding in regions where portions of the electrodes are slightly spaced from adjacent portions of the metal parts. The spot weld itself is typically not visible, as it is located between the parts.

In accordance with the present invention, the outer, exposed surfaces of the welding flanges 32 have only small, if any, deformations, and such deformations are difficult to see under ordinary viewing conditions. The volume of the weld deformation adjacent each spot weld location 38 is greater on the inner surface 24 of the band 22 than the volume of any deformations on the outer surfaces of the welding flanges 32 adjacent the same spot weld location 38.

The volume of the deformations is measured using microprobes that are guided across surfaces adjacent the spot weld locations 38. The microprobes follow the contour of the surfaces, and provide an indication of the volume of the deformation relative to an average height of surfaces surrounding the deformation. Preferably, the microprobes are connected to a programmable X-Y axis robotic arm that is programmed to move the microprobe across the entire area of the deformation as well as adjacent surfaces so that a volume measurement of the deformation can be accurately obtained.

Preferably, no weld deformations are visible on the outer surfaces of the welding flanges when the attachment is viewed at a distance of 24 inches (70 cm) from the naked eye under normal room lighting. More preferably, no deformations are visible on the outer surfaces of the welding flanges when the attachment is viewed at a distance of 12 (30.5 cm) inches from the naked eye under normal room lighting.

An automated welding apparatus **40** for welding the assembly **20** is illustrated in FIGS. 4-9. The apparatus **40** includes a frame **42**, an upright hollow housing **44** and a weld head **46** ("Thin-line" brand weld head, from Unitek Equipment). An electrode holder **48** is clamped to a vertically movable shaft of the weld head **46** and has a lower split, depending arm that releasably receives an L-shaped upper electrode **50**.

The electrode holder **48** is connected by a conductive strap (not shown) to one terminal of a power supply **52** ("Dual Pulse 125" stored energy resistance welding power supply; from Unitek Equipment). The power supply **52** is shown schematically in FIG. 6. The weld head **46** includes an adjustable pressure sensor electrically connected to the power supply **52** for initiating the flow of current to the upper electrode **50**. When the shaft of the weld head **46** descends to a degree sufficient to contact the parts to be welded with sufficient force to exceed a selected, preset pressure, the pressure sensor triggers the power supply to direct one or more pulses of current to the upper electrode **50** to provide a spot weld.

A carriage **54** of the apparatus **40** has two pair of bearing blocks **56** (FIGS. 4 and 5), each pair of which slides on a respective rail **58** that is fixed to the frame **42**. A double acting pneumatic piston and cylinder assembly **60** (FIG. 5) is connected to the carriage **54** and the frame **42**, and is operable to slide the carriage **54** in a horizontal, front-to-back or "Y" axis direction relative to the frame **42** when desired to either a front or back position.

Solenoid operated air valves (not shown) are interposed in tubing leading to the cylinder of the piston and cylinder assembly **60**, and the air valves are electrically connected to a programmable logic controller **62** (series no. SLC-500; Allen Bradley). The controller **62** is shown schematically in FIG. 6 and is electrically connected to the power supply **52**. Front and back adjustable micrometer stops **64** (FIG. 5) are connected to the frame **42** for limiting the front and back extent of the path of travel of the carriage **54** relative to the frame **42**.

A subframe **66** is carried by upstanding front and rear arms of the carriage **54**. As illustrated in FIG. 4, the front arm of the carriage **54** includes a curved track **68** that has a shape of a partial circle. A pair of rollers **70** that are connected to the subframe **66** travel along a curved path guided by the track **68**. An eccentric adjustment **72** (see FIG. 5) interconnects the rollers **70** and the subframe **66** to enable adjustment as may be needed to ensure that each roller **70** bears upon the track **68** with equal pressure.

The rear upstanding arm of the carriage **54** carries a bearing block that receives a shaft **74**. The shaft **74** is connected by intermeshed gears (not shown) to a stepmotor **76** (model S83-62-MO microstepping motor/drive system; Compumotor Division, Parker Hannifin Corp.). Activation of the stepmotor **76** by a microstepping drive **77** (FIG. 6) connected to the controller **62** enables the subframe **66** to swing relative to the carriage **54** in a partial arc about a horizontal axis. When the carriage **54** is moved forwardly or rearwardly by the piston and cylinder assembly **60**, the downstream gear of the intermeshed gears moves forwardly relative to the upstream gear but remains intermeshed with the latter so that the stepmotor **76** is operable to swing the subframe **66** regardless of whether the carriage **54** is in its rearward or forward position.

The stepmotor **76** is shown in FIGS. 5 and 6 and is connected to an encoder **78** (model no. E151000C865; from Dynapar). The encoder **78** is electrically connected to the

microstepping drive **77**. The encoder **78** provides confirmation of the rotative position of the shaft of the stepmotor **76** and hence of the subframe **66**. A photosensor **80** (FIG. 5) is also connected to the microstepping drive **77** and senses the arrival of a projecting member connected to the subframe **66**, in order to enable the microstepping drive **77** to determine a "home" position during start-up of the apparatus **40**.

As illustrated in FIG. 6, a pair of additional photosensors **82** are provided and are electrically connected to the microstepping drive **77**. The photosensors **82** enable the microstepping drive **77** to limit the rocking path of travel of the subframe **66** by sensing the arrival of the same projecting member sensed by the photosensor **80** to determine the home position.

A lower mounting plate **84** is fixed to the subframe **66**. An upper surface of the lower mounting plate **84** carries a linear bearing assembly **86** that, in turn, is connected to an upper mounting plate **88**. A micrometer adjustment mechanism **90**, as shown in FIGS. 6-7, is supported by the subframe **66** and is used to adjust the upper mounting plate **88** for selective, horizontal, front-to-back movement of the upper mounting plate **88** relative to the lower mounting plate **84** when desired.

An angulation plate **92** (not shown in FIG. 7) rests atop the upper mounting plate **88**, and is rigidly connected to a pair of threaded vertical rods **94** (FIG. 7) that pass through respective arcuate slots **96** of the upper mounting plate **88**. A nut **98** is threaded onto each rod **94**, and is connected to a lever (not shown).

The nuts **98** are located beneath the upper mounting plate **88**. After the levers are turned to loosen the nuts **98**, the angulation plate **92** may be pivoted about a vertical axis relative to the upper mounting plate **88**. As shown in FIG. 6, one end of the angulation plate **92** has a notch that is located above a set of indicia marks **100**, so that the user can determine the rotative position of the angulation plate **92** relative to the upper mounting plate **88** before tightening the nuts **98** to fix the position of the plate **92**.

The angulation plate **92** is shown in the drawings for exemplary purposes as aligned in parallel fashion, or "0" angulation, relative to the upper mounting plate **88**. Advantageously, the angulation plate **92** enables the operator to easily adjust the angle, or "angulation", of the attachment relative to the central axis of the band as may be prescribed by the orthodontist.

A band holding fixture comprises a pair of band clamping mechanisms **102**, **104** that are movably connected to the angulation plate **92** by metal slides. A band diameter adjustment knob **106** is connected to a threaded rod that passes through a threaded wall of the band clamping mechanism **102**. The threaded rod also bears against a wall of the band clamping mechanism **104**. Rotation of the knob **106** about a horizontal axis moves the band clamping mechanism **102** in a horizontal direction, either away or toward the band clamping mechanism **104**. Spring pressure is applied to the assembly **102** to keep the end of the rod in contact with the mechanism **104**.

A micrometer band position adjustment knob **108** is mounted on the angulation plate **92**, and is coupled to the band clamping mechanism **104**. Adjustment of the knob **108** simultaneously moves both of the band clamping mechanisms **102**, **104** in a horizontal direction either away or toward the knob **108** relative to the angulation plate **92**.

Each of the band clamping mechanisms **102**, **104** includes a stationary stop **110** having a shoulder. The shoulders of the stops **110** receive opposite sides of a band, such as the band **22**.

Each band clamping mechanism 102, 104 includes a clamping arm 112 that is movable in an arc about a pivot 114. For illustrative purposes, the clamping arm 112 of the band clamping mechanism 102 is shown in FIG. 7 in an open position to receive a band, while the clamping arm 112 of the band clamping mechanism 104 is shown in a closed position to clamp a band between a horizontal cylindrical pin 115 of the arm 112 and the shoulder of the stop 110. In practice, however, the clamping arms 112 of both mechanisms 102, 104 open and close simultaneously.

A single acting pneumatic piston and cylinder assembly 116 is mounted on each band clamping mechanism 102, 104 and has a piston rod that, when extended, moves the clamping arm 112 from an open position to a closed position. Each piston and cylinder assembly 116 is connected to a source of pressurized air by tubing, and a solenoid operated air valve interposed in the tubing is connected to a foot pedal switch for opening the clamping arms 112 when desired.

A horizontally extending shaft 118 extends forwardly from each clamping arm 112 and through a slot in the front of a housing for each band clamping mechanism 102, 104. A coiled compression spring 120 surrounds each shaft 118, and urges the respective clamping arm 112 toward an open position.

A lower electrode assembly 122 is illustrated in FIGS. 5, 8 and 9, and includes two movable, clamping electrode sections 124 that are each mounted on a linear bearing assembly 126 connected to the subframe 66. A conductive strap (not shown) electrically connects the assembly 122 to the power supply 52. A cylinder of a double acting pneumatic piston and cylinder assembly 128 is fixed to one electrode section 124, and a piston rod of the assembly 128 is coupled to the other electrode section 124.

The piston and cylinder assembly 128 moves the lower electrode sections 124 either toward or away from each other as desired. As shown in FIG. 9, a rack and gear mechanism 129 interconnects the electrode sections 124 to assure that both sections 124 move equal distances simultaneously in a horizontal, x-axis direction. The piston and cylinder assembly 128 is connected by tubing to a source of pressurized air, and solenoid operated air valves interposed in the tubing are connected to a second foot pedal switch.

A micrometer stop gauge 130 (FIG. 9) is mounted on the subframe 66 for limiting movement of the electrode sections 124 away from each other by the piston and cylinder assembly 128. A micrometer stop gauge 132 is also mounted on the subframe 66 to limit the distance between the electrode sections 124 when the latter are moved toward each other by the piston and cylinder assembly 128.

Each electrode section 124 includes a horizontal leg 134 and a vertical leg 136 removably received in a channel of the horizontal leg 134. Each vertical leg 136 includes a recess (not shown) at its upper end to receive either the mesial portion or the distal portion of the attachment to be welded to the band. The vertical legs 136 of the electrode sections 124 function as a holder for releasably receiving the attachment. When the electrode sections 124 are moved toward each other, the micrometer stop gauge 132 insures that undue pressure is not exerted on the attachment to deform the latter or cause the latter to snap out of the recesses of the vertical electrode section legs.

Optionally, both of the vertical legs 136 may be removed and replaced with a single vertical member having spaced apart legs for reception in the channels of the horizontal electrode section legs. Such single members are sometimes preferred for use with certain attachments such as buttons, when a movable, clamping-type lower electrode assembly is not desired.

Finally, an air nozzle 138 (FIGS. 5 and 7; not shown in FIG. 6) is connected to the frame 42, and is coupled by tubing to a source of pressurized air. A solenoid air valve is interposed in the tubing leading to the air nozzle 138 and is also electrically connected to the controller 62 for initiating a blast of air toward the welding site directly adjacent the upper electrode 50. The blast of air is sufficient to blow away slag or other debris away from the welding site.

In use, the operator depresses the foot switch (not shown) connected to the cylinder assembly 128 to extend the latter in a direction such that the lower electrode sections 124 are moved away from each other to allow the attachment to be placed onto the electrode legs 136. Next, an orthodontic attachment such as the buccal tube attachment 28 is placed in the recesses of the lower electrode section legs 136 in an orientation wherein the outer, or buccolabial surfaces of the attachment are facing downwardly and in contact with upwardly facing surfaces of the electrode section legs 136. Preferably, the recesses of the electrode section legs 136 are complementary in configuration to the adjacent surfaces of the attachment, so that mating contact between the attachment and the electrode section legs 136 is achieved.

When the foot switch is released, the cylinder 128 retracts and applies pressure through the electrode legs 136 to clamp the attachment. Next, the operator depresses the second foot switch which causes air to be released from cylinders 116 in order to open the arms 112. An orthodontic band such as band 22 is placed in the space between the shoulders of the stops 110 and the pins 115 connected to the arms 112. The operator then releases the second foot switch which causes air to be directed to the piston and cylinder assemblies 116 in order to extend their respective piston rods. As the piston rods extend, the arms 112 simultaneously swing about pivots 114 to cause the band to be clamped between the pins 115 and the stops 110.

The controller 62 and the microstepping drive 77 then begin a program sequence to provide spot welds for the assembly 20 in automated fashion. As one example, the stepmotor 76 may first be actuated to swing the subframe 66 in an arc to a position wherein a mesial flange of the attachment is directly between the upper electrode 50 and the lower electrode assembly legs 136. The controller 62 then activates the welding power supply 52 which directs current between the upper electrode 50 and the lower electrode assembly 122 and resistance weld the inner or lingual surface of the mesial flange of the attachment to the outer or buccolabial surface of the band.

The current may be supplied in each weld position in one or more pulses. Preferably, a first pulse of current at relatively low power is provided to help break surface oxides and prepare the surfaces for welding. A second pulse immediately follows at greater power to provide a strong finish weld.

In practice, the current flows in a direction from the upper electrode 50 to the lower electrode assembly 122, although reverse current flow is also possible. Importantly, the lower electrode assembly 122 has a larger area of surface in contact with the attachment than the area of contact between the upper electrode 50 and the inner surface of the band. As a consequence, a larger deformation, if any, of the metallic surfaces will occur on the inside of the band rather than on the outer surface of the attachment where such deformation would be more visible.

Next, the controller 62 actuates the solenoid valves connected to the piston and cylinder assembly 60 so that the piston rod of the latter retracts and moves the carriage 54

rearwardly relative to the frame 42 until the rear end of the piston rod is in contact with the rear stop 64. At that time, the upper electrode 50 and the lower electrode assembly 122 are directly adjacent another location on the assembly 20 that is adjacent the mesial flange, but spaced in a laterally offset, gingival direction relative to the location of the first spot weld. The controller 62 then activates the weld head 46 and the power supply 52 causes a second weld to be provided between the mesial flange and the band.

Next, the stepmotor 76 is actuated by the microstepping drive 77 to swing the subframe 66 in an arc until the distal welding flange of the attachment is directly between the upper electrode 50 and the lower electrode assembly 122. At that time, the controller 62 again activates the weld head 46 and the power supply 52 causes a third spot weld to be applied.

Next, the controller 62 activates the solenoid air valve connected to the piston and cylinder assembly 60 in order to cause the piston rod of the latter to extend and move the carriage 54 forwardly relative to the frame 42 until the carriage 54 is in contact with the front stop 64. The controller 62 again activates the weld head and the power supply 52 causes a fourth spot weld to be applied at a location on the distal welding flange oriented occlusally from the third spot weld.

Subsequently, the microstepping drive 77 activates the stepmotor 76 to swing the subframe 66 back to a central, preferably horizontal position. The operator then depresses both foot switches, causing the flow of pressurized air to the piston and cylinder assemblies 116 to be interrupted whereupon the clamping arms 112 pivot to an open position by means of the springs 120. Air is also directed to the piston and cylinder assembly 128 to move the lower electrode sections 124 away from each other. The welded attachment and band assembly is then removed from the apparatus 40.

Other welding sequences are also possible. Moreover, the apparatus 40 may be used with flangeless brackets and buccal tubes, as well as with a variety of other orthodontic attachments. In each instance, however, it is preferable that the recess of the lower electrode assembly legs 136 for receiving the attachment is complementary in shape to the configuration of the attachment.

As another alternative, the band and attachment may be received in stationary holders, and the welding electrodes may be mounted on a horizontally movable frame that is also swingable in an arc. The frame is movable in response to a preprogrammed series of instructions to bring the electrodes to the four weld locations described above.

Those skilled in the art can appreciate that many other variations, additions and modifications may be made to the

presently preferred embodiments of our invention that are described above in detail. Accordingly, the invention should not be deemed limited to the detailed embodiments described above, but only by a fair scope of the claims that follow along with their equivalents.

We claim:

1. A method of welding an orthodontic attachment to a band comprising the steps of:

placing the attachment in a holder;  
electrically connecting the holder and the attachment to one electrode of an electric resistance welder;

placing the band in a fixture in a certain orientation such that an outer surface of the band is directly adjacent an inner surface of the attachment;

placing a second electrode in contact with an inner surface of the band;

directing a current in a first instance along a path extending between the electrodes and through the bands the attachment and the holder to provide a first spot weld; relatively moving in an arc the second electrode and the holder while the fixture retains the band in said certain orientation relative to the holder and consequently to the attachment; and

directing a current in a second instance along a path extending between the electrodes and through the band, the attachment and the holder after said step of relatively moving the electrode and the band, in order to provide a second spot weld that is spaced from the first weld in an arc along the inner surface of the band.

2. The method of claim 1, wherein said step of placing an attachment in a holder includes the step of moving holder sections together to grasp the attachment.

3. The method of claim 1, wherein said step of placing the band in a fixture includes the step of moving an arm to contact the band and clamp the band to the fixture.

4. The method of claim 1, wherein said step of placing an attachment in a holder includes the step of placing two legs of a single electrode member into channels of holder sections.

5. The method of claim 1, wherein said steps of directing a current in a first instance and in a second instance provide welds that are characterized by the lack of any outer deformation that is circular in shape.

6. The method of claim 1, wherein said steps of directing a current in a first instance and in a second instance provide welds that are characterized by the lack of any outer deformation that is visible to the naked eye when viewed at a distance of twenty-four inches.

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 5,753,884

DATED : May 19, 1998

INVENTOR(S) : Hilgenfeldt, Thorsten G. et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Col. 10, Line 19, "bands" should read --band,--.

Signed and Sealed this  
Sixteenth Day of March, 1999

*Attest:*



**Q. TODD DICKINSON**

*Attesting Officer*

*Acting Commissioner of Patents and Trademarks*