



US 20100076370A1

(19) **United States**

(12) **Patent Application Publication**

Howlett et al.

(10) **Pub. No.: US 2010/0076370 A1**

(43) **Pub. Date: Mar. 25, 2010**

(54) **APPARATUS AND METHODS FOR PURGING
CATHETER SYSTEMS**

(75) Inventors: **Michael W. Howlett**, Salt Lake City, UT (US); **James V. Mercer**, West Jordan, UT (US); **Amelio Paolucci**, Westminster, CO (US)

Correspondence Address:

Michael W. Howlett
3015 Sun Drift Circle
Salt Lake City, UT 84121 (US)

(73) Assignee: **Infusion Advancements, LLC.**, Salt Lake City, UT (US)

(21) Appl. No.: **12/387,937**

(22) Filed: **May 9, 2009**

Related U.S. Application Data

(60) Provisional application No. 61/192,827, filed on Sep. 23, 2008.


Publication Classification



(51) **Int. Cl.**
A61M 5/168 (2006.01)
A61M 5/315 (2006.01)




(52) **U.S. Cl.** *604/65; 604/237*



(57) **ABSTRACT**

Apparatus and methods for providing controlled pressure-flow pulses which purge a catheter system with turbulent flow flushing. Accomplishment of such controlled pressure-flow pulses is provided by a variety of inventive devices including a special plunger rod for a conventional syringe, other interactive parts for conventional syringes, an in-line catheter attachable device which automatically generates the controlled pressure-flow pulses and also single pulse, digitally operated devices.



**FIGURE 1****FIGURE 2**

**FIGURE 2A****FIGURE 2B****FIGURE 2C**

**FIGURE 3****FIGURE 4**




FIGURE 5


















FIGURE 6

**FIGURE 7****FIGURE 8**

**FIGURE 9****FIGURE 10****FIGURE 11****FIGURE 12**

**FIGURE 13****FIGURE 14**

**FIGURE 15****FIGURE 16****FIGURE 17**

**FIGURE 18****FIGURE 19****FIGURE 20**

APPARATUS AND METHODS FOR PURGING CATHETER SYSTEMS

CONTINUITY

[0001] This non-provisional U.S. patent application is a continuation-in-part of a provisional U.S. Patent Application No. 61/192,827 filed Sep. 23, 2008, titled TURBULENT FLOW SYRINGE AND FLUID PATHWAY INSERT.

FIELD OF INVENTION

[0002] This invention is associated with apparatus and methods for clearing catheter systems (e.g. IV lines) by creating controlled and consistent turbulent flushing pressure and flow within the system to purge the line of unwanted residue, and, in particular, the invention is associated with apparatus and methods for creating such turbulent flushing pressure and flow substantially independent of clinician technique.

BACKGROUND AND RELATED ART

[0003] It is well known in IV care art that turbulent “start-stop” or “push-pause” flushing of IV catheters, e.g. central venous catheters, has become an accepted method for purging matter from catheters and, thereby, preventing build-up of deposits of blood, blood residue and IV drugs within a catheter. Such build-up can cause partial or complete blockage of the fluid pathway in a catheter system, requiring expensive and potentially dangerous methods for purging the catheter or necessitating a total catheter exchange. Often, such blockages lead to interruptions in therapy (e.g. IV therapy) that may compromise patient care. Further, build-up of residue within a catheter can also increase infection risk by providing a breeding medium for microorganisms. For this reason, push-pause flushing is traditionally, and more or less universally, taught to healthcare workers.

[0004] Push-pause (or turbulent) flushing simply requires a clinician to alternately increase and decrease an associated infusion rate during flushing. However, efficiency and success of catheter purging using push-pause flushing is well known to be completely dependent upon individual awareness, compliance and technique and a successful purging operation is often incomplete and problematic. For this reason, many users may not use such turbulent flushing effectively while others, due to lack of knowledge or perception of value, may not use it at all.

[0005] Also, other than using turbulence for catheter clearance, syringes, pumps and other fluid forcing mechanisms associated with IV infusion are substantially operated in a laminar flow domain. When pulsatile flow is used, pressure and flow characteristics are constrained well below those turbulent and volumetric flow levels required for effective catheter purging.

[0006] In the wide spectrum of syringe design, it is common to find art which provides periodic stops of various types and kinds for syringe plungers. Generally, many such stops are employed to aid in accurately measuring and dispensing a portion of a syringe fill. Once such stops are reached, it is common for the plunger to be released to thereby permit controlled and substantially laminar flow to the next stop. In other words, such stops are generally released without a calculated, intentional force to propel the stopper with sufficient force for catheter purging. Other stops are commonly used to

limit a syringe to a single use. Generally, these stops are hard and cannot be reasonably overcome, as is common in single-use hypodermic syringes.

[0007] An example of a plunger stop for the purpose of limiting injection of fluid from a syringe is found in U.S. Pat. No. 4,642,102 issued Feb. 10, 1987 to Hirofumi Ohmori (Ohmori). Ohmori discloses stops which engage recesses in a plunger rod associated with a plunger to interrupt discharge from the syringe. After each stop, the plunger rod is strictly stopped such that no excessive force is able to drive the plunger rod further. Similarly U.S. Pat. No. 5,024,661 issued Jun. 18, 1991 to Harry Wender (Wender) discloses a single use syringe having recesses along a plunger rod.

[0008] U.S. Pat. No. 5,318,544 issued Jun. 7, 1994 to John Drypen, et al. discloses a metering syringe having a plunger rod containing a plurality of stop surfaces. The stop surfaces are spaced apart to define a predetermined dose volume. Plunger rod rotation relieves each stop to permit further dispensing.

[0009] U.S. Pat. No. 5,059,181 issued Oct. 22, 1991 to Robert B. Agran (Agran) also discloses a syringe assembly having recesses in a plunger rod which are used to retard a second rearward displacement of the plunger rod associated with a second use of the syringe assembly. In similar manner, U.S. Pat. No. 5,084,017 issued Jan. 28, 1992 to John Maffetone (Maffetone) discloses a single use syringe having a notched plunger rod. The syringe of Maffetone is taught to operate smoothly, but to disassemble itself at the completion of a single use cycle.

[0010] U.S. Pat. No. 5,280,030 issued Oct. 5, 1993 to Cesar G. Corsich, et al. (Corsich) discloses a hypodermic syringe having a blockable piston capable of preventing recharge and reuse under some conditions.

[0011] U.S. Pat. No. 5,328,476 issued Jul. 12, 1994 to James Bidwell (Bidwell) discloses a single-use hypodermic syringe apparatus. Ratchet grooves in an associated plunger rod are used as lock members such that when plunger is fully inserted or reinserted into a casing, the plunger is prevented from being withdrawn relative to the casing.

[0012] U.S. Pat. No. 6,283,941 issued Sep. 4, 2001 to Joel Schoenfeld, et al. (Schoenfeld) discloses a rod-like syringe plunger having a plurality of bead-like ratchet teeth. Schoenfeld also discloses a single use syringe. Of particular note is the statement, “It is a further object of the present invention to provide a single use syringe which has a smooth mechanical operation and a plunger retraction force less than the industry maximum standard.” Such objectives are commonly held in the syringe art for manipulating syringe plunger rods.

[0013] U.S. Pat. No. 5,891,052 issued Apr. 6, 1999 to Paul L. Simmons (Simmons) teaches a syringe plunger sabot and sabot lock disposed within a syringe body, the sabot lock mechanism being selectively moveable between a locked and unlocked position. Thereby an engagement is made to create a vacuum for extracting material into the syringe body.

[0014] U.S. Pat. No. 6,488,651 issued Dec. 3, 2002 to David Paul Morris et al. (Morris) discloses a mixing syringe having a plunger rod dasher which permits flow within the barrel for communicating material to be mixed with material in a more proximal chamber. Other cylindrical barriers provide within chamber defining spaces which are selectively displaced by movement of the plunger rod. Other than resistances of fluid dynamics and friction (and stiction), no other retarding forces are taught.

[0015] U.S. Pat. No. 6,579,269 B1 issued Jun. 17, 2003 to Gennady I. Kleyman (Kleyman) discloses a dose measuring syringe. A plunger rod, as taught in Kleyman, has formations which increase resistance to displacement of the plunger rod and to produce an audible sound corresponding to a predetermined volume for a measured dose. Even so, there are no teachings in Kleyman for providing momentary stops which produce a predetermined amount of turbulent flow in a catheter.

[0016] U.S. Pat. No. 5,685,864 issued Nov. 11, 1997 to Laurence M. Shanley, et al. (Shanley) discloses an aspiration syringe device which operates oppositely to aspirate rather than discharge into a connected site. A right angle stem of an associated plunger is equipped with spaced flanges. Interior of the syringe barrel is equipped with at least one stop. When a flange is contiguous with a stop, advancement of the plunger is prohibited. Rotation of the plunger permits further advancement.

[0017] U.S. Pat. No. 4,995,869 issued Feb. 16, 1991 to Martin McCarthy (McCarthy) discloses a single-use hypodermic syringe. A syringe barrel according to McCarthy has an interior undulating surface over which a skirt rides rearward under direction of a proximally directed manual force. While it seems apparent that the undulations will cause a pulsation in flow while discharging fluids via a patient needle, it is clear that there are no related teachings for creating turbulent flow in a catheter, a subject untouched in McCarthy.

[0018] Generally, in summary, prior art, of which art cited above is an example, discloses and teaches plunger rod having slots, grooves and ratchet teeth are for providing obstructions used for measuring predetermined volumes of dispensed fluids or for stops associated with providing single use syringes. Just as clinician-dependent generation of push-pause flow is problematic, all such art is void of teachings which assure successful creation of turbulent flow for clearing an associated attached catheter system. Such is the specific and precise purpose of the present invention.

BRIEF SUMMARY AND OBJECTS OF THE INVENTION

[0019] In brief summary, this novel invention alleviates all of the known problems related to generating controlled and predetermined push-pause pressures and flows thereby providing controlled and consistent turbulent flow which is effective in purging matter disposed within a catheter system. The invention comprises methods and apparatus which are defined and designed to produce pressures resulting from dynamic releases by predetermined forces, each for a period which provides a controlled and consistent surge to effectively produce turbulent purging fluid flow at a site of concern within a catheter system.

[0020] Generally, such flow is provided to a catheter system from a source of flush liquid from a container sized to hold a volume of liquid consistent with flow volume requirements of a desired pressure pulse. In each case, an actuator opens a valve mechanism at a predetermined pressure to initiate the desired liquid pulse pressure and resulting liquid flow. The sensing actuator has an operating hysteresis which ultimately stops flow to end the pressure pulse. Of course, an implement which, by example, may be a pump or piston, is a crucial part of the apparatus for providing sufficient pressure to activate the valve mechanism. To retain adequate pressure throughout the pulse, a memory element provides a source of stored energy received from the implement and releases the stored

energy upon valve mechanism opening to retain the turbulent flushing fluid pressure and flow for a desired pulse period.

[0021] One embodiment of the apparatus is application of the invention to a syringe, and more specifically, to a plunger rod of a syringe. In such a case, the barrel of a syringe is the container. Displacement of the plunger rod (and associated plunger) within the barrel acts as an implement to dispense liquid from the syringe. Commonly found at the proximal end of conventional syringes is a retention ring formed of reduced diameter relative to the diameter of the rest of the syringe barrel. This retention ring is used as a tactile indicator between an entry disk disposed on the stem of a plunger rod just proximal from the plunger affixed to the plunger rod, providing an impedance which must be overcome to extract the plunger rod (and plunger) from the syringe barrel.

[0022] At least one actuating geometry, sized and shaped to require a predetermined force to displace the actuating geometry past the retention ring, is disposed proximally on the stem relative to the entry disk. Forcing the actuating geometry past the retention ring yields the force necessary to provide desired turbulent flushing fluid pressure and initiate flow. Such geometry may be a disk on the plunger or an interfacing nub on exterior edges of shafts of a plunger rod. Reflexive motion associated with forcing the actuating disk past the retention disk provides the memory based, stored energy necessary to assure continuation of forced flow thereby providing the pressure pulse. The length of the pressure pulse is determined by either the plunger being displaced to empty the syringe barrel or a second actuating disk disposed proximally on the stem relative to the actuating disk just forced through the retention ring to provide a tactile determinable stop. Note, that resistance of this stop, relative to reflexive energy applied to displace the syringe plunger rod, provides the hysteresis specified. In this manner, a conventional syringe barrel, in combination with a plunger rod made according to specifications of the instant invention, can provide desired pulse-pause pressure pulses from a syringe substantially independent of a syringe user. It may be preferred to provide a segment of a plunger rod free of actuating geometry to provide a "no-pulse" segment to enable conventional flush technique to check for possible occlusions and to verify blood return.

[0023] In another embodiment, the pulse-pause pressure pulse is provided by an in-line apparatus. Source for fluid is from a receptacle having sufficient volume to fill a container from which the pressure pulse is generated, the container being a hollow cylindrical vessel which receives liquid from the receptacle through a one-way valve. Communication for dispensing liquid to the catheter system is through another one-way valve.

[0024] The valve mechanism is a plunger, sized and shaped to displace fluid within the vessel through the one-way valve to the catheter system. Further, the vessel has a retention ring similar to the retention ring of the barrel of a conventional syringe. A valve-actuating disk associated with the plunger is sized and shaped to require predetermined force necessary to generate a desired pulse toward the catheter system. Volume of the vessel determines pulse volume. Again, as in the case of the syringe, reflexive action resulting from release of force when the actuating disk is driven past the retention ring assures adequate pulse pressure. The actual implement for driving the plunger is derived from a button affixed to the plunger and associated rod whereby the plunger is manually driven through the vessel. A spring disposed to be compressed

when the pressure pulse is generated stores energy to return the plunger and refill the vessel for a subsequent pulse-pause cycle.

[0025] Other embodiments of the present invention involve a pressure sensitive switch having an actuator which opens the valve at a higher predetermined pressure and closes at a lower predetermined pressure. Generally, the source is a fluid receptacle upstream from a pressure-providing device which provides fluid dispensed at a predetermined pressure and flow. A vessel acts as a container which communicates with the pressure providing device through a flow restrictor. Further, the vessel communicates with the catheter system through the pressure sensitive valve. The pressure sensitive valve is selected to have an opening pressure which provides a fluid pulse having desired turbulent flow characteristics and closing at a pressure after a desire flow volume has been achieved and pressure within the vessel is reduced below the lower predetermined pressure.

[0026] In one of these other embodiments, a pump provides pressure of the source. A spring loaded piston chamber provides opportunity to gather volume for the pressure pulse which fills at a pressure lower than the higher predetermined pressure through a flow restrictor affixed to the output of the pump, but at a pressure higher than the lower predetermined pressure. Thus, the higher predetermined pressure is reached only upon filling the chamber. Once the chamber is filled, the valve is opened by the actuator to initiate the controlled pressure pulse. When the chamber is emptied, pressure in the vessel drops below the lower predetermined pressure and the actuator closes the valve. If this embodiment remains affixed to the catheter system a subsequent pressure pulse is generated automatically.

[0027] Another of other embodiments involves a squeezable tube. In this case the tube communicates with the catheter system through a pressure sensitive valve, having valve actuator opening characteristics as disclosed supra. Upstream the tube communicates with the source through a one-way valve. Pressure from the source does not reach or exceed the higher predetermined pressure, but is sufficient to fill the tube. Thus, pressure from the upstream source and elastic memory in the tube cause the tube to fill through the upstream one-way valve. Once the tube is adequately filled, it is selectively squeezed to cause the pressure to rise to at least the higher predetermined pressure. Once pressure within the tube is at or above the higher predetermined pressure, the valve is opened and the pressure pulse is initiated. The pressure pulse is continued by reflexive action following valve opening. Expulsion of liquid from the tube ultimately results in valve closing ending the pressure pulse. The pressure pulse may be continued until the tube is substantially empty.

[0028] Methods for using embodiments of the instant invention generally involve filling a chamber or vessel, of predetermined size, from which a pulse of liquid is to be dispensed, causing pressure within the chamber or vessel to exceed a predetermined pressure and selectively opening a pathway to the catheter system only when that pressure is achieved. In that manner, a desired, controlled pulse-pause pressure pulse is achieved and provided substantially independent of performance of a user.

[0029] Accordingly, it is a primary object to provide apparatus which provides substantially user independent, controlled pulse-pause pulsatile flow of sufficiently turbulent flushing pressure and flow within a catheter system to substantially purge the line of unwanted residue.

[0030] It is a primary object to provide such apparatus which is used within a barrel of a conventional syringe.

[0031] It is another primary object to provide such apparatus which provides in-line operation between a fluid source and the catheter system.

[0032] It is an object to provide such apparatus which provides for a series of manually generated pulse-pause pressure pulses.

[0033] Is a an important object to provide such apparatus which uses a pump as an implement.

[0034] It is another object to provide apparatus which provide controlled pressure pulses resulting from opening and closing a pressure sensitive valve.

[0035] These and other objects and features of the present invention will be apparent from the detailed description taken with reference to accompanying drawings.

Definitions of Some Terms Used in the Specification

[0036] catheter system\n: a combination of tubes and other devices used to deliver fluids to patients, e.g. a medical catheter (e.g. IV catheter), delivery tubing (e.g. feeding tube) and associated connectors

[0037] fluid\n: a gas or liquid

[0038] IV\n: adj: a mode of delivery of fluids to a patient, in this case the mode is Intravascular

[0039] laminar flow\n: streamline flow which is relatively smooth and even, such as flow near a solid boundary and contrasted with turbulent flow

[0040] turbulent flow\n: a fluid flow in which the velocity at a given point varies erratically in magnitude and direction with time and is thus essentially variable in pattern and is contrasted with laminar flow

[0041] valve mechanism\n: a fluid control device generally defined herein to be a device for initiating a pressure pulse when opened and ending the pressure pulse when closed; within this general definition, pulse-pressure generating action of a syringe plunger rod being displaced to actuate a pressure pulse is considered to be a valve mechanism

BRIEF DESCRIPTION OF THE DRAWINGS

[0042] FIG. 1 is a perspective of a syringe and plunger rod made according to the present invention where stem of the plunger rod has a plurality of disks disposed upon the length thereof.

[0043] FIG. 2 is a cross section of the syringe and plunger rod and seen in FIG. 1.

[0044] FIG. 2A is a cross section of a syringe and plunger rod which is similar to the syringe and plunger rod of FIG. 2, but wherein edges of disks are shaped to facilitate displacing the plunger rod into the syringe and deterring the plunger rod from being removed from the barrel, once so displaced.

[0045] FIG. 2B is a cross section of a syringe and plunger rod which is similar to the syringe and plunger rod of FIG. 2, but wherein edges of disks are shaped to facilitate displacing the plunger rod out of the syringe once displaced therein.

[0046] FIG. 2C is a cross section of a syringe and plunger rod which is similar to syringes and plunger rods of FIGS. 2, 2A and 2B, but having nubs along a shaft of a plunger rod instead of disks.

[0047] FIG. 3 is a perspective of the plunger rod seen in FIG. 1.

[0048] FIG. 4 is a perspective of a syringe and plunger rod wherein the plunger rod is similar to the plunger rod of FIG.

1 but fabricated with a plurality of breakaway rings disposed about to stem of the plunger rod.

[0049] FIG. 5 is a perspective of the plunger rod seen in FIG. 4.

[0050] FIG. 6 is a perspective of the syringe and plunger rod seen in FIG. 4 with at least one breakaway ring sheered from the stem of the plunger rod.

[0051] FIG. 7 is a perspective of a syringe and plunger rod wherein the plunger rod is similar to the plunger rod of FIG. 1 but having a pattern of undulations on the stem and a constraining elastomeric ring about the proximal syringe barrel opening.

[0052] FIG. 8 is a cross section of the syringe, plunger rod and elastomeric ring seen in FIG. 7.

[0053] FIG. 9 is a perspective of an automatic, in-line pulsing device made according to the present invention.

[0054] FIG. 10 is a cross section of the automatic, in-line pulsing device seen in FIG. 9 showing state of the device at the end of a pulse.

[0055] FIG. 11 is a cross section of the automatic pulsing device seen in FIG. 9 showing state of the device when charged before actuating a pulse.

[0056] FIG. 12 is a cross section of the automatic pulsing device seen in FIG. 9 showing state of the device during pulse generation.

[0057] FIG. 13 is a perspective of the device seen in FIG. 9 with a syringe affixed to the device to provide a fluid pressure source.

[0058] FIG. 14 is a schematic drawing of a system which employs a pumped fluid source for the device seen in FIG. 9.

[0059] FIG. 15 is a perspective of a squeezable device for providing a controlled pressure pulse according to the instant invention.

[0060] FIG. 16 is a cross section of the device seen in FIG. 15.

[0061] FIG. 17 is a cross section of the device seen in FIG. 14 with a medical section squeezed at the end of a controlled release pressure pulse.

[0062] FIG. 18 is a perspective of a manually operated controlled pressure pulse device made according to the present invention.

[0063] FIG. 19 is a cross section of the device seen in FIG. 18 filled before initiating a controlled pressure pulse.

[0064] FIG. 20 is a cross section of the device seen in FIG. 18 at the end of a pressure pulse.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

[0065] In this description, the term proximal is used to indicate the segment of the device normally closest to the object of the sentence describing its position. The term distal refers to a site opposite the proximal section. Reference is now made to the embodiments illustrated in FIGS. 1-20 wherein like numerals are used to designate like parts throughout.

[0066] Reference is now made to FIG. 1 wherein a preferred embodiment of a syringe/plunger rod combination 10 of the instant invention is seen. Combination 10 comprises a conventional syringe barrel 20 and a plunger rod 30. Salient features of combination 10 are better seen in FIG. 2 to comprise barrel 20 having a retention ring 40 disposed at proximal barrel hole opening 42 and plunger rod 30 comprising a plurality of actuating geometry, interfaces or rings, generally numbered 50) disposed along a stem 60 thereof. In addition,

as is common with plunger rods of conventional syringes, plunger rod 30 has a plunger 70 affixed to the distal end 80 of stem 60. It may be noted that distal end 80 has a threaded geometry portion 90 which permits plunger rod 30 to be affixed to plunger 70 after barrel 20 is filled with liquid, generally referenced as liquid 72. A plunger rod 30 is seen alone in FIG. 3 providing a clearer view of threaded portion 90.

[0067] Further, plunger rod 30 has a first ring 92 which can be forced past retention ring 40 when plunger 70 and stem 60 are inserted into barrel 20. First ring 92 is sized and shaped to be forcibly displaced through retention ring 40, but provide a tactilely discernable stop such that plunger 70 is not inadvertently displaced out of barrel 20.

[0068] Each actuator ring 50 is sized and shaped to be obstructed by retention ring 40. Each actuator ring 50 is further sized and shaped to require a predetermined force which must be exceeded to displace a contacting actuator geometry (e.g. retention ring interface 50) past retention ring 40. For this reason, fluid within barrel 20 is displaced with resulting acceleration and velocity resulting from the predetermined force when the contacting ring 50 is releasibly displaced through retention ring 40. Generally the resulting acceleration and velocity is of liquid which is discharged from syringe barrel 20 to turbulently flush liquid 72 through an associated catheter system. In this manner, each time a contacting ring 50 is displaced past retention ring 40 a pulse of pressurized liquid 72 is purged into the catheter system providing a turbulent flushing pulse of liquid 72 there through.

[0069] As well, a more proximal ring 94 of rings 50 may be further shaped and sized to require a force which is greater than more distal rings 50 to provide a reminder that the pulse resulting from actuation using ring 94 is the last pulse provided by liquid 72 from combination 10. For this reason, ring 94 may be referenced as reminder ring 94 hereafter. Note, that, if plunger rod 30 is not displaced sufficiently far into barrel 20 to displace reminder ring 94 past retention ring 40, no back flow or reflux should occur in an associated catheter system. Note that proximal end 98 of stem 60 is convex or dome shaped to facilitate application of digital force against plunger rod 30.

[0070] As well, it may be noted that rings 50 are not necessarily spaced uniformly. As an example a space 99 between first ring 92 and next most proximal ring 50 is relatively large compared to space between other rings, generally numbered 50. This provides for a "no-pulse" segment which may be used for conventional sampling for catheter blood flow to assure proper catheter operation.

[0071] Attention is now directed to FIG. 2A wherein a second combination 20' of a conventional syringe barrel 20 and a plunger rod 30' is seen. Plunger rod 30' is similar to plunger rod 30, having a series of actuator rings 50' disposed along the length thereof. However, in the case of combination 10', rings 50' are shaped and sized (as seen in FIG. 2A) to be more easily displaced into barrel 20 (and distally through retention ring 40) than displaced barrel 20 (proximally through retention ring). Such meets a condition whereby plunger rod 30' is not easily removed from barrel 20, once used to promote a single use application.

[0072] On the other hand, it may be desired to refill and reuse such a combination. In such a case, it is desired to displace a plunger rod 30" of a third combination 10" more

easily proximally than distally. In such a case, actuating rings **50**" disposed along a stem **60** are shaped as seen in FIG. 2B.

[0073] Rings **50** seen in FIG. 2, may be replaced by nubs **52** on a plunger rod **32** as seen as combination **12** in FIG. 2C. Replacement of rings **50** by nubs **52** may be done without degradation of effect of producing desired turbulence by sizing and shaping nubs **52** to require forces similar to that required of rings **50** for displacement past retention ring **40**.

[0074] Another embodiment, seen as combination **110**, of the instant invention is seen in FIGS. 4-6. As in combination **10**, combination **110** comprises a conventional syringe barrel **20**. Note that syringe barrel **20** has a proximal entry hole **122** associated with retention ring **40**. As seen in FIGS. 4 and 5, an associated plunger rod **30** also comprises a series of actuator rings, generally numbered **150**, disposed along a stem **60** of plunger rod **130**. However, rather than being sized and shaped to be forced through retention ring **40** of barrel **20** to create a desired pressure pulse, rings **150** are affixed to stem **60** in a manner which permits each actuation ring **150** to be sheared from stem **60** as it is displaced into barrel entry hole **42**.

[0075] Shear force at separate actuation rings **150** from stem **60**, similar to displacement force past retention ring **40** of combination **10**, is geometrically and mechanically designed to provide a predetermined acceleration and velocity which purveys desired turbulent flow to purge and discharge unwanted contaminants from a downstream catheter system. Note, in FIG. 6, that a first more distally disposed actuator ring **150** is seen to be captured by a second, more proximally disposed actuator ring **150** exterior to hole in FIG. 6. Note that piling up of sheared actuation rings **150** may be used to prevent a syringe from being fully evacuated.

[0076] Yet another embodiment of the instant invention is seen as combination **210**, which may use a conventional syringe barrel **20**, is seen in FIGS. 7 and 8. In addition to barrel **20**, combination **210** comprises an elastomeric restrictor **230** a plunger rod **240** with a stem **242**. Stem **242** comprises a plurality of elongated side members, each numbered **244**. Each side member has an undulating exterior edge, numbered **246**. High points of the undulations are generally numbered **248**.

[0077] Restrictor **230** is shaped and configured to provide a port about barrel entry hole **42** (see FIGS. 1 and 2). A restrictor entry hole **250** is sized and shaped to obstruct inward displacement of plunger rod **240** upon collision between restrictor **230** and each high point **248**. A combination of selected durometer of the elastomer of restrictor **230**, and collision geometry of high points **248** and hole **250** combine to require a predetermined force for further displacement of plunger rod **240**. This predetermined force is comparable to the force required for displacement of plunger rod **30** past retention ring **40** (see FIGS. 1-3). In this manner, a pressure pulse which provides turbulent flow for purging an attached catheter system is generated each time high points **248** are displaced through hole **250** of restrictor **230**.

[0078] Reference is now made to FIGS. 9-12 wherein an in-line automatic pulsing device **310** made according to the instant invention is seen. As seen in FIG. 9, device **310** comprises an upstream or proximal connection **320**, into which liquid from a liquid source is provided. Further device **310** comprises an output port and connector **330** which may be connected to a downstream catheter system. For proper operation, liquid pressure available from the source must be greater than desired pressure of a purging liquid pulse emitted by device **310**.

[0079] As seen in FIG. 10, a pressure sensitive valve **340** is disposed to close output port and connector **330** when pressure is below the desired pressure. Just distal from proximal connection **320** is a check valve **350** to obstruct backflow and retard inflow to a predetermined level of flow. Medially disposed between pressure sensitive valve **340** and check valve **350** is a pulse reservoir chamber **360**. Disposed within chamber **360** is a piston **370** and spring **380** which acts within chamber **360** to store a volume of liquid when valve **330** is closed.

[0080] When choosing pressure sensitive valve **340**, a valve should be selected which has an opening pressure to closing pressure hysteresis having a predetermined pressure differential for purposes clarified hereafter. The pressure differential being defined as a difference between release high pressure and a low closing pressure. The high pressure being a pressure which creates a pressure pulse having sufficient force and flow to cause down stream turbulence which purges a desired amount of material from an attached catheter system. The lower pressure being a pressure to which pressure inside device **310** falls after clearing of liquid from chamber **360**. Note that, for pressure inside **310** to fall to the lower pressure, inflow from the source must be restricted to a lower flow rate than outflow through output port and connector **330**.

[0081] Steps of operation of device **310** are seen to embody a beginning state seen in FIG. 10 where chamber **360** is empty and spring **380** is decompressed and valve **350** is closed. Subsequent filling of chamber **360** is seen in FIG. 11. Valve **340** is opened when spring **380** is fully compressed to discharge liquid from device **310** thereby. Of course, once valve **350** closes, the pulse cycle repeats.

[0082] Sources for pressurized fluid for device **310** are seen in FIGS. 13 and 14. In FIG. 13, a conventional syringe **390** is affixed to proximal connection **320**. Source pressure is provided by the force displacing an associated plunger rod **392**. Note that sufficient pressure is required to fully charge chamber **360** before actuating valve **350**.

[0083] In FIG. 14, a more sophisticated pressure providing source system is seen including a saline bag **304**, a pump **396** and a variable liquid flow restrictor **398**. Source liquid from bag **304** is drawn and pumped by pump **396** to provide pressure equal to or greater than the high pressure necessary to open valve **350**. Variable restrictor is set to determine pump **396** to device **310** liquid transfer rate to determine device **310** output pulse rate.

[0084] Reference is now made to FIGS. 15-17 wherein an in-line pinch or squeeze pump **410**, made according to the instant invention, is seen. As seen in FIG. 16, device **410** comprises an upstream or proximal connection **420**, into which liquid from a liquid source is provided. Further device **410** comprises an output port and connector **430** which may be connected to a downstream catheter system. For proper operation, liquid pressure available from the source must only be greater than filling pressure of an expandable tube **440** which is sized and shaped to be easily filled and purged by squeezing.

[0085] As seen in FIG. 16, a pressure sensitive valve **340** (see also FIGS. 11-13 of device **310**, disclosed supra) is disposed to close output port and connector **430** when pressure is below a predetermined pressure. Just distal from proximal connection **420** is a check valve **450** to obstruct backflow. Tube **440** provides a storage medium which defines pulse flow quantity when device **410** is actuated. To operate, tube **440** is squeezed until valve **340** is opened to provide a

pressure pulse according to the present invention. Continued reflexive squeezing dispenses liquid through valve 340 to create a plusatile flow of liquid having sufficient turbulent flow and pressure to purge an attached catheter system. Note that pressure of source liquid need only be at a sufficiently high pressure to fill tube 440 and that tube 440 may have sufficient inherent structural memory to provide a somewhat negative filling pressure requirement. This same memory reduces liquid pressure inside tube 440 to cause valve 340 to close at the end of a pulse generating cycle.

[0086] Another device 510 which provides manually, digitally generated controlled pressure pulses for purging catheter systems according to the present invention is seen in FIGS. 18-20. As seen in FIG. 19, device 510 comprises an upstream or proximal connection 520, into which liquid from a liquid source is provided. Further device 510 comprises an output port and connector 530 which may be connected to a downstream catheter system. For proper operation, liquid pressure available from the source must only be greater than filling pressure of a spring piston combination 540. Combination 540 comprises a depressible button and rod 550, a compressible spring 560 and a plunger 570. Plunger 570 is sized and shaped to evacuate liquid from a hollow vertical chamber 580 which communicates orthogonally with a hollow liquid flow chamber 590 disposed for liquid communication between proximal connection 520 and output port 530. Amount of liquid stored in vertical chamber 580 and released upon displacement of plunger 570 determines pulse volume of liquid delivered to the downstream catheter system.

[0087] As seen in FIG. 19, a pressure sensitive valve 340 (see also FIGS. 11-13 of device 310, disclosed supra) is disposed to close output port and connector 530 when pressure is below a predetermined pressure. Just distal from proximal connection 520 is a check valve 450 to obstruct backflow. To operate device 510, button 550 is depressed to open valve 340 thereby providing a pressure pulse according to the present invention. Continued reflexively depressing button 550 dispenses liquid through valve 340 to create a plusatile flow of liquid having sufficient turbulent flow and pressure to purge an attached catheter system. Note that pressure of source liquid need only be at a sufficiently high pressure to fill chamber 580 and that combination 540 with spring 560 should have sufficient inherent structural memory to provide a negative filling pressure inside chamber 590. This same memory reduces liquid pressure inside chamber 590 to cause valve 340 to close at the end of a pulse generating cycle.

[0088] To operate device 510, chamber 580 is permitted to fill with liquid provided through connector 520. Button 550 is depressed to provide sufficient force to open valve 340 and reflexively thereafter continued to be depressed until liquid is purged from chamber 580 as seen in FIG. 20 to produce the desired purging pressure pulse. Once combination 540 is fully depressed, force on button 550 is relieved to permit refilling of chamber 580 for generating a subsequent pressure pulse.

[0089] The invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. The present embodiment is therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description, and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

What is claimed and desired to be secured by Letters Patent is:

1. An apparatus which provides controlled and consistent push-pause pulsatile flow of sufficiently turbulent flushing pressure and flow within a catheter system to substantially purge the line of unwanted residue, said apparatus comprising:

a source of flush fluid;

a container for retaining a predetermined volume of the fluid,

a valve mechanism interconnected for controllably interrupting fluid flow communication between the container and the catheter system;

a sensing actuator which controls opening and closing said valve mechanism, said sensing actuator opening said valve mechanism at a given predetermined pressure which yields the sufficiently turbulent flow of fluid from the container, said sensor actuator further having an operating hysteresis such that the valve mechanism is closed at another predetermined pressure which is lower than the opening pressure;

an implement for providing at least enough fluid force to engender the pressure within the container necessary to open the valve mechanism; and

a memory element which stores energy received from action of the implement and releases the stored energy upon valve opening to provide the turbulent flushing fluid pressure and flow for a period dependent upon time pressure within the container is above the other pressure.

2. The apparatus according to claim 1 wherein:

(i) said source comprises fluid contained within a barrel of a syringe;

(ii) said container comprises a housing comprising the distal portion of the barrel of the syringe and a plunger affixed to a plunger rod which are disposed for slideable displacement within said barrel, said barrel further comprising a retention ring on the proximal end thereof and said plunger comprising a proximally disposed entry disk associated with said plunger, said entry disk and retention ring cooperating to provide a tactilely discernible stop which prevents inadvertent removal of the plunger from the barrel;

(iii) said plunger rod further comprising at least one sensing actuator comprising a valve actuating disk proximally disposed relative to said plunger and entry disk, said valve actuating disk being sized and shaped to require controlled and consistent force upon displacement past the retention ring to produce pressure required for turbulent flow when the valve actuating disk is forced through the retention ring;

(iv) said implement comprising said plunger rod which comprises a proximally disposed button upon which force is manually applied to provide sufficient force to displace the actuating disk past the retention ring; and

(v) said memory element comprising continuing reflexive force resulting from force manually applied for displacing the actuating disk past the retention ring.

3. The apparatus according to claim 1 wherein:

(i) said source comprises a fluid receptacle which has a volume for liquid containment which is generally greater than the volume of a single push-pause pulse of fluid for purging an associated catheter system;

- (ii) said container comprising a hollow cylindrical vessel comprising a communication pathway via a one-way valve from the source receptacle and another communicating pathway through a second one-way valve to the catheter system;
- (iii) said valve mechanism comprising a plunger sized, shaped and disposed to displace fluid within the vessel, either a liquid drawn from the source or dispensed into the catheter system;
- (iv) said sensor actuator comprising a retention ring disposed at a proximal end of the plunger and plunger rod and associated manual activator button disposed for manually displacing the plunger, a valve actuating disk proximally disposed relative to said plunger and which is disposed proximal to the retention ring until forced there through, said retention ring retarding displacement of the plunger until force upon the plunger yields the pressure which provides the sufficiently turbulent flow of fluid from the container to the catheter system; and
- (v) said implement comprises a button associated with the plunger which is manually depressed to dispense fluid from the vessel, said implement further comprising a memory element which stores energy of plunger displacement during dispensing to return plunger and valve actuating disk to refill the vessel and reset the sensor actuator for a following pressure pulse cycle.

4. The apparatus according to claim 1 wherein:

- (i) said source comprises a fluid receptacle upstream from a pressure providing device, which provides fluid dispensed at a predetermined pressure and flow;
- (ii) said container comprises a vessel which communicates with said pressure providing device through a flow restrictor and with said catheter system through a selected pressure sensitive valve;
- (iii) the valve mechanism comprising the pressure sensitive valve which opens for dispensing fluid from the container to the catheter system at the predetermined pressure and which closes at the other predetermined pressure;
- (iv) said sensing actuator being that portion of the pressure sensitive valve which comprises a valve opening action at the predetermined pressure and which comprises a valve closing action at the other predetermined pressure;
- (v) said implement comprising the pressure providing device, which provides fluid dispensed at a predetermined pressure and flow, acting through said flow restrictor to fill said container and raise pressure within the container to the predetermined pressure; and
- (vi) said memory element comprising a compressible element disposed proximal to a plunger element which is displaced by pressure and flow from the pump through the flow restrictor to accrue controlled and consistent pressure and volume to thereby provide a desired pressure pulse for purging the catheter system.

5. The apparatus according to claim 4 wherein said device comprises a pump.

6. The apparatus according to claim 4 wherein said device comprises tubing which is manually squeezed as the implement to provide the predetermined pressure at which said valve is opened by said actuator to produce the push pause pulsatile flow.

7. A method for providing controlled push-pause pulsatile flow of sufficiently turbulent flushing pressure and flow within a catheter system to purge the line of unwanted residue comprising the steps of:

- (a) providing an apparatus comprising:
 - (i) a source of flush fluid;
 - (ii) a container for retaining a predetermined volume of the fluid;
 - (iii) a valve mechanism interconnected for controllably interrupting fluid flow communication between the container and the catheter system;
 - (iv) a sensing actuator which controls opening and closing said valve mechanism, said sensing actuator opening said valve at a given predetermined pressure which yields the sufficiently turbulent flow of fluid from the container, said sensor actuator further having an operating hysteresis such that the valve mechanism is closed at another predetermined pressure which is lower than the opening pressure;
 - (v) an implement for providing at least enough fluid force to engender the pressure within the container necessary to open the valve mechanism; and
 - (vi) a memory element which stores energy received from the implement and releases the stored energy from action of the implement upon valve opening to provide the turbulent flushing fluid pressure and flow for a period dependent upon time pressure within the container is above the other pressure.
- (b) filling container with fluid from the source;
- (c) providing force via the implement to create a fluid opening pressure within the
- (c) providing force via the implement to create a fluid opening pressure within the container thereby opening the valve at the given predetermined pressure;
- (c) dispensing flushing fluid having predetermined turbulent pressure and flow for a predetermined period into the catheter system; and
- (d) closing the valve once pressure within the container is reduced to a level below the other predetermined pressure.

8. The method according to claim 7 comprising the following specified steps associated with parts in use:

- (a) providing an apparatus wherein:
 - (i) said source comprises fluid contained within a barrel of a syringe;
 - (ii) said container comprises a housing comprising the distal portion of the barrel of the syringe and a plunger affixed to a plunger rod which are disposed for slideable displacement within said barrel, said barrel further comprising a retention ring on the proximal end thereof and said plunger comprising a proximally disposed entry disk associated with said plunger, said entry disk and retention ring cooperating to provide a tactilely discernable stop which prevents inadvertent removal of the plunger from the barrel;
 - (iii) said plunger rod further comprises at least one sensing actuator comprising at least one valve actuating disk proximally disposed relative to said plunger and entry disk, said valve actuating disk being sized and shaped to require controlled and consistent force upon displacement past the retention ring to produce pressure required for turbulent flow when the valve actuating disk is forced through the retention ring;

(iv) said implement comprises said plunger rod which comprises a proximally disposed button upon which force is manually applied to provide controlled and consistent force required to displace the actuating disk past the retention ring; and

(v) said memory element comprises continuing reflexive force resulting from force manually applied for displacing the actuating disk past the retention ring;

(b) affixing the syringe comprising the barrel filled with flushing fluid to the catheter system; and

(c) applying sufficient force upon the plunger rod button to displace one valve actuating disk past the retention ring and reflexively continuing displacement of the plunger rod to provide the desired pressure pulse.

9. The method according to claim 7 comprising the following specified steps associated with parts in use:

(a) providing an apparatus wherein:

(i) said source comprises a fluid receptacle which has a volume for liquid containment which is generally greater than the volume of a single push-pause pulse of fluid for purging an associated catheter system;

(ii) said container comprising a hollow cylindrical vessel comprising a communication pathway via a one-way valve from the source receptacle and another communicating pathway through a second one-way valve to the catheter system;

(iii) said valve mechanism comprises a plunger sized, shaped and disposed to displace fluid within the vessel, either a liquid drawn from the source or dispensed into the catheter system;

(iv) said sensor actuator comprises a retention ring disposed at a proximal end of the plunger and plunger rod and associated manual activator button disposed for manually displacing the plunger, a valve actuating disk proximally disposed relative to said plunger and which is disposed proximal to the retention ring until forced there through, said retention ring retarding displacement of the plunger until force upon the plunger yields the pressure which provides the sufficiently turbulent flow of fluid from the container to the catheter system; and

(v) said implement comprises a button associated with the plunger which is manually depressed to dispense fluid from the vessel, said implement further comprising a memory element which stores energy of plunger displacement during dispensing to return plunger and valve actuating disk to refill the vessel and reset the sensor actuator for a following pressure pulse cycle;

(b) affixing the container to the catheter system; and

(c) applying sufficient force upon the button to displace one valve actuating disk past the retention ring and reflexively continuing displacement of the plunger rod to provide the desired pressure pulse; and

(d) releasing the button to be displaced by the memory element to refill the vessel.

10. The method according to claim 7 comprising the following specified steps associated with parts in use:

(a) providing an apparatus wherein:

(i) said source comprises a fluid receptacle upstream from a pump;

(ii) said container comprises a vessel which communicates with said pump through a flow restrictor and with said IV line through a selected pressure sensitive valve;

(iii) the valve mechanism comprises the pressure sensitive valve which opens for dispensing fluid from the container to the catheter system at the predetermined pressure and which closes at the other predetermined pressure;

(iv) said sensing actuator is that portion of the pressure sensitive valve which comprises a valve opening action at the predetermined pressure and which comprises a valve closing action at the other predetermined pressure;

(v) said implement comprising the pump acting through said flow restrictor to fill said container and raise pressure within the container to the predetermined pressure; and

(vi) said memory element comprises a compressible element disposed proximal to a plunger element which is displaced by pressure and flow from the pump through the flow restrictor to accrue controlled and consistent pressure and volume to provide a desired pressure pulse for purging the catheter system;

(b) affixing the container to the catheter system; and

(c) initiating pumping to fill the container at a rate dependent upon pump output pressure and resistance of the restrictor to fill the vessel until the predetermined pressure is reached;

(d) opening the valve upon reaching the predetermined pressure to dispense fluid into the catheter system at a pressure and flow rate which purges the catheter system of undesired residue with a pressure pulse having a duration ended by closing of pressure sensitive valve at the other

(e) successively repeating steps c thru d until a desired number of pressure pulses has been delivered to the catheter system.

11. A plunger rod which, in combination with an attached plunger of a syringe, is used to displace liquid within a syringe barrel which has a proximally disposed retention ring which provides opportunity for a tactile indication of a discernable stop to indicate a limit of proximal displacement of the plunger and plunger rod within the barrel, said plunger rod comprising:

an elongated stem disposed between said plunger and a proximal end of the stem;

an entry disk proximally disposed relative to the plunger on said stem for interacting with the retention ring;

at least one valve actuating disk proximally disposed relative to said entry disk, said valve actuating disk being sized and shaped to require sufficient force upon displacement past the retention ring to produce pressure required for turbulent flow of liquid dispensed into an attached catheter when the valve actuating disk is forced through the retention ring.

12. The plunger rod according to claim 11 further comprising a second valve actuating disk disposed a more proximal distance from the at least one valve actuating disk to define a pressure pulse volume dispensed from the barrel as the plunger rod is displaced from contact by the at least one valve actuating disk with the retention ring to like contact by the second valve actuating disk.