



(22) **Date de dépôt/Filing Date:** 2014/01/03

(41) **Mise à la disp. pub./Open to Public Insp.:** 2014/09/14

(45) **Date de délivrance/Issue Date:** 2015/12/15

(30) **Priorité/Priority:** 2013/03/14 (US13/828,200)

(51) **Cl.Int./Int.Cl.** *B42D 15/02* (2006.01),
A63H 33/00 (2006.01)


(72) **Inventeurs/Inventors:**
COUGHLIN, SHEILA, US;
BEGIN, ANTHONY, US;
MARSH, ALLISON, US

(73) **Propriétaire/Owner:**
AMERICAN GREETINGS CORPORATION, US

(74) **Agent:** RIDOUT & MAYBEE LLP


(54) **Titre : ACCESSOIRE DE PAQUET-CADEAU MOTORISE**

(54) **Title: MOTORIZED GIFT PACKAGE ACCESSORY**



(57) **Abrégé/Abstract:**

The present invention and related disclosure describes greeting cards with moving elements or devices which are operable to create motion in connection with some portion of the greeting card. The greeting card may include a multi-panel greeting card body



(57) Abrégé(suite)/Abstract(continued):

or a three-dimensional foam greeting card body. At least one movable object is contained upon or within the greeting card body. A sound module having at least one pre-recorded digital audio file saved therein and a motor module are contained and concealed within the greeting card body. One or more switches may be used to activate the sound and motor modules, causing the pre-recorded audio file to play and causing movement of the movable or mobile object. This movement may be up-and-down or "bouncing" motion, spinning or rotational motion, side-to-side motion or any other reciprocating motion.

ABSTRACT

The present invention and related disclosure describes greeting cards with moving elements or devices which are operable to create motion in connection with some portion of the greeting card. The greeting card may include a multi-panel greeting card body or a three-dimensional foam greeting card body. At least one movable object is contained upon or within the greeting card body. A sound module having at least one pre-recorded digital audio file saved therein and a motor module are contained and concealed within the greeting card body. One or more switches may be used to activate the sound and motor modules, causing the pre-recorded audio file to play and causing movement of the movable or mobile object. This movement may be up-and-down or "bouncing" motion, spinning or rotational motion, side-to-side motion or any other reciprocating motion.

MOTORIZED GIFT PACKAGE ACCESSORY

RELATED APPLICATIONS

This application claims priority based on United States Patent Application 13/828,200 entitled "MOTORIZED GIFT PACKAGE ACCESSORY" filed March 14, 2013.

FIELD OF THE INVENTION

The present invention relates to greeting cards and more specifically, to greeting cards having one or more moving elements and functions which create motion.

BACKGROUND OF THE INVENTION

For many years paper greeting cards containing text sentiment and associated artwork have been widely used for celebratory occasions such as birthdays, graduations, weddings, and for other commercial purposes. More recently, greeting cards have been enhanced by incorporating sound and other effects. Sound generating devices have been incorporated into traditional paper greeting cards to increase entertainment value and emotional impact. In some forms, a talking or musical greeting card looks just like a conventional greeting card, except that it includes a hidden sound module with a pre-recorded sound track. Opening the greeting card will automatically turn on or close a switch so that the sound module will play the pre-stored music or dialog and closing the greeting card will automatically open the switch and stop the play of the music or dialog.

There is a need in the art for a greeting card that increases the entertainment value and raises the surprise factor of traditional or sound generating greeting cards that may still be mailed to a recipient and is relatively similar in size and thickness to a traditional paper greeting.

SUMMARY OF THE INVENTION

A first embodiment of the present invention and related disclosure includes a multi-panel greeting card body, a sound module concealed between two panels of the greeting card body, a motor module concealed between two panels of the greeting card body, a mobile object attached to the motor module, a power supply, at least one pre-recorded digital audio file saved within the sound module, and a switch which activates the sound module and the motor module upon opening of the greeting card, activation of the motor module causing movement of the mobile object and activation of the sound module causing the at least one pre-recorded digital audio file to play.

Another embodiment includes a multi-panel greeting card body, a sound module, a motor module, a mobile object comprising two or more die cut pieces that are connected to each other at a connection point such that the two or more die cut pieces are pivotable about the connection point, the mobile object being attached to a connecting rod, the connecting rod being attached to the motor module and the connecting rod being concealed between the greeting card body and the mobile object, at least one die cut piece having a front surface and a back surface, the at least one die cut piece being located proximate to the mobile object, a spring mechanism that is attached at one end to the greeting card body and attached at the other end to the at least one die cut piece, a switch to activate the sound module and the motor module wherein when the sound module is activated, a pre-recorded audio clip is played and when the motor module is activated, the connecting rod and mobile object are set in motion.

Still another embodiment includes a three-dimensional foam greeting card body, a first planar surface attached to a front surface of the three-dimensional foam greeting card body, a second planar surface attached to a back surface of the three-dimensional foam greeting card body, a movable object attached to the first planar surface and connected to a motor module through an opening in the three-dimensional foam greeting card body and the first planar surface, a sound module encased and concealed within the three-dimensional foam greeting card body, a

motor module encased and concealed within the three-dimensional foam greeting card body, a power source, and a push button switch, wherein when the push button switch is pressed, the sound module is activated causing a pre-recorded digital audio file to play, and the motor module is activated causing the mobile object to move or vibrate in an up-and-down motion.

Yet another embodiment of the motion greeting cards of the present invention includes a multi-panel greeting card, a sound module, a motor module having a rotating gear mechanism that when activated turns a circular gear, a mobile object attached to the circular gear of the motor module, a power supply, at least one pre-recorded digital audio file saved within the sound module, and a switch which activates the sound and motor modules module causing the at least one pre-recorded digital audio file to play and causing circular or rotational movement of the mobile object.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a front view of an inside panel of a first embodiment of the motion greeting cards of the present invention.

FIG. 2 is a cutaway view of the motion greeting card of FIG. 1.

FIG. 3 is a front view of an inside panel of a second embodiment of the motion greeting cards of the present invention.

FIG. 4 is a cutaway view of the motion greeting card of FIG. 3.

FIG. 5 is a front view of an inside panel of a third embodiment of the motion greeting cards of the present invention.

FIG. 6 is a front view of the motor module of the motion greeting card of FIG. 5.

FIG. 7 is an exploded view of the inside panel of the motion greeting card of FIG. 5.

FIG. 8 is a perspective view of a fourth embodiment of the motion greeting cards of the present invention.

FIG. 9 is an internal view of the motion greeting card of FIG. 8.

FIG. 10 is a perspective view of the motor of the motion greeting card of FIG. 1 and FIG. 8.

FIG. 11 is a cross-section view of the motor of FIG. 10.

FIG. 12 is a perspective view of fifth embodiment of the motion greeting card of the present invention, in an open position.

FIG. 13 is a tear away view of the motion greeting card of FIG. 12.

FIG. 14 is a perspective view of an alternate embodiment of the motion greeting card of claim 12, in an open position.

FIG. 15 is a tear away view of the motion greeting card of FIG. 14.

FIG. 16 is a perspective view the motorized gift package accessory of the present invention.

FIG. 17 is a perspective tear-away the motorized gift package accessory of FIG. 16.

FIG. 18 is an internal view of the motorized gift package accessory of FIG. 16 from the perspective of arrows 18-18.

DETAILED DESCRIPTION OF PREFERRED AND ALTERNATE EMBODIMENTS

The motion greeting cards of the present invention and related disclosure combine movement with sound and a photograph, illustration or digital art to create a new and novel category of greeting card. Each embodiment features a mobile object that is powered by a small motor and which simulates motions including, but not limited to, dancing, bouncing, hopping, shaking and spinning. Audio including music, voice and/or sound effect may accompany the motion and may be triggered before, after, or simultaneously with the motion effect. The mechanized movement may be synchronized with the audio.

A first embodiment of the motion greeting cards **100** of the present invention contains at least one motor module **10** which causes the movement or “bouncing” of at least one mobile object **14** associated with a greeting card body **12**. As used herein, the term “bouncing” is used to describe up and down motion, side to side motion or any other reciprocating motion. In a preferred embodiment, the greeting card body **12** contains three greeting card panels. A first panel that is connected to a second panel along a first fold line and a third panel connected to the second panel along a second fold line. The first panel serves as the front cover of the greeting card. The third greeting card panel is folded along the second fold line such that it overlies the second panel and creates an internal cavity wherein the greeting card electronics can be concealed. The electronic components, including a sound module **16** and a motor module **10**, are attached to the second panel and the second and third panels are attached, adhesively or otherwise, along at least one edge of the second and third panels. A small opening or aperture may exist on the third panel so that the motor component **10** can be connected to the moving or

“bouncing” object **14** attached thereto, as shown in **FIGS. 1** and **2**. The sound module **16** may contain any and all components necessary to store and produce or emit sound. The motor module **10** may contain any and all components necessary to create movement of the mobile object. Some of the internal electronic components may include, but are not limited to: at least one circuit board **18**; at least one integrated circuit chip **20**; at least one power source **22**; at least one speaker **24**; at least one motor **10**, at least one switch **26** and at least one pre-recorded digital audio clip. The electronic components of the greeting cards described herein are considered to be readily understood and appreciated by one of ordinary skill in the art and are therefore not discussed in detail herein. The motor **10** may be of the type shown in **FIG. 2** **FIG. 10** and **FIG. 11**, having a rotating arm **28** or shaft, which may be an offset shaft which creates oscillatory motion upon rotation of the shaft by the motor. A lightweight movement mechanism **30** is attached at one end to the rotating arm **28** of the motor **10** and at an opposite end to the greeting cards mobile object **14** via an attachment mechanism **66**. In a preferred embodiment, the mobile object **14** is die cut shape of a person, animated character, animal or any other object having a substantially planar front and back surface so that it will fit within the panels of the greeting card **100** without substantially increasing the thickness of the greeting card **100**. The mobile object **14** must be connected to the movement mechanism **30** which is in turn connected to the rotating arm **28** of the motor **10** so that when the motor **10** is activated, the mobile object **14** moves or “bounces”. The motor **10** may be activated upon the user opening the greeting card **100**. A slide switch **26** may be located across the first fold line between the first and second greeting card panels such that when the greeting card is opened, the electronic components are activated. The slide switch **26** may activate both the pre-recorded sound clip and the motor **10** so that when the greeting card **100** is opened, the pre-recorded sound clip will play along with the movement of the mobile object **14** contained within the greeting card **100**. The sound clip, mobile object **14** and greeting card artwork may all be coordinated with a particular theme or occasion. The movements of the mobile object **14** may be synchronized with the audio clip such as, for example, by operation of the motor **10** while the sound module **16** is turned on, or by motion of the mobile object **14** in synch with a song, music or sound clip played by the sound module **16**. Alternatively, the greeting card **100** may contain separate switches such that the sound and motion are not activated simultaneously. For example, the sound may be triggered by a slide

switch 26 upon opening the greeting card 100. Once the greeting card 100 is opened, a push button or other switch mechanism may be used to activate the motion. In an alternate embodiment, where the mobile object 14 is located on the outside of the greeting card 100, such as on the front face of the card, the motion and/or sound may be triggered by a push button mechanism also located on the front face of the greeting card 100.

In a second embodiment, shown in **FIGS. 3 and 4**, the greeting card 200 contains a motor module 32 which allows one or more mobile objects 34 associated with a greeting card body 36 to spin or rotate. The greeting card body 36 configuration may be the same as described above with regard to the first embodiment, having three greeting card panels attached along a first and second fold line. The electronic components are attached to the second panel and concealed by the overlapping third panel which is attached to the second panel along at least two edges of the second and third panels. The third panel may contain a small hole or aperture to connect the motor 32 to a mobile object 34. The motor 32 may be of the type shown in **FIG. 4**, having a rotating gear mechanism 37 that when activated turns a circular gear 38. A connecting rod 40 is located between and connects the gear 38 and the mobile object 34 (through the hole or aperture in the third panel of the greeting card). As the gear 38 is rotated by the gear mechanism 37, it in turn causes the moveable object 34 to rotate or “spin”. A slide switch 26 may activate a pre-recorded sound clip and the motor 32 upon opening of the greeting card 200. The sound and motor 32 may alternatively be activated by separate switches. The moveable object 34 may be contained on the inside of the greeting card 200 or on the outside front cover of the greeting card 200. The mobile object 34 may be a die cut shape such as a fan, a wheel or any other rotating object.

In a third embodiment, shown in **FIGS. 5 and 6**, the motion greeting card 300 of the present invention contains at least one motor module 42 that is associated with at least one body of a character 44 which, when activated allows the body 44 to move or to “dance” to the music or sound contained within the audio module. The greeting card body 46 may have three panels, as described above, with the second and third panels overlapping and concealing the greeting card electronics and related circuitry. The third panel may have a small opening or aperture which allows the motor 42 to be connected to the mobile object 44. The front panel may also contain a cut-out portion in the shape of the character head 48 so that it may be seen without opening the

greeting card 400. The motor module 42 may be of the type shown in FIG. 6, having a rotating gear mechanism 37 that when activated turns a circular gear 38, which is in turn attached to a connecting rod 40. The mobile object 44 is attached to the other end of the connecting rod 40. The character body 44 contains several separate and distinct pieces or elements representing the arms 52, legs 54 and main body 44 of the character. Each arm 52 and leg 54 is made from two separate die cut pieces. Each of the limbs 52, 54 are connected together and to the character using fiber optic strands so that the body 44 and limbs 52, 54 may move or pivot freely about the attachment point while moving in a reciprocating motion, giving the illusion that the character is dancing. The character head 48 is separated from the body 44 and is connected to a spring mechanism 68 that connects the character head 48 to the front surface of the third greeting card panel 46 and projects the character head 48 out beyond the position of the body 44. The character head 48 projects through the front of the greeting card through the cut-out contained in the first card panel. When the greeting card is opened, the audio and motor modules 42 are activated and the character body 44 and component parts of the character body move in a reciprocating motion and appear to dance to the sound or music played by the audio module.

In a fourth embodiment, shown in FIGS. 7 and 8, the motion greeting card 400 of the present invention contains a motor module 56 that is associated with a three-dimensional card body 58 having one or more moving parts and designed as a character which, when activated moves in a reciprocating motion, thereby appearing to talk or sing. In this embodiment, the greeting card body 58 is substantially made of foam having a three-dimensional character printed on the front face of the card. When a user presses a push button 60 located on the front face of the greeting card, the audio and motor modules 56 are activated, causing the one or more moving parts to move in a reciprocating motion with respect to the greeting card body 58 thus the making it appear as though the character is talking or singing. A first greeting card panel is attached to the front surface of a foam encasement. The foam encasement houses and conceals the electronic components, including the sound and motor modules 56, of the greeting card 400. A second greeting card panel is connected to a third greeting card panel along a first fold line. The back surface of the second greeting card panel is attached to the back surface of the foam encasement such that the first and second greeting card panels and the foam encasement (which is located between the first and second greeting card panels) serves as the front cover or page of the

greeting card and the third greeting card panel serves as the back page or panel of the greeting card. A separate fourth panel is attached via an attachment mechanism 66 to the front panel and serves as the mobile object 62. The panel 62 may be shaped like a mouth or may be shaped to correspond to the artwork printed on the front panel of the card such that when the motor module is activated, thereby moving the fourth panel in a reciprocating motion, it gives the illusion that the character is talking or singing. The fourth panel 62 may contain additional three-dimensional features such as moving eyes 64, etc. The motor 56 may be of the type shown in FIGS. 10 and 11 and described above as having a rotating arm 28 and movement mechanism 30 that is attached to the mobile object 62 or fourth panel 62 via an attachment mechanism 66.

Similarly, another embodiment, shown in FIGS. 12 through 15, may include a three-dimensional card body 72 made of foam or other lightweight foam-like material. The three-dimensional card body 72 may have a front surface, a back surface opposite the front surface, and a perimeter surface therebetween. The front surface of the card body may contain a front cover material 71A and the back surface of the card body may contain a back cover material (not shown). The front 71A and back cover material may be paperboard, cardboard, or other such material. The perimeter surface may remain uncovered and visible between the front and back cover material or may optionally be covered as well. A sound module operative to store and playback at least one audio file is contained within the three-dimensional card body 72. A motor module 75 operative to effect movement of a movable object is also contained within the three dimensional card body 72. A mobile object 73 is connected to the motor 75 through an opening in the three-dimensional card body 72 and the front cover material 71A. In a preferred embodiment, the mobile object 73 is a die cut shape (such as the pretzel shape shown in FIGS. 12 and 13), although other items can be used as a mobile object such as a plastic molded figurine or any other item having a relatively low profile. The mobile object 73 may also contain added embellishments or decorative effects attached thereto. A greeting card sentiment panel 74 may be attached along a fold line to either the front 71A or back cover material, thereby creating a traditional two-panel greeting card. The sentiment panel 74, along with the front 71A and/or back cover material may contain various text greetings or messages and printed artwork, graphics, photographs, or any other printed indicia. The sentiment panel 74 and front 71A and back cover material may also contain three dimensional embellishments attached thereto. In one

example, shown in **FIGS. 12 and 13**, the sentiment panel **74** is attached to the front cover material **71A** such that the sentiment panel **74** serves as the front cover of the greeting card and is folded over the three-dimensional card body **72**. The mobile object **73** may, as in the embodiment shown in **FIGS. 14 and 15**, be contained between the sentiment panel **74** and the front cover material **71A** (attached to the motor through the front cover material) so that when the user opens the greeting card by moving the sentiment panel **74** away from the three-dimensional card body **72**, the mobile object **73** would be visible. In another embodiment (**FIGS. 12 and 13**), the mobile object may **73** be attached to the motor **75** through an opening in the front cover material **71A** but be visible from the front of the greeting card and not located between the sentiment panel **74** and front cover material **71A**. In this case, the three-dimensional card body **72** may be larger in size than the sentiment panel **74** such that the sentiment panel **74** only covers part of the three-dimensional card body **72**. The sound and motor modules may be activated upon opening the greeting card by moving the sentiment panel **74** away from the three-dimensional card body **72**. In a preferred embodiment, a magnetic switch **76** may be located within the sentiment panel **74** and also beneath the front cover material **71A** such that when the sentiment panel **74** is in a closed position, the magnets **76A, 76B** are in contact, thereby breaking the electrical circuit. When the greeting card is moved to an open position by moving the sentiment panel **74** away from the three-dimensional foam card **72** the magnets **76A, 76B** break contact and allow the electrical circuit to be completed, thereby providing power to the sound and/or motor modules. While this embodiment has been described as having a magnetic switch or trigger, other switch mechanisms can be used such as slide switches, light sensitive switches, touch sensitive switches, pull string switches, or any other suitable switch. When a user opens the card **70**, the magnetic switch **76** activates the sound and motor modules so that the sound module initiates playback of the at least one audio file and the motor module moves the motor **75** to effect movement of the mobile object **73**. As discussed above with respect to the other embodiments, the movement of the mobile object **73** may be in an up-and-down, back-and-forth, circular, vibrational, or any other conceivable motion.

Another embodiment, shown in **FIGS. 16 through 18**, is a motorized gift package accessory **80** with internal sound and motor modules. The motorized gift package accessory **80** can be used to adorn a gift package while adding increased entertainment value thereto. A gift

packaging bow **82** or other decorative effect is attached via an attachment mechanism (as described above with respect to the aforementioned embodiments) to a motor **84** which is contained and concealed within a foam housing **86** with a push button switch **88** used to activate the motor module causing movement of the bow **82** and the sound module causing playback of at least one audio file contained in memory within the sound module. The bow **82** portion of the motorized gift package accessory **80** may be a typical decorative bow having various interlaced ribbons or other material with various knots, loops, ties, twists, ringlets, loose ends, or other decorative arrangements. The bow **82** may also contain additional adornments **83** such as die cut shapes, moving googly eyes, or any other decorative accessory. The bow **82** is connected at one end to an attachment arm or mechanism **85** which is also attached at an opposite end to a motor **84**. The motor **84**, when powered, causes movement to the bow **82**. The motor **84** may be of the type described above and shown in **FIGS. 6** or **10** or any other miniature motor type capable of producing any type of reciprocating motion. The motor **82** and sound modules are contained and concealed in a base structure **86**. The sound module is operative to store and playback one or more digital audio files. The base structure **86**, in a preferred embodiment, is made of foam, although any other lightweight material can be used. In the preferred embodiment, the base **86** is circular shaped having two separate circular foam pieces attached together using glue or other adhesive. Each of the foam pieces may have openings or cavities therein to accommodate the electronic and other components of the sound and motor modules. These components may include, but are not limited to: a circuit board **18**, an integrated circuit, a power source **22**, a speaker **24**, a motor **84**, and any other component which is required or which facilitates or improves storage and playback of digital audio and physical movement of a moveable object. These components are well known to one having skill in the art. A thin, planar paper or paper-like material **81** may be attached, adhesively or otherwise, to the outward planar surfaces of the two foam pieces which comprise the base structure **86**. The planar material **81** located at the bottom of the base structure **86**, opposite the bow **82**, may contain an adhesive thereon with removable backing layer to facilitate attachment of the motorized gift accessory **80** to a gift package or other item. Although the base structure **86** is described as being two separate, circular pieces of foam, it may alternatively be a single piece of foam with one or more cavities therein and it may take any conceivable shape. In a preferred embodiment, the base structure **86** may

have a diameter of between 3 and 6 inches. In a preferred embodiment, a push button switch 88 controls activation of both the sound and motor modules. The push button 88 is enveloped within a paperboard or other similar material 89 which conceals the push button 88 and the wires connecting the push button 88 to the internal electronic components. The material 89 surrounding the push button 88 may be the same or different from the material encasing the wires. The material 89 over the push button 88 may contain printing thereon instructing the user to "Press Here"; "Make Me Sing"; "Make Me Dance" or other phrase instructing the user where to press to effect movement of the bow 82 and to initiate playback of audio. Pressing the button 88 will initiate playback of the one or more pre-recorded digital audio saved within the sound module while also powering the motor module causing movement of the bow 82. The bow 82 may move in a circular, twisting, back and forth, up and down, vibrating or other type of motion, while the audio plays simultaneously. The audio or movement may automatically stop after a certain amount of time has passed or pressing the push button 88 may be required to stop the audio and movement of the bow 82. While the motorized gift package accessory 80 has been described herein as a bow 82 and in terms of a particular size and shape, other decorative structures in other sizes or shapes have been contemplated and are considered to be within the scope of the present invention.

Although the switches described herein with respect to the examples given are described as being slide switches or push-button switches, the use of other types of switches is considered to be within the scope of this invention. Alternate switch mechanisms include, but are not limited to: light activated switches; sound activated switches; touch sensor switches, magnetic switches; and contact arm switches.

All variations of the motion greeting cards, including those described above, may additionally include a microphone and related electronics that would allow a user to record and save one or more personalized messages to be played before, during, after or in place of a pre-recorded sound clip. The personalized message may be played before a pre-recorded audio clip to, for example, introduce the pre-recorded audio clip or may be played after the pre-recorded audio clip to, for example, leave a personalized message to end the audio experience. The personalized message may also be played simultaneously with the pre-recorded audio clip wherein the user may sing-along to a pre-recorded song or instrumental audio clip, karaoke style.

The personalized message may be triggered by the same switch mechanism that triggers the pre-recorded audio file or by a separate switch which may be a slide switch, a push button, a light-activated switch, motion sensor switch, or any other type of switch. The sound module may also include voice changing capabilities wherein a user may record a personalized message and then choose to alter the recorded voice message by increasing or decreasing the pitch or by speeding up or slowing down the cadence of the message. The sound module may also have the ability to store more than one personalized messages which can be played, in any combination before, during, after or in place of a pre-recorded audio clip. The additional messages may be triggered by the same trigger or by multiple trigger mechanisms.

Other variations of the motion greeting cards may include the addition of lights and additional pre-recorded digital audio files or additional mobile objects.

It will be appreciated by persons skilled in the art that numerous variations and/or modifications may be made to the invention as shown in the specific embodiments without departing from the spirit or scope of the invention as broadly described. The present embodiments are, therefore, to be considered in all respects as illustrative and not restrictive. Other features and aspects of this invention will be appreciated by those skilled in the art upon reading and comprehending this disclosure. Such features, aspects, and expected variations and modifications of the examples are clearly within the scope of the invention where the invention is limited solely by the scope of the following claims.

CLAIMS

1. A motorized gift accessory comprising:
a bow or ribbon;
a motor module operative to cause movement to the bow or ribbon;
a sound module operative to store and playback at least one audio file;
a base structure which contains and conceals the motor and sound modules, the base structure having a backing layer on a bottom surface thereof which may be removed to expose an adhesive surface;
a press button switch which controls activation of the sound and motor modules.
2. The motorized gift accessory of claim 1, wherein the base structure is made of foam.
3. The motorized gift accessory of claim 2, wherein the base structure comprises two pieces of foam attached to one another.
4. The motorized gift accessory of claim 1, wherein pressing the press button switch a first time causes movement of the bow or ribbon and playback of the at least one audio file.
5. The motorized gift accessory of claim 4, wherein pressing the press button a second time ceases movement of the bow or ribbon and playback of the at least one audio file.
6. The motorized gift accessory of claim 4, wherein movement of the bow or ribbon and playback of the at least one audio file lasts for a predetermined period of time before ceasing.
7. The motorized gift accessory of claim 1, wherein the press button switch is located outside of the base structure.

8. A motorized gift accessory comprising:
 - a gift bow;
 - a motor module operative to cause movement to the gift bow;
 - an attachment arm which connects the gift bow to the motor module in a perpendicular manner;
 - a base structure comprising a substantially planar top surface, a substantially planar bottom surface opposite the top surface, a perimeter surface which extends between all perimeter edges of the top surface and all perimeter edges of the bottom surface and a cavity therein for storage of the motor module;
 - a push button switch which is separate from the gift bow and which extends outward from the base structure and causes activation of the motor module;
 - wherein the gift bow extends upward from and perpendicular to the base structure.
9. The motorized gift accessory of claim 8 further comprising a sound module operative to store and playback at least one audio file.
10. The motorized gift accessory of claim 8, wherein the attachment arm is connected to the gift bow through an opening in a top surface of the base structure.
11. The motorized gift accessory of claim 8, wherein the base structure contains a backing layer on a bottom surface thereof which can be removed to expose an adhesive surface.
12. The motorized gift accessory of claim 8, wherein the base structure contains a planar sheet on a top surface thereon and a bottom surface thereof.
13. The motorized gift accessory of claim 8, wherein the push button switch is located outside of the base structure.
14. The motorized gift accessory of claim 9, wherein the push button switch also causes activation of the sound module.

15. The motorized gift accessory of claim 7, wherein the push button switch works as a toggle wherein pressing a first time causes activation of the motor module and pressing a second time causes deactivation of the motor module.
16. A motorized gift accessory comprising:
 - a decorative bow;
 - a base structure;
 - a motor module located within the base structure and attached to the decorative bow through an opening in the base structure;
 - a switch for activating the motor module which causes movement of the entire decorative bow, the switch extending outward from the base structure;
 - wherein the decorative bow is operative to be attached to a package via the base structure, the decorative bow being in a perpendicular position to the package.
17. The motorized gift accessory of claim 16 further comprising a sound module operative to store and playback at least one audio file.
18. The motorized gift accessory of claim 17, wherein the switch also activates the sound module.
19. The motorized gift accessory of claim 16, wherein the switch is a press button switch.
20. The motorized gift accessory of claim 16, wherein the base structure is made of foam.




Fig. 2




Fig. 1




Fig. 3




Fig. 4




Fig. 5




Fig. 6

4/12






Fig. 7

5/12

**Fig. 8****Fig. 9**




Fig. 11




Fig. 10

7/12




Fig. 12

8/12




Fig. 13

9/12







Fig. 14

10/12





12/12

**Fig. 18**

