



US008172017B2

(12) **United States Patent**
Ren

(10) **Patent No.:** **US 8,172,017 B2**
(45) **Date of Patent:** **May 8, 2012**

(54) **CIRCUMFERENTIAL MOVEMENT DEVICE**

(75) Inventor: **Wen Lin Ren**, Wuhan (CN)

(73) Assignees: **Wuhan Runlin Science**, Wuhan (CN);
Technology Development Co., Ltd.,
Wuhan (CN)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 484 days.

(21) Appl. No.: **12/343,483**

(22) Filed: **Dec. 24, 2008**

(65) **Prior Publication Data**

US 2009/0200093 A1 Aug. 13, 2009

(30) **Foreign Application Priority Data**

Jan. 21, 2008 (CN) 2008 2 0002487 U

(51) **Int. Cl.**
B60K 6/08 (2006.01)

(52) **U.S. Cl.** **180/65.21; 180/210**

(58) **Field of Classification Search** 180/165,
180/2.1, 2.2, 210, 215, 219, 220, 65.1, 301,
180/302, 65.21

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,968,851 A *	7/1976	Windt	180/117
4,011,919 A *	3/1977	Groeger	180/190
5,435,404 A *	7/1995	Garin, III	180/6.5
7,017,696 B2 *	3/2006	Pal	180/218
7,413,038 B2 *	8/2008	Mulhern et al.	180/22
2001/0042650 A1 *	11/2001	van den Berg	180/218
2001/0047902 A1 *	12/2001	Berg	180/219

FOREIGN PATENT DOCUMENTS

CN	1569495 A	1/2005
CN	1634745 A	7/2005



* cited by examiner

Primary Examiner — John Walters

(57) **ABSTRACT**

The invention relates to a circumferential movement field, including all circumferential movement devices such as transport vehicle, toy vehicle, space vehicle, blender etc, especially for energy-saving vehicles utilizing force of gravity. The energy-saving vehicle utilizes force of gravity as driving force, the vehicle body connects with the wheel by swing structure method or eccentric swing structure to utilize force of gravity more efficiently. The invention also provides solutions about two-wheel gravitational vehicle and multi-wheel vehicle and train connected by integrated vehicles or two-wheel vehicles.

3 Claims, 5 Drawing Sheets






Fig1




Fig2




Fig3




Fig4




Fig5




Fig6




Fig7




Fig8




Fig9




Fig10




Fig11




Fig12





Fig 13



A-A Fig 14




Fig 15




Fig 16




Fig 17




Fig 18




Fig 19




Fig 20




Fig21




Fig22




Fig 23




Fig 24




Fig 25




Fig 26




Fig 27




Fig 28




Fig 29




Fig 30




Fig 31




Fig 32




Fig 33




Fig 34




Fig 35




Fig 36




Fig 37




Fig 38

CIRCUMFERENTIAL MOVEMENT DEVICE

FIELD OF THE PRESENT INVENTION

The present invention relates to circumferential movement, especially to all circumferential movement devices utilizing force of gravity, such as transport vehicles, toy vehicles, space vehicles, blenders etc.

SUMMARY OF THE PRESENT INVENTION

The object of the present invention is to provide circumferential movement devices with new structures and new driving methods, including vehicles with new structures and corresponding driving methods, braking methods and steering methods etc. The devices can utilize force of gravity sufficiently and shall be safe, saving and high efficient. The device can be used in all circumferential movement devices such as transport vehicle, toy vehicle, space vehicle and blender and so on.

The disclosure of this invention is introduced as following.

1. Integrated vehicle. The integrated vehicle includes wheels and vehicle body. The vehicle body can be shaped as cylinder, square or polygonal canister. The vehicle body shall keep a certain distance from the road surface so as to ensure the movement of the vehicle. Wheels are installed at the middle or two ends of the vehicle body and are rotated with the vehicle body at same time in movement.

Such vehicle may has one wheel and installed at the middle of the surface of the vehicle body; or such vehicle has one wheel only, the width of tire reaches to $\frac{1}{3}$ of the width of the vehicle body or above; or the tire shall include tire and part of rim. Such tire shall include all kinds of tires of related Technology.

The tire surface shall be in sufficient width to ensure the vehicle drives on road placidly. Or the whole vehicle is just a wheel. Or several wheels can be installed on the surface of the vehicle.

Or, two or two group wheels are to be installed at two ends of the vehicle body. The two ends of the body shall include the surfaces of two ends and the positions near the two ends.

One tire can be comprehended as one group tires, i.e. one tire can be substituted by two or above tires to play the role of one tire. Tire is installed on the body and is rotated with the body as well as the cargo inside the vehicle together.

The wheel includes tire and rim; here, rim includes all parts inside the tire of the wheel. But, the wheel which is installed on the integrated vehicle shall have tire only, or has tire and part of rim. The vehicle body can replace part or all rim. The wheel may include tire and part of rim.

No driving force is needed when the vehicle drives downgrade, only the driving force greater than zero is needed when the vehicle drives on flat ground theoretically, when upgrade, more energy can be saved than other vehicles with related structure due to it can utilize the gravity force better. Such vehicle is comparatively suitable to carry water, oil, cement, sand, slurry, coal, and ore, etc, and there are inlet and outlet of cargo.

A trailer rack can be installed on the integrated vehicle to be used as a trail car, the integrated vehicle is rotated relative to the trailer rack on its axis, and the trailer rack connects with the motive vehicle, the trailer rack moves on by dragging of the integrated vehicle. The integrated vehicle can be used as boxcar of a train. Several integrated vehicle with the trailer tracks can be run as a train, such train shall at least include a head and several boxcars with trailer racks and pothooks, these boxcars move and be dragged by the head.

The integrated vehicle may be driven by the engines and transmission device with related technology. There is a trailer rack on the vehicle body, the trailer rack shapes as a frame and carries one or more trailer wheels. The trailer wheel adopts related technology. An engine is fixed on the trailer rack and a transmission device is fixed on the vehicle body to receive the transmission force from the engine. For example, a rubber roller with related technology transmits the driving force to the integrated vehicle; an electromotor is fixed on the top of the trailer rack, a rubber roller is on the axis of the electromotor, there is a rubber loop on the vehicle body to receive the friction from the rubber roller, the rubber roller drives the rubber loop and pushes the vehicle to move together.

Gear wheel or gear hole driving with related technology are also be available. China Patent application number 200410030581.x <A Sort of Vehicle>, FIG. 54-59 shows a kind of gear hole driving. It is also available to adopt remote control method to operate the integrated vehicle—unpiloted driving.

2. Swing structure vehicle. The swing structure vehicle includes a vehicle body, at least one wheel, and a swing bar for connecting the vehicle body and the wheel. There is an axis on the vehicle body and an axis at the centre of a wheel, one end of the swing bar connects with the body axis, the other end of the swing bar connects with the wheel axis. The body axis can also connect with the “dolly-car” at the bottom of the wheel, dolly-car “dolly-car” is attributed to a related technology and can be found in <A Sort of Vehicle>, China Patent number 200410030581.x, viz. a “dolly-car” in “large wheel driving method”. The vehicle body with swing structure is capable to match up the flirt of the wheel as like as pendulum and swing. As long as the barycenter of the vehicle body is not higher than the circle centre of the wheel, the swing structure can keep the vehicle in balance and stabilization.

The advantage of it can move the weight of the vehicle to the frontage of the gravity surface of the wheel and produce driving force. The position of the vehicle moves ahead can reduce the pressure to the vehicle body and change the force direction, to generate the component of forces and save energy.

The extent of swing can be controlled to keep it fore-and-aft, or only keep it go forwards, or limit the extent when it swings fore-and-aft: preset caging position on the body, swing bar or wheel, the caging device can be a stake, step or spring and set it at the side of swing bar, swing bar will be held up at a certain angle.

Another swing structure is use a swing bar with a bend and concave structure as a crank shaft in an internal-combustion engine to integrate with the axles of the body, swing bar and wheel within the swing structure. The vehicle body installs inside the concave and can swing fore-and-aft, more the space of the concave, and more the swing radius of the body. The sufficient wheel diameter in such structure is necessary to ensure the swing radius.

A swing bar can be a shaft, or a wobble tray. The wobble tray can be shaped as a circle or semicircle, or anomalous to play a role of swing bar. A swing bar can decline the barycenter of the body and increase its stability.

The stress point of the force of an engine can be at the wheel fringe. “Wheel flange transmission” and “large wheel transmission” with related technology can be driven on the top of a wheel, refer to China Patent application 200410030581.x <A Sort of Vehicle> for details of “Wheel flange transmission” and “large wheel transmission”. The vehicle body can be dragged as like as a trailer car, the body drives the swing bar, the swing bar drives the wheel and push the vehicle moves on.

3. Eccentric swing structure—the diameter of the vehicle body axis is smaller than that of axis hole of the wheel at the circle centre. In other words, the diameter of the wheel axis hole at the circle centre is greater than that of the vehicle body (the vehicle body axis here can also be swing bar axis). The body axis connects with the wheel axis hole and is located at the fringe of the bottom of inner loop of the axis. The body axis can change its position in the axis hole when in movement, it can be departed from the gravity surface and swing to the direction of forward, thus, the gravity force changes to the driving force.

Axis hole means the hole at the inner loop of the axis. The connection method between the vehicle body axis and the axis hole can use related technologies as welding, affixing and covering. The method of covering: connect the vehicle body axis with the inner loop cover which matches up to the inner loop of the axis hole, the inner loop cover shapes like a round cake, and fix it into the inner loop. The vehicle body axis is located at the fringe of the bottom of inner loop of the axis, i.e. the bottom fringe of the inner loop.

Such structure is “eccentric swing”, or “eccentric axis”. Eccentric swing can be used in the connection of swing, also can be used in all circle movements except the swing connection, e.g. wheel axis, to save energy by its gravity force.

4. Coaxial vehicle—also can be named as “two-wheel gravitational vehicle”, “two-wheel vehicle” or “sole-wheel vehicle”. A coaxial vehicle can have two or two group coaxial wheels which are located in the two sides of the body or bottom. Wheel runs relative to the vehicle body, and engine installed on the vehicle body can be regarded as the passenger seat. The wheel of coaxial vehicle in this invention contains the wheels with same axial direction. Coaxial means two or two group wheels share with same axis. Same axial direction means two or two group wheels with different axes are within the same straight line and same axial direction. Two sides as above said means the surfaces of two profiles of the body and the positions near to the two ends of the body.

An axis at the circle centre of the wheel connects with the vehicle body, wheel runs relative to the body, the body does not rotate. The wheel of coaxial vehicle can be larger; its diameter is similar with the height of the body. A distance of wheel radius shall keep from the ground to convenient to design sufficient space and height for the vehicle body; the vehicle body does not touch the ground when it in swing. Such vehicle may carry an anchoring plate which can be ascending and descending to act as a brake.

A coaxial vehicle may have only one wheel; such wheel is rather wide and is located at the bottom of the body. The vehicle body connects with the wheel axis and is located on the top of the wheel. “Large wheel transmission” can also be adopted to connect the vehicle body with a “dolly-car”.

A coaxial vehicle contains the wheels with the same axial direction. The wheels with the same axial direction can be in different axial positions, i.e. the wheels with the same axial direction can be disposed at front and rear positions, not in a same straight line. Such structure can increase the stability of the vehicle body, but the utilization of the gravity force is not so good.

There are engine and transmission device on the vehicle body, the method of the impetus transmission: transmit the engine driving force to the position on the vehicle body above the wheel first, then transmit to the top fringe of the wheel and drive the wheel running. Or, transmit the strength of human to the top position of the wheel of the vehicle body first, then drive the wheel. For example, lay an electromotor on the top position of the wheel corresponding to the body, by transmis-

sion device or rubber roller, the engine drives the wheel running. Other methods also can be adopted, such as to use wheel engine to drive.

In the structures as described above, an electromotor can also be laid at the bottom of the vehicle body, by transmission device, to transmit the engine driving force to the wheel. It is better to dispose the human, cargo and the vehicle facilities to the bottom of the body to decline the gravity centre and ensure the stability and utilize the gravity force perfectly.

It is also possible to lay the barycenter of the vehicle body on the circle centre of the wheel so as convenient to use swing structure; such structure shall be equipped with a supplementary wheel. Such supplementary wheel shall be installed at the front or rear position of the vehicle body and to play a balance role and prevent the overturn of the vehicle body. Such vehicle belongs to “multi-wheel vehicle”.

To drive a coaxial vehicle by human power, it is only need to transmit the human power to the top of the wheel to realize “wheel flange transmission” or “large wheel transmission” by related technology. For example, by a chain and a gear of bicycle, or transmission shaft and gear, or industrial strap and strap wheel, etc, to transmit the human power to the stress point on the top of the wheel to complete the transmission by human power. The driving of engine can also adopt above structure.

The differences of this structure with <A Sort of Balanceable Vehicle> of patent No.: 200310112992.9 are the driving force and transmission method. This structure provides with a technical resolution of engine driving, transmit the driving force of the engine or human power to the top or the fringe of the wheel, sufficiently use gravity and belongs to “wheel flange transmission” or “large wheel transmission”.

The stress point of “two-wheel vehicle” is same as the force point of a lever and stress the strength to the top of the wheel; the position wheel touch the ground is same as the pivot of a lever, the pivot is at the ground; the weight of the body is at the circle centre or at the bottom of the wheel, is same as the stress point of a lever at the circle centre or the bottom of the wheel, such structure matches up the 3rd law of Circumferential Law, the energy and power can be saved. The weight of the body (include passenger and cargo) is disposed at the bottom of the body, by the role of swing, half and more gravity can change to driving force and therefore save power and energy.

The driving force of an engine stresses on the top of the wheel by the top of the vehicle body, the top of the wheel produces a counter force to the top of the vehicle body, the bottom of the vehicle body will swing by the leverage, in this way, most of the gravity of the body will transmit to the front of the gravity surface of the wheel, i.e. to the forward direction, more than half of gravity of the vehicle becomes the driving force to drive the wheel.

Compressed air can also be used as the driving force, there is a huff nozzle on the top of the vehicle body, the baffle plate, or lamina, or a concave around the wheel will receive the puffing air, puff the air to the top of the wheel to drive the wheel running by the counter force of pulling air. To use compressed air as the driving force can be adopted according to related technology.

An jet engine can also be installed on the vehicle body, such as the jet aircraft and jet car to puff the air forward the rear of the body and drive the vehicle running and as well as compressed air.

The compressed air tank and engine can be fixed in the wheel and run together with the wheel, air switch controls the huff nozzle, huff the air backward when the wheel rotate to the peak and drive the vehicle go forward. Huff will halt when the wheel is over the peak.

5

The compressed air tank shapes like circle pipe or round cake which is suitable to the shape of tire, it shall be installed outside the steel rim or the position with the same axial direction outside the wheel. There are several huff nozzles with the valves around tank, the valves shall open only the wheel runs to the peak position and drive the vehicle forward.

The structure of huff switch: there is an elastic cover on the huff nozzle on the wheel, the cover can run around the axis, a baffle plate at the peak position of the wheel, when one huff nozzle runs to the peak position, baffle plate pull out the elastic cover and the high pressure air huff burst out to produce thrust. The elastic cover closes again when the nozzle runs over the baffle plate. Next nozzle will repeat the above movement. Baffle plate can be fixed on the wheel axis.

The second structure of huff switch: there is an elastic piston at the huff nozzle; the piston connects with a pull staff, the pull staff runs around the axis, and there is a baffle plate at the peak position of the wheel, when one huff nozzle runs to the peak position, baffle plate pull out the pull staff of the piston and the high pressure air huff burst out to produce thrust. The elastic cover closes again when the nozzle runs over the baffle plate. Next nozzle will repeat the above movement. Baffle plate can be fixed on the wheel axis.

The third structure of huff switch: there is a magnet at the position of baffle plate, when a huff nozzle runs to the peak position, the attraction of the magnet opens the elastic switch, high pressure air huff out and produce thrust, the elastic cover closes again when the nozzle runs over the baffle plate. Next nozzle will repeat the above movement. Baffle plate can be fixed on the wheel axis again.

The huff nozzle can be controlled by automobile and all related technology, such as gas-jet control technology of internal-combustion engine, ignition technology and touching-switch technology, etc. all relative Plea Know technology can be adopted.

The intermittent blowing, or stroke blowing can also be adopted, blow the air at each interval, e.g. per second. Continuous blowing produces smaller inertial counter force, while intermittent blowing can increase counter force and enhance the effectiveness. Of cause, the air-powered engine with related technology can be adopted as the impetus for this vehicle.

5. Multi-wheel gravity vehicle—means the gravity vehicle with two or more wheels. There are two coaxial wheels on multi-wheel gravity vehicle, including front and rear supplementary wheel. The supplementary wheel are installed at the front and rear of the body to play the role of auxiliary movement, balance and stability, furthermore, equipped with the flex function upward and downward as well as the function of universal wheel. Automobile and train with related technology can be changed to multi-wheel gravity vehicle. Any vehicle adopts the swing connection and/or eccentric swing structure of this invention can also use “wheel flange transmission” or “large wheel transmission”, which is a kind of multi-wheel gravity vehicle. The diameter of the wheel of this kind vehicle is rather small and can be similar or same with the wheels of the vehicles with related technology.

For example, a car with related technology has four wheels, change wheels into swing connection, or only change the rear two wheels into swing connection, adopt “wheel flange transmission” or “large wheel transmission”, the impetus of engine stresses on the top of the wheel and the top of the wheel produce a forward counter force to the body, more than half of the body weight changes to impetus and together with the engine power to drive the vehicle.

For multi-wheel vehicle, each wheel can connect with the body swing, or only part of wheels connects with the body

6

swing, e.g. only two rear coaxial wheels in a tricycle connect with the body swing, the front wheel does not. Both multi-wheel and dual wheel gravity vehicles adopt Circumferential Law to utilize gravity.

if adopt small wheel, the radius of the wheel is small accordingly, the vehicle body shall near to the ground and also less the swing extent of the body, this problem can be resolved by related technology “large wheel transmission”. Connect the body with the small swing in large wheel, there is a rack on the “dolly-car”, the rack can be same height with large wheel or higher. Because the “dolly-car” rack moves relative to large wheel, so the rack may higher than large wheel. Once such body connects with the dolly-car rack which height has been added, the swing extent can be greater. In this case, swing position limit is necessary to avoid the overturn of barycenter. Such structure is available to dual-wheel vehicle too.

“Dolly-car” can be substituted by a large bearing, that means the diameter of the bearing hole is greater than body axis, eccentric swing also adopt this kind of bearing. Bearing ball is equal to the wheel of a “dolly-car”. The body axis connects with the internal loop of the bearing as the method foresaid. Actually, such structure is a “large wheel transmission”. This invention can be adopted by a quadricycle with related technology, use swing structure and regard the front two or rear two wheels as the driving wheels and driven by the engine. Another two wheels adopt large bearing structure as above said, dragged or pushed by the driving wheels. This is also a kind of gravity and such technology can be adopted by any vehicle with related technology.

The technical classification of any integrated vehicle, swing structure and multi-wheel vehicle included in this invention is purposed to describe clearly and easy to comprehend, not mean that such technology should be used solely or synchronously. In practice, all technical resolutions and features in this invention can be utilized solely or synchronously and suitable to combine with related technology.

Any non-impetus vehicle, such as train carriage and trailer car, also can accept such eccentric axis and/or swing connection, when an external force draw the vehicle body, the body swing to the forward direction and get over the gravity surface of the wheel, such gravity changes into impetus, thus can save more energy to draw the vehicle. Eccentric axis can be used in all circumferential substance movement. Any wheel with related technology can adopt such structure.

6. Quadricycle—has two or two group coaxial wheels as main wheels, main wheels are located at the middle bottom of the body. A supplementary wheel is also carried. The supplementary wheel is installed at the front or rear part of the body. The main wheels play the roles of loading, driving, braking and turning. The coaxial wheels as foresaid include the wheels with the same axial direction. The coaxial means the same axis shared by two or two group wheels, and the same axial direction means two or two group wheels with different axes but located in the same straight line and same axial direction.

For example, main wheels have two coaxial wheels and located at the middle of the body, one supplementary wheel each at the front and rear part of the body, four wheels shape like diamond. Main wheels play the roles of loading, driving, braking and turning, these functions can realized by Related technology; e.g. only drive or brake one of main wheels, the vehicle can turn the direction; only brake one of main wheels in movement, the vehicle can make the round in same place and consume inertia energy to play the role of braking. Of cause, it is possible to brake the wheels at same time. Weight or the gravity of a vehicle, mainly is borne by main wheels, so as to utilize the gravity.

Supplementary wheel plays the role of stability and balance, avoid the body to touch the ground in movement, keep stability in braking; supplementary wheel can perform the feature of anchoring plate, to bear part of load when the front or rear part of the body receive the pressure downward, the above said roles can be played when the vehicle in movement or in braking. Supplementary wheel connects flexibly with the body and can turn in parallel follow the body turning. Supplementary wheel can adopt universal wheel structure with Related technology. Supplementary wheel carries an elastic device and be equipped with elasticity except the elasticity of tire, it can flex follow the pressure. In running, main wheels touch the ground while the supplementary wheel is unnecessary to touch the ground or slightly touch, or touch the ground in discontinuity; or, only one supplementary wheel touch the ground in running, or only one supplementary wheel slightly touch the ground or touch the ground in discontinuity. Of cause, there are two supplementary wheels each to be installed at the front and rear part of the body, there are four supplementary wheels in total. In this way, there are six wheel, two main wheels and four supplementary wheels. The number of supplementary wheel can depend on situation.

This invention adopts the liquid wheel in the Patent application 200410030581.x <A Sort of Vehicle>, the smaller the touchdown radius of the liquid wheel, the less the resistance. A light jelly, cream or semiliquid, the kind such as like as "aerogel" can be filled in liquid tire. Aerogel is a kind of jelly with light quality; it can transmit pressure in tire according to Pascal's Law.

One of the advantages in this invention is energy saving, i.e. to sufficiently use own weight by the structures of the gravity vehicle and swine connection designed by Circumferential Law, to realize the purpose of power and energy saving. A combination of eccentric axis and swing connection can save more energy. The second advantage is the structure of all vehicles is much more simple and reasonable than described in related technology. The third advantage is there is a new structure produced by dual-wheel and multi-wheel gravity vehicles and provide with more options. The fourth advantage is the wider applicability, available to all circle movement devices, such as human powered vehicle, motor vehicle, toy vehicle and space vehicle. The fifth advantage is safer by using of new braking method and new structure, avoid overturn due to its gravity declines and enhance its security in braking. The sixth advantage is cost reducing, due to the structure is greatly simplified, the manufacturing cost reduced. Moreover, the energy can be saved greatly during movement; therefore, not only decline the operating cost, but also benefit to the protection of global resources. The advantages of this invention are also specified in the relevant contents in the whole text.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a sketch drawing of a circumferential substance being stressed by a force.

FIGS. 2-3 are sketch drawings of a kind of swing connection structure.

FIGS. 4-6 are drawings of three kinds of swing structures.

FIGS. 7-9 are sketch drawings of eccentric axes.

FIGS. 10-12 are drawings of three kinds of integrated vehicles.

FIGS. 13-14 are drawings of a vehicle powered by compressed air.

FIG. 15 is a drawing of a vehicle powered by electric fan.

FIGS. 16-17 are drawings of structures of the connection between dolly-car and body swing.

FIG. 18 is a drawing of a structure of the circumferential substance gravity utilization (similar to the ball mill).

FIGS. 19-20 are drawings of movement of several dual-wheel vehicles.

FIGS. 21-22 are drawings of structures of a sort of dual-wheel vehicle.

FIGS. 23-25 are drawings of structures of a sort of quadracycles.

FIGS. 26-28 are drawings of structures of a sort of integrated vehicle.

FIG. 29 is a drawing of a sort of pendulum shaft with swing structure.

FIG. 30 is a drawing of a sort of wheel with part of wheel rim.

FIGS. 31-32 are drawings of a trailer rack of the integrated vehicle.

FIGS. 33-34 are drawings of an air tank with the shape of round cake & baffle installed on the axis.

FIG. 35 is a drawing of an air tank with the shape of circular loop.

FIG. 36 is a drawing of a round cake air tank installed as the axial direction outside the tire.

FIGS. 37-38 are drawings of a circular loop air tank installed inside the rim of the tire.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIG. 1—Circumferential substance 1 can be a ball, or a cylinder, or a wheel and located on the load surface 3. Its weight surface 2 is located at the center of the circle. The weight surface 2 is fictitious, but the interlace of the weight is in objective reality. A circumferential substance touch with the load surface can not but produces a weight interface, i.e. the weight interface. At both sides of the weight surface 2, the weight sizes are equal, directions are contrary. Although the weight is downward, but the both sides of the weight surface of the circumferential substance will produce two equal weights, their directions are contrary. The load surface includes the ground. If a perfect point or line of the circumferential substance touch with the firm load surface, whether different in their quality, the force to overcome the static inertia is greater than zero. The movement rule will follow Circumferential Law as foresaid in this article. This point is absolutely contrary with the Newton Law, which means Newton Law is not applicable to circumferential substance movement. It will be alternatively between us!

FIGS. 2-3—Wheel 101 is circumferential substance and connects with swing bar 4 at the place of wheel axis 5, body axis 6 is at the swing bar 4, and it is used to connect with vehicle body. When swing bar 4 in the figure moves to the left side of the weight surface 2, the body weight will produce the gravity to the wheel 101 lean to the left side, this gravity will become the forward impetus. The circumferential substance 101 can act as the wheel for the wheels of all vehicles including train, automobile, trail car and human powered vehicle.

FIG. 4—Wheel here is omitted, there is a limit stake 8 on the body 7, limit pole 10 on swing bar 4, limit stake 8 and limit pole 10 can be used alternatively or synchronously. Besides, limit spring can be used also. They can play the role to limit the body swing on the wheel within a certain extent. The ratchet structure with related technology can also be available to limit the swing forward only.

FIGS. 5-6—Wobble tray 401 or 402 on the wheel 101, there are several structures for swing bar, 401 and 402 is the swing bar with different structure and with the same function of the swing bar 4 in FIG. 3. Wobble tray 401 shapes like flat

plate or a round flat plate, a piece was cut off on the top in the figure. The geometry shape of a swing bar can be changed except its function of swing bar. The role of a swing bar is to connect the body and wheel and swing the body relative to the wheel. A swing bar has other functions, such as to carry a limit device. Wobble tray **402** is also equipped with the function to increase the swing extent. There is body axis **601** on the wobble tray **402**; it expresses that to move the body axis from the underside of the circle center of the wheel to the upside, even higher than the wheel. As long as the gravity of the body not exceeds the circle center of the wheel, the body can not be overturn. But in multi-wheel vehicles, the gravity of the body can exceed the circle center of the wheel due to the balance of the supplementary wheel; the vehicle body can not be overturn.

FIGS. 7-9—FIG. 8 is the inner loop cover; FIG. 9 is a left-view diagram. There is inner loop cover **11** in inner loop **13** of the bearing **100**, cover hole **12** on the inner loop cover **11**. Inner loop cover **11** is fixed on the inner loop cover **13**. Bearing **100** is installed on the wheel; bearing ball and inner loop **13** are similar with the “dolly-car” in large wheel transmission device. The body axis is fixed in the cover hole **12**, equals to connect with inner loop cover **13**. The body axis can be fixed on the inner loop by welding, covering or affixing, the figure displays the method of covering. In movement, the body axis can pull inner loop **13** to a certain angle and keep the body axis away from the weight surface of the wheel, i.e. swing the body relative to the wheel and change the gravity to forward impetus.

FIG. 10—The vehicle body **16** combines with the wheels at its two sides and becomes an integrated vehicle **18** the body and wheels shape round, the left-view and right-view diagrams show a small round in a larger round, so the left-view and right-view diagrams was omitted. The diameter of the body is smaller than the wheel and keeps a certain distance from the ground to ensure the movement. The body runs following the wheels. The integrated vehicle can be used to carry cargo, such as coal, ore, petroleum and gluewater, etc. the integrated vehicle. There is no inlet or outlet as well as the inspection opening for cargo in the integrated vehicle, just like a tank truck. An integrated vehicle can carry roller **14**, the trailer and vehicle tracks can be installed on it to control the movement of the vehicle. It is possible not to install engine on such vehicle and regard it as a trailer car when a trailer track installed on it. Gear **17** is used for receiving external force. The external force in this invention can be electromotor or internal-combustion engine. Such vehicle can be manned, unmanned or remote controlled.

FIG. 11—To integrate the body **16** with the wheel **19**, the body and wheels shape round, the left-view and right-view diagrams show a small round in a larger round, so the left-view and right-view diagrams was omitted. The diameter of the body is smaller than the wheel and keeps a certain distance from the ground to ensure the movement. The body runs following the wheels. Wheel **19** is located in the middle of the body, it can be a rubber loop to receive the impetus from the rubber roller upward and drive the vehicle.

FIG. 12—To integrate the body **16** with the wheels **20** at its two sides, the body and wheels shape round, the left-view and right-view diagrams show a small round in a larger round, so the left-view and right-view diagrams was omitted. The diameter of the body is smaller than the wheel and keeps a certain distance from the ground to ensure the movement. The body runs following the wheels. Wheel **20** carries an upstanding side **21**; there is cargo inlet and outlet **166** on the body **16**.

Such vehicle is used to drive on rail. The integrated vehicle can be used to transport water, oil, cement, coal, coal slurry and concrete, etc.

FIGS. 13-14—FIG. 14 is an A-A cutaway view of FIG. 13. Body **22** connects with wheel **101** flexibly through wheel axis **5**; these two coaxial wheels are located at the two sides of the body. It is possible to dispose tow or two group coaxial wheels at two ends of the body. The wheel can run relative to the body. The figure shows that: there is compressed air stored at the bottom of body **22**. The huff nozzle **23** is located on the top of the body; huff nozzle **23** connects with the compressed air. There is baffle plate or lamina, or a concave around the wheel as well as the air valve, the device with related technology. FIG. 13 shows the left wheel and the baffle plate around the wheel. During the vehicle moving, huff nozzle blow the air to the baffle plate or concave at upper fringe and drive the wheel running; meanwhile, huff nozzle produce counter force to the body. The counter force play the role of leverage through wheel axis **5**, the bottom of the body **22** inclines forward, and the weight shifts ahead too, the weight now changes to impetus. Again, due to the bottom of the body is heavier, cause the weight greater. The bottom of the body **22** is heavier than the top, so the vehicle can not be overturn. Such vehicle can carry supplementary wheel or anchoring plate also to avoid the vehicle overturn.

FIG. 15—There is a storage battery **26** at the bottom of body **22** to supply the power for electric fan **25**, the electric fan blow the air backward to drive the vehicle. Electric fan **25** makes the bottom of body **22** inclines forward, shift the weight ahead and change the weight into impetus. Due to the bottom of body **22** is heavier than the top, so it is possible than the top of body **22** is higher than the wheel. Electric fan **25** can be located at the middle or the top of the body too, electric fan blows the air backward and drive the vehicle. Electric fan can be substituted by jet engine or compressed air. Jet engine or compressed air can be installed on the body, blow the air backward and drive the vehicle.

FIGS. 16-17—A “dolly-car” **27** is inside the wheel **101**, the small wheel of dolly-car **27** moves at the bottom of wheel **101**. By Plea Know technology, to dispose dolly-car and wheel **101**, the body connects with two body axes **601**. Such dual-axis swing connection can bear heavier load. Two body axes swing at same time and the effect is as same as single swing. In this invention, the body axis can be one, two or more. There are two swing axes **501**, located at the upper middle position in the parallel line of wheel; due to the bottom of the body is much heavier, so dolly-car **27** can never loss its barycenter inside the wheel **101** and overturn. Such structure is of a kind of “large wheel transmission”. Wheel **101** is large wheel **101**, wheel **101** runs relative to dolly-car **27**. Just as like as there is electromotor and gear on the top of dolly-car, an internal gear ring is installed on wheel **101**, power supply is inside the body, direct supply the power to electromotor, transmit on the top of wheel and drive the wheel **101** running around the wheel axis **502**, and push the dolly-car **27** moves forward, dolly-car **27** bring the vehicle body following the wheel **101** moves forward. Due to the body can swing forward and make the weight in a status of inclining forward and change the weight into the impetus.

FIG. 17 is A-A cutaway view of FIG. 16. Dolly-car **27** has the same circle center with large wheel **101**; the position of large wheel **101** is limited by wheel axis **502**. Wheel **502** does not load the weight, nor limit the movement come-and-go of the large wheel, it limits the position of the large wheel **101** only to prevent it dislocate from the axial direction. Dolly-car rack also plays the role of the position limit to the large wheel **101**, the area of dolly-car rack is greater 50% and above than

11

the large wheel **101**, it top exceeds the center parallel line of the large wheel **101** and has a caging device relative to the large wheel **101**, such as the facette, to make the position of the large wheel **101** controlled by dolly-car **27**. Wheel axis **502** can be connected with the body flexibly, there is a long round hole on the body and the wheel axis **502** can move inside the round hole, no any influence to the swing of the body or the movement of the large wheel. Wheel axis **502** also can play the role of position limit to swing bar **401** to limit its swing extent. It is possible for a vehicle to have two or more such wheels. Wheel **101** can be the wheel for any vehicle, including trail car and human powered vehicles.

FIG. **18**—Circumferential substance **102** represents a ball mill, concrete blender or a tumbling-box washing machine. The installation and the transmission method of such machines are unreasonable by Plea Know technology, no “gravity surface” and waste power. In this invention, to dispose such circumferential substance **102** on base wheel **30**, base wheel shall be installed on the base seat **31** by Plea Know technology to run the base wheel relative to circumferential substance **102**. Two or more base wheels can be disposed around the axial direction of circumferential substance **102** to bear the weight, make the bottom of circumferential substance **102** close to the ideal point or line connection of the base wheel **30**, establish a weight surface to save energy by the weight. A rotary wheel **32** can be set up at two sides of circumferential substance **102** to keep it in perfect position. To install rotary wheel **32** by related technology, make it running followed by circumferential substance **102**. It is possible to have two or more rotary wheels as same as base wheels and to be disposed around the axial direction. FIG. **18** only shows the surface, two or more base wheels and rotary wheels are same as such structure. A transmitting wheel **29** is on the top of circumferential substance **102** and to be driven by an engine to bring circumferential substance **102** running. The installation of transmitting wheel and engine can be completed by related technology. Transmitting wheel **29** can be located at the middle or the bottom of circumferential substance **102**. To use roller bearing on base seat **31** because the load of a roller bearing is greater, the pressure of a rotary wheel is less, so roller bearing is applicable. Base seat **31** can be substituted by a magnetic suspension device.

FIG. **19**—One driver is needed only for the combination of four or more dual-wheel vehicles to save human power and the space within vehicles. The connection device or method between two vehicles can adopt the method of a train, not only to be connected with pothook **34**, but also wire, water pipe and others. Change the wheels of dual-wheel vehicle **33** into the train wheel which carries the upstanding side, such vehicle can run on the rail. FIG. **20** shows: pothooks **34** are carried by body **222** at front and rear parts, each section of dual-wheel vehicle can be the head vehicle and has driver scat and runs forwardly and reversely. Each section of dual-wheel vehicle **33** can has its own driving device, it can solely run solely or run as a string as shown in the figure. When running as a string, each section can be driven by own engine and form a composition force. It is convenient for driving due to each vehicle has own controlling capability. Also, a dual-wheel vehicle does not carry own engine and to be used as a trail car, driven by the main vehicle. Main vehicle means the head vehicle, it provides impetus and controlling. Several integrated vehicles which carry trail racks or pothooks can form a train and be towed by a head vehicle.

FIG. **21** is the left-view diagram of FIG. **22**; dual-wheel vehicle **22** is composed by large wheel **101** and body **223** as well as two anchoring plates **36**, anchoring plates **36** stands on the ground **3** to play the roles of braking and stability. Anchor-

12

ing plates will be picked up pulled up during movement. The wheels of a dual-wheel vehicle are comparatively larger and close to the body. Vehicle rung shapes as a strip. Wheel axis **5** connects with wheel and body. Electromotor **39** is located on the top of body **223**, one at each side and to be installed by related technology. There is gear **38** on the electromotor; an internal gear ring matched up to the gear is carried by wheel **101**. The internal gear ring is driven by gear **38**. Although the body can swing against the wheel, but the extent is not so great, can never influence to the transmission from the gear **38** on the body to the internal gear ring on the wheel. The body can swing around the circle centre of wheel axis, the body has the same circle centre with the wheel, the swing direction and the radius of the body are consistent with that of internal gear ring of the wheel, so it can not influence to the normal operation. The counter force of gear **38** to the top of body can transmit to the bottom of the body through wheel axis **5** and makes the bottom of body inclining forward, the weight shift forward too, and change the weight into impetus. Power supply **26** is located at the base of the body to decline the bary-center and increase the effective weight. Power supply **26** provides the power to electromotor. Within the body, driver scat and relative facilities as well as the passenger scat can be set up by related technology. It is possible not to set up driver scat. As shown in FIG. **20**, it is necessary to set up connection device, such as pothook in cabin. Electric axis and electric wheel engine with related technology are also available. To brake the wheel at one side can complete the functions of turning or shut down. The broken line in FIG. **22** shows gear and internal gear ring.

No engine can be carried for a dual-wheel vehicle; such vehicle can be used as trial car or human power vehicle. The body can shape as a square, flat plate or others with Plea Know technology. To drive the vehicle by human power is also available, in this case, only need to change electromotor to human powered device. To use chain wheel device transmit the human power to the top of large wheel **101** to drive the vehicle.

FIGS. **23-25**—FIG. **23** is the left-view diagram of FIG. **24**; FIG. **25** is the upward-view diagram of FIG. **24**. All wheels are located at the bottom of the body. Four wheels **44** of quadricycle are disposed as diamond, two main wheels **44** are coaxial wheels and located the middle of the body, two supplementary wheels **43** are located at front and rear of the body. This is a kind of gravity vehicle. Wheel **44** can adopt the structure of FIG. **16** and “large wheel transmission”. It is also available to adopt the wheel electromotor described in <A Sort of Vehicle> of Plea Know technology document 200410030581.x. Vehicle body connects with wheel swing. Supplementary wheel can run in parallel to match up turning. Supplementary wheel carries an elastic device which flexes up and down following pressure, the wheel is unnecessary to touch the ground or slightly touch, or touch the ground in discontinuity, or, only one supplementary wheel touch the ground. Only need one main wheel can realize turning and braking, to use two main wheels at same time can brake or decelerate the vehicle.

FIGS. **26-28**—FIG. **26** is the left-view diagram; FIG. **28** is the top-view diagram of FIG. **27**. An integrated vehicle **18** carries a rack beam **45**, an electromotor **170**, and trail wheels **46**. Electromotor **170** is located at the bottom of the rack beam **45** and on the top of integrated vehicle **18**. Electromotor **170** drives gear **17** and pushes the vehicle **18** forward. Trail wheel **46** plays the role of balance. Such vehicle can also be unmanned or remote controlled. The body **16** can optionally include a compressed air tank **47**. Details of the compressed air tank **47** are described in FIG. **33-35**.

13

FIG. 29—Pendulum shaft 503 shows a structure of bend and concave, wheel axis 504 is integrated with the body axis 505, wheel axis 504 connects with wheel, and body axis connects with body. This is an axle with swing structure, pulling the body, the body swing forward and change the weight into impetus. The swing bar connects with wheel and body, the body is installed inside the structure of bend and concave.

FIG. 30—Wheel 19 is installed on the body 16 of the integrated vehicle with tire and part of rim 199.

FIGS. 31-32—FIG. 32 is the left-view diagram of FIG. 31, trail rack 141 shapes like a semi-frame, trail rack 141 is equipped with a juncture 142 and a juncture hole 143 is on it. Trail rack 141 carries an axial hole 144 to connect with roller 14. It is unnecessary to carry power for an integrated vehicle and to be regarded as the trail car when it is installed on a rack.

FIGS. 33-34—FIG. 34 is the left-view diagram of FIG. 33. The compressed air tank 47 shapes like a round cake, there is a huff nozzle 48 on it, wheel axis 5 carries baffle plate 49.

FIG. 35—Air tank 50 shapes like a hollow round loop, a huff nozzle 48 is on it.

FIG. 36—Air tank is installed on the position of axial direction outside the wheel 101 (also can be installed on large wheel 101 shown in FIG. 22). Air tank can be installed on any side of the position of axial direction outside the tire.

FIGS. 37-38—FIG. 37 is the left-view diagram of FIG. 38. Most part of air tank is to be installed inside the tire rim; a huff nozzle 48 is at the bare part.

This invention is applicable to all devices and method with circumferential movement, including automobile, train, space vehicle, toy vehicle, crane, trail car, blender, and ball mill, etc. all technical resolutions and technical features in this invention can be used solely or in combination and not limit to a certain example case described in this manual and the figures attached.

14

What is claimed is:

1. A vehicle comprising:

a vehicle body;

an engine installed on the vehicle body, the vehicle body having a passenger seat;

two or two group coaxial wheels as main wheels, the main wheels being located at the middle bottom of the vehicle body;

at least one supplementary wheel carried on the vehicle body, the least one supplementary wheel being installed at the front or rear part of the vehicle body, the main wheels playing the roles of loading, driving, braking and turning, in running, main wheels touching the ground while the least one supplementary wheel not touching the ground or slightly touching the ground or touching the ground in discontinuity, or, main wheels touching the ground while only one supplementary wheel touching the ground or slightly touching the ground or touching the ground in discontinuity;

at least one compressed air tank installed on the wheel, wherein the compressed air tank is shaped as circle pipe or round cake for fitting the shape of tire; and

a plurality of huff nozzles disposed around compressed air tank to puff the air forward the rear of the vehicle body and drive the vehicle running.

2. The vehicle as claimed in claim 1, further comprising a transmission device disposed on the vehicle body, wherein a driving force of the engine is transmitted to the top position of the main wheels of the vehicle body for driving the wheel.

3. The vehicle as claimed in claim 1, further comprising at least one valve fixed at the least one huff nozzle.

* * * * *