




(86) Date de dépôt PCT/PCT Filing Date: 2001/08/07
(87) Date publication PCT/PCT Publication Date: 2002/02/14
(45) Date de délivrance/Issue Date: 2011/04/26
(85) Entrée phase nationale/National Entry: 2002/03/14
(86) N° demande PCT/PCT Application No.: US 2001/024851
(87) N° publication PCT/PCT Publication No.: 2002/012913
(30) Priorités/Priorities: 2000/08/08 (US60/223,670);
2001/07/13 (US09/905,266)

(51) Cl.Int./Int.Cl. *G01S 5/14* (2006.01),
G01S 1/00 (2006.01)
(72) Inventeur/Inventor:
GAAL, PETER, US
(73) Propriétaire/Owner:
QUALCOMM INCORPORATED, US
(74) Agent: SMART & BIGGAR

(54) Titre : PROCÉDE, APPAREIL ET SYSTÈME DE PREDICTION DE SIGNAUX
(54) Title: METHOD, APPARATUS, AND SYSTEM FOR SIGNAL PREDICTION



(57) Abrégé/Abstract:

An apparatus, method, and system for predicting subframes of GPS signals. The apparatus includes a processor capable of determining whether a subframe is an almanac subframe, setting a timehead and adding it to a TOW, setting a TLM message based on a value of the TOW, generating a CRC for a predicted subframe, and a memory for storing the predicted subframe. The memory may vary in size based on the number of predicted subframes. The processor is further capable of determining whether the value of the TOW is less than the number of seconds in a week, calculating a position of the predicted subframe in the memory, and setting a valid flag.



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
14 February 2002 (14.02.2002)

PCT

(10) International Publication Number
WO 02/12913 A2

(51) International Patent Classification⁷: **G01S 5/00**

(21) International Application Number: PCT/US01/24851

(22) International Filing Date: 7 August 2001 (07.08.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/223,670 8 August 2000 (08.08.2000) US
09/905,266 13 July 2001 (13.07.2001) US

(71) Applicant: **QUALCOMM INCORPORATED** [US/US];
5775 Morehouse Drive, San Diego, CA 92121-1714 (US).

(72) Inventor: **GAAL, Peter**; 9515 Easter Way #6, San Diego,
CA 92121 (US).

(74) Agents: **WADSWORTH, Philip, R.** et al.; Qualcomm In-
corporated, 5775 Morehouse Drive, San Diego, CA 92121-
1714 (US).


(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD, APPARATUS, AND SYSTEM FOR SIGNAL PREDICTION



(57) Abstract: An apparatus, method, and system for predicting subframes of GPS signals. The apparatus includes a processor capable of determining whether a subframe is an almanac subframe, setting a timehead and adding it to a TOW, setting a TLM message based on a value of the TOW, generating a CRC for a predicted subframe, and a memory for storing the predicted subframe. The memory may vary in size based on the number of predicted subframes. The processor is further capable of determining whether the value of the TOW is less than the number of seconds in a week, calculating a position of the predicted subframe in the memory, and setting a valid flag.

WO 02/12913 A2

74769-520

1

**METHOD, APPARATUS, AND SYSTEM FOR SIGNAL
PREDICTION**

BACKGROUND OF THE INVENTION

Field of the Invention

5 **[0002]** The present invention relates to reception of signals from known sources, and more specifically to predicting the content of signals received from known sources.

Description of Related Art

10 **[0003]** Ease and accuracy of position and time determination has increased significantly since the development of the well-known NAVSTAR Global Positioning Satellite (GPS) System. The NAVSTAR GPS system is described in Global Positioning System Standard Positioning Service
15 Signal Specification, 2nd edition, June 2, 1995, United States Coast Guard Navigation Center, Alexandria, VA. Another such system is the GLONASS GPS system maintained by the Russian Republic. GPS receivers are currently available for use in aircraft, ships, and ground vehicles and for hand
20 carrying by individuals.

[0004] The NAVSTAR GPS system provides for thirty-two satellites or "space vehicles" (SVs) that orbit the earth in six orbital planes (four satellites, plus spares, in each plane). Each SV orbit repeats almost the same ground track
25 each day as the earth turns beneath the SVs of the system. The orbital

planes are equally spaced and inclined with respect to the equatorial plane, thus ensuring that a line-of-sight path exists to at least five SVs from any (unobstructed) point on the earth.

[0005] Ground-based monitor stations measure signals from the SVs and incorporate these measurements into orbital models for each satellite. Orbital data and SV clock corrections are computed for each satellite from these models and uploaded to each SV. The SV then transmits information relating to its position at a data rate of 50 bits per second, via BPSK modulating a direct sequence spread spectrum signal having a chip rate of 1.023 MHz that is modulated onto an RF carrier, with each SV using a different spreading code (also called a Gold code or a coarse acquisition or C/A code). Hereinafter the information carried on the signal transmitted by a SV is called 'navigation data.'

[0006] A GPS receiver calculates its position by combining navigation data that indicates the position of the SVs with the delay or phase of the signal received from the SVs (which indicates the distance between the receiver and the SVs). Because of inaccuracies in the receiver's timebase oscillator, signals from at least four SVs are required to resolve a position in three dimensions, although signals from additional SVs (if available) may be used to provide better accuracy.

[0007] It is desirable to augment certain wireless systems for mobile communications by adding the capability to locate the position of a particular mobile unit. One reason is a regulation promulgated by the Federal Communications Commission (FCC) (Docket No. 94-102, Third Report and Order adopted September 15, 1999, released October 6, 1999) which requires all cellular carriers in the United States to be able to locate the position of a cellular telephone making an emergency 911 call within 50 meters for 67 percent of calls and within 150 meters for 95 percent of calls by October 2001. Other uses for position location capability in wireless communications systems

include value-added consumer features such as navigation and vehicle fleet management support.

[0008] One possible approach to supporting position location in a wireless communications system is to add GPS location capabilities to the mobile units.

5 However, GPS receivers generally require unobstructed, strong signals, which may not be available to a mobile unit. GPS signal detection under unfavorable SNR conditions (for example, inside a building or vehicle where no direct line of sight can be established from the receiver to at least four SVs) is a continuing problem.

10 [0009] In order to detect the GPS signal at the receiver, a matched filter may be used to generate the spreading code and apply it to the received signal in a search for a correlation peak. This method is called coherent integration. Short coherent integration denotes integration over a period of less than one data bit (in the case of a GPS signal, less than 20 milliseconds), while long
15 coherent integration denotes integration over a period of more than one data bit. It may be desirable to apply long coherent integration, as a longer integration period may allow for a higher processing gain.

[00010] One drawback to using long coherent integration on a signal such as a GPS signal is that the data modulated onto it may integrate to produce an
20 output of low or zero magnitude. In other words, if each binary data symbol that is modulated onto the signal (expressed herein as '0' or '1') appears as frequently as the other binary data symbol during the integration period, then the output of the matched filter over the integration period will sum to zero and no signal will be detected. Even if the data symbols sum to a nonzero value,
25 the resulting receiver performance will be severely reduced in most cases.

[00011] U.S. Pat. No. 6,118,977, issued to Vannucci, discloses a method where the known GPS navigation data is used in a mobile receiver to generate a local replica of the transmitted signal, which includes representation of the

74769-520

4

data modulation on the signal. This allows the mobile receiver to correlate the received signal utilizing long coherent integration period without experiencing the output degradation explained above. The method of Pat. No. '977
5 requires carrying out the processing steps described subsequently in this paragraph. The mobile receiver stores processed data samples of the received signal to a FIFO memory for later off-line processing. An auxiliary system, which has unobstructed view of all SVs above the
10 horizon, receives GPS signals at the same time with the mobile receiver and demodulates the transmitted navigation data bits. The auxiliary system conveys the demodulated navigation data bits to the mobile receiver. The mobile receiver off-line processes the stored data samples,
15 utilizing the navigation data bits conveyed to it by the auxiliary system.

[00012] Unfortunately, the memory capacity needed for storing processed data samples in the mobile receiver makes the method of Pat. No. '977 impractical. The required
20 memory capacity is dictated by the data sampling rate, the coherent integration length, the number of SVs and the number of code phase and Doppler hypotheses for which signal search is attempted simultaneously. Note that a typical mobile receiver cannot detect signals from both the SVs and
25 the auxiliary unit at the same time, thus, the required memory capacity cannot be reduced by cyclic operation (i.e. when the same memory cell is reused for storing different segments of the received signal while maintaining coherent integration).

30 **[00013]** Thus, there is a need for a method, apparatus and system that would allow a receiver to perform long coherent integration on signal receivers without the undue burden of

74769-520

4a

having to incorporate large-scale memory devices in those receivers.

SUMMARY

According to one aspect the invention provides a
5 method of providing predicted navigation data, said method
comprising: receiving GPS data, including a subframe of a
GPS signal, from a transmitter; predicting future navigation
data based on the received GPS data; storing the predicted
future navigation data to a buffer; receiving a prediction
10 request defining a time interval for which prediction is
requested; obtaining predicted future navigation data
corresponding to the time interval from the buffer; and
transmitting the predicted future navigation data.

According to another aspect the invention provides
15 a method comprising: receiving a subframe of a GPS signal;
storing the received subframe in a buffer; and predicting a
next corresponding subframe by changing a TOW and
regenerating a CRC of the received subframe; and
incrementing a timestamp associated with the received
20 subframe by a predetermined value.

According to another aspect the invention provides
an apparatus comprising: a processor capable of: receiving a
subframe of a GPS signal; storing the received subframe in a
buffer; and predicting a next corresponding subframe by
25 changing a TOW and regenerating a CRC of the received
subframe; and a memory for storing the predicted subframe.

According to another aspect the invention provides
a method of predicting subframes of GPS signals, comprising:
determining whether a subframe is an almanac subframe;
30 setting a timehead based on whether the subframe is an

74769-520

4b

almanac subframe; adding the set timehead to TOW; setting a TLM message based on a value at the TOW; generating a CRC for a predicted subframe; and storing the predicted subframe in a buffer.

5 According to another aspect the invention provides a method of updating almanac data of an SV at a central site, comprising: extracting a page ID of a subframe; determining whether the page ID is valid based on a first criteria; extracting old and new TOWs from a buffer based on
10 the validity of the page ID based on the first criteria; determining whether the old TOW and a last almanac update time are the same; resetting an almanac update table based on whether the old TOW and the last almanac update time are the same; determining whether the new TOW and the last
15 almanac time are the same; ending the almanac update process based on whether the new TOW and the last almanac update time are the same; determining whether the page ID is valid based on second criteria; ending the almanac update process based on whether the page ID is valid based on the second
20 criteria; determining whether the subframe is valid in the almanac update table; storing the subframe in the almanac update table, setting a valid flag for the subframe, and beginning a subframe prediction process based on whether the subframe is valid in the almanac update table; and
25 extracting all valid subframe from the almanac update table and substituting words 2-10 in the predicted subframes for this SV and performing the subframe prediction process based on whether the subframe is valid in the almanac update table.

74769-520

4c

According to another aspect the invention provides a method of determining whether a subframe prediction is feasible at a central site, comprising: receiving a subframe from an SV; determining whether a certain bit of a word of the subframe is zero; storing the subframe in a buffer if it is determined that the bit of the word is zero; inverting all bits in the received subframe and storing them in the buffer if it is determined that the bit of the word is not zero; determining whether a subframe header is valid; ending the process and waiting for a next subframe based on whether the subframe header is valid; checking CRC validity for all words; ending the process and waiting for the next subframe based on whether the CRC for all the words is valid; checking a TLM message to see if it is different from a last TLM message received; setting the TLM message as a regular TLM message based on whether the TLM message is different from the last TLM received; storing the TLM message as the last TLM message received; determining whether there is a valid prediction for this subframe; performing a subframe prediction based on whether there is a valid prediction for this subframe; determining whether the received and predicted TOW match; performing the subframe prediction based on whether the received and predicted TOW match; determining whether there is a perfect match between the received and predicted subframes based on whether the received and predicted TOW match; determining an errorcode and logging an error based on whether there is a perfect match between the received and the predicted subframes; determining whether the subframe is an almanac subframe; performing an almanac update based on whether the subframe is an almanac subframe; and performing the subframe prediction.

74769-520

4d

According to another aspect the invention provides an apparatus for predicting subframes of GPS signals at a central site, comprising: a processor capable of:

determining whether a subframe is an almanac subframe;

5 setting a timehead based on whether the subframe is an almanac subframe; adding the set timehead to a TOW; setting a TLM message based on a value of the TOW; generating a CRC for a predicted subframe; and a memory for storing the predicted subframe.

10 According to another aspect the invention provides an apparatus for updating almanac data of an SV at a central site, comprising: a memory for storing subframes; and a processor capable of: extracting a page ID of a subframe;

determining whether the page ID is valid based on a first
15 criteria; extracting old and new TOWs from a buffer based on a validity of the page ID based on the first criteria;

determining whether the old TOW and a last almanac update time are the same; resetting an almanac update table based on whether the old TOW and the last almanac update time are
20 the same; determining whether the new TOW and the last almanac time are the same; ending the almanac update process based on whether the new TOW and the last almanac update time are the same; determining whether the page ID is valid based on a second criteria; ending the almanac update

25 process based on whether the page ID is valid based on the second criteria; determining whether the subframe is valid in the almanac update table; storing the subframe in the almanac update table, setting a valid flag for the subframe, and beginning a subframe prediction it process based on

30 whether the subframe is valid in the almanac update table;

74769-520

4e

and extracting all valid subframe from the almanac update table and substituting words 2-10 in the predicted subframes for this SV and performing the subframe prediction process based on whether the subframe is valid in the almanac update
5 table.

According to another aspect the invention provides an apparatus for determining whether a subframe prediction is feasible at a central site, comprising: a memory for storing subframes; and a processor capable of: retrieving a
10 subframe from the memory; determining whether a certain bit of a word in the subframe is zero; storing the subframe back into the memory if it is determined that the bit of the word is zero; inverting all bits in the retrieved subframe and storing them back into the memory if it is determined that
15 the bit of the word is not zero; determining whether a subframe header is valid; ending the process and waiting for a next subframe based on whether the subframe header is valid; checking CRC validity for all words; ending the process and waiting for the next subframe based on whether
20 the CRC for all the words is valid; checking a TLM message to see if it is different from a last TLM message received; setting the TLM message as a regular TLM message based on whether the TLM message is different from the last TLM received; storing the TLM message in the memory as the
25 last TLM message received; determining whether there is a valid prediction for this subframe; performing subframe prediction based on whether there is a valid prediction for this subframe; determining whether the received and predicted TOW match; performing the subframe prediction
30 based on whether the received and predicted TOW match;

74769-520

4f

determining whether there is a perfect match between the received and predicted subframes based on whether the received and predicted TOW match; determining an errorcode and logging an error based on whether there is a perfect
5 match between the received and the predicted subframes; determining whether the subframe is an almanac subframe; performing an almanac update based on whether the subframe is an almanac subframe; and performing the subframe prediction.

10 According to another aspect the invention provides a system comprising: a receiver to receive GPS signals and to transmit information; a processor capable of: receiving the information from the receiver including a subframe of a GPS signal; storing the receive subframe in a buffer; and
15 predicting a next corresponding subframe by changing a TOW and regenerating a CRC of the received subframe; and a memory for storing the predicted subframe.

BRIEF DESCRIPTION OF THE DRAWINGS

[00014] FIGURE 1 illustrates various divisions of a GPS data message.

[00015] FIGURE 2 illustrates the structure of a GPS subframe and the structure of a GPS handover word.

[00016] FIGURE 3 illustrates the division of a GPS frame into a transmitter
5 status(or ephemeris) group of subframes and a system status (or almanac)
group of subframes.

[00017] FIGURE 4 is a flowchart of a method of predicting data according
to an embodiment of the invention.

[00018] FIGURE 5 is a flowchart of a method of predicting data according
10 to another embodiment of the invention.

[00019] FIGURE 6 illustrates a principle of operation of a prediction buffer.

[00020] FIGURE 7A illustrates a principle of operation of a set of
prediction buffers.

[00021] FIGURE 7B illustrates a principle of operation of another set of
15 prediction buffers.

[00022] FIGURES 8A–C show block diagrams of apparatus according to
embodiments of the invention.

[00023] FIGURE 9A is a flowchart of a method of predicting data
according to a further embodiment of the invention.

20 [00024] FIGURE 9B is a flowchart of a method of predicting data
according to a further embodiment of the invention.

[00025] FIGURE 10 is a flowchart of a method of predicting data according
to a further embodiment of the invention.

[00026] FIGURE 11 is a flowchart showing an implementation of a task to test a TLM word and a task to correct a TLM word.

[00027] FIGURE 12 is a flowchart of a method of predicting data according to a further embodiment of the invention.

5 [00028] FIGURE 13A is a flowchart of a method of predicting data according to a further embodiment of the invention.

[00029] FIGURE 13B is a flowchart of a method of predicting data according to a further embodiment of the invention.

10 [00030] FIGURE 14 is a flowchart of a method of predicting data according to a further embodiment of the invention.

[00031] FIGURE 15A is a flowchart of a method of predicting data according to a further embodiment of the invention.

[00032] FIGURE 15B is a flowchart of a method of predicting data according to a further embodiment of the invention.

15 [00033] FIGURE 16A is a flowchart of a method of predicting data according to a further embodiment of the invention.

[00034] FIGURES 16B and 16C show block diagrams of apparatus according to embodiments of the invention.

20 [00035] FIGURE 16D is a flowchart of a method of predicting data according to a further embodiment of the invention.

[00036] FIGURES 16E and 16F show block diagrams of apparatus according to embodiments of the invention.

[00037] FIGURE 17 is a flowchart of a method of predicting data according to a further embodiment of the invention.

[00038] FIGURE 18 is a flowchart of an implementation of a task to resolve phase ambiguity.

[00039] FIGURE 19 is a flowchart of an implementation of a task to check integrity of a received subframe.

5 [00040] FIGURE 20 is a flowchart of an implementation P700a of a task P700 to predict a subframe.

[00041] FIGURE 21 is a flowchart of an implementation of a subtask to calculate and store a predicted subframe.

10 [00042] FIGURE 22 is a flowchart of an implementation of a subsubtask to check and correct for week number change.

[00043] FIGURE 23 is a flowchart of an implementation of a task to predict subframes.

[00044] FIGURE 24 is a flowchart of a method of providing predicted data according to an embodiment of the invention.

15 [00045] FIGURE 25A is a block diagram of a system according to an embodiment of the invention.

[00046] FIGURE 25B is a block diagram of a system according to another embodiment of the invention.

20 [00047] FIGURE 26 is a flowchart of an implementation of a task to transmit predicted data.

[00048] FIGURES 27A, B show block diagrams of apparatus according to embodiments of the invention.

[00049] FIGURES 28A, B show block diagrams of apparatus according to embodiments of the invention.

[00050] FIGURE 29 is a flowchart of an implementation of a task to transmit predicted data.

[00051] FIGURE 30 is a flowchart of an implementation P400c of a task P400 to transmit predicted data.

5 [00052] FIGURE 31 is a flowchart of an implementation of a task to transmit predicted data.

[00053] FIGURE 32 is a flowchart of an implementation of a task to test and correct old predicted data.

10 [00054] FIGURE 33 shows a block diagram of an apparatus according to an embodiment of the invention.

[00055] FIGURE 34 shows a block diagram of an apparatus according to an embodiment of the invention.

[00056] FIGURE 35 shows a block diagram of an apparatus according to an embodiment of the invention.

15

DETAILED DESCRIPTION

[00057] Throughout the course of this disclosure, the term “exemplary” should be interpreted to indicate one example or one instance and not to imply that there is any preference for that particular exemplar.

20 [00058] *A priori* knowledge of the data carried by a received signal may be applied to support long coherent integration. If the sequence of binary data symbols in a signal (e.g. the navigation data in a GPS signal) were known, then the problem of performance degradation due to data symbol integration during long coherent integration could be avoided, and better receiver
25 performance could be achieved. Such process will also be called “modulation

wipe-off" hereinafter. For example, modulation wipe-off could be applied to GPS data reception by predicting the navigation data.

[00059] As shown in FIGURE 1, a NAVSTAR GPS (hereinafter 'GPS') data frame comprises 1500 bits transmitted over a period of 30 seconds (i.e., at a rate of 50 bits per second). A GPS data message is transmitted over a block of twenty-five frames (commonly referred to as a "superframe"). Each frame within a superframe is divided into five 300-bit subframes. Accordingly, at a rate of 50 bits per second, each subframe has a duration of six seconds. Each subframe is further divided into ten 30-bit words, each word containing 24 bits of data and a 6-bit code string (commonly a cyclic redundancy code (CRC) checksum). The GPS CRC algorithm may be expressed as follows:

checksum bit 1 = XOR{data bits 1, 2, 3, 5, 6, 10, 11, 12, 13, 14, 17, 18, 20, 23};

checksum bit 2 = XOR{data bits 2, 3, 4, 6, 7, 11, 12, 13, 14, 15, 18, 19, 21, 24};

checksum bit 3 = XOR{data bits 1, 3, 4, 5, 7, 8, 12, 13, 14, 15, 16, 19, 20, 22};

checksum bit 4 = XOR{data bits 2, 4, 5, 6, 8, 9, 13, 14, 15, 16, 17, 20, 21, 23};

checksum bit 5 = XOR{data bits 1, 3, 5, 6, 7, 9, 10, 14, 15, 16, 17, 18, 21, 22, 24};

checksum bit 6 = XOR{data bits 3, 5, 6, 8, 9, 10, 11, 13, 15, 19, 22, 23, 24};

where data bit 1 and checksum bit 6 are the leftmost and rightmost bits, respectively, of a word as shown in FIGURE 1, and XOR{•} indicates the modulo-2 sum of the quantities within the brackets. Other signal formats may

use one or more other error-detecting code algorithms to produce checksums. These checksums may appear at the beginning or in the middle of a data word, for example, or may be interleaved with other bits of the word.

[00060] Each bit of a GPS subframe (including the bits of the CRC checksum) is also parity covered before transmission by XORing it with a specified one of the last two bits of the checksum of the previous word (as transmitted) as follows:

transmitted bit 1 = (data bit 1) XOR (previous transmitted bit 30);

transmitted bit 2 = (data bit 2) XOR (previous transmitted bit 30);

10 transmitted bit 3 = (data bit 3) XOR (previous transmitted bit 30);

...

transmitted bit 24 = (data bit 24) XOR (previous transmitted bit 30);

transmitted bit 25 = (checksum bit 1) XOR (previous transmitted bit 29);

15 transmitted bit 26 = (checksum bit 2) XOR (previous transmitted bit 30);

transmitted bit 27 = (checksum bit 3) XOR (previous transmitted bit 29);

20 transmitted bit 28 = (checksum bit 4) XOR (previous transmitted bit 30);

transmitted bit 29 = (checksum bit 5) XOR (previous transmitted bit 30);

transmitted bit 30 = (checksum bit 6) XOR (previous transmitted bit 29).

[00061] Other signal formats may use a different encoding, covering, or encryption scheme. Likewise, in another format only a portion of the bits of a data string may be encoded. Additionally, the GPS error-detecting and parity covering operations outlined above may be expressed in other forms (for example, they may be combined into a single operation producing an equivalent result, as described in section 2.5.2 of the GPS Standard document cited above and diagrams referenced therein).

[00062] As shown in FIGURE 2, each GPS subframe comprises in sequence a string (called a telemetry or 'TLM' word), a handover word, and eight message words. The handover word (or "HOW") comprises in sequence a seventeen-bit timestamp called a time-of-week (or "TOW") value, two flag bits, a three-bit subframe identification (or 'SFID') code indicating the position of the subframe within the frame, two parity control bits, and the six-bit checksum. The parity control bits (i.e. bits 23 and 24 of the HOW) are selected such that the final two bits of the checksum (i.e. bits 5 and 6 of the checksum, or bits 29 and 30 of the HOW) will be zero. Because the tenth (last) word of each subframe also has parity control bits at these locations, the parity covering operation described above will not alter the first and third words of a GPS subframe. In a method according to an embodiment of the invention, this effect may be applied to prevent data errors from propagating beyond subframe boundaries (e.g. by forcing the last two bits of a subframe to have values of zero).

[00063] As shown in FIGURE 3, each subframe of a GPS frame may indicate transmitter status or system status. Specifically, the message words of the first three subframes of each GPS data frame (which comprise the transmitter status group) contain orbital and clock data for the transmitting SV. Subframe 1 contains clock corrections and health information relating to the transmitting SV, and subframes two and three contain precise orbital data sets (also called 'ephemeris data') for the transmitting SV. Hereinafter, the message

data of subframes 1–3 is called the “ephemeris data set.” In the absence of data updates, the SV-specific ephemeris data set repeats at every frame.

[00064] Subframes four and five comprise the system status group, and the message words of these subframes contain almanac and other data that is
5 common to all of the satellites. In the absence of data updates, the system-wide almanac data set repeats only every superframe (i.e. every twenty-five frames or 125 subframes). Therefore, a complete data message is transmitted by a SV every 12.5 minutes. [For a more detailed description of the NAVSTAR GPS system, see, e.g., Global Positioning System: Theory and
10 Applications (Volume I), edited by B. W. Parkinson and J. J. Spilker Jr., 1996.]

[00065] FIGURE 4 shows a flow chart for a method for predicting data according to an embodiment of the invention. In task P100, data is received (e.g. navigation data is received from a SV). In task P200, “future” data (e.g.
15 data to be received in the future) is predicted based on at least the received data, and in task P300, the predicted future data is stored.

[00066] Assuming that no data updates occur, most of the data in a superframe may be expected to be the same as the data in the previous superframe. Given any sequence of 125 consecutive subframes, therefore, the
20 next 125 subframes may be expected to be largely the same. FIGURE 5 shows a method for predicting data according to another embodiment of the invention. In task P110, a GPS superframe is received. In task P310, since there is little change in the content of two adjacent superframes transmitted one after another, the received superframe is stored to a buffer (hereinafter
25 called a 'prediction buffer') as a prediction of a superframe to be transmitted by the SV at a later time, and typically as a prediction of the next superframe). It should be noted that the further into the future the prediction is used, the less accurate the prediction will be. Therefore, the most recently received superframe is most accurately used to predict the next superframe to be

received. The predicted future data (i.e., the previously received superframe) is stored in a prediction buffer. Task P310 may occur contemporaneously with task P110 such that at least a portion of the predicted data will be available before the entire superframe has been received.

5 [00067] FIGURE 6 shows one example of the operation of a prediction buffer suitable for use with a method as shown in FIGURE 4 or 5. The prediction buffer of this example may be implemented as a circular queue (also called a "ring buffer"). In a particular example, the buffer has a capacity of two GPS superframes (i.e. 250 subframes, or 25 minutes of navigation data). The predicted data bits are written to the buffer at locations as indicated
10 by a write pointer, which traverses the buffer in one direction only. Once the buffer has been filled, further writing operations will overwrite the data previously stored at the written locations. In a method as shown in FIGURE 5, the write pointer may indicate an effective time that is 12.5 minutes (i.e. one
15 GPS superframe) in advance of t_0 , where t_0 is defined as the time at which the observed data (corresponding to the predicted data being written) was received.

[00068] Using a buffer as shown in FIGURE 6, predicted data may be supplied for any part of a time window that spans from t_0 to 25 minutes (i.e. two GPS superframes) past t_0 . This twenty-five-minute window may be
20 arbitrarily extended (or reduced) by a simple change in buffer size. Depending on the specifications of a particular implementation, it may be desirable to write the received data to the buffer and/or retrieve predicted data from the buffer in units of 8-bit bytes, navigation message words or subframes, or
25 blocks of a different size.

[00069] As shown in FIGURE 7A, an array of buffers may be maintained for a limited number of SVs (e.g. only for a subset of the SVs that are currently visible). Alternatively, a prediction buffer comprising an array of 32 individual buffers may be maintained as shown in FIGURE 7B, with each

individual buffer being dedicated to a particular one of the GPS SVs and indexed according to the SV identification (ID) number (expressed in FIGURE 7B as a binary number from 00000 to 11111). In such an arrangement, any particular predicted data subframe in the buffer array may be
5 identified by specifying the ID number of the transmitting SV to select the relevant buffer and a subframe index number (e.g. the desired TOW value mod 250, for a 250-subframe buffer as shown in FIGURE 6) to select the subframe within the buffer.

[00070] FIGURE 8A shows a block diagram of an apparatus 100 according to an embodiment of the invention. Predicting entity 10 receives data (e.g. as
10 outputted by a receiver) and performs a method for data prediction as described herein. A prediction buffer (e.g. prediction buffer 20) includes a storage element that may be configured as described above with reference to FIGURES 6, 7A, and/or 7B. For example, a prediction buffer may comprise
15 one or more semiconductor memory devices [e.g. dynamic or static random-access memory (RAM)], ferroelectric memory devices, and/or optical storage devices. Such a device may be fabricated as a dedicated chip or package, or such a device may be integrated into a chip or package that includes one or more other elements of the apparatus and/or of an appliance that incorporates
20 such an apparatus. In one implementation, the prediction buffer is coupled to a predicting entity via one or more buses that may carry control, data, and/or address signals.

[00071] A prediction buffer may have a dual-port or other mechanism to allow simultaneous storage and retrieval of data. A storage element of a
25 prediction buffer may also store other data of the apparatus and/or of an appliance that incorporates such an apparatus. In such a case, the prediction buffer need not reside in a fixed part of a storage element, and an area of the storage element may be used at one time to store prediction data and at another

time to store other data. In some implementations, a storage element of a prediction buffer may be accessible by devices other than the predicting entity.

[00072] A predicting entity (e.g. predicting entity 10) may include a processing unit having one or more microprocessors, digital signal processors, and/or other arrays of logic elements. Such an array may be fabricated as a dedicated chip or package, or such an array may be integrated into a chip or package that includes one or more other elements of the apparatus and/or of an appliance that incorporates such an apparatus. For example, a predicting entity may include an embedded processor and/or a processor core fabricated into an application-specific integrated circuit (ASIC).

[00073] A predicting entity performs a method as described herein (and possibly other functions) by executing instructions (in sequence and/or in parallel) according to one or more programs or routines that may be hard-wired or stored in read-only memory (ROM), programmable ROM (PROM) such as erasable or electrically erasable PROM (EPROM or EEPROM, respectively), RAM, or nonvolatile RAM (NVRAM) such as flash memory. In some implementations, at least a part of the instructions and/or associated values (such as variables accessed during execution) may be stored in a storage element of the prediction buffer. Alternatively, a predicting entity may receive all or part of its instructions from one or more other devices or appliances (e.g. over a network connection that may be wired and/or wireless). A predicting entity may also execute instructions relating to other functions of the apparatus and/or of an appliance that incorporates such an apparatus. Instead of or addition to such instructions, a predicting entity may also perform a method as described herein in response to signals (e.g. interrupt requests) received from other devices within or outside of the apparatus and/or from other programs or routines executing on the processing unit.

[00074] FIGURE 8B shows a block diagram of an apparatus 110 according to an alternate embodiment of the invention that includes a signal receiver 30

that receives a transmitted signal and outputs data to predicting entity 12, which calculates and stores predicted data to prediction buffer 21. FIGURE 8C shows a block diagram of an implementation 110a of apparatus 110 that includes a GPS receiver 32. Receiver 32 receives a signal transmitted by a SV
5 and outputs GPS navigation data to predicting entity 14, which calculates and stores predicted data to prediction buffer 22 as described herein.

[00075] In one implementation, each individual prediction buffer comprises four-byte (i.e. 32-bit) cells containing predicted data and additional information. For example, each cell may have a valid flag, which is set to
10 show that the cell contains a valid prediction. At the start of operation, all valid flags are reset. After a SV comes into view, received data becomes available and the valid bits are set as predictions are stored. Thereafter, valid flags may be reset in accordance with events that may affect prediction reliability, or no resetting may be performed. In another implementation, a
15 valid flag of more than one bit may be used to indicate differing degrees of reliability.

[00076] Each 32-bit cell may contain a 30-bit navigation word and a one-bit valid flag. Alternatively, the ten navigation words may be stored as a 300-bit subframe with one or more valid flags. Alternatively, the data of each
20 navigation word may be stored as 24 data bits (i.e. without checksum calculation and/or without parity covering), or the data of each ten-word subframe may be stored as 240 bits or 30 bytes. The storage length of a predicted subframe may be further reduced by omitting other redundant information such as the parity control bits and/or other bits of the data message
25 that may easily be regenerated. In the latter cases, checksum calculation, parity covering, and/or calculation of other redundant information may be performed at some point while or after the data is retrieved from the buffer (for example, in response to a prediction request as described below).

[00077] Although the method of FIGURE 5 has little processing overhead, portions of the received data may change from one superframe to the next. For example, at least some portions of a GPS navigation data message will change from one superframe to the next. Because of the checksum and parity covering operations, a change to only one bit may corrupt a significant portion of the remainder of a GPS subframe.

[00078] One portion of a GPS message that changes at every subframe is the timestamp that appears as the first 17 bits of the HOW (i.e. the TOW value). Reset at midnight Saturday–Sunday, the TOW value indicates the GPS time of the next subframe transition. Each unit in the TOW value indicates a period of six seconds (i.e. one GPS subframe), and the TOW value is incremented by exactly one unit from one subframe to the next. As a result of this incrementing, the timestamps (and therefore the HOWs) in GPS subframes as predicted by the method of FIGURE 5 will be incorrect.

[00079] Because the last two bits of the HOW are defined to have values of zero, it may be desirable to suppress propagation of HOW errors into GPS subframes 3–10 by forcing these bits to zero (i.e. before referencing them in checksum or parity covering operations for the next subframe). The HOW may also be skipped or discarded during the prediction, or the interval for which prediction is requested may be adjusted (with appropriate notification to the requestor) so that the predicted data retrieved from the prediction buffer does not include a HOW. Alternatively, a unit applying the predicted data may ignore the predicted HOW.

[00080] In FIGURE 9A, a method according to an alternate embodiment of the invention is presented. A data message is received in task P105, and task P205 updates one or more timestamps in the message. Task P215 generates new error-detecting codes that may reflect a change in the message as a result of the new timestamps, and task P315 stores the predicted message to a prediction buffer.

[00081] FIGURE 9B shows a flowchart for an implementation of a method as shown in FIGURE 9A. In task P210, the TOW of each received subframe is incremented by 125. In task P220, the checksum for each words of each subframe is regenerated, the parity control bits 23 and 24 of words two and ten
5 are calculated, and all bits are parity covered as described above. Alternatively, only the checksum of word 2 and the parity control bits 23 and 24 of word 2 may be regenerated. One or more among tasks P210, P220, and P320 may contemporaneously with task P110 such that at least a portion of the predicted data may be processed and/or available before the entire superframe has been
10 received. In another implementation, tasks P210 and P220 may be performed after the received data is stored to the prediction buffer, with the appropriate valid bits being reset until these tasks are completed. Assuming perfect signal reception and no data updates, a completely accurate prediction may be expected.

15 [00082] In a method of predicting data according to a further embodiment of the invention, a fixed string (e.g. the GPS TLM word) is tested. The GPS TLM word includes a constant 8-bit preamble for synchronization and, in most cases, the TLM word is the same over all GPS subframes for a period of one week. Occasionally, however, a SV will transmit a subframe in which the
20 regular TLM word is replaced by an irregular one (e.g. a TLM word that contains a classified system message). While the occurrence of an irregular TLM word is largely unpredictable, the appearance of irregular TLM words in consecutive subframes is highly unlikely. By storing a copy of the regular TLM word, and substituting this copy in the prediction for an irregular TLM
25 word that was received, the number of TLM word prediction errors can be reduced by about 50%.

[00083] FIGURE 10 shows a flowchart for a particular implementation of a method as described above. In task P112, a portion of a data message (e.g. a GPS subframe) is received. In task P212, a fixed string of the portion is tested.

The fixed string may be a TLM word in a GPS data message, or a synchronization and/or training sequence (e.g. for channel estimation) in another data message. The result of such a test may be used for correcting the string in the prediction or, alternatively, flagging the error (e.g. by issuing a warning signal or resetting the valid flag for the affected predicted data block). In task P322, the predicted data is stored to a prediction buffer (e.g. as indexed by the SV ID and TOW).

[00084] FIGURE 11 shows one implementation P212a of task P212 that performs GPS TLM word testing, along with an implementation of a task P770 that performs TLM correction. In task P562, the received TLM word is checked to see if it is different from the last TLM word received. If the same TLM word has been received twice consecutively, then it is stored (e.g. to a microprocessor register or other memory location) as the regular TLM word in task P564. In task P566, the received TLM is stored in memory as the last received TLM word. In task P770, the regular TLM is substituted for the received TLM in the predicted data.

[00085] In the message data of a GPS data message, two principal types of updates may occur. The first is an update to the ephemeris data, which occurs once every two hours and starts exactly at the GPS hour boundary. Ephemeris updates leave the almanac data unchanged, and because the complete ephemeris data set has a length of only 3 subframes, each two-hour period will include only 18 seconds during which the ephemeris prediction is likely to be erroneous. Even within this span of three subframes, limited prediction can still be performed because the first two words of each of the three missing GPS subframes can be predicted: the TLM word is most likely unchanged and the flag bits of the HOW are also unchanged, while the remainder of the HOW may be generated from past received data and the GPS time.

[00086] In applying a method for predicting data that predicts the next superframe (e.g. as shown in FIGURE 5), it may be necessary in some

casesSV) to wait for 12.5 minutes before the first prediction for a SV is available. (e.g. after a cold start or during a reacquisition of a SV), even though the ephemeris data set repeats FIGURE 12 shows a method according to a further embodiment of the invention in which predictions for much of a
5 GPS data message may be available after only 30 seconds.

[00087] In task P120, words 3–10 of subframes 1–3 are received (any other data received may be processed or ignored). In task P330, the words 3–10 are stored to the prediction buffer as predictions of the corresponding words in the following frame. As noted above, the parity encoding and CRC operations on
10 words 3–10 do not depend on the contents of words 1 and 2. The TLM word (word 1) may also be included in the prediction if desired, as it is expected to change only infrequently.

[00088] FIGURE 13 shows a method in which the techniques described above are applied to obtain predicted data for an entire subframe after only 30
15 seconds (subframes 1–3 only). In task P230, the TOW of the subframe received in task P130 is updated to correspond to the next frame (i.e. its value is incremented by 5). In task P240, the parity check bits are recalculated based on the other bits of the predicted future data, the checksum is regenerated, and covering is performed as described above with respect to task P220. In task
20 P340, the predicted subframe is stored to the prediction buffer at a location corresponding to the same subframe of the following frame. Note that while this method is useful for providing predictions of subframes 1–3 after only 30 seconds, the almanac data of subframes 4 and 5 repeats only every superframe even in the absence of a update, and the information necessary to provide a
25 prediction for the following frame may not generally be available.

[00089] Upon a cold start of a GPS receiver (for example, a handheld GPS receiver, or a GPS receiver which is installed in a vehicle or in a mobile unit such as a cellular telephone), or in the case of an acquisition of an ascending SV at low elevation or a reacquisition of a SV, a method as shown in FIGURE

13 may be used to predict up to 60% of the bits of a GPS data message after only a 30-second delay. If an operation that applies the predicted data can be synchronized to be active only during subframes 1–3 of each received frame, then the prediction may be 100% efficient. In such a case, it is assumed that
5 the receiver applying the predicted data is or may be synchronized to GPS time (within the initial 30 seconds of operation if necessary).

[00090] FIGURES 14 and 15 show versions of the methods of FIGURES 12 and 13 that are modified to allow duplicate prediction. In these embodiments, the ephemeris data is copied not only to the next frame in the
10 prediction buffer but to one or more other frames as well. Under normal operation, such an operation might be redundant. In case of an interruption in or a corruption of the received data signal (which may be indicated by a checksum failure, and which may be caused by, e.g., a satellite dropout occurring at low elevation angles), however, duplicate prediction can help to
15 reduce or avoid the effect of the data loss. In a distributed implementation of a method according to an embodiment of the invention, predicted data may be forwarded to other predictors (e.g. across a local-area network) to alleviate the effects of localized SV invisibilities.

[00091] An update to the almanac table, which occurs when new almanac
20 data is uploaded to the SV, is the other principal type of update in a GPS system. The GPS almanac table is divided into 50 sections, sections 1–32 corresponding to individual SVs, and sections 33–37 being reserved for other devices such as additional transmitters deployed at airports. Such other devices have assigned Gold codes and may appear to a GPS receiver as just
25 another SV.

[00092] Although the exact timing and frequency of the almanac updates is unpredictable, each update takes 12.5 minutes (or one superframe) to complete, and an update is most likely to occur once every 20–40 hours. It has been observed that when a satellite updates an almanac page, it will also

update all pages that are to be transmitted by the other satellites. In a method according to a further embodiment of the invention, a copy of the most recent almanac data set is maintained and used to overwrite the almanac portions of the prediction buffer for a SV when an update is detected at that SV. Such an operation may reduce the number of almanac prediction errors by a factor of N, where N is the number of operational satellites.

[00093] Within every frame, the first three subframes can be validly predicted, except for the ones in the first frame because, again, the same ephemeris data is used. Thus, out of the 12.5 minutes = 750 seconds, 30+(24x12) = 318 seconds are lost. By using the almanac update method described earlier, this outage can be reduced by a factor of 5.

[00094] In accordance with one embodiment of the invention, the almanac table is corrected. As explained above, the almanac data set is the same for all satellites. Unfortunately, although subframe boundaries occur at the same moment at all GPS SVs, the almanac updates are not synchronized between satellites, so that any two SVs may each be transmitting a different version of the same almanac subframe at any given time. Furthermore, in any given frame for any given satellite, it is possible that there is a mix of old and new almanac pages.

[00095] In accordance with another embodiment of the invention, old almanac data is used in the predictions. That is, for satellites that have just risen over the horizon, the old almanac data as it was last seen can be used because there is a good chance that those satellites did not get uploads during the 6-7 hours while they were at negative elevation angles. If a change in the almanac bits is observed, then there was indeed an update, and in this case, all almanac predictions for the given satellites must be replaced with the known most recent almanac data. The basic mechanism to use old data is to adjust the TOW or timestamp upon transmission. If the TOW of the predicted subframe matches the current, then a valid prediction can be transmitted. If there is a

mismatch, then that means the data is old, which can still be used as prediction, but the TOW and subsequently the CRC have to be updated.

[00096] (FIGURE 18) At the GPS week boundary (midnight Saturday–Sunday), the frame and subframe numbers are reset. In a method according to
5 a further embodiment of the invention, changes in the week change correction. In this embodiment, when the TOW approaches its maximum value, we know that a week change follows. That is, when the predicted TOW indicates a week change, the TOW value is corrected and the week number in word 3 of subframe 1 is incremented. Since at the week boundary both the frame and
10 subframe numbers are reset, the index in the prediction buffer is adjusted accordingly. It should be noted that while the total number of subframes in a week (100,800) is an integer multiple of 5, it is not an integer multiple of 125. Thus, at week boundaries, there will be a jump in the frame index sequence.

[00097] The operation of the bit prediction algorithm is explained in the
15 flowcharts shown in FIGS. 3-6. First, a current subframe from a GPS signal is received in step 300 and is stored in a buffer in step 310. Next, a next corresponding subframe is predicted using the methods described above in step 320. The predicted subframe is saved and the process ends in step 330. Referring to FIG. 4, flowchart 2 illustrates the process of whether a subframe
20 prediction is feasible, which takes a few milliseconds, or the user has to wait for the next subframe, which takes 6 seconds.

[00098] First, a subframe from an SV is received in task P510. Next, (resolve BPSK ambiguity, task P520 and FIGURE 14) the process determines whether bit 30 of word 2 is zero in step 402, and if the bit 30 of word 2 is zero,
25 then the subframe is stored in a buffer in step 404. If the bit 30 of word 2 is not zero, then all the bits in the received subframe are inverted in step 406 and stored in the buffer in step 404.

[00099] After storing the received subframe in the buffer in step 404, the process determines whether the subframe header is valid in step 408. (test preamble in task P540, check CRC in task P550) If the subframe header is not valid, then the process will exit in step 412 and wait for the next subframe,
5 which takes 6 seconds. If the subframe header is valid, then the process checks to see if the CRC is valid for all 10 words in step 410. Again, if the CRC for all 10 words is not valid, then the process will exit in step 416 and wait for the next subframe.

[000100] (task P570) Next, the process determines whether there is a valid
10 prediction for this subframe in step 422. If there is no valid prediction for this subframe, then the process will perform subframe prediction in step 434, which is shown in flowchart 3 in FIG. 5. If there is a valid prediction for the subframe, then the process will determine whether the received and predicted TOW match in step 424. If the received and predicted TOW do not match in
15 step 424, then the process will perform the subframe prediction in step 434 in flowchart 3. If the received and predicted TOW do match, then the process will go to the next step which is to determine whether there is a perfect match between the received and predicted subframes in step 426. If there is no perfect match, then the process will determine the errorcode in step 428 and
20 log the error in step 430. If there is a perfect match between the received and the predicted subframes, then the process will perform the subframe prediction in step 434 in flowchart 3. After the errorcode is logged in step 430, the process determines whether the subframe is an almanac subframe in step 432, and if it is not, then the process will perform the subframe prediction in step
25 434. If the process determines that the subframe is an almanac subframe, then the process will perform the almanac update in step 436 as shown in flowchart 4 in FIG. 6. After the almanac update is done in step 436, the process will perform the subframe prediction in step 434.

[000101] The subframe prediction task P700 as shown in FIG. 14 will now be described. The value of the TOW as received is saved in task P710. Next, the process determines whether the subframe was an almanac subframe in task P720. If the received subframe is an almanac subframe, then the loop increment value is set to 125 in task P730. If the received subframe is not an almanac subframe, then the loop increment value is set to 5 in task P740. In task P750, the TOW is incremented by the loop increment value. Calculation and storage of the predicted subframe is performed in task P760.

[000102] Task P760 in FIGURE 17. Correct TOW for week change in task P765 (FIGURE 18). The process determines whether the TOW is less than the number of seconds in a week in task P762. If the TOW is not less than the number of seconds in a week, then the process reduces the TOW modulo to the number of seconds in a week in task P763 and increments the WIN by 1 in task P764. The process will discard the TLM and use the regular TLM instead as shown in task P770.

[000103] In task P775, the process generates the CRC for the subframe. The process then performs an XOR scrambling operation in task P780, stores the predicted subframe at the appropriate position in the prediction buffer (e.g. as indicated by the TOW) in task P785, and sets a valid flag in task P787.

[000104] The almanac update flowchart as shown in FIG. 6. will now be explained. The process starts the almanac update at step 600. Next, the process extracts the page ID in step 602. The process then determines if either the page ID is 51 or if it is a valid SV ID in step 604, then the process will extract the old and new TOWs in step 608, and store the TOWs for the SV in a buffer in step 610. If the page ID is neither 51 nor is it a valid SV, then the process will pull the old and new TOWs from the buffer in step 606. After steps 606 and 610, the process proceeds to determine whether the old TOW and the last almanac update time are the same in step 612. If the old TOW and the last almanac update time are the same, then the process will reset the

almanac update table as shown in step 616; if the old TOW and the last almanac update time are not the same, then the process will determine whether the new TOW and the last almanac time are the same in step 614.

[000105] If the new TOW and the last almanac update time are not the same,
5 then the process will exit and end the almanac update process as shown in step 620. If new TOW and the last almanac update time are the same, then the process will determine whether the page ID is a valid SV ID, a dummy SV ID or if it is 51, 55 or 56 as shown in step 618. If the page ID is not a valid SV ID, a dummy SV ID or 51, 55 or 56, then the process ends as shown in step
10 624. If the page ID is a valid SV ID, a dummy SV ID or 51, 55 or 56, then the process will determine whether the subframe is valid in the almanac update table in step 622. If the subframe is not valid in the almanac update table, then the process will store the subframe in the almanac update table in step 628, set a valid flag for this subframe in step 630 and ends the almanac update process
15 and begins the subframe prediction process at step 632. Going back to step 622, if the process determines that the subframe is valid in the almanac update table, then the process will pull all valid subframes from the almanac update table and substitute words 2-10 in the predicted subframes for this SV in step 626 and proceed to do the subframe prediction in step 632.

20 [000106] Based on the above considerations, an estimate on the prediction can be performed. Assuming that almanac updates occur every 20 hours, then in a given 20 hour- or 72,000 second-period, for any satellite, there will be one almanac update and 10 ephemeris updates. The outage due to the almanac update can be estimated as $318 / 5 = 64$ seconds, while the outage due
25 to the ephemeris update will be $10 \times 18 = 180$ seconds. In addition, during almanac updates, based on experimental data, it is expected that approximately five irregular TLM messages will occur, which are transmitted within the ephemeris subframes. This will add an additional 30 seconds of prediction error. Thus, the rate of erroneous subframe predictions can be estimated as

$(180 + 64 + 30) / 72,000 = 0.38\%$. The experimental data shows about a 0.5% error rate. The difference is due to unpredictable irregular system messages contained in the reserved data fields, for example, classified data.

[000107] The bit prediction error rate could be estimated as one-half of the subframe error rate. This would seem reasonable if it is assumed that the bits are changed with 50% probability. This assumption, however, is invalid for two reasons. First, in an update, often only a few less significant bits are changed in the navigation data. This results in a reduced bit error rate. Second, when a word prediction is erroneous, then with 50% probability, bit 30 of the CRC will be changed, which will invert all data bits in the following word. Overall, the second effect prevails, which gives a bit error rate slightly above one-half of the subframe error rate. This is in good match with the experimental data.

[000108] Seemingly, it is an additional problem that the unknown 29th and 30th bits of the unpredicted subframes propagate through the XOR mechanism into the predictable part of the data. Obviously, if all four hypotheses according to all possible values of bits 29 and 30 are determined, then one of the prediction hypotheses will always be correct. Further, if it is considered that it is sufficient to predict all bits with a modulo 2 additive constant (i.e., it is okay to have all bits inverted, to get the same GPS performance), then it can be claimed that two hypotheses are sufficient. Unfortunately, every doubling of the number of hypotheses also doubles the probability of false alarm (i.e., picking the wrong timeshift/frequency in the code search). Multiple hypotheses can be dismissed altogether, however, if the bit prediction always start at subframe boundaries. This is because the second and tenth words in every subframe contain bits 23 and 24, which are determined in such a way that bits 29 and 30 of the second and tenth words are always zeros. The data sequence that follows then can be perfectly predicted.

[000109] Even if we do not start the prediction at subframe boundaries, the performance degradation of the GPS receiver due to the bit error propagation through the XOR mechanism will still be limited. This is because most of the bit errors can be modeled as a random modulation with a ± 1 digital waveform that has a very low bit rate of $50 \text{ Hz} / 30 = 1.6 \text{ Hz}$, where 50 Hz is the navigation bit rate and the factor of 30 is the number of bits in a word. Thus, when the GPS signal detection is done in the frequency domain, then the spectra is expected to be widened by only 1.6 Hz. The discrete periodic components of the modulation spectra will be zeros because the +1 and -1 modulating error bits are equally likely.

[000110] FIGURE 2 shows a flow chart for a method for predicting navigation data according to another embodiment of the invention. In task P400, a portion of the predicted data is provided to a requestor. As described below, the requestor may be a GPS receiver (e.g. a mobile unit), and the predicted data may be used to support a long coherent integration period. In other embodiments, the predicting entity may push predicted data to another entity instead of (or in addition to) responding to a request for data.

[000111] In one implementation of a system according to an embodiment of the invention, predictions for word 2 of each subframe may be ignored (e.g. by the mobile unit applying the predictions) in order to avoid the TOW inaccuracy described above.

[000112] As described below, a method according to an embodiment of the invention may be applied to support position location upon request in mobile receivers. The prediction method can be implemented fully at a central site, which has access to the unobstructed satellite signals, or at the receiver side, in which case the central site only sends a minimal set of information that enables the receiver to perform the navigation data prediction.

[000113] The prediction start time and duration may be adjusted on demand, according to the terms of the requestor's query. In this manner, the overhead that would be incurred in transmitting more of the navigation data than the requestor needs is avoided.

5 [000114] A position determining entity (PDE) may include an apparatus that performs a method of prediction as described herein. In a cellular system for mobile wireless communications, a base station may include a PDE (which may receive GPS data from or may itself include a GPS receiver). In other implementations, a base station including a PDE may receive GPS data from a
10 reference GPS receiver which receives and forwards the data to more than one base station. Alternatively, a PDE may be located apart from the base station. In a cellular system for wireless communications, for example, a base station controller (BSC) or mobile services controller (MSC) may include the PDE rather than the base station, and such a PDE may support prediction
15 capabilities for more than one base station. In other implementations and/or in other systems, the elements of a PDE may be found in more than one location. Note that in a system that already uses GPS signals for synchronization purposes (e.g., a CDMA cellular telephone system), it may even be possible to incorporate one or more PDEs into the existing structure.

20 [000115] Data from a single GPS receiver may be used to support prediction over a wide geographical area. One practical limit to the size of such an area may be keeping the set of visible SVs substantially constant over the area. If the receiver cannot see all of the SVs visible to a particular mobile unit, for example, it may not be able to supply the prediction data needed by the mobile
25 unit to perform modulation wipeoff. In another implementation, GPS data received by receivers in different locations may be combined to provide appropriate prediction data to mobile units over a wider geographical area.

[000116] A PDE need not be constrained by geography in the same manner, and that it is possible for a single PDE to support a method of prediction as

described herein over an arbitrarily large area. On the other hand, the effective distance between a PDE and an entity receiving the predicted data (e.g. a mobile unit) may be limited by the delay between the transmission of the prediction data and its reception (also called 'latency'). In some applications
5 (e.g. in which the latency is not severe enough to affect position location accuracy), predictions may be supplied sufficiently in advance to counteract such effects of latency.

[000117] In a system according to an embodiment of the invention, a requesting entity (e.g. a mobile unit) sends a query to a PDE that comprises a
10 request for a string of predicted data (a 'prediction string'). Several different query formats are possible. For example, the request may indicate the starting and ending times of a GPS data period for which a corresponding prediction string is desired. In another example, the request may indicate the starting time and duration of a GPS data period for which a corresponding prediction
15 string is desired. In a further example, the starting time and/or duration of a GPS data period for which a corresponding prediction string is desired may be inferred (e.g. according to a predetermined relation) from a time at which the query is transmitted by the requestor or received by the PDE.

[000118] In a system according to an alternate embodiment of the invention,
20 a PDE may send a prediction string to one or more entities without having received an explicit corresponding request. For example, a prediction string that corresponds to a GPS data period having a predetermined length and/or starting time may be broadcast by a PDE at predetermined intervals. In another example, transmission of a series of prediction strings according to a
25 predetermined schedule may be initiated at least in part by a requesting entity such as a mobile unit. In a further example, initiation of the transmission of a prediction string may be determined or influenced at least in part by an event such as a registration event (e.g. upon power up of a mobile unit, movement of a mobile unit between service areas, etc.). In a further example, the

characteristics of the corresponding GPS data period may be determined or influenced at least in part by environmental conditions (e.g. the service rates currently in effect (peak or off-peak), the quality of the signal received from an SV, etc.).

5 **[000119]** In an apparatus according to a further embodiment of the invention, a requesting entity such as a mobile unit includes a local GPS receiver. Information received by the local GPS receiver may be stored for offline processing. To support modulation wipeoff in this case, the mobile unit may
10 send a request for a historical string (i.e. a string of GPS data that was received by a PDE in the past) as opposed to a prediction string. Although the processing requirements for a PDE in a system including such an apparatus may be reduced (e.g. because no prediction is required), this reduction may be offset by increased storage requirements at the requesting entity for the information received by the local GPS receiver.

15 **[000120]** In an apparatus according to a further embodiment of the invention, a requesting entity such as a mobile unit includes a local GPS receiver. Almanac information received by the local GPS receiver from a visible SV is stored in an almanac table. Information from the almanac table is then used to support modulation wipeoff on GPS signals received by the local GPS receiver
20 from SVs that are less visible. In this manner, an accurate position and/or time determination may be obtained even though only a limited number of satellites may be visible. Note that such an apparatus may be used even without a PDE.

[000121] Note in particular a transmission link between a PDE and a requesting entity need not be wireless. For example, a PDE may include a
25 server connected to the Internet, and a requesting entity may comprise any device connected to the Internet that may request (e.g. via a HTTP connection) and/or apply a prediction and/or historical string as described herein. For such an application, it is possible that latency would be significantly greater than might occur over an application that included a wireless connection between a

base-station-based PDE and a requesting mobile unit. In another example, the prediction request and/or prediction string is transmitted over a connection that conforms to at least a portion of one or more versions of the Bluetooth™ specification.

5 [000122] Alternatively, the PDE may send a prediction string on its own initiative. In another implementation, a mobile unit may collect and log GPS signals on its own. These signals may be stored for processing offline. In order to perform modulation wipe-off, the mobile will need to obtain GPS data from the past. Note that no prediction is required in this case. However, this
10 variation may be less likely to be implemented because of the increased storage requirements it imposes on the mobile unit. (Using past data for past/present/future modulation wipe-off).

[000123] In a case where the mobile unit can see one or more satellites well but not one or more others (for example, it is indoors but next to a
15 window), the almanac data received from the visible satellite(s) may be used to predict the data received from the less visible satellite(s). In such a case, the data may be received by the mobile unit instead of a reference receiver, and the mobile unit may be a stand-alone unit that does not require a PDE.

[000124] Several different formats for the prediction string (or the historical
20 string) are possible. When the receiver has to service frequent satellite measurement requests, then the communication overhead will be reduced if instead of sending the navigation bit prediction every time, the central site only sends the minimal amount of information that enables the receiver to perform the bit prediction. For example, the preamble, week number (WIN), TOW,
25 subframe ID (SFID) and CRC are unnecessary to be communicated because they can be easily regenerated at the receiver if a local clock is available. A significant part of the rest of the navigation data has to be conveyed to the receiver anyway when autonomous receiver mode is to be supported.

- [000125] As such, an object of a mobile unit is to measure the GPS signal phase. However, there is no direct way for the mobile unit to measure a signal phase. This is because for each possible phase delay, the mobile unit must test to see whether a correlation signal is there. There are more than 2,000 possible locations in the phase circle in a particular mobile implementation. Specifically, there are 2,046 possible locations from the 1,023 chips (in one cycle of the known code CA) with a sampling rate of two (x2). The number of locations that must be searched can be reduced, however, if it is known where or approximately where searching should take place on the phase circle.
- 10 [000126] The mobile unit thus may ask for a prediction at some point in the future. Usually, a start time of 10 seconds in the future is typical. It should be noted that the mobile unit only asks for a sequence of predicted bits when it needs it, for example, when the mobile unit has been requested to provide its position.
- 15 [000127] The request by the mobile unit contains two elements, a time at which to begin the prediction in the future, and duration of the prediction. The length of the duration is tied to the integration period. Typically, thirty phase hypotheses is provided, and the integration period is greater than 20 milliseconds. This results in a long coherent integration requiring modulation wipe-off. Typically, it takes one-half to one second for the mobile unit to test all of the phase hypotheses, depending on the mobile unit's request parameters at the time such as the time to first fix, the rate of data transfer from the base station to the mobile unit, and the processing or correlation time required.
- 20 [000128] When the receiver does a cold start, then the central site sends over all data fields, omitting the redundant parts mentioned above. The receiver stores this data in memory. The central site also keeps an up-to-date copy of the data that it sent to the receiver. The receiver can extract the ephemeris, almanac and SV health data from the received information if it works in

autonomous operating mode. In any case, the bit prediction can be carried out at the receiver using the data stored in its memory. If there were no navigation data updates, then no further communication between the central site and the receiver would be necessary to sustain continuous bit prediction. When an
5 update indeed occurs, then the central site only sends the difference (bit-wise XOR) between the new data and the stored data to the receiver. The difference is transmitted using run-length coding, to further reduce the communication overhead. The receiver then updates its version of the navigation data. The central site does the same, so that it always has a precise copy of the
10 navigation data memory content of the receiver. To maintain synchronism between the two copies of the navigation data, the receiver periodically sends checksums for all words or subframes. If there is a mismatch, then the data contents of the words or subframes in question will be retransmitted from the central site to the receiver.

15 **[000129]** The disclosed apparatus, method, and system are provided to enable any person of ordinary skill in the art to make or use the present invention. The various modifications to the disclosed apparatus, method, and system will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments without the use
20 of inventive faculty. Thus, the present invention is not intended to be limited to the apparatuses, methods, and systems described herein but is to be accorded the widest scope consistent with the claims set forth below.

WHAT IS CLAIMED IS:

74769-520

35

CLAIMS:

1. A method of providing predicted navigation data, said method comprising:

receiving GPS data, including a subframe of a
5 GPS signal, from a transmitter;

predicting future navigation data based on the received GPS data;

storing the predicted future navigation data to a buffer;

10 receiving a prediction request defining a time interval for which prediction is requested;

obtaining predicted future navigation data corresponding to the time interval from the buffer; and

transmitting the predicted future navigation data.

15 2. The method of predicting navigation data according to claim 1 wherein the GPS data includes a plurality of received subframes of a GPS signal, the method further comprising;

incrementing a timestamp associated with one among
20 the plurality of received subframes by a predetermined value.

3. The method of predicting navigation data according to claim 2, wherein the incrementing a timestamp associated with one among the plurality of received subframes by a
25 predetermined value is performed before said predicting future navigation data and predicting said future navigation data is based on the received GPS data with incremented timestamp.

74769-520

36

4. The method of predicting navigation data according to claim 1, further including:

error correction testing a fixed string of received GPS data; and

5 correcting the tested fixed string if the test indicates that such correction is necessary.

5. The method of predicting navigation data according to claim 2, wherein the timestamp has a predetermined maximum value, the method further including:

10 detecting that the timestamp is at the predetermined maximum value; and

correcting the timestamp in response to detecting that the timestamp is at the predetermined maximum value.

6. The method of predicting navigation data according to claim 1, wherein the predicted future navigation data includes parity bits, the method further including:

recalculating the parity bits of the predicted future navigation data based on the state of the other bits in the predicted future navigation data.

20 7. The method of predicting navigation data according to claim 1, wherein the predicted future navigation data includes checksum bits, the method further including:

regenerating the checksum bits of the predicted future navigation data based on the state of the other bits in the predicted future navigation data.

8. The method of predicting navigation data according to claim 1, wherein storing the predicted future navigation

74769-520

37

data includes storing the predicted future navigation data in a predetermined location of a buffer.

9. The method of predicting navigation data according to claim 8, wherein the received GPS data includes a plurality of received subframes, the method further comprising incrementing a timestamp associated with one among the plurality of received subframes by a predetermined value, and wherein storing the predicted future navigation data further includes selecting said predetermined location as a buffer location associated with a time indicted by the incremented timestamp.

10. The method of predicting navigation data according to claim 2, wherein the incrementing a timestamp associated with one among the plurality of received subframes by a predetermined value is performed after said storing the predicted future data.

11. The method of predicting navigation data according to claim 2, wherein the incrementing a timestamp associated with one among the plurality of received subframes by a predetermined value is performed contemporaneously with at least one of said receiving, storing, and predicting.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A




FIG. 9B




FIG. 10




FIG. 11




FIG. 12




FIG. 13A




FIG. 13B




FIG. 14




FIG. 15A




FIG. 15B




FIG. 16A




FIG. 16B




FIG. 16C




FIG. 16D




FIG. 16E





FIG. 16F






FIG. 18




FIG. 19





FIG. 20

FIG. 21







FIG. 22

FIG. 23






FIG. 24




FIG. 25A




FIG. 25B




FIG. 26




FIG. 27A




FIG. 27B




FIG. 28A




FIG. 28B





FIG. 29

FIG. 30







FIG. 31






FIG. 33




FIG. 34




FIG. 35

receive data

P100

predict data

P200

store predicted data

P300

