

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 11,463,563 B2**
(45) **Date of Patent:** **Oct. 4, 2022**

(54) **ELECTRONIC DEVICE INCLUDING INDICATOR**

(71) Applicant: **Samsung Electronics Co., Ltd.**, Suwon-si (KR)

(72) Inventors: **Taewon Kim**, Suwon-si (KR); **Minsoo Kim**, Suwon-si (KR); **Bongsub Kim**, Suwon-si (KR); **Sangmin Lee**, Suwon-si (KR); **Jongheon Lee**, Suwon-si (KR); **Jiwoo Lee**, Suwon-si (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.**, Suwon-si (KR)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2011/0063783 A1* 3/2011 Shim G06F 1/1615 361/679.01

2014/0218321 A1 8/2014 Lee et al.
(Continued)

FOREIGN PATENT DOCUMENTS

JP 10-200463 * 7/1998
JP 10-200463 A 7/1998
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 300 days.

OTHER PUBLICATIONS

International Search Report dated Jun. 19, 2020, issued in International Application No. PCT/KR2020/003312.

Primary Examiner — Yuwen Pan
Assistant Examiner — Angelica M Perez
(74) *Attorney, Agent, or Firm* — Jefferson IP Law, LLP

(21) Appl. No.: **16/829,340**

(22) Filed: **Mar. 25, 2020**

(65) **Prior Publication Data**
US 2020/0314222 A1 Oct. 1, 2020

(30) **Foreign Application Priority Data**
Mar. 28, 2019 (KR) 10-2019-0035518

(51) **Int. Cl.**
H04M 1/02 (2006.01)
H05K 5/00 (2006.01)
(Continued)


(52) **U.S. Cl.**
CPC **H04M 1/0218** (2013.01); **G02B 6/0055** (2013.01); **G02B 6/0088** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04M 1/0218; H04M 1/0268; G02B 6/0055; G02B 6/0088; G02B 6/0091; H05K 5/0017; H05K 5/0026
See application file for complete search history.

(57) **ABSTRACT**

An electronic device including an indicator is provided. The electronic device includes a first housing structure including a first face oriented in a first direction, and a second face oriented in a second direction opposite the first direction, a second housing structure including a third face oriented in a third direction, and a fourth face oriented in a fourth direction opposite the third direction, a hinge structure rotatably connecting the first housing structure and the second housing structure to each other, the hinge structure configured to provide a folding axis that is a rotating center of the first housing structure and the second housing structure, a flexible display extending from the first face to the third face across the hinge structure, and a hinge case disposed between the first housing structure and the second housing structure to accommodate the hinge structure therein to conceal or protect the hinge structure.

20 Claims, 10 Drawing Sheets



- (51) **Int. Cl.**
F21V 8/00 (2006.01)
H05K 5/02 (2006.01)

- (52) **U.S. Cl.**
CPC *G02B 6/0091* (2013.01); *H04M 1/0268*
(2013.01); *H05K 5/0004* (2013.01); *H05K*
5/0017 (2013.01); *H05K 5/0226* (2013.01)

- (56) **References Cited**

U.S. PATENT DOCUMENTS

2016/0109908	A1	4/2016	Siddiqui
2017/0131741	A1	5/2017	In-Sung et al.
2018/0024590	A1	1/2018	Nakamura et al.
2018/0129459	A1	5/2018	Sylvan et al.

FOREIGN PATENT DOCUMENTS

JP	2018-013849	A	1/2018
KR	10-2006-0008624	A	1/2006
KR	1020060008624	*	1/2006
KR	10-0630127	B1	9/2006
KR	10-2014-0099133	A	8/2014

* cited by examiner




FIG.2




FIG.3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG.12




FIG.13




FIG. 14




FIG. 15




FIG.16

1

ELECTRONIC DEVICE INCLUDING INDICATOR**CROSS-REFERENCE TO RELATED APPLICATION(S)**

This application is based on and claims priority under 35 U.S.C. § 119 of a Korean patent application number 10-2019-0035518, filed on Mar. 28, 2019, in the Korean Intellectual Property Office, the disclosure of which is incorporated by reference herein in its entirety.

BACKGROUND

1. Field

The disclosure relates to an electronic device. More particularly, the disclosure relates to an electronic device including an indicator using a light-emitting element.

2. Description of Related Art

As electronic, information, and communication technologies have developed, various functions have come to be integrated into a single electronic device. For example, a smart phone includes functions of an audio reproduction device, an imaging device, and a digital diary, in addition to a communication function, and further various functions may be implemented in the smart phone through additional installation of applications.

Without being limited to the functions (e.g., applications) and information provided in an electronic device itself, the user is capable of searching for and selectively acquiring more information by connecting to a network. In connecting to a network, a direct connection scheme (e.g., wired communication) may provide fast and stable communication establishment, but a utilization region may be limited to a fixed position or a predetermined extent of space. In connecting to a network, a wireless communication scheme has fewer constraints on position and space, and the transmission speed and stability of the wireless communication scheme are gradually reaching the same level as those of the direct connection scheme. In the future, the wireless communication scheme is expected to provide faster and more stable communication establishment than the direct connection scheme.

As the use of personal and portable electronic devices such as smart phones is becoming more common, there is increasing user demand for portability and ease of use. For example, a touch screen display may provide a virtual keypad that replaces a physical input device (e.g., a keypad) while serving as an output device that outputs a screen, for example, visual information. As a result, electronic devices have come to be capable of providing the same or further improved usability (e.g., a larger screen) while being reduced in size. In the future, if a flexible (e.g., foldable or rollable) display is commercially available, the portability and ease of use of electronic devices is expected to be further improved.

The above information is presented as background information only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the disclosure.

SUMMARY

In an embodiment, when an event occurs (e.g., when a call or various messages are received), the electronic device may

2

allow the user to recognize the occurrence of the event by activating the display or using sound or vibration. However, in the state in which the display is folded or rolled up, it may be difficult for a user to recognize the occurrence of the event even if the display is activated. In another embodiment, when the sound or vibration of the electronic device is deactivated, the user may not recognize the occurrence of the event in the state in which the display is folded or rolled up.

In another embodiment, the electronic device may further include a sub-display, for example, a display capable of outputting a screen to the outside even in the state in which the electronic device is folded or rolled up. However, depending on the position where the electronic device is placed, the sub-display may be blocked from view and thus limited to provide visual information to the user.

Aspects of the disclosure are to address at least the above-mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the disclosure is to provide an electronic device including an indicator that displays visual information at least in an environment in which the display is blocked from view.

Another aspect of the disclosure is to provide an electronic device including an indicator that implements various visual effects in the exterior thereof.

Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

In accordance with an aspect of the disclosure, an electronic device is provided. The electronic device includes a first housing structure including a first face oriented in a first direction, a second face oriented in a second direction opposite the first direction, and a first side member at least partially surrounding a space between the first face and the second face, a second housing structure including a third face oriented in a third direction, a fourth face oriented in a fourth direction opposite the third direction, and a second side member at least partially surrounding a space between the third face and the fourth face, a hinge structure rotatably connecting the first housing structure and the second housing structure to each other, the hinge structure configured to provide a folding axis that is a rotating center of the first housing structure and the second housing structure, a flexible display extending from the first face to the third face across the hinge structure, a hinge case disposed between the first housing structure and the second housing structure to accommodate therein the hinge structure to conceal or protect the hinge structure, and one or more first light-emitting elements disposed on an outer face of the hinge case. The electronic device may be configured to transmit light emitted from the one or more first light-emitting elements to outside of the electronic device.

In accordance with another aspect of the disclosure, an electronic device is provided. The electronic device includes a first housing structure, a second housing structure, a hinge structure disposed between the first housing structure and the second housing structure, the hinge structure being configured to couple the first housing structure and the second housing structure to be rotatable between a position at which the first housing structure and the second housing structure are unfolded to be arranged side by side with respect to each other (hereinafter, referred to as a "first position") and a position at which the first and second housing structures are folded to face each other (hereinafter, referred to as a "second" position), a flexible display extend-

ing from one face of the first housing structure to one face of the second housing structure across the hinge structure, a hinge case disposed between the first housing structure and the second housing structure to accommodate the hinge structure therein so as to conceal or protect the hinge structure, one or more first light-emitting elements disposed on an outer face of the hinge case, and an optical cover mounted on the outer face of the hinge case and including a translucent region formed in a region at least corresponding to the one or more first light-emitting elements. The one or more first light-emitting elements may emit light to outside of the electronic device through the translucent region.

According to various embodiments, the electronic device is capable of providing visual information to the user using the indicator even in an environment in which the display is concealed. For example, when an event such as reception of a call or a message occurs, the user easily recognizes the event. In an embodiment, the first light-emitting element constituting the indicator may emit red light, green light, blue light, or white light, and the electronic device is able to implement various visual effects on the exterior thereof using the first light-emitting element. For example, the indicator according to various embodiments may provide a visual decoration effect on the exterior of the electronic device while providing visual information about the occurrence of an event.

Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

FIG. 1 is a perspective illustrating an electronic device in the unfolded state according to an embodiment of the disclosure;

FIG. 2 is a view illustrating the electronic device of FIG. 1 in the folded state according to an embodiment of the disclosure;

FIG. 3 is an exploded perspective view illustrating an electronic device according to an embodiment of the disclosure;

FIG. 4 is an exploded perspective view illustrating a hinge cover of an electronic device according to an embodiment of the disclosure;

FIG. 5 is a plan view illustrating an inner face of a hinge cover according to an embodiment of the disclosure;

FIG. 6 is a cross-sectional view of the hinge cover taken along line A-A in FIG. 5 according to an embodiment of the disclosure;

FIG. 7 is a projective plan view illustrating a portion of the hinge cover according to an embodiment of the disclosure;

FIG. 8 is a cross-sectional view of the hinge cover taken along line B-B in FIG. 5 according to an embodiment of the disclosure;

FIG. 9 is a cross-sectional view illustrating a hinge cover in which the hinge cover is cut in the longitudinal direction according to an embodiment of the disclosure;

FIG. 10 is a projective plan view illustrating a portion of a hinge cover according to an embodiment of the disclosure;

FIG. 11 is a cross-sectional view illustrating a hinge cover in which the hinge cover is cut in a direction perpendicular to the longitudinal direction according to an embodiment of the disclosure;

FIG. 12 is a projective plan view illustrating a portion of a hinge cover according to an embodiment of the disclosure;

FIG. 13 is a cross-sectional view illustrating a hinge cover in which the hinge cover is cut in a direction perpendicular to the longitudinal direction according to an embodiment of the disclosure;

FIG. 14 is a projective plan view illustrating a portion of a hinge cover according to an embodiment of the disclosure;

FIG. 15 is a cross-sectional view illustrating a hinge cover in which the hinge cover is cut in a direction perpendicular to the longitudinal direction according to an embodiment of the disclosure; and

FIG. 16 is a cross-sectional view illustrating a hinge cover in which the hinge cover is cut in a direction perpendicular to the longitudinal direction according to an embodiment of the disclosure.

Throughout the drawings, it should be noted that like reference numbers are used to depict the same or similar elements, features, and structures.

DETAILED DESCRIPTION

The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit of the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.

The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration purpose only and not for the purpose of limiting the disclosure as defined by the appended claims and their equivalents.

It is to be understood that the singular forms "a," "an," and "the" include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to "a component surface" includes reference to one or more of such surfaces.

It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as "A or B," "at least one of A and B," "at least one of A or B," "A, B, or C," "at least one of A, B, and C," and "at least one of A, B, or C," may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases.

As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

As used herein, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

Various embodiments as set forth herein may be implemented as software (e.g., the program) including one or more instructions that are stored in a storage medium (e.g., internal memory or external memory) that is readable by a machine (e.g., the electronic device). For example, a processor (e.g., the processor) of the machine (e.g., the electronic device) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer’s server, a server of the application store, or a relay server.

According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added.

Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the

same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

FIG. 1 is a perspective illustrating the unfolded state of an electronic device 100 according to an embodiment of the disclosure.

FIG. 2 is a view illustrating the folded state of the electronic device 100 of FIG. 1 according to an embodiment of the disclosure.

In the following detailed description, a configuration in which a pair of housing structures are rotatably and/or pivotably coupled by a hinge structure may be exemplified. It is noted that an electronic device according to various embodiments disclosed herein is not limited by the embodiments. For example, an electronic device according to various embodiments disclosed herein may include three or more housing structures, and a pair of housing structures in the embodiments disclosed below may mean “two housing structures rotatably coupled to each other among three or more housing structures”.

Referring to FIG. 1, an electronic device 100 may include a pair of housing structures 110 and 120 rotatably and/or pivotably coupled to each other via a hinge structure (e.g., the hinge structure 164 in FIG. 3) so as to be folded with respect to each other, a hinge cover 165 that covers the foldable portions of the pair of housing structures 110 and 120, and a display 130 (e.g., a flexible display or a foldable display) disposed in a space formed by the pair of housing structures 110 and 120. In an embodiment, the electronic device 100 may include a foldable housing in which the pair of housing structures 110 and 120 are coupled to be rotatable from a position at which the pair of housing structures 110 and 120 are folded to face each other to a position at which the pair of housing structures 110 and 120 are unfolded to be parallel to each other. Herein, a face on which the display 130 is disposed may be defined as a front face of the electronic device 100, and a face opposite the front face may be defined as a rear face of the electronic device 100. In addition, the face surrounding the space between the front face and the rear face may be defined as a side face of the electronic device 100.

In an embodiment, the pair of housing structures 110 and 120 may include a first housing structure 110 including a sensor region 131d, a second housing structure 120, a first rear cover 140, and a second rear cover 150. The pair of housing structures 110 and 120 of the electronic device 100 are not limited to the shape and assembly illustrated in FIGS. 1 and 2, but may be implemented by other shapes or other combinations and/or assemblies of components. For example, in another embodiment, the first housing structure 110 and the first rear cover 140 may be integrally formed, and the second housing structure 120 and the second rear cover 150 may be integrally formed. In another embodiment, the first housing structure 110 may include a first rear cover 140, and the second housing structure 120 may include a second rear cover 150.

According to an embodiment, the first housing structure 110 and the second housing structure 120 may be disposed on opposite sides about a first axis (e.g., a folding axis A), and may have generally symmetrical shapes with respect to the folding axis A. In some embodiments, the first housing structure 110 and the second housing structure 120 are

rotatable with respect to the hinge structure **164** or the hinge cover **165** about different folding axes, respectively. For example, the first housing structure **110** and the second housing structure **120** may be coupled to the hinge structure **164** or the hinge cover **165** to be individually rotatable. By rotating the first housing structure **110** and the second housing structure **120** about the folding axis A or about different folding axes, respectively, it is possible to rotate the first housing structure **110** and the second housing structure **120** from the positions at which the first housing structure **110** and the second housing structure **120** are folded to each other to the positions at which the first housing structure **110** and the second housing structure **120** are inclined with respect to each other or the positions at which the first housing structure **110** and the second housing structure **120** are unfolded to be parallel to each other.

Herein, the wording “positioned side by side” or “extended side by side” may mean the state in which two structures are at least partially positioned next to each other or the state in which at least portions positioned next to each other are arranged parallel. In some embodiments, the wording “arranged side by side” may mean that the two structures are arranged to look in parallel or in the same direction while being located next to each other. Expressions such as “side by side”, “parallel”, and the like may be used in the following detailed description, which will be readily understood according to the shapes or arrangements of the structures with reference to the accompanying drawings.

According to an embodiment, the angle or difference between the first housing structure **110** and the second housing structure **120** may vary depending on whether the electronic device **100** is in the unfolded state (the extended state, flat state, or open state), in the folded state, or in the intermediate state. According to an embodiment, unlike the second housing structure **120**, the first housing structure **110** may further include the sensor region **131d** in which various sensors are disposed. However, the first housing structure **110** and the second housing structure **120** may have mutually symmetrical shapes in the regions other than the sensor region **131d**. In another embodiment, the sensor region **131d** may be further disposed in or replaced with at least one region of the second housing structure **120**.

In an embodiment, in the unfolded state of the electronic device **100**, the first housing structure **110** may include a first face **111** connected to a hinge structure (e.g., the hinge structure **164** in FIG. 3) and arranged to face the front side of the electronic device **100**, a second face **112** facing away from the first face **111**, and a first side member **113** surrounding at least a part of the space between the first face **111** and the second face **112**. In an embodiment, the first side member **113** may include a first side face **113a** arranged parallel to the folding axis A, a second side face **113b** extending from one end of the first side face **113a** in a direction perpendicular to the folding axis A, and a third face **113c** extending from the other end of the first side face **113a** in a direction perpendicular to the folding axis A. In describing various embodiments, expressions such as “parallel” or “perpendicular” are used in connection with the arrangements of the above-described side faces, but in some embodiments, the expressions may include the meaning of “partially parallel” or “partially perpendicular”. In some embodiments, expressions such as “parallel” or “perpendicular” may include an inclined arrangement relationship in an angular range within 10 degrees.

In an embodiment, in the unfolded state of the electronic device **100**, the second housing structure **120** may include a third face **121** connected to the hinge structure (e.g., the

hinge structure **164** in FIG. 3) and arranged to face the front side of the electronic device **100**, a fourth face **122** facing away from the third face **121**, and a second side member **123** surrounding at least a part of the space between the third face **121** and the fourth face **122**. In an embodiment, the second side member **123** may include a fourth side face **123a** arranged parallel to the folding axis A, a fifth side face **123b** extending from one end of the fourth side face **123a** in a direction perpendicular to the folding axis A, and a sixth face **123c** extending from the other end of the fourth side face **123a** in a direction perpendicular to the folding axis A. In an embodiment, in the folded state, the third face **121** may face the first face **111**. In some embodiments, although there are some differences in specific shapes, the second side member **123** may be made, in shape and material, to be substantially the same as the first side member **113**.

In an embodiment, the electronic device **100** may include a recess **101** formed to accommodate the display **130** through structural shape coupling of the first housing structure **110** and the second housing structure **120**. The recess **101** may have substantially the same size as the display **130**. In an embodiment, due to the sensor region **131d**, the recess **101** may have two or more different widths in a direction perpendicular to the folding axis A. For example, the recess **101** may have a first width w_1 between a first portion **120a** of the second housing structure **120**, which is parallel to the folding axis A and a first portion **110a** formed at an edge of the sensor region **131d** of the first housing structure **110** and a second width w_2 between a second portion **120b** of the second housing structure **120** and a second portion **110b** of the first housing structure **110**, which does not correspond to the sensor region **131d** and is parallel to the folding axis A. In this case, the second width w_2 may be longer than the first width w_1 . For example, the recess **101** may have the first width W_1 formed from the first portion **110a** of the first housing structure **110** to the first portion **120a** of the second housing structure **120**, which are asymmetric to each other, and the second width W_2 formed from the second portion **110b** of the first housing structure **110** to the second portion **120b** of the second housing structure **120**, which are symmetric to each other. In an embodiment, the first portion **110a** and the second portion **110b** of the first housing structure **110** may have different distances from the folding axis A, respectively. The widths of the recess **101** are not limited to the illustrated example. In various embodiments, the recess **101** may have two or more different widths due to the shape of the sensor region **131d** or the asymmetric portions of the first housing structure **110** and the second housing structure **120**.

In an embodiment, the first housing structure **110** and the second housing structure **120** may be at least partially formed of a metal material or a non-metal material having the rigidity of a level selected in order to support the display **130**. In another embodiment, the first housing structure **110** and the second housing structure **120** may at least partially include a conductive material. When the first housing structure **110** and the second housing structure **120** include a conductive material, the electronic device **100** may transmit/receive radio waves using the portions formed of the conductive material in the first housing structure **110** and the second housing structure **120**. For example, a processor or a communication module of the electronic device **100** may perform wireless communication using a part of each of the first housing structure **110** and the second housing structure **120**.

In an embodiment, the sensor region **131d** may be formed to have a predetermined region adjacent to one corner of the

first housing structure **110**. However, the arrangement, shape, and size of the sensor region **131d** is not limited to the illustrated example. For example, in another embodiment, the sensor region **131d** may be provided at another corner of the first housing structure **110** or in any region between the upper and lower end corners. In another embodiment, the sensor region **131d** may be disposed in at least one region of the second housing structure **120**. In another embodiment, the sensor region **131d** may be disposed to extend over the first housing structure **110** and the second housing structure **120**. In an embodiment, the electronic device **100** may include components exposed to the front face of the electronic device **100** through the sensor region **131d** or through one or more openings provided in the sensor region **131d**, and may perform various functions using these components. In various embodiments, the components disposed in the sensor region **131d** may include, for example, at least one of a front camera device, a proximity sensor, an illuminance sensor, an iris recognition sensor, an ultrasonic sensor, or an indicator.

In an embodiment, the first rear cover **140** may be disposed on the second face **112** of the first housing structure **110**, and may have a substantially rectangular periphery. In an embodiment, the periphery of the first rear cover **140** may be at least partially wrapped by the first housing structure **110**. Similarly, the second rear cover **150** may be disposed on the fourth face **122** of the second housing structure **120**, and at least a portion of the periphery of the second rear cover **150** may be at least partially wrapped by the second housing structure **120**.

In the illustrated embodiment, the first rear cover **140** and the second rear cover **150** may have substantially symmetrical shapes with respect to the folding axis A. According to another embodiment, the first rear cover **140** and the second rear cover **150** may have various different shapes. In a still another embodiment, the first rear cover **140** may be formed integrally with the first housing structure **110**, and the second rear cover **150** may be formed integrally with the second housing structure **120**.

In an embodiment, the first rear cover **140**, the second rear cover **150**, the first housing structure **110**, and the second housing structure **120** may provide, through a mutually coupled structure, a space in which various components (e.g., a printed circuit board, an antenna module, a sensor module, or a battery) of the electronic device **100** may be arranged. According to an embodiment, one or more components may be disposed or visually exposed on the rear face of the electronic device **100**. For example, one or more components or sensors may be visually exposed through a first rear region **141** of the first rear cover **140**. In various embodiments, the sensors may include a proximity sensor, a rear camera, and/or a flash. In another embodiment, at least a portion of the sub-display **152** may be visually exposed through a second rear region **151** of the second rear cover **150**.

The display **130** may be disposed in a space formed by the pair of housing structures **110** and **120**. For example, the display **130** may be seated in the recess (e.g., the recess **101** in FIG. 1) formed by the pair of housing structures **110** and **120**, and may be disposed to occupy substantially the majority of the front face of the electronic device **100**. For example, the front face of the electronic device **100** may include the display **130**, and a region (e.g., a peripheral region) of the first housing structure **110** and a region (e.g., a peripheral region) of the second housing structure **120**, which are adjacent to the display **130**. In an embodiment, the rear face of the electronic device **100** may include the first

rear cover **140**, a region (e.g., a peripheral region) of the first housing structure **110** adjacent to the first rear cover **140**, the second rear cover **150**, and a region (e.g., a peripheral region) of the second housing structure **120** adjacent to the second rear cover **150**.

According to an embodiment, the display **130** may mean a display in which at least one region is deformable into a planar face or a curved face. In an embodiment, the display **130** may include a folding region **131c**, a first region **131a** disposed on one side of the folding region **131c** (e.g., the right region of the folding region **131c**), and a second region **131b** disposed on the other side of the folding region **131c** (e.g., the left region of the folding region **131c**). For example, the first region **131a** may be disposed in the first face **111** of the first housing structure **110**, and the second region **131b** may be disposed in the third face **121** of the second housing structure **120**. For example, the display **130** may extend from the first face **111** to the third face across the hinge structure **164** in FIG. 3, and at least a region corresponding to the hinge structure (e.g., the folding region **131c**) may be a flexible region that is deformable from a flat plate shape to a curved shape.

In an embodiment, the region division of the display **130** is exemplary, and the display **130** may be divided into multiple regions (e.g., four or more regions or two regions) depending on the structure or functions thereof. For example, in the embodiment illustrated in FIG. 1, the folding region **131c** extends in the direction of the vertical axis (e.g., the y axis in FIG. 3) parallel to the folding axis A, and the regions of the display **130** may be divided with reference to the folding region **131c** or the folding axis (the axis A). However, in another embodiment, the regions of the display **130** may be divided with reference to another folding region (e.g., a folding region parallel to the horizontal axis (e.g., the x axis in FIG. 3)) or another folding axis (e.g., a folding axis parallel to the x axis in FIG. 3). The aforementioned region division of the display is merely physical division based on the pair of housing structures **110** and **120** and the hinge structure (e.g., the hinge structure **164** in FIG. 3), and the display **130** may display one full screen substantially through the pair of housing structures **110** and **120** and the hinge structure (e.g., the hinge structure **164** in FIG. 3).

According to an embodiment, the first region **131a** and the second region **131b** may have generally symmetrical shapes about the folding region **131c**. However, unlike the second region **131b**, the first region **131a** may include a notch region (e.g., the notch region **133** in FIG. 3), which provides the sensor region **131d**. The first region **131a** may have a shape symmetrical to the second region **131b** in the region other than the sensor region. In other words, the first region **131a** and the second region **131b** may include mutually symmetrical portions and mutually asymmetrical portions.

Referring to FIG. 3, the hinge cover **165** may be disposed between the first housing structure **110** and the second housing structure **120** so as to cover internal components (e.g., the hinge structure **164** in FIG. 3). In an embodiment, the hinge cover **165** may be covered by a portion of each of the first and second housing structures **110** and **120** or may be exposed to the outside depending on the operating state of the electronic device **100** (the unfolded state or the folded state). According to an embodiment, an indicator **169** may be disposed in the hinge cover **165**. The indicator **169** may include a first light-emitting element **415** or a translucent region **421** to be described with reference to FIG. 4 or the like. According to an embodiment, the first light-emitting element **415** may be concealed from the exterior of the electronic device **100**, and the light emitted by the first

11

light-emitting element **415** may be transmitted to the outside of the electronic device **100** through the translucent region **421**.

According to an embodiment, as illustrated in FIG. 1, when the electronic device **100** is in the unfolded state, the hinge cover **165** may be blocked from view by the first housing structure **110** and the second housing structure **120** so as not to be exposed. In an embodiment, when the electronic device is in the unfolded state, a portion of the indicator **169** may be visually exposed between the first rear cover **140** and the second rear cover **150**. As another example, as illustrated in FIG. 2, when the electronic device **100** is in the folded state (e.g., the completely folded state), the hinge cover **165** may be exposed to the outside between the first housing structure **110** and the second housing structure **120**. As still another example, when the first housing structure **110** and the second housing structure **120** are in the intermediate state in which the first housing structure **110** and the second housing structure **120** are folded to form a predetermined angle therebetween, a portion of the hinge cover **165** may be exposed to the outside between the first housing structure **110** and the second housing structure **120**. In this case, the exposed region may be smaller than that in the completely folded state. In an embodiment, the hinge cover **165** may include a curved face. According to an embodiment, when the electronic device is in the folded state or in the intermediate state, the indicator **169** may be more visually exposed than in the unfolded state. In another embodiment, when the electronic device is in the folded state, the indicator **169** (e.g., the translucent region **421** in FIG. 4) may be visually fully exposed. In another embodiment, the extent to which the indicator **169** is visually exposed may differ from that illustrated above depending on the shapes or positional relationship of the first housing structure **110** and the second housing structure **120**. In some embodiments, even when the electronic device **100** is placed such that the sub-display **152** faces the floor in the folded state, the indicator **169** may not be blocked from view. For example, even when the display **130** or the sub-display **152** is in the state in which it is impossible for the display **130** or the sub-display **152** to provide visual information to the user, the indicator **169** may be exposed to the outside so as to provide visual information to the user.

Hereinafter, the operations of the first housing structure **110** and the second housing structure **120** and respective regions of the display **130** depending on the operating state of the electronic device **100** (e.g., the unfolded state (extended state) and the folded state) will be described.

In an embodiment, when the electronic device **100** is in the unfolded state (e.g., the state of FIG. 1), the first housing structure **110** and the second housing structure **120** may form an angle of 180 degrees therebetween, and the first region **131a** and the second region **131b** of the display may be disposed to face the same direction, for example, to display screens in parallel directions. In addition, the folding region **131c** may form the same plane as the first region **131a** and the second region **131b**.

In an embodiment, when the electronic device **100** is in the folded state (e.g., the state of FIG. 2), the first housing structure **110** and the second housing structure **120** may be disposed to face each other. For example, when the electronic device **100** is in the folded state (e.g., the state of FIG. 2), the first region **131a** and the second region **131b** of the display **130** may form a narrow angle (e.g., 0 to 10 degrees) therebetween and may face each other. When the electronic device **100** is in the folded state (e.g., the state of FIG. 2),

12

at least a portion of the folding region **131c** may form a curved face having a predetermined curvature.

In an embodiment, when the electronic device **100** is in the intermediate state, the first housing structure **110** and the second housing structure **120** may be disposed to form therebetween a predetermined angle of, for example, 90 degrees or 120 degrees. For example, in the intermediate state, the first region **131a** and the second region **131b** of the display **130** may form therebetween an angle larger than that in the folded state and smaller than that in the unfolded state. At least a portion of the folding region **131c** may be formed in a curved face having a predetermined curvature, and the curvature in this case may be smaller than that in the folded state.

FIG. 3 is an exploded perspective illustrating the electronic device **100** according to an embodiment of the disclosure.

Referring to FIG. 3, in an embodiment, the electronic device **100** may include a display **130**, a support member assembly **160**, at least one printed circuit board **170**, a first housing structure **110**, a second housing structure **120**, a first rear cover **140**, and a second rear cover **150**. Herein, the display **130** may be referred to as a display module or a display assembly.

The display **130** may include a display panel **131** (e.g., a flexible display panel), and at least one plate **132** or layer on which the display panel **131** is seated. In an embodiment, the plate **132** may be disposed between the display panel **131** and the support member assembly **160**. The display panel **131** may be disposed on at least a portion of one face (e.g., the face in the Z direction in FIG. 3) of the plate **132**. The plate **132** may be formed in a shape corresponding to that of the display panel **131**. For example, a region of the plate **132** may be formed in a shape corresponding to that of the notch region **133** in the display panel **131**.

The support member assembly **160** may include a first support member **161**, a second support member **162**, a hinge structure **164** disposed between the first support member **161** and the second support member **162**, a hinge cover **164** that covers the hinge structure **165** when the hinge structure **164** is viewed from the outside, and a wiring member **163** (e.g., a flexible printed circuit board (FPCB)) extending across the first and second support members **161** and **162**.

In an embodiment, the support member assembly **160** may be disposed between the plate **132** and at least one printed circuit board **170**. For example, the first support member **161** may be disposed between the first region **131a** of the display **130** and a first printed circuit board **171**. The second support member **162** may be disposed between the second region **131b** of the display **130** and a second printed circuit board **172**.

In an embodiment, the wiring member **163** and the hinge structure **164** may be at least partially disposed inside the support member assembly **160**. The wiring member **163** may be disposed in a direction across the first support member **161** and the second support member **162** (e.g., the x-axis direction). The wiring member **163** may be disposed in a direction (e.g., the x-axis direction) perpendicular to the folding axis (e.g., the y axis or the folding axis A in FIG. 1) of the folding region **131c**.

As described above, the at least one printed circuit board **170** may include the first printed circuit board **171** disposed on the first support member **161** side and the second printed circuit board **172** disposed on the second support member **162** side. The first printed circuit board **171** and the second printed circuit board **172** may be disposed in a space formed by the support member assembly **160**, the first housing

13

structure **110**, the second housing structure **120**, the first rear cover **140**, and the second rear cover **150**. Components for implementing various functions of the electronic device **100** may be mounted on the first printed circuit board **171** and the second printed circuit board **172**.

In an embodiment, the first housing structure **110** and the second housing structure **120** may be assembled to each other so as to be coupled to the opposite sides of the support member assembly **160** in the state in which the display **130** is coupled to the support member assembly **160**. The first housing structure **110** and the second housing structure **120** may be slidably coupled to the opposite sides of the support member assembly **160**, for example, to the first support member **161** and the second support member **162**, respectively. The first support member **161** and the second support member **162** are substantially accommodated in the first housing structure **110** and the second housing structure **120**. According to an embodiment, the first support member **161** and the second support member **162** may be interpreted as portions of the first housing structure **110** and the second housing structure **120**, respectively.

In an embodiment, the first housing structure **110** may include a first rotational support face **114** (e.g., a fourth side face **514** in FIG. 5 to be described later), and the second housing structure **120** may include a second rotational support face **124** (e.g., an eighth side face **524** in FIG. 5 to be described later), which corresponds to the first rotational support face **114**. The first rotational support face **114** and the second rotational support face **124** may include curved faces corresponding to curved faces included in the hinge cover **165**.

In an embodiment, when the electronic device **100** is in the unfolded state (e.g., the state of FIG. 1), the first rotational support face **114** and the second rotational support face **124** cover the hinge cover **165**, so that the hinge cover **165** may not be exposed or may be minimally exposed to the rear face of the electronic device **100**. In an embodiment, when the electronic device **100** is in the unfolded state (e.g., the state of FIG. 2), the first rotational support face **114** and the second rotational support face **124** rotate along the curved faces included in the hinge cover **165**, so that the hinge cover **165** can be maximally exposed to the rear face of the electronic device **100**.

In the foregoing detailed description, in the first housing structure **110**, the second housing structure **120**, the first side member **113**, the second side member **123**, and the like, ordinal numbers are used merely to distinguish components. It is noted that various embodiments are not limited by the description of the ordinal numbers. For example, although the sensor region **131d** is illustrated as being formed in the first housing structure **110**, the sensor region **131d** may be formed in the second housing structure **120** or may be formed in both the first and second housing structures **110** and **120**. In another embodiment, a configuration in which the first rear region **141** is disposed in the first rear cover **140** and the sub-display **152** is disposed on the second rear cover **150**, is illustrated. However, both the first rear region **141** on which a sensor or the like is disposed and the sub display **152** for outputting a screen may be disposed on any one of the first rear cover **140** and the second rear cover **150**.

In the following detailed description, the configuration of an indicator (e.g., the indicator **169** in FIG. 2) will be described with reference to FIG. 4 or the like, and the electronic device **100** of FIGS. 1 to 3 may be referred to as needed. In describing the following embodiments, the components that are the same as those of the preceding embodiments or can be easily understood through the preceding

14

embodiments may be denoted by the same reference numerals or the reference numerals may be omitted, and the detailed descriptions thereof may also be omitted. In addition, hereinafter, the state of FIG. 1 in which the first housing structure **110** and the second housing structure **120** are unfolded to be arranged side by side in relation to each other may be referred to as a “first position”, and the state of FIG. 2 in which the first housing structure **110** and the second housing structure **120** are folded to face each other may be referred to as a “second position”.

FIG. 4 is an exploded perspective view illustrating a hinge cover (e.g., the hinge cover **165** in FIG. 2) of an electronic device (e.g., the electronic device **100** in FIG. 1) according to an embodiment of the disclosure.

FIG. 5 is a plan view illustrating an inner face of a hinge cover **400** (e.g., the hinge case **401**) according to an embodiment of the disclosure.

Referring to FIGS. 4 and 5, the hinge cover **400** of the electronic device may include a hinge case **401** and an optical cover **402**, and may include at least one first light-emitting element **415** disposed between the hinge case **401** and the optical cover **402**, for example, on the outer face of the hinge case **401**. The optical cover **402** may be coupled to enclose the outer face of the hinge case **401**, and may include a translucent region **421**. The translucent region **421** may be located to at least correspond to the first light-emitting element **415**, and may visually conceal the first light-emitting element **415** from the outside while transmitting light, emitted by the first light-emitting element **415**, to the outside. For example, the indicator **169** of FIG. 1 or FIG. 2 may include the translucent region **421** and the first light-emitting element **415**.

According to various embodiments, the hinge case **401** may accommodate the hinge structure **164** of FIG. 1 therein. One or more hinge structures **164** may be mounted on or fixed to an inner face of the hinge case **401** by fastening members such as screws. According to an embodiment, the hinge structures **164** may be mounted on the inner face of the central portion in the longitudinal direction of the hinge case **401** (e.g., the y direction in FIG. 3), and depending on the size of the electronic device (e.g., the electronic device **100** in FIG. 1), the hinge structures **164** may also be mounted at respective opposite ends of the hinge case **401**. When two or more hinge structures **164** are disposed, an inner space (e.g., the inner space of the hinge case **401**) between two adjacent hinge structures **164** may be used as a space for wiring that connects electronic components (e.g., the first printed circuit board **171** and the second printed circuit board **172** in FIG. 3) accommodated in each of the first and second housing structures (e.g., the first and second housing structures **110** and **120** in FIG. 1).

According to various embodiments, the hinge case **401** may include an accommodation recess **411** formed in the outer face thereof. The accommodation recess **411** is a space for accommodating or arranging the first light-emitting element **415** therein, and may at least partially extend in the longitudinal direction of the hinge case **401**. According to various embodiments, the accommodation recess **411** may extend along a path that bypasses the central portion of the hinge case **401**, for example, the portion in which the hinge structure **164** is mounted (hereinafter, referred to as a “mounting portion **411a**”). According to an embodiment, in the portion in which the accommodation recess **411** is formed, the thickness of the hinge case **401** may be smaller than that of the other portions. When the hinge structure **164** is mounted in the portion having the smaller thickness, the fastening force of the fastening member may be reduced or

may cause deformation of the hinge case **401**. For example, by forming the accommodation recess **411** in a path or shape that does not overlap with the mounting portion **411a**, it is possible to prevent the deformation of the hinge case **401** while stably mounting the hinge structure **164**. The shape or size of the accommodation recess **411**, the mounting portion **411a**, or the placement portion **413a** may vary. For example, the position or shape of the accommodation recess **411**, the mounting portion **411a** or the placement portion **413a** in a region provided by the hinge case **401** may be different from that in the embodiment illustrated in the drawing. Modifications thereof will be further described with reference to FIG. 7, FIG. 10, FIG. 12, or FIG. 14.

According to various embodiments, the electronic device (e.g., the electronic device **100** in FIG. 1) may further include a flexible printed circuit board **413** disposed in the hinge cover **400**. According to an embodiment, the flexible printed circuit board **413** may include a placement portion **413a** fixed in the accommodation recess **411**, and a connection portion **413b** extending out of the accommodation recess **411** or the hinge case **401**. The placement portion **413a** may have a shape extending substantially in the longitudinal direction of the hinge case **401** or a shape bypassing the mounting portion **411a** in a portion. The connection portion **413b** may connect the placement portion **413a** to another circuit board (e.g., the first printed circuit board **171** or the second printed circuit board **172** in FIG. 3).

According to various embodiments, at least one first light-emitting element **415** may be mounted on the placement portion **413a**. In an embodiment, a plurality of first light-emitting elements **415** may be disposed in the longitudinal direction of the hinge case **401**. As will be described with reference to FIG. 6, when the plurality of first light-emitting elements **415** are disposed, the first light-emitting elements **415** may be disposed at a predetermined interval. An interval at which the first light-emitting elements **415** are disposed may be determined based on the width of the mounting portion **411a** (e.g., the length measured in the longitudinal direction of the hinge case **401**). According to an embodiment, even if the mounting portion **411a** is not formed, when sufficient space and mechanical strength for mounting the hinge structure **164** are secured, the interval between the first light-emitting elements **415** may be freely set. For example, when the mounting portion **411a** is not formed, design freedom may be improved in the arrangement of the first light-emitting elements **415**.

According to various embodiments, the optical cover **402** may be mounted on the outer face of the hinge case **401** so as to conceal or protect the first light-emitting elements **415**, or the like. For example, the optical cover **402** may be made of a generally opaque or translucent material. In an embodiment, the optical cover **402** may include the translucent region **421** formed at least in the region in which the first light-emitting element **415** is disposed (or the region in which the plurality of first light-emitting elements **415** are arranged). For example, the translucent region **421** extends in the longitudinal direction of the hinge case **401** or the optical cover **402**, and may be disposed to face at least the region in which the first light-emitting elements **415** are arranged.

According to various embodiments, the translucent region **421** may transmit the light, emitted by the first light-emitting elements **415**, to the outside while preventing the first light-emitting elements **415** from being visually exposed to the outside (e.g., the outside of the electronic device **100** in FIG. 1 or FIG. 2). For example, the first light-emitting elements **415** emit light to the inner face of the translucent

region **421**, and the light emitted to the translucent region **421** at least partially passes through the translucent region **421**. According to an embodiment, the first light-emitting elements **415** may include light-emitting diodes, and the electronic device (e.g., the electronic device **100** in FIGS. 1 to 3) may provide visual information to the user using the light emitted from the first light-emitting elements. For example, when an event such as call reception or message reception occurs, the electronic device may allow the user to recognize the event using the first light-emitting elements **415**. In another embodiment, each of the first light-emitting elements **415** may emit at least one of red light, blue light, and green light. The electronic device (e.g., the electronic device **100** in FIG. 1 or FIG. 2) may provide various visual effects or decorative effects outside the electronic device by combining colors of light emitted by the first light-emitting elements **415**.

FIG. 6 is a cross-sectional view of the hinge cover **400** taken along line A-A in FIG. 5 according to an embodiment of the disclosure.

FIG. 7 is a projective plan view illustrating a portion of the hinge cover **400** according to an embodiment of the disclosure.

FIG. 8 is a cross-sectional view of the hinge cover **400** taken along line B-B in FIG. 5 according to an embodiment of the disclosure.

Referring to FIGS. 6 to 8, the hinge structure **164** may be mounted on the mounting portion **411a** inside the hinge case **401**, and may rotatably and/or pivotably connect the first support member **161** and the second support member of FIG. 3. The first support member **161** and the second support member **162** may be part of the first housing structure **110** and the second housing structure **120** of the electronic device, whereby each of the first housing structure **110** and the second housing structure **120** is rotatable with respect to the hinge structure **164** or the hinge cover **400**.

According to various embodiments, the plurality of first light-emitting elements **415** may be accommodated in the accommodation recess **411** on the outer face of the hinge case **401**. The plurality of first light-emitting elements **415** may be arranged in the longitudinal direction of the hinge case **401** at a first interval **I1**. In an embodiment, the first interval **I1** may be substantially the same as or larger than the length **W3** of the mounting portion **411a** measured in the longitudinal direction of the hinge case **401**. In arranging the first light-emitting elements **415**, a flexible printed circuit board (e.g., the flexible printed circuit board **413** in FIG. 4), for example, the placement portion **413a** may generally extend in the longitudinal direction of the hinge case **401**, and a portion of the placement portion **413a** may be formed to bypass the mounting portion **411a**. Thus, the accommodation recess **411** is formed in the hinge case **401** so as to accommodate the placement portion **413a** or the first light-emitting elements **415**, and the hinge structure **164** may be firmly mounted in the mounting portion **411a**. In an embodiment, if it is possible to firmly mount the hinge structure **164** in the hinge case **401** even without forming the mounting portion **411a**, it is not necessary for the accommodation recess **411** or the placement portion **413a** to bypass the mounting portion **411a**.

According to various embodiments, the optical cover **402** may be coupled to face the outer face of the hinge case **401** at a first distance **D1**. Referring to FIG. 6, the first distance **D1** indicates the distance between the inner face of the hinge case **401** and the outer face of the optical cover **402**, but may practically mean the distance between the face on which the first light-emitting elements **415** emit light and the inner face

of the optical cover **402**. In an embodiment, the optical cover **402** may include an opaque layer **402a**, a translucent layer **402b**, and a diffusion layer **402c**. The opaque layer **402a** may substantially form a part of the exterior of the optical cover **402** or the exterior of the electronic device (e.g., the electronic device **100** in FIG. **1**). The translucent layer **402b** is formed as an inner face of the opaque layer **402a**, and may be partially exposed to the outside of the opaque layer **402a**. For example, the opaque layer **402a** may include an opening, and the translucent layer **402b** may be accommodated in the opening of the opaque layer **402a** and exposed to the outside. According to an embodiment, the translucent layer **402b** exposed to the outside may substantially form the translucent region **421**. For example, a region (e.g., the region indicated by “**421a**” in FIG. **6**) exposed to the outside of the translucent layer **402b** may correspond to the region in which the first light-emitting elements **415** are arranged. In another embodiment, the translucent layer **402b** exposed to the outside may form the exterior of the optical cover **402** together with the opaque layer **402a**. The diffusion layer **402c** may be disposed on an inner face of the translucent layer **402b** and may at least partially face the first light-emitting elements **415**. For example, the first light-emitting elements **415** may emit light to the surface of the diffusion layer **402c**. In an embodiment, the exposed region **421a** in the translucent layer **402b** and a region corresponding to the exposed region **421a** in the diffusion layer **402c** (e.g., the region indicated by “**421b**” in FIG. **6**) may substantially form the translucent region **421**. For example, the exposed region **421a** and the region indicated by “**421a**” in FIG. **6** may be disposed to correspond to the region in which the first light-emitting elements **415** are arranged.

According to various embodiments, the light emitted from the first light-emitting elements **415** may be incident on the diffusion layer **402c** and diffused through the translucent region **421**. When the region, which is illuminated by light from one first light-emitting element **415**, or the region, in which the diffusion layer **402c** is able to diffuse light, is partially limited, the plurality of the first light-emitting elements **415** may be arranged so as to substantially illuminate the entire translucent region **421** with light therefrom. In an embodiment, light passing through the diffusion layer **402c** may be transmitted to the outside through the translucent layer **402b**.

According to various embodiments, the illumination angle α of the first light-emitting element **415** may not reach an angle of 180 degrees, and an area illuminated by light from one first light-emitting element **415** (hereinafter, an “illuminated area”) may vary depending on the first distance **D1**. For example, when the optical cover **402** is disposed closer than the first distance **D1** from the hinge case **401**, an illuminated area may be reduced. In an embodiment, depending on the distance between the hinge case **401** and the optical cover **402** (e.g., the first distance **D1**), some sections or regions of the translucent region **421** in the longitudinal direction of the hinge cover **400** (e.g., the y direction in FIG. **3**) may not be illuminated by light. In this case, the entire section or area of the translucent region **421** may be uniformly illuminated by adjusting the first interval **I1** between the first light-emitting elements **415**. For example, when the illuminated area is reduced, the entire section or area of the translucent region **421** may be illuminated by reducing the interval between the first light-emitting elements **415**. In an embodiment, the regions illuminated by the first light-emitting elements **415** on the inner face of the translucent region **421** may be disposed to be in contact with each other. In another embodiment, the

region illuminated by the first light-emitting elements **415** may be designed or manufactured to at least partially overlap each other in consideration of manufacturing tolerances, assembly tolerances, or the like of respective products. For example, at least 2 to 15% of the illuminated area of one first light-emitting element **415** may be designed or manufactured to overlap the illuminated area of another adjacent first light-emitting element. In some embodiments, the degree of overlap of the illuminated areas of two adjacent first light-emitting elements **415** may be determined in consideration of the thickness or the optical characteristic of the light-diffusing structure such as the diffusion layer **402c**. For example, even if a narrow region at a point on the translucent region **421** is illuminated by light, when it is possible to diffuse the light to the entire translucent region **421**, the light may be transmitted to the outside through the entire translucent region **421** even when only one first light-emitting element **415** is used. When the area in which the diffusion layer **402c** is capable of diffusing light is limited, the arrangement interval of the first light-emitting elements **415** may be appropriately designed in consideration of this.

FIG. **9** is a cross-sectional view illustrating a hinge cover **500** (e.g., the hinge cover **400** in FIG. **4**) in which the hinge cover **500** is cut in the longitudinal direction according to an embodiment of the disclosure.

FIG. **10** is a projective plan view illustrating a portion of the hinge cover **500** according to an embodiment of the disclosure.

FIG. **11** is a cross-sectional view illustrating the hinge cover **500** in which the hinge cover **500** is cut in a direction perpendicular to the longitudinal direction according to an embodiment of the disclosure.

According to various embodiments, as the distance between the hinge case **401** and the optical cover **402** becomes smaller, miniaturization of the electronic device may be easier. For example, when the distance between the hinge case **401** and the optical cover **402** increases, the first housing structure and the second housing structure (e.g., the first housing structure **110** and the second housing structure **120** in FIGS. **1** to **3**) may also increase. According to various embodiments disclosed herein, by reducing the distance between the hinge case **401** and the optical cover **402**, it is possible to miniaturize the electronic device. For example, when the optical cover **402** is disposed closer to the hinge case **401**, it is possible to reduce at least the thickness of the electronic device.

According to various embodiments, when the distance between the hinge case **401** and the optical cover **402** decreases, the area illuminated by light from the first light-emitting elements **415** on the inner face of the translucent region **421** also decreases, as described above. When the distance between the hinge case **401** and the optical cover **402** decreases, it is possible to provide uniform illumination throughout the translucent region **421** by arranging the first light-emitting elements **415** at smaller intervals. Referring to FIGS. **9** to **11**, when the hinge case **401** and the optical cover **402** are disposed at a second distance **D2** smaller than the first distance **D1**, the first light-emitting elements **415** may be arranged at a second interval **I2** smaller than the first interval **I1**. For example, the area illuminated by the first light-emitting elements **415** is proportional to the distance between the hinge case **401** and the optical cover **402**, and it is possible to provide uniform illumination throughout the translucent region **421** by adjusting the intervals between the first light-emitting elements in proportion to the distance between the hinge case **401** and the optical cover **402**.

According to various embodiments, the first light-emitting elements **415** may be disposed on the opposite sides of the mounting portion **411a** in the longitudinal direction of the hinge case **401** (e.g., the y-axis direction of FIG. 3). For example, when viewed from the outside of the hinge case **401**, the first light-emitting elements **415** may be arranged side by side on the opposite sides of the mounting portion **411a**. The width of the mounting portion **411a**, for example, the length **W3** of the mounting portion **411a** measured in the longitudinal direction of the hinge case **401** may be larger than the second interval **I2**. For example, since the interval of the first light-emitting elements **415** disposed on the opposite sides of the mounting portion **411a** are determined based on the length **W3** of the mounting portion, the first light-emitting elements may be arranged further away from each other than the second interval **I2**. In an embodiment, since the first light-emitting elements **415** disposed at the opposite sides of the mounting portion **411a** are arranged further away from each other than the second interval **I2**, a discontinuous section, in which illumination is not directly provided, may be formed in a portion corresponding to the mounting portion **411a** in the translucent region **421**.

According to various embodiments, when the electronic device (e.g., the electronic device **100** in FIGS. 1 to 3) or the hinge cover (e.g., the hinge cover **400** in FIG. 4) further includes at least one light guide **513**, such a discontinuous section may be eliminated. For example, the light guide **513** is able to transfer a part of the light emitted from the first light-emitting elements **415** to the region corresponding to the mounting portion **411a**. According to an embodiment, the light guide **513** may be disposed in the hinge case **401** and the optical cover **402** at a position corresponding to the mounting portion **411a**. For example, in the longitudinal direction of the hinge case **401**, the light guide **513** may be aligned between the first light-emitting elements **415**. In another embodiment, one face of the light guide **513** may be attached to the hinge case **401**, and the other face of the light guide **513** may be attached to the optical cover **402**. In describing this embodiment, the light guide **513** is exemplified as a structure or a component mounted on the hinge case **401** or the optical cover **402**, but the disclosure is not limited thereto. For example, the light guide **513** may be disposed on the hinge case **401** or the optical cover **402** in a manner such as printing, painting, or coating.

According to various embodiments, at least a portion of the light guide **513** may be disposed in a region illuminated by the first light-emitting element **415** adjacent thereto. For example, the light guide **513** is able to receive a part of light emitted from the first light-emitting element **415** adjacent thereto. In an embodiment, the light guide **513** may include a reflective layer **513a** disposed on the side facing the hinge case **401** or a diffuse reflection pattern **513b** disposed on the side facing the optical cover **402**. Light incident on the light guide **513** may be transferred to the translucent region **421** from the region corresponding to the mounting portion **411a** by the reflective layer **513a** or the diffuse reflection pattern **513b**. For example, a region where the light emitted from the first light-emitting element **415** does not directly arrive may be provided with light via the light guide **513**.

According to various embodiments, the electronic device or the hinge cover **500** may further include a second light-emitting element so as to provide additional illumination to a discontinuous section, for example, a region corresponding to the mounting portion **411a**. This will be described with reference to FIGS. 12 and 13.

FIG. 12 is a projective plan view illustrating a portion of a hinge cover **600** (e.g., the hinge cover **400** in FIG. 4) according to an embodiment of the disclosure.

FIG. 13 is a cross-sectional view illustrating the hinge cover **600** in which the hinge cover **600** is cut in a direction perpendicular to the longitudinal direction according to an embodiment of the disclosure.

Referring to FIGS. 12 and 13, the hinge cover **600** (e.g., the hinge cover **165** or **400** in FIGS. 1 to 4) may further include at least one second light-emitting element **615** mounted on the outer face of the hinge case **401**. For example, the second light-emitting element **615** may be mounted on a placement portion **613a** of a flexible printed circuit board disposed in an accommodation recess **611**. In an embodiment, a pair of second light-emitting elements **615** may be disposed adjacent to the opposite edges of the hinge case **401** or may be disposed to face the opposite edges of the light guide **513**. The second light-emitting elements **615** may be side-emitting-type light emitting diodes, and may emit light into the light guide **513**. The light guide **513** may transfer the light incident thereon by the second light-emitting elements **615** using the reflective layer or the diffuse reflection pattern (e.g., the reflective layer **513a** or the diffuse reflection pattern **513b** in FIG. 9) to the translucent region **421**. For example, illumination may be provided via the second light-emitting elements **615** and the light guide **513** to a region where the illumination of the first light-emitting elements **415** does not directly arrive.

According to various embodiments, the illumination angle (e.g., the illumination angle α in FIG. 6 or FIG. 13) of the first light-emitting element **415** may be, for example, about 120 degrees. According to an embodiment, the second light-emitting elements **615** may have an illumination angle β of approximately 120 degrees, and may emit light to the light guide **513** from one side of the mounting portion (e.g., the mounting portion **411a** in FIG. 6 or FIG. 7). For example, at least a portion of the region corresponding to the mounting portion **411a** may transmit light emitted from the first light-emitting elements **415** and light emitted from the second light-emitting elements **615** to the outside.

According to the above-described embodiments, at the first position (e.g., the state of FIG. 1) at which the first housing structure **110** and the second housing structure **120** are unfolded to be arranged side by side with respect to each other, the translucent region **421** may be at least partially concealed by the first housing structure or the second housing structure. At the second position (e.g., the state of FIG. 2) at which the first housing structure **110** and the second housing structure **120** are folded to face each other, the translucent region **421** may be exposed to the outside. In an embodiment, when an event occurs at the second position, the electronic device (e.g., the electronic device **100** in FIG. 2) may provide visual information through the translucent region **421** using one or more first light-emitting elements **415**. For example, even in an environment in which providing visual information through a display (e.g., the display **130** or the sub-display **152** in FIG. 1) is limited, the user may easily recognize whether a call or a message is received. In another embodiment, in the region where illumination of the first light-emitting elements **415** does not arrive, the second light-emitting element **615** or the light guide **513** may be disposed so as to provide illumination to the translucent region **421**.

FIG. 14 is a projective plan view illustrating a portion of the hinge cover **700** according to an embodiment of the disclosure.

21

FIG. 15 is a cross-sectional view illustrating the hinge cover 700 in which the hinge cover 700 is cut in a direction perpendicular to the longitudinal direction according to an embodiment of the disclosure.

FIG. 16 is a cross-sectional view illustrating the hinge cover 700 in which the hinge cover 600 is cut in a direction perpendicular to the longitudinal direction according to an embodiment of the disclosure.

Referring to FIGS. 14 and 16, an electronic device (e.g., the electronic device 100 in FIGS. 1 to 3) may further include a plurality of first light-emitting elements 415 arranged in two rows in the longitudinal direction on the hinge cover 700. A placement portion 713a of the flexible printed circuit board (e.g., the flexible printed circuit board 413 in FIG. 4) may extend substantially in the longitudinal direction of the hinge cover 700 (e.g., they direction in FIG. 3). A pair of placement portions 713a may be disposed adjacent to respective edges of the hinge case 401. For example, a pair of accommodation recesses 711 extending in the longitudinal direction may be formed parallel to each other on the outer face of the hinge case 401, and the placement portions 713a may be accommodated in the accommodation recesses 711, respectively. The mounting portion 411a to which the hinge structure (e.g., the hinge structure 164 in FIG. 4) is coupled may be located between the placement portions 713a (or between the accommodation recesses 711). An optical cover (e.g., the optical cover 402 in FIG. 4) may include a plurality of translucent regions 721a and 721b corresponding to the arrangement of the first light-emitting elements 415, thereby transmitting light, emitted from the first light-emitting elements 415, to the outside.

Referring to FIG. 15, at the first position, for example, when the first housing structure 110 and the second housing structure 120 are located at the first position are unfolded to be arranged side by side with respect to each other, one or more first light-emitting elements 415 on one side (e.g., the first light-emitting element 415 on the left side in FIG. 15, which is referred to as a “first row light-emitting element” below) may be concealed by the first housing structure 110. At the first position, one or more first light-emitting elements 415 on the other side (e.g., the first light-emitting element 415 on the right side in FIG. 15, which is referred to as a “second row light-emitting element” below) may be concealed by the second housing structure 120.

Referring to FIG. 16, at the second position, for example, when the first housing structure 110 and the second housing structure 120 are folded to face each other, both the first row light-emitting element and the second row light-emitting element may be exposed to the outside. For example, as the first housing structure 110 or the second housing structure 120 rotates with respect to the hinge cover 700, one or more regions of the hinge cover 700 may be concealed to the inside of the first housing structure 110 or the second housing structure 120 or may be exposed to the outside of the first housing structure 110 or the second housing structure 120. The first light-emitting elements 415 may emit light to the outside of the electronic device through the translucent regions 721a and 721b at the second position.

According to various embodiments, when the electronic device (e.g., the electronic device 100 of FIG. 2) is placed on a flat face of a table or the like at the state of the second position, the outer face of the first housing structure 110 or the second housing structure 120 (e.g., the first rear cover 140 or the second rear cover 150 in FIG. 4) may be located to face the flat face. In an embodiment, the above-mentioned hinge cover 165, 400, 500, 600, or 700 or the optical cover

22

402 may be exposed to the external space even if the electronic device is placed on a flat face at the state of the second position. For example, an indicator (e.g., the indicator 169 in FIG. 2) or a translucent region (e.g., the translucent region 421, 721a, or 721b in FIG. 4 or FIG. 16) may be at least partially exposed to the external space. For example, in an environment in which providing visual information through a display (e.g., the display 130 or the sub-display 152 in FIG. 1) is limited, the electronic device 100 may visually provide information about occurrence of an event or the like to the user using the indicator 169.

According to various embodiments disclosed herein, an electronic device (e.g., the electronic device 100 in FIGS. 1 to 3) may include: a first housing structure (e.g., the first housing structure 110 in FIGS. 1 to 3) including a first face (e.g., the first face 111 in FIGS. 1 to 3) oriented in a first direction, a second face (e.g., the second face 112 in FIGS. 1 to 3) oriented in a second direction opposite the first direction, and a first side member (e.g., the first side member 113 in FIGS. 1 to 3) at least partially surrounding a space between the first face and the second face; a second housing structure (e.g., the second housing structure 120 in FIGS. 1 to 3) including a third face (e.g., the third face 121 in FIGS. 1 to 3) oriented in a third direction, a fourth face (e.g., the fourth face 122 in FIGS. 1 to 3) oriented in a fourth direction opposite the third direction, and a second side member (e.g., the second side member 123 in FIGS. 1 to 3) at least partially surrounding a space between the third face and the fourth face; a hinge structure (e.g., the hinge structure 164 in FIG. 3 or FIG. 4) rotatably connecting the first housing structure and the second housing structure to each other, the hinge structure being configured to provide a folding axis (e.g., the folding axis A in FIG. 1) that is a rotating center of the first housing structure and the second housing structure; a flexible display (e.g., the display 130 in FIG. 1 or FIG. 3) extending from the first face to the third face across the hinge structure; a hinge case (e.g., the hinge case 401 in FIG. 4) disposed between the first housing structure and the second housing structure to accommodate the hinge structure therein so as to conceal or protect the hinge structure; and at least one first light-emitting element (e.g., the first light-emitting element 415 in FIG. 4) disposed on an outer face of the hinge case. The electronic device may transmit light, emitted from the first light-emitting element, to the outside.

According to various embodiments, the electronic device described above may further include an optical cover (e.g., the optical cover 402 in FIG. 4 or FIG. 6) mounted on the outer face of the hinge case, and the first light-emitting element may be concealed by the optical cover.

According to various embodiments, the optical cover includes a translucent region (e.g., the translucent region 421 in FIG. 4 or FIG. 6), and the translucent region is disposed to correspond to the first light-emitting element so as to transmit light, emitted from the first light-emitting element, to the outside.

According to various embodiments, the first housing structure and the second housing structure may rotate about the hinge structure between a position at which the first housing structure and the second housing structure are unfolded to be arranged side by side with respect to each other (the state of FIG. 1) (hereinafter, referred to as a “first position”) and a position at which the first face and the third face are folded to face each other (the state of FIG. 2) (hereinafter, referred to as a “second position”), and at the second position, at least a portion of the translucent region may be exposed to the outside.

23

According to various embodiments, at the first position, the translucent region may be concealed by the first housing structure or the second housing structure.

According to various embodiments, the optical cover may include an opaque layer (e.g., the opaque layer **402a** in FIG. **8**), a translucent layer (e.g., the translucent layer **402b** in FIG. **8**) disposed on an inner face of the opaque layer, a portion of translucent layer being exposed to outside of the opaque layer, and a diffusion layer (e.g., the diffusion layer **402c** in FIG. **8**) disposed on an inner face of the translucent layer and directly facing at least partially the first light-emitting element.

According to various embodiments, in the longitudinal direction of the hinge case, the hinge structure may be mounted on the central portion of the inner face of the hinge case (e.g., the mounting portion **411a** in FIG. **4**), and when the hinge case is viewed from the outer face thereof, the first light-emitting element is mounted at each side of a portion in which the hinge structure is mounted.

According to various embodiments, the electronic device may further include an optical cover mounted on the outer face of the hinge case and including translucent regions corresponding to at least the first light-emitting elements, and regions illuminated by the first light-emitting elements on the inner face of the translucent region may at least partially overlap each other.

According to various embodiments, the electronic device may further include an optical cover mounted on the outer face of the hinge case and including a translucent region corresponding to the first light-emitting elements, and at least one light guide (e.g., the light guide **513** in FIG. **9** or FIG. **13**) disposed between the hinge case and the optical cover at a position corresponding to the portion in which the hinge structure is mounted, and aligned between the first light-emitting elements.

According to various embodiments, the electronic device may further include at least one second light-emitting element (e.g., the second light-emitting element **615** in FIG. **13**) mounted on the outer face of the hinge case and configured to cause light to enter the light guide.

According to various embodiments, the second light-emitting element may include a side-emitting-type light-emitting diode.

According to various embodiments, the light guide may include a reflective layer or a diffuse reflection pattern (e.g., the reflective layer **513a** or the diffuse reflection pattern **513b** in FIG. **9**).

According to various embodiments, the electronic device may further include an accommodation recess (e.g., the accommodation recess **411** in FIG. **4** or FIG. **6**) formed in the outer face of the hinge case, and a flexible printed circuit board (e.g., the flexible printed circuit board **413** in FIG. **4**) at least partially disposed in the accommodation recess, and the first light-emitting elements are mounted on the flexible printed circuit board.

According to various embodiments, the plurality of first light-emitting elements may be arranged in a longitudinal direction of the hinge case.

According to various embodiments, the first housing structure and the second housing structure may rotate about the hinge structure between a position at which the first housing structure and the second housing structure are unfolded to be arranged side by side with respect to each other (hereinafter, referred to as a “first position”) and a position at which the first face and the third face are folded to face each other (hereinafter, referred to as a “second position”). The electronic device may include one or more

24

first light-emitting elements (e.g., the left light-emitting element among the first light-emitting elements **415** in FIG. **15**) disposed in a region concealed by the first housing structure at the first position and exposed to the outside at the second position, and one or more other first light-emitting elements (e.g., the right light-emitting element among the first light-emitting elements **415** in FIG. **15**) disposed in a region concealed by the second housing structure at the first position and exposed to the outside at the second position.

According to various embodiments disclosed herein, an electronic device may include: a first housing structure; a second housing structure; a hinge structure disposed between the first housing structure and the second housing structure, the hinge structure being configured to couple the first housing structure and the second housing structure to be rotatable between a position at which the first housing structure and the second housing structure are unfolded to be arranged side by side with respect to each other (hereinafter, referred to as a “first position”) and a position at which the first and second housing structures are folded to face each other (hereinafter, referred to as a “second” position); a flexible display extending from one face of the first housing structure to one face of the second housing structure across the hinge structure; a hinge case disposed between the first housing structure and the second housing structure to accommodate the hinge structure therein so as to conceal or protect the hinge structure; at least one first light-emitting element disposed on an outer face of the hinge case; and an optical cover mounted on the outer face of the hinge case and including a translucent region formed in a region at least corresponding to the first light-emitting element. The first light-emitting element may emit light to the outside of the electronic device through the translucent region.

According to various embodiments, the translucent region may be exposed to the outside of the electronic device at least at the second position.

According to various embodiments, at the first position, the translucent region may be exposed to the outside of the electronic device between another face of the first housing structure and another face of the second housing structure.

According to various embodiments, a plurality of first light-emitting elements may be arranged on the outer face of the hinge case, and regions illuminated by the first light-emitting elements on the inner face of the translucent region may at least partially overlap each other.

According to various embodiments, the hinge structure may be mounted on the inner face of the hinge case, and at least one pair of first light-emitting elements are mounted on the outer face of the hinge case. The at least one pair of first light-emitting elements may be aligned in a longitudinal direction of the hinge case with a portion in which the hinge structure is mounted interposed therebetween.

While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the appended claims and their equivalents.

What is claimed is:

1. An electronic device comprising:
 - a first housing structure including:
 - a first face oriented in a first direction,
 - a second face oriented in a second direction opposite the first direction, and
 - a first side member at least partially surrounding a space between the first face and the second face;

25

a second housing structure including:
 a third face oriented in a third direction,
 a fourth face oriented in a fourth direction opposite the third direction, and
 a second side member at least partially surrounding a space between the third face and the fourth face;
 a hinge structure rotatably connecting the first housing structure and the second housing structure to each other, the hinge structure configured to provide a folding axis that is a rotating center of the first housing structure and the second housing structure;
 a flexible display extending from the first face to the third face across the hinge structure;
 a hinge case disposed between the first housing structure and the second housing structure to accommodate the hinge structure therein to conceal or protect the hinge structure; and
 one or more first light-emitting elements disposed on an outer face of the hinge case,
 wherein the electronic device is configured to transmit light emitted from the one or more first light-emitting elements to outside of the electronic device, and
 wherein the electronic device includes:
 one or more first light-emitting elements disposed in a region concealed by the first housing structure at a first position and exposed to an outside at a second position, and
 one or more other first light emitting elements disposed in a region concealed by the second housing structure at the first position and exposed to the outside at the second position.

2. The electronic device of claim 1, further comprising: an optical cover mounted on the outer face of the hinge case,
 wherein the one or more first light-emitting elements are concealed by the optical cover.

3. The electronic device of claim 2,
 wherein the optical cover includes a translucent region, and
 wherein the translucent region is disposed to correspond to the one or more first light-emitting elements to transmit light emitted from the one or more first light-emitting elements to outside of the electronic device.

4. The electronic device of claim 3,
 wherein the first housing structure and the second housing structure are configured to rotate about the hinge structure between a first position at which the first housing structure and the second housing structure are unfolded to be arranged side by side with respect to each other and a second position at which the first face and the third face are folded to face each other, and
 wherein, at the second position, at least a portion of the translucent region is exposed to outside of the electronic device.

5. The electronic device of claim 4, wherein at the first position, the translucent region is concealed by at least one of the first housing structure or the second housing structure.

6. The electronic device of claim 3, wherein the optical cover includes:
 an opaque layer;
 a translucent layer disposed on an inner face of the opaque layer, a portion of translucent layer being exposed to outside of the opaque layer; and
 a diffusion layer disposed on an inner face of the translucent layer and directly facing at least partially the one or more first light-emitting elements.

26

7. The electronic device of claim 1,
 wherein, in a longitudinal direction of the hinge case, the hinge structure is mounted on a central portion of an inner face of the hinge case, and
 wherein, based on the hinge case being viewed from an outer face thereof, the one or more first light-emitting elements being mounted at each side of a portion in which the hinge structure is mounted.

8. The electronic device of claim 7, further comprising: an optical cover mounted on the outer face of the hinge case and including translucent regions corresponding to the one or more first light-emitting elements,
 wherein regions illuminated by the one or more first light-emitting elements on an inner face of the translucent region at least partially overlap each other.

9. The electronic device of claim 7, further comprising: an optical cover mounted on the outer face of the hinge case and including a translucent region corresponding to the one or more first light-emitting elements; and
 at least one light guide disposed between the hinge case and the optical cover at a position corresponding to the portion in which the hinge structure is mounted, and aligned between the one or more first light-emitting elements.

10. The electronic device of claim 9, further comprising: one or more second light-emitting elements mounted on the outer face of the hinge case and configured to cause light to enter the light guide.

11. The electronic device of claim 10, wherein the one or more second light-emitting elements include a side-emitting-type light-emitting diode.

12. The electronic device of claim 9, wherein the light guide includes at least one of a reflective layer or a diffuse reflection pattern.

13. The electronic device of claim 7, further comprising: an accommodation recess formed in the outer face of the hinge case; and
 a flexible printed circuit board at least partially disposed in the accommodation recess,
 wherein the one or more first light-emitting elements are mounted on the flexible printed circuit board.

14. The electronic device of claim 1, wherein a plurality of first light-emitting elements are arranged in a longitudinal direction of the hinge case.

15. The electronic device of claim 1,
 wherein the first housing structure and the second housing structure are configured to rotate about the hinge structure between the first position at which the first housing structure and the second housing structure are unfolded to be arranged side by side with respect to each other and the second position at which the first face and the third face are folded to face each other.

16. An electronic device comprising:
 a first housing structure;
 a second housing structure;
 a hinge structure disposed between the first housing structure and the second housing structure, the hinge structure being configured to couple the first housing structure and the second housing structure to be rotatable between a first position at which the first housing structure and the second housing structure are unfolded to be arranged side by side with respect to each other and a second position at which the first and second housing structures are folded to face each other;
 a flexible display extending from one face of the first housing structure to one face of the second housing structure across the hinge structure;

27

a hinge case disposed between the first housing structure and the second housing structure to accommodate the hinge structure therein so as to conceal or protect the hinge structure;

one or more first light-emitting elements disposed on an outer face of the hinge case; and

an optical cover mounted on the outer face of the hinge case and including a translucent region formed in a region at least corresponding to the one or more first light-emitting elements,

wherein the one or more first light-emitting elements are configured to emit light to outside of the electronic device through the translucent region, and

wherein the electronic device includes:

one or more first light-emitting elements disposed in a region concealed by the first housing structure at the first position and exposed to an outside at the second position, and

one or more other first light emitting elements disposed in a region concealed by the second housing structure at the first position and exposed to the outside at the second position.

17. The electronic device of claim 16, wherein the translucent region is exposed to outside of the electronic device at least at the second position.

28

18. The electronic device of claim 16, wherein at the first position, the translucent region is exposed to outside of the electronic device between another face of the first housing structure and another face of the second housing structure.

19. The electronic device of claim 16,

wherein the one or more first light-emitting elements are arranged on the outer face of the hinge case, and

wherein a plurality of regions illuminated by the one or more first light-emitting elements on an inner face of the translucent region at least partially overlap each other.

20. The electronic device of claim 16,

wherein the hinge structure is mounted on an inner face of the hinge case, and at least one pair of one or more first light-emitting elements are mounted on the outer face of the hinge case, and

wherein the at least one pair of the one or more first light-emitting elements are aligned in a longitudinal direction of the hinge case with a portion in which the hinge structure being mountingly interposed therebetween.

* * * * *