

(Model.)

R. HOFFMAN.
WICK TRIMMER.

No. 303,849.

Patented Aug. 19, 1884.

Fig. 1.





Fig. 2.



WITNESSES:

Theo. G. Foster.
C. Sedgwick

INVENTOR:

R. Hoffman
BY *Munn & Co*
ATTORNEYS.

UNITED STATES PATENT OFFICE.

ROBERT HOFFMAN, OF COHOES, NEW YORK.

WICK-TRIMMER.

SPECIFICATION forming part of Letters Patent No. 303,849, dated August 19, 1884.

Application filed December 26, 1883. (Model.)

To all whom it may concern:

Be it known that I, ROBERT HOFFMAN, of Cohoes, in the county of Albany and State of New York, have invented a new and Improved Lamp-Wick Trimmer, of which the following is a full, clear, and exact description.

The object of my invention is to provide a new and improved device for trimming lamp-wicks which are to have their upper ends rounded.

The invention consists in the combination, with a wick-trimmer, of a clamping-frame for pressing and holding the wick to the edge of levers or blades of the wick-trimmer.

The invention also consists in various parts and details and combinations of the same, as will be fully set forth hereinafter.

Reference is to be had to the accompanying drawings, forming part of this specification, in which similar letters of reference indicate corresponding parts in both the figures.

Figure 1 is a perspective view of my improved lamp-wick trimmer, the same being shown inverted. Fig. 2 is an enlarged cross-sectional elevation of the same.

The trimmer is formed of two levers, A B, pivoted to each other, and provided with handle-loops in the same manner as scissors. The lever A is provided with a flat plate, A', having a flange, C, forming a pan for receiving the carbonized parts cut from the wick, and in its lower surface and at the free edge the plate A' is provided with a curved recess, *a*, which makes the inner edge of the plate A' segmental. The lever B is provided with a curved plate, B', on its end, which plate B' fits over the curved edge of the plate A'. On the under side of the plate A' two ridges or lugs, *d*, are formed, which extend from the outer curved edge of the said plate over the flat part to the inner curved edge of the recess *a*, and serve to guide the longitudinally-slotted stem D of a clamping-frame, E, resting on the under surface of the plate A'. The outside piece, E', of the frame E is curved to fit against the curved inner edge of the plate A', the said edge and the inner edge of the piece E' being serrated transversely, or rough-

ened in any other suitable manner. A screw, F, is passed through the slot of the stem D into the under surface of the plate A', for the purpose of holding the frame E on the plate A'. At its free end the stem D is provided with an upwardly-projecting flange, D', between which and the flange C a spiral spring, G, is held. The flange C is provided on its outer edge with a projection, C', under which the spring G is held. Curved cutting-blades M and N are held on the upper surfaces of the plates A' B' of the levers A B, the piece E' of the frame E being held below the projecting part of the blade M on the plate A'.

The trimmer is used in the following manner: The end D' of the stem D of the frame E is pushed in the direction of the arrow *a'*, Fig. 2, whereby the piece E' of the frame E is moved from the serrated edge of the plate A'. The wick *o* is then passed through the space between the piece E' and the serrated edge of the plate A'. If the frame E is released, the spring G will press it in the inverse direction of the arrow *a'*, and the cross-piece E' will press the wick against the serrated edge of the plate A'. The wick will thus be clamped and held firmly between the serrated edge of the plate A' and the piece E', and the projecting end of the wick can then be cut off evenly by the blades M and N. The wick-clamping frame E, if modified slightly, can also be applied on wick-trimmers constructed differently from the one described.

Having thus described my invention, what I claim as new, and desire to secure by Letters Patent, is—

1. The combination, with a wick-trimmer, of a sliding clamping-frame mounted to slide beneath one of the plates or blades for pressing the wick against the edge of the said plate or blade or blades, substantially as herein shown and described.

2. The combination, with a wick-trimmer, of a clamping-frame for pressing the wick against one of the levers or blades, and of a spring for acting on the said frame, substantially as herein shown and described.

3. The combination, with a wick-trimmer having the edge of the lower levers serrated, of a

clamping-frame having a serrated cross-piece for pressing the wick against the serrated edge of the lever, substantially as herein shown and described.

- 5 4. The combination, with a wick-trimmer, of the sliding clamping-frame E, provided with a stem, D, mounted to slide on the under side of plate A', and having an angular

end, D', and of the spring G, held between one of the levers and the angular end D', substantially as herein shown and described.

ROBERT HOFFMAN.

Witnesses:

JAMES S. CLUTE,
JAMES EDWARD MUSSEY.