




(86) Date de dépôt PCT/PCT Filing Date: 2012/09/17
 (87) Date publication PCT/PCT Publication Date: 2013/07/18
 (45) Date de délivrance/Issue Date: 2019/11/12
 (85) Entrée phase nationale/National Entry: 2014/07/08
 (86) N° demande PCT/PCT Application No.: NL 2012/050654
 (87) N° publication PCT/PCT Publication No.: 2013/105847
 (30) Priorité/Priority: 2012/01/13 (NL2008118)

(51) Cl.Int./Int.Cl. *B60J 7/02* (2006.01),
B60J 10/82 (2016.01)
 (72) Inventeurs/Inventors:
MATOS RICARDO, CARLOS ALBERTO, PT;
LAMMERS, GEERTRUIDA ANNA PETRONELLA
MARIA, PT
 (73) Propriétaire/Owner:
VERACHTERT, AUGUSTINUS MARIA, NL
 (74) Agent: METHOD LAW PROFESSIONAL
CORPORATION

(54) Titre : BUS CABRIOLET
 (54) Title: CABRIOBUS



(57) Abrégé/Abstract:

The present invention relates to a bus of the hardtop type having at least six seats. The bus comprises a chassis and a body with an at least substantially U-shaped roof construction, which covers, at least some of the seats of the bus, which roof construction can be removed, and be replaced again, over at least some of the at least six seats. The substantially U-shaped roof construction comprises at least two substantially shape retaining, nestable roof elements of at least substantially U-shaped cross-section, which are movable relative to each other and which are positioned at least substantially one behind another, at least in the covering position.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau(10) International Publication Number
WO 2013/105847 A1(43) International Publication Date
18 July 2013 (18.07.2013)

(51) International Patent Classification:

B60J 7/02 (2006.01) *B60J 10/12* (2006.01)
B60J 10/00 (2006.01)

(21) International Application Number:

PCT/NL2012/050654

(22) International Filing Date:

17 September 2012 (17.09.2012)

(25) Filing Language:

Dutch

(26) Publication Language:

English

(30) Priority Data:

2008118 13 January 2012 (13.01.2012) NL

(71) Applicant: VERACHTERT, Augustinus, Maria
[NL/NL]; Mooieweg 186, NL-6836 AL Arnhem (NL).(72) Inventors: MATOS RICARDO, Carlos, Alberto; Rua
Eng. Frederico Ulrich 2959 E, P-4470 Maia (PT). LAM-
MERS, Geertruida, Anna, Petronella, Maria; Rua Eng.
Frederico Ulrich 2959 E, P-4470 Maia (PT).(74) Agent: ALGEMEEN OCTROOI- EN MERKENBUR-
EAU B.V.; P.O. Box 645, NL-5600 AP Eindhoven (NL).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: CABRIOBUS




Fig. 2

(57) Abstract: The present invention relates to a bus of the hardtop type having at least six seats. The bus comprises a chassis and a body with an at least substantially U-shaped roof construction, which covers, at least some of the seats of the bus, which roof construction can be removed, and be replaced again, over at least some of the at least six seats. The substantially U-shaped roof construction comprises at least two substantially shape retaining, nestable roof elements of at least substantially U-shaped cross-section, which are movable relative to each other and which are positioned at least substantially one behind another, at least in the covering position.

Title:

Description

The present invention relates to a bus of the hardtop type having at least ten seats and comprising a chassis and a body with an at least substantially U-shaped roof construction, which covers at least some of the seats of the bus, which roof construction can be removed, and be replaced again, over at least some of the at least ten seats. Unless explicitly stated otherwise, the term "remove" as used herein is understood to mean removing the cover from its original, seat-covering position. Furthermore preferably, the bus has at least thirteen seats, so that the bus will be suitable for group transport or for touristic purposes.

Such a bus is known as a cabrio bus. The known cabrio bus has a substantially U-shaped roof construction, which is detachably attached to the bus body. Upon conversion of the known cabrio bus from a closed bus to an open bus, the roof construction is detached and the roof construction, or at least the removable part thereof, is removed from the body and temporarily stored outside the bus. The cabrio bus can now be used with an open roof. When the roof of the cabrio bus is to be closed, the bus is driven to the location where the removable part of the roof construction is temporarily stored. At that location, the roof construction is placed on the body again and attached thereto.

A drawback of the known cabrio bus is the fact that the conversion from a closed roof state to an open roof state, and vice versa, is a relatively laborious job. In addition, the removable part of the roof construction is separated from the bus, so that the roof construction is not available for being placed back in the case of a sudden change of the weather.

Accordingly it is the object of the present invention to provide a bus as described in the introduction which is easier to convert between a closed roof state and an open roof state and/or which remains with the bus also in the open position of the roof.

This object is achieved by the present invention in that the substantially U-shaped roof construction comprises at least two substantially shape retaining, nestable roof elements of at least substantially U-shaped cross-section, which are movable relative to each other and which are positioned at least substantially one behind another, at least in the covering position, with the legs of

the U-shaped cross-section extending downwards the windows present in the roof construction. Usually, such windows will be provided in the downwardly extending side panels that correspond to the legs of the U-shape. The shape of the roof elements distinguishes the cabrio bus according to the present invention from, inter alia, buses of the sliding roof type, in which only a part of the roof located above windows present in the bus can be moved. A sliding roof reduces the structural strength of a bus significantly less than does an open roof, or at least a roof that can be opened. Moreover, a movable roof comprising side panels that extend relatively far downwards makes higher demands on the seal between moving parts than does a sliding roof.

The characteristic aspects of the present invention make it possible to store the nestable roof elements in a nested position in or on the bus in the non-covering position, as a result of which one or more roof elements can be removed from their original position by being moved from an original, covering position to a nested position. This is realised without the storage thereof objectionably taking up any space, or at least hardly any space, for any passengers in the bus. Thus, the roof elements that have been removed from their covering position can be carried along by the bus at all times, also in their removed position. The object of the present invention is thus achieved, at least partially so. The term "non-covering position" of a roof element is understood to mean the position of the roof element in which the roof element does not cover the original part of the bus. Nested roof elements may jointly cover another part of the bus, however.

Passenger cars of the hardtop convertible type in which the roof elements can be stored in a compact manner in relation to each other in the open position of the roof do exist, to be true, but insofar as the relative position of the roof elements in that state may be regarded as nested, there is this important difference that vehicles comprising fewer seats, as a rule no more than two rows of seats, are concerned in that case. The removable part of the roof construction is relatively small. Because of the relatively small size of such a passenger car, its movable roof construction does not have to meet high requirements.

A known convertible of the passenger car type comprises a hinged frame provided with a flexible fabric, wherein the fabric, which functions as a roof, can be folded open by swinging hinging elements of the hinged frame rearwards, seen in the driving direction of the car. The fabric folds onto itself, so that it will take

up relatively little space in the open position of the roof. This is not a hardtop convertible type, however. A drawback of such a roof is the fact that the construction is not shape-retaining and that weather influences are relatively easily noticeable by the occupants also in the closed position of the roof construction. In addition, the windows of the removable part of the roof construction are less suitable for looking out therethrough in the closed position of the bus. They are made of a flexible plastic material.

In a preferred embodiment of the present invention, at least one of the nestable roof elements is immovably connected to the body. The other roof elements can be nested relative to said at least one immovable roof element. It is preferable in that regard if the immovable roof element is larger than the movable roof elements, with the movable roof elements being accommodable within said immovable roof element. The largest (immovable) roof element forms an adequate protection against the influence of the weather on the movable roof elements, in particular while the bus is driving.

A movable roof element is preferably movable along a guide element relative to the chassis. This makes it possible to move a movable roof element to the desired position in a relatively simple and guided manner along a guide. Although a guide is an excellent aid during said movement, the provision of a guide is not necessary, however. The movable roof elements might be simply detached from the bus body, for example, to be subsequently moved to a desired position in or on the bus, for example be carried to the storage location by persons.

In a preferred embodiment of the present invention, the body comprises at least one guide element, along which the movable roof element is guided upon being moved. The guide element on the body can cooperate with a guide element on a movable roof element, so that the movable roof element can be guided between a closed position and an open position of the roof in a simple manner through cooperation of the guides.

Alternatively, or additionally, the at least one guide element is provided on a further roof element, relative to which further roof element the movable roof element is nestable. In such a situation, a guide element on the movable roof element can cooperate with the at least one guide element on the further roof element, for example in the way a drawer cooperates with a cabinet in which the draw is slidably accommodated.

The guide element preferably comprises one or more rails extending in the longitudinal direction of the bus so as to make it possible to move a movable roof element in the longitudinal direction of the bus from the open position to the closed position of the roof.

5 In a preferred embodiment of the invention, an expandable seal is provided, at least in the closed position of the roof construction, between at least some of the parts of the roof construction that are movable relative to each other. Relative movability and sealing are opposing concepts. To obtain an adequate seal, for example against the passage of air or water, the seal must press firmly against
10 the surfaces of an opening to be sealed, in the case of the bus two roof elements that are movable in parallel directions relative to each other. This, however, causes the resistance against movement of one part or both parts to increase. An expandable seal makes it possible on the one hand to expand the seal so as to obtain a proper abutment against the movable parts, and on the other hand to
15 release the expansion so as to be able to move two mutually movable parts more easily relative to each other.

It is preferable in that regard if the expandable seal comprises at least one sealing element of an elastic material, which defines a fluid channel, wherein a fluid is present in the fluid channel, wherein the interior of the sealing
20 element is impermeably sealed from the environment, at least to the fluid in question, and wherein pressure means are provided for increasing and decreasing the pressure of the fluid in said at least one sealing element. Seals between two movable parts often consist of an elongated strip of a resilient material, such as rubber, comprising an elongated hollow chamber. The material slightly adapts to the
25 state of the opening to be sealed. As a result of the resilience of the material, however, the seal can be released in a relatively simple manner in case of an undesirably high load, for example during stormy weather, so that there is a risk of leakage. By increasing the internal pressure in the fluid channel as prescribed by the present invention, the resilience of the seal decreases and thus the quality of the
30 seal increases.

The pressure means preferably comprise a compressor. The compressor may be a compressor of the bus engine, but according to another possibility a separate compressor may be provided for realising the seal. When the roof elements are to be moved relative to each other in the closed position, the

sealing elements are in their expanded state and the compressor must be operated to release the pressure. Following that, the roof elements can be moved relative to each other.

In a preferred embodiment of the present invention, the bus
5 comprises two or more movable roof elements, each provided with an associated guide element. If the number of movable roof elements of the bus is larger, a relatively larger part of the roof construction can be removed, at least if the roof elements are about the same length. When two roof elements are used, one being movable, approximately half the roof construction can be removed by nesting one
10 movable roof element in the immovable roof element (or conversely). If three movable roof elements can be nested in an immovable roof element, approximately three quarters of the roof construction can be removed. Furthermore, relatively small roof elements are relatively easy to move. On the other hand, each next nestable, movable roof element needs to be smaller than the preceding one, and consequently
15 a situation in which the space within the bus, i.e. the space covered by the smallest roof element, is limited by the presence of a (too) large number of roof elements must be prevented.

In a preferred embodiment of the present invention, a roof element comprises a roof part and two window parts, i.e. the base of the inverted U-shape of
20 the roof construction comprises the roof part and the legs of the inverted U-shape comprise the window parts. Thus, the space above and beside the passenger spaces covered by the movable roof element in the closed position thereof can be cleared in one go by moving a movable roof element. Alternatively, the roof part of the roof element is movable in the longitudinal direction of the bus in a manner as described
25 above, and window parts of the roof element are separate from the roof part so that they can be accommodated in the body in vertical direction, for example in a known manner similar to car windows of passenger cars. The presence of vertical guides for the windows above the body must preferably be prevented, not only because said vertical guides are vulnerable in the lowered position of the window parts, but also
30 because passenger safety may be affected by their presence.

The bus is preferably suitable and approved for passenger transport on public roads. It is also conceivable to use a roof construction as described above with another type of passenger vehicle comprising ten or more seats for passenger transport, for example a railroad carriage, an amphibious vehicle or the like.

The present invention will now be explained with reference to the appended drawings, in which:

Figure 1 is a perspective view of a first embodiment of a bus according to the present invention in a closed state thereof;

5 Figure 2 is a perspective view of the bus of figure 1, in this case in an open state thereof;

Figure 3a is a perspective view of an alternative embodiment of a bus according to the present invention in a closed state thereof;

10 Figure 3b is a perspective view of the bus of figure 3a, in this case in an open state thereof;

Figure 4a is a schematic, cutaway side view of the bus with a guide mechanism for the roof elements of the bus of figure 1;

Figure 4b is a schematic, partially cutaway top view of the bus with the guide mechanism of figure 4a;

15 Figures 5a and 5b show an alternative embodiment of the seal as shown in the encircled, larger-scale detail of figure 4b in two different states thereof;

Figure 6a shows the bus of figure 4a with the roof open;

Figure 6b shows the bus of figure 4b with the roof closed;

20 Figures 7a and 7b are perspective views of a guide arrangement for use in the bus of figure 1; and

Figure 7c is a perspective view of a guide arrangement for use in a bus as shown in figures 3a, 3b.

With reference now to figure 1, there is shown a passenger bus 1 having a body 2 comprising a front wall 3, two side walls 4 and a rear wall (not shown in the figures). The body has two A-pillars 5, two B-pillars 6, two C-pillars 7 and two Z-pillars 8. Present between the right-hand A-pillar 5 and B-pillar 6 is a door 9 via which passengers can get on and off. Disposed between the B-pillar 6 and the C-pillar 7 on each side is a conventional window 10. The bus 1 is provided with rows of seats 11a-f for passengers. The bus 1 further comprises the usual means known to the skilled person that enable the bus 1 to function, of course. Above the driver's seat 11 and the first row of seats 11a, near the window 10, part of a conventional roof 12 extends. The (part of a) conventional roof 12 is provided with a skylight 12a. The body 2 is further provided with guides 13a, 13b. The bus 1 has one immovable roof element, which is provided with a skylight 12a of a transparent plastic, and two

25
30

movable roof elements 15a, 15b, which are made of a frame 14 with transparent plastic. At the rear end of the roof 12, seen in the driving direction, the roof 12 overlaps the roof element 15a over a short distance. Provided between the roof 12 and the roof element 15a is a seal (not shown in figures 1 and 2), such that the roof element 15a is capable of sliding movement in part of the roof 12 and that a seal against weather influences, such as precipitation and wind, is provided in the closed position of the roof 12 and the roof elements 14, 15a as shown in figure 1. A comparable construction is provided between the roof element 15a and the roof element 15b. At the rear side, the roof element 15b sealingly abuts against the Z-pillars 8 and the roof part 16 present therebetween.

Figure 2 shows the bus 1 of figure 1. In figure 2, corresponding parts of the bus 1 are indicated by the same numerals as in figure 1. In figure 2, the bus 1 is shown with its roof construction in the open position. The roof element 15b has to that end been moved over the guide rail 13b from its original position (see figure 1) to a position under the roof element 15a. Subsequently, the two roof elements 15a, 15b have jointly been moved to a position under part of the roof 12. The seat rows 11c-11f are thus no longer covered. The seat rows 11a and 11b are covered by the roof 12 and the stored roof elements 15a and 15b. This position of the roof elements 15a and 15b is referred to as a non-covering position or state herein. After all, the seats 11a and 11b and the roof elements 15a and 15b are covered by the roof 12. Since the roof element 15b is smaller than the roof element 15a, and the roof element 15a is in turn smaller than the roof 12, the roof elements 15a and 15b do not experience any hindrance from the wind or the like while driving in the thus stored position shown in figure 2.

Figure 3a shows an alternative embodiment of a bus 61 according to the present invention. The bus 61 exhibits a great deal of similarity to the bus 1 shown in figures 1a, 1b. The body 62 is comparable to that of the bus 1 of figures 1a and 1b, with this difference that the bus 61 has rear side wall parts 64a and a roof part 72a at the rear. Figure 3a shows the bus 61 in the closed state, whilst figure 3b shows the bus 61 with its open roof construction in an open state. As figure 3b shows, the guides 73a, 73b are positioned higher than the guides of the bus 1. Furthermore, two movable roof elements 75a, 75b are provided, which roof elements are made of an opaque plastic. In this embodiment, the roof elements 75a and 75b can be accommodated practically in their entirety, because the roof elements 75a,

75b have no side wall, or at least practically no side wall, so that they can be moved to a position under the roof 72 in the front of the bus 1 without obstructing access through the door 69 to the passengers. With the bus 1, on the contrary, such would be the case. As a result, one additional row of seats, i.e. the row of seats 71b, can
5 be cleared by the movable roof elements 75a, 75b in the bus 61 in comparison with the bus 1, in which the roof elements cannot move beyond the B-pillar 6. The windows 70b, 70c, 70d and 70e can be accommodated in the spaces in the side wall 64 that are intended for that purpose, as is known with conventional passenger cars, in particular of the convertible type.

10 Figures 4a and 4b show a schematic and partially cutaway side view and top view, respectively, of the bus 1 of figure 1 (in the closed state), by way of illustration of the way the roof elements 15a, 15b are guided relative to the body 2. The roof elements 15a and 15b are supported in guides 13a, 13b, which extend in the longitudinal direction of the bus 1. Under said joint guides 13, an endless
15 conveyor 17 extends, which is driven by an electric motor 19 via a drive shaft 18. Said conveyor 17 is connected to a pillar 20 of the rear roof element 15b and as such keeps the roof elements 15a and 15b in their locked position. The encircled detail view of figure 4a shows that the conveyor 17 is clamped down by two fixing elements 29 connected to bolts 30, which fixing elements are attached to the rear
20 pillar 20 of the rear roof element 15b. When the drive shaft 18 is driven in clockwise direction by the electric motor 19 in figure 4a, the upper part of the conveyor 17 moves to the right in figure 4a, carrying along the pillar 20 connected thereto. The rear roof element 15b thus moves toward the front of the bus 1. The roof element 15a remains in the position shown in figure 1a for the time being until the pillar 20
25 comes into contact with the pillar 21 of the roof element 15a, thus pushing the roof element 14 toward the front of the bus 1 as well. The roof element 15b, which has entirely or substantially entirely moved under the roof element 15a, thus moves under the roof 12 together with the roof element 15a. When the two roof elements 15a, 15b have thus moved entirely or substantially entirely under the roof 12, the
30 electric motor 19 is stopped and the conveyor 17 keeps the pillar 20, and thus the roof elements 15a and 15b, positioned under the roof 12.

The rear wall 22 of the body 2 of the bus 1 extends with its flank parts 23 from the rear of the bus to the front over a small distance on two sides. Each flank part 23 slightly overlaps the roof element 15b, so that the pillars 20 are

positioned beside the flank parts 23. At its front end, the flank part 23 is provided with a recess 24, in which a sealing element 25 as known per se for sliding panels is provided. A comparable interaction takes place between the element 15a with the pillar 21 and the roof element 15b with the pillar 26, beside which pillar 21 a sealing element 25 is provided. A sealing element 25 is also provided between the pillar 27 of the roof element 15a and the pillar 28 that connects the rear part of the roof 12 to the part of the body 2 of the bus 1 that is located thereunder.

Figures 5a and 5b show an alternative seal between two adjacent roof elements to the seal shown in figure 4b. A wall part 31 of an outer roof element, in this case a rear roof element that is fixedly connected to the body, overlaps a movable wall part 32 of an inner roof element in figures 5a, 5b. Of the wall part 31, a pillar 33 is shown, which pillar is located near an end section 34 of the movable wall part 32. In this state, the roof of the bus is closed. In figure 5a, an expandable sealing element 35 formed by a rubber wall 36 that forms a non-air permeable envelope of the hollow air channel 37 is in an expanded state. The air pressure in the hollow chamber ranges between 1.25 and 2.5 bar, preferably 2.0 bar. The rubber wall 36 firmly presses against the end section of the movable wall part 32 on the side remote from the pillar 33. Thus the sealing element 35 not only seals the space between the two wall parts 31, 32, but it also offers resistance against movement of the movable wall part 32 with respect to the fixed wall part 31.

When the cover of the bus is to be opened, air is sucked from the hollow air chamber 37 by a compressor (not shown) until the prevailing pressure in the air channel 37 is lower than 1 bar, so that the part of the rubber wall 36 remote from the pillar 33 is pushed inwards by the higher ambient pressure. Thus, the contact between the wall parts 31 and 32 is released, and the movable roof element, of which the wall part 32 forms part, can be removed in a simple manner. A separate locking arrangement for the movable roof element may be provided, for example in a conveyor for the roof elements, with the sealing element 35 providing additional locking. While the operation of the seal in figures 5a, 5b is shown for a fixed and a movable roof element, it is equally well possible to use such a seal with two movable roof elements.

Referring now to figures 6a and 6b, there is again shown a schematic and partially cutaway side view and top view, respectively, of the bus 1 of figures 4a and 4b, in this case with an open roof, however, i.e. with the roof elements

15a, 15b in the stored position. The fixing element 29 is still positioned under the pillar 20, of course, which pillar is connected to the conveyor 17 via the fixing element 29. In the insets of figure 6b, the position of the sealing elements 25 relative to the pillars 26, 27 and 20, 21, 28, respectively, is shown. When the bus 1 is to be converted again from the state shown in figures 6a, 6b to the closed state, the electric motor, 19 is driven in the reverse direction so as to rotate the drive shaft 18 (in figure 4) in anticlockwise direction. Thus, the upper part of the conveyor 17 will move rearwards, carrying along the pillar 20 via the fixing element 29, and the roof element 15b will move to the rear, whilst initially, the roof element 15a will remain stored under the roof 12. At some point the pillar 26 will come into contact with the pillar 21, and the pillar 21, and thus the roof element 15a, will be carried along with the pillar 26. When finally, the pillar 20 has returned to the position shown in figures 4a, 4b, the roof of the bus 1 will be closed and the electric motor 19 will be deactivated. The roof elements 15a, 15b are now locked in the covering position.

15 Figures 7a and 7b show the above-described movements of the roof elements 15a, 15b, whilst the body of the bus is not shown. In figures 7a and 7b corresponding parts are indicated by the same numerals as in figures 4 and 6. Since the discussion of figures 4 and 6 is sufficiently clear, it will not be repeated with regard to figures 7a and 7b.

20 Figure 7c shows an alternative embodiment of a driving mechanism for roof elements 45a, 45b of a bus comparable to the bus shown in figure 2, which roof elements 45a, 45b, in contrast to the roof elements of the bus 61 shown in figure 3, comprise window elements. The driving mechanism of the roof elements 45a, 45b is positioned at the top of a bus, however, so that the roof elements 45a, 45b are, at least partially, supported on the endless conveyor belts 47, which are driven by the electric motor 49 via the drive shaft 48. The roof elements 45a, 45b comprise guide elements (not shown) at the bottom side, which guide elements cooperate with a guide on the body of a bus or other vehicle. Instead of providing the two conveyors 47, it is also possible to provide one central conveyor in or near the centre of the roof elements 45a, 45b, so that the roof elements 45a, 45b are supported on a conveyor and the body of a bus.

30 In the figures and the description the present invention has been shown and described on the basis of a few embodiments thereof. It will be understood, however, that many variants, which may or may not be obvious to the

skilled person, are conceivable within the scope as defined in the following claims:
Thus, guides of a different type may be provided at different positions. The roof elements need not be driven, or be movable via guides, but they may also be carried by hand between a covering and a non-covering position or be moved otherwise.

- 5 The roof elements may also be nestable at the rear of the bus or even in the middle of the bus rather than in the front of the bus. The number of movable roof elements may alternatively be 1, 3, 4 or even more. The roof elements may be entirely or partially made of a material other than a plastic material, for example of glass or another transparent or even non-transparent material. Locking the roof elements can
- 10 be done in many different ways with or without interaction with any guides. Instead of being guided in separate guides, the roof elements may also be guided in a common guide, etc.

1. A bus of the hardtop type having at least ten seats, comprising a chassis and a body with an at least substantially U-shaped roof construction, which covers at least some of the seats of the bus, which roof construction can be removed, and be replaced again, over at least some of the at least ten seats, the bus, at the rear
5 side, comprising two Z-pillars and a roof part therebetween characterised in that the substantially U-shaped roof construction comprises at least two substantially shape retaining, nestable roof elements of at least substantially U-shaped cross-section, wherein windows are provided in the downwardly extending side panels that correspond to the legs of the U-shape, which nestable roof elements are movable
10 relative to each other and which are positioned at least substantially one behind another, at least in the covering position, with the legs of the U-shaped cross-section extending beyond the windows present in the roof construction.
2. A bus according to claim 1, characterised in that at least one of the nestable roof elements is immovably connected to the body.
- 15 3. A bus according to claim 1 or 2, characterised in that a movable roof element is movable along a guide element relative to the chassis.
4. A bus according to claim 3, characterised in that the body comprises at least one guide element, along which a movable roof element is guided upon movement thereof.
- 20 5. A bus according to claim 3, characterised in that the at least one guide element is provided on a further roof element, relative to which the movable roof element is nestable.
6. A bus according to claim 3, 4 or 5, characterised in that the guide element comprises a rail extending in the longitudinal direction of the bus.
- 25 7. A bus according to any one of claims 1-6, characterised in that an expandable seal is provided, at least in the closed position of the roof construction, between at least some of the parts of the roof construction that are movable relative to each other.
8. A bus according to claim 7, characterised in that the expandable seal
30 comprises at least one sealing element of an elastic material, which defines a fluid channel, wherein a fluid is present in the fluid channel, wherein the interior of the sealing element is impermeably sealed from the environment, at least to the fluid in question, and wherein pressure means are provided for increasing and decreasing the pressure of the fluid in said at least one sealing element.

9. A bus according to claim 8, characterised in that the pressure means comprise a compressor.
10. A bus according to any one of claims 3-9, characterised in that the bus comprises two or more movable roof elements, each provided with an associated
5 guide element.
11. A bus according to any one of claims 1-10, characterised in that the dimensions of the successive nestable roof elements decrease toward the rear, seen in the driving direction of the bus, in the closed state of the bus.
12. A bus according to any one of claims 1-11, characterised in that a roof element
10 comprises a roof part and two window parts.




Fig. 2




Fig.3a




Fig. 3b




Fig. 4a




Fig. 4b




Fig.5a





Fig.5b






Fig. 7c

