

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 November 2006 (02.11.2006)

PCT

(10) International Publication Number
WO 2006/116078 A1

(51) International Patent Classification:
E21B 36/00 (2006.01) *E21B 36/04* (2006.01)

Palo Alto, California 94303 (US). **VINEGAR, Harold J.**
[US/US]; 4613 Laurel, Bellaire, Texas 77401 (US).

(21) International Application Number:
PCT/US2006/015084

(74) Agent: **CHRISTENSEN, Del, S.**; SHELL OIL COMPANY, One Shell Plaza, P.O. Box 2463, Houston, TX 77252-2463 (US).

(22) International Filing Date: 21 April 2006 (21.04.2006)

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/674,081 22 April 2005 (22.04.2005) US

(71) Applicant (*for all designated States except US*): **SHELL OIL COMPANY** [US/US]; One Shell Plaza, P.O. Box 2463, Houston, Texas 77252-2463 (US).


(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **SANDBERG, Chester Ledlie** [US/US]; 758 Torreya Ct, Palo Alto,

[Continued on next page]

(54) Title: INSULATED CONDUCTOR TEMPERATURE LIMITED HEATER FOR SUBSURFACE HEATING COUPLED IN A THREE-PHASE WYE CONFIGURATION



(57) Abstract: A heating system for a subsurface formation is described. The heating system includes a first heater (212), a second heater (212), and a third heater (212) placed in an opening in the subsurface formation. Each heater includes an electrical conductor (218), an insulation layer (220) at least partially surrounding the electrical conductor, and an electrically conductive sheath (222) at least partially surrounding the insulation layer. The electrical conductor is electrically coupled to the sheath at a lower end portion of the heater. The lower end portion is the portion of the heater distal from a surface of the opening. The first heater, the second heater, and the third heater are electrically coupled at the lower end portions of the heaters. The first heater, the second heater, and the third heater are electrically coupled in a three-phase wye configuration.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INSULATED CONDUCTOR TEMPERATURE LIMITED HEATER FOR SUBSURFACE HEATING COUPLED
IN A THREE-PHASE WYE CONFIGURATION**BACKGROUND**1. Field of the Invention

The present invention relates generally to methods and systems for heating and production of hydrocarbons, hydrogen, and/or other products from various subsurface formations such as hydrocarbon containing formations. Embodiments relate to insulated conductor temperature limited heaters used to heat subsurface formations.

2. Description of Related Art

Hydrocarbons obtained from subterranean formations are often used as energy resources, as feedstocks, and as consumer products. Concerns over depletion of available hydrocarbon resources and concerns over declining overall quality of produced hydrocarbons have led to development of processes for more efficient recovery, processing and/or use of available hydrocarbon resources. In situ processes may be used to remove hydrocarbon materials from subterranean formations. Chemical and/or physical properties of hydrocarbon material in a subterranean formation may need to be changed to allow hydrocarbon material to be more easily removed from the subterranean formation. The chemical and physical changes may include in situ reactions that produce removable fluids, composition changes, solubility changes, density changes, phase changes, and/or viscosity changes of the hydrocarbon material in the formation. A fluid may be, but is not limited to, a gas, a liquid, an emulsion, a slurry, and/or a stream of solid particles that has flow characteristics similar to liquid flow.

Heaters may be placed in wellbores to heat a formation during an in situ process. Examples of in situ processes utilizing downhole heaters are illustrated in U.S. Patent Nos. 2,634,961 to Ljungstrom; 2,732,195 to Ljungstrom; 2,780,450 to Ljungstrom; 2,789,805 to Ljungstrom; 2,923,535 to Ljungstrom; and 4,886,118 to Van Meurs et al.; each of which is incorporated by reference as if fully set forth herein.

Application of heat to oil shale formations is described in U.S. Patent Nos. 2,923,535 to Ljungstrom and 4,886,118 to Van Meurs et al. Heat may be applied to the oil shale formation to pyrolyze kerogen in the oil shale formation. The heat may also fracture the formation to increase permeability of the formation. The increased permeability may allow formation fluid to travel to a production well where the fluid is removed from the oil shale formation. In some processes disclosed by Ljungstrom, for example, an oxygen containing gaseous medium is introduced to a permeable stratum, preferably while still hot from a preheating step, to initiate combustion.

A heat source may be used to heat a subterranean formation. Electric heaters may be used to heat the subterranean formation by radiation and/or conduction. An electric heater may resistively heat an element. U.S. Patent No. 2,548,360 to Germain, which is incorporated by reference as if fully set forth herein, describes an electric heating element placed in a viscous oil in a wellbore. The heater element heats and thins the oil to allow the oil to be pumped from the wellbore. U.S. Patent No. 4,716,960 to Eastlund et al., which is incorporated by reference as if fully set forth herein, describes electrically heating tubing of a petroleum well by passing a relatively low voltage current through the tubing to prevent formation of solids. U.S. Patent No. 5,065,818 to Van Egmond, which is incorporated by reference as if fully set forth herein, describes an electric heating element that is cemented into a well borehole without a casing surrounding the heating element.

Some heaters may be difficult to coupled in a subsurface formation. Electrical current flow between heaters downhole in a subsurface formation may be unreliable due to difficult to make subsurface connections and the

uncertainty of current flow in subsurface conditions. Thus, it is advantageous to have a heater that does not have current flow between heaters in the subsurface.

SUMMARY

Embodiments described herein generally relate to systems, methods, and heaters for treating a subsurface formation. Embodiments described herein also generally relate to heaters that have novel components therein. Such heaters can be obtained by using the systems and methods described herein.

In certain embodiments, the invention provides one or more systems, methods, and/or heaters. In some embodiments, the systems, methods, and/or heaters are used for treating a subsurface formation.

In certain embodiments, the invention provides a heating system for a subsurface formation, comprising: a first heater, a second heater, and a third heater placed in an opening in the subsurface formation, wherein each heater comprises: an electrical conductor; an insulation layer at least partially surrounding the electrical conductor; an electrically conductive sheath at least partially surrounding the insulation layer; wherein the electrical conductor is electrically coupled to the sheath at a lower end portion of the heater, the lower end portion being the portion of the heater distal from a surface of the opening; the first heater, the second heater, and the third heater being electrically coupled at the lower end portions of the heaters; and the first heater, the second heater, and the third heater are configured to be electrically coupled in a three-phase wye configuration.

In further embodiments, features from specific embodiments may be combined with features from other embodiments. For example, features from one embodiment may be combined with features from any of the other embodiments.

In further embodiments, treating a subsurface formation is performed using any of the methods, systems, or heaters described herein.

In further embodiments, additional features may be added to the specific embodiments described herein.

BRIEF DESCRIPTION OF THE DRAWINGS

Advantages of the present invention may become apparent to those skilled in the art with the benefit of the following detailed description and upon reference to the accompanying drawings in which:

FIG. 1 depicts an illustration of stages of heating a hydrocarbon containing formation.

FIG. 2 shows a schematic view of an embodiment of a portion of an in situ conversion system for treating a hydrocarbon containing formation.

FIGS. 3A and 3B depict cross-sectional representations of an embodiment of a temperature limited heater component used in an insulated conductor heater.

FIGS. 4A and 4B depict an embodiment for installing heaters in a wellbore.

FIG. 4C depicts an embodiment of an insulated conductor with the sheath shorted to the conductors.

FIGS. 5A and 5B depict an embodiment of a three conductor-in-conduit heater.

While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and may herein be described in detail. The drawings may not be to scale. It should be understood, however, that the drawings and detailed description thereto are not intended to limit the invention to the particular form disclosed, but on the contrary, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the present invention as defined by the appended claims.

DETAILED DESCRIPTION

The following description generally relates to systems and methods for treating hydrocarbons in the formations. Such formations may be treated to yield hydrocarbon products, hydrogen, and other products.

"Hydrocarbons" are generally defined as molecules formed primarily by carbon and hydrogen atoms.

5 Hydrocarbons may also include other elements such as, but not limited to, halogens, metallic elements, nitrogen, oxygen, and/or sulfur. Hydrocarbons may be, but are not limited to, kerogen, bitumen, pyrobitumen, oils, natural mineral waxes, and asphaltites. Hydrocarbons may be located in or adjacent to mineral matrices in the earth. Matrices may include, but are not limited to, sedimentary rock, sands, silicilytes, carbonates, diatomites, and other porous media. "Hydrocarbon fluids" are fluids that include hydrocarbons. Hydrocarbon fluids may include, entrain,
10 or be entrained in non-hydrocarbon fluids such as hydrogen, nitrogen, carbon monoxide, carbon dioxide, hydrogen sulfide, water, and ammonia.

A "formation" includes one or more hydrocarbon containing layers, one or more non-hydrocarbon layers, an overburden, and/or an underburden. The "overburden" and/or the "underburden" include one or more different types of impermeable materials. For example, overburden and/or underburden may include rock, shale, mudstone,
15 or wet/tight carbonate. In some embodiments of in situ conversion processes, the overburden and/or the underburden may include a hydrocarbon containing layer or hydrocarbon containing layers that are relatively impermeable and are not subjected to temperatures during in situ conversion processing that result in significant characteristic changes of the hydrocarbon containing layers of the overburden and/or the underburden. For example, the underburden may contain shale or mudstone, but the underburden is not allowed to heat to pyrolysis temperatures
20 during the in situ conversion process. In some cases, the overburden and/or the underburden may be somewhat permeable.

A "heat source" is any system for providing heat to at least a portion of a formation substantially by conductive and/or radiative heat transfer. For example, a heat source may include electric heaters such as an insulated conductor, an elongated member, and/or a conductor disposed in a conduit. A heat source may also
25 include systems that generate heat by burning a fuel external to or in a formation. The systems may be surface burners, downhole gas burners, flameless distributed combustors, and natural distributed combustors. In some embodiments, heat provided to or generated in one or more heat sources may be supplied by other sources of energy. The other sources of energy may directly heat a formation, or the energy may be applied to a transfer medium that directly or indirectly heats the formation. It is to be understood that one or more heat sources that are applying heat
30 to a formation may use different sources of energy. Thus, for example, for a given formation some heat sources may supply heat from electric resistance heaters, some heat sources may provide heat from combustion, and some heat sources may provide heat from one or more other energy sources (for example, chemical reactions, solar energy, wind energy, biomass, or other sources of renewable energy). A chemical reaction may include an exothermic reaction (for example, an oxidation reaction). A heat source may also include a heater that provides heat to a zone
35 proximate and/or surrounding a heating location such as a heater well.

A "heater" is any system or heat source for generating heat in a well or a near wellbore region. Heaters may be, but are not limited to, electric heaters, burners, combustors that react with material in or produced from a formation, and/or combinations thereof.

An "in situ conversion process" refers to a process of heating a hydrocarbon containing formation from heat
40 sources to raise the temperature of at least a portion of the formation above a pyrolysis temperature so that pyrolyzation fluid is produced in the formation.

“Insulated conductor” refers to any elongated material that is able to conduct electricity and that is covered, in whole or in part, by an electrically insulating material.

An elongated member may be a bare metal heater or an exposed metal heater. “Bare metal” and “exposed metal” refer to metals that do not include a layer of electrical insulation, such as mineral insulation, that is designed to provide electrical insulation for the metal throughout an operating temperature range of the elongated member. Bare metal and exposed metal may encompass a metal that includes a corrosion inhibitor such as a naturally occurring oxidation layer, an applied oxidation layer, and/or a film. Bare metal and exposed metal include metals with polymeric or other types of electrical insulation that cannot retain electrical insulating properties at typical operating temperature of the elongated member. Such material may be placed on the metal and may be thermally degraded during use of the heater.

“Temperature limited heater” generally refers to a heater that regulates heat output (for example, reduces heat output) above a specified temperature without the use of external controls such as temperature controllers, power regulators, rectifiers, or other devices. Temperature limited heaters may be AC (alternating current) or modulated (for example, “chopped”) DC (direct current) powered electrical resistance heaters.

“Curie temperature” is the temperature above which a ferromagnetic material loses all of its ferromagnetic properties. In addition to losing all of its ferromagnetic properties above the Curie temperature, the ferromagnetic material begins to lose its ferromagnetic properties when an increasing electrical current is passed through the ferromagnetic material.

“Time-varying current” refers to electrical current that produces skin effect electricity flow in a ferromagnetic conductor and has a magnitude that varies with time. Time-varying current includes both alternating current (AC) and modulated direct current (DC).

“Alternating current (AC)” refers to a time-varying current that reverses direction substantially sinusoidally. AC produces skin effect electricity flow in a ferromagnetic conductor.

“Modulated direct current (DC)” refers to any substantially non-sinusoidal time-varying current that produces skin effect electricity flow in a ferromagnetic conductor.

“Turndown ratio” for the temperature limited heater is the ratio of the highest AC or modulated DC resistance below the Curie temperature to the lowest resistance above the Curie temperature for a given current.

In the context of reduced heat output heating systems, apparatus, and methods, the term “automatically” means such systems, apparatus, and methods function in a certain way without the use of external control (for example, external controllers such as a controller with a temperature sensor and a feedback loop, PID controller, or predictive controller).

The term “wellbore” refers to a hole in a formation made by drilling or insertion of a conduit into the formation. A wellbore may have a substantially circular cross section, or another cross-sectional shape. As used herein, the terms “well” and “opening,” when referring to an opening in the formation may be used interchangeably with the term “wellbore.”

Hydrocarbons in formations may be treated in various ways to produce many different products. In certain embodiments, hydrocarbons in formations are treated in stages. FIG. 1 depicts an illustration of stages of heating the hydrocarbon containing formation. FIG. 1 also depicts an example of yield (“Y”) in barrels of oil equivalent per ton (y axis) of formation fluids from the formation versus temperature (“T”) of the heated formation in degrees Celsius (x axis).

Desorption of methane and vaporization of water occurs during stage 1 heating. Heating of the formation through stage 1 may be performed as quickly as possible. For example, when the hydrocarbon containing formation is initially heated, hydrocarbons in the formation desorb adsorbed methane. The desorbed methane may be produced from the formation. If the hydrocarbon containing formation is heated further, water in the hydrocarbon containing formation is vaporized. Water may occupy, in some hydrocarbon containing formations, between 10% and 50% of the pore volume in the formation. In other formations, water occupies larger or smaller portions of the pore volume. Water typically is vaporized in a formation between 160 °C and 285 °C at pressures of 600 kPa absolute to 7000 kPa absolute. In some embodiments, the vaporized water produces wettability changes in the formation and/or increased formation pressure. The wettability changes and/or increased pressure may affect pyrolysis reactions or other reactions in the formation. In certain embodiments, the vaporized water is produced from the formation. In other embodiments, the vaporized water is used for steam extraction and/or distillation in the formation or outside the formation. Removing the water from and increasing the pore volume in the formation increases the storage space for hydrocarbons in the pore volume.

In certain embodiments, after stage 1 heating, the formation is heated further, such that a temperature in the formation reaches (at least) an initial pyrolyzation temperature (such as a temperature at the lower end of the temperature range shown as stage 2). Hydrocarbons in the formation may be pyrolyzed throughout stage 2. A pyrolysis temperature range varies depending on the types of hydrocarbons in the formation. The pyrolysis temperature range may include temperatures between 250 °C and 900 °C. The pyrolysis temperature range for producing desired products may extend through only a portion of the total pyrolysis temperature range. In some embodiments, the pyrolysis temperature range for producing desired products may include temperatures between 250 °C and 400 °C or temperatures between 270 °C and 350 °C. If a temperature of hydrocarbons in the formation is slowly raised through the temperature range from 250 °C to 400 °C, production of pyrolysis products may be substantially complete when the temperature approaches 400 °C. Average temperature of the hydrocarbons may be raised at a rate of less than 5 °C per day, less than 2 °C per day, less than 1 °C per day, or less than 0.5 °C per day through the pyrolysis temperature range for producing desired products. Heating the hydrocarbon containing formation with a plurality of heat sources may establish thermal gradients around the heat sources that slowly raise the temperature of hydrocarbons in the formation through the pyrolysis temperature range.

The rate of temperature increase through the pyrolysis temperature range for desired products may affect the quality and quantity of the formation fluids produced from the hydrocarbon containing formation. Raising the temperature slowly through the pyrolysis temperature range for desired products may inhibit mobilization of large chain molecules in the formation. Raising the temperature slowly through the pyrolysis temperature range for desired products may limit reactions between mobilized hydrocarbons that produce undesired products. Slowly raising the temperature of the formation through the pyrolysis temperature range for desired products may allow for the production of high quality, high API gravity hydrocarbons from the formation. Slowly raising the temperature of the formation through the pyrolysis temperature range for desired products may allow for the removal of a large amount of the hydrocarbons present in the formation as hydrocarbon product.

In some in situ conversion embodiments, a portion of the formation is heated to a desired temperature instead of slowly heating the temperature through a temperature range. In some embodiments, the desired temperature is 300 °C, 325 °C, or 350 °C. Other temperatures may be selected as the desired temperature. Superposition of heat from heat sources allows the desired temperature to be relatively quickly and efficiently established in the formation. Energy input into the formation from the heat sources may be adjusted to maintain the

temperature in the formation substantially at the desired temperature. The heated portion of the formation is maintained substantially at the desired temperature until pyrolysis declines such that production of desired formation fluids from the formation becomes uneconomical. Parts of the formation that are subjected to pyrolysis may include regions brought into a pyrolysis temperature range by heat transfer from only one heat source.

5 In certain embodiments, formation fluids including pyrolyzation fluids are produced from the formation. As the temperature of the formation increases, the amount of condensable hydrocarbons in the produced formation fluid may decrease. At high temperatures, the formation may produce mostly methane and/or hydrogen. If the hydrocarbon containing formation is heated throughout an entire pyrolysis range, the formation may produce only small amounts of hydrogen towards an upper limit of the pyrolysis range. After all of the available hydrogen is
10 depleted, a minimal amount of fluid production from the formation will typically occur.

After pyrolysis of hydrocarbons, a large amount of carbon and some hydrogen may still be present in the formation. A significant portion of carbon remaining in the formation can be produced from the formation in the form of synthesis gas. Synthesis gas generation may take place during stage 3 heating depicted in FIG. 1. Stage 3 may include heating a hydrocarbon containing formation to a temperature sufficient to allow synthesis gas
15 generation. For example, synthesis gas may be produced in a temperature range from about 400 °C to about 1200 °C, about 500 °C to about 1100 °C, or about 550 °C to about 1000 °C. The temperature of the heated portion of the formation when the synthesis gas generating fluid is introduced to the formation determines the composition of synthesis gas produced in the formation. The generated synthesis gas may be removed from the formation through a production well or production wells.

20 Total energy content of fluids produced from the hydrocarbon containing formation may stay relatively constant throughout pyrolysis and synthesis gas generation. During pyrolysis at relatively low formation temperatures, a significant portion of the produced fluid may be condensable hydrocarbons that have a high energy content. At higher pyrolysis temperatures, however, less of the formation fluid may include condensable hydrocarbons. More non-condensable formation fluids may be produced from the formation. Energy content per
25 unit volume of the produced fluid may decline slightly during generation of predominantly non-condensable formation fluids. During synthesis gas generation, energy content per unit volume of produced synthesis gas declines significantly compared to energy content of pyrolyzation fluid. The volume of the produced synthesis gas, however, will in many instances increase substantially, thereby compensating for the decreased energy content.

FIG. 2 depicts a schematic view of an embodiment of a portion of the in situ conversion system for treating
30 a hydrocarbon containing formation. The in situ conversion system may include barrier wells 200. Barrier wells 200 are used to form a barrier around a treatment area. The barrier inhibits fluid flow into and/or out of the treatment area. Barrier wells include, but are not limited to, dewatering wells, vacuum wells, capture wells, injection wells, grout wells, freeze wells, or combinations thereof. In the embodiment depicted in FIG. 2, barrier wells 200 are shown extending only along one side of heat sources 202, but the barrier wells typically encircle all heat sources
35 202 used, or to be used, to heat a treatment area of the formation.

Heat sources 202 are placed in at least a portion of the formation. Heat sources 202 may include heaters such as insulated conductors, conductor-in-conduit heaters, surface burners, flameless distributed combustors, and/or natural distributed combustors. Heat sources 202 may also include other types of heaters. Heat sources 202 provide heat to at least a portion of the formation to heat hydrocarbons in the formation. Energy may be supplied to heat
40 sources 202 through supply lines 204. Supply lines 204 may be structurally different depending on the type of heat source or heat sources used to heat the formation. Supply lines 204 for heat sources may transmit electricity for

electric heaters, may transport fuel for combustors, or may transport heat exchange fluid that is circulated in the formation.

Production wells 206 are used to remove formation fluid from the formation. In some embodiments, production well 206 may include one or more heat sources. A heat source in the production well may heat one or more portions of the formation at or near the production well. A heat source in a production well may inhibit condensation and reflux of formation fluid being removed from the formation.

Formation fluid produced from production wells 206 may be transported through collection piping 208 to treatment facilities 210. Formation fluids may also be produced from heat sources 202. For example, fluid may be produced from heat sources 202 to control pressure in the formation adjacent to the heat sources. Fluid produced from heat sources 202 may be transported through tubing or piping to collection piping 208 or the produced fluid may be transported through tubing or piping directly to treatment facilities 210. Treatment facilities 210 may include separation units, reaction units, upgrading units, fuel cells, turbines, storage vessels, and/or other systems and units for processing produced formation fluids.

Temperature limited heaters may be in configurations and/or may include materials that provide automatic temperature limiting properties for the heater at certain temperatures. In certain embodiments, ferromagnetic materials are used in temperature limited heaters. Ferromagnetic material may self-limit temperature at or near the Curie temperature of the material to provide a reduced amount of heat at or near the Curie temperature when a time-varying current is applied to the material. In certain embodiments, the ferromagnetic material self-limits temperature of the temperature limited heater at a selected temperature that is approximately the Curie temperature. In certain embodiments, the selected temperature is within about 35 °C, within about 25 °C, within about 20 °C, or within about 10 °C of the Curie temperature. In certain embodiments, ferromagnetic materials are coupled with other materials (for example, highly conductive materials, high strength materials, corrosion resistant materials, or combinations thereof) to provide various electrical and/or mechanical properties. Some parts of the temperature limited heater may have a lower resistance (caused by different geometries and/or by using different ferromagnetic and/or non-ferromagnetic materials) than other parts of the temperature limited heater. Having parts of the temperature limited heater with various materials and/or dimensions allows for tailoring the desired heat output from each part of the heater.

Temperature limited heaters may be more reliable than other heaters. Temperature limited heaters may be less apt to break down or fail due to hot spots in the formation. In some embodiments, temperature limited heaters allow for substantially uniform heating of the formation. In some embodiments, temperature limited heaters are able to heat the formation more efficiently by operating at a higher average heat output along the entire length of the heater. The temperature limited heater operates at the higher average heat output along the entire length of the heater because power to the heater does not have to be reduced to the entire heater, as is the case with typical constant wattage heaters, if a temperature along any point of the heater exceeds, or is about to exceed, a maximum operating temperature of the heater. Heat output from portions of a temperature limited heater approaching a Curie temperature of the heater automatically reduces without controlled adjustment of the time-varying current applied to the heater. The heat output automatically reduces due to changes in electrical properties (for example, electrical resistance) of portions of the temperature limited heater. Thus, more power is supplied by the temperature limited heater during a greater portion of a heating process.

In certain embodiments, the system including temperature limited heaters initially provides a first heat output and then provides a reduced (second heat output) heat output, near, at, or above the Curie temperature of an

electrically resistive portion of the heater when the temperature limited heater is energized by a time-varying current. The first heat output is the heat output at temperatures below which the temperature limited heater begins to self-limit. In some embodiments, the first heat output is the heat output at a temperature 50 °C, 75 °C, 100 °C, or 125 °C below the Curie temperature of the ferromagnetic material in the temperature limited heater.

5 The temperature limited heater may be energized by time-varying current (alternating current or modulated direct current) supplied at the wellhead. The wellhead may include a power source and other components (for example, modulation components, transformers, and/or capacitors) used in supplying power to the temperature limited heater. The temperature limited heater may be one of many heaters used to heat a portion of the formation.

10 In certain embodiments, the temperature limited heater includes a conductor that operates as a skin effect or proximity effect heater when time-varying current is applied to the conductor. The skin effect limits the depth of current penetration into the interior of the conductor. For ferromagnetic materials, the skin effect is dominated by the magnetic permeability of the conductor. The relative magnetic permeability of ferromagnetic materials is typically between 10 and 1000 (for example, the relative magnetic permeability of ferromagnetic materials is typically at least 10 and may be at least 50, 100, 500, 1000 or greater). As the temperature of the ferromagnetic
15 material is raised above the Curie temperature and/or as the applied electrical current is increased, the magnetic permeability of the ferromagnetic material decreases substantially and the skin depth expands rapidly (for example, the skin depth expands as the inverse square root of the magnetic permeability). The reduction in magnetic permeability results in a decrease in the AC or modulated DC resistance of the conductor near, at, or above the Curie temperature and/or as the applied electrical current is increased. When the temperature limited heater is powered by
20 a substantially constant current source, portions of the heater that approach, reach, or are above the Curie temperature may have reduced heat dissipation. Sections of the temperature limited heater that are not at or near the Curie temperature may be dominated by skin effect heating that allows the heater to have high heat dissipation due to a higher resistive load.

25 An advantage of using the temperature limited heater to heat hydrocarbons in the formation is that the conductor is chosen to have a Curie temperature in a desired range of temperature operation. Operation within the desired operating temperature range allows substantial heat injection into the formation while maintaining the temperature of the temperature limited heater, and other equipment, below design limit temperatures. Design limit temperatures are temperatures at which properties such as corrosion, creep, and/or deformation are adversely affected. The temperature limiting properties of the temperature limited heater inhibits overheating or burnout of the
30 heater adjacent to low thermal conductivity "hot spots" in the formation. In some embodiments, the temperature limited heater is able to lower or control heat output and/or withstand heat at temperatures above 25 °C, 37 °C, 100 °C, 250 °C, 500 °C, 700 °C, 800 °C, 900 °C, or higher up to 1131 °C, depending on the materials used in the heater.

35 The temperature limited heater allows for more heat injection into the formation than constant wattage heaters because the energy input into the temperature limited heater does not have to be limited to accommodate low thermal conductivity regions adjacent to the heater. For example, in Green River oil shale there is a difference of at least a factor of 3 in the thermal conductivity of the lowest richness oil shale layers and the highest richness oil shale layers. When heating such a formation, substantially more heat is transferred to the formation with the temperature limited heater than with the conventional heater that is limited by the temperature at low thermal conductivity layers. The heat output along the entire length of the conventional heater needs to accommodate the low thermal
40 conductivity layers so that the heater does not overheat at the low thermal conductivity layers and burn out. The heat output adjacent to the low thermal conductivity layers that are at high temperature will reduce for the temperature

limited heater, but the remaining portions of the temperature limited heater that are not at high temperature will still provide high heat output. Because heaters for heating hydrocarbon formations typically have long lengths (for example, at least 10 m, 100 m, 300 m, at least 500 m, 1 km or more up to about 10 km), the majority of the length of the temperature limited heater may be operating below the Curie temperature while only a few portions are at or near the Curie temperature of the temperature limited heater.

The use of temperature limited heaters allows for efficient transfer of heat to the formation. Efficient transfer of heat allows for reduction in time needed to heat the formation to a desired temperature. For the same heater spacing, temperature limited heaters may allow a larger average heat output while maintaining heater equipment temperatures below equipment design limit temperatures. Pyrolysis in the formation may occur at an earlier time with the larger average heat output provided by temperature limited heaters than the lower average heat output provided by constant wattage heaters. Temperature limited heaters counteract hot spots due to inaccurate well spacing or drilling where heater wells come too close together. In certain embodiments, temperature limited heaters allow for increased power output over time for heater wells that have been spaced too far apart, or limit power output for heater wells that are spaced too close together. Temperature limited heaters also supply more power in regions adjacent the overburden and underburden to compensate for temperature losses in these regions.

Temperature limited heaters may be advantageously used in many types of formations. For example, in tar sands formations or relatively permeable formations containing heavy hydrocarbons, temperature limited heaters may be used to provide a controllable low temperature output for reducing the viscosity of fluids, mobilizing fluids, and/or enhancing the radial flow of fluids at or near the wellbore or in the formation. Temperature limited heaters may be used to inhibit excess coke formation due to overheating of the near wellbore region of the formation.

The use of temperature limited heaters, in some embodiments, eliminates or reduces the need for expensive temperature control circuitry. For example, the use of temperature limited heaters eliminates or reduces the need to perform temperature logging and/or the need to use fixed thermocouples on the heaters to monitor potential overheating at hot spots.

In some embodiments, temperature limited heaters are more economical to manufacture or make than standard heaters. Typical ferromagnetic materials include iron, carbon steel, or ferritic stainless steel. Such materials are inexpensive as compared to nickel-based heating alloys (such as nichrome, Kanthal™ (Bulten-Kanthal AB, Sweden), and/or LOHM™ (Driver-Harris Company, Harrison, New Jersey, U.S.A.)) typically used in insulated conductor (mineral insulated cable) heaters. In one embodiment of the temperature limited heater, the temperature limited heater is manufactured in continuous lengths as an insulated conductor heater to lower costs and improve reliability.

Temperature limited heaters may be used for heating hydrocarbon formations including, but not limited to, oil shale formations, coal formations, tar sands formations, and heavy viscous oils. Temperature limited heaters may also be used in the field of environmental remediation to vaporize or destroy soil contaminants. Embodiments of temperature limited heaters may be used to heat fluids in a wellbore or sub-sea pipeline to inhibit deposition of paraffin or various hydrates. In some embodiments, a temperature limited heater is used for solution mining a subsurface formation (for example, an oil shale or a coal formation). In certain embodiments, a fluid (for example, molten salt) is placed in a wellbore and heated with a temperature limited heater to inhibit deformation and/or collapse of the wellbore. In some embodiments, the temperature limited heater is attached to a sucker rod in the wellbore or is part of the sucker rod itself. In some embodiments, temperature limited heaters are used to heat a near wellbore region to reduce near wellbore oil viscosity during production of high viscosity crude oils and during

transport of high viscosity oils to the surface. In some embodiments, a temperature limited heater enables gas lifting of a viscous oil by lowering the viscosity of the oil without coking the oil. Temperature limited heaters may be used in sulfur transfer lines to maintain temperatures between about 110 °C and about 130 °C.

Certain embodiments of temperature limited heaters may be used in chemical or refinery processes at elevated temperatures that require control in a narrow temperature range to inhibit unwanted chemical reactions or damage from locally elevated temperatures. Some applications may include, but are not limited to, reactor tubes, cokers, and distillation towers. Temperature limited heaters may also be used in pollution control devices (for example, catalytic converters, and oxidizers) to allow rapid heating to a control temperature without complex temperature control circuitry. Additionally, temperature limited heaters may be used in food processing to avoid damaging food with excessive temperatures. Temperature limited heaters may also be used in the heat treatment of metals (for example, annealing of weld joints). Temperature limited heaters may also be used in floor heaters, cauterizers, and/or various other appliances. Temperature limited heaters may be used with biopsy needles to destroy tumors by raising temperatures in vivo.

Some embodiments of temperature limited heaters may be useful in certain types of medical and/or veterinary devices. For example, a temperature limited heater may be used to therapeutically treat tissue in a human or an animal. A temperature limited heater for a medical or veterinary device may have ferromagnetic material including a palladium-copper alloy with a Curie temperature of about 50 °C. A high frequency (for example, a frequency greater than about 1 MHz) may be used to power a relatively small temperature limited heater for medical and/or veterinary use.

The ferromagnetic alloy or ferromagnetic alloys used in the temperature limited heater determine the Curie temperature of the heater. Curie temperature data for various metals is listed in "American Institute of Physics Handbook," Second Edition, McGraw-Hill, pages 5-170 through 5-176. Ferromagnetic conductors may include one or more of the ferromagnetic elements (iron, cobalt, and nickel) and/or alloys of these elements. In some embodiments, ferromagnetic conductors include iron-chromium (Fe-Cr) alloys that contain tungsten (W) (for example, HCM12A and SAVE12 (Sumitomo Metals Co., Japan) and/or iron alloys that contain chromium (for example, Fe-Cr alloys, Fe-Cr-W alloys, Fe-Cr-V (vanadium) alloys, Fe-Cr-Nb (Niobium) alloys). Of the three main ferromagnetic elements, iron has a Curie temperature of approximately 770 °C; cobalt (Co) has a Curie temperature of approximately 1131 °C; and nickel has a Curie temperature of approximately 358 °C. An iron-cobalt alloy has a Curie temperature higher than the Curie temperature of iron. For example, iron-cobalt alloy with 2% by weight cobalt has a Curie temperature of approximately 800 °C; iron-cobalt alloy with 12% by weight cobalt has a Curie temperature of approximately 900 °C; and iron-cobalt alloy with 20% by weight cobalt has a Curie temperature of approximately 950 °C. Iron-nickel alloy has a Curie temperature lower than the Curie temperature of iron. For example, iron-nickel alloy with 20% by weight nickel has a Curie temperature of approximately 720 °C, and iron-nickel alloy with 60% by weight nickel has a Curie temperature of approximately 560 °C.

Some non-ferromagnetic elements used as alloys raise the Curie temperature of iron. For example, an iron-vanadium alloy with 5.9% by weight vanadium has a Curie temperature of approximately 815 °C. Other non-ferromagnetic elements (for example, carbon, aluminum, copper, silicon, and/or chromium) may be alloyed with iron or other ferromagnetic materials to lower the Curie temperature. Non-ferromagnetic materials that raise the Curie temperature may be combined with non-ferromagnetic materials that lower the Curie temperature and alloyed with iron or other ferromagnetic materials to produce a material with a desired Curie temperature and other desired

physical and/or chemical properties. In some embodiments, the Curie temperature material is a ferrite such as NiFe_2O_4 . In other embodiments, the Curie temperature material is a binary compound such as FeNi_3 or Fe_3Al .

Certain embodiments of temperature limited heaters may include more than one ferromagnetic material. Such embodiments are within the scope of embodiments described herein if any conditions described herein apply to at least one of the ferromagnetic materials in the temperature limited heater.

Ferromagnetic properties generally decay as the Curie temperature is approached. The "Handbook of Electrical Heating for Industry" by C. James Erickson (IEEE Press, 1995) shows a typical curve for 1% carbon steel (steel with 1% carbon by weight). The loss of magnetic permeability starts at temperatures above 650 °C and tends to be complete when temperatures exceed 730 °C. Thus, the self-limiting temperature may be somewhat below the actual Curie temperature of the ferromagnetic conductor. The skin depth for current flow in 1% carbon steel is 0.132 cm at room temperature and increases to 0.445 cm at 720 °C. From 720 °C to 730 °C, the skin depth sharply increases to over 2.5 cm. Thus, a temperature limited heater embodiment using 1% carbon steel begins to self-limit between 650 °C and 730 °C.

Skin depth generally defines an effective penetration depth of time-varying current into the conductive material. In general, current density decreases exponentially with distance from an outer surface to the center along the radius of the conductor. The depth at which the current density is approximately $1/e$ of the surface current density is called the skin depth. For a solid cylindrical rod with a diameter much greater than the penetration depth, or for hollow cylinders with a wall thickness exceeding the penetration depth, the skin depth, δ , is:

$$(1) \delta = 1981.5 * (\rho / (\mu * f))^{1/2};$$

in which: δ = skin depth in inches;
 ρ = resistivity at operating temperature (ohm-cm);
 μ = relative magnetic permeability; and
 f = frequency (Hz).

EQN. 1 is obtained from "Handbook of Electrical Heating for Industry" by C. James Erickson (IEEE Press, 1995). For most metals, resistivity (ρ) increases with temperature. The relative magnetic permeability generally varies with temperature and with current. Additional equations may be used to assess the variance of magnetic permeability and/or skin depth on both temperature and/or current. The dependence of μ on current arises from the dependence of μ on the magnetic field.

Materials used in the temperature limited heater may be selected to provide a desired turndown ratio. Turndown ratios of at least 1.1:1, 2:1, 3:1, 4:1, 5:1, 10:1, 30:1, or 50:1 may be selected for temperature limited heaters. Larger turndown ratios may also be used. A selected turndown ratio may depend on a number of factors including, but not limited to, the type of formation in which the temperature limited heater is located (for example, a higher turndown ratio may be used for an oil shale formation with large variations in thermal conductivity between rich and lean oil shale layers) and/or a temperature limit of materials used in the wellbore (for example, temperature limits of heater materials). In some embodiments, the turndown ratio is increased by coupling additional copper or another good electrical conductor to the ferromagnetic material (for example, adding copper to lower the resistance above the Curie temperature).

The temperature limited heater may provide a minimum heat output (power output) below the Curie temperature of the heater. In certain embodiments, the minimum heat output is at least 400 W/m (Watts per meter), 600 W/m, 700 W/m, 800 W/m, or higher up to 2000 W/m. The temperature limited heater reduces the amount of heat output by a section of the heater when the temperature of the section of the heater approaches or is above the

Curie temperature. The reduced amount of heat may be substantially less than the heat output below the Curie temperature. In some embodiments, the reduced amount of heat is at most 400 W/m, 200 W/m, 100 W/m or may approach 0 W/m.

The AC or modulated DC resistance and/or the heat output of the temperature limited heater may decrease as the temperature approaches the Curie temperature and decrease sharply near or above the Curie temperature due to the Curie effect. In certain embodiments, the value of the electrical resistance or heat output above or near the Curie temperature is at most one-half of the value of electrical resistance or heat output at a certain point below the Curie temperature. In some embodiments, the heat output above or near the Curie temperature is at most 90%, 70%, 50%, 30%, 20%, 10%, or less (down to 1%) of the heat output at a certain point below the Curie temperature (for example, 30 °C below the Curie temperature, 40 °C below the Curie temperature, 50 °C below the Curie temperature, or 100 °C below the Curie temperature). In certain embodiments, the electrical resistance above or near the Curie temperature decreases to 80%, 70%, 60%, 50%, or less (down to 1%) of the electrical resistance at a certain point below the Curie temperature (for example, 30 °C below the Curie temperature, 40 °C below the Curie temperature, 50 °C below the Curie temperature, or 100 °C below the Curie temperature).

In some embodiments, AC frequency is adjusted to change the skin depth of the ferromagnetic material. For example, the skin depth of 1% carbon steel at room temperature is 0.132 cm at 60 Hz, 0.0762 cm at 180 Hz, and 0.046 cm at 440 Hz. Since heater diameter is typically larger than twice the skin depth, using a higher frequency (and thus a heater with a smaller diameter) reduces heater costs. For a fixed geometry, the higher frequency results in a higher turndown ratio. The turndown ratio at a higher frequency is calculated by multiplying the turndown ratio at a lower frequency by the square root of the higher frequency divided by the lower frequency. In some embodiments, a frequency between 100 Hz and 1000 Hz, between 140 Hz and 200 Hz, or between 400 Hz and 600 Hz is used (for example, 180 Hz, 540 Hz, or 720 Hz). In some embodiments, high frequencies may be used. The frequencies may be greater than 1000 Hz.

In certain embodiments, modulated DC (for example, chopped DC, waveform modulated DC, or cycled DC) may be used for providing electrical power to the temperature limited heater. A DC modulator or DC chopper may be coupled to a DC power supply to provide an output of modulated direct current. In some embodiments, the DC power supply may include means for modulating DC. One example of a DC modulator is a DC-to-DC converter system. DC-to-DC converter systems are generally known in the art. DC is typically modulated or chopped into a desired waveform. Waveforms for DC modulation include, but are not limited to, square-wave, sinusoidal, deformed sinusoidal, deformed square-wave, triangular, and other regular or irregular waveforms.

The modulated DC waveform generally defines the frequency of the modulated DC. Thus, the modulated DC waveform may be selected to provide a desired modulated DC frequency. The shape and/or the rate of modulation (such as the rate of chopping) of the modulated DC waveform may be varied to vary the modulated DC frequency. DC may be modulated at frequencies that are higher than generally available AC frequencies. For example, modulated DC may be provided at frequencies of at least 1000 Hz. Increasing the frequency of supplied current to higher values advantageously increases the turndown ratio of the temperature limited heater.

In certain embodiments, the modulated DC waveform is adjusted or altered to vary the modulated DC frequency. The DC modulator may be able to adjust or alter the modulated DC waveform at any time during use of the temperature limited heater and at high currents or voltages. Thus, modulated DC provided to the temperature limited heater is not limited to a single frequency or even a small set of frequency values. Waveform selection using the DC modulator typically allows for a wide range of modulated DC frequencies and for discrete control of the

modulated DC frequency. Thus, the modulated DC frequency is more easily set at a distinct value whereas AC frequency is generally limited to multiples of the line frequency. Discrete control of the modulated DC frequency allows for more selective control over the turndown ratio of the temperature limited heater. Being able to selectively control the turndown ratio of the temperature limited heater allows for a broader range of materials to be used in designing and constructing the temperature limited heater.

In certain embodiments, the temperature limited heater includes a composite conductor with a ferromagnetic tubular and a non-ferromagnetic, high electrical conductivity core. The non-ferromagnetic, high electrical conductivity core reduces a required diameter of the conductor. The core or non-ferromagnetic conductor may be copper or copper alloy. The core or non-ferromagnetic conductor may also be made of other metals that exhibit low electrical resistivity and relative magnetic permeabilities near 1 (for example, substantially non-ferromagnetic materials such as aluminum and aluminum alloys, phosphor bronze, beryllium copper, and/or brass). A composite conductor allows the electrical resistance of the temperature limited heater to decrease more steeply near the Curie temperature. As the skin depth increases near the Curie temperature to include the copper core, the electrical resistance decreases very sharply.

The composite conductor may increase the conductivity of the temperature limited heater and/or allow the heater to operate at lower voltages. In an embodiment, the composite conductor exhibits a relatively flat resistance versus temperature profile at temperatures below a region near the Curie temperature of the ferromagnetic conductor of the composite conductor. In some embodiments, the temperature limited heater exhibits a relatively flat resistance versus temperature profile between 100 °C and 750 °C or between 300 °C and 600 °C. The relatively flat resistance versus temperature profile may also be exhibited in other temperature ranges by adjusting, for example, materials and/or the configuration of materials in the temperature limited heater. In certain embodiments, the relative thickness of each material in the composite conductor is selected to produce a desired resistivity versus temperature profile for the temperature limited heater.

In certain embodiments, the relative thickness of each material in a composite conductor is selected to produce a desired resistivity versus temperature profile for a temperature limited heater.

A composite conductor (for example, a composite inner conductor or a composite outer conductor) may be manufactured by methods including, but not limited to, coextrusion, roll forming, tight fit tubing (for example, cooling the inner member and heating the outer member, then inserting the inner member in the outer member, followed by a drawing operation and/or allowing the system to cool), explosive or electromagnetic cladding, arc overlay welding, longitudinal strip welding, plasma powder welding, billet coextrusion, electroplating, drawing, sputtering, plasma deposition, coextrusion casting, magnetic forming, molten cylinder casting (of inner core material inside the outer or vice versa), insertion followed by welding or high temperature braising, shielded active gas welding (SAG), and/or insertion of an inner pipe in an outer pipe followed by mechanical expansion of the inner pipe by hydroforming or use of a pig to expand and swage the inner pipe against the outer pipe. In some embodiments, a ferromagnetic conductor is braided over a non-ferromagnetic conductor. In certain embodiments, composite conductors are formed using methods similar to those used for cladding (for example, cladding copper to steel). A metallurgical bond between copper cladding and base ferromagnetic material may be advantageous. Composite conductors produced by a coextrusion process that forms a good metallurgical bond (for example, a good bond between copper and 446 stainless steel) may be provided by Anomet Products, Inc. (Shrewsbury, Massachusetts, U.S.A.).

FIGS. 3-5 depict various embodiments of temperature limited heaters. One or more features of an embodiment of the temperature limited heater depicted in any of these figures may be combined with one or more features of other embodiments of temperature limited heaters depicted in these figures. In certain embodiments described herein, temperature limited heaters are dimensioned to operate at a frequency of 60 Hz AC. It is to be understood that dimensions of the temperature limited heater may be adjusted from those described herein in order for the temperature limited heater to operate in a similar manner at other AC frequencies or with modulated DC current.

For a temperature limited heater in which the ferromagnetic conductor provides a majority of the resistive heat output below the Curie temperature, a majority of the current flows through material with highly non-linear functions of magnetic field (H) versus magnetic induction (B). These non-linear functions may cause strong inductive effects and distortion that lead to decreased power factor in the temperature limited heater at temperatures below the Curie temperature. These effects may render the electrical power supply to the temperature limited heater difficult to control and may result in additional current flow through surface and/or overburden power supply conductors. Expensive and/or difficult to implement control systems such as variable capacitors or modulated power supplies may be used to attempt to compensate for these effects and to control temperature limited heaters where the majority of the resistive heat output is provided by current flow through the ferromagnetic material.

In certain temperature limited heater embodiments, the ferromagnetic conductor confines a majority of the flow of electrical current to an electrical conductor coupled to the ferromagnetic conductor when the temperature limited heater is below or near the Curie temperature of the ferromagnetic conductor. The electrical conductor may be a sheath, jacket, support member, corrosion resistant member, or other electrically resistive member. In some embodiments, the ferromagnetic conductor confines a majority of the flow of electrical current to the electrical conductor positioned between an outermost layer and the ferromagnetic conductor. The ferromagnetic conductor is located in the cross section of the temperature limited heater such that the magnetic properties of the ferromagnetic conductor at or below the Curie temperature of the ferromagnetic conductor confine the majority of the flow of electrical current to the electrical conductor. The majority of the flow of electrical current is confined to the electrical conductor due to the skin effect of the ferromagnetic conductor. Thus, the majority of the current is flowing through material with substantially linear resistive properties throughout most of the operating range of the heater.

In certain embodiments, the ferromagnetic conductor and the electrical conductor are located in the cross section of the temperature limited heater so that the skin effect of the ferromagnetic material limits the penetration depth of electrical current in the electrical conductor and the ferromagnetic conductor at temperatures below the Curie temperature of the ferromagnetic conductor. Thus, the electrical conductor provides a majority of the electrically resistive heat output of the temperature limited heater at temperatures up to a temperature at or near the Curie temperature of the ferromagnetic conductor. In certain embodiments, the dimensions of the electrical conductor may be chosen to provide desired heat output characteristics.

Because the majority of the current flows through the electrical conductor below the Curie temperature, the temperature limited heater has a resistance versus temperature profile that at least partially reflects the resistance versus temperature profile of the material in the electrical conductor. Thus, the resistance versus temperature profile of the temperature limited heater is substantially linear below the Curie temperature of the ferromagnetic conductor if the material in the electrical conductor has a substantially linear resistance versus temperature profile. The resistance of the temperature limited heater has little or no dependence on the current flowing through the heater

until the temperature nears the Curie temperature. The majority of the current flows in the electrical conductor rather than the ferromagnetic conductor below the Curie temperature.

Resistance versus temperature profiles for temperature limited heaters in which the majority of the current flows in the electrical conductor also tend to exhibit sharper reductions in resistance near or at the Curie temperature of the ferromagnetic conductor. The sharper reductions in resistance near or at the Curie temperature are easier to control than more gradual resistance reductions near the Curie temperature.

In certain embodiments, the material and/or the dimensions of the material in the electrical conductor are selected so that the temperature limited heater has a desired resistance versus temperature profile below the Curie temperature of the ferromagnetic conductor.

Temperature limited heaters in which the majority of the current flows in the electrical conductor rather than the ferromagnetic conductor below the Curie temperature are easier to predict and/or control. Behavior of temperature limited heaters in which the majority of the current flows in the electrical conductor rather than the ferromagnetic conductor below the Curie temperature may be predicted by, for example, its resistance versus temperature profile and/or its power factor versus temperature profile. Resistance versus temperature profiles and/or power factor versus temperature profiles may be assessed or predicted by, for example, experimental measurements that assess the behavior of the temperature limited heater, analytical equations that assess or predict the behavior of the temperature limited heater, and/or simulations that assess or predict the behavior of the temperature limited heater.

In certain embodiments, assessed or predicted behavior of the temperature limited heater is used to control the temperature limited heater. The temperature limited heater may be controlled based on measurements (assessments) of the resistance and/or the power factor during operation of the heater. In some embodiments, the power, or current, supplied to the temperature limited heater is controlled based on assessment of the resistance and/or the power factor of the heater during operation of the heater and the comparison of this assessment versus the predicted behavior of the heater. In certain embodiments, the temperature limited heater is controlled without measurement of the temperature of the heater or a temperature near the heater. Controlling the temperature limited heater without temperature measurement eliminates operating costs associated with downhole temperature measurement. Controlling the temperature limited heater based on assessment of the resistance and/or the power factor of the heater also reduces the time for making adjustments in the power or current supplied to the heater compared to controlling the heater based on measured temperature.

As the temperature of the temperature limited heater approaches or exceeds the Curie temperature of the ferromagnetic conductor, reduction in the ferromagnetic properties of the ferromagnetic conductor allows electrical current to flow through a greater portion of the electrically conducting cross section of the temperature limited heater. Thus, the electrical resistance of the temperature limited heater is reduced and the temperature limited heater automatically provides reduced heat output at or near the Curie temperature of the ferromagnetic conductor. In certain embodiments, a highly electrically conductive member is coupled to the ferromagnetic conductor and the electrical conductor to reduce the electrical resistance of the temperature limited heater at or above the Curie temperature of the ferromagnetic conductor. The highly electrically conductive member may be an inner conductor, a core, or another conductive member of copper, aluminum, nickel, or alloys thereof.

The ferromagnetic conductor that confines the majority of the flow of electrical current to the electrical conductor at temperatures below the Curie temperature may have a relatively small cross section compared to the ferromagnetic conductor in temperature limited heaters that use the ferromagnetic conductor to provide the majority

of resistive heat output up to or near the Curie temperature. A temperature limited heater that uses the electrical conductor to provide a majority of the resistive heat output below the Curie temperature has low magnetic inductance at temperatures below the Curie temperature because less current is flowing through the ferromagnetic conductor as compared to the temperature limited heater where the majority of the resistive heat output below the Curie temperature is provided by the ferromagnetic material. Magnetic field (H) at radius (r) of the ferromagnetic conductor is proportional to the current (I) flowing through the ferromagnetic conductor and the core divided by the radius, or:

$$(2) H \propto I/r.$$

Since only a portion of the current flows through the ferromagnetic conductor for a temperature limited heater that uses the outer conductor to provide a majority of the resistive heat output below the Curie temperature, the magnetic field of the temperature limited heater may be significantly smaller than the magnetic field of the temperature limited heater where the majority of the current flows through the ferromagnetic material. The relative magnetic permeability (μ) may be large for small magnetic fields.

The skin depth (δ) of the ferromagnetic conductor is inversely proportional to the square root of the relative magnetic permeability (μ):

$$(3) \delta \propto (1/\mu)^{1/2}.$$

Increasing the relative magnetic permeability decreases the skin depth of the ferromagnetic conductor. However, because only a portion of the current flows through the ferromagnetic conductor for temperatures below the Curie temperature, the radius (or thickness) of the ferromagnetic conductor may be decreased for ferromagnetic materials with large relative magnetic permeabilities to compensate for the decreased skin depth while still allowing the skin effect to limit the penetration depth of the electrical current to the electrical conductor at temperatures below the Curie temperature of the ferromagnetic conductor. The radius (thickness) of the ferromagnetic conductor may be between 0.3 mm and 8 mm, between 0.3 mm and 2 mm, or between 2 mm and 4 mm depending on the relative magnetic permeability of the ferromagnetic conductor. Decreasing the thickness of the ferromagnetic conductor decreases costs of manufacturing the temperature limited heater, as the cost of ferromagnetic material tends to be a significant portion of the cost of the temperature limited heater. Increasing the relative magnetic permeability of the ferromagnetic conductor provides a higher turndown ratio and a sharper decrease in electrical resistance for the temperature limited heater at or near the Curie temperature of the ferromagnetic conductor.

Ferromagnetic materials (such as purified iron or iron-cobalt alloys) with high relative magnetic permeabilities (for example, at least 200, at least 1000, at least 1×10^4 , or at least 1×10^5) and/or high Curie temperatures (for example, at least 600 °C, at least 700 °C, or at least 800 °C) tend to have less corrosion resistance and/or less mechanical strength at high temperatures. The electrical conductor may provide corrosion resistance and/or high mechanical strength at high temperatures for the temperature limited heater. Thus, the ferromagnetic conductor may be chosen primarily for its ferromagnetic properties.

Confining the majority of the flow of electrical current to the electrical conductor below the Curie temperature of the ferromagnetic conductor reduces variations in the power factor. Because only a portion of the electrical current flows through the ferromagnetic conductor below the Curie temperature, the non-linear ferromagnetic properties of the ferromagnetic conductor have little or no effect on the power factor of the temperature limited heater, except at or near the Curie temperature. Even at or near the Curie temperature, the effect on the power factor is reduced compared to temperature limited heaters in which the ferromagnetic conductor

provides a majority of the resistive heat output below the Curie temperature. Thus, there is less or no need for external compensation (for example, variable capacitors or waveform modification) to adjust for changes in the inductive load of the temperature limited heater to maintain a relatively high power factor.

5 In certain embodiments, the temperature limited heater, which confines the majority of the flow of electrical current to the electrical conductor below the Curie temperature of the ferromagnetic conductor, maintains the power factor above 0.85, above 0.9, or above 0.95 during use of the heater. Any reduction in the power factor occurs only in sections of the temperature limited heater at temperatures near the Curie temperature. Most sections of the temperature limited heater are typically not at or near the Curie temperature during use. These sections have a high power factor that approaches 1.0. The power factor for the entire temperature limited heater is maintained above
10 0.85, above 0.9, or above 0.95 during use of the heater even if some sections of the heater have power factors below 0.85.

Maintaining high power factors also allows for less expensive power supplies and/or control devices such as solid state power supplies or SCRs (silicon controlled rectifiers). These devices may fail to operate properly if the power factor varies by too large an amount because of inductive loads. With the power factors maintained at the
15 higher values; however, these devices may be used to provide power to the temperature limited heater. Solid state power supplies also have the advantage of allowing fine tuning and controlled adjustment of the power supplied to the temperature limited heater.

In some embodiments, transformers are used to provide power to the temperature limited heater. Multiple voltage taps may be made into the transformer to provide power to the temperature limited heater. Multiple voltage
20 taps allows the current supplied to switch back and forth between the multiple voltages. This maintains the current within a range bound by the multiple voltage taps.

The highly electrically conductive member, or inner conductor, increases the turndown ratio of the temperature limited heater. In certain embodiments, thickness of the highly electrically conductive member is increased to increase the turndown ratio of the temperature limited heater. In some embodiments, the thickness of
25 the electrical conductor is reduced to increase the turndown ratio of the temperature limited heater. In certain embodiments, the turndown ratio of the temperature limited heater is between 1.1 and 10, between 2 and 8, or between 3 and 6 (for example, the turndown ratio is at least 1.1, at least 2, or at least 3).

In some embodiments, a relatively thin conductive layer is used to provide the majority of the electrically resistive heat output of the temperature limited heater at temperatures up to a temperature at or near the Curie
30 temperature of the ferromagnetic conductor. Such a temperature limited heater may be used as the heating member in an insulated conductor heater. The heating member of the insulated conductor heater may be located inside a sheath with an insulation layer between the sheath and the heating member.

FIGS. 3A and 3B depict cross-sectional representations of an embodiment of the insulated conductor heater with the temperature limited heater as the heating member. Insulated conductor 212 includes core 214,
35 ferromagnetic conductor 216, inner conductor 218, electrical insulator 220, and jacket 222. Core 214 is a copper core. Ferromagnetic conductor 216 is, for example, iron or an iron alloy.

Inner conductor 218 is a relatively thin conductive layer of non-ferromagnetic material with a higher electrical conductivity than ferromagnetic conductor 216. In certain embodiments, inner conductor 218 is copper. Inner conductor 218 may also be a copper alloy. Copper alloys typically have a flatter resistance versus temperature
40 profile than pure copper. A flatter resistance versus temperature profile may provide less variation in the heat output as a function of temperature up to the Curie temperature. In some embodiments, inner conductor 218 is copper with

6% by weight nickel (for example, CuNi6 or LOHM™). In some embodiments, inner conductor 218 is CuNi10Fe1Mn alloy. Below the Curie temperature of ferromagnetic conductor 216, the magnetic properties of the ferromagnetic conductor confine the majority of the flow of electrical current to inner conductor 218. Thus, inner conductor 218 provides the majority of the resistive heat output of insulated conductor 212 below the Curie temperature.

In certain embodiments, inner conductor 218 is dimensioned, along with core 214 and ferromagnetic conductor 216, so that the inner conductor provides a desired amount of heat output and a desired turndown ratio. For example, inner conductor 218 may have a cross-sectional area that is around 2 or 3 times less than the cross-sectional area of core 214. Typically, inner conductor 218 has to have a relatively small cross-sectional area to provide a desired heat output if the inner conductor is copper or copper alloy. In an embodiment with copper inner conductor 218, core 214 has a diameter of 0.66 cm, ferromagnetic conductor 216 has an outside diameter of 0.91 cm, inner conductor 218 has an outside diameter of 1.03 cm, electrical insulator 220 has an outside diameter of 1.53 cm, and jacket 222 has an outside diameter of 1.79 cm. In an embodiment with a CuNi6 inner conductor 218, core 214 has a diameter of 0.66 cm, ferromagnetic conductor 216 has an outside diameter of 0.91 cm, inner conductor 218 has an outside diameter of 1.12 cm, electrical insulator 220 has an outside diameter of 1.63 cm, and jacket 222 has an outside diameter of 1.88 cm. Such insulated conductors are typically smaller and cheaper to manufacture than insulated conductors that do not use the thin inner conductor to provide the majority of heat output below the Curie temperature.

Electrical insulator 220 may be magnesium oxide, aluminum oxide, silicon dioxide, beryllium oxide, boron nitride, silicon nitride, or combinations thereof. In certain embodiments, electrical insulator 220 is a compacted powder of magnesium oxide. In some embodiments, electrical insulator 220 includes beads of silicon nitride.

In certain embodiments, a small layer of material is placed between electrical insulator 220 and inner conductor 218 to inhibit copper from migrating into the electrical insulator at higher temperatures. For example, the small layer of nickel (for example, about 0.5 mm of nickel) may be placed between electrical insulator 220 and inner conductor 218.

Jacket 222 is made of a corrosion resistant material such as, but not limited to, 347 stainless steel, 347H stainless steel, 446 stainless steel, or 825 stainless steel. In some embodiments, jacket 222 provides some mechanical strength for insulated conductor 212 at or above the Curie temperature of ferromagnetic conductor 216. In certain embodiments, jacket 222 is not used to conduct electrical current.

In certain embodiments of temperature limited heaters, three temperature limited heaters are coupled together in a three-phase wye configuration. Coupling three temperature limited heaters together in the three-phase wye configuration lowers the current in each of the individual temperature limited heaters because the current is split between the three individual heaters. Lowering the current in each individual temperature limited heater allows each heater to have a small diameter. The lower currents allow for higher relative magnetic permeabilities in each of the individual temperature limited heaters and, thus, higher turndown ratios. In addition, there may be no return current needed for each of the individual temperature limited heaters. Thus, the turndown ratio remains higher for each of the individual temperature limited heaters than if each temperature limited heater had its own return current path.

In the three-phase wye configuration, individual temperature limited heaters may be coupled together by shorting the sheaths, jackets, or canisters of each of the individual temperature limited heaters to the electrically conductive sections (the conductors providing heat) at their terminating ends (for example, the ends of the heaters at

the bottom of a heater wellbore). In some embodiments, the sheaths, jackets, canisters, and/or electrically conductive sections are coupled to a support member that supports the temperature limited heaters in the wellbore.

FIG. 4A depicts an embodiment for installing and coupling heaters in a wellbore. The embodiment in FIG. 4A depicts insulated conductor heaters being installed into the wellbore. Other types of heaters, such as conductor-in-conduit heaters, may also be installed in the wellbore using the embodiment depicted. Also, in FIG. 4A, two insulated conductors 212 are shown while a third insulated conductor is not seen from the view depicted. Typically, three insulated conductors 212 would be coupled to support member 224, as shown in FIG. 4B. In an embodiment, support member 224 is a thick walled 347H pipe. In some embodiments, thermocouples or other temperature sensors are placed inside support member 224. The three insulated conductors may be coupled in a three-phase wye configuration.

In FIG. 4A, insulated conductors 212 are coiled on coiled tubing rigs 226. As insulated conductors 212 are uncoiled from rigs 226, the insulated conductors are coupled to support member 224. In certain embodiments, insulated conductors 212 are simultaneously uncoiled and/or simultaneously coupled to support member 224. Insulated conductors 212 may be coupled to support member 224 using metal (for example, 304 stainless steel or Inconel® alloys) straps 228. In some embodiments, insulated conductors 212 are coupled to support member 224 using other types of fasteners such as buckles, wire holders, or snaps. Support member 224 along with insulated conductors 212 are installed into opening 230. In some embodiments, insulated conductors 212 are coupled together without the use of a support member. For example, one or more straps 228 may be used to couple insulated conductors 212 together.

Insulated conductors 212 may be electrically coupled to each other (for example, for a three-phase wye configuration) at a lower end of the insulated conductors. In a three-phase wye configuration, insulated conductors 212 operate without a current return path. In certain embodiments, insulated conductors 212 are electrically coupled to each other in contactor section 232. In section 232, sheaths, jackets, canisters, and/or electrically conductive sections are electrically coupled to each other and/or to support member 224 so that insulated conductors 212 are electrically coupled in the section.

In certain embodiments, the sheaths of insulated conductors 212 are shorted to the conductors of the insulated conductors. FIG. 4C depicts an embodiment of insulated conductor 212 with the sheath shorted to the conductors. Sheath 222 is electrically coupled to core 214, ferromagnetic conductor 216, and inner conductor 218 using termination 233. Termination 233 may be a metal strip or a metal plate at the lower end of insulated conductor 212. For example, termination 233 may be a copper plate coupled to sheath 222, core 214, ferromagnetic conductor 216, and inner conductor 218 so that they are shorted together. In some embodiments, termination 233 is welded or brazed to sheath 222, core 214, ferromagnetic conductor 216, and inner conductor 218.

The sheaths of individual insulated conductors 212 may be shorted together to electrically couple the conductors of the insulated conductors, depicted in FIGS. 4A and 4B. In some embodiments, the sheaths may be shorted together because the sheaths are in physical contact with each other. For example, the sheaths may in physical contact if the sheaths are strapped together by straps 228. In some embodiments, the lower ends of the sheaths are physically coupled (for example, welded) at the surface of opening 230 before insulated conductors 212 are installed into the opening.

In certain embodiments, three conductors are located inside a single conduit to form a three conductor-in-conduit heater. FIGS. 5A and 5B depict an embodiment of a three conductor-in-conduit heater. FIG. 5A depicts a top down view of the three conductor-in-conduit heater. FIG. 5B depicts a side view representation with a cutout to

show the internals of the three conductor-in-conduit heater. Three conductors 234 are located inside conduit 236. The three conductors 234 are substantially evenly spaced within conduit 236. In some embodiments, the three conductors 234 are coupled in a spiral configuration.

One or more centralizers 238 are placed around each conductor 234. Centralizers 238 are made from electrically insulating material such as silicon nitride or boron nitride. Centralizers 238 maintain a position of conductors 234 in conduit 236. Centralizers 238 also inhibit electrical contact between conductors 234 and conduit 236. In certain embodiments, centralizers 238 are spaced along the length of conductors 234 so that the centralizers surrounding one conductor overlap (as seen from the top down view) centralizers from another conductor. This reduces the number of centralizers needed for each conductor and allows for tight spacing of the conductors.

In certain embodiments, the three conductors 234 are coupled in a three-phase wye configuration. The three conductors 234 may be coupled at or near the bottom of the heaters in the three-phase wye configuration. In the three-phase wye configuration, conduit 236 is not electrically coupled to the three conductors 234. Thus, conduit 236 may only be used to provide strength for and/or inhibit corrosion of the three conductors 234.

In some embodiments, a heating system includes one or more heaters (for example, one first heater, a second heater, and a third heater), a plurality of electrical insulators and a conduit. The heaters, electrical insulators, and the conduit may be coupled and/or connected to allow placement in an opening in a subsurface formation. The conduit may surround the heaters and the electrical insulators. In some embodiments, the conduit is electrically insulated from the heaters by one or more electrical insulators. A configuration of the conduit, in some embodiments, inhibits formation fluids from entering the conduit.

Each heater of the heating system may be surrounded by at least one electrical insulator. The electrical insulators may be spaced along the lengths of each of the heaters to allow the electrical insulators surrounding one of the heaters to laterally overlap the electrical insulators surrounding another one of the heaters. In some embodiments, the electrical insulators include silicon nitride.

The heaters may include a ferromagnetic member electrically coupled to an electrical conductor. The electrical conductor may be any electrical conductor described herein that provides a first heat output below the Curie temperature of the ferromagnetic member. The electrical conductor may allow a majority of the electrical current to pass through the cross-section of the heater at about 25 °C. In certain embodiments, the ferromagnetic member and the electrical conductor are electrically coupled such that a power factor of the heater remains above 0.85 during use of each heater.

In some embodiments, the ferromagnetic conductor is positioned relative to the electrical conductor. Positioning the ferromagnetic conductor relative to the electrical conductor allows an electromagnetic field produced by current flow in the ferromagnetic conductor to confine a majority of the flow of the electrical current to the electrical conductor at temperatures below or near the Curie temperature of the ferromagnetic conductor.

In some embodiments, the heating system described herein allows heat to transfer from the heaters to a part of the subsurface formation. The heating system has a turndown ratio of at least about 1.1. In some embodiments, the heating system described herein provides (a) a first heat output below the Curie temperature of the ferromagnetic conductor, and (b) a second heat output approximately at and above the Curie temperature of the ferromagnetic conductor. The second heat output being reduced compared to the first heat output. In some embodiments, the second heat output is at most 90% of the first heat output when the first heat output is at about 50 °C below the selected temperature.

In some embodiments, the temperature limited heater is used to achieve lower temperature heating (for example, for heating fluids in a production well, heating a surface pipeline, or reducing the viscosity of fluids in a wellbore or near wellbore region). Varying the ferromagnetic materials of the temperature limited heater allows for lower temperature heating. In some embodiments, the ferromagnetic conductor is made of material with a lower Curie temperature than that of 446 stainless steel. For example, the ferromagnetic conductor may be an alloy of iron and nickel. The alloy may have between 30% by weight and 42% by weight nickel with the rest being iron. In one embodiment, the alloy is Invar 36. Invar 36 is 36% by weight nickel in iron and has a Curie temperature of 277 °C. In some embodiments, an alloy is a three component alloy with, for example, chromium, nickel, and iron. For example, an alloy may have 6% by weight chromium, 42% by weight nickel, and 52% by weight iron. A 2.5 cm diameter rod of Invar 36 has a turndown ratio of approximately 2 to 1 at the Curie temperature. Placing the Invar 36 alloy over a copper core may allow for a smaller rod diameter. A copper core may result in a high turndown ratio. The insulator in lower temperature heater embodiments may be made of a high performance polymer insulator (such as PFA or PEEKTM) when used with alloys with a Curie temperature that is below the melting point or softening point of the polymer insulator.

Further modifications and alternative embodiments of various aspects of the invention may be apparent to those skilled in the art in view of this description. Accordingly, this description is to be construed as illustrative only and is for the purpose of teaching those skilled in the art the general manner of carrying out the invention. It is to be understood that the forms of the invention shown and described herein are to be taken as the presently preferred embodiments. Elements and materials may be substituted for those illustrated and described herein, parts and processes may be reversed, and certain features of the invention may be utilized independently, all as would be apparent to one skilled in the art after having the benefit of this description of the invention. Changes may be made in the elements described herein without departing from the spirit and scope of the invention as described in the following claims. In addition, it is to be understood that features described herein independently may, in certain embodiments, be combined.

CLAIMS

1. A heating system for a subsurface formation, comprising:
a first heater, a second heater, and a third heater placed in an opening in the subsurface formation, wherein
5 each heater comprises:
an electrical conductor;
an insulation layer at least partially surrounding the electrical conductor;
an electrically conductive sheath at least partially surrounding the insulation layer;
wherein the electrical conductor is electrically coupled to the sheath at a lower end portion of the
10 heater, the lower end portion being the portion of the heater distal from a surface of the opening;
the first heater, the second heater, and the third heater being electrically coupled at the lower end portions of
the heaters; and
the first heater, the second heater, and the third heater are configured to be electrically coupled in a three-
phase wye configuration.
- 15 2. The heating system as claimed in claim 1, wherein the system further comprises a support member, the first
heater, the second heater, and the third heater being coupled to the support member.
3. The heating system as claimed in any of claims 1 or 2, wherein the electrical conductor comprises:
an inner electrical conductor;
a ferromagnetic conductor at least partially surrounding the inner electrical conductor and electrically
20 coupled to the inner electrical conductor;
an outer electrical conductor electrically coupled to the ferromagnetic conductor, the outer electrical
conductor at least partially surrounding the ferromagnetic conductor, and the outer electrical conductor providing a
majority of a resistive heat output of the heater at temperatures up to a temperature approximately 50 °C below a
selected temperature; and
25 one or more electrical insulators at least partially surrounding the outer electrical conductor.
4. The heating system as claimed in claim 3, wherein the ferromagnetic conductor is positioned relative to the
outer electrical conductor such that an electromagnetic field produced by current flow in the ferromagnetic
conductor confines a majority of the flow of the electrical current to the outer electrical conductor at temperatures
below or near the selected temperature.
- 30 5. The heating system as claimed in any of claims 3-4, wherein the heating system is configured to provide (a)
a first heat output below the selected temperature, and (b) a second heat output approximately at and above the
selected temperature, the second heat output being reduced compared to the first heat output.
6. The heating system as claimed claim 5, wherein the heating system is configured to automatically provide
the second heat output.
- 35 7. The heating system as claimed in any of claims 5-6, wherein the second heat output is at most 90% of the
first heat output, the first heat output being at about 50 °C below the selected temperature.
8. The heating system as claimed in any of claims 3-7, wherein the inner electrical conductors, the
ferromagnetic conductors, and the outer electrical conductors are electrically coupled such that a power factor of the
heating system remains above about 0.85 during use of the heater.
- 40 9. The heating system as claimed in any of claims 3-8, wherein the selected temperature is the Curie
temperature of the ferromagnetic conductor.

10. The heating system as claimed in any of claims 1-9, wherein the insulation layer comprises one or more electrical insulators at least partially surrounding the electrical conductor.

11. The heating system as claimed in any of claims 1-10, wherein the heating system has a turndown ratio of at least about 1.1.

12. A method for installing the heating system in any one of claims 1-11 in a subsurface formation, the method comprising:

locating the first heater on a first spool, the second heater on a second spool, and the third heater on a third spool at a location of the opening in the subsurface formation;

uncoiling each of the first heater, the second heater, and the third heater as the heaters are being installed in the opening in the subsurface formation;

coupling each of the heaters as the heaters are installed in the opening in the subsurface formation; and electrically coupling the heaters in the three-phase wye configuration.

13. The method as claimed in claim 12, further comprising coupling each of the heaters to a support member as the heaters are installed in the opening in the subsurface formation.

14. The method as claimed in any of claims 12 or 13, wherein the one or more electrical insulators are positioned along a length of the outer electrical conductor such that each heater can be placed on each spool without damaging the electrical insulators.

15. The method as claimed in any of claims 13 or 14, wherein the three heaters are coupled to the support member such that the three heaters are approximately evenly spaced around the support member.

16. A method of heating using the heating system in any one of claims 1-11, the method comprising providing heat from the heaters to a portion of the subsurface formation.

17. The method as claimed in claim 16, wherein the subsurface formation comprises hydrocarbons, the method further comprising allowing the heat to transfer to the formation such that at least some hydrocarbons are pyrolyzed in the formation.

18. The method as claimed in claim 16 or 17, further comprising producing a fluid from the formation.

19. A composition comprising hydrocarbons produced using the heating system as claimed in any of claims 1-11, or using the method as claimed in any of claims 16-18.

20. A transportation fuel made from the composition as claimed in claim 19.

21. A heating system for a subsurface formation, comprising:

a first heater, a second heater, and a third heater placed in an opening in the subsurface formation, wherein each heater comprises:

an electrical conductor;

an insulation layer;

an electrically conductive sheath;

wherein the electrical conductor is electrically coupled to the sheath at a position along the length of the heater;

the first heater, the second heater, and the third heater being electrically coupled; and

the first heater, the second heater, and the third heater are configured to be electrically coupled in a three-phase configuration.

1/4





FIG. 2




FIG. 3B

FIG. 3A

3/4




FIG. 4A




FIG. 4B




FIG. 4C

4/4




FIG. 5A




FIG. 5B

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2006/015084

A. CLASSIFICATION OF SUBJECT MATTER
 INV. E21B36/00 E21B36/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 E21B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2004/140095 A1 (VINEGAR HAROLD J ET AL) 22 July 2004 (2004-07-22) paragraphs [0004], [0623], [0626]; figures 64,112,120 last sentence, paragraph 656 paragraphs [0662], [0667], [0705], [0727], [0744]	1-7, 9-12, 14-21
Y	-----	13
X	US 2005/051327 A1 (VINEGAR HAROLD J ET AL) 10 March 2005 (2005-03-10) paragraphs [0004], [0726]; figures 83,137,145	1,8
Y	----- WO 00/19061 A (SONNIER, ERROL, A) 6 April 2000 (2000-04-06) page 1, lines 8-11; figures 1,2 -----	13

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

31 August 2006

Date of mailing of the international search report

06/09/2006

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Georgescu, M

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2006/015084

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2004140095	A1	22-07-2004	NONE
US 2005051327	A1	10-03-2005	NONE
WO 0019061	A	06-04-2000	AT 319912 T 15-03-2006
		AU 761606 B2	05-06-2003
		AU 1516200 A	17-04-2000
		BR 9914055 A	16-10-2001
		DK 1123454 T3	03-07-2006
		EP 1123454 A1	16-08-2001
		MX PA01003057 A	14-07-2003
		NO 20011500 A	23-05-2001